ALL HOSE

CATALOG





WWW.ALLHOSEINC.NET

FIND WHAT YOU NEED

- TABLE OF CONTENTS ..... INTRO 2-3
- PICTORIAL ..... INTRO 16-38
- NUMERICAL INDEX ..... PAGES 432-462

PICTORIAL INDEX PGS 4-26

BRASS PGS 1-156

LEAD FREE PGS 157-167

VALVES PGS 168-213

NIPPLES & FITTINGS PGS 214-293

PLASTIC PGS 294-304

HOSE ACCESSORIES PGS 305-315

CLAMPS PGS 316-334

TUBING PGS 335-341

PRESSURE WASHER 342-347

PNEUMATICS PGS 348-370

TRUCK & TRAILER PGS 371-392

HYDRAULICS PGS 393-431

NUMERICAL INDEX

TABLE OF CONTENTS

BRASS FITTINGS
Pipe Fittings..... 1
Hose Barb Fittings..... 15
Push-On Barb Fittings..... 31
Garden Hose Fittings..... 37
45° Flare Fittings..... 49
Inverted Flare Fittings..... 69
Compression Fittings..... 77
Flareless Fittings..... 91
Push-In Fittings..... 97
Air Brake Fittings..... 120
Grease Fittings..... 141

SPECIALTY VALVES AND COCKS..... 147-156

LEAD FREE BRASS.....154-163
VALVES.....168-213
Lead Free Brass Valves..... 169
Brass Ball Valves..... 173
Brass Gate Valves..... 190
Stainless Steel Ball Valves..... 198
SS Gate, Globe, Y-Strainer..... 203
Carbon Steel Ball Valves..... 204-206
Steel Check Valves..... 207
PVC Ball Valves..... 208
MISC Plastic Valves..... 209

FITTINGS AND NIPPLES.....214-293
Brass Nipples..... 215
Bronze and Lead Free Fittings..... 223
Stainless Nipples..... 233
Stainless Steel Fittings..... 235
Steel Nipples..... 250
Merchant Couplings..... 267
API Line Couplings..... 268
Malleable Fittings..... 269
Steel Fittings..... 279
300# Malleable..... 281
Bull Plugs and Swages..... 283
Forged Steel Flanges..... 285
Copper Fittings..... 287

PLASTIC FITTINGS 294-304
Pipe-Nylon Poly..... 295
Hose Barb..... 297
Garden Hose..... 301
Compression..... 302
Push-In..... 303

HOSE ACCESSORIES.....305-315
Cam & Groove..... 306
King Nipples..... 312
Universal Couplings..... 313
Ground Joint Couplings..... 314
Fire Hose Fittings..... 315

CLAMPS.....316-334
Worm Gear Clamps..... 317
Quick Release..... 321
T-Bolt Clamps..... 322
Spring Loaded T-Bolt..... 323
Constant torque..... 324
V-Band..... 324
Muffler..... 325
Exhaust..... 326
1 Ear Clamps..... 327
Preformed..... 329
Clamp Tools/Strapping..... 331
Lined Band Clamps..... 332
Hose Ferrules..... 334

TUBING.....335-341
Polyurethene..... 336
Polyethylene..... 337
Nylon 12 Tubing..... 339
PVC Tubing..... 340
Tube Cutters..... 340
Aluminum..... 341
Copper..... 341

TABLE OF CONTENTS

HIGH PRESSURE SPRAYERS 342-347
Nozzles 343
Swivels 344
Sprayers 345
Quick Disconnects 346

PNEUMATICS 348-370
Industrial Interchange 349
Universal Couplings 351
ARO 210 Interchange 352
Automotive Interchange 353
Lincoln Interchange 354
Straight Through 355
Mini/Mold 355
Vents, Mufflers and Filters 356
Manifolds 358
Safety Valves 359
Tank & Vent 360
Blow Guns 361
Tire Gauges 361
Foot Chucks 363
Air Accessory Sets 364
Gauges 367
Teflon Tape 370

TRUCK AND TRAILER 371-392
Air Coils 371
Hose Support 372
Gladhands 375
Air Cylinder 379
Coiled Cable 383
Accessories 389
Air Brake Tubing 391
Hose 392

HYDRAULICS.....393-341
STEEL ADAPTERS
Technical information 394
Profile size chart 390
Steel Pipe Swivels 402
37° JIC Flare Straights 404
37° JIC Flare Shapes 406
Bulkhead Adapters 407
Steel Pipe Fittings 409
O-Ring Adapters Straight 413
JIC Swivels 415
O-Ring Adapters 417
O-Ring Face Seal 419
BSPT/ BSPP Adapters 423
Metric Adapters 426
QUICK DISCONNECTS
Thread to Connect - Wing 427
ISO A Interchange 427
ISO B Interchange 427
Flush Face ISO 428
VEP Series 428
AG Interchange 429
Hydraulic Jack Q/D 429
VALVES & ACCESSORIES
Flow Control Valve 430
Variable Flow Counter 431
Air Breathers 431

PICTORIAL INDEX

BRASS

BRASS FITTINGS PGS 1-169	**PIPE PGS 1-13**	90° ELBOW PG 2	90° FORGED EL PG 2	45° ELBOW PG 2	UNION TEE PG 2	UNION PG 2	RED FRG TEE PG 3	CROSS PG 3
FORGED PG 3	COUPLING PG 3	REDCOUPLING PG 4	UNION PG 4	CAP PG 4	90° ST EL PG 4	90° ST EL PG 4	FORGE 90° PG 5	FORGE RED PG 5
HEX BUSHING PG 5	FACE BUSHING PG 6	SQ HEAD PLUG PG 6	COUNTER-SUNK PG 6	SLOTTED HEAD PG 6	CORED HEX PG 6	SOLID HEX PG 7	LOCKNUT PG 7	CLOSE NIPPLE PG 7
LONG NIPPLE PG 7	HEX NIPPLE PG 8	RED HEX NIPPLE PG 8	45° ST EL PG 8	45° FORGE ST EL PG 8	STREET TEE PG 9	FORGED ST TEE PG 9	EXTENDER PG 9	FPT X MPT SWIVEL PG 9
MPT X FPT SWIVEL PG 9	90° MALE ELBOW PG 10	BARSTOCK ELBOW PG 10	90° RED EL-BOW PG 10	MALE BRANCH T PG 10	FGD BRANCH TEE PG 10	ALL MALE T PG 11	LONG ST EL PG 11	LONG EX ADAPT PG 11
FIP X MIP WYE PG 11	MALE WYE N/P PG 11	ALL FIP N/P WYE PG 11	**BULK-HEAD FITTINGS PGS 12-13**	BULKHEAD FXF PG 12	BULKHEADFXM PG 12	BULKHEAD FXM PG 12	BULKHEAD FXM PG 12	BULK TUBE X F PG 12
FPXCLAMP-STUD PG 12	MARINE BULK-HEAD PG 12	STEEL BULK-HEAD PG 13	STEEL BULK-HEAD PG 13	STEEL BULK-HEAD PG 13	STEEL BULK-HEAD PG 13	STEEL BULK-HEAD PG 13	STAINLESS BULKHEAD PG 13	STAINLESS BULKHEAD PG 13
HOSE BARB PGS 15-22	MALE ADAPTER PG 15	BSPT ADAPTER PG 16	SWL MALE ADPT PG 16	SWL MALE ADPT PG 16	MENDER/ SPLICER PG 16	FEMALE ADAPT PG 17	FEMALE SWIVEL PG 17	MALE SWIVEL PG 17

MALE SWIVEL PG 17	GASKET PG 18	HB 90° ELBOW PG 18	BS 90° ELBOW PG 19	TEE PG 19	90° HB ELBOW PG 19	FEMALE HB EL PG 20	45° ELBOW PG 20	CROSS PG 20
BALL END PG 21	BALLSEAT PG 21	BALLSEAT PG 21	45° FLARE PG 21	DUAL FLARE PG 22	DUAL FLARE PG 22	FEM FLARE PG 22	FEM FLARE PG 22	JIC FLARE SWL PG 22
REUSE-ABLE FITTINGS PGS 23	REUSABLE MALE PG 23	REUSABLE STEMS PG 23	REUSABLE SWIVELS PG 23	REUSABLE FERRULES PG 23	REUSABLE STEMS PG 23	**FUEL HOSE PGS 24-25**	FUEL HOSE PG 24	BUBBLE BARB PG 24
INV FLARE CONN PG 24	90° MALE ELBOW PG 24	BUBBLE BARB PG 24	SWL MALE ELBOW PG 25	WELD CON-NECTOR PG 25	WELD HOSE NUT PG 25	HOSE CON-NECT PG 25	**TUBE BARB PGS 26**	UNION SINGLE BARB PG 26
MALE ADAPT-ER 1 BARB PG 26	FEMALE ADAPTER PG 26	BULKHEAD UNION PG 26	UNION ELBOW PG 26	MALE 90° ELBOW PG 26	FEMALE 90° EL PG 26	1 BARB TEE PG 26	MALE BRANCH T PG 26	FEMALE BRANCH T PG 26
TWO BARB PG 26	2 BARB TEE PG 26	90° ELBOW 2 BARB PG 26	**SS. HOSE BARB PGS 27**	SS ADAPTER PG 27	SS SPLICER PG 27	SS BARB ELBOW PG 27	#304 SS HOSE PG 27	#304 RED NIPPLE PG 27
#316 SS HOSE NIPPLE PG 27	**BEVERAGE BARB PGS 28-29**	PIPE ADAPTER PG 28	HOSE SPLICER PG 28	BRASS SPLIC-ERS PG 28	FLARE ADAPTER PG 28	THINWALL SPLICERS PG 28	TAILPIECE PG 28	SWIVEL SETS PG 28
PLUG PG 28	TAILPIECE PG 28	SWIVEL BARB PG 28	COMPRES-SION PG 28	90° ELBOW PG 28	SWIVEL EL-BOW PG 29	U-BEND PG 29	HOSE TEES PG 29	SWIVEL EL-BOW  PG 29

PICTORIAL INDEX

BRASS

U-BEND PG 29	THINWALL PG 29	MALE ELBOWS PG 29	CROSS PG 29	BARB SPLICER PG 29	**PUSH-ON BARB PGS 31-36**	MALE PG 31	MALE SWIVEL PG 31	FEMALE PG 31
HOSE SPLICER PG 32	FEMALE PG 32	MALE ELBOW PG 32	TUBE PG 33	SAE FLARE PG 33	37° JIC FLARE PG 33	DUAL SEAL PG 33	45° SAE FL PG 34	37° JIC FL SWL PG 34
INV FLARE SWL PG 34	FEMALE ADAPTER PG 35	BALLSEAT SWIVEL PG 35	FEMALE SWIVEL PG 35	316 MALE ADPT PG 36	FEMALE SWIVEL PG 36	37° JIC FL SWL PG 36	**GARDEN HOSE PGS 37-47**	SWL MGH X FGH PG 38
SWL FGH X FGH PG 38	FGH X FGH PG 38	SWL FGH X FPIPE PG 38	COOLER FIT-TINGS PG 38	COOLER FIT-TINGS PG 38	COOLER FIT-TINGS PG 38	RGD FGH X FPIPE PG 38	RGD FGH X FPIPE PG 39	SWL FGH X MPIPE PG 39
DSHWSHR ELBOW PG 39	SWL FGH X MPIPE PG 39	SWL FGH X MPIPE PG 39	RGD FGH X MPIPE PG 39	RGD FEMALE PIPE PG 40	RGD FEMALE PIPE PG 40	RGD MALE PIPE PG 40	RGD MGH X MGH PG 40	GH NUT PG 40
GH NUT PG 40	GH WASHER PG 41	GH WASHER PG 41	GH FILTER WSHR PG 41	GH CAP PG 41	GH CAP W/ CHAIN PG 41	GH PLUG PG 41	MENDER PG 42	QCK DISCON GH PG 41
QCK DISCON GH PG 41	MALE FL X FGH RGD PG 42	MALE FL SWIVEL PG 42	COMP X FGH PG 42	COMP X MGH PG 42	FEMALE SWIVEL PG 43	SS FEMALE SWL PG 43	MALE END PG 43	SS MALE END PG 43
GH COUPLING PG 43	GH COUPLING PG 43	FEMALE END PG 44	MALE END PG 44	GH COUPLING PG 44	FEMALE SWL 2” PG 44	MALE END 2” PG 44	GH COUPLING 2” PG 44	FE. SHRT SHNK PG 45

BRASS

PICTORIAL INDEX

MALE SHRT PG 45	SHRT SHNK PG 45	FE. LONG PG 45	M. LONG PG 45	LONG SHNK PG 45	FEMALE END PG 46	BRASS BALL PG 46	HOSE SHUT- PG 46	PL. GH VALVE PG 46
CAST WYE PG 47	2-WAY SHUT- PG 47	"Y" CONNEC- PG 47	SWL HOSE PG 47	"Y" CONNEC- PG 47	BRASS PG 48	CROSS PTTRN PG 48	CROSS PTTRN PG 48	SPRAY PG 48
SPRAY NOZZLE PG 48	SPRAY NOZZLE PG 48	PL. SPRAY NOZZ PG 48	**FLARE PGS 49-60**	SHORT ROD NUT PG 50	RED. SHRT ROD PG 50	LONG ROD NUT PG 50	LONG FRG. NUT PG 51	SHORT FRG. NUT PG 51
HVY. SHRT NUT PG 51	REDUCING NUT PG 51	FLARED PLUG PG 52	FLARED CAP PG 52	FNGR TIGHT. CAP PG 52	COPPER GASKET PG 52	COPPER BON- NET PG 53	M BALL CHK CON PG 53	UNION PG 53
REDUCING UNION PG 54	UNION TEE PG 54	REDUCING TEE PG 54	M. BRANCH TEE PG 55	FE. ADAPTER PG 55	MALE ADAPTER PG 56	MALE ELBOW PG 57	MALE ELBOW PG 57	FEMALE ELBOW PG 58
MALE RUN TEE PG 58	FLARE CROSS PG 59	ADAPTER TEE PG 59	FLARE ELBOW PG 59	REDUCING ELBOW PG 59	45° ELBOW PG 60	UNION PG 60	FE. FL ADAPTER PG 60	FL REDUCER PG 60
FORGED SWIVEL PG 61	REDUCING SWL PG 61	SWIVEL EL- BOW PG 61	FL X SWT PG 61	**SPACE HEATER PG 61**	SPACE NUT PG 62	HEATER MALE PG 62	SPACE FE- MALE PG 62	HEATER UNION PG 62
GAS RANGE PG 62	GAS MALE PG 62	RANGE FE- MALE PG 62	DRUM ADTR PG 62	RANGE CAP PG 62	**POL PGS 63-65**	POL TEE PG 63	TAILPIECE PG 63	TAIL AND NUT PG 63

PICTORIAL INDEX

BRASS

POL CAP PG 63	PLUG AND PG 63	ADAPTER PG 63	MALE PG 63	TAILPIECE PG 64	POL ADADPTER PG 64	TAILPIECE PG 64	POL ADAPTER PG 64	HEX HEAD PG 64
POL ADAPTER PG 64	SOFT NOSE PG 64	POL ADAPTER PG 64	PROPANE PG 65	DUST PLUG PG 65	POL X MIP PG 65	APPLIANCE PG 65	FPT X POL PG 65	APPLIANCE PG 65
APPLIANCE TEE PG 65	O-RING PG 65	DUAL APPLI-ANCE PG 65	**37 FLARE PGS 66-67**	JIC UUNION PG 66	JIC FE ADPT PG 66	MALE ADAPTER PG 66	JIC SWIVEL PG 66	90° ELBOW PG 67
FE ELBOW PG 67	45° ELBOW PG 67	**INVERTED FLARE PGS 69-75**	CHROMATE NUT PG 69	LONG STEEL NUT PG 69	INVERTED FL NUT PG 69	METRIC TUBE NUT PG 69	UNION INTER-NAL PG 70	FE. ADAPTER PG 70
MALE ADAPTER PG 70	ELBOW PG 71	45° ELBOW PG 71	UNION TEE PG 71	STEEL PLUG PG 72	M. BRANCH TEE PG 72	FEMALE ELBOW PG 72	MALE RUN TEE PG 72	FE. BRANCH TEE PG 73
TRAIL BRAKE TEE PG 73	CYLINDER ADAPT PG 73	CYLINDER ADAPT PG 74	CARBURETOR PG 74	RESTRICT. ADAPT PG 74	SAE FL X INVERT PG 75	METRIC ADAPTER PG 75	ADAPT STAN-DARD PG 75	METRIC UNION PG 75
COMPRESSION PG 77-85	BRASS SLEEVE PG 77	BRASS NUT PG 77	UNION PG 77	REDUCING UNION PG 78	BULKHEAD UNION PG 75	DRILLED UNION PG 75	CHECK VALVE PG 76	TEE PG 76
TEE PG 76	REDUCING TEE PG 76	UNION ELBOW PG 77	REDUCING ELBOW PG 77	TANK ADAPTER PG 77	COMP X SWEAT PG 77	FE. ADAPTER PG 78	MALE ADAPTER PG 79	MALE ELBOW PG 80

BRASS

PICTORIAL INDEX

MALE ELBOW PG 80	MALE RUN TEE PG 81	M. BRANCH PG 81	M. BRANCH PG 81	FE. ELBOW PG 82	FE. ELBOW PG 82	FORGED TEE PG 82	ADAPTER TEE PG 83	FE. BRANCH PG 83
45° ELBOW PG 83	CAP PG 84	COMPRESS PG 84	BULKHEAD PG 85	CHECK VALVE PG 85	TANK PG 85	**DOUBLE COMP. PG 84**	DOUBLE COM- PG 86	MALE PG 86
90° ELBOW PG 86	BREAK-AWAY NUT PG 86	**SPLIT SLEEVE PG 87**	SPLIT SLEEVE PG 87	NUT PG 87	DBL. END UNION PG 87	CONNECTOR TRANSMIS-SION PG 87	ELBOW PG 87	**COMP AS-SEMBLIES PG 88**
DELRIN SLEEVE PG 88	BRASS INSERT PG 88	LONG NUT COMP PG 88	SELF-ALIGN SLEEVE PG 88	**CAPTIVE SLEEVE PG 89**	CAP SLEEVE NUT PG 89	UNION PG 89	MALE ADAPTER PG 89	MALE ELBOW PG 89
M. BRANCH TEE PG 89	ANG. NEED. VALV PG 89	SLE. NEED. VALV PG 89	**FLARE-LESS PGS 91-94**	NUT PLS. SLEEVE PG 91	UNION PG 91	BULKHEAD UNION PG 91	UNION TUBE PG 91	BULKHEAD UNION PG 91
UNION TEE PG 92	FE. CONNEC-TOR PG 92	M. CONNEC-TOR PG 92	MALE ELBOW PG 92	FEMALE ELBOW PG 93	MALE RUN TEE PG 93	M. BRANCH TEE PG 93	FE. BRANCH TEE PG 93	UNI NUT SLEEVE PG 94
NUT PG 94	PLASTIC SLEEVE PG 94	PLASTIC CAP PG 94	**BRASS PUSH-IN PGS 97-101**	UNION CON-NECT PG 97	UNION TEE PG 97	UNION ELBOW PG 97	FE. CONNEC-TOR PG 97	M. CONNEC-TOR PG 98
SWVL. M. ELBOW PG 98	FIXED M. ELBOW PG 99	FE. SWVL ELBOW PG 99	FEMALE ELBOW PG 99	SWVL M. RUN T PG 100	FIXED M. RUN T PG 100	SWVL M. BRANCH PG 100	FIX M. BRANCH T PG 100	UNION "Y" PG 101

PICTORIAL INDEX

BRASS

BULKHEAD PG 101	FE. BLKHD PG 101	REDUCER PG 101	PLASTIC PLUG PG 101	**N/P BRASS PUSH-IN PGS 103-106**	UNION CON- PG 103	UNION TEE PG 103	UNION ELBOW PG 103	FE. CONNEC- PG 103
FIXED M. PG 104	MALE W/INT 104	M. CONNEC- PG 104	SWVL. M. 105	FE. SWVL PG 105	SWVL. M. PG 105	REDUCER PG 106	UNION "Y" PG 106	SWVL M. PG 106
BULKHEAD UNION PG 106	**N/P VALVES PG 107**	PUSH-IN VALVE PG 107	TUBE X MIP MINI PG 107	FIP MINI BALL PG 107	MXF MINI BALL PG 107	FIP ANGLE BALL PG 107	3-WAY MINI PG 107	3_WAY MINI PG 107
METRIC N/P BRASS PGS 108-110	BULKHEAD UNION PG 108	UNION TEE PG 108	UNION ELBOW PG 108	UNION "Y" PG 108	PLUG PG 108	METRIC TUBE M. PG 109	INTERNAL HEX PG 109	METRIC TUBE ELB PG 109
METRIC SWVL TEE PG 110	METRIC SWVL TEE PG 110	BULKHEAD PG 110	**COM-POSITE PUSH-IN PGS 112-115**	UNION PG 112	UNION TEE PG 112	FE. CONNEC-TOR PG 112	90° UNION ELB. PG 112	UNION "Y" CONN PG 112
SWIVEL "Y" CONM. CON-NECTOR PG 113	SW MALE ELBOW PG 113	LONG PTTN M. EL PG 113	FE. SWVL ELBOW PG 114	45 SWIVEL ELL PG 114	SWVL M. RUN T PG 114	SWVL M. BRANCH PG 114	BULKHEAD FE. PG 114	BULKHEAD UNION PG 115
SWIVEL "Y" CON PG 115	NEEDLE VALVE PG 115	FLOW CON-TROL PG 115	FLOW CON-TROL PG 115	**METRIC PUSH-IN PGS 116-118**	METRIC MALE PG 116	METRIC EL-BOW PG 116	METRIC TEE PG 116	METRIC UNION PG 116
METRIC TEE PG 117	METRIC TEE PG 117	METRIC SW ELBOW PG 117	METRIC WYE PG 118	METRIC SW WYE PG 118	**DOT BRASS PUSH-IN PGS 120-125**	PLUG PG 120	UNION PG 120	UNION TEE PG 120

UNION ELBOW PG 120	FEMALE CONN PG 121	MALE CON- PG 121	MALE ELBOW PG 122	MALE SWL PG 122	FEMALE PG 123	FEMALE SWL PG 123	MALE RUN TEE PG 123	MALE SWL PG 124
MALE 45° PG 124	45° SWL EL- PG 124	MALE BRANCH PG 124	SWL BRANCH PG 125	FEM BRANCH T PG 125	BULK CON- PG 125	BULKHEAD PG 125	FEM BULK PG 125	**DOT COMP PUSH-IN PGS 127-130**
STRAIGHT UNION PG 127	UNION TEE PG 127	UNION 90° EL PG 127	FEM CONNEC-TOR PG 127	MALE CON-NECTOR PG 128	90° MALE ELBOW PG 128	90° FEMALE EL PG 128	MALE RUN TEE PG 129	MALE BRANCH T PG 129
FEM BRANCH T PG 129	45° MALE ELBOW PG 129	UNION "Y" PG 130	MALE BRANCH "Y" PG 130	BULKHEAD UNION PG 130	FEM BULK CONN PG 130	**DOT FOR NYLON TUBE PG 132-135**	SLEEVE PG 132	NUT PG 132
UNION PG 132	BULKHEAD UNION PG 132	SS INSERT PG 132	BRASS INSERT PG 132	TEE PG 133	RED BRANCH TEE PG 133	ELBOW PG 133	FEMALE ADAPTER PG 133	MALE ADAPTER PG 134
SWL MALE ADPT PG 134	MALE ELBOW PG 134	SWL MALE ELBOW PG 134	FEMALE ELBOW PG 134	MALE RUN TEE PG 135	MALE BRANCH T PG 135	FEM BRANCH T PG 135	45° ELBOW PG 135	SWL 45° EL-BOW PG 135
DOT FOR COPPER PGS 136-137	SLEEVE PG 136	NUT PG 136	UNION PG 136	MALE ADAPTER PG 137	90° MALE ELBOW PG 137	MALE BRANCH T PG 137	**DOT FOR HOSE PGS 138-140**	SLEEVE PG 138
NUT PG 138	NUT-USE SPRING PG 138	SPRING PG 139	NUT/SPRING PG 139	UNION PG 139	CONNECTOR HOSE PG 139	MALE CON-NECTOR PG 139	ADAPTER FOR SWL PG 140	MALE ADAPTER PG 140

PICTORIAL INDEX

BRASS

ADAPTER PG 140	MALE PG 140	**GREASE FITTINGS PGS 141-145**	1/8 STR. PG 141	BALL CHECK PG 141	1/8" 30 PG 141	1/8" 45 PG 141	65° 1/8" PG 141	90° 1/8" PG 141
1/4 STR PG 141	65° BALL PG 142	SHORT 1/4-28 PG 142	LONG 1/4-28 PG 142	EXTRA LONG PG 142	SHORT 45° BC PG 142	SHORT 45° BC PG 142	LONG 45° BC PG 142	90° BALL PG 142
DRIVE TYPE PG 143	DRIVE TYPE PG 143	6MM PG 143	6MM 45° PG 143	6MM 90° PG 143	8MM PG 143	8MM 45° PG 143	8MM 90° PG 143	10MM PG 144
10MM 45° PG 144	10MM 90° PG 144	5/16"-24 PG 144	3/8" - 24 PG 144	BUTTON HEAD PG 144	WHIP HOSE PG 144	ADAPTERS PG 145	ADAPTERS PG 145	EXTENSIONS PG 145
45° ANGLE PG 145	90° ANGLE PG 145	COUPLING PG 145	BULKHEAD PG 145	**DRAIN COCKS PGS 147-148**	GAS SHUT OFF PG 147	DRAIN COCK PG 147	TRUCK DRAIN PG 147	SHUT OFF PG 147
LEVER HANDLE PG 147	AIR TANK VALVE PG 147	INTERNAL SEAT PG 148	INTERNAL SEAT PG 148	LG INTERNAL SEAT PG 148	TEE HANDLE PG 148	EXT W/ SPOUT PG 148	BIBB NEEDLE PG 148	RADIATOR TYPE PG 148
SHUT OFF COCKS PG 149	COMP X MALE PG 149	COMP X COMP PG 149	FEMALE X FEM PG 149	MALE X FE-MALE PG 149	MALE X MALE PG 149	**NEEDLE VALVES PGS 150-151**	COMP X MALE PG 150	COMP X M ANGLE PG 150
COMP X COMP PG 150	FLARE X MALE PG 150	FLARE X MALE PG 151	FLARE X FLARE PG 151	AIR VENT PG 151	MALE TO MALE PG 151	F X F PG 151	MALE X FE-MALE PG 151	**TRUCK VALVES PG 152**

TRUCK VALVE PG 152	FEMALE TO PG 152	FLARE TO PG 152	**SOLID BOTTOM VALVES PG 152**	SOLID BOT- PG 152	FIP X FIP PG 152	FUEL VALVE PG 152	MALE X MALE PG 152	F X F PG 152
MALE X FLARE PG 152	**MULTI PORT VALVES PGS 153**	3-WAY (SIDE) PG 153	3-WAY (BOT- PG 153	4-WAY PG 153	**MARINE VALVES PG 154**	ANTI-SIPHON PG 154	ANTI-SIPHON PG 154	ALUM ANTI- PG 154
MXF ANTI-SIPHON PG 154	ALUM MXF PG 154	ALUM BARB PG 154	FL X MIP PG 154	6-PORT PG 154	**MINI BALL VALVES PG 155**	MINI BALL PG 155	MALE X MALE PG 155	PIPE X BARB PG 155
F X F PG 155	F X F PG 155	F X F PG 155	FNPT X FNPT PG 155	MNPT X FNPT PG 155	**PANEL MOUNT VALVES PG 155**	PANAL MOUNT PG 155	F X F PG 155	F X F PG 155
CHECK VALVES PG 156	FIPXFIP BUNA-N PG 156	FXF BUNA-N PG 156	MXM BUNA PG 156	M X F BUNA-N PG 156	MNPT X MNPT PG 156	MNPT X FNPT PG 156	FNPT X FNPT PG 156	NPT X NPSM PG 156
F X F PG 156	F X M PG 156	M X F PG 156	M X M CHECK PG 156	**L/F PIPE PGS 158-160**	90 ELBOW PG 158	TEE PG 158	90° STREET EL PG 158	COUPLING PG 158
RED COU-PLING PG 158	HEX BUSHING PG 158	FACE BUSHING PG 158	HEX CAP PG 159	SOLID SQ PLUG PG 159	COUNTER-SUNK PG 159	CORED HEX PLUG PG 159	CLOSE NIPPLE  PG 159	HEX NIPPLE PG 159
MALE BRANCH T PG 160	EXT ADAPTER PG 160	STR/SERVICE TEE PG 160	**L/F BARB PGS 160-161**	RIGID M ADAPTER PG 160	MENDER/ SPLICER PG 160	FE ADAPTER PG 161	FORGED HB 90° PG 161	HB TEE PG 161

PICTORIAL INDEX

VALVES

FE FL SWIVEL PG 161	BXB BALL PG 161	**L/F PUSH-ON PG 161**	MALE PG 161	SAE/JIC F SWL PG 161	**L/F GARDEN PGS 162**	FGHXFGH SWL PG 162	MGH X F PIPE PG 162	FGH X F PG 162
MGH X M PIPE PG 162	RIGID FGH PG 162	RIGID MGH PG 162	FGHXMIP SWL PG 162	GARDEN HOSE PG 162	RIGID FGH PG 162	RIGID MGH PG 162	**L/F FLARE PGS 163-164**	SHORT ROD PG 163
SHORT FORGE NUT PG 163	FLARED CAP PG 163	UNION PG 163	TEE PG 163	FEMALE ADAPTER PG 163	MALE ADAPTER 163	90° MALE ELBOW PG 164	MALE RUN TEE PG 164	FORGED SWIVEL PG 164
L/F COMP PGS 164-165	BRASS SLEEVE PG 164	NUT PG 164	TEE PG 164	BRASS INSERT PG 164	CAP PG 165	UNION PG 165	RED UNION PG 165	TEE PG 165
FORGED RED TEE PG 165	UNION ELBOW PG 165	FORGED RED EL PG 165	COMP X SWEAT PG 165	FEMALE ADAPTER PG 166	MALE ADAPTER PG 166	MALE ELBOW PG 166	FEMALE ELBOW PG 166	NEEDLE VALVE  PG 167
M X F PIPE PG 167	COMP X M ANGLE PG 167	DISHWASHER TEE PG 167	ICE MAKER KIT PG 167	SADDLE VALVE PG 167	**VALVES PGS 168-213**	**L/F BALL VALVES PGS 169-171**	LF BALL VALVE PG 169	SWT X SWT PG 169
FIP X FIP LF PG 170	SWT X SWT LF PG 170	LF ITALIAN PG 171	SWT X SWT LF PG 171	**L/F VALVES PG 172**	GATE VALVE CXC PG 172	LF BRASS CHECK PG 172	SWING CHECK PG 172	CXC SWING CHK 172
Y-STRAINER PG 172	**BRASS BALL VALVES PGS 173-184**	FORGED BRASS PG 173	LOCKING HANDLE PG 174	BUTTERFLY HANDLE PG 175	FXF NICKEL PLTD PG 176	NP/SS TRIM PG 177	ITALIAN BALL VALVE PG 178	M X F PG 179

ITALIAN M X F PG 180	MXF TEE PG 181	FXM LOCKING PG 182	SPRING PG 183	RIGHT ANGLE PG 183	3WAY NON- PG 184	3WAY VENTED PG 184	SAFETY EX- PG 184	**GAS BALL VALVES PG 185**
GAS BALL PG 185	FLARE X PG 185	FLARE X MIP PG 185	FLARE X FIP PG 185	ITALIAN GAS PG 185	**MINI BALL VALVES PGS 186-189**	ITALIAN MINI PG 186	M X F PG 186	MINI MXF PG 187
FXF FLAG HANDLE PG 187	LEVER HANDLE PG 187	TEE HANDLE PG 187	TEE HANDLE PG 188	MXF FLAG PG 188	LEVER HANDLE PG 188	SCREW-DRIVER PG 188	F X F MINI PG 189	F X M MINI PG 189
M X M MINI PG 189	BARB X MALE MINI PG 189	BARB X FE-MALE PG 189	BARB X BARB MINI PG 189	**BRASS VALVES PGS 190-194**	3-WAY SIDE OUT PG 190	3-WAY BOT-TOM PG 190	STRAINER PG 191	VACUUM BREAK PG 191
RADIATOR AIR PG 191	KEY ONLY PG 191	SILLCOCK PG 191	HOSE BIBBS PG 191	GARDEN VALVE PG 191	GATE VALVE PG 192	QUICK OPEN-ING PG 193	Y-STRAINER PG 194	**CHECK VALVES PGS 195-197**
SWING CHECK PG 195	Y-SWING CHECK PG 195	CHECK VALVE PG 196	IN LINE CHECK PG 196	IN LINE CHECK PG 197	**SS BALL VALVES PGS 198-207**	2000# PG 198	316 SS 1-PC 1000 STD PORT PG 199	316 SS 2-PC 1000 FP PG 200
SS MINI PG 201	SS M X F PG 201	FXF BUTTER-FLY PG 202	MXF BUT-TERFLY PG 202	MXM BUT-TERFLY PG 202	**CHECK PGS 203-207**	304 CHECK PG 203	SS IN LINE PG 204	FXF SPRING CHK PG 205
MXF SPRING CHK PG 205	Y-SPRING CHECK PG 206	2PC BARREL PG 206	SS SWING CHK PG 207	SS GLOBE VALVE PG 207	SS GATE VALVE PG 207	**STEEL VALVES PGS 208-211**	STANDARD PORT PG 208	2PC FULL PORT PG 209

PICTORIAL INDEX

NIPPLES & FITTINGS

2 WAY PG 210	3 WAY PG 210	CHECK PG 211	**PVC PGS 212-213**	PVC THREAD PG 212	SLIP X SLIP PG 212	FIP X FIP PG 212	SLIP X SLIP PG 212	IN LINE PG 213
IN LINE FE- PG 213	DRUM FAUCET PG 213	DRUM & BAR- PG 213	**NIPPLES & FITTINGS PGS 214-293**	**BRASS NIPPLES PGS 215-222**	SEAMLESS PG 215	CHROME PG 222	**BRONZE FITTINGS PG 223-231**	**LEAD FREE BRONZE PG 223-231**
90° ELBOW PG 223	90° REDUCE ELB PG 223	90° STREET ELLS PG 223	45° ELBOW PG 224	45 ST ELBOW PG 224	CROSS PG 224	TEE PG 225	REDUCING TEE PG 225	REDUCING TEE PG 225
COUPLING PG 226	REDUCE COUP PG 226	CAP PG 227	UNION PG 227	HEX LOCKNUT PG 227	HEX BUSHING PG 228	HEX BUSHING PG 228	CNTRSUNK PLUG PG 229	CORED PLUG PG 229
SOLID PLUG PG 229	HEX NIPPLE PG 230	REDUCE HEX NIP PG 230	**CLEANOUT PLUGS PG 232**	CLEANOUT PLUG PG 232	CS C/O PLUG 232	C/O PLUG W/ TAP PG 232	**DROP EAR ELBOWS PG 232**	BRONZE D/E PG 232
SWT X SWT PG 232	PEX X FIP PG 232	**BRASS INSERTS PGS 233-234**	BARB FOR PL PIPE PG 233	BRONZE TEE BARB PG 233	90 BRONZE BARB PG 233	UNION 90 PG 233	**STEEL INSERTS PG 233**	STEEL INSERT 233
REDUCER PG 233	UNION PG 233	**SS INSERTS PG 234**	SS MALE ADAPTER PG 234	SS 90 ELBOW PG 234	**L/F INSERTS PG 234**	LF UNION PG 234	LF MALE BRANCH PG 234	LF UNION ELBOW PG 234
WELL COUPLINGS PG 234	SS DROP WELL PG 234	SS HEAVY CPLG PG 234	SS MERCHANT PG 234	**SS NIPPLES PG 235-240**	304 SCH 40 WELDED PG 235	316 SCH 40 WELDED PG 235	**SS FITTINGS PG 241-248**	90° ELBOW PG 242

90° STREET PG 242	45° STREET PG 242	TEE PG 243	CROSS PG 243	HEX NIPPLE PG 243	REDUCE HEX PG 243	COUPLING PG 244	REDUCE COUP PG 244	MACHINED PG 244
HALF COU- PG 245	UNION PG 245	CAP-CAST PG 245	HEX CAP- PG 245	HEX BUSHING PG 246	HEX LOCKNUT PG 247	HEX SOCKET PG 248	CORED PLUG PG 247	SOLID PLUG PG 248
SOLID HEX PLUG PG 248	CORED HEX PLUG PG 247	HOSE NIPPLE PG 247	REDUCING PG 248	**STEEL NIPPLES PG 250-264**	SCH 40 GALVA-NIZED PG 250	SCH 40 BLACK PG 250	ASSORT-MENTS PG 257	TOTE TRAYS PG 257
SCH 80 SEAM-LESS PG 258	XXS SEAM-LESS PG 264	**GROOVE NIPPLES PG 265-266**	THREAD X GROOVE PG 265	GROOVE X GROOVE PG 266	**MERCHANT COUPLINGS PG 267-268**	MERCHANT COUP PG 267	MERCHANT COUP PG 267	HALF MECHANT C PG 267
API LINE COUP PG 268	**MALLEABLE FITTINGS PG 269-278**	90° ELBOW GALV PG 270	90° ELB. BLACK PG 270	REDUCE ELBOW PG 270	REDUCE ELBOW PG 270	GALV ST. ELBOW PG 270	BLK. ST. EL-BOW PG 270	45° GALV ELBOW PG 271
45° BLK. EL-BOW PG 271	45° GALV ST. ELB PG 271	45° BLK. ST. ELB PG 271	GALV CROSS PG 271	BLACK CROSS PG 271	GLAV TEE PG 272	BLACK TEE PG 272	GALV REDUCE T PG 272	BLK. REDUCE T PG 272
BULLHEAD TEE PG 273	BLK. BLKHD TEE PG 273	REDUCING TEE PG 273	MALL SERVICE T PG 273	MALL SERVICE T PG 273	GALV OUT TEE PG 273	BLK. OUT TEE PG 273	GALV COU-PLING PG 274	BLK. COU-PLING PG 274
GALV RED COUP PG 274	BLK. RED COUP PG 274	GALV HEX BUSH PG 275	BLK. HEX BUSH PG 275	GALV HEX BUSH PG 275	GALV UNION PG 276	BLACK UNION PG 276	GALV SQR PLUG PG 276	BLK SQR PLUG PG 276

PICTORIAL INDEX

PLASTIC FITTINGS

GALV CAP PG 276	BLACK CAP PG 276	LATERAL Y PG 277	LOCKNUTS PG 277	COUPLING PG 277	OUTLET PG 277	GALV FLR PG 278	BLK FLR PG 278	EXTENSION PG 278
SHROOM CAP PG 278	**STEEL FITTINGS PG 279-280**	PG 279	BLK HEX BUSH PG 279	GALV CAP  PG 279	BLK CAP PG 279	GALV FACE PG 279	BLK FACE PG 279	GALV SQR PG 280
BLK SQR PLUG PG 280	GALV HEX PLUG PG 280	BLK HEX PLUG PG 280	GALV CS PLUG PG 280	BLK CS PLUG PG 280	CS HEX PG 280	BLK CS PLUG PG 280	**300# MALLEABLE PG 281-282**	90° ELBOW PG 281
45° ELBOW PG 281	90° ST ELBOW PG 281	TEE PG 281	COUPLING PG 281	REDUCE COUP PG 282	CAP PG 282	UNION PG 282	MAG DRAIN PLUG PG 282	**BULL PLUGS & SWAGES PG 283-284**
BULL PLUG PG 283	XH BULL PLUG PG 283	SCH 40 SWAGE PG 283	HEX SWAGE PG 284	SCH 80 SWAGE PG 284	XXH SWAGE PG 284	**STEEL FLANGES PG 285-286**	SLIP-ON PG 285	THREADED PG 285
WELD NECK FLNG PG 286	BLIND FLNG PG 286	**COPPER FITTINGS PG 287-293**	PG 288	90° ST EL FTG X C PG 288	90° LONG TURN PG 288	90° LONG TURN ST PG 288	45° EL CXC PG 289	45° ST FTG X C PG 289
COUPLING PG 289	COUPLING PG 289	COUPLING PG 290	REDUCER W/ STOP PG 290	FITTING RE-DUCER PG 290	MALE ADAPTER PG 291	FTGXM ADAPTER PG 291	FEMALE ADAPTER PG 292	FTG X F ADAPTER PG 292
CAP PG 292	UNION C X C PG 292	U-TYPE STRAP PG 292	TEE PG 293	**PLASTIC FITTINGS PG 294-304**	**PIPE PG 295-297**	ELBOW PG 295	ELBOW PG 295	TEE PG 295

HOSE ACCESSORIES

PICTORIAL INDEX

TEE PG 295	STREET PG 295	STREET PG 295	HEX HEAD PG 295	HEX HEAD PG 295	HEX BUSHING PG 296	HEX BUSHING PG 296	HEX NIPPLE PG 296	HEX NIPPLE PG 296
RED NIPPLE PG 296	RED NIPPLE PG 296	COUPLING PG 297	COUPLING PG 297	PIPE CAP PG 297	PLASTIC BULK- PG 297	**HOSE BARB PG 297-300**	MALE PG 297	MALE PG 298
HOSE X MALE 90° PG 298	HOSE X MALE 90° PG 298	UNION ELBOW PG 298	SPLICER PG 299	SPLICER PG 299	RED SPLICER PG 299	RED SPLICER PG 299	BARBED TEE PG 300	BARBED TEE PG 300
BARBED Y PG 300	BARBED Y PG 300	REDUCING TEE PG 300	REDUCING TEE PG 300	M BRANCH TEE PG 300	**GARDEN HOSE PG 301**	GH CAP PG 301	GH NUT PG 301	GH ADPT INSERT PG 301
GH THREAD ADPT PG 301	MGH X F PG 301	FGH X M PG 301	FGH X F PG 301	MGH X M PG 301	**COMPRESSION PG 302**	UNION CONNECTOR PG 302	BULKHEAD UNION PG 302	UNION TEE PG 302
UNION ELBOW PG 302	FEMALE CONNECT PG 302	MALE CONNECTOR PG 302	MALE ELBOW PG 302	**PUSH-IN PG 303-304**	UNION CONNECT PG 303	REDUCING UNION PG 303	BULKHEAD UNION PG 303	UNION TEE PG 303
RED BRANCH TEE PG 303	UNION ELBOW PG 303	REDUCING ELBOW 303	FEMALE CONNECT PG 303	MALE CONNECTOR PG 304	STEM ADAPTER PG 304	REDUCER PG 304	FIXED ELBOW PG 304	PLUG-IN ELBOW PG 304
2-WAY DIVIDER PG 304	PLUG PG 304	PLXPL PG 304	CHECK VALVE PG 304	**HOSE ACCESSORIES PG 305-315**	**ALUMINIUM CAM & GROOVE PG 306-307**	M ADPT X F NPT A PG 306	FEMALE COUPLER B PG 306	HOSE SHANK C PG 306

PICTORIAL INDEX

PLASTIC/ HOSE ACCESSORIES

FEMALE COU- PG 306	HOSE SHANK E PG 306	MALE ADAPER PG 306	DUST CAP DC PG 306	DUST CAP DP PG 306	MALE PG 307	FEMALE COU- PG 307	FEMALE COU- PG 307	MALE ADAPT- PG 307
FEMALE COU- PG 307	FEMALE COU- PG 307	MALE ADAPT- PG 307	POLYPROPYLENE CAM & GROOVE PG 308	MALE ADAPT- PG 308	FEMALE COU- PG 308	HOSE SHANK PG 308	FEMALE COU- PG 308	M X HOSE PG 308
MALE ADAPT- ER F PG 308	DUST CAP DC PG 308	DUST PLUG DP PG 308	STAINLESS STEEL CAM & GROOVE PG 309	FEMALE ADAPTER A PG 309	FEMALE COU- PLER B PG 309	HOSE SHANK C PG 309	FEMALE COU- PLER D PG 309	HOSE SHANK E PG 309
MALE ADAPT- ER F PG 309	DUST CAP DC PG 309	DUST PLUG DP PG 309	BRASS CAM & GROOVE PG 310-311	MALE ADAPT- ER A PG 310	FEMALE COU- PLER B PG 310	HOSE SHANK C PG 310	FEMALE COU- PLER D PG 310	HOSE SHANK E PG 310
MALE ADAPT- ER F PG 310	DUST CAP DC PG 310	DUST CAP DP PG 310	SS ADAPTER PG 311	SS COUPLER DD PG 311	SS DA PG 311	BRASS ADAPTER PG 311	BRASS DA PG 311	SS HANDLE PG 311
BRASS HANDLE PG 311	BUNA-N GAS- KET PG 311	SAFETY CLIP PG 311	SILICONE GASKET PG 311	VITON GASKET PG 311	KING NIPPLES PG 312	HOSE NIPPLE STEEL PG 312	ZINC PLATED PG 312	REDUCER/EX- PANDER PG 312
316 SS PG 312	BRASS PG 312	ALUMINUM PG 312	HOSE MENDER STEEL PG 312	PLATED STEEL MENDER PG 312	316 HOSE MEND PG 312	UNIVERSAL GROUND JOINT PG 313-314	UNIVERSAL PG 313	WASHER PG 313
FEMALE NPT PG 313	HOSE END PG 313	TRIPLE CON- NECT PG 313	GROUND JOINT PG 314	HOSE STEM ONLY PG 314	WING NUT ONLY PG 314	F SPUT ONLY PG 314	M NPT STEM PG 314	BOLT CLAMP PG 314

FIRE HOSE FITTINGS PG 315	FIRE HOSE PG 315	FXM HEX ADPT PG 315	DBL M HEX NIP PG 315	M SWL PG 315	BRASS CAP PG 315	**HOSE CLAMPS** PG 316-334	300 SERIES PG 317	600 SERIES PG 317
325 SERIES PG 318	611 SERIES PG 318	350 SERIES PG 319	620 SERIES PG 319	350 SS SERIES PG 320	620 SS SERIES PG 320	QUICK RE- PG 321	T-BOLT PG 322	SPRING LOAD- PG 323
CONSTANT TORQUE PG 324	V-BAND PG 324	MUFFLER PG 325	FLAT BAND PG 325	GUILLOTINE PG 325	STEEL BUTT EXHAUST PG 326	STEEL LAP PG 326	SS STEEL LAP PG 326	SS EASY-FORM PG 326
1-EAR PG 327	2-EAR PG 328	GAPLESS EAR PG 328	F-CLAMP PG 329	K-CLAMP PG 329	CLAMP-IT PG 330	BUCKLES PG 330	JAW PINCH-ERS PG 331	HOSE CRIMPER PG 331
FOLD UP ADAPTER PG 331	LOKING TOOL PG 331	LOKING TOOL PG 331	LINED BAND PG 332	MARINE PG 332	MINI-F PG 332	SS MINI PG 332	RUBBER CLIP PG 333	RUBBER CUSHION PG 333
VINYL COATED PG 333	HOSE FER-RULE PG 334	SS FERRULE PG 334	**TUBING** PGS 335-341	POLYURE-THANE PG 336	BLACK PG 336	BLUE PG 336	RED PG 336	POLYETHYL-ENE PG 337
BLACK POLY PG 338	GREEN POLY PG 338	WHITE POLY PG 338	BLUE POLY PG 338	RED POLY PG 338	YELLOW POLY PG 338	ORANGE POLY PG 338	NYLON 12 PG 339	PVC PG 340
MINITUBING CUT PG 340	TUBING CUT-TER PG 340	PLASTIC TUBE CUT PG 340	MOUNTING RACK  PG 340	ALUMINUM  PG 341	COPPER TUBE PG 341	SOFT COPPER PG 341	**PRESSURE WASHER** PGS 342-347	QD NOZZLE PG 343

PICTORIAL INDEX

PNEUMATICS

MEG NOZZLE PG 343	RUBBER TIP PG 344	SS LIVE PG 344	THERMAL PG 344	BOOM SWIVEL PG 344	WAND PG 345	SPRAY GUN PG 345	GUN W/EXT PG 345	MALE STEEL PG 346
FE. STEEL PG 346	MOLDED GRIP PG 347	MOLDED GRIP PG 347	**PNEUMATICS PG 348**	**QUICK DISCONNECTS PGS 349-355**	INDUSTRIAL PG 349	BRASS M. PG 349	STEEL FE. PG 349	STEEL M. PG 349
BR. HOSE COUP PG 349	STL. HOSE COUP PG 349	BR. PUSH-ON PG 349	STL PUSH-ON PG 350	STEEL M. PLUG PG 350	STEEL FE. PLUG PG 350	BRASS M. PLUG PG 350	STL HOSE PLUG PG 350	PUSH-ON PLUG PG 350
STL SWL M. PLUG PG 350	**UNIVERSAL QD PGS 351**	UNIVERSAL SERIES PG 351	BRASS FE. COUP PG 351	BR. HOSE COUP PG 351	SS M. COU-PLER PG 351	SS FE. COU-PLER PG 351	SS MALE PLUG PG 351	SS FE. PLUG PG 351
ARO QD PG 352	ARO 210 PG 352	FEMALE COU-PLER PG 352	HOSE ID COUP PG 352	MALE PLUG PG 352	FEMALE PLUG PG 352	HOSE ID PLUG PG 352	**AUTO QD PGS 353-354**	AUTO INTER-CHANGE PG 353
BR. FE. COU-PLER PG 353	STL. M. COU-PLER PG 353	STL. FE. COU-PLER PG 353	BR. MALE PLUG PG 353	BR. FE. PLUG PG 353	STEEL MALE PLUG PG 353	STEEL FE. PLUG PG 353	HOSE ID COUP PG 354	PUSH-ON COUP PG 354
HOSE ID PLUG PG 354	PUSH-ON PLUG PG 354	**LINCOLN QD PG 354**	LINCOLN PG 354	FEMALE COU-PLER PG 354	STEEL MALE PLUG PG 354	STEEL FE. PLUG PG 354	**MISC QD PG 355**	HIGH FLOW PG 355
FEMALE COU-PLER PG 355	MALE PLUG PG 355	FEMALE PLUG PG 355	MOLD COOL-ANT PG 355	FEMALE PLUG PG 355	MINI QD PG 355	FE PLUG PG 355	**MUFFLERS/ BREATHERS PG 356-357**	BR. MUFFLER PG 356

STAINLESS PG 356	BR. BREATH PG 356	STLS BREATH PG 356	PSI SNUBBER PG 356	SPEED VALVE PG 356	SPEED VALVE PG 357	MUFF W/ FLOW PG 357	HI FLOW MUFF PG 357	HI FLOW MUFF PG 357
HI FLOW MUFF PG 357	HI FLOW MUFF PG 357	NIP INLINE PG 357	RPR AIR/OIL PG 357	CP BRASS PG 358	AIR REGULA- PG 358	MANIFOLD PG 358	AIR MANIFOLD PG 358	**SAFETY VALVES** PG 359
SAFETY VALVES PG 359	SAFETY VALVES PG 359	CHECK VALVE PG 359	CHECK VALVE PG 359	**TANK VALVES** PG 360	BIKE PUMP FITT PG 360	INFLATOR PG 360	SLIDE VALVE PG 360	SPRING CORE PG 360
SPRING CORE PG 360	SPRING CORE PG 360	BLK PLASTIC CAP PG 360	DOME CAP PG 360	**BLOW GUNS** PG 361	CPCT BLOW GUN PG 361	SAFE BLOW GUN PG 361	SAFE BLOW GUN PG 361	CPCT BLOW GUN PG 361
PISTOL BLOW GUN PG 361	PISTOL BLO-GUN PG 361	**GAUGES & CHUCKS** PG 361-363	RUB TIP NOZZLE PG 361	HI FLOW NOZZLE PG 361	M-TIRE GAUGE PG 362	STANDARD NOZZ PG 362	VOL REGULA-TOR PG 362	EXTENSION PG 362
GUN ADAPTER PG 362	COIL AIR HOSE PG 362	COIL AIR HOSE PG 362	HEX BALL CHUCK PG 363	M. BALL CHUCK PG 363	BALL CHCK BARB PG 363	DUAL AIR CHUCK PG 363	DUAL STRT AIR PG 363	INFLATOR/ GAUGE PG 363
INFLATOR/ GAUGE PG 363	**AIR ACCESSORY KITS** PG 364-366	**GAUGES** PG 367-369	DRY GAUGE PG 367	CENTER BACK MOUNT PG 367	LIQUID FILLED PG 368	WATER TEST PG 369	GAS TEST PG 369	THREAD SEAL PG 370
BLUE SEAL TAPE PG 370	YEL GAS TAPE PG 370	GRE OXY TAPE PG 370	GREY SS TAPE PG 370	**TRUCK & TRAILER** PG 371-392	AIR COIL PG 371	SLIDER COIL PG 371	AIRLINE CABLE PG 371	AIRBRAKE REPAIR PG 372

PICTORIAL INDEX

TRUCK AND TRAILER

POGO STICK PG 372	HOSE HOLDER PG 372	HOSE HOLDER PG 372	HOSE HOLDER PG 372	HOSE HOLDER PG 372	HOSE SEPARA- PG 372	HOSE SEPARA- PG 372	CLIP CARA- PG 373	HANGER PG 373
YOKE PG 373	FRAME CLIP PG 373	AIRHOSE CLIP PG 373	AXLE CLIP PG 373	TENDER KIT PG 374	TUBE PG 374	SPRING PG 374	SLIDER BAR PG 374	GLADHANDS PG 375
BRACKET MOUNT PG 376	KNOB STYLE GH PG 376	LEVER STYLE GH PG 376	GLADHAND GRIP PG 377	AL GLADHAND PG 377	GLADHAND PACIFER PG 377	GLADHAND SEAL PG 377	GLADHAND SEAL PG 377	GLADHAND SEAL PG 377
GH COUPLING KIT PG 378	NYLON GH HOLDER PG 378	GH HOLDER KIT PG 378	GLADHAND LOCK PG 378	KING PIN LOCK PG 378	AIR CYLINDER PG 379	HIGH LIFT CYLINDER PG 379	TAILGATE CYLINDER PG 379	TAILGATE AIR CYLINDER PG 380
FIFTH WHEEL CYLINDER PG 380	AIR TANK CHECK PG 381	D2 AIR GOVER-NOR PG 381	QCK RELEASE VALVE PG 381	R12 RELAY VALVE PG 381	R14 RELAY VALVE PG 382	3 WAY SOLE-NOID PG 382	UNI SOLENOID PG 382	AIR SOLENOID PG 382
7 WAY CABLE PG 383	7 WAY CABLE PG 383	6 WAY ELEC CABLE PG 384	4 WAY ELEC CABLE PG 384	DUEL POLE PG 384	SINGLE POLE PG 384	PLUG PG 385	PLUG PG 385	PLUG PG 385
SOCKET PG 385	7W DBLE GRIP PG 385	ADAPTER PG 385	RV 7WAY PLUG PG 385	RV 7WAY SOCK PG 385	6WAY PLUG PG 386	6WAY SOCKET PG 386	4WAY PLUG PG 386	4WAY SOCKET PG 386
2 POLE PLUG PG 386	2 POLE SOCKET PG 386	1WAY PLUG PG 386	1WAY SOCKET PG 386	GROUND KIT PG 386	PROTECTOR BOOT PG 386	7WAY SOCKET PG 387	CIRCUIT BREAKER PG 387	NOSE BOX-DEEP PG 387

BATT GRND STRAP PG 388	SS BATTERY NUT PG 388	RUB GROM-MET PG 388	DEER WHISTLE PG 389	CONSP TAPE  PG 390	TARP STRAP PG 390	DOT TUBING PG 391	FUEL LINE PG 392	AIR BRAKE HOSE PG 392
HYDRAULIC ADAPTERS PG 393-431	**TECHNICAL INFORMATION** PG 394-401	**PIPE SWIVELS** PG 402-403	M. SWL ADAPTER PG 402	FE. SWL ADAPTER PG 402	M. ELB ADAPTER PG 402	FE. UNION ELB. PG 402	M. 45° ELBOW PG 403	FE. 45° UNION PG 403
M. SWL TEE 403	FE. SWL TEE PG 403	FE. SWL TEE PG 403	**JIC 37 FLARE** PG 404-407	JIC CAP PG 404	JIC TUBE UNION PG 404	JIC M. CONN PG 405	JIC FE. CONN PG 405	JIC RED/EXP PG 405
PLUG PG 406	JIC UNION ELB. PG 406	JIC M. ELBOW PG 406	JIC M. ELBOW PG 406	MALE 45° ELBOW PG 407	M. BRANCH TEE PG 407	JIC FE. TEE PG 407	JIC UNION TEE PG 407	JIC BULK UNION PG 407
BULK UNION ELB PG 408	45° UNION ELB PG 408	BULK BRANCH T PG 408	BULK RUN TEE PG 408	JIC TO FEMALE 408	JIC TO MALE PG 408	**PIPE FITTINGS** PG 409-412	PIPE COU-PLING PG 409	HEX PIPE NIPPLE PG 409
EXP/ PIPE ADAP PG 409	HEX RED/ BUSH PG 409	HEX HEAD PLUG PG 410	HOLLOW HEX PLG PG 410	FLUSH HLW PLUG PG 410	SQR HEAD PLUG PG 410	PIPE CAP PG 410	MALE ELBOW PG 410	45° M. ELBOW PG 411
90° ST ELBOW PG 411	45° ST ELBOW PG 411	FE. ELBOW PG 411	45° FE. ELBOW PG 411	MALE PIPE TEE PG 412	FE. PIPE TEE PG 412	ST PIPE TEE PG 412	FE. RUN PIPE T PG 412	MALE PIPE TEE PG 412
FE. PIPE TEE PG 412	**O-RING ADAPTERS** PG 413-414	JIC TO O-RING PG 413	O-RING TO PIPE PG 413	O-RING TO 37° PG 413	FE. O-RING PG 413	O-RING TO FE. PG 414	O-RING PLUG PG 414	O-RING HLW PLG PG 414

PICTORIAL INDEX

HYDRAULICS

O-RING PORT PG 414	**FEMALE SWIVELS** PG 415-416	JIC SWL PG 415	JIC SWL PG 415	JIC SWL 45° PG 415	JIC SWL TO PG 415	JIC SWL CONN PG 415	JIC SWL TO M PG 415	JIC SWL TOF PG 416
JIC SWL PG 416	JIC SWL RUN T PG 416	**SAE O-RING ADAPTERS** PG 417-419	JIC TO ORING PG 417	JIC TO ORING PG 417	JIC BRANCH PG 417	JIC RUN TEE PG 417	ORING TO PG 417	ORING TO PG 418
ORING JIC 90° PG 418	F TO M ORING 90° PG 418	M ORING SWL AD PG 418	90° ORING SWL PG 418	45° ORING SWL PG 419	VITON O-RING PG 419	NITRILE O-RING PG 419	**O-RING FACE SEAL** PGS 419-423	BRAZE TUBE NUT PG 419
BRAZETUBE SLV PG 420	CAP PG 420	BULKHEAD LKNUT PG 420	FACE SEAL ADPT PG 420	PLUG PG 421	ORFS UNION 90° PG 421	ORFS TO M 90° PG 421	ORFS TO PIPE 90° PG 421	ORFS UNION T PG 421
M ORFS TO ORB PG 422	M TO F 37° SWL PG 422	SWL NUT ELBOW PG 422	37° SWIVEL PG 422	O-RING ELBOW PG 422	ORFS TO 45° PG 422	SWIVEL ELBOW PG 423	**BSPT, BSPP METRIC** PGS 423-426	JIC BSPT PG 423
BSPT ELBOW PG 423	HEX NIPPLE PG 423	PLUG PG 423	HEX NIPPLE BSPP PG 423	COUPLING PG 424	FEMALE SWIVEL PG 424	ELBOW PG 424	45° ELBOW PG 424	MALE NIPPLE PG 424
MALE BSPP PG 424	SWIVEL BSPP PG 425	PLUG BSPP PG 425	HOLLOW BSPP PG 425	FEMALE BSPP PG 425	MALE ELBOW PG 426	STRAIGHT SWIVEL PG 426	METRIC PARALLEL PG 426	HOLLOW PG 426
FEMALE ADAPTER PG 426	**QUICK DISCONNECTS** PGS 427-429	NO SPILL PG 427	DRYBREAK PG 427	ISO-A COUPLER PG 427	ISO-A PLUG PG 427	ISO-B COUPLER PG 427	ISO-B PLUG PG 427	FLUSH FACE PG 428
FEMALE ADAPTER-FLUSH FACE PG 428	FEMALE ADAPTERLSQ SERIES PG 428	NO SPILLLSQ SERIES PG428	AG SERIES PG 427429	ISO-A COUPLERKZE SERIES PG 427429	ISO-A PLUG-FLOW VALVE PG 427430	ISO-B COUPLERNEEDLE VALVE PG 427430	ISO-B PLUG-PRESSURE VALVE PG 427431	FLUSH FACEAIR BREATHER PG 428431

PIPE

Pipe Size	1/16	1/8	1/4	3/8	1/2	3/4	1
Thread Size	1/16-27	1/8-27	1/4-18	3/8-18	1/2-14	3/4-14	1-11 1/2
Working Pressure	1200	1200	1200	1200	1200	1000	1000
Thread OD	1/4	3/8	1/2	5/8	3/4	1	1-1/4

•Typical Application
Grease, fuels, LP and Natural gas (available on special order), refrigeration, instrumentation and hydraulic systems.

•Pressure
Operating pressure up to 1200 PSI.

•Vibration
Fair resistance.

•Temperature Range
-65^{0}F to +250^{0}F (-53^{0}C to +121^{0}C).

•Used With
Brass, bronze, copper, steel, aluminum and iron pipe.

• Tolerance
+/- .02 on all dimensions. Dimension Data can change without notice. Please call us when dimensions are critical.

• Conformance
Meets specifications and standards of ASA, ASME and SAE

• Not lead free

• "L" at the end of a Part# means Light Pattern
- these fittings are completely interchangeable with full pattern fittings, but have been modified in some way. This modification is usually in the length of the pipe threads. Used in plumbing and light industrial applications.

•Assembly Instructions
1- Tighten approximately 2-1/2 turns past hand tight.
2- Fittings with Everseal tighten two turns past hand tight. Brittle materials require special cautions.

• see page 409-412 for hydraulic pipe steel fittings.

• see page 295-297 for plastic pipe fittings.

• Lead Free Fittings see pages 158-160
• For Bronze & Larger Sizes see pages 223-231

*** For larger sizes, see bronze fittings on pg. 220-227**

Actual outside diameters of pipe threads



Actual Male Thread Profiles



WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

SAE# 130238

90° FEMALE ELBOW



	Part #	Thread Size NPTF	A	B	Approx. Wt. Lbs.	
	28-001	1/8”	0.55	0.56	0.09	----
	28-002	1/4”	0.78	0.68	0.13	----
	28-003	3/8”	0.84	0.81	0.16	----
	28-004	1/2”	1.09	1.00	0.34	----
	28-005	3/4”	1.16	1.25	0.60	----
NEW	28-015B	3/8" x 1/4"	0.84	0.81	0.18	----
NEW	28-053B	1/2" x 1/4"	1.09	1.00	0.37	----
NEW	28-016B	1/2" x 3/8"	1.09	1.00	0.36	----

100 2200P 3500 302 200

90° FORGED FEMALE ELBOW



Part #	Thread size NPTF	A	Body Width	Approx. Wt. Lbs.	
28-009	1/8”	0.57	0.50	0.04	----
28-010	1/4”	0.70	0.68	0.10	----
28-011	3/8”	0.81	0.81	0.12	----
28-012	1/2”	1.00	1.00	0.23	----
28-013	3/4”	1.13	1.25	0.42	----
28-014	1/4” x 1/8”	0.72	0.65	0.12	----
28-015	3/8” x 1/4”	0.81	0.81	0.15	----
28-016	1/2” x 3/8”	1.00	1.00	0.28	----
28-017	1"	1.42	1.50	0.75	----

1200P E7 100AF 100B

45° FEMALE ELBOW



Part #	Thread size NPTF	A	B	Approx. Wt. Lbs.	
28-018	1/8”	0.45	0.56	0.06	----
28-019	1/4”	0.66	0.68	0.12	----
28-020	3/8"	0.69	0.81	0.16	----
28-021B	1/2"	0.94	1.00	0.25	----

129 2201P 205 23355 45EZ 105 100-45A

UNION TEE

SAE# 130438



Part #	Thread size NPTF	A	B	C	Approx. Wt. Lbs.	
28-022	1/16"	0.55	0.55	0.58	0.11	----
28-024	1/8”	0.55	0.55	0.56	0.08	----
28-025	1/4”	0.78	0.78	0.68	0.17	----
28-026	3/8”	0.84	0.84	0.81	0.22	----
28-027	1/2”	1.09	1.09	1.00	0.43	----
28-028	3/4”	1.16	1.16	1.25	0.64	----

311 101A 322 2203P 3700 203

UNION FORGED TEE



Part #	Thread size NPTF	A & B	Body Width	Approx. Wt. Lbs.	
28-032	1/8”	0.56	0.50	0.06	----
28-033	1/4”	0.71	0.68	0.13	----
28-034	3/8”	0.81	0.81	0.16	----
28-035	1/2”	1.00	1.00	0.27	----
28-036	3/4”	1.16	1.25	0.53	----
28-023	1”	1.42	1.50	.924	----

1203P LT7 101AF 101B

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

REDUCING FORGED TEES



Part #	1 NPT	2 NPT	3 NPT	A & B	Body Width	Approx. Wt. Lbs.	
28-029	1/8”	1/8”	1/4”	0.72	0.69	0.16	----
28-030	1/4”	1/4”	1/8”	0.72	0.69	0.14	----
28-031	1/4”	1/4”	3/8”	0.81	0.81	0.21	----
28-038	3/8”	1/4”	3/8”	0.81	0.81	0.18	----
28-039	3/8”	3/8”	1/4”	0.81	0.81	0.18	----
28-046	1/2”	1/2”	3/8”	1.00	1.00	0.30	----
28-047	3/4"	1/2"	3/4"	1.20	1.25	0.59	----
28-048	3/4”	3/4”	1/2”	1.16	1.25	0.59	----

CROSS



Part #	Thread size NPTF	A	B	Approx. Wt. Lbs.	
28-041	1/8”	0.55	0.56	0.10	----
28-042	1/4”	0.78	0.68	0.21	----
28-043	3/8”	0.84	0.81	0.25	----
28-044	1/2”	1.09	1.00	0.51	----
28-045	3/4”	1.16	1.25	0.75	----

2205P 3950 228 102A 102BE

FORGED CROSS



Part #	Thread size NPTF	A	Body Width	Approx. Wt. Lbs.	
28-049	1/8”	0.56	0.50	0.06	----
28-050	1/4”	0.72	0.69	0.15	----
28-051	3/8”	0.81	0.81	0.18	----
28-052	1/2”	1.00	1.00	0.34	----

C7 105 102AF 102B

COUPLING

SAE# 130138



Part #	Thread size NPTF	A	Hex	Approx. Wt. Lbs.	
28-057	1/16"	0.75	0.44	0.02	
28-058L	1/8”	0.75	0.50	0.02	----
28-058	1/8”	0.75	0.56	0.03	----
28-059L	1/4”	0.88	0.63	0.03	----
28-059	1/4”	1.12	0.75	0.09	----
28-060L	3/8”	1.00	0.81	0.06	----
28-060	3/8”	1.12	0.87	0.10	----
28-061L	1/2”	1.19	0.93	0.09	----
28-061	1/2”	1.50	1.06	0.19	----
28-062L	3/4”	1.19	1.25	0.18	----
28-062	3/4”	1.53	1.25	0.24	----
28-063	1"	1.89	1.50	.357	----

207P 371 3300 103AH 103B

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

REDUCING COUPLING

SAE# 130138



	Part #	Thread size NPTF	A	Hex	Approx. Wt. Lbs.	
	28-181L	1/4" x 1/8"	0.94	0.62	0.04	----
	28-181	1/4" x 1/8"	0.97	0.75	0.08	----
	28-182	3/8" x 1/8"	0.94	0.87	0.10	----
	28-183L	3/8" x 1/4"	1.00	0.81	0.06	----
	28-183	3/8" x 1/4"	1.16	0.87	0.12	----
	28-180*	1/2" x 1/8"	1.19	0.93	0.15	----
	28-184L	1/2" x 1/4"	1.11	1.00	0.10	----
	28-184	1/2" x 1/4"	1.28	1.06	0.20	----
	28-185L	1/2" x 3/8"	1.19	0.93	0.10	----
	28-185	1/2" x 3/8"	1.38	1.06	0.20	----
NEW	28-186	3/4" x 1/8"	1.19	1.19	0.16	----
NEW	28-187	3/4" x 1/4"	1.19	1.19	0.17	----
	28-188*	3/4" x 3/8"	1.32	1.37	0.20	----
	28-189*	3/4" x 1/2"	1.19	1.18	0.14	----
NEW	28-178	1" x 1/2"	1.50	1.56	0.41	----
NEW	28-179	1" x 3/4"	1.56	1.56	0.39	----

*Not to SAE specs

377 3300 208P 108 119B 119AH

UNION



	Part #	Thread size NPTF	A	Hex	Approx. Wt. Lbs.	
	28-067	1/8"	1.25	0.94	0.13	----
	28-068	1/4"	1.31	1.06	0.18	----
	28-069	3/8"	1.75	1.25	0.33	----
	28-070	1/2"	1.79	1.56	0.50	----
NEW	28-071	3/4"	1.96	1.68	0.47	----

3250 212P 104A 104B

CAP



Part #	Thread size NPTF	A	Hex	Approx. Wt. Lbs.	
28-075	1/8"	0.47	0.56	0.03	----
28-076	1/4"	0.60	0.68	0.04	----
28-077	3/8"	0.69	0.81	0.06	----
28-078	1/2"	0.78	0.93	0.08	----
28-079	3/4"	0.94	1.25	0.16	----
28-080	1"	1.13	1.50	0.23	----

3129 213P 23129 108A 108B

90⁰ STREET ELBOW

SAE# 130239



	Part #	Thread size NPTF	A	B	C	Approx. Wt. Lbs.	
NEW	28-161	1/16"	0.69	0.60	0.47	0.04	----
	28-156	1/8"	0.48	0.66	0.56	0.05	----
	28-156S	1/8" short	0.34	0.57	0.50	0.03	----
	28-157	1/4"	0.72	0.91	0.735	0.09	----
	28-157S	1/4" short	0.45	0.78	0.68	0.07	----
	28-158	3/8"	0.78	0.97	0.81	0.16	----
	28-159	1/2"	1.03	1.25	1.00	0.33	----
	28-160	3/4"	1.12	1.38	1.25	0.52	----

2202P 304 115 202 3400 116A

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

FORGED 90° STREET ELBOW



Part #	Thread size NPTF	A	B	Wrench Flats	Approx. Wt. Lbs.	
28-165	1/8”	0.61	0.85	0.62	0.06	----
28-166	1/4”	0.50	0.86	0.72	0.08	----
28-167	3/8”	0.70	1.00	0.88	0.10	----
28-168	1/2”	0.96	1.43	1.00	0.20	----
28-169	3/4”	0.90	1.40	1.25	0.25	----

5E8 1202P 116AF 116B

FORGED REDUCING 90° STREET ELBOW



	Part #	Thread size NPTF FxM	A	B	Wrench flats	Approx. Wt. Lbs.	
NEW	28-259*	1/8" x 1/16"					----
	28-260	1/8” x 1/4”	0.50	0.87	0.71	0.08	----
	28-261B*	1/4” x 1/8”	0.53	0.72	0.69	0.07	----
	28-261	1/4” x 1/8”	0.50	0.81	0.72	0.06	----
	28-262	1/4” x 3/8”	0.93	1.06	0.59	0.12	----
	28-263	3/8” x 1/4”	0.58	0.94	0.81	0.07	----
	28-264	3/8” x 1/2”	0.97	1.36	1.00	0.28	----
	28-265	1/2” x 3/8”	0.96	1.37	1.00	0.22	----
NEW	28-265B*	1/2" x 3/8"	1.03	1.11	1.00	0.24	----

*Barstock

HEX BUSHING

SAE# 130140



Part #	Thread size NPTF MxF	A	Hex	Approx. Wt. Lbs.	
28-102L	1/4” x 1/8”	0.62	0.56	0.02	----
28-102	1/4” x 1/8”	0.75	0.56	0.04	----
28-103	3/8” x 1/8”	0.75	0.68	0.05	----
28-104L	3/8” x 1/4”	0.69	0.68	0.03	----
28-104	3/8” x 1/4”	0.75	0.75	0.05	----
28-105L	1/2” x 1/8”	0.81	0.81	0.08	----
28-105	1/2” x 1/8”	1.00	0.87	0.10	----
28-106L	1/2” x 1/4”	0.81	0.81	0.08	----
28-106	1/2” x 1/4”	1.00	0.87	0.11	----
28-107L	1/2” x 3/8”	0.81	0.81	0.05	----
28-107	1/2” x 3/8”	1.00	0.87	0.10	----
28-108	3/4” x 1/8”	0.94	1.06	0.20	----
28-109L	3/4” x 1/4”	0.94	1.06	0.18	----
28-110L	3/4” x 3/8”	0.94	1.06	0.15	----
28-111L	3/4” x 1/2”	0.94	1.06	0.11	----
28-111	3/4” x 1/2”	1.00	1.12	0.14	----
NEW 28-091	1" x 1/8"	1.15	1.37	0.29	----
28-112	1” x 1/4”	1.15	1.37	0.32	----
28-113	1” x 3/8”	1.12	1.37	0.30	----
28-114	1” x 1/2”	1.31	1.44	0.29	----
28-115	1” x 3/4”	1.31	1.37	0.20	----

373 3220 209P 110A 110B

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

FACE BUSHING



	Part #	Thread size NPTF MxF	A	Approx. Wt. Lbs.	
	28-121	1/4" x 1/8"	0.45	0.01	----
	28-122	3/8" x 1/8"	0.50	0.03	----
	28-116	3/8" x 1/4"	0.50	0.02	----
	28-090	1/2" x 1/8"	0.56	0.06	----
	28-128	1/2" x 1/4"	0.56	0.05	----
	28-117	1/2" x 3/8"	0.56	0.03	----
	28-129	3/4" x 1/4"	0.62	0.11	----
	28-130	3/4" x 3/8"	0.62	0.08	----
	28-118	3/4" x 1/2"	0.64	0.03	----
NEW	28-120	1" x 1/2"	0.75	0.11	----
	28-119	1" x 3/4"	0.77	0.10	----

SQUARE HEAD PLUG
1/8 - 1/2 Solid



Part #	Thread size NPTF	A	B	Approx. Wt. Lbs.	
28-084	1/8"	0.58	0.27	0.02	----
28-085	1/4"	0.80	0.37	0.03	----
28-086	3/8"	0.80	0.43	0.06	----
28-087	1/2"	1.07	0.55	0.13	----
28-088**	3/4"	1.09	0.61	0.20	----
28-089**	1"	1.24	0.81	0.35	----

** Cored

3151 211P 109A 109B

COUNTERSUNK HEX PLUG
3/4" taper thread



Part #	Thread size NPTF	A	Socket size	Approx. Wt. Lbs.	
28-092	1/16"	0.30	0.12	0.01	----
28-093	1/8"	0.30	0.18	0.01	----
28-094	1/4"	0.45	0.26	0.02	----
28-095	3/8"	0.45	0.31	0.03	----
28-096	1/2"	0.61	0.39	0.05	----
28-097	3/4"	0.62	0.56	0.10	----

3153 219P 109CS 118

SLOTTED-HEAD PLUG

	Part #	Thread size NPTF	A	Approx. Wt. Lbs.	
	28-174	1/8"	0.31	0.01	----
	28-175	1/4"	0.42	0.02	----
	28-176	3/8"	0.45	0.05	----
NEW	28-177	1/2"	0.56	0.10	

220P 3150 117A 117B

CORED HEX PLUGS



	Part #	Thread size NPTF	A	Hex	Approx. Wt. Lbs.	
NEW	28-200	1/16"	0.48	0.38	0.01	----
	28-201	1/8"	0.55	0.43	0.01	----
	28-202	1/4"	0.62	0.56	0.02	----
	28-203	3/8"	0.72	0.68	0.06	----
	28-204	1/2"	0.81	0.87	0.09	----
	28-205	3/4"	0.94	1.06	0.16	----
	28-206	1"	1.16	1.37	0.28	----

218P 3152 121A 103 121B PPH 218P

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

SOLID HEX HEAD PLUGS



Part #	Thread size NPTF	A	Hex	Approx. Wt. Lbs.	
28-201S	1/8’	0.55	0.43	0.02	----
28-202S	1/4”	0.75	0.56	0.05	----
28-203S	3/8”	0.66	0.68	0.07	----
28-204S	1/2”	0.81	0.87	0.12	----
28-205S	3/4”	0.92	1.06	0.24	----
28-206S	1”	1.00	1.31	0.38	----

121AS

LOCKNUT

- **Jam Nuts**
- **Straight pipe thread**

	Part #	Thread size NPSL	Hex	Thickness	Approx. Wt. Lbs.	
	28-123	1/8”	0.68	0.19	0.02	----
	28-124	1/4”	0.87	0.25	0.04	----
	28-125	3/8”	1.00	0.31	0.04	----
	28-126	1/2”	1.125	0.25	0.04	----
NEW	28-127	3/4"	1.38	0.38	0.09	----

210P 21102 111A 111B

CLOSE NIPPLE



Part #	Thread size NPTF	A	Approx. Wt. Lbs.	
28-131	1/8”	0.75	0.01	----
28-132	1/4”	0.88	0.02	----
28-133	3/8”	1.00	0.05	----
28-134	1/2”	1.12	0.06	----
28-135	3/4”	1.31	0.11	----

165 215PN 3326 112A 112B

LONG NIPPLE



Part #	Thread size NPTF	A Length	Approx. Wt. Lbs.	
28-140	1/8”	1.50	0.03	----
28-141	1/8”	2.00	0.04	----
28-142	1/8”	2.50	0.06	----
28-143	1/8”	3.00	0.06	----
28-475	1/8"	3.50	0.07	----
28-144	1/4”	1.50	0.03	----
28-145	1/4”	2.00	0.05	----
28-146	1/4”	2.50	0.08	----
28-147	1/4”	3.00	0.10	----
28-481	1/4"	3.50	0.12	----
28-148	3/8”	1.50	0.06	----
28-149	3/8”	2.00	0.10	----
28-150	3/8”	2.50	0.10	----
28-151	3/8”	3.00	0.13	----
28-487	3/8"	3.50	0.17	----
28-152	1/2”	1.50	0.08	----
28-153	1/2”	2.00	0.12	----
28-154	1/2”	2.50	0.16	----
28-155	1/2”	3.00	0.20	----
28-493	1/2"	3.50	0.24	----
28-136	3/4"	1.50	0.12	----
28-497	3/4"	2.00	0.18	----
28-498	3/4"	2.50	0.23	----
28-499	3/4"	3.00	0.28	----

• NOTE: For longer lengths and larger diameters, see our red brass nipples section, pg. 215-222

113B 113A 166 3327, 3328, 3329, 3330 3331 215PNL

HEX NIPPLE

SAE# 130137



	Part #	Thread size NPTF	A	Hex	Approx. Wt. Lbs.	
NEW	28-210	1/16"	0.97	0.38	0.02	----
	28-211L	1/8”	0.91	0.43	0.02	----
	28-211	1/8”	0.97	0.43	0.03	----
	28-212L	1/4”	1.12	0.56	0.04	----
	28-212	1/4”	1.38	0.56	0.06	----
	28-213L	3/8”	1.25	0.68	0.07	----
	28-213	3/8”	1.41	0.68	0.07	----
	28-214L	1/2”	1.50	0.87	0.11	----
	28-214	1/2”	1.81	0.87	0.17	----
	28-215L	3/4"	1.55	1.07	0.17	----
	28-215	3/4”	1.96	1.13	0.23	----
	28-216L	1"	1.75	1.39	0.22	----
	28-216	1”	2.30	1.37	0.43	----

216P 3325 379 122AH 122B

REDUCING HEX NIPPLE

SAE# 130137



	Part #	Thread size NPTF	A	Hex	Approx. Wt. Lbs.	
NEW	28-218	1/8" x 1/16"	1.00	0.56	0.05	----
	28-220L	1/4” x 1/8”	1.00	0.56	0.04	----
	28-220	1/4” x 1/8”	1.19	0.56	0.04	----
	28-221L	3/8” x 1/8”	1.11	0.68	0.06	----
	28-221	3/8” x 1/8”	1.22	0.68	0.07	----
	28-222L	3/8” x 1/4”	1.19	0.68	0.06	----
	28-222	3/8” x 1/4”	1.41	0.68	0.07	----
	28-223L	1/2” x 1/4”	1.34	0.87	0.09	----
	28-223	1/2” x 1/4”	1.62	0.87	0.12	----
	28-224L	1/2” x 3/8”	1.41	0.87	0.11	----
	28-224	1/2” x 3/8”	1.62	0.87	0.12	----
NEW	28-225L	3/4" x 1/2"	1.81	1.06	0.19	----
	28-225	3/4” x 1/2”	1.50	1.06	0.15	----
NEW	28-227	1" x 3/4"	2.31	1.38	0.38	----

216P 3325 379 122AH 122B

45° STREET ELBOW

SAE# 130339



Part #	Thread size NPTF	B	A	C	Approx. Wt. Lbs.	
28-230	1/8”	0.38	0.50	0.56	0.03	----
28-231	1/4”	0.56	0.72	0.68	0.09	----
28-232	3/8”	0.56	0.78	0.81	0.12	----
28-233	1/2”	0.75	1.00	1.00	0.20	----
28-234	3/4”	0.75	1.06	1.25	0.34	----

306 3350 2214P 224

45⁰ FORGED STREET ELBOW



Part #	Thread size NPTF	A	B	Wrench flats	Approx. Wt. Lbs.	
28-238	1/8”	0.63	0.81	0.56	0.05	----
28-239	1/4”	0.63	1.06	0.81	0.11	----
28-240	3/8”	0.72	1.06	0.93	0.17	----

45E8 124B

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

STREET TEE/ SERVICE TEE/ MALE RUN TEE

SAE# 130424



Part #	Thread size NPTF	A	B	C	Approx. Wt. Lbs.	
28-245	1/8”	0.55	0.66	0.56	0.08	----
28-246	1/4”	0.78	0.91	0.68	0.17	----
28-247	3/8”	0.84	0.97	0.81	0.22	----
28-248	1/2”	1.09	1.25	1.00	0.40	----
28-249	3/4”	1.16	1.39	1.25	0.60	----

225 2225P 3750 326 225 127A

FORGED STREET TEE



Part #	Thread size NPTF	A	B	Body Width	Approx. Wt. Lbs.	
28-253	1/8”	0.56	0.75	0.50	0.05	----
28-254	1/4”	1.03	1.00	0.46	0.13	----
28-255	3/8”	1.19	1.09	0.68	0.24	----
28-256	1/2”	1.52	1.40	0.88	0.45	----
28-257	3/4”	1.34	1.73	1.25	0.65	----

107 T8 127B

EXTENDER ADAPTER

SAE# 130139



	Part #	Thread size NPTF FxM	A	Hex	Approx. Wt. Lbs.	
	28-190L	1/8” x 1/8”	0.83	0.50	0.03	----
	28-190	1/8” x 1/8”	0.88	0.56	0.04	----
	28-191L	1/4” x 1/8”	0.94	0.62	0.04	----
	28-191	1/4” x 1/8”	1.06	0.75	0.07	----
	28-192L	1/4” x 1/4”	1.00	0.62	0.04	----
	28-192	1/4” x 1/4”	1.25	0.75	0.07	----
	28-198	3/8” x 1/8”	1.00	0.81	0.06	----
	28-193L	3/8” x 1/4”	1.12	0.81	0.08	----
	28-193	3/8” x 1/4”	1.25	0.87	0.09	----
	28-194L	3/8” x 3/8”	1.24	0.81	0.10	----
	28-194	3/8” x 3/8”	1.25	0.87	0.11	----
NEW	28-197	1/2" x 1/8"	1.09	0.94	0.07	----
	28-199	1/2” x 1/4”	1.46	1.06	0.08	----
	28-195L	1/2” x 3/8”	1.19	0.93	0.09	----
	28-195	1/2” x 3/8”	1.47	1.06	0.18	----
	28-196L	1/2" x 1/2"	1.25	0.94	0.10	----
	28-196	1/2” x 1/2”	1.66	1.06	0.12	----
	28-207	3/4” x 3/8”	1.59	1.25	0.26	----
	28-208	3/4” x 1/2”	1.69	1.37	0.14	----
	28-208L	3/4” x 1/2”	1.22	1.25	0.13	----
	28-209	3/4” x 3/4”	1.69	1.37	0.34	----

375 222P 3200 R1 120AH 120B

PIPE SWIVEL ADAPTER

*300 PSI all sizes



Part #	Thread size NPTF FxM	A	Hex 1	Hex 2	Approx. Wt. Lbs.	
28-424	1/8"	1.10	0.43	0.50	0.05	----
28-425	1/4”	1.34	0.56	0.62	0.06	----
28-426	3/8”	1.36	0.68	0.75	0.08	----
28-427	1/2"	1.87	0.87	0.95	0.10	----

Male NPT x Female NPT

- 360° Turning
- Swivels

Part #	Size	
320-061	1/4	----

344R 3183

FORGED 90° MALE ELBOW



Part #	Thread size NPTF	A	Body Width	Approx. Wt. Lbs.	
28-266	1/8”	0.79	0.38	0.04	----
28-267	1/4”	0.87	0.45	0.06	----
28-268	3/8”	1.06	0.59	0.12	----
28-269	1/2”	1.38	0.78	0.21	----

LE5 3455 116AMF

BARSTOCK 90° MALE ELBOW

NEW



Part #	Thread size NPTF	A	Body Width	Approx. Wt. Lbs.	
28-266B	1/8"	0.69	0.56	0.08	----
28-267B	1/4"	0.95	0.59	0.09	----
28-268B	3/8"	1.01	0.71	0.15	----
28-269B	1/2"	1.40	1.00	0.38	----
28-270B	3/4"	1.50	1.25	0.55	----
28-276B	1/2" x 3/8"	1.12	1.00	0.35	----

FORGED 90° MALE REDUCING ELBOW

Part #	Thread size NPTF	A	B	Body Width	Approx. Wt. Lbs.	
28-274	1/4”x 1/8”	0.88	0.78	0.47	0.06	----
28-275	3/8” x 1/4”	0.90	0.90	0.46	0.06	----
28-276	1/2” x 3/8”	1.12	1.00	0.59	0.12	----

MALE BRANCH TEE

SAE# 130425



Part #	Thread size NPTF	A	B	C	Approx. Wt. Lbs.	
28-281	1/8”	0.66	0.55	0.56	0.08	----
28-282	1/4”	0.91	0.78	0.68	0.15	----
28-283	3/8”	0.97	0.84	0.81	0.22	----
28-284	1/2”	1.25	1.09	1.00	0.40	----
28-285	3/4”	1.38	1.16	1.25	0.62	----

T9 X106 23601 3600 2224P 226 329 128

FORGED MALE BRANCH TEE



Part #	Thread size NPTF	A	B	Body Width	Approx. Wt. Lbs.	
28-281F	1/8”	0.75	0.56	0.50	0.06	----
28-282F	1/4”	1.00	1.03	0.46	0.12	----

T9

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

FORGED ALL MALE TEE



Part #	Thread size NPTF	A	B	Body Width	Approx. Wt. Lbs.	
28-290	1/8”	0.75	0.75	0.43	0.06	----
28-291	1/4”	0.86	0.86	0.43	0.08	----
28-292	3/8”	1.09	1.09	0.60	0.16	----
28-293	1/2”	1.22	1.22	0.68	0.22	----
28-294	3/4”	1.43	1.43	0.87	0.38	----

T12 M101

LONG STREET ELLS

D.O.T. Approved



Part #	Thread size NPTF	A	B	Approx. Wt. Lbs.	
28-440	1/8”	1-3/16”	0.50	0.06	----
28-441	1/8”	1-7/16”	0.50	0.06	----
28-442	1/8”	1-11/16”	0.50	0.06	----
28-443	1/8”	1-7/8”	0.50	0.16	----
28-328	1/4”	1-3/16”	0.75	0.12	----
28-329	1/4”	1-7/16”	0.75	0.14	----
28-330	1/4”	1-11/16”	0.75	0.15	----
28-331	1/4"	1-7/8"	0.62	0.09	----
28-332	1/4”	2-1/4”	0.75	0.17	----
28-333	3/8”	1-3/4”	0.87	0.22	----

LONG EXTENSION ADAPTERS

D.O.T. Approved



Part #	Thread size NPTF	A	Hex	Approx. Wt. Lbs.	
28-335	1/8”	1-1/4”	0.50	0.04	----
28-336	1/8”	1-3/4”	0.50	0.05	----
28-337	1/8”	3”	0.50	0.09	----
28-338	1/4”	1-9/16”	0.62	0.07	----
28-339	1/4”	1-13/16”	0.62	0.08	----
28-340	1/4”	2-1/16”	0.62	0.10	----

PIPE WYE FIP x MIP



28-295



28-296

Part #	Thread Size NPT	A	Approx. Wt. Lbs.	
28-295	1/4"	1.56	.15	----
28-296	1/4 N/P	1.4	.12	----

PIPE WYE FIP x FIP - NICKEL PLATED

Part #	Thread Size NPT	A	Approx. Wt. Lbs.	
28-298	1/4	1.4	.12	----

BULKHEAD / ANCHOR / FRAME COUPLINGS

FEMALE PIPE X FEMALE PIPE



Part #	Terminal Bolts/ Frame A	B	Hole Size	Length (in.)	
28-299	1/8-27 NPTF	5/8-18 UNS	5/8	0.96	----
28-300	1/8-27 NPTF	5/8-18 UNS	5/8	1-1/2	----
28-301	1/4-18 NPTF	3/4-16 UNS	3/4	15/16	----
28-302	1/4-18 NPTF	3/4-16 UNS	3/4	1-1/2	----
28-315*	1/4-18 NPTF	3/4-16 UNS	3/4	1-1/2	----
28-303	3/8-18 NPTF	1-14 UNS	1	1-5/16	----
28-304	1/2-14 NPTF	1-1/8-14 UNS	1-1/8	1-1/2	----
28-311	3/4-14 NPTF	1-5/16-12	1-5/16	1-1/2	----
28-316**	1-11/1/2	1-5/8-14	1-5/8	1.68	----

* Same as 28-302 except with a larger mounting nut. **Without washer



FEMALE PIPE X MALE PIPE

	A	B	C		
28-317	1/4-18 NPTF	1-14 UNS	1/2-14 NPTF	2-1/8	----
28-318	3/8-18 NPTF	1-14 UNS	1/2-14 NPTF	1-11/16	----
28-319	3/8-18 NPTF	1-14 UNS	1/2-14 NPTF	1-29/32	----



FEMALE PIPE X MALE PIPE

28-313	1/4-18 NPTF	1-14 UNS	1/2-14 NPTF	2-7/8	----



FEMALE PIPE X MALE PIPE

28-346	3/8-18 NPTF	1-14 UNS	1/2-14 NPTF	1-7/8	----
28-347	1/2-14 NPTF	1-14 UNS	1/2-14 NPTF	2-3/8	----



TUBE X FEMALE PIPE

28-321	1/2-O.D. Tube	7/8-20 UNCF	3/8-18 NPTF	1-5/16	----
28-322	3/8-O.D. Tube	7/8-20 UNCF	3/8-18 NPTF	1-3/8	----



FEMALE PIPE X CLAMPING STUD ELBOW

28-348	3/8-18 NPTF	7/8-20 UNEF	3/8-18 NPTF	2-5/16	----

BRASS MARINE BULKHEAD

46-540	5/16 Hose ID	----	----	2.37	----
46-541	3/8 Hose ID	----	----	2.37	----

CROSSOVER NUMBERS

28-300	207x2	129A-A	50004	55207								1495B-A	ACBH207-2	207ACBH-2					
28-301	207X4	129AS-B		55611		S611	114-44	1345	382-44S	392C-94			ACBHS207-4						
28-302	207X4	129A-B	50005	55661			114B-44	1344	382-44L		035081		ACBH207-4	207ACBH-4			11306		90648
28-303	207X6	129A-C	50006	55607		S661/S607	114-66	1346	382-66		035087		ACBH207-6	207ACBH-6			11307	17709	
28-304	207X8	129A-D	50007	55807		S807	114-88	1351					ACBH207-8	207ACBH-8					
28-317				55615		S615	117-84												
28-318				55620		S620			381-86S						11304				
28-319			50001				115-86				035079	1496-DC							
28-313			50010	55600		S664	115-88	1342	380-84	5730	035021				11300	55X6			
28-346			50013	55613		S613													
28-347			50012	55629		S629					035039								
28-321					391-86/1347	S608													
28-322					391-66	S609													
28-348				55616															

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

STEEL BULKHEAD FITTINGS

	Part #	Terminal Bolts/ Frame A	B	C	Length (in.)	List
	28-306	1/4-18 NPTF	3/4 - 16 UNS		0.94	----
	28-307	1/4-18 NPTF	3/4 - 16 UNS		1.50	----
	28-308	3/8-18 NPTF	1 - 14 UNS		1.31	----
		FEMALE PIPE X MALE PIPE				
	28-309	1/4-18 NPTF	3/4 - 16 UNS	1/2-14 NPTF	2.16	----
	28-310	1/4-18 NPTF	3/4 - 16 UNS	1/2-14 NPTF	2.53	----
	28-345	1/4-18 NPTF	3/4 - 16 UNS	1/2-14 NPTF	2-5/32	----
		FEMALE PIPE X MALE PIPE				
	28-325	1/4-18 NPTF	3/4 - 16 UNS	1/2-14 NPTF	1-11/16	----
	28-312	1/4-18 NPTF	1-14 UNS	1/2-14 NPTF	2.94	----
	28-320	1/4-18 NPTF	1-14 UNS	1/2-14 NPTF	3-15/16	----

STAINLESS STEEL BULKHEAD FITTINGS

- Temperature range: -20F°- 360F°
- Working pressure: 1450 - 2175PSI

BULKHEAD FITTINGS - STAINLESS STEEL 316L NPT (1/8-1/2")

Part #	Size	Hole Size	Hex	Length	
28300SS	1/8"	0.701	0.866	0.748	----
28301SS	1/4"	0.858	1.063	0.748	----
28303SS	3/8"	1.055	1.260	1.102	----
28304SS	1/2"	1.173	1.417	1.378	----

BULKHEAD FITTINGS - STAINLESS STEEL 316 NPT (3/4-2")

Part #	Size	Hole Size	Hex	Length	
63214	3/4"	1-5/8"	2-15/32"	1-13/16"	----
63215	1"	2-1/4"	3-1/16"	2-7/8"	----
63216	1-1/4"	2-1/4"	3-1/16"	2-3/8"	----
63217	1-1/2"	3"	4-1/4"	2-5/8"	----
63218	2"	3"	4-1/4"	2-5/8"	----

No act of kindness, no matter how small, is ever wasted. - Aesop

HOSE BARB FITTINGS

• Temperature and Working Pressure Ranges
From -40^{0}F to + 160^{0}F at 150 PSI maximum.

• Tolerance
+/- .02 on all dimensions. Dimension Data can change without notice. Please call us when dimensions are critical.

Note: These fittings are intended for use with hose clamp, similar type clamp or a crimped ferrule.

• Assembly Instructions

1- Cut hose cleanly and squarely to length.
2- Slide clamp on hose.
3- Lubricate hose. Push hose on fitting until hose bottoms against stop ring or hex.
4- Position hose clamp as shown below and secure with a screwdriver or wrench. Maintain "A" dimension noted below for proper clamp positioning.



• For Lead Free AB1953 Compliant Fittings
see pages 160--161
Other Barbs available

See page 292-295 for plastic hose barb fittings

See page 27-28 for stainless steel hose barbs

See page 307 for King Nipples

Stainless Steel hose barbs for beverage service available -
See beverage fitting section, pg. 28-29

Hose Size	A
3/16"	1/4"
1/4"	1/4"
5/16"	1/4"
3/8"	1/8"
1/2"	1/8"
5/8"	1/8"
3/4"	1/8"

Actual Profile of Hose Barbs



WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

RIGID MALE ADAPTER

• These are not Lead Free



	Part #	Hose I.D. x Male NPTF	A	B	Hex	Approx. Wt. Lbs.	
NEW	32-950	1/16" x 10/32"	0.90	0.45	0.38	0.01	----
NEW	32-951	1/16" x 1/16"	0.91	0.48	0.38	0.01	----
NEW	32-912	1/8" x 10/32"	0.92	0.48	0.38	0.01	----
NEW	32-300	1/8" x 1/16"	0.93	0.48	0.38	0.01	----
	32-001 *	1/8” x 1/8”	1.19	0.69	0.43	0.02	----
	32-027	1/8” x 1/4”	1.16	0.46	0.56	0.02	----
NEW	32-952	3/16" x 1/16"	1.20	0.75	0.38	0.02	----
	32-002 *	3/16” x 1/8”	1.19	0.75	0.43	0.02	----
	32-003 *	3/16” x 1/4”	1.37	0.69	0.56	0.04	----
NEW	32-953	3/16" x 3/8"	1.44	0.69	0.68	0.04	----
	32-301	1/4” x 1/16”	1.44	0.88	0.43	0.02	----
	32-004 *	1/4” x 1/8”	1.47	0.97	0.43	0.02	----
	32-005 *	1/4” x 1/4”	1.72	0.97	0.56	0.04	----
	32-006 *	1/4” x 3/8”	1.72	0.97	0.68	0.05	----
	32-007	1/4” x 1/2”	1.72	0.81	0.87	0.10	----
NEW	32-954	1/4" x 3/4"	1.86	0.96	1.06	0.15	----
	32-008 *	5/16” x 1/8”	1.47	0.97	0.43	0.02	----
	32-009 *	5/16” x 1/4”	1.72	0.97	0.56	0.04	----
	32-010 *	5/16” x 3/8”	1.76	0.97	0.68	0.06	----
	32-390	5/16” x 1/2”	1.88	0.95	0.87	0.10	----
NEW	32-955	5/16" x 3/4"	1.95	0.95	1.06	0.15	----
	32-011 *	3/8” x 1/8”	1.53	0.97	0.56	0.03	----
	32-012 *	3/8” x 1/4”	1.75	0.97	0.56	0.05	----
	32-013 *	3/8” x 3/8”	1.72	0.96	0.68	0.06	----
	32-014 *	3/8” x 1/2”	1.87	0.97	0.87	0.09	----
	32-026 *	3/8” x 3/4”	1.97	0.97	1.06	0.16	----
NEW	32-956	7/16" x 1/4"	1.75	0.97	0.56	0.05	----
NEW	32-957	7/16" x 3/8"	1.73	0.97	0.70	0.07	----
NEW	32-958	7/16" x 1/2"	1.87	0.97	0.88	0.10	----
	32-302	1/2” x 1/8”	1.57	0.95	0.56	0.06	----
	32-015 *	1/2” x 1/4”	1.72	0.97	0.56	0.04	----
	32-016 *	1/2” x 3/8”	1.76	0.97	0.68	0.07	----
	32-017 *	1/2” x 1/2”	1.87	0.96	0.87	0.11	----
	32-018 *	1/2” x 3/4”	1.94	0.97	1.06	0.16	----
	32-303	1/2” x 1”	2.31	0.99	1.37	0.33	----
	32-304	5/8” x 1/4”	1.67	0.92	0.68	0.06	----
	32-019 *	5/8” x 3/8”	1.76	0.97	0.68	0.08	----
	32-020 *	5/8” x 1/2”	1.87	0.96	0.87	0.11	----
	32-021 *	5/8” x 3/4”	1.87	0.96	1.06	0.14	----
	32-305	5/8” x 1”	2.31	0.96	1.37	0.36	----
NEW	32-915	3/4" x 1/4"	1.64	0.87	0.81	0.11	----
	32-306	3/4” x 3/8”	1.65	0.87	0.81	0.12	----
	32-022 *	3/4” x 1/2”	1.87	0.96	0.87	0.14	----
	32-023 *	3/4” x 3/4”	1.87	0.96	1.06	0.15	----
	32-316	3/4” x 1”	2.55	1.15	1.37	0.38	----
	32-307	1” x 1/2”	1.80	0.87	1.06	0.18	----
	32-024 *	1” x 3/4”	2.19	1.19	1.06	0.32	----
	32-025 *	1” x 1”	2.48	1.19	1.37	0.39	----
	32-029	1-1/4" x 3/4"	2.37	1.19	1.37	0.35	----
	32-028	1-1/4” x 1”	2.55	1.19	1.37	0.46	----

4244 PGH 101 102 201A 125HBL 105B-1 KF-PS MPB

* See page 27 for stainless steel.

See page 28 for beverage #303 stainless fittings

HOSE BARB

BRASS RIGID MALE BSPT BARB ADAPTER

Part #	Hose I.D. x MALE BSPT	
32-450	1/4" x 1/8"	----
32-451	1/4" x 1/4"	----
32-452	3/8" x 1/4"	----
32-453	3/8" x 3/8"	----
32-454	3/8" x 1/2"	----
32-455	1/2" x 3/8"	----
32-456	1/2" x 1/2"	----
32-457	3/4" x 3/4"	----
32-458	1" x 1"	----

SWIVEL MALE ADAPTER



Rotation 360°

Part #	Hose I.D. x Male NPTF	A	B	Hex	Approx. Wt. Lbs.	
32-329	3/16" x 1/8"	2.00	0.78	0.56	0.06	----
32-331	3/16" x 1/4"	1.95	0.78	0.56	0.06	----
32-332	1/4" x 1/8"	2.19	0.97	0.56	0.06	----
32-349	1/4" x 1/4"	2.12	0.97	0.56	0.06	----
32-351	3/8" x 1/8"	2.12	0.97	0.56	0.07	----
32-201	3/8" x 1/4"	2.12	0.97	0.56	0.07	----
32-360	3/8" x 3/8"	2.12	0.97	0.69	0.08	----
32-355	1/2" x 3/8"	2.12	0.97	0.68	0.10	----
32-356	1/2" x 1/2"	2.33	0.97	0.87	0.14	----
32-357	3/4" x 3/4"	2.33	0.97	1.06	0.20	----
32-386	1" x 1"	2.88	1.19	1.38	0.40	----

SMS 103



Part #	Hose I.D. x Male NPTF	A	B	Hex	Approx. Wt. Lbs.	
32-200	1/4" x 1/4"	1.65	.89	0.56	0.04	----
32-202	3/8" x 3/8"	1.75	1.00	0.68	0.08	----

MENDER/ SPLICER



	Part #	Hose I.D. x Hose I.D.	A	B	O.D.	Approx. Wt. Lbs.	
	32-091 *	1/8"	0.98	0.45	0.31	0.01	----
	32-092	3/16"	1.62	0.77	0.36	0.02	----
	32-093 *	1/4"	2.00	0.96	0.37	0.02	----
	32-079 *	1/4" x 1/8"	1.50	0.97	0.37	0.02	----
	32-094 *	5/16"	2.00	0.96	0.39	0.02	----
	32-090 *	5/16" x 1/4"	2.00	0.97	0.50	0.03	----
	32-095 *	3/8"	2.00	0.97	0.51	0.04	----
NEW	32-960	3/8 x 1/8	1.58	1.00	0.50	0.03	----
NEW	32-961	3/8 x 3/16	1.75	1.00	0.50	0.03	----
	32-080 **	3/8" x 1/4"	2.06	0.97	0.56	0.03	----
	32-375 *	3/8" x 5/16"	2.00	0.97	0.50	0.03	----
	32-096 *	1/2"	2.00	0.96	0.62	0.06	----
	32-087 *	1/2" x 3/8"	2.06	0.97	0.71	0.06	----
	32-097	5/8"	2.05	0.96	0.75	0.08	----
	32-088	5/8" x 3/8"	2.06	0.97	0.75	0.06	----
	32-376	5/8" x 1/2"	2.06	0.97	0.75	0.07	----
	32-098 *	3/4"	2.50	1.15	0.87	0.10	----
	32-089	3/4" x 1/2"	2.28	1.19	0.87	0.10	----
	32-379	3/4" x 5/8"	2.02	0.96	0.87	0.10	----
	32-380	1" x 3/4"	2.58	1.19	1.12	0.18	----
	32-099	1"	3.00	1.44	1.02	0.23	----

* Add SS to the end of the part number for Stainless.

** See hose splicers on page 27 for Stainless.

MSB 122HBL HM 129 178 73 108

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

RIGID FEMALE ADAPTER



	Part #	Hose I.D. x Female NPTF	A	B	Hex	Approx. Wt. Lbs.	
	32-050	1/8” x 1/8”	0.96	0.46	0.50	0.02	----
	32-317	1/8” x 1/4”	1.15	0.46	0.62	0.04	----
	32-051	3/16” x 1/8”	1.10	0.68	0.50	0.02	----
	32-062	3/16” x 1/4”	1.44	0.75	0.62	0.04	----
	32-052	1/4” x 1/8”	1.35	0.93	0.50	0.02	----
	32-053	1/4” x 1/4”	1.60	0.97	0.62	0.06	----
	32-054	1/4” x 3/8”	1.65	1.03	0.75	0.04	----
	32-441	1/4" x 1/2"	1.66	0.97	0.93	0.08	----
	32-055	5/16” x 1/8”	1.47	0.97	0.56	0.04	----
	32-056	5/16” x 1/4”	1.66	0.97	0.62	0.04	----
	32-318	5/16” x 3/8”	1.66	0.97	0.75	0.06	----
	32-320	5/16” x 1/2”	1.67	0.96	0.93	0.08	----
	32-057	3/8” x 1/8”	1.47	0.97	0.56	0.04	----
	32-058	3/8” x 1/4”	1.61	0.97	0.62	0.06	----
	32-059	3/8” x 3/8”	1.63	1.00	0.81	0.08	----
	32-063	3/8” x 1/2”	1.72	0.94	0.93	0.12	----
	32-442	3/8" x 3/4"	1.97	0.97	1.18	0.20	----
NEW	32-449	1/2" x 1/8"	1.51	0.98	0.56	0.06	----
	32-064	1/2” x 1/4”	1.66	0.96	0.62	0.08	----
	32-060	1/2” x 3/8”	1.66	0.97	0.75	0.08	----
	32-061	1/2” x 1/2”	1.76	0.96	0.93	0.12	----
	32-443	1/2" x 3/4"	1.97	0.97	1.18	0.26	----
	32-444	5/8" x 3/8"	1.66	0.97	0.75	0.08	----
	32-445	5/8" x 1/2"	1.66	0.97	0.93	0.10	----
	32-446	5/8" x 3/4"	1.97	0.97	1.18	0.21	----
	32-447	3/4" x 1/2"	1.88	1.19	0.93	0.13	----
	32-065	3/4” x 3/4”	2.19	1.21	1.18	0.22	----
	32-049	1” x 3/4”	2.19	1.19	1.18	0.26	----
	32-321	1" x 1"	2.32	1.19	1.44	0.35	----
	32-448	1-1/4" x 1"	2.32	1.19	1.43	0.44	----

209A 128 29A 29F 126HB 126 FPB 105B-2 KF-RS 104 144

SWIVEL FEMALE ADAPTER NPTF

Part #	Hose I.D. x Female NPTF	A	B	Hex	Approx. Wt. Lbs.	
32-470	1/4" x 1/4"	1.80	0.97	0.62	0.06	----
32-472	3/8" x 1/4"	1.80	0.97	0.62	0.06	----
32-473	3/8" x 3/8"	1.82	0.97	0.75	0.09	----
32-475	1/2" x 3/8"	1.82	0.97	0.75	0.09	----
32-476	1/2" x 1/2"	1.86	0.97	0.93	0.14	----

HIGH VOLUME MALE SWIVEL

• 300 PSI • Nitrile Buna (NBR) O-Ring



32-781

28-415

Part #	Hose I.D. x Male NPTF	A	B	Hex	Approx. Wt. Lbs.	
32-781	3/8” x 1/4”	1.83	0.87	0.62	0.07	----
28-415	1/4" x 1/4"	1.30	0.94	0.81	0.14	----

4065

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

SWIVEL FEMALE ADAPTER - With Gasket

• NPSM Thread

National Pipe Straight Gasket Seal Swivel



• Not recommend for water due to fiber gasket - for air service only.

Part #	Hose I.D. x Female NPSM	A	B	Hex	Approx. Wt. Lbs.	
32-131	1/8" x 1/8"	0.90	0.46	0.50	0.02	----
32-132	3/16" x 1/8"	1.19	0.75	0.50	0.03	----
32-133	3/16" x 1/4"	1.28	0.75	0.62	0.04	----
32-120	1/4” x 1/8”	1.41	0.97	0.50	0.02	----
32-121	1/4” x 1/4”	1.50	0.97	0.62	0.02	----
32-129	1/4” x 3/8”	1.63	0.97	0.75	0.04	----
32-130	5/16” x 1/4”	1.50	0.97	0.62	0.04	----
32-122	3/8” x 1/4”	1.54	1.00	0.62	0.06	----
32-123	3/8” x 3/8”	1.60	0.97	0.75	0.06	----
32-354	3/8” x 1/2”	1.66	0.97	0.93	0.10	----
32-124	1/2” x 3/8”	1.60	0.97	0.75	0.08	----
32-125	1/2” x 1/2”	1.66	0.97	0.93	0.12	----
32-117	1/2” x 3/4”	1.82	1.19	1.18	0.16	----
32-118	5/8” x 3/4”	1.82	1.19	1.18	0.18	----
32-119	3/4” x 3/4”	1.82	1.19	1.18	0.14	----

130 126 29FSG KF-RN NPSM Gasket Seat

FORGED HOSE BARB 90° ELBOW



32-330
**Square Barstock Body

Part #	Hose I.D. x Male NPTF	A	B	C	Body Size	Approx. Wt. Lbs.	
32-308	3/16” x 1/8”	0.95	0.70	0.66	0.37	0.02	----
32-391	3/16” x 1/4”	1.00	0.84	0.63	0.46	0.10	----
32-038 *	1/4” x 1/8”	1.01	0.81	0.71	0.47	0.06	----
32-039 *	1/4” x 1/4”	1.01	0.87	0.63	0.47	0.06	----
32-309 **	1/4” x 3/8”	1.08	0.97	0.73	0.69	0.12	----
32-036	5/16” x 1/8”	1.01	0.81	0.63	0.47	0.04	----
32-040	5/16” x 1/4”	1.01	0.87	0.63	0.47	0.06	----
32-310	5/16” x 3/8”	1.06	0.94	0.63	0.50	0.06	----
32-046 *	3/8” x 1/8”	1.01	0.81	0.63	0.47	0.06	----
32-041 *	3/8” x 1/4”	1.02	0.88	0.65	0.47	0.06	----
32-042 *	3/8” x 3/8”	1.09	0.93	0.68	0.50	0.08	----
32-047 *	3/8” x 1/2”	1.11	1.09	0.63	0.59	0.10	----
32-048	1/2” x 1/4”	1.06	1.00	0.68	0.59	0.10	----
32-043 *	1/2” x 3/8”	1.06	1.09	0.69	0.59	0.10	----
32-311 *	1/2” x 1/2”	1.31	1.19	0.87	0.56	0.12	----
32-044	5/8” x 3/8”	1.12	1.06	0.61	0.56	0.12	----
32-045	5/8” x 1/2”	1.12	1.12	0.68	0.63	0.14	----
32-312	5/8” x 3/4”	1.46	1.26	0.93	1.06	0.32	----
32-313	3/4” x 1/2”	1.31	1.28	0.87	0.85	0.22	----
32-314 *	3/4” x 3/4”	1.46	1.26	0.91	1.06	0.32	----
32-330 **	3/4” x 1”	1.57	1.64	0.90	1.34	0.64	----
32-315	1” x 3/4”	1.60	1.40	0.95	1.06	0.32	----
32-319	1" x 1"	1.69	1.64	0.98	1.30	0.43	----

129 HBE1 KF-PS90 HE-1 29E 146

* Add SS to the end of the part number for Stainless. See page 27.

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

BARSTOCK HOSE BARB 90° ELBOW



	Part #	Hose I.D. x Male NPTF	A	B	C	Body Size	Approx. Wt. Lbs.	
	32-038B	1/4” X 1/8”	1.00	0.75	0.75	0.50	0.02	----
	32-039B	1/4” X 1/4”	1.02	0.91	0.74	0.56	0.04	----
NEW	32-309B	1/4" X 3/8"	1.19	0.84	0.76	0.58	0.09	----
NEW	32-036B	5/16" X 1/8"	1.06	0.66	0.76	0.44	0.04	----
NEW	32-040B	5/16" X 1/4"	1.12	0.84	0.76	0.58	0.07	----
NEW	32310B	5/16" X 3/8"	1.19	0.84	0.76	0.72	0.09	----
NEW	32046B	3/8" X 1/8"	1.32	0.94	0.97	0.58	0.06	----
	32-041B	3/8” X 1/4”	1.32	0.89	0.97	0.58	0.08	----
	32-042B	3/8” X 3/8”	1.50	1.06	0.97	0.75	0.14	----
NEW	32047B	3/8" X 1/2"	1.52	1.25	0.97	0.90	0.26	----
NEW	32048B	1/2" X 1/4"	1.53	1.06	0.97	0.72	0.12	----
	32-043B	1/2” X 3/8”	1.53	1.07	0.97	0.72	0.16	----
NEW	32311B	1/2" X 1/2"	1.53	1.25	0.97	0.90	0.26	----
NEW	32314B	3/4" X 3/4"	1.33	1.27	0.97	1.10	0.32	----

129HB

HOSE BARB TEES



32-128

Part #	Hose Barb Size (1 & 2) x 3	A	B	Body Size	Approx. Wt. Lbs.	
32-367 *	1/8”	0.84	0.83	0.25	0.02	----
32-368	3/16"	1.02	1.02	0.37	0.03	----
32-365 **	1/4”	1.00	1.00	0.44	0.06	----
32-350 *	(1/4") x 1/8"	0.94	0.94	0.44	0.04	----
32-366	5/16”	1.00	1.00	0.44	0.06	----
32-126 **	3/8”	1.01	1.01	0.43	0.06	----
32-400 *	1/2”	1.02	1.00	0.43	0.08	----
32-352 *	(1/2") x 3/8"	1.26	1.26	0.43	0.10	----
32-361	5/8"	1.26	1.26	0.75	0.16	----
32-363	3/4"	1.45	1.45	0.90	0.18	----
32-353	(3/4") x 1/2"	1.41	1.41	0.88	0.23	----
32-128 *	3/8”HB x 1/4” MIP	1.00	0.94	0.43	0.06	----

* Add SS to the end of the part number for Stainless.
** See page 29 for stainless steel.

90° HOSE BARB ELBOW



Part #	Hose I.D. x Hose I.D.	A	B	Body Size	Approx. Wt. Lbs.	
32-429	1/8" x 1/8"	0.55	0.55	0.37	0.03	----
32-433	3/16" x 3/16"	0.90	0.90	0.37	0.03	----
32-412	1/4” x 1/8”	1.02	1.02	0.44	0.04	----
32-413 *	1/4” x 1/4”	1.01	1.01	0.44	0.04	----
32-425	5/16" x 5/16"	1.15	1.15	0.48	0.05	----
32-414	3/8” x 1/8”	1.01	1.01	0.44	0.04	----
32-415	3/8” x 1/4”	1.00	1.00	0.44	0.04	----
32-416 *	3/8” x 3/8”	1.02	1.02	0.44	0.04	----
32-417	3/8” x 1/2”	1.24	1.10	0.50	0.06	----
32-418	1/2” x 1/4”	1.24	1.08	0.50	0.06	----
32-419	1/2” x 3/8”	1.22	1.09	0.50	0.06	----
32-420 *	1/2” x 1/2”	1.24	1.24	0.50	0.06	----
32-434	5/8" x 5/8"	1.20	1.20	0.75	0.16	----
32-435	3/4" x 1/2"	1.41	1.41	0.88	0.21	----
32-436	3/4" x 3/4"	1.41	1.41	0.88	0.21	----

* Add SS to the end of the part number for Stainless.

90° FEMALE HOSE BARB ELBOW



Part #	Hose I.D. x Female NPTF	A	B	Body Size	Approx. Wt. Lbs.	
32-401	1/4” x 1/8”	1.01	0.82	0.47	0.06	----
32-402	1/4” x 1/4”	1.13	0.91	0.56	0.10	----
32-403	3/8” x 1/8”	1.01	0.82	0.47	0.06	----
32-404	3/8” x 1/4”	1.15	0.91	0.56	0.10	----
32-405	3/8” x 3/8”	1.15	1.11	0.68	0.14	----
32-406	3/8” x 1/2”	1.26	1.39	0.75	0.20	----
32-407	1/2” x 1/4”	1.26	0.91	0.56	0.10	----
32-410	1/2” x 3/8”	1.24	1.11	0.68	0.14	----
32-411	1/2” x 1/2”	1.37	1.39	0.75	0.20	----
32-409	3/4" x 3/4"	1.52	1.75	0.81	0.50	----

45° ELBOW



Part #	Hose I.D. x Male NPTF	A	B	Body Size	Approx. Wt. Lbs.	
32-110	1/4” x 1/8”	0.91	0.62	0.53	0.04	----
32-109*	1/4” x 1/4”	1.00	0.62	0.57	0.06	----
32-111	3/8” x 1/8”	0.83	0.66	0.53	0.04	----
32-112	3/8” x 1/4”	0.82	0.84	0.53	0.06	----
32-113	3/8” x 3/8”	0.93	0.87	0.59	0.08	----
32-346	1/2” x 1/4”	1.00	0.84	0.59	0.08	----
32-114	1/2” x 3/8”	1.00	0.88	0.59	0.08	----
32-116	1/2" x 1/2"	1.15	0.94	0.59	0.12	----
32-115	5/8” x 3/8”	0.97	0.88	0.59	0.10	----
32-345	3/4" x 1/2"	1.15	0.94	0.81	0.13	----

* Barstock

140 HE145 139HB KF-PS45 13945

CROSSES

Part #	Hose ID	
32-608	1/4	----
32-609	5/16	----
32-610	3/8	----

HOSE WYES AVAILABLE WITH EXTENDED LEAD TIME.

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

BALL END SWIVEL

NPSM - Ball seat type



Part #	Hose I.D. x NPSM	A	B	Hex	Approx. Wt. Lbs.	
32-066	1/8" x 1/8"	0.46	0.44	0.50	0.03	----
32-067	3/16" x 1/8"	0.75	0.44	0.50	0.03	----
32-068	3/16" x 1/4"	0.75	0.52	0.62	0.04	----
NEW 32-962	3/16" x 3/8"	0.75	0.63	0.75	0.05	----
32-069	1/4" x 1/8"	0.97	0.44	0.50	0.04	----
32-070	1/4" x 1/4"	0.97	0.53	0.62	0.06	----
32-078	1/4" x 3/8"	0.97	0.63	0.75	0.06	----
32-071	5/16" x 1/4"	0.97	0.52	0.62	0.05	----
32-389	5/16" x 3/8"	0.97	0.63	0.75	0.07	----
32-072	3/8" x 1/4"	0.97	0.53	0.62	0.06	----
32-073	3/8" x 3/8"	0.97	0.59	0.75	0.08	----
32-074	3/8" x 1/2"	0.97	0.69	0.94	0.14	----
32-075	1/2" x 3/8"	0.97	0.59	0.75	0.08	----
32-076	1/2" x 1/2"	0.97	0.69	0.94	0.10	----
32-077	3/4" x 3/4"	0.97	0.70	1.12	0.14	----

128HBLSV 29FS 209AS 124 131

BALLSEAT MALE ADAPTER

Beveled seat



30° Seat

Part #	NPSM x Male NPTF	A	Hex	Approx. Wt. Lbs.	
32-359	1/8" x 1/8"	0.94	0.43	0.03	----
32-034	1/4" x 1/8"	1.06	0.56	0.04	----
32-030	1/4" x 1/4"	1.25	0.56	0.06	----
32-362	3/8" x 1/4"	1.28	0.68	0.08	----
32-031	3/8" x 3/8"	1.30	0.68	0.08	----
32-392	3/8" x 1/2"	1.47	0.88	0.13	----
32-364	1/2" x 3/8"	1.35	0.87	0.10	----
32-032	1/2" x 1/2"	1.53	0.87	0.14	----
32-033	3/4" x 3/4"	1.53	1.06	0.20	----

172 134 127HB 122AS

BALLSEAT UNION



30° Seat

Part #	NPSM x NPSM	A	Hex	Approx. Wt. Lbs.	
32-460	1/8"	0.79	0.43	0.02	----
32-461	1/4"	1.09	0.56	0.04	----
32-462	3/8"	1.19	0.68	0.07	----
32-463	1/2"	1.31	0.87	0.10	----

45° FLARE ADAPTER



Part #	Hose I.D. x 45° Flare	Thread	A	B	Hex	Approx. Wt. Lbs.	
32-322	3/16" x 1/4"	7/16-20	1.5	0.75	0.43	0.03	----
32-081 *	1/4" x 1/4"	7/16-20	1.72	0.97	0.43	0.03	----
32-082 *	1/4" x 3/8"	5/8-18	1.82	0.97	0.62	0.07	----
32-083	5/16" x 5/16"	1/2-20	1.75	0.97	0.50	0.08	----
32-084 *	3/8" x 3/8"	5/8-18	1.82	0.97	0.62	0.08	----
32-085	3/8" x 1/2"	3/4-16	1.97	0.97	0.75	0.10	----
32-086	1/2" x 1/2"	3/4-16	1.97	0.97	0.75	0.10	----

* Add SS to the end of the part number for Stainless.

142 201BF KF-MS KDS

COMPRESSION ADAPTER - BARB X MALE COMPRESSION THREAD

NEW

Part #	Size	
18-534	1/4" x 1/4"	

DUAL 45°/ 37° FLARE SWIVEL



CRIMP STYLE

Part #	Hose ID x Dual Seat	Thread	A	B	Hex	Approx. Wt. Lbs.	
32-107	3/16” x 1/4”	7/16-20	1.34	0.75	0.56	0.04	----
32-107C**	3/16 X 1/4	7/16-20	1.42	0.78	0.56	0.04	----
32-337	1/4” x 1/4”	7/16-20	1.56	0.97	0.56	0.04	----
32-337C**	1/4" X 1/4"	7/16-20	1.60	0.97	0.56	0.04	----
32-102	1/4” x 5/16”	1/2-20	1.61	0.97	0.62	0.06	----
32-339	5/16” x 5/16”	1/2-20	1.60	0.97	0.62	0.06	----
32-340	3/8” x 1/2”	3/4-16	1.68	0.97	0.87	0.10	----
32-341	1/2” x 1/2”	3/4-16	1.68	0.97	0.87	0.10	----
32-341C**	1/2" X 1/2"	3/4-16	1.75	0.97	0.87	0.09	----
32-342	1/2” x 5/8”	7/8-14	1.76	0.97	1.00	0.12	----
32-394**	5/8" x 5/8"	7/8-14	1.83	0.97	1.00	0.14	----

** Swivel crimp style

KDS

FEMALE 45° FLARE SWIVEL



CRIMP STYLE

Part #	Hose I.D. x Female 45° Flare	UNF Thread	A	B	Hex	Approx. Wt. Lbs.	
32-326	3/16” x 3/16”	3/8-24	1.19	0.75	0.43	0.04	----
30-295**	3/16" x 3/8"	5/8-18	1.82	0.90	0.75	0.04	----
32-101	1/4” x 1/4”	7/16-20	1.57	0.97	0.56	0.04	----
32-103	1/4” x 3/8”	5/8-18	1.64	0.97	0.75	0.08	----
32-104	5/16” x 5/16”	1/2-20	1.61	0.97	0.62	0.05	----
32-327	5/16” x 3/8”	5/8-18	1.67	0.97	0.75	0.08	----
32-105	3/8” x 3/8”	5/8-18	1.64	0.97	0.75	0.08	----
32-105C**	3/8" x 3/8"	5/8-18	1.71	0.97	0.75	0.07	----
32-106	3/8” x 1/2”	3/4-16	1.81	0.97	0.87	0.10	----
32-100	1/2” x 1/2”	3/4-16	1.68	0.97	0.87	0.12	----
32-328	3/4" x 3/4"	1-1/16-14	2.00	0.97	1.25	0.20	----

29SAE 209ASF 146HBLFSV KF-NS 128 FSS 146 144

** Swivel crimp style (crimped on the outside of fitting)

FEMALE 37° J.I.C. FLARE SWIVEL



CRIMP STYLE

STAINLESS STEEL

32338SS

Part #	Hose ID x Female 37° Flare	Thread	A	B	Hex	Approx. Wt. Lbs.	
32-334	1/4” x 3/8”	9/16-18	1.60	0.97	0.68	0.06	----
32-335	5/16” x 3/8”	9/16-18	1.60	0.97	0.68	0.06	----
32-336	3/8” x 3/8”	9/16-18	1.60	0.97	0.68	0.10	----
32-336C**	3/8" X 3/8"	9/16-18	1.66	0.97	0.68	0.06	----
32-338*	3/4" x 3/4"	1-1/16-12	2.00	0.97	1.25	0.20	----
32-338SS	3/4" x 3/4"	1-1/16-12	2.00	0.97	1.25	0.24	----
32-338C	3/4" x 3/4"	1-1/16-12	2.13	1.19	1.25	0.20	----
32-397**	1" x 1"	1-5/16-12	2.31	1.19	1.50	0.33	----

KJS

*Available in swivel crimp style - add a "C" at the end of the part # (100 piece minimum)

** Swivel crimp style

Put your heart, mind, and soul into even your smallest acts. This is the secret of success.

- Swami Sivananda

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

REUSABLE MALE FITTINGS

Part #	Hose ID	Hose OD	Male NPTF	
32-727	1/4"	1/2"	1/4"	----
32-728	1/4"	9/16"	1/4"	----
32-726	1/4"	5/8"	1/4"	----
32-741	5/16"	5/8"	1/4"	----
32-742	3/8"	5/8"	1/4"	----
32-744	3/8"	11/16"	1/4"	----
32-725	3/8"	3/4"	1/4"	----
32-747	3/8"	5/8"	3/8"	----
32-750	3/8"	11/16"	3/8"	----
32-746	1/2"	7/8"	1/2"	----

REUSABLE FEMALE SWIVEL STEMS



Part #	Hose ID	Female NPSM	
32-770	1/4"	1/4"-18	----
32-771	3/8"	3/8"-18	----

REUSABLE FEMALE SWIVELS

Part #	Hose ID	Hose OD	Female NPSM	
32-772	1/4"	1/2"	1/4"	----
32-773	3/8"	5/8"	3/8"	----
32-774	3/8"	11/16"	3/8"	----
32-775	1/2"	7/8"	1/2"	----

REUSABLE FERRULES

Part #	Hose ID	Hose OD	
32-749	1/4"	1/2"	----
32-751	1/4"	9/16"	----
32-752	1/4"	5/8"	----
32-753	3/8"	5/8"	----
32-754	3/8"	11/16"	----
32-755	3/8"	3/4"	----
32-756	1/2"	7/8"	----

REUSABLE MALE STEMS



Part #	Hose ID	Male NPT Thread	
32-758	1/4"	1/4"	----
32-759	3/8"	1/4"	----
32-760	3/8"	3/8"	----
32-761	1/2"	1/2"	----

Your work is going to fill a large part of your life, and the only way to be truly satisfied is to do what you believe is great work. And the only way to do great work is to love what you do. If you haven't found it yet, keep looking. Don't settle. As with all matters of the heart, you'll know when you find it.

– Steve Jobs

HOSE BARB

BRASS FUEL HOSE BARBS

Typical Application: Low pressure air, fuel and oil applications. Generally used for automotive, light truck, and small engine fuel lines. Use with fuel hose SAE 30R7 & SAE 30R9.

Advantages: Easy to assemble, just push the fitting into the hose & clamp. Good selection of configurations at reasonable cost.

MALE CONNECTOR

HOSE BARB X MALE PIPE

	Part #	Hose ID	MIP	Ind #	
	38-800	3/16	1/8	1541	----
	38-802	1/4	1/8	1537	----
	32-377	1/4	1/4	1581	----
	38-806	5/16	1/8	1551	----
	38-808	5/16	1/4	1555	----
	38-810	3/8	1/8	1565	----
	32-381	3/8	1/4	1564	----
	32-382	3/8	3/8	1566	----
NEW	32-383	1/2	3/8		----
NEW	32-384	1/2	1/2		----
	32-385	5/8	1/2	1431	----
	32-387	3/4	1/2	1430	----
NEW	32-388	3/4	3/4		----

68HB

BUBBLE BARB MALE ADAPTER

BUBBLE X MIP

Part #	Bubble x MIP	
32176	3/8 x 3/8	----
32177	1/2 x 1/4	----
32178	1/2 x 3/8	----
32179	1/2 x 1/2	----
32182	5/8 x 3/8	----
32183	5/8 x 1/2	----
32184	3/4 x 1/2	----
32180	3/4 x 3/4	----
32185	1 x 3/4	----
32181	1 x 1	----

INVERTED FLARE MALE CONNECTOR

HOSE BARB X INVERTED FLARE

Part #	Hose ID	Inv. Flare	Ind #	
38-828	5/16	1/4	1598	----
38-830	5/16	5/16	1560	----
38-832	5/16	3/8	1561	----
38-834	3/8	5/16	1568	----
38-836	3/8	3/8	1570	----

269HB

90° MALE ELBOW

HOSE BARB X MALE PIPE

Part #	Hose ID	MIP	Ind #	
38-860	1/4	1/8	1582	----
38-862	5/16	1/8	1556	----
38-864	5/16	1/4	1557	----
38-866	3/8	1/8	1572	----
38-868	3/8	1/4	1571	----

BUBBLE BARB

Part #	Hose ID	MIP	
32-186	3/8	3/8	----
32-194	1/2	1/4	----
32-187	1/2	3/8	----
32-191	1/2	1/2	----
32-195	5/8	1/4	----
32-188	5/8	3/8	----
32-189	5/8	1/2	----
32-190	3/4	1/2	----
32-192	3/4	3/4	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

INVERTED FLARE MALE SWIVEL 90° ELBOW

HOSE BARB X TUBE O.D.

Part #	Hose ID	Inv. Flare	Ind #	
38-873	5/16	5/16	1405	----
38-874	3/8	3/8	1407	----

WELDED HOSE FITTINGS

STEM ONLY - WELDING HOSE CONNECTOR



Part #	Hose I.D.	A	Approx. Wt. Lbs.	
30-410	3/16”	1.43	0.02	----
30-411	1/4”	1.43	0.02	----
30-413	3/8”	1.43	0.04	----

Assemble with nuts below.

201RWA WRS WLS

RIGHT HAND 9/16 - 18 FOR OXYGEN LINE - WELDING HOSE NUT



Part #	Size	A	Hex	Approx. Wt. Lbs.	
30-420	R.H. Nut only	0.63	0.68	0.04	----

Assemble with stem above.

201RWA WRS KF-PE 152

LEFT HAND 9/16 - 18 FOR ACETYLENE LINE - WELDING HOSE NUT



Part #	Size	A	Hex	Approx. Wt. Lbs.	
30-421	L.H. Nut only	0.63	0.68	0.04	----

Assemble with stem above.

209LWA WLS 154 KF-RE

RIGHT HAND 9/16 - 18 #122RWA - WELDING HOSE CONNECTOR



Part #	Size	A	Hex	Approx. Wt. Lbs.	
30-401	1/4”-18	1.30	0.62	0.06	----
32-437	3/8"-18	1.30	0.68	0.09	----
32-438*	9/16"-18	1.25	0.68	0.07	----

* Right UNF thread

156

LEFT HAND 9/16 - 18 #122LWA - WELDING HOSE CONNECTOR



Part #	Size	A	Hex	Approx. Wt. Lbs.	
30-406	1/4”-18	1.30	0.62	0.06	----
32-439	3/8"-18	1.30	0.68	0.09	----
32-440*	9/16"-18	1.25	0.68	0.07	----

* Left UNF thread

158

BARBED FOR PLASTIC TUBING

BRASS BARBS FOR POLYETHYLENE TUBING

• Quick connecting fittings that do not require tube preparations for hand assembly. Inexpensive with excellent resistance to vibration.
• **All sizes are tube O.D. (I.D.)**



UNION

TUBE O.D. (TUBE I.D.) X TUBE O.D. (TUBE I.D.)

Part #	Size	
21-003	1/4(1/8) x 1/4(1/8)	----
21-007	3/8(1/4) x 1/4(1/8)	----
21-009	3/8(1/4) x 3/8(1/4)	----

1062 962

MALE ADAPTER

TUBE O.D. (TUBE I.D.) X MALE PIPE

Part #	Size	
21-021	1/4(1/8) x 1/16	----
21-023	1/4(1/8) x 1/8	----
21-025	1/4(1/8) x 1/4	----
21-027	3/8(1/4) x 1/8	----

1068 968 688

FEMALE ADAPTER

TUBE O.D. (TUBE I.D.) X FEMALE PIPE

Part #	Size	
21-043	1/4(1/8) x 1/8	----
21-046	3/8(1/4) x 1/4	----
21-049	1/2(3/8) x 3/8	----

1066 966 26 668

BULKHEAD UNION

TUBE O.D. (TUBE I.D.)

Part #	Size	
21-082	1/4(1/8)	----
21-083	3/8(1/4)	----
21-084	1/2(3/8)	----

1074

UNION ELBOW

1065
965

TUBE O.D (I.D.)

Part #	Size	
21-095	1/4(1/8)	----
21-097	3/8(1/4)	----
21-099	1/2(3/8)	----

MALE 90° ELBOW

TUBE O.D. (I.D.) X MALE PIPE

Part #	Size	
21-109	1/8" x 1/4-28"	----
21-111	1/4(1/8) x 1/16	----
21-113	1/4(1/8) x 1/8	----
21-115	1/4(1/8) x 1/4	----
21-117	3/8(1/4) x 1/8	----
21-119	3/8(1/4) x 1/4	----
21-121	1/2(3/8) x 3/8	----

1069 969 229

FEMALE 90° ELBOW

TUBE O.D. (I.D.) X FEMALE PIPE

Part #	Size	
21-133	1/4(1/8) x 1/8	----

1070 970 230

UNION TEE

O.D. (I.D.) X O.D. (I.D.) X O.D. (I.D.)

Part #	Size	
21-151	1/4(1/8)	----
21-153	3/8(1/4)X 3/8(1/4)X1/4(1/8)	----
21-155	3/8(1/4)	----
21-159	1/2(3/8)X1/2(3/8)X3/8(1/4)	----
21-161	1/2(3/8)	----

1064 964 224

MALE BRANCH TEE



O.D. (I.D.) X O.D. (I.D.) X MALE PIPE

Part #	Size	
21-193	1/4(1/8) x 1/4(1/8) x 1/8	----
21-195	3/8(1/4) x 3/8(1/4) x 1/8	----
21-197	3/8(1/4) x 3/8(1/4) x 1/4	----

1072 972 232

FEMALE BRANCH TEE



O.D. (I.D.) X O.D. (I.D.) X FEMALE PIPE

Part #	Size	
21-207	1/4(1/8) x 1/4(1/8) x 1/8	----

1077 978

TWO BARB FITTINGS

More Sizes Available - Please Ask!



MALE ADAPTER PIPE

TUBE O.D. (I.D.) X MALE PIPE

Part #	Size	
32-150	1/4(1/8) x 1/8	----
32-151	1/4(1/8) x 1/4	----
32-153	3/8(1/4) x 1/4	----

28

UNION TEE

Part #	Tube O.D. (I.D.)	
32-159	1/4(1/8 ID)	----
32-160	3/8(1/4 ID)	----

90° ELBOW

Part #	Tube O.D. (I.D.)	
32-170	1/4(1/8 ID)	----
32-171	3/8(1/4 ID)	----

225

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

316 STAINLESS STEEL MACHINED RIGID MALE ADAPTER

Part #	Hose I.D. x NPT	
32-001SS	1/8" x 1/8"	----
32-002SS	3/16" x 1/8"	----
32-003SS	3/16" x 1/4"	----
32-004SS	1/4" x 1/8"	----
32-005SS	1/4" x 1/4"	----
32-006SS	1/4" x 3/8"	----
32-008SS	5/16" x 1/8"	----
32-009SS	5/16" x 1/4"	----
32-010SS	5/16" x 3/8"	----
32-011SS	3/8" x 1/8"	----
32-012SS	3/8" x 1/4"	----
32-013SS	3/8" x 3/8"	----
32-014SS	3/8" x 1/2"	----
32-015SS	1/2" x 1/4"	----
32-016SS	1/2" x 3/8"	----
32-017SS	1/2" x 1/2"	----
32-018SS	1/2" x 3/4"	----
32-019SS	5/8" x 3/8"	----
32-020SS	5/8" x 1/2"	----
32-021SS	5/8" x 3/4"	----
32-022SS	3/4" x 1/2"	----
32-023SS	3/4" x 3/4"	----
32-024SS	1" x 3/4"	----

316 STAINLESS STEEL SPLICER



Part #	Hose I.D. x Hose I.D.	A	B	
32-091SS	1/8"			----
32-093SS	1/4"	2.03	0.97	----
32-094SS	5/16"			----
32-095SS	3/8"	2.06	0.97	----
32-096SS	1/2"	2.06	0.97	----
32-098SS	3/4"	2.50	1.19	----

316 STAINLESS STEEL BARB ELBOW

Part #	Hose I.D. x NPT	
32-038SS	1/4 x 1/8	----
32-039SS	1/4 x 1/4	----
32-041SS	3/8 x 1/4	----
32-042SS	3/8 x 3/8	----
32-043SS	1/2" x 3/8"	----
32-311SS	1/2 x 1/2	----
32-314SS	3/4" x 3/4"	----

304 STAINLESS STEEL HOSE NIPPLES

• Cast

Part #	Hose I.D. x Male Pipe	
73-951	1/4"	----
73-952	3/8"	----
73-953	1/2"	----
73-954	3/4"	----
73-955	1"	----
73-956	1-1/4"	----
73-957	1-1/2"	----
73-958	2"	----
73-959	2-1/2"	----
73-960	3"	----

304 STAINLESS STEEL REDUCING HOSE NIPPLES

• Cast

Part #	Hose I.D. x Male Pipe	
73-970	1/4" X 1/8"	----
73-971	3/8" X 1/4"	----
73-972	1/2" X 3/8"	----
73-973	1/2" X 1/4"	----
73-974	3/4" X 1/2"	----
73-975	1" X 3/4"	----
73-976	1" X 1/2"	----
73-977	1-1/4" X 1"	----
73-979	1-1/2" X 1-1/4"	----
73-980	1-1/2" X 1"	----
73-981	2" X 1-1/2"	----
73-982	2" X 1-1/4"	----

316 STAINLESS STEEL HOSE NIPPLES

• Cast

Part #	Hose I.D. x Male Pipe	
973-951	1/4"	----
973-952	3/8"	----
973-953	1/2"	----
973-954	3/4"	----
973-955	1"	----
973-956	1-1/4"	----
973-957	1-1/2"	----
973-958	2"	----
973-959	2-1/2"	----
973-990	3"	----
973-991	4"	----

• See King nipples on page 312

BEVERAGE FITTINGS

STAINLESS STEEL

BARB TO MALE PIPE ADAPTER

HOSE ID x MALE NPT

Part #	Size	
34-587	1/4" x 1/8"	----
34-588	1/4" x 1/4"	----
34-589	1/4" x 3/8"	----
34-590	3/8" x 1/8"	----
34-591	3/8" x 1/4"	----
34-592	3/8" x 3/8"	----
34-595	3/8" x 1/2"	----
34-597	1/2" x 3/4"	----

BARB TO MALE FLARE ADAPTER

NEW

HOSE ID x 45° FLARE

Part #	Size	
34-579	1/4" x 1/4"	----
34-586	1/4" x 5/16"	----
34-584	1/4" x 3/8"	----
34-580	1/4" x 1/2-16"	----
34-583	3/8" x 1/4"	----
34-585	3/8" x 3/8"	----
34-581	3/8" x 1/2-16"	----

FEMALE FLARE SWIVEL SETS

NEW

Part #	Size	
34-501	1/4" x 1/4"	----
34-502	5/16" x 1/4"	----
34-504	3/8" x 3/8"	----

ONE PIECE SWIVEL BARB X FE. FL

NEW

Part #	Size	
34-510	3/8" x 1/4"	----

HOSE SPLICER (STRAIGHT)

ID HOSE

Part #	Size	
34-532	3/16"	----
34-533	1/4"	----
34-534	1/4" x 3/16"	----
34-536	5/16"	----
34-537	5/16" x 1/4"	----
34-535	3/8"	----
34-538	3/8" x 3/16"	----
34-543	3/8" x 1/4"	----
34-539	3/8" x 5/16"	----
34-540	1/2" x 3/8"	----

THINWALL SPLICERS

Part #	Size	
34-533T	1/4"	----
34-535T	3/8"	----
34-541T	1/2"	----
34-540T	1/2" x 3/8"	----
34-543T	3/8" x 1/4"	----

PLUG

Part #	Size	
34-572	1/4"	----
34-574	3/8"	----

THINWALL

Part #	Size	
34-572T	1/4"	----
34-574T	3/8"	----

BARB X COMPRESSION

Part #	Size	
34-625	1/4" x 3/8"	----
34-626	3/8" x 3/8"	----

PLATED BRASS SPLICERS

NEW

Part #	Size	
34-725	3/16"	----
34-726	1/4" x 3/16"	----
34-728	5/16"	----
34-727	5/16" x 3/16"	----

TAILPIECES

NEW

SS BARB X SWIVEL SHANK

Part #	Size	
34-711	3/16"	----
34-713	1/4"	----
34-715	5/16"	----
34-716	3/8"	----
34-717	1/2"	----

NEW

N/P BRASS

Part #	Size	
34-710	3/16"	----
34-712	1/4"	----
34-714	5/16"	----
34-716	3/8"	----
34-718	1/2"	----

NEW

#304 SS 90° ELBOW

Part #	Size	
34-720	3/16"	----
34-721	1/4"	----
34-722	5/16"	----
34-723	3/8"	----
34-724	1/2"	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

90° SWIVEL ELBOW

90° SWIVEL ELBOW

HOSE ID x FEMALE 45° FLARE

Part #	Size	
34-525	1/4" x 1/4"	----
34-526	3/8" x 1/4"	----
34-529	3/8" x 3/8"	----
34-531	1/2" x 1/2"	----

BARB TO SWIVEL ELBOW



HOSE ID x FEMALE 45° FLARE

Part #	Size	
34-600	1/4" x 1/4"	----
34-601	3/8" x 1/4"	----

MALE ELBOWS

HOSE ID x MALE NPTF

Part #	Size	
34-610	1/4" x 1/8"	----
34-611	3/8" x 1/4"	----
34-612	3/8" x 3/8"	----
34-613	1/2" x 1/2"	----

FEMALE ADAPTERS

BARB X FEMALE PIPE

Part #	Size	
34-661	1/4"	----
34-658	1/2"	----

U-BEND



Part #	Size	A	
34-633	3/8"	2	----

THINWALL U-BEND

Part #	Size	A	
34-633T	3/8"	1-1/2	----

U-BEND W/MANIFOLD

THINWALL

Part #	Size	
34-621T	1/4"	----
34622T	3/8"	----

CROSS

CROSS - THINWALL

Part #	Size	
34-635T	1/4"	----
34-638T	3/8"	----

Y TEES



THINWALL

Part #	Size	A	
34-650T	1/4"	1-1/8	----
34-652T	3/8"	1-1/4	----

BARB HOSE TEES

ID HOSE

Part #	Size	
34-561	1/8"	----
34-562	1/4"	----
34-565	5/16"	----
34-563	3/8"	----

REDUCING TEES

Part #	1&2	3	
34-567	1/4"	3/8"	----
34-568	3/8"	1/4"	----

THINWALL TEES

Part #	Size	
34-562T	1/4"	----
34-565T	5/16"	----
34-563T	3/8"	----
34-564T	1/2"	----

REDUCING THINWALL TEES

Part #	1&2	3	
34-567T	1/4"	3/8"	----
34-568T	3/8"	1/4"	----

90° BARB SPLICER

ID HOSE

Part #	Size	
34-551	1/4"	----
34-550	5/16"	----
34-552	3/8"	----

THINWALL 90° BARB SPLICERS

Part #	Size	
34-551T	1/4"	----
34-552T	3/8"	----
34-553T	1/2"	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

PUSH ON BARB FITTINGS

Typical Application: Low Pressure Air, Fuel, Lube, and Oil Lines

• Pressure determined by tube material and hardness.Our Parts have been tested to max 150 PSI.

Advantages: Easy assembly. No clamps needed!!

• Assembly Instructions

1- Lubricate insert.

2- Hold hose at angle as shown & push on and up over first barb.

3- Continue to push straight on until hose is seated under protective plastic cap. Keep hands back from hose end area so that hose can expand.

• Disassembling Instructions

1- Split hose. Do not cut completely through hose. Sealing edge of barb could be damaged.

2- Bend hose and remove with a quick pull.

See lead free section for lead free push-on barb fittings.

Stainless steel available at the end of this section.

Actual Profile of Push On Barbs



WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

MALE ADAPTER



	Part #	Hose I.D. x Male NPTF	A	B	Hex	Approx. Wt. Lbs.	
	30-200 *	1/4” x 1/8”	1.43	0.87	0.50	0.04	----
	30-201 *	1/4” x 1/4”	1.66	0.87	0.56	0.06	----
	30-211	1/4” x 3/8”	1.66	0.87	0.68	0.06	----
NEW	30-208	1/4" x 1/2"	1.83	0.88	0.88	0.10	----
	30-212	5/16” x 1/8”	1.42	0.77	0.43	0.04	----
	30-213	5/16” x 1/4”	1.66	0.87	0.56	0.06	----
	30-202	3/8” x 1/8”	1.53	0.97	0.50	0.04	----
	30-203 *	3/8” x 1/4”	1.69	0.89	0.56	0.07	----
	30-204 *	3/8” x 3/8”	1.76	0.97	0.68	0.08	----
	30-205	3/8” x 1/2”	1.97	0.97	0.87	0.10	----
	30-392	3/8” x 3/4”	1.97	0.92	1.06	0.16	----
	30-216	1/2” x 1/4”	1.76	0.97	0.68	0.08	----
	30-206 *	1/2” x 3/8”	1.76	0.97	0.68	0.09	----
	30-207 *	1/2” x 1/2”	1.97	0.97	0.87	0.14	----
	30-217	1/2” x 3/4”	1.97	0.97	1.06	0.16	----
NEW	30-218	1/2" x 1"	2.29	0.97	1.37	0.34	----
	30-219	5/8” x 3/8”	2.34	1.50	0.75	0.12	----
	30-209	5/8” x 1/2”	2.45	1.45	0.87	0.16	----
	30-214	5/8” x 3/4”	2.45	1.45	1.06	0.18	----
	30-215 *	3/4” x 1/2”	2.45	1.45	0.87	0.21	----
	30-210 *	3/4” x 3/4”	2.45	1.45	1.06	0.20	----
	30-238	1” x 3/4”	2.93	1.50	1.25	0.43	----

• See page 161 for lead free

• See page 36 for Stainless

301 P990A HLM 100B-1 KA-MB 272 29PO 725 625 BPN 941 30182

MALE SWIVEL



Part #	Hose I.D. x Male NPTF	A	B	Hex	Approx. Wt. Lbs.	
30-422	1/4" x 1/8"	2.07	0.87	0.56	0.06	----
30-385	1/4” x 1/4”	2.02	0.87	0.56	0.06	----
30-423	3/8" x 1/8"	2.12	0.97	0.56	0.07	----
30-386	3/8” x 1/4”	2.12	0.97	0.56	0.08	----
30-387	3/8” x 3/8”	2.12	0.97	0.68	0.08	----
30-388	1/2” x 3/8”	2.12	0.97	0.68	0.10	----
30-389	1/2” x 1/2”	2.33	0.97	0.87	0.14	----
30-424	5/8" x 1/2	2.80	1.45	0.88	0.18	----
30-390	3/4” x 3/4”	2.80	1.45	1.06	0.24	----

921 HMS 285 31382

FEMALE GASKET SEAL SWIVEL - NPSM



Part #	Hose I.D. x Gasket Swivel (NPSM)	A	B	Hex	Approx. Wt. Lbs.	
30-359	1/4” x 1/8”	1.39	0.77	0.50	0.03	----
30-358	1/4” x 1/4”	1.47	0.82	0.68	0.06	----
30-360	3/8” x 1/4”	1.61	1.00	0.68	0.06	----
30-361	3/8” x 3/8”	1.77	0.97	0.81	0.08	----
30-362	3/8” x 1/2”	1.80	0.92	0.93	0.09	----
30-363	1/2” x 1/2”	1.90	1.02	0.93	0.11	----
30-366	3/4” x 3/4”	2.36	1.55	1.18	0.32	----

280

• Not recommend for water due to fiber gasket - for air service only.

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

PUSH ON HOSE BARB

HOSE SPLICER



Part #	Hose I.D.	A	Approx. Wt. Lbs.	
30-300	1/4"	1.87	0.04	----
30-305	5/16"	1.80	0.04	----
30-301	3/8"	2.00	0.06	----
30-302	1/2"	2.01	0.08	----
30-303	5/8"	3.03	0.14	----
30-304	3/4"	3.03	0.14	----
30-306	1"	3.21	0.28	----

BPM 696 29SPO 296 915 729 100B-Y KA-RM MHL 296 38282

RIGID FEMALE ADAPTER



Part #	Hose I.D. x Female NPTF	A	B	Hex	Approx. Wt. Lbs.	
30-220	1/4" x 1/8"	1.35	0.87	0.50	0.02	----
30-221	1/4" x 1/4"	1.51	0.87	0.62	0.06	----
30-384	1/4" x 3/8"	1.51	0.77	0.75	0.06	----
30-391	5/16" x 1/8"	1.32	0.77	0.50	0.03	----
30-222	5/16" x 1/4"	1.51	0.87	0.62	0.06	----
30-393	3/8" x 1/8"	1.47	0.92	0.56	0.06	----
30-224	3/8" x 1/4"	1.61	0.97	0.62	0.06	----
30-225	3/8" x 3/8"	1.63	0.97	0.75	0.06	----
30-394	3/8' x 1/2"	1.66	0.92	0.93	0.12	----
30-397	3/8" x 3/4"	1.97	0.97	1.18	0.20	----
30-223	1/2" x 1/4"	1.76	1.02	0.68	0.08	----
30-226	1/2" x 3/8"	1.63	0.97	0.75	0.08	----
30-227	1/2" x 1/2"	1.77	0.97	0.93	0.14	----
30-396	1/2" x 3/4"	2.07	1.02	1.18	0.20	----
30-398	5/8" x 3/8"	2.24	1.55	0.75	0.10	----
30-229	5/8" x 1/2"	2.24	1.48	0.93	0.11	----
NEW 30-403	5/8" x 3/4"	2.26	1.44	1.19	0.20	
30-399	3/4" x 1/2"	2.24	1.50	0.93	0.14	----
30-395	3/4" x 3/4"	2.55	1.50	1.18	0.24	----
30-400	1" x 3/4"	2.55	1.55	1.18	0.25	----
30-402	1" x 1"	2.68	1.55	1.43	0.37	----

30282 29FPO HLF 626 274 726 940

MALE ELBOW



Part #	Hose I.D. x Male NPTF	A	B	Body Width	Approx. Wt. Lbs.	
30-372	1/4" x 1/8"	0.98	0.75	0.50	0.04	----
30-373	1/4" x 1/4"	1.04	0.95	0.56	0.06	----
30-374	5/16" x 1/8"	1.02	0.94	0.50	0.06	----
30-375	5/16" x 1/4"	1.09	0.94	0.56	0.08	----
30-370	3/8" x 1/8"	1.11	0.75	0.50	0.10	----
30-371	3/8" x 1/4"	1.13	0.90	0.56	0.10	----
30-376	3/8" x 3/8"	1.21	0.92	0.70	0.12	----
30-377	3/8" x 1/2"	1.30	1.19	0.87	0.22	----
30-382	1/2" x 3/8"	1.32	1.02	0.70	0.13	----
30-378	1/2" x 1/2"	1.50	1.19	0.87	0.22	----
30-379	5/8" x 1/2"	1.98	1.19	0.87	0.26	----
30-383	3/4" x 1/2"	2.15	1.24	0.87	0.25	----
30-381	3/4" x 3/4"	2.07	1.28	1.06	0.34	----

100-C 29EPO 273

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

RIGID TUBE ADAPTER



Part #	Hose I.D. x O.D Tube	A	B	Approx. Wt. Lbs.	
30-290	1/4" x 3/16"	1.68	0.77	0.04	----
30-291	1/4" x 1/4"	1.88	0.77	0.04	----
30-292	1/4" x 5/16"	1.88	0.77	0.04	----
30-293	5/16" x 5/16"	1.91	0.79	0.04	----
30-294	3/8" x 3/8"	2.03	0.92	0.06	----
30-426	3/8" x 1/2	1.81	0.97	0.04	----
30-297	1/2" x 1/2"	2.13	1.02	0.06	----
30-298	5/8" x 5/8"	2.61	1.50	0.10	----
30-299	3/4" x 3/4"	2.61	1.50	0.25	----

294 100B-X KA-RL 303 732 694

MALE SAE FLARE ADAPTER



Part #	Hose I.D. x 45° Male Flare	UNF Thread	A	B	Hex	Approx. Wt. Lbs.	
30-240	1/4" x 1/4"	7/16-20	1.45	0.75	0.43	0.04	----
30-241	1/4" x 5/16"	1/2-20	1.59	0.84	0.50	0.04	----
30-249	5/16" x 5/16"	1/2-20	1.60	0.80	0.50	0.06	----
30-271	3/8" x 5/16"	1/2-20	1.64	0.86	0.50	0.08	----
30-243	3/8" x 3/8"	5/8-18	1.83	0.92	0.62	0.08	----
30-245	1/2" x 1/2"	3/4-16	1.98	1.02	0.875	0.10	----
30-246	5/8" x 5/8"	7/8-14	2.73	1.50	0.87	0.19	----
30-247	3/4" x 3/4"	1-1/16-14	2.98	1.50	1.06	0.32	----

100B-3 KA-MS 727 945 682 302 282

37° MALE JIC FLARE ADAPTER



• more sizes available

Part #	Hose I.D. x Male JIC	UNF Thread	A	B	Hex	Approx. Wt. Lbs.	
32-900	1/4" x 1/4"	7/16-20	1.57	0.84	0.50	0.04	----
32-901	1/4" x 5/16"	1/2-20	1.60	0.83	0.56	0.04	----
32-906	1/4" x 3/8"	9/16-18	1.63	0.77	0.62	0.05	----
32-902	3/8" x 3/8"	9/16-18	1.78	0.97	0.62	0.06	----
32-903	1/2" x 1/2"	3/4-16	1.97	0.97	0.75	0.10	----
32-907	5/8" x 5/8"	7/8-14	2.62	1.50	0.93	0.19	----
32-905	3/4" x 3/4"	1-1/16-12	2.79	1.50	1.12	0.29	----

SAE/JIC DUAL 45°/37° FEMALE SWIVEL



Part #	Hose I.D. x Dual Seat	UNF Thread	A	B	Hex	Approx. Wt. Lbs.	
30-230 *	1/4" x 1/4"	7/16-20	1.53	0.87	0.56	0.06	----
30-231	1/4" x 5/16"	1/2-20	1.53	0.87	0.62	0.04	----
30-232	5/16" x 5/16"	1/2-20	1.56	0.87	0.62	0.04	----
30-427	3/8" x 5/16"	1/2-20	1.74	0.87	0.62	0.06	----
30-233	3/8" x 1/2"	3/4-16	1.79	0.97	0.87	0.10	----
30-234 *	1/2" x 1/2"	3/4-16	1.77	0.97	0.87	0.10	----
30-235	1/2" x 5/8"	7/8-14	1.84	0.97	1.00	0.12	----
30-236	5/8" x 1/2"	3/4-16	2.27	1.45	0.87	0.18	----
30-237	5/8" x 5/8"	7/8-14	2.33	1.45	1.00	0.14	----
30-428	3/4" x 5/8"	7/8-14	2.33	1.45	1.00	0.20	----

* See page 36 for stainless
* See page 161 for lead free

29FDS 287 HDF 309 735 690 P990-K 305 935/ 934

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

45° SAE FLARE FEMALE SWIVEL



Part #	Hose I.D. x 45° Female Flare	UNF Thread	A	B	Hex	Approx. Wt. Lbs.	
30-250	1/4" x 1/4"	7/16-20	1.54	0.87	0.56	0.04	----
30-251	1/4" x 5/16"	1/2-20	1.57	0.87	0.62	0.04	----
30-253	1/4" x 3/8"	5/8-18	1.63	0.87	0.75	0.06	----
30-254	5/16" x 5/16"	1/2-20	1.58	0.87	0.68	0.06	----
30-260	5/16" x 3/8"	5/8-18	1.63	0.87	0.75	0.08	----
30-252	3/8" x 3/8"	5/8-18	1.73	0.97	0.75	0.10	----
30-257	3/8" x 1/2"	3/4-16	1.85	0.87	0.87	0.10	----
30-261	1/2" x 3/8"	5/8-18	1.92	1.05	0.75	0.10	----
30-255	1/2" x 1/2"	3/4-16	1.77	0.97	0.87	0.12	----
30-258	5/8" x 5/8"	7/8-14	2.35	1.45	1.00	0.14	----
30-259	3/4" x 3/4"	1-1/16-14	2.42	1.45	1.25	0.22	----

30882 728 P990-H 29AEPO 307 284 100S-4 KA-NS HSF 684 934

FEMALE 37° JIC FLARE SWIVEL



Part #	Hose I.D. x Female JIC	UNF Thread	A	B	Hex	Approx. Wt. Lbs.	
30-265	1/4" x 1/4"	7/16-20	1.54	0.87	0.56	0.04	----
30-264	1/4" x 3/8"	9/16-18	1.57	0.87	0.68	0.06	----
30-270	5/16" x 3/8"	9/16-18	1.60	0.82	0.68	0.06	----
30-266 *	3/8" x 3/8"	9/16-18	1.70	0.97	0.68	0.08	----
30-267	1/2" x 1/2"	3/4-16	1.78	0.97	0.87	0.10	----
30-268	5/8" x 5/8"	7/8-14	2.33	1.45	1.00	0.14	----
30-269 *	3/4" x 3/4"	1-1/16-12	2.40	1.45	1.25	0.22	----
30-429	1" x 1"	1-5/16-12	2.60	1.45	1.50	0.39	----

* See page 36 for stainless

JF 944/934 29J1CPO HJF 688 738 288 100B-6 308 P990-F 30682 KA-NJ

INVERTED FLARE MALE SWIVEL



Part #	Hose I.D. x Male INV Flare	UNF Thread	A	B	Hex	Approx. Wt. Lbs.	
30-275	1/4" x 3/16"	3/8-24	1.52	0.87	0.37	0.04	----
30-276	1/4" x 1/4"	7/16-24	1.56	0.87	0.43	0.04	----
30-277	1/4" x 5/16"	1/2-20	1.62	0.87	0.50	0.04	----
30-280	5/16" x 5/16"	1/2-20	1.62	0.87	0.50	0.06	----
30-283	5/16" x 3/8"	5/8-18	1.63	0.87	0.62	0.06	----
30-284	3/8" x 5/16"	1/2-20	1.72	0.97	0.50	0.06	----
30-279	3/8" x 3/8"	5/8-18	1.76	0.97	0.62	0.06	----
30-282	1/2" x 1/2"	3/4-18	1.84	0.97	0.75	0.10	----
30-286	5/8" x 5/8"	7/8-18	2.50	1.57	0.87	0.14	----

290 100B-B KA-MF 1MS 947

The best preparation for tomorrow is doing your best today. – H. Jackson Brown, Jr.

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

INVERTED FLARE FEMALE ADAPTER



Part #	Hose I.D. x Female INV Flare	A	B	Hex	Approx. Wt. Lbs.	
30-310	1/4" x 3/16"	1.12	0.84	0.50	0.02	----
30-311	1/4" x 1/4"	1.14	0.84	0.56	0.02	----
30-312	1/4" x 5/16"	1.18	0.82	0.62	0.02	----
30-316	5/16" x 5/16"	1.25	0.81	0.62	0.04	----
30-313	3/8" x 5/16"	1.32	0.87	0.62	0.04	----
30-314	3/8" x 3/8"	1.35	0.95	0.75	0.06	----
30-315	1/2" x 1/2"	1.73	1.04	0.87	0.12	----

306 100B-A KA-NG 292 P990-J 736 692 946

FEMALE BALLSEAT SWIVEL



Part #	Hose I.D. x Female NPSM	A	B	Hex	Approx. Wt. Lbs.	
30-340	1/4" X 1/8"	1.39	0.85	0.50	0.06	----
30-341	1/4" X 1/4"	1.47	0.80	0.68	0.06	----
30-342	1/4" x 3/8"	1.40	0.77	0.68	0.09	----
30-343	3/8" X 1/4"	1.61	0.97	0.68	0.08	----
30-344	3/8" X 3/8"	1.75	0.95	0.81	0.10	----
30-430	3/8" x 1/2"	1.79	0.97	0.93	0.11	----
30-346	1/2" X 1/2"	1.88	1.09	0.93	0.12	----
30-345	1/2" x 3/4"	2.36	1.02	1.18	0.18	----
30-349	3/4" X 3/4"	2.36	1.55	1.18	0.22	----

628 278 29SPO 731 NPSM

SAE/ JIC 37°/ 45° FEMALE SWIVEL 90° ZINC PLATED STEEL



Part #	Hose I.D. x Female 37°/45°	UNF Thread	A	B	Approx. Wt. Lbs.	
30-480	1/4"	7/16-20	1.55	0.83	.064	----
30-482	3/8"	9/16-18	1.85	0.91	.095	----
30-483*	3/8"	5/8-18	1.98	0.85	.095	----
30-484	1/2"	3/4-16	2.33	1.09	.171	----
30-486	3/4"	1-1/16-12	3.26	1.81	.281	----

* SAE

Nearly all men can stand adversity, but if you want to test a man's character, give him power.

- Abraham Lincoln

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

316 STAINLESS STEEL MALE ADAPTERS



Part #	Hose I.D. x NPT	A	B	Hex	Approx. Wt. Lbs.	
30-200SS	1/4" x 1/8"	1.42	0.77	0.44	0.027	----
30-201SS	1/4" x 1/4"	1.61	0.77	0.56	0.043	----
30-203SS	3/8" x 1/4"	1.76	0.92	0.56	0.053	----
30-204SS	3/8" x 3/8"	1.76	0.92	0.69	0.067	----
30-206SS	1/2" x 3/8"	1.86	1.02	0.69	0.071	----
30-207SS	1/2" x 1/2"	2.07	1.02	0.88	0.119	----
30-215SS	3/4" x 1/2"	2.55	1.50	0.88	0.20	----
30-210SS	3/4" x 3/4"	2.55	1.50	1.06	0.194	----

316 STAINLESS STEEL SAE/ JIC 45°/ 37° FEMALE SWIVEL



Part #	Hose I.D. x Female 45°/37°	A	B	Hex	Approx. Wt. Lbs.	
30-230SS	1/4" x 1/4"	1.48	0.74	0.56	0.023	----
30-234SS	1/2" x 1/2"	1.93	1.03	0.88	0.04	----

316 STAINLESS STEEL FEMALE 37° JIC FLARE SWIVEL



Part #	Hose I.D. x Female 37°	A	B	Hex	Approx. Wt. Lbs.	
30-266SS	3/8" x 3/8"	1.75	.92	0.68	0.065	----
30-269SS	3/4" x 3/4"	2.53	1.50	1.25	0.259	----

only two things are infinite, the universe and human stupidity, and I'm not sure about the former.

- Albert Einstein

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

GARDEN HOSE FITTINGS

• Temperature and Working Pressure Ranges

From +35^{0}F to +100^{0}F at 75 PSI maximum or the recommended working pressure of the garden hose. (Not to exceed 150 PSI.)

Note: All female connector ends should have a rubber washer inserted prior to usage.

FGH = Female Garden Hose threads
MGH = Male Garden Hose threads
Male garden hose threads are all 3/4" with an outside diameter of 1.0625 and 11-1/2" threads per inch.

Male Garden Hose Profile

See Plastic section for Plastic Garden Hose Fittings

See page 162 for lead free Garden Hose

Washers included are #30150B black rubber washers.

Actual Profile of Garden Hose Barbs



WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

SWIVEL - MGH X FGH

•WASHER INCLUDED

Internal Hex

Part #	MGH X FGH	A	Hex	Approx. Wt. Lbs.	
30-000**	3/4" x 3/4"	1.03	0.50*	0.26	----

* Internal Hex
* Not a live swivel
** available in swivel crimp style

SWIVEL - FGH X FGH

•WASHER INCLUDED



30-011 30-012

Part #	FGH X FGH	A	Hex	Approx. Wt. Lbs.	
30-011	3/4" x 3/4"	1.03	1.18 O.D.	0.24	----
30-012	No Swivel	1.08	1.19	0.24	----

HUS 91 203W GSU 101GHSV 22AS 506 FS66

SWIVEL - FGH X FEMALE PIPE

•WASHER INCLUDED

Part #	FGH x Female NPTF	A	Hex	Approx. Wt. Lbs.	
30-001	3/4" x 1/2"	1.20	1.00	0.11	----
30-006	3/4" x 3/4"	1.11	1.12	0.11	----

S1 HSU11 91Z 197S 98GHSV 5AS 21517 502 FS65

EVAPORATIVE COOLER FITTINGS



50-016 30-013 30-020

Part #	Size	
50-016	MGH x 1/2" FIP	----
30-013	1/2 MIP x 1/2 FIP x 1/8	----
30-019	3/4 MIP x 3/4 FIP x 1/8	----
30-020	MGH x FGH x 1/8	----

RIGID - FGH X FEMALE PIPE

•WASHER INCLUDED



30-017

Part #	FGH x Female NPTF	A	Hex	Approx. Wt. Lbs.	
30-016	3/4" x 1/8"	1.02	1.18	0.08	----
30-017	3/4" x 1/4"	0.65	1.12	0.07	----
30-018	3/4" x 3/8"	1.19	1.18	0.11	----

95GH 501

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

RIGID - FGH X FEMALE PIPE

Part #	FGH x Female NPTF	A	Hex	Approx. Wt. Lbs.	
30-078	3/4” x 1/2”	1.06	1.18	0.10	----
30-083	3/4” x 3/4”	1.06	1.18	0.12	----

FS67 198 HU11 21507 501 99GH 5A H15PP

SWIVEL - FGH X MALE PIPE

•WASHER INCLUDED



Part #	FGH x Male NPTF	A	Hex	Approx. Wt. Lbs.	
30-047	3/4” x 1/4”	2.04	0.75	0.13	----
30-048	3/4” x 3/8”	2.06	0.75	0.14	----
30-049	3/4” x 1/2”	2.06	0.87	0.18	----

504 89GH W1 62H4 88GH W1

3/8" Comp 3/4" FGH DISHWASHER 90° ELBOW

• WASHER INCLUDED



Part #	3/4 Female Garden Hose Thread x 3/8 Compression	
30-055	3/4" x 3/8" Body Only	----
30-056	3/4" x 3/8" w/ nut & sleeve	----

SWIVEL - FGH X MALE PIPE

• WASHER INCLUDED



* Crimp style

Part #	FGH x Male NPTF	A	Hex	Approx. Wt. Lbs.	
30-181*	3/4" x 1/4"	1.43	1.18	0.13	----
30-184*	3/4" x 3/8"	1.43	1.18	0.15	----
30-183	3/4” x 1/2”	1.32	0.81	0.11	----
30-182*	3/4" x 3/4"	1.43	1.18	0.14	----

RIGID - FGH X MALE PIPE

• WASHER INCLUDED



Part #	FGH x Male NPTF	A	Hex	Approx. Wt. Lbs.	
30-087	3/4" x 3/8"	1.37	1.18	0.11	----
30-088	3/4” x 1/2”(1/2”SWT)**	1.06	1.18	0.09	----
30-093	3/4” x 3/4”	1.06	1.18	0.11	----
30-094	3/4” x 3/4”(1/2” FIP)	1.17	1.18	0.11	----
30-093L*	3/4” x 3/4”	1.22	1.18	0.14	----

* Long pattern

** 1/2 Swt = 5/8 O.D.

21505 503 83GH 20A HU21 199 H7

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

RIGID - MGH X FEMALE PIPE

30-068

	Part #	MGH X Female NPTF	A	Hex	Approx. Wt. Lbs.	
	30-066	3/4” x 1/4”	1.10	1.06	0.09	----
	30-067	3/4” x 3/8”	1.09	1.06	0.12	----
	30-068	3/4” x 1/2”	0.81	1.06	0.10	----
	30-073	3/4” x 3/4”	1.12	1.18	0.10	----
NEW	30-074	3/4" x 1"	1.36	1.37	0.19	
NEW	30-075	1" x 1"	1.60	1.38	0.25	

197 18R HU12 H11PP 18A 507 18H 81GH 21503 MF67

RIGID - MGH X MALE PIPE

	Part #	MGH X Male NPTF	A	Hex	Approx. Wt. Lbs.	
NEW	30-054	3/4" x 1/4"	1.26	1.06	0.12	
	30-053	3/4” x 3/8”	1.25	1.06	0.10	----
	30-058*	3/4” x 1/2”	1.31	1.06	0.12	----
	30-063**	3/4” x 3/4” x 1/2”	1.31	1.06	0.13	----
	30-063BE***	3/4” x 3/4”	1.31	1.06	0.15	----
	30-063S	3/4” x 3/4” Short	1.10	1.06	0.10	----
	30-064	3/4" x 1"	1.88	1.37	0.35	----
NEW	30-065	1" x 1"	1.88	1.37	0.26	

No Tap

19R 196 H530 21501 508 HU22 514 71GH 19A

* (1/2 Swt = 5/8 O.D.)

** (Tapped 1/2 FIP)

*** (Tapped 1/2 FIP Both ends)

RIGID - MGH X MGH



	Part #	MGH X MGH	A	Hex	Approx. Wt. Lbs.	
	30-098	3/4” x 3/4” (1/2" FIP)	1.22	1.06	0.13	----
	30-099	3/4" x 3/4"	1.38	1.06	0.15	----
	30-100*	1" x 3/4"	1.31	1.37	0.21	----
NEW	30-101	1" x 1"	1.38	1.37	0.23	

* 1-11-1/2

21500 509 75GH 23A H8 19R

GARDEN HOSE NUT

30-021

30-022

Part #	Size	A	Hex	Approx. Wt. Lbs.	
30-021	Knurled	0.61	1.37 O.D.	0.08	----
30-022	Hex Nut	0.62	1.18	0.08	----

94GH GHN1 HNR 21514

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

GARDEN HOSE WASHERS



30-150

30-150R

Part #	Size	A	B	Thickness	Approx. Wt. Lbs.	
30-150	black*	0.98	0.68	0.13	0.01	----
30-150R	red	1.00	0.68	0.13	0.01	----
30-150B	black rubber	1.00	0.68	0.13	0.01	----
30-151	1"	1.27	0.86	0.16	0.01	----

GHW 901GH

* plasticized rubber

GARDEN HOSE FILTER WASHER



• 300 Series Stainless Steel Screen

Part #	Size	A	B	Approx. Wt. Lbs.	
30-180	30 Mesh	0.52	1.00	0.02	----
30-180F	60 Mesh	0.52	1.00	0.02	----

LA662

GARDEN HOSE CAP

30-103



30-103B

Part #	Size	A	Approx. Wt. Lbs.	
30-103	3/4" Die Cast	0.58	0.04	----
30-103B	3/4" Barstock	0.60	0.048	----

513 96GH GHN5 HC1 LA215 21518 200-W

• Garden hose washers sold seperately

GARDEN HOSE CAP WITH CHAIN



Part #	Size	A	Approx. Wt. Lbs.	
30-142	3/4" w/ 12" Chain	0.58	0.06	----

* Zinc die cast

GARDEN HOSE PLUG



Part #	Size	A	B	Approx. Wt. Lbs.	
30-026	3/4"	0.69	0.61	0.12	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

HOSE MENDERS - SOLID BARB X BARB

Part #	Hose I.D. x Hose I.D.	A	B	O.D.	Approx. Wt. Lbs.	
32-096	1/2”	2.00	0.96	0.62	0.06	----
32-097	5/8”	2.05	0.96	0.75	0.08	----
32-098	3/4”	2.50	1.15	0.87	0.10	----
32-099	1"	3.00	1.44	1.02	0.23	----

QUICK DISCONNECT GARDEN HOSE COUPLERS

•WASHER INCLUDED



30-452 30-451

- Unvalved construction allows maximum Flow
- 150 PSI
- NBR Seals

Part #	Size	A	Approx. Wt. Lbs.	
30-450	Complete	1.70	0.24	----
30-451	Female end	1.14	0.12	----
30-452	Male end	1.26	0.12	----
30-149	Recessed Washer	1.02	0.01	

LA73C

MALE FLARE X FGH RIGID

Part #	Male Flare x FGH	A	Hex	Approx. Wt. Lbs.	
30-123	3/8” x 3/4”	1.31	1.18	0.10	----
30-128	1/2” x 3/4”	1.38	1.18	0.12	----
30-133	5/8” x 3/4”	1.53	1.18	0.14	----

190 46WH HFU21

MALE FLARE x FGH SWIVEL

•WASHER INCLUDED



Part #	Male Flare x FGH	A	Hex	Approx. Wt. Lbs.	
30-052	1/4” x 3/4”	1.24	0.75	0.10	----
30-138	3/8” x 3/4”	1.25	0.25*	0.12	----
30-139	1/2” x 3/4”	1.49	0.81	0.14	----

* Internal Hex

50GHSV 51GHSV W1 68H 191

COMPRESSION X FGH

•WASHER INCLUDED



Part #	Swivel Compression x FGH	A	Hex 1	Hex 2	Approx. Wt. Lbs.	
30-050	1/4” x 3/4”	1.02	0.50	0.75	0.09	----
30-051	3/8” x 3/4”	1.04	0.62	0.75	0.12	----



Part #	No Swivel Compression x MGH	A	Hex 1	Hex 2	Approx. Wt. Lbs.	
30-135	1/4” x 3/4”	1.45	0.50	0.625	0.14	----
30-136	3/8” x 3/4”	1.525	0.625	0.62	0.15	----
30-137	1/2" x 3/4"	1.8	0.815	0.685	0.19	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

BARSTOCK BRASS GARDEN HOSE COUPLINGS

FEMALE SWIVEL ONLY

•WASHER INCLUDED



BRASS

Part #	Hose Barb x FGH	A	B	Hex	Approx. Wt. Lbs.	
30-031	3/8” x 3/4"	1.82	1.19	1.18	0.11	----
30-032	1/2” x 3/4"	1.82	1.19	1.18	0.12	----
30-033	5/8” x 3/4"	1.82	1.19	1.18	0.13	----
30-034	3/4” x 3/4"	1.82	1.19	1.18	0.15	----
30-044	1" x 3/4"	2.10	1.19	1.18	0.18	----
30-035	1” x 1"	2.28	1.47	1.50	0.18	----

STAINLESS STEEL 316

30-032SS	1/2" x 3/4"	1.82	1.19	1.18	0.12	----
30-033SS	5/8" x 3/4"	1.82	1.19	1.18	0.13	----
30-034SS	3/4" x 3/4"	1.82	1.19	1.18	0.15	----

MALE END ONLY



BRASS

Part #	Hose Barb x MGH	A	B	Hex	Approx. Wt. Lbs.	
30-039	3/8” x 3/4"	1.88	1.19	1.06	0.12	----
30-040	1/2” x 3/4"	1.88	1.19	1.06	0.12	----
30-041	5/8” x 3/4"	1.88	1.19	1.06	0.12	----
30-042	3/4” x 3/4"	1.88	1.19	1.06	0.13	----
30-045	1" x 3/4"	1.94	1.19	1.06	0.21	----
30-043	1” x 1"	2.34	1.47	1.37	0.26	----

STAINLESS STEEL 316

30-040SS	1/2" x 3/4"	1.88	1.19	1.06	0.12	----
30-041SS	5/8" x 3/4"	1.88	1.19	1.06	0.12	----
30-042SS	3/4" x 3/4"	1.88	1.19	1.06	0.13	----

GARDEN HOSE COUPLING

•WASHER INCLUDED

BRASS

Part #	Hose Barb	
30-025	3/8”	----
30-027	1/2”	----
30-028	5/8”	----
30-029	3/4”	----
30-046	1"(3/4" threads)	----
30-030	1”	----

STAINLESS STEEL 316

30-027SS	1/2"	----
30-028SS	5/8"	----
30-029SS	3/4"	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

FEMALE SWIVEL ONLY - Short Shank Knurled Nut



	Part #	Hose Barb x FGH	A	B	Approx. Wt. Lbs.	
NEW	30-464	1/4" x 3/4"	1.39	0.77	0.09	
	30-466	1/2" x 3/4"	1.50	0.88	0.08	----
	30-467	5/8" x 3/4"	1.50	0.88	0.09	----
	30-468	3/4" x 3/4"	1.47	0.88	0.10	----

FEMALE END ONLY - Short Shank w/ hex

Part #	Hose x FGH	A	B	Hex	Approx. Wt. Lbs.	
30-453	1/2" x 3/4"	1.63	1.00	1.18	0.11	----
30-454	5/8" x 3/4"	1.63	1.00	1.18	0.11	----
30-455	3/4" x 3/4"	1.63	1.00	1.18	0.13	----

MALE END ONLY - Short Shank



	Part #	Hose Barb x MGH	A	B	Hex	Approx. Wt. Lbs.	
NEW	30-469	1/4" x 3/4"	1.55	0.88	1.06	0.11	
	30-471	1/2" x 3/4"	1.55	0.88	1.06	0.11	----
	30-472	5/8" x 3/4"	1.56	0.88	1.06	0.12	----
	30-473	3/4" x 3/4"	1.56	0.88	1.06	0.13	----

GARDEN HOSE COUPLING SETS - Short Shank w/ hex nut

Part #	Hose Barb	
30-457	1/2"	----
30-458	5/8"	----
30-459	3/4"	----

FEMALE SWIVEL ONLY - 2" SHANK

•WASHER INCLUDED



Part #	Hose Barb x FGH	A	B	Hex	Approx. Wt. Lbs.	
30-505	1/2" x 3/4"	2.55	2.04	1.18	0.13	----
30-506	5/8" x 3/4"	2.56	2.04	1.18	0.16	----
30-507	3/4" x 3/4"	2.67	2.04	1.18	0.17	----
30-508	1" x 1"	2.84	2.03	1.43	0.29	----

GHFL 594

MALE END ONLY - 2" SHANK



Part #	Hose Barb x MGH	A	B	Hex	Approx. Wt. Lbs.	
30-510	1/2" x 3/4"	2.72	2.04	1.06	0.16	----
30-511	5/8" x 3/4"	2.72	2.04	1.06	0.17	----
30-512	3/4" x 3/4"	2.72	2.04	1.06	0.20	----
30-513	1" x 1"	2.90	2.03	1.37	0.28	----

GHML 593

GARDEN HOSE COUPLING SETS - 2" SHANK

Part #	Hose x FGH	
30-516	1/2"	----
30-517	5/8"	----
30-518	3/4"	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

NPSM FEMALE SHORT SHANK



Part #	Hose ID	NPSM Thread	A	B	Hex	
30-545	1/2	3/4"	1.45	0.88	1.18	----
30-546	5/8	3/4"	1.47	0.88	1.18	----
30-547	3/4	3/4"	1.47	0.88	1.18	----
30-548	1	1"	1.50	1.00	1.50	----

NPSM MALE SHORT SHANK



Part #	Hose ID	NPSM Thread	A	B	Hex	
30-550	1/2	3/4"	1.56	0.88	1.06	----
30-551	5/8	3/4"	1.56	0.88	1.06	----
30-552	3/4	3/4"	1.56	0.88	1.06	----
30-553	1	1"	1.77	0.98	1.30	----

NPSM SHORT SHANK SETS

Part #	Size	
30-540	1/2"	----
30-541	5/8"	----
30-542	3/4"	----
30-543	1"	----

NPSM FEMALE LONG SHANK



Part #	Hose ID	NPSM Thread	A	B	Hex	
30-565	1/2	1/2"	2.09	1.50	0.94	----
30-566	5/8	3/4"	2.09	1.50	1.18	----
30-567	3/4	3/4"	2.09	1.50	1.18	----
30-568	1	1"	2.12	1.53	1.50	----

NPSM MALE LONG SHANK



Part #	Hose ID	NPSM Thread	A	B	Hex	
30-570	1/2	1/2"	2.18	1.50	0.87	----
30-571	5/8	3/4"	2.18	1.50	1.06	----
30-572	3/4	3/4"	2.18	1.50	1.06	----
30-573	1	1"	2.32	1.53	1.30	----

NPSM LONG SHANK SETS

Part #	Size	
30-560	1/2"	----
30-561	5/8"	----
30-562	3/4"	----
30-563	1"	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

WROUGHT BRASS

WROUGHT BRASS - Female end only

•WASHER INCLUDED



Part #	Hose Barb x FGH	A	B	Approx. Wt. Lbs.	
30-526	5/8” x 3/4"	1.58	0.91	0.05	----

85L

WROUGHT BRASS COUPLINGS - Male end only



Part #	Hose Barb x MGH	A	B	Approx. Wt. Lbs.	
30-530	1/2” x 3/4"	1.50	0.88	0.02	----

85M

GARDEN HOSE VALVES

ONE WAY BRASS BALL VALVE - FGH x MGH

• 500 PSI • 180°F

• WASHER INCLUDED



Part #	FGH x MGH	A	B	C	Hex	Approx. Wt. Lbs.	
30-161	3/4” x 3/4"	1.87	1.89	1.31	1.06	0.42	----

ONE WAY BRASS BALL VALVE - Female Pipe x MGH

• 500 PSI • 180°F



Part #	Female NPTF x MGH	A	B	C	Hex	Approx. Wt. Lbs.	
30-162	3/4” x 3/4"	1.55	1.89	1.31	1.06	0.42	----

ZINC ALLOY HOSE SHUT-OFF W/ ONE LEVER

• WASHER INCLUDED

Part #	FGH x MGH	A	Approx. Wt. Lbs.	
30-631	3/4" x 3/4"	1.67	0.08	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

PLASTIC GARDEN HOSE VALVE

• CYCOLAC BODY & BALL • WASHER INCLUDED

Part #	FGH x MGH	A	Hex	Approx. Wt. Lbs.	
30-163	3/4" x 3/4"	1.75	1.25	0.04	----

LA45OC

CAST BRASS HOSE - "Y" CONNECTOR

• WASHER INCLUDED



Part #	Size FGH x MGH(2)	A	B	Approx. Wt. Lbs.	
30-140	3/4"	1.40	0.67	0.22	----

86Y 21A

PLASTIC, NON-CORROSIVE, 2-WAY HOSE SHUT-OFF "Y"

• WASHER INCLUDED



No Swivel

Part #	Size FGH x MGH(2)	A	B	Approx. Wt. Lbs.	
30-160	3/4"	0.74	1.87	0.08	----

"Y" SHAPE ZINC ALLOY CONNECTOR W/ TWO LEVERS

• WASHER INCLUDED



No Swivel

Part #	Size FGH x MGH(2)	A	B	Approx. Wt. Lbs.	
30-626	3/4"	0.60	1.66	0.10	----

"Y" SHAPE BRASS CONNECTOR W/ 2-WAY SHUT OFF

• WASHER INCLUDED

• Brass Levers

Part #	Size	Description FGH Swivel x MGH(2)	Approx. Wt. Lbs.	
30-627	3/4"	3/4 Double Y valve, swivel inlet	0.56	----

ZINC ALLOY SWIVEL HOSE CONNECTOR



Part #	Size FGH x MGH	A	B	Approx. Wt. Lbs.	
30-629	3/4"	1.31	1.50	0.08	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

GARDEN HOSE NOZZLES | BRASS FITTINGS

2-1/2" BRASS NOZZLE

• WASHER INCLUDED



Part #	Size	A	Approx. Wt. Lbs.	
30-637	3/4"	2.50	0.14	----

3" CROSSED PATTERN BRASS NOZZLE

• WASHER INCLUDED



Part #	Size	A	Approx. Wt. Lbs.	
30-640	3/4"	2.89	0.25	----

4" CROSSED PATTERN BRASS NOZZLE

• WASHER INCLUDED



Part #	Size	A	Approx. Wt. Lbs.	
30-638	3/4"	3.80	0.50	----

• WASHER INCLUDED

Adjustable Spray

Part #	Size		
30-600	5-1/2"	Zinc Alloy spray nozzle with insulated handle soft grip and front thread protector	----

• WASHER INCLUDED

Lead Free

Part #	Size		
30-620	4-1/4"	Zinc Alloy spray nozzle	----

• WASHER INCLUDED

Lead Free
Adjustable Spray

Part #	Size		
30-609	5-1/4"	Zinc Alloy spray nozzle with easily adjustable brass head and plastic grip	----

• WASHER INCLUDED

Part #	Size		
30-630	4-1/2"	Plastic spray nozzle	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

SAE 45° FLARE

Tube O.D.	1/8	3/16	1/4	5/16	3/8	7/16	1/2	5/8	3/4
Thread Size-B	5/16-24	3/8-24	7/16-20	1/2-20	5/8-18	11/16-16	3/4-16	7/8-14	1-1/16-14

•Typical Application
LP and natural gas, flammable liquids, instrumentation, refrigeration, power steering, hydraulic and pneumatic systems.

•Working Pressure Ranges
Temperature and type of tubing used are important factors. However, the following table is a good guide for proper selection. Temperature 73^{0}F with copper tubing:

PSI	Tube O.D. (in.)	Tube Wall (in.)
2800	1/8	.030
1900	3/16	.030
1400	1/4	.030
1200	5/16	.032
1000	3/8	.032
750	1/2	.032
650	5/8	.035
550	3/4	.035
450	7/8	.035

•Vibration
Good resistance - use long nut when greater vibration resistance is required.

•Temperature Range
-65^{0}F to +250^{0}F (-53^{0}C to +121^{0}C) range at maximum operating pressures.

•Used With
Copper, brass, aluminum and steel hydraulic tubing that can be flared.

• Tolerance
+/- .03 on all dimensions. Dimension data can change without notice. Please call us when dimensions are critical.

•Conformance
Meets specifications and standards of ASA, ASME, SAE and MS (Military standards).

Assembly Instructions
1- Cut tubing to desired length. Make sure all burrs are removed and ends are cut square.
2- Slide nut on tube. Threaded end "A" of nut must face out.
3- Flare end of tube with a 45^0 flaring tool.
a-Measure flare diameter.
b- Examine flare for excessive thin out.
4- Lubricate threads and assemble to fitting body. Nut should be turned hand tight.
5- Tighten assembly with wrench until a solid feeling is encountered. From that point, apply a one-sixth turn.
Note: Do not over-torque as it may damage the fitting or split the tubing at the flare.

• See Lead Free Flare Fittings page 163-164

Actual O.D. of Flare Fittings

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

SHORT ROD NUT

SAE# 010110



Part #	Thread Size UNF	Thread	A	Hex	Approx. Wt. Lbs.	
10-013	1/8”	5/16-24	0.50	0.37	0.01	----
10-014	3/16”	3/8-24	0.62	0.43	0.02	----
10-015	1/4”	7/16-20	0.75	0.56	0.03	----
10-015L	1/4"	7/16-20	0.75	0.50	0.03	----
10-016	5/16”	1/2-20	0.88	0.62	0.04	----
10-017L	3/8”	5/8-18	0.77	0.75	0.05	----
10-017	3/8”	5/8-18	1.00	0.75	0.04	----
10-018	7/16”	11/16-16	1.06	0.81	0.06	----
10-019L	1/2”	3/4-16	0.93	0.87	0.06	----
10-019	1/2”	3/4-16	1.12	0.87	0.09	----
10-020L	5/8”	7/8-14	1.08	1.00	0.10	----
10-020	5/8”	7/8-14	1.31	1.06	0.15	----
10-021	3/4”	1-1/16-14	1.50	1.25	0.24	----
10-022	7/8”	1-1/4-12	1.62	1.50	0.36	----
10-026	1”	1-3/8-12	1.81	1.62	0.44	----

20910 41FS 1110 N1 41FX 441S 'L'

REDUCING SHORT ROD NUT



Part #	Thread Size UNF	A	Hex	Approx. Wt. Lbs.	
10-023	3/8” x 1/4”	0.74	0.81	0.06	----
10-024	1/2” x 3/8”	0.86	0.94	0.10	----
10-025	5/8” x 1/2”	0.99	1.06	0.12	----

LONG ROD NUT

SAE# 010111



Part #	Thread Size UNF	A	Hex	Approx. Wt. Lbs.	
10-001	1/8”	0.75	0.37	0.01	----
10-002	3/16”	0.81	0.43	0.02	----
10-003L	1/4"	0.98	0.55	0.03	----
10-003	1/4”	0.94	0.56	0.03	----
10-004	5/16”	1.12	0.62	0.04	----
10-005	3/8”	1.31	0.75	0.06	----
10-006	1/2”	1.62	0.87	0.12	----
10-007	5/8”	1.88	1.06	0.20	----
10-008	3/4”	2.19	1.25	0.34	----

41FL N2 241 441 41

"L" means light pattern.

-These fittings are completely interchangeable with full pattern fittings, but have been modified in some way. This modification is usually in the length of the pipe threads. Used in plumbing and light industrial applications.

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

LONG FORGED NUT

SAE# 010167



Part #	Thread Size UNF	A	Hex	Approx. Wt. Lbs.	
10-028	1/4”	0.94	0.62	0.05	----
10-030	3/8”	1.06	0.81	0.08	----
10-031	1/2”	1.19	0.94	0.12	----
10-032	5/8”	1.44	1.06	0.26	----
10-033	3/4”	1.75	1.31	0.35	----

41FF 39 N4 14FL 641

SHORT FORGED NUT

SAE# 010166

Part #	Thread Size UNF	A	Hex	Approx. Wt. Lbs.	
10-038	3/16”	0.56	0.50	0.02	----
10-039	1/4”	0.60	0.62	0.04	----
10-040	5/16”	0.66	0.69	0.04	----
10-041	3/8”	0.70	0.81	0.06	----
10-042	1/2”	0.82	0.94	0.08	----
10-043	5/8”	0.95	1.06	0.12	----
10-044	3/4”	1.16	1.31	0.22	----
10-045	7/8”	1.18	1.38	0.30	----

14FS 41FFS 40 641-S 1116 NS4

EXTRA HEAVY SHORT FORGED NUT

Part #	Thread Size UNF	A	Hex	Approx. Wt. Lbs.	
10-046	1/4”	0.63	0.75	0.04	----
10-047	3/8”	0.72	0.88	0.06	----
10-048	1/2”	0.88	1.00	0.08	----
10-049	5/8”	0.98	1.12	0.12	----

NSA

FORGED REDUCING NUT

Part #	Female Flare x OD	A	Hex	Approx. Wt. Lbs.	
10-051	5/16” x 1/4”	0.66	0.75	0.06	----
10-052	3/8” x 1/4”	0.72	0.81	0.06	----
10-053	3/8” x 5/16”	0.72	0.81	0.08	----
10-054	1/2” x 3/8”	0.81	0.94	0.08	----
10-055	5/8” x 3/8”	0.96	1.12	0.15	----
10-056	5/8” x 1/2”	0.97	1.06	0.12	----
10-058	3/4” x 5/8”	1.17	1.31	0.30	----

NSR4 14FS 41FRS 40R 662-S

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

FLARED PLUG



	Part #	Thread Size UNF	A	Hex	Approx. Wt. Lbs.	
NEW	10-062	1/8"	0.53	0.34	0.01	
	10-063	3/16"	0.59	0.50	0.02	----
	10-064 *	1/4"	0.69	0.43	0.02	----
	10-065 *	5/16"	0.78	0.50	0.04	----
	10-066 *	3/8"	0.88	0.62	0.06	----
	10-067	1/2"	1.06	0.75	0.10	----
	10-068	5/8"	1.19	0.87	0.14	----
	10-069	3/4"	1.32	1.06	0.22	----

* Available in Stainless Steel. Add SS to the part#

58 639F PF 57 P2 2229 439

FLARED CAP



	Part #	Thread Size UNF	A	Hex	Approx. Wt. Lbs.	
NEW	10-073	1/8"	0.46	0.37	0.02	
	10-074	3/16"	0.47	0.50	0.02	----
	10-075 *	1/4"	0.48	0.50	0.02	----
NEW	10-075EH	1/4"	0.54	0.57	0.02	
	10-076	5/16"	0.62	0.62	0.04	----
	10-077 *	3/8"	0.58	0.75	0.03	----
	10-078	1/2"	0.69	0.81	0.14	----
	10-079	5/8"	0.81	0.94	0.20	----
	10-080	3/4"	1.17	1.37	0.30	----

* Available in Stainless Steel. Add SS to the part#

640F 41FC 56 N5 2129 54 440

FINGER TIGHTENING CAP

- Neoprene
- **O-Ring Included**



	Part #	Thread Size UNF	A	Approx. Wt. Lbs.	
	10-081	1/4"	0.62	0.02	----
NEW	10-082	3/8"	0.70	0.03	

NFT5

COPPER GASKET

SAE# 010113



Part #	Size	A	B	Approx. Wt. Lbs.	
10-084	3/16"	0.31	0.12	0.01	----
10-085	1/4"	0.36	0.19	0.01	----
10-086	5/16"	0.42	0.22	0.01	----
10-087	3/8"	0.55	0.28	0.01	----
10-088	1/2"	0.66	0.41	0.01	----
10-089	5/8"	0.77	0.50	0.01	----
10-090	3/4"	0.95	0.62	0.01	----

B2 2GF 6251 FG 157 59 46

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

COPPER BONNET

SAE# 010114



Part #	Size	A	B	Approx. Wt. Lbs.	
10-094	3/16”	0.16	0.31	0.01	----
10-095	1/4”	0.22	0.36	0.01	----
10-097	3/8”	0.34	0.55	0.01	----
10-098	1/2”	0.41	0.66	0.01	----
10-099	5/8”	0.44	0.77	0.01	----
10-100	3/4”	0.56	0.95	0.01	----

B1 3GF 64C 57 156 FB 695 464

MALE BALL CHECK CONNECTOR





	Part #	Male Flare x Male NPTF	A	Hex	Approx. Wt. Lbs.	
	10-131*	1/4" x 1/8"	1.06	0.43		----
	10256WC	1/4” x 1/4”	1.24	0.6	0.04	----
	10-133*	3/8” x 1/4”	1.31	0.62	0.08	----
NEW	10-132	5/16" x 1/8"	1.14	0.50	0.04	

43A

* Note: Ball & Spring position may be reversed to change flow/check position. Min working pressure 3 PSI.

UNION

SAE# 010101



	Part #	Thread Size UNF	A	Hex	Approx. Wt. Lbs.	
	10-104	1/8”	0.91	0.31	0.02	----
	10-105	3/16”	1.06	0.37	0.02	----
	10-106L	1/4”	1.19	0.43	0.03	----
	10-106 *	1/4”	1.19	0.43	0.03	----
NEW	10-106EH	1/4"	1.55	0.56	0.05	
	10-107	5/16”	1.34	0.50	0.05	----
	10-108L	3/8”	1.50	0.62	0.09	----
	10-108 *	3/8’	1.50	0.62	0.09	----
	10-109L	1/2”	1.67	0.75	0.12	----
	10-109	1/2”	1.81	0.75	0.14	----
	10-110L	5/8”	2.00	0.87	0.20	----
	10-110	5/8”	2.12	0.87	0.20	----
	10-111	3/4”	2.44	1.06	0.35	----
	10-112	7/8”	2.72	1.25	0.52	----

* Available in Stainless Steel. Add SS to the part#

42F U2

"L" means light pattern.

-These fittings are completely interchangeable with full pattern fittings, but have been modified in some way. This modification is usually in the length of the pipe threads. Used in plumbing and light industrial applications.

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

REDUCING UNION



Part #	Thread Size UNF	A	Hex	Approx. Wt. Lbs.	
10-115	1/4" x 1/8"	1.11	0.44	0.03	----
10-116	1/4" x 3/16"	1.12	0.44	0.03	----
10-117	5/16" x 1/4"	1.28	0.50	0.04	----
10-118	3/8" x 1/4"	1.38	0.62	0.06	----
10-119	3/8" x 5/16"	1.44	0.62	0.08	----
10-120	1/2" x 1/4"	1.53	0.75	0.10	----
10-121	1/2" x 3/8"	1.69	0.75	0.10	----
10-122	5/8" x 3/8"	1.88	0.87	0.17	----
10-123	5/8" x 1/2"	1.87	0.87	0.14	----
10-126	3/4" x 1/2"	2.18	1.06	0.26	----
10-127	3/4" x 5/8"	2.20	1.06	0.27	----

656F UR2 42-R

UNION TEE



Forged Tee

SAE# 010401

Part #	Thread Size UNF	A	Body Size	Approx. Wt. Lbs.	
10-157	1/8"	0.67	0.36	0.04	----
10-158	3/16"	0.75	0.36	0.06	----
10-159 **	1/4"	0.78	0.36	0.06	----
10-160 **	5/16"	0.91	0.44	0.10	----
10-161 **	3/8"	1.00	0.44	0.12	----
10-162	1/2"	1.16	0.59	0.19	----
10-163	5/8"	1.41	0.69	0.30	----
10-164	3/4"	1.64	0.88	0.53	----
10-165	7/8"	1.75	1.25	0.93	----

** Available in Stainless Steel. Add SS to the part#

244F T2 144F

REDUCING TEE 1 x 2 x 3



Part #	Thread Size UNF 1x2x3	A	C	Body Size	Approx. Wt. Lbs.	
10-170	1/4" x 1/4" x 3/8"	0.91	1.00	0.44	0.10	----
10-171	5/16" x 5/16" x 1/4"	0.94	0.94	0.44	0.12	----
10-172	3/8" x 1/4" x 1/4"	0.91	1.00	0.44	0.10	----
10-173	3/8" x 1/4" x 3/8"	1.00	0.91	0.44	0.12	----
10-174	3/8" x 3/8" x 1/4"	1.00	0.88	0.44	0.11	----
10-175	3/8" x 3/8" x 1/2"	1.00	1.19	0.59	0.14	----
10-176	3/8" x 3/8" x 5/8"	1.16	1.44	0.69	0.16	----
10-178	1/2" x 3/8" x 3/8"	1.16	1.12	0.59	0.18	----
10-179	1/2" x 3/8" x 1/2"	1.16	1.09	0.59	0.18	----
10-180	1/2" x 1/2" x 1/4"	1.16	0.97	0.59	0.18	----
10-181	1/2" x 1/2" x 3/8"	1.16	1.12	0.59	0.19	----
10-182	1/2" x 1/2" x 5/8"	1.28	1.41	0.69	0.28	----
10-187	5/8" x 1/2" x 5/8"	1.44	1.33	0.69	0.27	----
10-188	5/8" x 5/8" x 3/8"	1.38	1.16	0.69	0.30	----
10-189	5/8" x 5/8" x 1/2"	1.38	1.28	0.69	0.28	----
10-197	3/4" x 3/4" x 5/8"	1.66	1.50	0.88	0.36	----

144F TR2 659F 684F 44R

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

MALE BRANCH TEE
SAE# 010425



Forged Tee

Part #	Male Flare x Male NPT (1&2)x3	A	B	Body Size	Approx. Wt. Lbs.	List Price
10-203	3/16" x 1/8"	0.75	0.75	0.36	0.10	----
10-204	1/4" x 1/8"	0.78	0.75	0.36	0.05	----
10-205	1/4" x 1/4"	0.88	0.88	0.44	0.08	----
10-206	1/4" x 3/8"	0.92	1.00	0.47	0.10	----
10-207	5/16" x 1/8"	0.89	0.78	0.44	0.08	----
10-208	5/16" x 1/4"	0.94	0.94	0.44	0.08	----
10-209	3/8" x 1/8"	1.00	0.91	0.44	0.14	----
10-210	3/8" x 1/4"	1.00	0.94	0.44	0.12	----
10-211 **	3/8" x 3/8"	1.00	1.00	0.47	0.13	----
10-212 **	3/8" x 1/2"	1.12	1.22	0.69	0.22	----
10-213	1/2" x 1/4"	1.16	1.00	0.59	0.20	----
10-214	1/2" x 3/8"	1.16	1.14	0.59	0.19	----
10-215	1/2" x 1/2"	1.22	1.22	0.69	0.24	----
10-216	1/2" x 3/4"	1.38	1.41	0.88	0.22	----
10-217	5/8" x 3/8"	1.38	1.25	0.69	0.24	----
10-218	5/8" x 1/2"	1.41	1.31	0.69	0.29	----
10-219	5/8" x 3/4"	1.41	1.41	0.88	0.36	----
10-220	3/4" x 1/2"	1.63	1.59	0.88	0.49	----
10-221	3/4" x 3/4"	1.63	1.44	0.88	0.48	----

** Available in Stainless Steel. Add SS to the part#

T1 145F 45

FEMALE ADAPTER
SAE# 010103



Part #	Male Flare x Female NPTF	A	Hex	Approx. Wt. Lbs.	List Price
10-227	3/16" x 1/8"	0.97	0.56	0.03	----
10-228L	1/4" x 1/8"	1.03	0.56	0.03	----
10-228	1/4" x 1/8"	1.03	0.56	0.04	----
10-229L	1/4" x 1/4"	1.06	0.68	0.06	----
10-229	1/4" x 1/4"	1.23	0.68	0.07	----
10-230	1/4" x 3/8"	1.18	0.81	0.08	----
10-231	1/4" x 1/2"	1.31	0.94	0.06	----
10-232	5/16" x 1/8"	1.06	0.56	0.05	----
10-233	5/16" x 1/4"	1.28	0.68	0.08	----
10-234	3/8" x 1/8"	1.09	0.62	0.08	----
10-235L	3/8" x 1/4"	1.25	0.68	0.08	----
10-235	3/8" x 1/4"	1.31	0.81	0.08	----
10-236L	3/8" x 3/8"	1.25	0.81	0.08	----
10-236	3/8" x 3/8"	1.25	0.81	0.10	----
10-237L	3/8" x 1/2"	1.31	0.94	0.08	----
10-237	3/8" x 1/2"	1.60	1.00	0.16	----
10-238	3/8" x 3/4"	1.41	1.18	0.11	----
10-239	1/2" x 1/4"	1.37	0.75	0.10	----
10-240L	1/2" x 3/8"	1.38	0.81	0.12	----
10-240	1/2" x 3/8"	1.50	0.81	0.14	----
10-241L	1/2" x 1/2"	1.42	0.94	0.10	----
10-241	1/2" x 1/2"	1.75	1.00	0.12	----
10-242L	1/2" x 3/4"	1.40	1.10	0.16	----
10-242	1/2" x 3/4"	1.60	1.12	0.16	----
10-243	5/8" x 3/8"	1.24	0.87	0.12	----
10-244L	5/8" x 1/2"	1.51	0.86	0.15	----
10-244	5/8" x 1/2"	1.62	0.94	0.12	----
10-245	5/8" x 3/4"	1.65	1.12	0.17	----
10-246	3/4" x 1/2"	1.74	1.18	0.32	----
10-247	3/4" x 3/4"	1.75	1.18	0.22	----
10-248	7/8" x 3/4"	1.94	1.31	0.26	----

46 U3

"L" means light pattern.

-These fittings are completely interchangeable with full pattern fittings, but have been modified in some way. This modification is usually in the length of the pipe threads. Used in plumbing and light industrial applications.

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

SAE 45° FLARE

MALE ADAPTER



SAE# 010102

Part #	Male Flare x Male NPTF	A	Hex	Approx. Wt. Lbs.	List Price
10-253	1/8” x 1/8”	0.92	0.43	0.02	----
10-254	3/16” x 1/8”	1.00	0.43	0.03	----
10-255L	1/4” x 1/8”	1.06	0.43	0.03	----
10-255 *	1/4” x 1/8”	1.06	0.43	0.04	----
NEW 10-255EH	1/4" x 1/8"	1.06	0.44	0.03	
10-256L	1/4” x 1/4”	1.15	0.56	0.03	----
10-256 *	1/4” x 1/4”	1.25	0.56	0.04	----
10-257 *	1/4” x 3/8”	1.31	0.68	0.06	----
10-258	1/4” x 1/2”	1.44	0.87	0.11	----
10-259L	5/16” x 1/8”	1.15	0.50	0.04	----
10-259	5/16” x 1/8”	1.16	0.50	0.04	----
10-260L	5/16” x 1/4”	1.31	0.56	0.06	----
10-260	5/16” x 1/4”	1.34	0.56	0.06	----
10-261 *	5/16” x 3/8”	1.38	0.68	0.08	----
10-262	3/8” x 1/8”	1.25	0.62	0.07	----
10-263L	3/8” x 1/4”	1.31	0.62	0.06	----
10-263 *	3/8” x 1/4”	1.44	0.62	0.08	----
10-264L	3/8” x 3/8”	1.37	0.68	0.09	----
10-264 *	3/8” x 3/8”	1.42	0.68	0.09	----
10-265L	3/8” x 1/2”	1.44	0.89	0.12	----
10-265 *	3/8” x 1/2”	1.69	0.87	0.14	----
10-266	3/8” x 3/4”	1.81	1.06	0.18	----
10-267	1/2” x 1/4”	1.60	0.75	0.11	----
10-268L	1/2” x 3/8”	1.46	0.75	0.10	----
10-268	1/2” x 3/8”	1.62	0.75	0.12	----
10-269L	1/2” x 1/2”	1.62	0.87	0.13	----
10-269	1/2” x 1/2”	1.79	0.87	0.15	----
10-270	1/2” x 3/4”	1.75	1.06	0.22	----
10-271	5/8” x 1/4”	1.81	0.87	0.14	----
10-272L	5/8” x 3/8”	1.67	0.87	0.14	----
10-272	5/8” x 3/8”	1.81	0.87	0.18	----
10-273L	5/8” x 1/2”	1.80	0.87	0.11	----
10-273	5/8” x 1/2”	2.00	0.87	0.20	----
10-274	5/8” x 3/4”	1.85	1.06	0.21	----
10-275	3/4” x 1/2”	2.19	1.06	0.28	----
10-276	3/4” x 3/4”	2.08	1.06	0.28	----
10-277	7/8” x 1/2”	2.22	1.25	0.52	----
10-278	7/8” x 3/4”	2.35	1.25	0.41	----
10-279	1” x 3/4”	2.44	1.43	0.53	----
10-280	1” x 1”	2.44	1.43	0.53	----

* Available in Stainless Steel. Add SS to the part#

U1 48

"L" means light pattern.

-These fittings are completely interchangeable with full pattern fittings, but have been modified in some way. This modification is usually in the length of the pipe threads. Used in plumbing and light industrial applications.

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

90° MALE ELBOW

SAE# 010202



Forged Elbow



Barstock Elbow

Part #	Male Flare x Male NPTF	A	B	Body Size	Approx. Wt. Lbs.	List Price
10-283	1/8" x 1/8"	0.63	0.73	0.37	0.04	----
10-283B*	1/8" x 1/8"	0.62	0.69	0.43	0.04	----
10-284	3/16" x 1/8"	0.75	0.75	0.38	0.04	----
10-284B*	3/16" x 1/8"	0.75	0.75	0.43	0.06	----
10-285	3/16" x 1/4"	0.81	0.88	0.44	0.08	----
10-286	1/4" x 1/8"	0.84	0.78	0.38	0.04	----
10-286L	1/4" x 1/8"	0.96	0.80	0.37	0.04	----
10-286B*	1/4" x 1/8"	0.81	0.78	0.47	0.05	----
10-287 **	1/4" x 1/4"	0.81	0.88	0.44	0.05	----
10-287B*	1/4" x 1/4"	0.91	0.93	0.59	0.08	----
10-288 **	1/4" x 3/8"	0.91	0.91	0.47	0.08	----
10-289	1/4" x 1/2"	1.03	1.09	0.59	0.10	----
10-290	5/16" x 1/8"	0.91	0.88	0.44	0.06	----
10-290B*	5/16" x 1/8"	0.91	0.78	0.52	0.06	----
10-291	5/16" x 1/4"	0.98	0.96	0.44	0.08	----
10-291B*	5/16" x 1/4"	0.95	0.92	0.62	0.08	----
10-292	5/16" x 3/8"	1.06	1.09	0.59	0.08	----
10-293	3/8" x 1/8"	1.00	0.91	0.53	0.08	----
10-293B*	3/8" x 1/8"	1.03	0.91	0.65	0.08	----
10-294	3/8" x 1/4"	1.01	0.89	0.48	0.08	----
10-294B*	3/8" x 1/4"	0.97	1.04	0.68	0.11	----
10-295 **	3/8" x 3/8"	1.00	0.88	0.47	0.10	----
10-295L	3/8" x 3/8"	0.95	0.89	0.46	0.11	----
10-295B*	3/8" x 3/8"	1.06	1.09	0.69	0.12	----
10-296 **	3/8" x 1/2"	1.10	1.09	0.59	0.12	----
10-297	3/8" x 3/4"	1.25	1.31	0.81	0.12	----
10-298	1/2" x 1/4"	1.19	1.00	0.59	0.12	----
10-298B*	1/2" x 1/4"	1.22	1.19	0.81	0.12	----
10-299	1/2" x 3/8"	1.10	1.00	0.59	0.13	----
10-299B*	1/2" x 3/8"	1.22	1.12	0.77	0.18	----
10-300	1/2" x 1/2"	1.16	1.13	0.59	0.14	----
10-300B*	1/2" x 1/2"	1.26	1.26	0.94	0.26	----
10-301	1/2" x 3/4"	1.42	1.25	0.81	0.24	----
10-311	5/8" x 1/4"	1.34	1.13	0.72	0.28	----
10-302	5/8" x 3/8"	1.35	1.22	0.72	0.20	----
10-302B*	5/8" x 3/8"	1.41	1.25	0.94	0.20	----
10-303	5/8" x 1/2"	1.35	1.22	0.72	0.20	----
10-303L	5/8" x 1/2"	1.29	1.11	0.70	0.20	----
10-303B*	5/8" x 1/2"	1.41	1.38	0.94	0.20	----
10-304	5/8" x 3/4"	1.44	1.31	0.81	0.25	----
10-305	3/4" x 1/2"	1.67	1.50	0.88	0.34	----
10-306	3/4" x 3/4"	1.67	1.63	0.88	0.30	----
10-306B*	3/4" x 3/4"	1.60	1.62	0.91	0.32	----
10-307	7/8" x 3/4"	1.75	1.68	1.00	0.44	----
10-308	1" x 3/4"	1.94	1.69	1.31	0.75	----
10-309	1" x 1"	1.94	1.75	1.25	0.78	----

* Barstock

** Available in Stainless Steel. Add SS to the part#

249F 49 E1 149F

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

90° FEMALE ELBOW

SAE# 010203



Forged Elbow

	Part #	Male Flare x Female NPTF	A	B	Body Size	Approx. Wt. Lbs.	List Price
	10-312	3/16" x 1/8"	0.81	0.44	0.56	0.05	----
	10-313	1/4" x 1/8"	0.90	0.46	0.56	0.06	----
NEW	10-313B*	1/4" x 1/8"	0.95	0.46	0.56	0.06	----
	10-314	1/4" x 1/4"	0.97	0.59	0.75	0.08	----
NEW	10-314B*	1/4" x 1/4"	0.95	0.66	0.75	0.08	----
	10-315	1/4" x 3/8"	1.03	0.57	0.81	0.09	----
	10-333	1/4" x 1/2"	1.08	0.66	1.00	0.12	----
	10-316	5/16" x 1/8"	0.94	0.88	0.45	0.08	----
NEW	10-306B*	5/16" x 1/8"	0.94	0.87	0.56	0.07	----
	10-317	5/16" x 1/4"	1.03	0.58	0.75	0.06	----
	10-318	3/8" x 1/8"	1.00	0.88	0.47	0.10	----
	10-319	3/8" x 1/4"	1.06	0.59	0.75	0.09	----
NEW	10-319B*	3/8" x 1/4"	1.15	0.73	0.68	0.14	----
	10-320	3/8" x 3/8"	1.06	0.57	0.81	0.10	----
NEW	10-320B*	3/8" x 3/8"	1.10	0.75	0.82	0.16	----
	10-321	3/8" x 1/2"	1.16	0.66	1.00	0.14	----
	10-321L	3/8" x 1/2"	1.21	0.42	0.96	0.13	----
	10-322	3/8" x 3/4"	1.28	0.72	1.25	0.12	----
	10-323	1/2" x 1/4"	1.25	0.70	0.88	0.13	----
	10-324	1/2" x 3/8"	1.25	0.70	0.88	0.12	----
NEW	10-324B*	1/2" x 3/8"	1.26	0.75	0.88	0.16	----
	10-325	1/2" x 1/2"	1.29	0.72	1.00	0.18	----
	10-325L	1/2" x 1/2"	1.24	0.71	0.98	0.17	----
	10-326	1/2" x 3/4"	1.41	0.72	1.25	0.20	----
	10-327	5/8" x 3/8"	1.35	1.22	0.72	0.22	----
	10-328	5/8" x 1/2"	1.38	0.75	1.00	0.20	----
	10-329	5/8" x 3/4"	1.50	0.76	1.25	0.28	----
	10-330	3/4" x 1/2"	1.63	1.06	1.06	0.42	----
	10-331	3/4" x 3/4"	1.88	1.06	1.31	0.40	----

* Barstock

E3 50 150F

FORGED MALE RUN TEE



	Part #	Male Flare x Male NPTF (1&3) x 2	A	B	C	Body Size	Approx. Wt. Lbs.	List Price
	10-361	3/16" x 5/16" x 1/8"	0.87	0.78	0.97	0.44	0.08	----
	10-343	3/16" x 1/8"	0.75	0.75	0.75	0.37	0.05	----
	10-344	1/4" x 1/8"	0.78	0.75	0.78	0.37	0.06	----
NEW	10-344B*	1/4" x 1/8"	0.90	0.76	0.86	0.37	0.07	----
	10-345	1/4" x 1/4"	0.88	0.88	0.88	0.44	0.08	----
	10-347	5/16" x 1/8"	0.88	0.80	0.88	0.44	0.08	----
	10-348	5/16" x 1/4"	0.94	0.94	0.94	0.44	0.08	----
	10-350	3/8" x 1/4"	1.00	0.94	1.00	0.44	0.12	----
	10-351	3/8" x 3/8"	1.00	1.00	1.00	0.47	0.10	----
	10-340	3/8" x 1/2" x 3/8"	1.09	1.09	1.16	0.59	0.18	----
	10-352	3/8" x 1/2"	1.12	1.22	1.12	0.69	0.12	----
	10-353	1/2" x 3/8" x 1/2"	1.22	1.22	1.15	0.69	0.22	----
	10-354	1/2" x 3/8"	1.16	1.09	1.16	0.59	0.18	----
	10-355	1/2" x 1/2"	1.22	1.22	1.22	0.69	0.22	----
	10-357	5/8" x 1/2"	1.41	1.31	1.41	0.69	0.28	----
	10-359	3/4" x 1/2"	1.63	1.59	1.63	0.88	0.48	----
	10-360	3/4" x 3/4"	1.62	1.44	1.62	0.88	0.48	----

* Barstock

T3 151F 51

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

FORGED FLARE CROSS

SAE# 010501



Part #	Thread Size UNF	A	Body Size	Approx. Wt. Lbs.	List Price
10-373	1/4”	0.88	0.44	0.10	----
10-374	5/16”	0.92	0.44	0.10	----
10-375	3/8”	1.00	0.44	0.16	----
10-376	1/2”	1.16	0.59	0.24	----

455 C1 147F 52

FORGED ADAPTER TEE / SERVICE TEE



Part #	Size 1 x 2 x 3	A	B	C	Body Size	Approx. Wt. Lbs.	List Price
10-382	1/8” x 1/8” x 1/4”	0.72	0.53	0.80	0.47	0.08	----
10-383	1/4” x 1/4” x 1/4”	0.88	1.00	0.91	0.47	0.11	----

T17 53

FORGED 90° FLARE ELBOW



	Part #	Thread Size UNF	A	Approx. Wt. Lbs.	List Price
	10-404	1/8”	0.64	0.04	----
	10-405	3/16”	0.75	0.06	----
	10-406	1/4”	0.81	0.08	----
NEW	10-406B*	1/4"	0.89	0.04	----
	10-407	5/16”	0.91	0.10	----
	10-408	3/8”	1.00	0.10	----
	10-409	1/2”	1.16	0.14	----
NEW	10-409B*	1/2"	1.23	0.22	----
	10-410	5/8”	1.41	0.22	----
	10-411	3/4”	1.66	0.68	----
	10-412	7/8”	1.81	0.82	----

* Barstock

E2 155F

FORGED REDUCING ELBOW



Part #	Male Flare x Male Flare	A	B	Body Size	Approx. Wt. Lbs.	List Price
10-416	3/8” x 1/4”	1.00	0.88	0.47	0.08	----
10-419	1/2” x 3/8”	1.19	1.02	0.59	0.14	----
10-421	5/8” x 1/2”	1.34	1.23	0.72	0.21	----

ER2 657F 55R

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

SAE 45° FLARE — BRASS FITTINGS

45° ELBOW



Forged



Barstock

SAE# 010302

Part #	Male Flare x Male NPTF	A	B	Body Size	Approx. Wt. Lbs.	List Price
10-448	1/4" x 1/8"	0.67	0.64	0.41	0.04	----
10-448B*	1/4" x 1/8"	0.67	0.64	0.44	0.04	----
10-449	1/4" x 1/4"	0.75	0.86	0.53	0.07	----
10-450	5/16" x 1/8"	0.78	0.64	0.53	0.06	----
10-451	5/16" x 1/4"	0.81	0.86	0.53	0.07	----
10-452	3/8" x 1/4"	0.91	0.86	0.53	0.09	----
10-452B*	3/8" x 1/4"	0.89	0.86	0.64	0.12	----
10-453	3/8" x 3/8"	0.93	0.94	0.59	0.11	----
10-454	3/8" x 1/2"	0.99	1.17	0.75	0.19	----
10-455	1/2" x 3/8"	1.07	0.88	0.59	0.12	----
10-455B*	1/2" x 3/8"	1.06	0.94	0.76	0.18	----
10-456	1/2" x 1/2"	1.12	1.18	0.75	0.20	----
10-460	5/8" x 3/8"	1.13	0.95	0.81	0.22	----
10-457	5/8" x 1/2"	1.12	1.17	0.78	0.18	----
10-458	3/4" x 1/2"	1.28	1.16	0.88	0.26	----
10-459	3/4" x 3/4"	1.41	1.20	0.88	0.31	----

* Barstock

E145 54 159F 654F 59FF 254 47 4945

FEMALE 45° FLARE FITTINGS

UNION



- Use with Copper Gasket

SAE# 010107

	Part #	Female Flare x Female Flare	A	Hex	Approx. Wt. Lbs.	List Price
	10-135	1/4"	1.00	0.62	0.06	----
	10-136	3/8"	1.25	0.81	0.14	----
	10-137	1/2"	1.43	0.94	0.18	----
NEW	10-138	5/8"	1.69	1.07	0.24	----
NEW	10-139	3/4"	2.00	1.31	0.42	----

2310 U4 660HD 32

FEMALE FLARE ADAPTER



SAE# 010106

Part #	Female Flare x Male NPTF	A	Hex	Approx. Wt. Lbs.	List Price
10-440	1/4" x 1/8"	0.91	0.62	0.05	----
10-441	1/4" x 1/4"	1.01	0.62	0.06	----
10-442	3/8" x 1/4"	1.28	0.81	0.10	----
10-443	1/2" x 3/8"	1.36	0.94	0.14	----
10-444	1/2" x 1/2"	1.46	0.94	0.14	----

U5 664FHD 33 48-FF

FLARE REDUCER

SAE# 010105



Part #	Male Flare x Female Flare	A	Hex	Approx. Wt. Lbs.	List Price
10-462	1/4" x 3/8"	1.22	0.81	0.10	----
10-461	1/4" x 1/2"	1.36	0.94	0.14	----
10-463 *	3/8" x 1/4"	1.12	0.62	0.06	----
10-464	3/8" x 1/2"	1.44	0.94	0.14	----
10-473	3/8" x 5/8"	1.63	1.12	0.16	----
10-467	1/2" x 3/8"	1.41	0.81	0.13	----
10-468	1/2" x 5/8"	1.68	1.06	0.20	----
10-469	5/8" x 1/2"	1.63	1.00	0.17	----
10-470	5/8" x 3/4"	1.97	1.31	0.31	----
10-471	3/4" x 5/8"	1.75	1.18	0.32	----

* Available in Stainless Steel. Add SS to the part#

UR3 661FHD 227 46-FF

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

BRASS FLARE SWIVEL FITTINGS

FORGED SWIVEL
SAE# 010108



Part #	Female Flare UNF	A	Hex	Approx. Wt. Lbs.	List Price
10-481	1/4”	0.59	0.62	0.04	----
10-482	5/16”	0.62	0.68	0.06	----
10-483	3/8”	0.69	0.81	0.10	----
10-483L	3/8"	0.63	0.80		----
10-484	1/2”	0.81	0.94	0.16	----
10-484L	1/2"	0.82	0.92		----
10-485	5/8”	0.94	1.06	0.24	----
10-486	3/4”	1.12	1.31	0.34	----

1350 US4 14FSV 34

REDUCING SWIVELS



Part #	Female Flare UNF	A	B	Hex 1	Hex 2	Approx. Wt. Lbs.	List Price
10-487	3/8” x 1/4”	0.72	0.60	0.81	0.62	0.08	----
10-488	1/2” x 3/8”	0.84	0.70	0.94	0.81	0.12	----
10-489	5/8” x 1/2”	0.98	0.82	1.03	0.94	0.22	----

FORGED SWIVEL ELBOWS



Part #	Male Flare x Female Flare	A	B	Hex	Approx. Wt. Lbs.	List Price
10-493	1/4”	0.93	0.86	.563	0.12	----
10-494	3/8”	1.13	1.1	.75	0.20	----
10-495	1/2"	1.29	1.20	.88	0.25	----
10-496	5/8"	1.50	1.30	1.00	0.37	----
10-497	3/4"	1.83	1.60	1.25	0.54	----

ES4

FLARE SWEAT FITTINGS

NEW

Part #	Flare x Sweat	List Price
10-600	1/4" x 1/4"	----
10-602	1/4" x 3/8"	----
10-620	3/8" x 1/4"	----
10-612	3/8" x 3/8"	----
10-613	3/8" x 1/2"	----
10-621	1/2" x 1/2"	----
10-611	1/2" x 5/8"	----
10-614	5/8" x 5/8"	----
10-622	5/8" x 7/8"	----
10-615	3/4" x 3/4"	----
10-616	3/4" x 7/8"	----
10-617	7/8" x 7/8	----
10-618	1" x 1-1/8"	----
10-619	1-1/8" x 1-1/8"	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

SPACE HEATER/ GAS RANGE FITTINGS | BRASS FITTINGS

SPACE HEATER FITTINGS

9/16-24 FINE THREAD FLARE

NUT

#M-82SH

Part #	Size	
14-001	3/8	----

MALE ADAPTER

#M-83SH

Part #	Size	
14-016	3/8 x 3/8	----
14-017	3/8 x 1/2	----

FEMALE ADAPTER

#M-80SH

Part #	Size	
14-018	3/8 x 3/8	----
14-025	3/8 x 1/2	----

UNION

Part #	Size	
14-011	3/8	----

BRASS GAS RANGE FITTINGS

BRASS MALE ADAPTERS

	Part #	Male Flare x Male NPTF	
NEW	35-130	3/8" x 3/8"(1/8 Tap)	----
NEW	35-133	3/8" x 3/8"(1/4 Tap)	----
NEW	35-131	3/8" x 1/2"(3/8 Tap)	----
	35-132	1/2” x 1/2” (3/8” FIP TAP)	----
	35-134	15/16” x 1/2”	----
	35-135	15/16" x 3/4" (1/2" FIP TAP)	----

BRASS FEMALE ADAPTERS

15/16-16 FLARE THREAD

Part #	Flare x FIP	
35-136	15/16" x 1/2"	----
35-142	15/16" x 3/4"	----

CAP

Part #	Size	
35-186	15/16"	----

DRUM ADAPTERS

- Straight Thread

SAE# 010165

Part #	Male Flare x FIP	
50-011	1/4” x 1/2”	----
50-001	1/4” x 3/4”	----

RD IF K1

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

TEE CONNECTION

Part #	Pipe Size	
34-001	1/4" Inverted flare x 1/4" MPT	----

41-1-390-0014 2000

TAILPIECE WITH FLATS

1/4 NPT

Part #	Description	
34-011	2.34 w/ wrench Flats	----
34-012	2.13 w/ Hex	----

1001AUL 21605 M-2001-A 2002A 2001AHN

STANDARD NUT

7/8" Hex

Part #	Pipe Size	
34-016	.880-14 LH	----

2001B

TAILPIECE & NUT ASSEMBLY

Part #	Pipe Size	
34-022	1/4	----

2002AB

POL CAP

Part #	Pipe Size	
34-031	.880-14LH	----

ME1699 POL2004 1004A M-2004

POL PLUG WITH CHAIN

Part #	Description	
34-141	POL PLUG WITH CHAIN	----

ME1691-1

SINGLE PIECE POL ADPATER

Part #	Description	
34-130	MALE POL X 1/4 FPT	----
34-131	MALE POL X 1/2 FPT	----

ME351 ME357

ADAPTERS

Part #	Pipe Size	
34-041	3/8 Flare x .880-14LH	----
34-046	1/2 Flare x .880-14LH	----
34-051	5/8 Flare x .880-14LH	----

ME3510 2906E 2007

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

TAILPIECE ASSEMBLY W/HEX HEAD NUT & STEM

NEW

Part #	Length	
34-080	1/4 NPT X POL 2 LONG HARD NOSE 2 OAL	----
34-082	MALE POL X 3/8 NPT	----

2906D ME352

NEW

Part #	Length	
34-088	MPOL HARD NOSE 9/16-18 FE LH THREAD	----

ME1650

NEW

Part #	Length	
34-084	MPOL X 1/4 HOSE BARB 7/8 HEX	----

ME5930 970JR

SOFT NOSE TAILPIECE ASSEMBLY

NEW

Part #	Length	
34-060	1/4 NPT X POL 2.1 LONG #60 ORIFICE	----
34-061	1/4 MPT X POL SOFT NOSE 2-1/2	----
34-062	1/4 NPT POL SOFT NOSE #60 ORIFICE 2.3 LONG	----
34-063	POL X 9/16-18 LH TAILPIECE SOFT NOSE	----
34-064	1/4 NPT X POL SOFT NOSE 2 3/8 LONG	----

ME1638 2003-T-GH-60 2002 2018-L 2003-T 970S

HAND WHEEL POL ADAPTERS

NEW



Part #	Length	
34-065	MPOL SOFT NOSE X 1/4 HOSE BARB BR.WHEEL	----

ME1656AR

NEW

Part #	Length	
34-072	1/4 MPT POL SOFT NOSE W/PLASTIC WHEEL	----

ME1654

NEW

Part #	Length	
34-073	1/4 MPT POL SOFT NOSE WITH BRASS WHEEL	----

ME1654AR

NEW

Part #	Length	
34-074	MPOL SOFT NOSE X 1/4 HB W/PLASTIC WHEEL	----

ME1656

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

PROPANE MOTOR FUEL FILL ADAPTER

NEW

• Allows a standard POL fitting to be adapted to fill an engine fuel tank.

Part #	Length	
34-079	FE POL X 1 3/4 ACME FUEL FILL ADPT	----

ME458 2017

FEMALE POL X MIP ADAPTER

NEW

Part #	Length	
34-111	1/4 MPT X FE POL ADAPTER	----
34-112	3/8 MPT X FE POL ADAPTER	----
34-113	1/2 MPT X FE POL ADAPTER	----
34-114	3/4 MPT X FE POL ADAPTER	----

2011-B ME285 2011-D 2011-E

FEMALE FPT X FEMALE POL ADAPTER

NEW

Part #	Length	
34-120	1/4 FPT X FE POL	----
34-121	3/8 FPT X FE POL	----
34-122	1/2 FPT X FE POL	----
34-123	3/4 FPT X FE POL	----

2016-B ME302 2016-D ME304

POL O-RING ONLY

NEW

Part #	Length	
34-143	POL O-RING ONLY	----

C5-OR-POL 568-110-01

POL PLASTIC DUST PLUG

NEW

Part #	Length	
34-160	POL PLASTIC DUST PLUG	----

ME970P

APPLIANCE TEE

NEW

• Tap & Add

Part #	Length	
34-170	M.POLXF.POL W/1-20M CYL AND 1/4 INV FLAR	----

2090

NEW

• Add an appliance

Part #	Length	
34-172	M.POLXF. POL W/1-20 MALE CYLINDER THREAD	----

2012

NEW

• With QCC1 connection

Part #	Length	
34-174	QCC1 X F. POL W/1-20 MALE CYLINDER THD	----

2013

DUAL APPLIANCE TEE

NEW

Part #	Length	
34-176	M.POL X (2) OF 1-20 MALE CYLINDER THREAD	----

2099

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

JIC 37° FLARE STRAIGHTS

STRAIGHT TUBE UNION

Part #	Tube OD	Tube Thread	L	Hex	Working Pressure	
28-966	1/4	7/16-20	1.35	0.49	3250 psi	----
28-969	3/8	9/16-18	1.41	0.63	3250 psi	----
28-970	1/2	3/4-16	1.62	0.81	3250 psi	----
28-971	3/4	1-1/16-12	2.14	1.13	3250 psi	----
28-972	1"	1-5/16-12	2.25	1.38	2600 psi	----

SBC 132403 HTXB

FEMALE STRAIGHT ADAPTER

Part #	Tube OD	Pipe	Tube Thread	L	Hex	Working Pressure	
28-957	1/4	1/8-27	7/16-20	1.19	0.56	3250 psi	----
28-958	1/4	1/4-18	7/16-20	1.40	0.75	3250 psi	----
28-959	3/8	1/4-18	9/16-18	1.40	0.75	3250 psi	----
28-960	3/8	3/8-18	9/16-18	1.40	0.88	3250 psi	----
28-961	1/2	3/8-18	3/4-16	1.56	0.88	3250 psi	----
28-962	1/2	1/2-14	3/4-16	1.79	1.13	3250 psi	----
28-963	5/8	1/2-14	7/8-14	1.87	1.13	3250 psi	----
28-964	3/4	3/4-1/4	1-1/16-12	2.06	1.38	2600 psi	----

STRAIGHT

	Part #	Tube OD	A NPTF	Tube Thread	L	Hex	Working Pressure	
	28-701	1/4	1/8-27	7/16-20	1.22	0.45	3250 psi	----
	28-702	1/4	1/4-18	7/16-20	1.37	0.56	3250 psi	----
	28-703	1/4	3/8-18	7/16-20	1.42	0.75	3250 psi	----
NEW	28-704	5/16	1/8-27	1/2-20	1.41	0.56	3250 psi	----
	28-705	5/16	1/4-18	1/2-20	1.42	0.56	3250 psi	----
	28-706	3/8	1/8-27	9/16-18	1.24	0.63	3250 psi	----
	28-707	3/8	1/4-18	9/16-18	1.43	0.63	3250 psi	----
	28-708	3/8	3/8-18	9/16-18	1.38	0.75	3250 psi	----
	28-709	3/8	1/2-14	9/16-18	1.69	0.88	3250 psi	----
	28-710	1/2	1/4-18	3/4-16	1.53	0.81	3250 psi	----
	28-711	1/2	3/8-18	3/4-16	1.53	0.81	3250 psi	----
	28-712	1/2	1/2-14	3/4-16	1.79	0.88	3250 psi	----
	28-713	1/2	3/4-14	3/4-16	1.85	1.13	2600 psi	----
NEW	28-714	5/8	3/8	7/8-14	1.84	0.94	3250 psi	----
	28-715	5/8	1/2-14	7/8-14	1.89	0.94	3250 psi	----
	28-716	5/8	3/4-14	7/8-14	1.95	1.13	2600 psi	----
	28-748	3/4	1/2-14	1 1/16-12	2.06	1.13	2925 psi	----
	28-717	3/4	3/4-14	1 1/16-12	2.06	1.13	2600 psi	----
	28-749	3/4	1-11 1/2	1 1/16-12	2.25	1.38	1950 psi	----
	28-719	1	3/4-14	1 5/16-12	2.06	1.13	2275 psi	----
	28-718	1	1-11 1/2	1 5/16-12	2.3	1.38	1950 psi	----

B2404 SB FTXB

STRAIGHT SWIVEL ADAPTER

Part #	Tube OD	A NPTF	Tube Thread	L	Hex	Working Pressure	
28-752	1/4	1/4-18	7/16-20	1.389	.563	3250 psi	----
28-753	3/8	1/4-18	9/16-18	1.6	.563	3250 psi	----
28-754	3/8	3/8-18	9/16-18	1.574	.690	2925 psi	----
28-756	1/2	1/2-14	3/4-16	1.706	.875	2600 psi	----

B6505 SJS

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

90° FORGED ELBOW



• Swivel available

Part #	Tube OD	Tube Thread	A NPTF	M	N	Y	Working Pressure	
28-760F	1/4	7/16-20	1/8-27	0.89	0.78	0.5	2160 psi	----
28-762F	1/4	7/16-20	1/4-18	1.05	1.03	0.53	1846 psi	----
28-766F	5/16	1/2-20	1/4-18	1.10	1.10	0.55	3905 psi	----
28-768F	3/8	9/16-18	1/8-27	1.06	1.00	0.56	3128 psi	----
28-770F	3/8	9/16-18	1/4-18	1.06	1.09	0.54	1564 psi	----
28-772F	3/8	9/16-18	3/8-18	1.15	1.22	0.74	1464 psi	----
28-773F	3/8	9/16-18	1/2-14	1.22	1.47	0.90	1265 psi	----
28-774F	1/2	3/4-16	3/8-18	1.25	1.22	0.81	1467 psi	----
28-777F	1/2	3/4-16	1/2-14	1.31	1.47	0.90	1265 psi	----
28-778F	1/2	3/4-16	3/4-14	1.4	1.59	0.89	2061 psi	----
28-780F	5/8	7/8-14	1/2-14	1.45	1.47	0.88	1265 psi	----
28-781F	3/4	1 1/16-12	1/2-14	1.66	1.56	1.08	1265 psi	----
28-783F	3/4	1 1/16-12	3/4-14	1.66	1.59	1.06	1084 psi	----
28-784F	1	1 5/16-12	3/4-14	1.88	1.77	1.32	1802 psi	----
28-786F	1	1 5/16-12	1-11 1/2	1.81	1.97	1.3	2361 psi	----

DL3B2 3F69CL GGL6A1 F23L2 EE48D3 EE46B2 FF45A2 F48C3 FF22C3 D49B1 D25B1 3F47C1

FEMALE ELBOW FORGED BODY



Part #	Tube OD	Tube Thread	A NPTF	M	N	Working Pressure	
28-973	1/4	7/16-20	1/8-27	1.08	0.66	2797 psi	----
28-974	1/4	7/16-20	1/4-18	1.25	0.55	3066 psi	----
28-975	3/8	9/16-18	1/4-18	1.23	0.88	2842 psi	----

B2502 EBF DTXB

45° FORGED ELBOW



• Swivel available

Part #	Tube OD	Tube Thread	A NPTF	M	N	Y	Working Pressure	
28-722F	1/4	7/16-20	1/8-27	0.72	0.64	0.5	4367 psi	----
28-724F	1/4	7/16-20	1/4-18	0.81	0.84	0.53	3750 psi	----
28-728F	5/16	1/2-2	1/4-18	0.88	0.86	0.54		
28-729F	3/8	9/16-18	1/8-27	0.83	0.65	0.63	3128 psi	----
28-731F	3/8	9/16-18	1/4-18	0.83	0.86	0.63	3128 psi	----
28-733F	3/8	9/16-18	3/8-18	0.91	0.95	0.81	3100 psi	----
28-734F	3/8	9/16-18	1/2-14	1.03	1.17	0.94	2826 psi	----
28-736F	1/2	3/4-16	3/8-18	0.98	0.95	0.75	2938 psi	----
28-738F	1/2	3/4-16	1/2-14	1.13	1.17	0.86	2826 psi	----
28-740F	5/8	7/8-14	1/2-14	1.13	1.08	0.88		
28-742F	3/4	1 1/16-12	3/4-14	1.28	1.2	1.13	2442 psi	----

B2503 FBC-F VTXB

Thread Chart	
Size	JIC Thread
1/8	5/16-24
3/16	3/8-24
1/4	7/16-20
5/16	1/2-20
3/8	9/16-18
1/2	3/4-16
5/8	7/8-14
3/4	1-1/16-12
1	1-5/16-12

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

INVERTED FLARE

Tube O.D.	1/8	3/16	1/4	5/16	3/8	7/16	1/2	5/8	3/4	7/8	1
Thread O.D. threads per inch	5/16-28	3/8-24	7/16-24	1/2-20	5/8-18	11/16-18	3/4-18	7/8-18	1-1/16-16	1-3/16-16	1-5/16-16

•Typical Application
Hydraulic brake, power steering, fuel lines and transmission cooler lines, LP and natural gas.

•Working Pressure Ranges
Temperature and type of tubing used are important factors. However, the following table is a good guide for proper selection. Temperature 73^{0}F with copper tubing:

PSI	Tube O.D. (in.)	Tube Wall (in.)
2800	1/8	.030
1900	3/16	.030
1400	1/4	.030
1200	5/16	.032
1000	3/8	.032
750	1/2	.032
650	5/8	.035
550	3/4	.035

•Vibration
Excellent resistance.

•Temperature Range
-65^{0}F to +250^{0}F (-53^{0}C to +121^{0}C) range at maximum operating pressures.

•Used With
Copper, brass, aluminum and steel hydraulic tubing that can be flared.

•Advantages
Very low cost and reusable. Seats and threads are internal and protected. Compact, excellent vibration life. Short nut affords very close tube bends. Steel or brass tube nut.

• Tolerance
+/- .03 on all dimensions.

•Conformance
Meets specifications and standards of ASA, ASME, SAE and MS (Military Standards).

•Assembly Instructions
1-Cut tubing to desired length. Make sure all burrs are removed and the ends are cut square.
2- Slide nut on tube. Threaded end "A" of nut must face out.
3- Flare end of tube with a 45^0 flaring tool.
a- Measure flare diameter.
b- Examine flare for excessive thin out.
c- On thin wall, welded or brazed tubing, use double flare to prevent pinch-off and cracked flares.
4- Lubricate threads and assemble to fitting body. Nut should be turned hand tight.
5- Tighten assembly with wrench until a solid feeling is encountered. From that point, apply a one-sixth turn.

Note: Do not over-torque as it may damage the fitting or split the tubing at the flare.

STANDARD METRIC THREADS

Description Tube Size	Thread O.D.	Crest (Pitch)	Thread Description
Japanese 3/16"	10mm	1.0mm	M10 x 1.0
European 3/16"	10mm	1.0mm	M10 x 1.0
GM 6mm	12mm	1.0mm	M12 x 1.0
Fuel 5/16"	14mm	1.5mm	M14 x 1.5
Fuel 3/8?	16mm	1.5mm	M16 x 1.5

Measuring Metric Threads: Measure the O.D. of the threads and the crest to crest distance (pitch) in millimeters between threads.

Actual O.D. of male inverted flare threads

5/16"-28 2800 PSI	3/8"-24 1900 PSI	7/16"-24 1400 PSI	1/2"-20 1200 PSI	5/8"-18 1000 PSI	3/4"-18 750 PSI	7/8"-18 650 PSI	1-1/16"-16 550 PSI
1/8"	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

ZINC CHROMATE STEEL NUT

SAE# 040110

	Part #	Size	Thread	A	Hex	Approx. Wt. Lbs.	
	12-001	1/8”	5/16-28	0.52	0.31	0.01	----
	12-002	3/16”	3/8-24	0.56	0.37	0.02	----
	12-018	3/16"	7/16-24	0.56	0.43	0.02	----
	12-003	1/4”	7/16-24	0.56	0.43	0.02	----
	12-004	5/16”	1/2-20	0.62	0.50	0.02	----
	12-005	3/8”	5/8-18	0.66	0.62	0.03	----
	12-000	7/16”	11/16-18	0.68	0.68	0.04	----
	12-011	3/8"	11/16-18	0.66	0.68	0.05	----
	12-006	1/2”	3/4-18	0.74	0.75	0.08	----
	12-007	5/8”	7/8-18	0.80	0.87	0.10	----
	12-008	3/4”	1-1/16-16	0.88	1.06	0.10	----
NEW	12-083	7/8"	1-3/16-16	1.07	1.19	0.14	----
NEW	12-084	1"	1-5/16-16	1.18	1.375	0.21	----

121XXX 2105 411FS 105 41W

LONG STEEL NUT



for Domestic lines

Part #	Size	A	Hex	Approx. Wt. Lbs.	
12-009	3/16”	0.84	0.37	0.02	----
12-010	1/4”	0.81	0.43	0.02	----

7896

INVERTED FLARE BRASS NUT

SAE# 040110



Part #	Size	A	Hex	Approx. Wt. Lbs.	
12-012	1/8”	0.52	0.31	0.01	----
12-013	3/16”	0.56	0.37	0.01	----
12-014	1/4”	0.56	0.43	0.02	----
12-015	5/16”	0.62	0.50	0.03	----
12-016	3/8”	0.66	0.62	0.04	----
12-017	1/2”	0.74	0.75	0.05	----

2100 41IF 100 41IB

ZINC STEEL METRIC TUBE NUTS

Part #	Tubesize	Thread	Ref#	
12-260	3/16 British	3/8-24 Bubble	---	----
12-261	3/16 European	M10 x 1.0 Bubble	276110	----
12-262	3/16 Japanese	M10 x 1.0 Inv.	121050	----
12-263	3/16 Domestic	1/2 x 20 Inv.	---	----
12-264	3/16 Domestic	9/16 - 18 Inv.	121039	----
12-265	3/16 Imported	M11 x 1.5 Bubble	276011	----
12-266	3/16 Imported	M12 x 1.0 Bubble	276012	----
12-267	3/16 Imported	M13 x 1.5 Bubble	276013	----
12-268	1/4 Domestic	9/16 x 18 Inv.	121049	----
12-269	1/4 Domestic	1/2 x 20 Inv.	121045	----
12-270	6mm Imported	M12 x 1.0 Bubble		----
12-271	6mm GM	M12 x 1.0 Bubble		----
12-272	6mm GM	M12 x 1.5 Bubble		----
12-273	6mm GM	M14 x 1.5 Bubble		----
12-274	5/16 Domestic	M14 x 1.5 Surface Seal	121069	----
12-275	3/8 Domestic	M16 x 1.5 Surface Seal	121070	----

UNION INTERNAL



SAE# 040101

	Part #	Inv. Flare X Inv. Flare	A	Hex	Approx. Wt. Lbs.	
	12-022	1/8”	0.59	0.40	0.02	----
	12-023	3/16”	0.62	0.43	0.02	----
	12-024	1/4”	0.62	0.50	0.03	----
	12-025	5/16”	0.70	0.56	0.04	----
	12-026	3/8”	0.80	0.75	0.08	----
	12-027	1/2”	0.91	0.90	0.10	----
NEW	12-028	5/8"	1.31	1.06	0.22	----

see page 72 for metric unions

302 2300 42IFHD

FEMALE ADAPTER



SAE# 040103

	Part #	Inv. Flare X Female NPTF	A	Hex	Approx. Wt. Lbs.	
NEW	12-029	1/8" x 1/8"	0.716	0.50	0.03	----
	12-032	3/16” x 1/8”	0.75	0.50	0.02	----
	12-033	1/4” x 1/8”	0.75	0.53	0.02	----
NEW	12-030	1/4" x 1/4"	1.01	0.751	0.11	----
	12-034	5/16” x 1/8”	0.78	0.59	0.04	----
	12-035	3/8” x 1/4”	1.03	0.75	0.08	----
NEW	12-031	7/16" x 1/4"	1.06	0.81	0.11	----
NEW	12-037	1/2" x 1/4"	1.09	0.90	0.12	----
	12-036	1/2” x 3/8”	1.10	0.90	0.12	----
NEW	12-039	5/8" x 1/2"	1.32	1.065	0.19	----
NEW	12-099	3/4" x 3/4"	1.50	1.25	0.36	----

46IFHD 252 46W

MALE ADAPTER



SAE# 040102

	Part #	Inv. Flare X Male NPTF	A	Hex	Approx. Wt. Lbs.	
	12-041	1/8” x 1/8”	0.63	0.40	0.02	----
	12-042	3/16” x 1/8”	0.70	0.43	0.02	----
NEW	12-053	3/16" x 1/4"	0.72	0.56	0.04	----
	12-043	1/4” x 1/8”	0.74	0.50	0.03	----
	12-044	1/4” x 1/4”	0.89	0.56	0.04	----
	12-045	5/16” x 1/8”	0.79	0.56	0.03	----
	12-046	5/16” x 1/4”	0.98	0.56	0.05	----
NEW	12-055	5/16" x 3/8"	1.01	0.75	0.07	----
	12-047	3/8” x 1/8”	0.88	0.72	0.05	----
	12-048	3/8” x 1/4”	1.02	0.75	0.06	----
	12-049	3/8” x 3/8”	1.02	0.75	0.08	----
NEW	12-104	7/16" x 1/4"	1.05	0.81	0.06	----
	12-038	1/2” x 1/4”	0.97	0.87	0.10	----
	12-050	1/2” x 3/8”	1.06	0.87	0.08	----
	12-051	1/2” x 1/2”	1.06	0.87	0.11	----
	12-052	5/8” x 1/2”	1.32	1.06	0.15	----
NEW	12-105	3/4" x 1/2"	1.38	1.25	0.18	----
	12-040	3/4” x 3/4”	1.39	1.25	0.24	----
NEW	12-107	7/8" x 3/4"	1.375	1.375	0.21	----
NEW	12-108	1" x 1"	1.62	1.50	0.37	----

2200 48IFHD 202 48W 200

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

ELBOW

SAE# 040202



	Part #	Inv. Flare X Male NPTF	A	B	Approx. Wt. Lbs.	
	12-057	1/8” x 1/8”	0.26	0.59	0.03	----
	12-058	3/16” x 1/8”	0.26	0.61	0.03	----
	12-059	1/4” x 1/8”	0.33	0.65	0.04	----
	12-054*	1/4” x 1/8”	0.33	0.65	0.04	----
	12-060	1/4” x 1/4”	0.28	0.82	0.06	----
	12-061	5/16” x 1/8”	0.47	0.68	0.05	----
	12-062	5/16” x 1/4”	0.45	0.85	0.08	----
NEW	12-082	5/16" x 3/8"	0.47	0.86	0.12	----
	12-063	3/8” x 1/8”	0.54	0.76	0.14	----
	12-064	3/8” x 1/4”	0.53	0.92	0.14	----
	12-065	3/8” x 3/8”	0.50	0.94	0.12	----
NEW	12-114	1/2" x 1/4"	0.72	1.08	0.14	----
	12-066	1/2” x 3/8”	0.59	1.03	0.16	----
	12-067	1/2” x 1/2”	0.66	1.22	0.25	----
	12-056	5/8” x 3/8”	0.67	1.09	0.20	----
	12-068	5/8” x 1/2”	0.67	1.29	0.18	----
	12-069	3/4” x 1/2”	0.80	1.39	0.42	----
	12-080	7/8” x 3/4”	0.94	1.43	0.48	----
	12-081	1” x 1”	1.02	1.69	0.60	----

*** Restricted pipe end .062**

400 2400 249IFHD 402 249IF 49W

45° ELBOW

SAE# 040302



	Part #	Inv. Flare X Male NPTF	A	B	Hex	Approx. Wt. Lbs.	
NEW	12-070	1/8" x 1/8"	0.22	0.48	0.50	0.03	----
	12-072	3/16” x 1/8”	0.25	0.55	0.53	0.02	----
	12-073	1/4” x 1/8”	0.27	0.58	0.56	0.04	----
	12-074	5/16” x 1/8”	0.36	0.56	0.62	0.06	----
	12-075	5/16” x 1/4”	0.23	0.83	0.62	0.06	----
NEW	12-115	3/8" x 1/8"	0.34	0.87	0.87	0.09	----
	12-076	3/8” x 1/4”	0.51	0.84	0.78	0.09	----
	12-077	1/2” x 3/8”	0.38	0.91	0.84	0.11	----
	12-079	5/8” x 1/2”	0.44	1.00	1.06	0.21	----

154 2352 259IFHD 352 94W

UNION TEE

SAE# 040401



Part #	Size	A	B	Approx. Wt. Lbs.	
12-085	1/8”	0.33	0.47	0.04	----
12-086	3/16”	0.39	0.55	0.04	----
12-087	1/4”	0.42	0.56	0.08	----
12-088	5/16”	0.45	0.63	0.09	----
12-089	3/8”	0.56	0.74	0.17	----
12-090	1/2”	0.67	0.88	0.24	----

244IFHD 702 441

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

STEEL PLUG

• cored



SAE# 040109

	Part # Steel	Size	A	Hex	Approx. Wt. Lbs.	
	12-091	3/16”	0.53	0.37	0.01	----
	12-092	1/4”	0.54	0.43	0.02	----
	12-093	5/16”	0.59	0.50	0.03	----
	12-094	3/8”	0.66	0.62	0.04	----
	Brass					
NEW	12-095	3/8"	0.66	0.63	0.04	----
NEW	12-096	1/2"	0.82	0.75	0.07	----
NEW	12-097	5/8"	0.90	0.87	0.10	----
NEW	12-098	3/4"	0.95	1.07	0.17	----

106 41IP 131 2131

MALE BRANCH TEE



SAE# 040425

Part #	Inv. Flare x Male NPTF (1&2)x3	A	B	Approx. Wt. Lbs.	
12-100	3/16” x 1/8”	0.41	0.60	0.04	----
12-101	1/4” x 1/8”	0.42	0.64	0.06	----
12-102	5/16” x 1/8”	0.47	0.68	0.07	----
12-103	3/8” x 1/4”	0.58	0.93	0.15	----

145 245IFHD 602 2600 600

FEMALE ELBOW



SAE# 040203

Part #	Inv. Flare x Female NPTF	A	Approx. Wt. Lbs.	
12-110	1/4” x 1/8”	0.55	0.07	----
12-111	5/16” x 1/8”	0.51	0.08	----
12-112	3/8” x 1/4”	0.68	0.10	----

450

MALE RUN TEE



SAE# 040424

Part #	Inv. Flare x Male NPTF (1&3)x2	A	B	C	Approx. Wt. Lbs.	
12-118	3/16” x 1/8”	0.53	0.72	0.39	0.06	----
12-119	1/4” x 1/8”	0.56	0.75	0.42	0.08	----
12-120	5/16” x 1/8”	0.62	0.85	0.45	0.10	----
12-121	3/8” x 1/4”	0.75	1.08	0.56	0.14	----

251IFHD 752 550 151

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

FEMALE BRANCH TEE

SAE# 040427



Part #	Inv. Flare x Female NPTF (1&2)x3	A	B	Approx. Wt. Lbs.	
12-127	3/16" x 1/8"	0.39	0.55	0.06	----
12-129	5/16" x 1/8"	0.45	0.63	0.12	----
12-130	3/8" x 1/4"	0.56	0.74	0.17	----

252IFHD 652 136

TOWED TRAILER BRAKE TEE



Part #	A	B	C	Reference #	Approx. Wt. Lbs.	
12-147	3/16" 0.57	3/16" 0.76	3/16" 0.42	7900	0.08	----
12-145	3/16" (1/2-20) 0.68	3/16" (3/8-24) 0.94	3/16" (1/2-20) 0.47	7906	0.17	----
12-148	3/16" (9/16-18)	3/16" (3/8-24)	3/16" (9/16/18)	7933	0.10	----
12-144	3/16" (9/16-20) 0.82	3/16" (3/8-24) 0.94	3/16" (9/16-20) 0.47	7905	0.18	----
12-146	3/16" (7/16-24) 0.54	3/16" (3/8-24) 0.78	1/4" (7/16-24) 0.42	7914	0.08	----
12-150	1/4" 0.56	3/16" 0.77	1/4" 0.43	7901	0.10	----
12-149	1/4" (9/16-18) 0.81	3/16" (3/8-24) 0.93	1/4" (9/16-18) 0.50	7904	0.10	----
12-151	1/4" 0.56	1/4" 0.77	1/4" 0.43	7898	0.12	----

INVERTED FLARE AUTO FITTINGS

DUAL MASTER CYLINDER ADAPTER



Part #	Male Flare x Female Inv.	A	Hex	Reference #	Approx. Wt. Lbs.	
12-200	3/16" x 3/16"	1.00	0.50	1441	0.03	----
12-202	5/16" x 3/16"	0.96	0.68	7897	0.07	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

DUAL MASTER CYLINDER ADAPTER



*** Seals on hex face**

Part #	Male Inverted Thread	Female Inverted Thread	Ref#	
12-206	3/16(9/16-18)	3/16	7911	----
12-209	3/16(9/16-18)	3/16(1/2-20)	7913	----
12-207	3/16(9/16-20)	3/16	7910	----
12-210	3/16	1/4	7828	----
12-212	1/4	3/16	7818	----
12-214*	7/16-20	1/4	7732	----
12-211	1/4(9/16-18)	1/4	7908	----
12-215	1/4	5/16	7917	----
12-213*	5/16	3/16	7817	----
12-216	5/16	3/16	7909	----
12-208	5/16	3/16(9/16-18)	7912	----
12-218*	5/16	1/4	7727	----
12-220	5/16	1/4	7829	----
12-222*	5/16	5/16	1074	----
12-221	5/16	3/8	7915	----
12-224	3/8" NPTF	5/16	7771	----
12-217	3/8	5/16	7916	----

47W

CARBURETOR TO FUEL LINE ADAPTER - FORD



Part #	Female Tube OD x Male NPTF	A	Hex	Ref #	Approx. Wt. Lbs.	
12-230	1/4"(1/2-20) x 1/8"	1.06	0.56	1513	0.04	----

1513

RESTRICTION PIPE ADAPTER

(.0625 ORIFICE)



Part #	Size FIP x MIP	A	Hex	Ref #	Approx. Wt. Lbs.	
12-310	1/8"	0.75	0.50	1512	0.02	----

1510

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

SAE FLARE X INVERTED FLARE



Part #	SAE Flare x Inv. Flare	A	Hex	Ref #	Approx. Wt. Lbs.	
12-250	1/4" x 3/16"	1.03	0.43	1518	0.02	----
12-252	1/4" x 1/4"	1.03	0.43	1522	0.03	----
12-254	3/8" x 5/16"	1.34	0.63	1553	0.08	----
12-256	3/8" x 3/8"	1.37	0.63	1563	0.09	----
12-257	3/8" x 7/16"	1.40	0.68	1554	0.10	----

4205

METRIC HYDRAULIC BRAKE FITTINGS

METRIC ADAPTER



Part #	Bubble Male Thread	Tube O.D./ Female Thread	A	Hex	Ref #	Approx. Wt. Lbs.	
12-335	M10x1.0	3/16"(3/8-24)	1.02	0.50	1442	0.02	----
12-326	M11x1.5	3/16"(M10x1.0)	1.06	0.50	7935	0.02	----
12-327	M12x1.0	3/16"(M10x1.0)	1.02	0.53	7936	0.04	----
12-328	M16x1.5	3/16"(M10x1.0)	1.02	0.56	7937	0.06	----

ADAPTER STANDARD TO METRIC BUBBLE



Part #	Female Inv. Flare Seat	Male Metric Bubble Flare	A	Hex	Ref #	Approx. Wt. Lbs.	
12-336	3/16" (3/8-24)	11x1.5			7973		----
12-337	3/16" (3/8-24)	(3/16") (10x1.25)	1.00	0.50	7970	0.02	----
12-339	3/16" (3/8-24)	13x1.5	1.03	0.56	7972	0.04	----
12-341	3/16" (3/8-24)	12x1.0	1.02	0.53	7974	0.04	----

FEMALE X MALE ADAPTERS

Part #	Female Standard Flare Seat	Male Bubble Flare	Material	
12-330	3/8-24 (3/16)	7/16-20	Steel	----

Part #	Tube OD/ Female Thread	Inverted Male Thread	Ref #	
12-205	3/16 (3/8-24)	M10 x 1.0	1443	----

Part #	Female Standard Flare	Inverted Male Thread	Material	
12-329	3/8-24 (3/16)	M9 x 1.0	Steel	----

METRIC UNION



Part #	Size	A	Hex	Ref #	Approx. Wt. Lbs.	
12-342	British Brake Lines 3/16 (3/8-24 Bubble)	0.87	0.50	1594	0.03	----
12-343	European Brake Lines 3/16"(10.0MM)	1.04	0.56	7975	0.04	----
12-344	Japanese Brake Lines 3/16 (M10 x 1.0) Inverted	1.00	0.50	7934A	0.04	----
12-345	GM Brake Lines 6mm M12 x 1.0 Bubble	1.11	0.63		0.06	----

COMPRESSION FITTINGS

These are NOT Lead Free

See pages 164-166 for Lead Free products

Tube O.D.	1/8	3/16	1/4	5/16	3/8	7/16	1/2	5/8	3/4	7/8
Thread Size-B	5/16-24	3/8-24	7/16-24	1/2-24	9/16-24	5/8-24	11/16-20	13/16-18	1-18	1-1/8-18
Working Pressure	400	400	300	300	200	200	200	150	100	75

• Typical Application
Use with copper, aluminum and thermoplastic tubing. Not recommended for steel tubing. Manufactured for low and medium pressure tubing connection work where excessive vibration or tube movement is not involved. Not recommended for application using gaseous media.

•Pressure
See table above for working pressures at 73°F.

•Vibration
Fair resistance - use long nut when greater vibration resistance is needed.

•Temperature Range
-65°F to +250°F (-53°C to +121°C) range at maximum operating pressures. (Refer to tubing temperature range.)

•Used With
Aluminum, copper, brass and plastic tubing. Plastic tubing requires insert. Not recommended for steel tubing.

• Tolerance
+/- .02 on all dimensions. Dimension data can change without notice. Please call us when dimensions are critical.

• Conformance
Meets specifications and standards of ASA, ASME and SAE.

•Assembly Instructions
1- Cut tubing to desired length.
2- Slide nut and then sleeve on tube. Threaded end "A" of nut must face toward fitting.
3- Insert tubing into fitting body. Be sure tubing is bottomed on fitting shoulder.
4- Lubricate threads and assemble nut to fitting body.
5- Tighten nut hand tight. From that point, tighten with a wrench the number of turns indicated in the chart below.

Tube Size	Additional Turns from Hand Tight
1/8" thru 1/4"	1-1/4"
5/16"	1-3/4"
3/8" thru 1"	2-1/4"

• "L" at the end of a Part# means Light Pattern -These fittings are completely interchangeable with full pattern fittings, but have been modified in some way. This modification is usually in the length of the pipe threads. Used in plumbing and light industrial applications.

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

Actual Profile of Compression Threads

BRASS SLEEVE

• FERRULES

SAE# 060115



Part #	Size	A	B	Approx. Wt. Lbs.	
18-001	1/8”	0.19	0.19	0.01	----
18-002	3/16”	0.22	0.27	0.01	----
18-003	1/4”	0.25	0.34	0.01	----
18-004	5/16”	0.25	0.41	0.01	----
18-005	3/8”	0.25	0.47	0.02	----
18-006	7/16”	0.31	0.53	0.02	----
18-007	1/2”	0.38	0.59	0.02	----
18-008	5/8”	0.38	0.71	0.03	----
18-009	3/4”	0.44	0.87	0.03	----
18-010	7/8”	0.41	0.99	0.03	----
18-011	1"	0.55	1.16	0.03	----

60 260

BRASS NUT

SAE# 060110



Part #	Size	Thread	A	Hex	Approx. Wt. Lbs.	
18-033	1/8”	5/16-24	0.38	0.37	0.01	----
18-034	3/16”	3/8-24	0.41	0.43	0.01	----
18-035L	1/4”	7/16-24	0.44	0.50	0.02	----
18-035	1/4”	7/16-24	0.44	0.50	0.02	----
18-036	5/16”	1/2-24	0.44	0.56	0.02	----
18-037L	3/8”	9/16-24	0.47	0.62	0.04	----
18-037	3/8”	9/16-24	0.47	0.62	0.04	----
18-038	7/16”	5/8-24	0.50	0.68	0.04	----
18-039L	1/2”	11/16-20	0.56	0.75	0.04	----
18-039	1/2”	11/16-20	0.62	0.81	0.04	----
18-040L	5/8”	13/16-18	0.56	0.87	0.06	----
18-040	5/8”	13/16-18	0.62	0.94	0.06	----
18-041	3/4”	1-18	0.68	1.12	0.08	----
18-042	7/8”	1-1/8 - 18	0.62	1.25	0.10	----
18-043	1"		0.94	1.38	0.15	----

61 261

UNION

SAE# 060101BA



Part #	Size	A	Hex	Approx. Wt. Lbs.	
18-062	1/8”	0.64	0.31	0.03	----
18-063	3/16”	0.75	0.37	0.04	----
18-064L	1/4”	0.79	0.43	0.06	----
18-064	1/4”	0.81	0.43	0.06	----
18-065	5/16”	0.88	0.50	0.06	----
18-066L	3/8”	0.96	0.56	0.09	----
18-066	3/8”	0.98	0.56	0.10	----
18-067	7/16”	1.02	0.62	0.12	----
18-068L	1/2”	1.06	0.68	0.16	----
18-068	1/2”	1.25	0.68	0.16	----
18-069L	5/8”	1.43	0.81	0.24	----
18-069	5/8”	1.25	0.81	0.26	----
18-070	3/4”	1.41	1.00	0.35	----
18-071L	7/8”	1.03	1.12	0.34	----
18-071	7/8”	1.00	1.12	0.36	----
18-072	1"	1.78	1.38	0.58	----

NEW

M-62

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

REDUCING UNION



	Part #	Size	A	Hex	Approx. Wt. Lbs.	
	18-076	1/4” x 1/8”	0.73	0.44	0.04	----
	18-077	1/4” x 3/16”	0.78	0.44	0.06	----
	18-078	5/16” x 1/4”	0.81	0.50	0.06	----
	18-079	3/8” x 1/4”	0.90	0.56	0.10	----
	18-080	3/8” x 5/16”	0.94	0.56	0.10	----
	18-081	1/2” x 3/8”	1.03	0.68	0.12	----
	18-082	5/8” x 3/8”	1.03	0.81	0.15	----
NEW	18-083	5/8" x 1/2"	1.16	0.81	0.18	----
NEW	18-085	7/8" x 3/8"	1.18	1.18	0.26	----
NEW	18-086	7/8" x 1/2"	1.21	1.18	0.24	----
	18-084	7/8” x 5/8”	1.23	1.18	0.20	----

62-R

TEE

SAE# 060401



Forged



Barstock

Part #	Size	A	Body Size	Approx. Wt. Lbs.	
18-101	1/8”	0.61	0.37	0.04	----
18-101B*	1/8”	0.62	0.33	0.04	----
18-102	3/16”	0.59	0.36	0.08	----
18-102B*	3/16”	0.60	0.38	0.08	----
18-103	1/4”	0.63	0.36	0.10	----
18-103B*	1/4”	0.62	0.49	0.10	----
18-104	5/16”	0.72	0.50	0.13	----
18-104B*	5/16”	0.60	0.50	0.14	----
18-105	3/8”	0.75	0.50	0.16	----
18-105B*	3/8”	0.73	0.59	0.16	----
18-106	1/2”	0.94	0.59	0.22	----
18-106B*	1/2”	0.94	0.69	0.24	----
18-107	5/8”	1.06	0.69	0.28	----
18-108	3/4”	1.22	0.88	0.32	----
18-109	7/8”	1.25	0.94	0.34	----

* Barstock

64 **264C**

FORGED REDUCING TEE



Part #	Size 1 x 2 x 3	A	B	Body Size	Approx. Wt. Lbs.	
18-114	1/4” x 1/4” x 1/8”	0.62	0.59	0.38	0.09	----
18-110	1/4” x 1/4” x 3/8”	0.69	0.75	0.50	0.14	----
18-111	3/8” x 1/4” x 1/4”	0.75	0.69	0.50	0.12	----
18-115	3/8” x 3/8” x 1/4”	0.75	0.69	0.50	0.14	----
18-116	1/2” x 1/2” x 1/4”	0.94	0.81	0.59	0.16	----
18-117	1/2” x 1/2” x 3/8”	0.94	0.81	0.59	0.24	----
18-118	5/8” x 5/8” x 3/8”	1.06	0.94	0.69	0.28	----
18-119	5/8” x 5/8” x 1/2”	1.06	1.06	0.69	0.30	----

64-R

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

UNION ELBOW SAE# 060201



Forged Barstock

Part #	Size	A	Body Size	Approx. Wt. Lbs.	
18-122B*	1/8”	0.62	0.35	0.04	----
18-123	3/16”	0.61	0.37	0.06	----
18-124	1/4”	0.66	0.38	0.08	----
18-125	5/16”	0.69	0.47	0.09	----
18-126	3/8”	0.72	0.43	0.12	----
18-127	1/2”	0.94	0.59	0.19	----
18-128	5/8”	1.06	0.72	0.26	----
18-129	3/4”	1.19	0.94	0.48	----
18-130	7/8”	1.25	0.94	0.44	----

65 BSE2 165C 265C

REDUCING ELBOW - Forged



Part #	Size	A	B	Body Size	Approx. Wt. Lbs.	
18-135	3/8” x 1/4”	0.69	0.75	0.47	0.12	----
18-136	1/2” x 3/8”	0.88	0.94	0.59	0.15	----
18-137	5/8” x 3/8”	0.88	0.97	0.56	0.18	----
31-137	3/8" OD x 5/8" OD	Chrome Plated				----

65-R

FEMALE ADAPTER SAE# 060103



Part #	Comp. X Female NPTF	A	Hex	Approx. Wt. Lbs.	
18-142	1/8” x 1/8”	0.75	0.56	0.02	----
18-143	3/16” x 1/8”	0.78	0.56	0.04	----
18-144	3/16” x 1/4”	0.96	0.68	0.04	----
18-145L	1/4” x 1/8”	0.84	0.50	0.05	----
18-145	1/4” x 1/8”	0.78	0.56	0.05	----
18-146L	1/4” x 1/4”	0.88	0.62	0.09	----
18-146	1/4” x 1/4”	1.03	0.68	0.09	----
18-148	1/4” x 1/2”	1.02	0.87	0.12	----
18-149	5/16” x 1/8”	0.81	0.56	0.05	----
18-150	5/16” x 1/4”	0.91	0.62	0.06	----
18-152	3/8” x 1/8”	0.88	0.56	0.06	----
18-153L	3/8” x 1/4”	0.97	0.62	0.08	----
18-153	3/8” x 1/4”	1.06	0.68	0.08	----
18-154L	3/8” x 3/8”	1.03	0.75	0.08	----
18-154	3/8” x 3/8”	1.06	0.81	0.10	----
18-155	3/8” x 1/2”	1.12	1.00	0.08	----
18-156	3/8” x 3/4”	1.19	1.16	0.14	----
18-157	1/2” x 1/4”	1.09	0.68	0.10	----
18-158L	1/2” x 3/8”	0.94	0.81	0.12	----
18-158	1/2” x 3/8”	1.12	0.81	0.12	----
18-159L	1/2” x 1/2”	1.19	1.00	0.12	----
18-159	1/2” x 1/2”	1.31	1.00	0.12	----
18-160	1/2” x 3/4”	1.25	1.16	0.18	----
18-162L	5/8” x 1/2”	1.20	0.94	0.18	----
18-162	5/8” x 1/2”	1.38	1.00	0.18	----
18-163	5/8” x 3/4”	1.20	1.12	0.22	----
18-164	3/4” x 1/2”	1.25	1.06	0.26	----
18-165	3/4” x 3/4”	1.28	1.19	0.28	----
18-167	7/8” x 1/2”	1.28	1.19	0.32	----
18-166	7/8” x 3/4”	1.31	1.12	0.34	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

COMPRESSION — BRASS FITTINGS

MALE ADAPTER

SAE# 060102



	Part #	Comp. X Male NPTF	A	Hex	Approx. Wt. Lbs.	
	18-175	1/8” x 1/16”	0.78	0.37	0.02	----
	18-176	1/8” x 1/8”	0.78	0.43	0.04	----
	18-177	3/16” x 1/8”	0.84	0.43	0.04	----
	18-178	3/16” x 1/4”	0.94	0.56	0.06	----
	18-179L	1/4” x 1/8”	0.88	0.56	0.04	----
	18-179	1/4” x 1/8”	0.88	0.43	0.04	----
	18-180L	1/4” x 1/4”	0.94	0.56	0.05	----
	18-180	1/4” x 1/4”	1.06	0.56	0.06	----
	18-181	1/4” x 3/8”	1.03	0.68	0.08	----
	18-182	1/4” x 1/2”	1.09	0.81	0.10	----
	18-183	5/16” x 1/8”	0.91	0.50	0.05	----
	18-184L	5/16” x 1/4”	1.01	0.56	0.06	----
	18-184	5/16” x 1/4”	1.09	0.56	0.06	----
	18-185	5/16” x 3/8”	1.06	0.68	0.07	----
	18-186	5/16” x 1/2”	1.14	0.87	0.10	----
	18-187L	3/8” x 1/8”	0.94	0.56	0.06	----
	18-187	3/8” x 1/8”	0.97	0.56	0.06	----
	18-188L	3/8” x 1/4”	1.03	0.56	0.06	----
	18-188	3/8” x 1/4”	1.16	0.56	0.07	----
	18-189L	3/8” x 3/8”	1.09	0.68	0.08	----
	18-189	3/8” x 3/8”	1.14	0.69	0.08	----
	18-190L	3/8” x 1/2”	1.19	0.88	0.12	----
	18-190	3/8” x 1/2”	1.34	0.87	0.13	----
	18-191	3/8” x 3/4”	1.29	1.06	0.16	----
	18-192	7/16” x 1/4”	1.06	0.62	0.10	----
	18-204	7/16” x 3/8”	1.10	0.68	0.12	----
	18-193L	1/2” x 1/4”	1.09	0.69	0.11	----
	18-193	1/2” x 1/4”	1.22	0.68	0.11	----
	18-194L	1/2” x 3/8”	1.16	0.68	0.12	----
	18-194	1/2” x 3/8”	1.16	0.69	0.12	----
	18-195L	1/2” x 1/2”	1.09	0.81	0.12	----
	18-195	1/2” x 1/2”	1.41	0.87	0.19	----
	18-196	1/2” x 3/4”	1.38	1.06	0.22	----
NEW	18-216	5/8" x 1/4"	1.21	0.87	0.22	----
	18-197	5/8” x 3/8”	1.22	0.87	0.24	----
	18-198	5/8” x 1/2”	1.12	0.81	0.24	----
	18-199	5/8” x 3/4”	1.31	1.06	0.26	----
	18-200	3/4” x 1/2”	1.44	1.00	0.26	----
	18-201	3/4” x 3/4”	1.50	1.06	0.26	----
	18-202	7/8” x 1/2”	1.18	1.12	0.26	----
	18-203	7/8” x 3/4”	1.22	1.12	0.28	----
	18-205	7/8” x 1”	1.67	1.37	0.32	----
NEW	18-206	1" x 3/4"	1.95	1.37	0.44	----
NEW	18-207	1" x 1"	2.00	1.38	0.48	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

MALE ELBOW

SAE# 060202



Forged



Barstock

	Part #	Comp. X Male NPTF	A	B	Body Size	Approx. Wt. Lbs.	
NEW	18-219	1/8" x 1/16"	0.59	0.73	0.34	0.02	----
	18-220	1/8” x 1/8”	0.59	0.75	0.34	0.02	----
	18-220B*	1/8” x 1/8”	0.60	0.67	0.43	0.04	----
	18-221	3/16” x 1/8”	0.63	0.72	0.34	0.04	----
	18-221B*	3/16” x 1/8”	0.62	0.69	0.43	0.06	----
	18-223	3/16” x 1/4”	0.60	0.81	0.39	0.05	----
NEW	18-223B*	3/16" x 1/4"	0.65	0.85	0.41	0.08	----
	18-224	1/4” x 1/8”	0.60	0.75	0.37	0.06	----
	18-224B*	1/4” x 1/8”	0.62	0.75	0.43	0.06	----
	18-225	1/4” x 1/4”	0.65	0.94	0.36	0.08	----
	18-225B*	1/4” x 1/4”	0.61	0.81	0.56	0.08	----
	18-226	1/4” x 3/8”	0.75	0.91	0.47	0.08	----
	18-227	1/4” x 1/2”	0.81	1.13	0.56	0.12	----
	18-228	5/16” x 1/8”	0.66	0.75	0.47	0.06	----
	18-228B*	5/16” x 1/8”	0.62	0.75	0.42	0.06	----
	18-229	5/16” x 1/4”	0.66	0.81	0.47	0.07	----
	18-229B*	5/16” x 1/4”	0.69	0.84	0.57	0.08	----
	18-230	5/16” x 3/8”	0.75	0.91	0.47	0.10	----
	18-231	5/16” x 1/2”	0.84	1.12	0.56	0.12	----
	18-232	3/8” x 1/8”	0.72	0.66	0.39	0.06	----
	18-232B*	3/8” x 1/8”	0.69	0.69	0.57	0.06	----
	18-233	3/8” x 1/4”	0.75	0.82	0.46	0.08	----
	18-233B*	3/8” x 1/4”	0.75	0.94	0.57	0.08	----
	18-234	3/8” x 3/8”	0.81	0.94	0.46	0.10	----
	18-234B*	3/8” x 3/8”	0.71	0.83	0.69	0.10	----
	18-235	3/8” x 1/2”	0.87	1.12	0.56	0.14	----
	18-235B*	3/8” x 1/2”	0.88	1.16	0.94	0.14	----
	18-248	3/8” x 3/4”	1.03	1.19	0.81	0.18	----
NEW	18-248B*	3/8" x 3/4"	1.03	1.20	0.86	0.16	----
	18-247	7/16” x 1/4”	0.84	1.00	0.56	0.14	----
	18-236	1/2” x 1/4”	0.88	0.97	0.56	0.14	----
NEW	18-236B*	1/2" x 1/4"	0.85	0.94	0.07	0.17	----
	18-237	1/2” x 3/8”	0.88	1.03	0.56	0.19	----
	18-237B*	1/2” x 3/8”	0.94	1.12	0.70	0.19	----
	18-238	1/2” x 1/2”	0.94	1.13	0.59	0.17	----
	18-238B*	1/2” x 1/2”	0.94	1.31	0.86	0.17	----
	18-239	1/2” x 3/4”	1.16	1.25	0.81	0.18	----
	18-240	5/8” x 3/8”	1.06	1.12	0.68	0.18	----
	18-241	5/8” x 1/2”	1.06	1.16	0.68	0.20	----
	18-241B*	5/8” x 1/2”	1.06	1.31	0.86	0.20	----
	18-242	5/8” x 3/4”	1.16	1.31	0.81	0.24	----
	18-243	3/4” x 1/2”	1.19	1.31	0.94	0.26	----
	18-245	3/4” x 3/4”	1.19	1.38	0.94	0.30	----
	18-246	7/8” x 3/4”	1.25	1.38	0.94	0.35	----

* Barstock

Dimension data can change without notice. Please see our website when dimensions are critical.

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

FEMALE ELBOW

SAE# 060203





	Part #	Comp. X Female NPTF	A	B	Body Size	Approx. Wt. Lbs.	
	18-251	1/8” x 1/8”	0.69	0.56	0.56	0.04	----
NEW	18-251B*	1/8" x 1/8"	0.69	0.60	0.57	0.06	----
	18-252	3/16” x 1/8”	0.69	0.47	0.56	0.04	----
NEW	18-252B*	3/16” x 1/8”	0.60	0.60	0.58	0.07	----
	18-253	1/4” x 1/8”	0.69	0.47	0.56	0.06	----
	18-253B*	1/4” x 1/8”	0.69	0.56	0.56	0.06	----
	18-254	1/4” x 1/4”	0.75	0.50	0.72	0.08	----
NEW	18-254B*	1/4” x 1/4”	0.72	0.85	0.68	0.13	----
	18-267	1/4” x 3/8”	0.81	0.58	0.81	0.08	----
	18-268	1/4” x 1/2”	0.89	0.66	1.00	0.10	----
	18-255	5/16” x 1/8”	0.72	0.84	0.47	0.08	----
	18-256	5/16” x 1/4”	0.78	0.50	0.72	0.09	----
	18-257	3/8” x 1/8”	0.75	0.84	0.47	0.10	----
	18-258	3/8” x 1/4”	0.84	0.59	0.75	0.10	----
	18-259	3/8” x 3/8”	0.88	0.58	0.81	0.12	----
	18-260	3/8” x 1/2”	0.97	0.66	1.00	0.14	----
	18-250	3/8” x 3/4”	1.09	0.72	1.25	0.18	----
	18-261	1/2” x 1/4”	1.06	0.70	0.88	0.18	----
	18-262	1/2” x 3/8”	1.00	0.70	0.88	0.16	----
	18-263	1/2” x 1/2”	1.03	0.72	1.00	0.20	----
	18-270	1/2” x 3/4”	1.16	0.72	1.25	0.23	----
	18-269	5/8” x 3/8”	1.09	0.77	1.00	0.20	----
	18-264	5/8” x 1/2”	1.09	0.77	1.00	0.22	----
	18-265	5/8” x 3/4”	1.22	0.77	1.25	0.24	----
	18-266	3/4” x 1/2”	1.25	1.25	0.94	0.28	----

* Barstock

70 270C BSE3 170C

FORGED MALE RUN TEE



	Part #	Comp. X Male NPTF (1&3) X 2	A	B	Body Size	Approx. Wt. Lbs.	
	18-272	1/8” x 1/8”	0.63	0.69	0.36	0.06	----
	18-273	3/16” x 1/8”	0.63	0.69	0.36	0.07	----
NEW	18-273B*	3/16" x 1/8"	0.63	0.69	0.36	0.06	----
NEW	18-274B*	1/4" x 1/8"	0.63	0.75	0.36	0.07	----
	18-274	1/4” x 1/8”	0.63	0.75	0.36	0.08	----
	18-275	1/4” x 1/4”	0.69	0.88	0.44	0.10	----
	18-276	5/16” x 1/8”	0.72	0.75	0.50	0.10	----
	18-277	5/16” x 1/4”	0.75	0.88	0.44	0.10	----
	18-278	3/8” x 1/8”	0.75	0.75	0.50	0.14	----
	18-279	3/8” x 1/4”	0.79	0.87	0.44	0.18	----
	18-280	3/8” x 3/8”	0.88	1.00	0.47	0.20	----
	18-281	1/2” x 3/8”	0.94	1.09	0.59	0.24	----
	18-282	1/2” x 1/2”	0.97	1.19	0.69	0.26	----
	18-283	5/8” x 1/2”	1.06	1.31	0.69	0.28	----
	18-284	3/4” x 1/2”	1.22	1.34	0.88	0.30	----

* Barstock

71 171C BST3

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

MALE BRANCH TEE

SAE# 060425



Forged



Barstock

Part #	Comp. X Male NPTF (1&2) X 3	A	B	Body Size	Approx. Wt. Lbs.	
18-290	3/16" x 1/8"	0.63	0.69	0.36	0.08	----
18-291	1/4" x 1/8"	0.62	0.75	0.36	0.10	----
18-291B*	1/4" x 1/8"	0.64	0.73	0.45	0.10	----
18-292	1/4" x 1/4"	0.69	0.86	0.44	0.10	----
18-293	5/16" x 1/8"	0.72	0.75	0.50	0.11	----
18-294	5/16" x 1/4"	0.75	0.88	0.44	0.12	----
18-295	3/8" x 1/8"	0.75	0.75	0.50	0.14	----
18-296	3/8" x 1/4"	0.78	0.88	0.44	0.16	----
18-297	3/8" x 3/8"	0.78	0.97	0.47	0.18	----
18-298	3/8" x 1/2"	0.88	1.22	0.69	0.20	----
18-304	1/2" x 1/4"	0.94	0.97	0.59	0.22	----
18-299B*	1/2" x 3/8"	0.96	1.09	0.70	0.24	----
18-299	1/2" x 3/8"	0.94	1.12	0.59	0.24	----
18-300	1/2" x 1/2"	0.97	1.19	0.69	0.30	----
18-301	5/8" x 1/2"	1.06	1.31	0.69	0.32	----
18-302	3/4" x 1/2"	1.22	1.34	0.88	0.50	----
18-303	3/4" x 3/4"	1.25	1.50	0.88	0.54	----

* Barstock

72 BST1 172C

FORGED TEE



Part #	Comp. X Female NPTF x Male NPTF 1x(2&3)	A	B	C	Approx. Wt. Lbs.	
18-307	1/4" x 1/8"	0.72	0.53	0.72	0.20	----

71 171C BST3

ADAPTER TEE



Part #	Male NPTF x Female NPTF x Comp. 3x (1&2)	A	B	C	Body Size	Approx. Wt. Lbs.	
18-314	1/8" x 1/4"	0.72	0.53	0.72	0.47	0.08	----
18-316	3/8" x 1/4"	0.84	0.97	0.81	0.47	0.10	----

76 176C

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

FEMALE BRANCH FORGED TEE



Part #	Comp. X Female NPTF (1&2)x3	A	B	Body Size	Approx. Wt. Lbs.	
18-321	1/4" x 1/8"	0.78	0.75	0.45	0.10	----
18-328	1/4" x 1/4"	0.78	0.75	0.44	0.12	----
18-325	3/8" x 1/8"	0.75	0.63	0.50	0.12	----
18-322	3/8" x 1/4"	0.81	0.97	0.47	0.14	----
18-323	3/8" x 3/8"	0.97	0.69	1.05	0.16	----
18-326	1/2" x 1/8"	0.94	0.75	0.59	0.20	----
18-324	1/2" x 3/8"	1.00	0.72	0.88	0.22	----
18-327	5/8" x 1/8"	1.06	0.81	0.69	0.26	----

78 **BST4** 77 **177C** 2908

45° ELBOW

SAE# 060302



Part #	Comp. X Male NPTF	A	B	Body Size	Approx. Wt. Lbs.	
18-329	3/16" x 1/8"	0.40	0.63	0.41	0.04	----
18-330	1/4" x 1/8"	0.40	0.61	0.41	0.04	----
18-336	1/4" x 1/4"	0.59	0.84	0.53	0.06	----
18-331	5/16" x 1/8"	0.59	0.65	0.53	0.06	----
18-332	5/16" x 1/4"	0.59	0.83	0.53	0.08	----
18-333	3/8" x 1/4"	0.62	0.83	0.53	0.08	----
18-338	3/8" x 3/8"	0.75	0.95	0.59	0.10	----
18-334	1/2" x 3/8"	0.75	0.88	0.59	0.14	----
18-339	1/2" x 1/2"	0.94	1.14	0.75	0.14	----
18-335	5/8" x 1/2"	0.78	1.14	0.78	0.14	----

6945 **45BSE1** 74 **179C** 273 **77**

COMPRESSION PLUG



	Part #	Size	A	B	Approx. Wt. Lbs.	
NEW	18-028	1/4"	0.30	0.34	0.01	----
	18-029	3/8"	0.31	0.47	0.04	----
	18-032	5/16"	0.40	0.40	0.01	----
	18-030	1/2"	0.34	0.59	0.06	----
NEW	18-031	5/8"	0.45	0.72	0.04	----

CSP

CAP



Part #	Size	A	Hex	Approx. Wt. Lbs.	
18-047	1/4"	0.44	0.50	0.02	----
18-048	3/8"	0.40	0.62	0.04	----
18-049	1/2"	0.48	0.75	0.06	----
18-050	5/8"	0.56	0.94	0.10	----

61-CC **N5CT**

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

BULKHEAD UNIONS

SAE# 060101



	Part #	Size	A	Hex 1	Hex 2	Approx. Wt. Lbs.	
NEW	18-087	3/16"	1.25	0.56	0.50	0.07	----
	18-088	1/4"	1.58	0.56	0.56	0.10	----
NEW	18-089	5/16	1.68	0.625	0.625	0.11	----
	18-090	3/8"	1.76	0.68	0.68	0.14	----
NEW	18-091	1/2"	1.92	0.82	0.875	0.24	----
NEW	18-093	5/8"	2.01	1.000	0.94	0.32	----

See our website for bulkhead nuts

62BH **75** 274

BALL CHECK VALVE - Min. Working pressure 3 psi.





Part #	Tube OD x Male NPTF	A	Hex	Approx. Wt. Lbs.	
18-092	1/8" x 1/8"	0.78	0.44	0.04	----
18-094	1/4" x 1/8"	0.88	0.44	0.04	----
18-096	3/8" x 1/4"	1.16	0.56	0.08	----

63 **263** 63A

TANK ADAPTER DRILLED THRU (NO STOP)



Part #	Comp. X Male NPTF	A	Hex	Approx. Wt. Lbs.	
18-208	1/4" x 1/8"	0.88	0.43	0.04	----
18-209	1/4" x 1/4"	0.99	0.56	0.05	----
18-210	3/8" x 1/4"	1.16	0.56	0.05	----
18-211	3/8" x 3/8"	1.09	0.68	0.08	----
18-212	3/8" x 1/2"	1.19	0.87	0.10	----
18-213	1/2" x 3/8"	1.22	0.68	0.12	----
18-214	1/2" x 1/2"	1.09	0.81	0.14	----
18-215	5/8" x 1/2"	1.12	0.81	0.18	----

68-T **682C** 80F

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

COMPRESSION — BRASS FITTINGS

DOUBLE COMPRESSION THREADED SLEEVE FITTINGS

- Use with aluminum and copper tubing or plastic tubing with internal tube support. Not recommended for steel tubing.
- Easy to assemble, no flaring, two piece construction.
- For use on oil, air, water and grease lubrication systems.
- When design makes a dimension critical, contact us for information.

Tube OD	1/8	3/16	1/4	5/16	3/8
Thread	5/16-24	3/8-24	7/16-24	1/2-20	9/16-20
Working Pressure	500	500	500	250	250

NUT



	Part #	Size	A	Hex	Approx. Wt. Lbs.	
	16-001	1/8”	0.50	0.37	0.02	----
	16-002	3/16”	0.53	0.43	0.02	----
	16-003	1/4”	0.56	0.50	0.04	----
	16-004	5/16”	0.61	0.56	0.04	----
	16-005	3/8”	0.61	0.62	0.04	----
NEW	16-006	1/2"	0.90	0.69	0.05	----
NEW	16-007	5/8"	1.07	0.88	0.06	----

181 **6100** 11

MALE ADAPTER



	Part #	THRD Sleeve x Male NPTF	A	Hex	Approx. Wt. Lbs.	
	16-117	1/8” x *	0.62	0.43	0.02	----
	16-118	1/8” x 1/8”	0.62	0.43	0.02	----
	16-119	3/16” x 1/8”	0.69	0.43	0.02	----
	16-121	1/4” x 1/8”	0.75	0.50	0.04	----
NEW	16-120	1/4" x 1/4"	1.06	0.56	0.05	----
	16-122	5/16” x 1/8”	0.89	0.56	0.04	----
NEW	16-125	5/16" x 1/4"	1.09	0.56	0.05	----
	16-123	3/8” x 1/4”	0.84	0.62	0.06	----

* 1/4 - 28 Male Thread Tapered.

188 **6200** 12

90° ELBOW



	Part #	THRD Sleeve x Male NPTF	A	B	Body Size	Approx. Wt. Lbs.	
	16-127	1/8” x *	0.50	0.52	0.41	0.02	----
	16-128	1/8” x 1/8”	0.50	0.66	0.43	0.02	----
	16-129	3/16” x 1/8”	0.56	0.62	0.44	0.02	----
	16-130	1/4” x 1/8”	0.52	0.62	0.50	0.04	----
NEW	16-131	5/16" x 1/8"	0.75	0.81	0.56	0.09	----
NEW	16-133	3/8" x 1/4"	0.88	1.00	0.56	0.13	----

* 1/4 - 28 Male Thread Tapered

189 **6400** 15

BREAK-AWAY NUT

- 1-Piece Fiting



	Part #	Size	A	Hex	Approx. Wt. Lbs.	
NEW	16-009	1/8"	0.66	0.31	0.02	----
	16-090	3/16”	0.57	0.37	0.02	----
	16-010	1/4”	0.62	0.43	0.02	----
NEW	16-011	5/16"	0.77	0.50	0.04	----
NEW	16-012	3/8"	0.84	0.56	0.04	----
NEW	16-013	1/2"	0.92	0.69	0.05	----

* Threaded sleeve fittings on page 85.

181-BA **21604** 99LB **81LB**

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

BRASS SPLIT SLEEVE D.O.T. FITTINGS (5/32 O.D.)

TRANSMISSION BRASS FITTINGS

APPLICATIONS: Used with SAE J844 Type A nylon tube in pressure protected air transmission applications.
TECHNICAL DATA: Maximum working pressure up to 150 PSI. Fittings will withstand variations from -40°F to +220°F (-40°C to + 104°C)

Ideally suited for use in passive protected air transmission applications. A specially designed slotted sleeve helps eliminate notch stress related to over torque.

COLLET

	Part #	Tube O.D.	
	38-711	5/32"	----
	25-001	1/8"	----
NEW	25-002	3/16"	----
NEW	25-003	1/4"	----

1460 **90791** 280 **90946**

NUT

Part #	Tube O.D.	
38-732	5/32"	----
25-033	1/8"	----

1461 **90790** 281 **90885**

DOUBLE END UNION

Part #	Tube O.D.	
38-761	5/32"	----
25-062	1/8"	----
25-064	1/4"	----

1462 **90792** 283 **90891**

CONNECTOR WITH NUT AND SLEEVE

	Part #	Tube O.D.	Pipe Thread	
	38-769	5/32"	1/16"	----
	38-770	5/32"	1/8"	----
	25-175	1/8"	1/16"	----
	25-176	1/8"	1/8"	----
NEW	25-177	3/16"	1/8"	----
NEW	25-179	1/4"	1/8"	----

• Shipped with nut and split sleeve, picture shows insert 1468 **90794** 282 **90985**

ELBOW

	Part #	Tube O.D.	Pipe Thread	
NEW	38-715	5/32"	1/16"	----
	38-718	5/32"	1/8"	----
	25-220	1/8"	1/8"	----
NEW	25-219	1/8"	1/16"	----
NEW	25-221	3/16"	1/8"	----
NEW	25-224	1/4"	1/8"	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

SPECIAL COMPRESSION ASSEMBLIES

To purchase special compression assemblies, delete the 18 prefix on part# and add the prefix of the type of special assembly you desire. Pricing and availability upon request.

22 - Plastic sleeve (inserts should be ordered seperately)
24 - Long nut compression
26 - Captive sleeve (parts listed on following pages)
27 - Self align sleeve

DELRIN SLEEVE



	Part #	Size	A	B	Approx. Wt. Lbs.	
	18-015	1/4”	0.19	0.37	0.01	----
	18-016	5/16”	0.19	0.43	0.01	----
	18-017	3/8”	0.19	0.50	0.02	----
	18-018	1/2”	0.25	0.63	0.02	----
	18-019	5/8”	0.22	0.74	0.02	----
NEW	18-020	3/4"	0.25	0.93	0.02	----

60-P

BRASS INSERT

• SLEEVE



	Part #	Size	A	B	Approx. Wt. Lbs.	Wall	
	22-008	1/8”	0.46	0.080	0.01	.016	----
NEW	22-008A	1/8"	0.46	0.080	0.01	.016	----
	22-009	3/16”	0.45	0.135	0.01	.025	----
	22-009A	3/16”	0.52	0.095	0.01	.040	----
	22-010	1/4”	0.50	0.163	0.02	.04	----
	22-010A	1/4”	0.59	0.125	0.02	.04	----
	22-010B	1/4”	0.53	0.172	0.02	.03	----
	22-011A	5/16”	0.50	0.232	0.02	.04	----
	22-011	5/16”	0.53	0.187	0.02	.062	----
	22-012	3/8”	0.56	0.250	0.03	.062	----
	22-013	1/2”	0.72	0.370	0.03	.062	----
	22-014	5/8”	0.72	0.483	0.03	.062	----
	22-015	3/4”	1.03	0.563	0.03	.03	----

63-BI **60AE** 2030 **63PT**

LONG NUT COMPRESSION - Can be assembled on any compression fitting



Part #	Size	A	Hex	Approx. Wt. Lbs.	
10-013	1/8"	0.50	0.37	0.01	----
24-002	3/16"	0.62	0.43	0.01	----
24-003	1/4”	0.75	0.50	0.02	----
24-004	5/16”	0.84	0.56	0.02	----
24-005	3/8”	0.97	0.62	0.04	----
24-006	1/2”	1.06	0.81	0.06	----
24-007	5/8"	1.19	0.94	0.11	----
24-008	3/4"	1.50	1.25	0.14	----

161

SELF-ALIGN SLEEVES

Part #	Size	
27-001	1/8"	----
27-002	3/16"	----
27-003	1/4"	----

860 **601**

Part #	Size	
27-005	3/8"	----
27-006	1/2"	----

860

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

CAPTIVE SLEEVE NUT

Part #	Size	
26-001	1/8”	----
26-002	3/16”	----
26-003	1/4”	----
26-004	5/16”	----
26-005	3/8”	----
26-007	1/2”	----
26-008	5/8”	----

CS61 **61CA**

UNION

Part #	Size	
26-062	1/8”	----
26-063	3/16”	----
26-064	1/4”	----
26-065	5/16”	----
26-066	3/8”	----
26-079	3/8” x 1/4”	----
26-068	1/2"	----
26-069	5/8"	----

CS62 **62CA**

TEE

Part #	Size	
26-102	3/16”	----
26-103	1/4”	----
26-105	3/8”	----

CS64 **164CA**

FEMALE ADAPTER

Part #	Comp. X Female NPTF	
26-142	1/8" x 1/8"	----
26-145	1/4” x 1/8”	----
26-146	1/4" x 1/4"	----
26-153	3/8” x 1/4”	----

CS66 **66CA**

MALE ADAPTER

Part #	Comp. X Male NPTF	
26-175	1/8" x 1/4"	----
26-176	1/8” x 1/8”	----
26-177	3/16” x 1/8”	----
26-179	1/4” x 1/8”	----
26-180	1/4” x 1/4”	----
26-180L	1/4" x 1/4"	----
26-181	1/4” x 3/8”	----
26-182	1/4" x 1/2"	----
26-183	5/16” x 1/8”	----
26-184	5/16” x 1/4”	----
26-188	3/8” x 1/4”	----
26-189	3/8” x 3/8”	----
26-190	3/8” x 1/2”	----
26-194	1/2" x 3/8"	----
26-195	1/2” x 1/2”	----
26-198	5/8" x 1/2"	

CS68 **68CA**

MALE ELBOW

Part #	Comp. X Male NPTF	
26-220	1/8” x 1/8”	----
26-220B	1/8” x 1/8”	----
26-221	3/16” x 1/8”	----
26-224B	1/4" x 1/8"	----
26-224	1/4” x 1/8”	----
26-221B	3/16" x 1/8"	----
26-225	1/4” x 1/4”	----
26-225B	1/4” x 1/4”	----
26-228	5/16” x 1/8”	----
26-229	5/16” x 1/4”	----
26-232	3/8" x 1/8"	----
26-233	3/8” x 1/4”	----
26-233B	3/8" x 1/4"	----
26-234	3/8" x 3/8"	----
26-235	3/8" x 1/2"	----
26-237	1/2” x 3/8”	----
26-238	1/2” x 1/2”	----

CS69 **169CA**

MALE BRANCH TEE

Part #	Comp. X Male NPTF (1&2) X 3	
26-291	1/4” x 1/8”	----
26-292	1/4” x 1/4”	----
26-293	5/16” x 1/8”	----
26-296	3/8” x 1/4”	----

CS72 **172CA**

CAPTIVE SLEEVE x MALE PIPE ANGLE NEEDLE VALVE



Part #	Comp X Male Pipe	
26-011	1/4” x 1/8”	----
26-014	5/16” x 1/4”	----

CAPTIVE SLEEVE x CAPTIVE SLEEVE NEEDLE VALVE

Part #	Comp X Comp	
26-021	1/4”	----
26-023	3/8”	----

Interchangeable with compress-align fittings.

These are NOT Lead Free
Lead Free products
available upon request

- More sizes available
- Lead Free - add LF to part #

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

Flareless

Flareless Brass Tube Fittings are Interchangeable with Poly-Flo®, Poly-Tite® and Poly-Line® and Poly-Fit®

Built-in SS
Tube Support

Tube O.D.	1/8	3/16	1/4	5/16	3/8	1/2
Thread Size-B	5/16-24	3/8-24	3/8-24	7/16-24	1/2-24	11/16-20

•Typical Application
Pneumatic instrumentation circuits, lubricant and cooling lines.

•Working Pressure and Temperature Ranges
Up to 150 PSI from 0°F to + 150°F with thermoplastic tubing. Up to 300 PSI from 0°F to + 175°F with soft metal tubing.

•Maximum allowable metal tube wall thickness for use with Poly-Tite fittings:
1/8", 3/16" O.D. --no limitation,
1/4" O.D.--.035 5/16", 3/8",1/2" O.D.--.049

•Vibration
Excellent Resistance.

•Temperature Range
Depends on tubing used. -65°F to +250°F (-53°C to +121°C) with brass sleeve, -40°F to +150°F (-40°C to +66°C) with plastic sleeve. (Refer to tubing temperature range.)

•Used With
Aluminum & copper tubing. Hard plastic tubing requires brass sleeve. Not recommended for steel tubing.

• Tolerance
+/- .02 on all dimensions. Dimension data can change without notice. Please call us when dimensions are critical.

•Advantages
No flaring of tubing required. Easy installation, captive sleeve, pre-assembled for installation and can be reassembled. Nuts rotate around the sleeve during tightening, preventing twisting of tubing.

•Assembly Instructions
1- Cut tubing to desired length.
2- Slide nut/sleeve assembly on tube. Threaded end "A" of nut must face toward fitting.
3- Bottom tubing into fitting.
4- Plastic sleeve - Tighten nut hand tight.
Brass Sleeve - Tighten nut hand tight, then an additional 3/4 turn.

* Note: 1/8 and 3/16 sizes have brass sleeves

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

NUT AND PLASTIC SLEEVE ASSEMBLY

Part #	Tube O.D.	Thread	A	Hex (Dia.)	Approx. Wt. Lbs.	
20-211	1/4”	3/8-24	0.34	0.43	0.02	----
20-212	5/16”	7/16-24	0.45	0.50	0.02	----
20-213	3/8”	1/2-24	0.38	0.56	0.04	----
20-214	1/2”	11/16-20	0.42	0.81	0.04	----

261PF **1261** 61PN

UNION



Part #	Tube O.D.	A	Hex	Approx. Wt. Lbs.	
20-240	1/8”	0.66	0.31	0.02	----
20-241	3/16”	0.75	0.37	0.04	----
20-242	1/4”	0.69	0.37	0.04	----
20-243	5/16”	0.69	0.44	0.04	----
20-244	3/8”	0.72	0.50	0.10	----
20-200	3/8” x 1/4”	0.72	0.50	0.08	----
20-245	1/2”	0.84	0.69	0.14	----

262PF **1262** 62P **262P**

BULKHEAD UNION



Part #	Tube O.D.	A	Hex	Approx. Wt. Lbs.	
20-337	1/4”	1.25	0.56	0.06	----
20-338	5/16”	1.25	0.62	0.08	----
20-339	3/8”	1.31	0.69	0.10	----

62PBH **329P** 282P

UNION TUBE #M62C - FLARELESS X STANDARD COMPRESSION



Part #	Tube O.D.	A	Hex 1	Hex 2	Approx. Wt. Lbs.	
20-235	1/4”	0.75	0.44	0.50	0.04	----
20-237	3/8”	0.84	0.62	0.62	0.08	----

262S **62PCA** 262PC

BULKHEAD UNION - FLARELESS X COMPRESSION



Part #	Tube O.D.	A	Hex	Approx. Wt. Lbs.	
20-333	1/4”	1.31	0.56	0.07	----
20-334	3/8”	1.44	0.69	0.12	----

1274

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

FLARELESS BRASS FITTINGS

UNION TEE



Part #	Tube O.D.	A	Body Size	Approx. Wt. Lbs.	
20-248	1/8”	0.62	0.31	0.02	----
20-249	3/16”	0.62	0.31	0.04	----
20-250	1/4”	0.73	0.44	0.06	----
20-251	5/16”	0.62	0.37	0.08	----
20-252	3/8”	0.86	0.56	0.08	----
20-330*	3/8” x 1/4”	0.72	0.44	0.08	----
20-253	1/2”	0.81	0.62	0.24	----

* Reducing Branch

1264 **164P** 264P

FEMALE CONNECTOR



Part #	Tube O.D. x Female NPTF	A	Hex	Approx. Wt. Lbs.	
20-256	1/8” x 1/8”	0.75	0.56	0.03	----
20-257	3/16” x 1/8”	0.78	0.56	0.05	----
20-259	1/4” x 1/8”	0.76	0.50	0.04	----
20-260	1/4” x 1/4”	1.08	0.62	0.05	----
20-261	5/16” x 1/8”	0.75	0.50	0.03	----
20-265	3/8” x 1/8”	0.77	0.56	0.05	----
20-262	3/8” x 1/4”	0.94	0.62	0.05	----
20-263	1/2” x 3/8”	1.00	0.81	0.12	----

1266 **66P** 266P

MALE CONNECTOR



Part #	Tube O.D. x Male NPTF	A	Hex	Approx. Wt. Lbs.	
20-268	1/8” x 1/8”	0.80	0.34	0.04	----
20-269	3/16” x 1/8”	0.86	0.44	0.04	----
NEW 20-270	1/4" x 10/32"				
20-271	1/4” x 1/8”	0.82	0.44	0.03	----
20-272	1/4” x 1/4”	1.00	0.56	0.05	----
20-273	1/4” x 3/8”	1.03	0.69	0.08	----
20-274	5/16” x 1/8”	0.81	0.44	0.04	----
20-275	5/16” x 1/4"	1.00	0.56	0.05	----
20-276	3/8” x 1/8”	1.00	0.56	0.06	----
20-277	3/8” x 1/4”	1.03	0.56	0.08	----
20-278	3/8” x 3/8”	1.03	0.69	0.10	----
20-279	1/2” x 3/8”	1.09	0.69	0.16	----
20-282	1/2” x 1/2”	1.33	0.88	0.18	----

1268 **68P** 268P

MALE ELBOW



Part #	Tube O.D. x Male NPTF	A	B	Body Size	Approx. Wt. Lbs.	
20-287	1/8” x 1/8”	0.62	0.69	0.31	0.02	----
20-288	3/16” x 1/8”	0.62	0.69	0.37	0.04	----
20-289*	1/4” x 1/8”	0.53	0.73	0.50	0.04	----
20-290	1/4” x 1/4”	0.66	0.94	0.37	0.06	----
20-291	1/4” x 3/8”	0.75	1.03	0.50	0.10	----
20-292	5/16” x 1/8”	0.62	0.75	0.41	0.04	----
20-293	3/8” x 1/8”	0.79	0.73	0.37	0.08	----
20-294	3/8” x 1/4”	0.72	0.94	0.44	0.10	----
20-295	3/8” x 3/8”	0.78	1.03	0.50	0.14	----
20-296	1/2” x 3/8”	1.09	1.10	0.73	0.16	----

* Barstock

1269 **169P** 269P

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

FEMALE ELBOW



Part #	Tube O.D. x Female NPTF	A	B	Body Size	Approx. Wt. Lbs.	
20-300	1/8" x 1/8"	0.69	0.55	0.56	0.02	----
20-301	3/16" x 1/8"	0.72	0.55	0.56	0.02	----
20-302	1/4" x 1/8"	0.62	0.75	0.37	0.08	----
20-303	1/4" x 1/4"	0.72	0.88	0.50	0.10	----
20-304	3/8" x 1/4"	0.72	0.88	0.50	0.12	----
20-305	1/2" x 3/8"	0.91	0.94	0.63	0.16	----

1270 **170P**

MALE RUN TEE



Part #	Tube O.D. x Male NPTF	A	B	Body Size	Approx. Wt. Lbs.	
20-308	1/8" x 1/8"	0.62	0.69	0.31	0.04	----
20-309	3/16" x 1/8"	0.62	0.69	0.31	0.04	----
20-310	1/4" x 1/8"	0.62	0.75	0.37	0.08	----
20-311	1/4" x 1/4"	0.66	0.94	0.37	0.10	----
20-312	5/16" x 1/8"	0.62	0.75	0.37	0.08	----
20-313	3/8" x 1/4"	0.66	0.94	0.44	0.10	----
20-314	1/2" x 3/8"	0.81	1.06	0.63	0.16	----

1271 **171P**

MALE BRANCH TEE



Part #	Tube O.D. x Male NPTF	A	B	Body Size	Approx. Wt. Lbs.	
20-317	1/8" x 1/8"	0.63	0.69	0.31	0.04	----
20-318	3/16" x 1/8"	0.63	0.69	0.31	0.04	----
20-319	1/4" x 1/8"	0.63	0.75	0.37	0.07	----
20-320	1/4" x 1/4"	0.66	0.94	0.37	0.09	----
20-321	5/16" x 1/8"	0.63	0.75	0.37	0.10	----
20-322	3/8" x 1/8"	0.63	0.75	0.44	0.08	----
20-323	3/8" x 1/4"	0.66	0.94	0.44	0.11	----
20-324	1/2" x 3/8"	0.81	1.06	0.63	0.21	----

1272 **172P** 272P

FEMALE BRANCH TEE



Part #	Tube O.D. x Female NPTF	A	B	Body Size	Approx. Wt. Lbs.	
20-327	1/4" x 1/8"	0.66	0.94	0.37	0.12	----
20-328	1/4" x 1/4"	0.84	1.16	0.56	0.16	----

1277 **177P** 277P

Dimension data can change without notice. Please see our website when dimensions are critical.

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

UNIVERSAL NUT AND BRASS SLEEVE ASSEMBLY

Part #	Tube O.D.	Thread	A	Hex	Approx. Wt. Lbs.	
20-227	1/8”	5/16-24	0.37	0.37	0.02	----
20-228	3/16”	3/8-24	0.41	0.44	0.02	----
20-229	1/4”	3/8-24	0.34	0.43	0.02	----
20-230	5/16”	7/16-24	0.34	0.50	0.02	----
20-231	3/8”	1/2-24	0.37	0.56	0.04	----
20-232	1/2”	11/16-20	0.42	0.81	0.04	----

261PFB **1261B** 61PB **261UB**

NUT

Part #	Tube O.D.	Thread	A	Hex (Dia.)	Approx. Wt. Lbs.	
20-218	1/8”	5/16-24	0.37	0.37	0.01	----
20-219	3/16”	3/8-24	0.41	0.44	0.01	----
20-220	1/4”	3/8-24	0.34	0.44	0.02	----
20-221	5/16”	7/16-24	0.34	0.50	0.02	----
20-222	3/8”	1/2-24	0.38	0.56	0.04	----
20-223	1/2”	11/16-20	0.42	0.81	0.06	----

61PN **1261** 261FPN

PLASTIC SLEEVE



Part #	Tube O.D.	A	B	Approx. Wt. Lbs.	
20-205	1/4”	0.34	0.26	0.01	----
20-206	5/16”	0.39	0.32	0.01	----
20-207	3/8”	0.41	0.38	0.01	----
20-208	1/2”	0.44	0.51	0.01	----

260FF **1260** 60P **260P**

PLASTIC CAP

Part #	Tube O.D.	A	Approx. Wt. Lbs.	
20-201	1/4”	0.50	0.01	----
20-203	3/8”	0.56	0.01	----
20-204	1/2”	0.59	0.01	----

1229 **59P** 259P

Dimension data can change without notice. Please see our website when dimensions are critical.

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

PUSH-IN/ PUSH-TO-CONNECT FITTINGS

BRASS PUSH-IN
PAGE 96-101

NICKEL PLATED BRASS PUSH-IN
PAGE 102-106

BALL VALVES FOR N/P PUSH-IN
PAGE 107

METRIC N/P BRASS PUSH-IN
PAGE 108-110

COMPOSITE BODY PUSH-IN
PAGE 111-115

COMPOSITE BODY METRIC PUSH-IN
PAGE 116-118

FDA PLASTIC PUSH-IN
PAGE 303-304

DOT BRASS PUSH-IN
PAGE 119-125

DOT COMPOSITE PUSH-IN
PAGE 126-130

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

BRASS PUSH-IN FITTINGS

ENGINEERING AND DESIGN

• **QUICK CONNECT**, simply push tubing in, no tools. Saves up to 75% of assembly time of standard compression fittings.
• **QUICK DISCONNECT**, hold two fingers on insert and pull tubing out, no tools required.
• **REUSEABLE**, connect and disconnect numerous times.
• **FULL FLOW DESIGN**, provides up to 60% more flow area than conventional fittings with internal tube supports.
• **POSITIVE SEAL**, no leaks. After tubing is inserted, seal is made.
• **VERSATILE**, BunaN "O" rings standard. Other materials of "O" rings available.
• **SECURE TUBE RETENTION**, pulling on tubing only serves to tighten the connection.
• **SELF CONTAINED ASSEMBLY**, no loose parts, brass body and insert.



When tubing (1) is inserted into the fitting, it first passes through the gripping teeth (2). Just beyond the gripping teeth is the o-ring (3) which provides the leak proof seal against the OD of the tube. The gripping teeth grab the tube, which expands the insert. Pulling back on the tube only tightens the grip as the insert moves onto the camming surface (4). Pressure through the tube also serves to tighten the grip. The tube bottoms against a positive tube stop (5) in a cavity providing tube support to prevent leakage.

• **BRASS CONSTRUCTION**, elbows and tees are forged brass.
• **CHOICE** of convenient swivel of economical stationary elbows and tees.
• **STRAIGHT CONNECTORS** have interior hex for Allen key tightening where space is limited...no need to use a wrench.
• **PRE-APPLIED TEFLON ®** based pipe sealant on all male pipe threads, saving customer additional labor.
• **METRIC SIZES AVAILABLE**: Metric tube sizes from 2mm through 12mm in both standard NPT and metric pipe sizes are available on a special order basis.
• **WORKING TEMPERATURE**:
-10^{0}F to 200^{0}F (other ranges available on request).
• **PIPE THREAD**: NPTF with Teflon ® based sealant pre-applied.

• **Tolerance**
+/- .02 on all dimensions. Dimension data can change without notice. Please call us when dimensions are critical

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

UNION CONNECTOR



Part #	Tube O.D.	A	B	Approx. Wt. Lbs.	
20-017	1/8”	1.07	0.38	0.03	----
20-018	5/32”	1.07	0.38	0.03	----
20-019	1/4”	1.50	0.44	0.05	----
20-022	3/8” x 1/4”	1.46	0.56	0.05	----
20-020	3/8”	1.44	0.56	0.06	----
20-021	1/2”	1.63	0.81	0.18	----

AQ62 **6580** 3106 **62PL** KQH **12-020** 50-562 **262-OF** 1162 **262PP**

UNION TEE



Part #	Tube O.D.	A	Body Size	Approx. Wt. Lbs.	
20-025	1/8”	0.65	0.31	0.04	----
20-026	5/32”	0.67	0.31	0.04	----
20-027	3/16”	0.75	0.37	0.06	----
20-028	1/4”	0.92	0.37	0.09	----
20-031*	5/16”	0.89	0.49	0.10	----
20-029	3/8”	0.98	0.50	0.13	----
20-030	1/2”	1.16	0.62	0.24	----

* Nickel Plated

KQT **12-060** 50-564 **264OF** 264PP **1164** AQ64 **6540** 3140

UNION ELBOW



Part #	Tube O.D.	A	Body Size	Approx. Wt. Lbs.	
20-150	1/8”	0.65	0.31	0.02	----
20-151	5/32”	0.67	0.31	0.04	----
20-152	1/4”	0.87	0.37	0.06	----
20-155	5/16”	0.91	0.47	0.08	----
20-153	3/8”	0.97	0.50	0.09	----
20-154	1/2”	1.15	0.62	0.18	----

AQ65 **6550** 3102 **165PL** KQL **12-040** 50-565 **265-OF**

FEMALE CONNECTOR



Part #	Tube O.D. x Female NPTF	A	Hex	Approx. Wt. Lbs.	
20-032	1/8” x 1/8”	0.96	0.56	0.04	----
20-038	1/8” x 1/4”	1.04	0.67	0.04	----
20-012	5/32" x 1/8"	1.09	0.56	0.05	----
20-034	1/4” x 1/8”	1.23	0.56	0.06	----
20-035	1/4” x 1/4”	1.42	0.75	0.09	----
20-036	3/8” x 1/4”	1.32	0.75	0.09	----
20-037	3/8” x 3/8”	1.31	0.87	0.12	----

266PP **AQ66** 6463 **3114** 66PL **12-426** 50-566 **266-OF** 1166

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

MALE CONNECTOR



Part #	Tube O.D. x Male NPTF	A	Hex	Approx. Wt. Lbs.	
20-047*	1/8” x 10-32”*	0.69	0.37	0.02	----
20-045	1/8" x 1/16"	0.68	0.37	0.02	----
20-048	1/8” x 1/8”	0.61	0.43	0.02	----
20-023	1/8” x 1/4”	0.98	0.56	0.04	----
20-049*	5/32” x 10-32”*	0.67	0.37	0.02	----
20-050	5/32” x 1/8”	0.67	0.43	0.03	----
20-046	5/32” x 1/4”	0.85	0.56	0.05	----
20-051*	3/16” x 10-32”*	0.80	0.37	0.02	----
20-052	3/16” x 1/8”	0.93	0.43	0.03	----
20-053*	1/4” x 10-32”*	0.70	0.43	0.03	----
20-039	1/4" x 1/16"	0.92	0.43	0.06	----
20-054	1/4” x 1/8”	0.93	0.43	0.06	----
20-055	1/4” x 1/4”	0.93	0.56	0.10	----
20-056	1/4” x 3/8”	0.94	0.68	0.08	----
20-530	5/16” x 1/8”	1.07	0.56	0.05	----
20-531	5/16” x 1/4”	0.98	0.56	0.10	----
20-532	5/16” x 3/8”	1.06	0.75	0.08	----
20-057	3/8” x 1/8”	1.10	0.56	0.06	----
20-058	3/8” x 1/4”	1.11	0.56	0.05	----
20-059	3/8” x 3/8”	1.02	0.68	0.08	----
20-062	3/8”x 1/2”	1.02	0.87	0.08	----
20-060	1/2” x 1/4”	1.36	0.81	0.11	----
20-061	1/2” x 3/8”	1.30	0.81	0.12	----
20-063	1/2” x 1/2”	1.23	0.87	0.14	----

* Furnished with gaskets

268PP **AQ68** 6510 **3115** 68PL **KQH** 12-425 **50-568** 268-OF **1168**

SWIVEL MALE ELBOW



Part #	Tube O.D. x Male NPTF	A	B	Hex	Approx. Wt. Lbs.	
20-079	1/8” x 1/8”	0.69	0.98	0.43	0.07	----
20-535*	1/8” x 1/4”	0.76	0.87	0.56	0.06	----
20-076**	5/32” x 10-32”	0.67	0.71	0.37	0.04	----
20-080	5/32” x 1/8”	0.68	0.89	0.43	0.05	----
20-077	5/32” x 1/4”	0.68	1.08	0.56	0.07	----
20-078**	1/4” x 10-32”	0.86	0.79	0.31	0.05	----
20-081	1/4” x 1/8”	0.90	0.93	0.37	0.08	----
20-082	1/4” x 1/4”	0.90	0.99	0.56	0.10	----
20-086	1/4” x 3/8”	0.98	1.14	0.68	0.09	----
20-538*	5/16” x 1/4”	0.91	0.85	0.56	0.07	----
20-539*	5/16” x 3/8”	0.91	0.87	0.75	0.08	----
20-087	3/8” x 1/8”	1.00	1.06	0.43	0.09	----
20-083	3/8” x 1/4”	0.99	1.15	0.56	0.10	----
20-084	3/8” x 3/8”	1.00	1.24	0.68	0.20	----
20-088	3/8” x 1/2”	1.00	1.54	0.87	0.19	----
20-085	1/2” x 3/8”	1.16	1.34	0.68	0.18	----
20-092	1/2” x 1/2”	1.16	1.51	0.87	0.24	----

* Nickel Plated

** Furnished with gaskets

aq69-ps **56520** 3109 **169pl** kql **12-447** 50-579 **269-OFS** 11695

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

FIXED MALE ELBOW



Part #	Tube O.D. x Male NPTF	A	B	Body Size	Approx. Wt. Lbs.	
20-065	1/8" x 1/8"	0.69	0.69	0.31	0.03	----
20-066	5/32" x 1/8"	0.68	0.68	0.31	0.03	----
20-067	3/16" x 1/8"	0.75	0.71	0.37	0.04	----
20-068	1/4" x 1/8"	0.89	0.75	0.37	0.06	----
20-069	1/4" x 1/4"	0.95	0.96	0.37	0.08	----
20-070	1/4" x 3/8"	1.00	0.98	0.50	0.10	----
20-071	3/8" x 1/8"	0.99	0.80	0.50	0.06	----
20-072	3/8" x 1/4"	0.98	0.98	0.50	0.09	----
20-073	3/8" x 3/8"	0.97	0.98	0.50	0.12	----
20-074	1/2" x 1/4"	1.15	1.05	0.62	0.15	----
20-075	1/2" x 3/8"	1.18	1.05	0.62	0.22	----
20-064	1/2" x 1/2"	1.16	1.66	0.62	0.20	----

269PP **AQ69-P** 6500 **169PLNS** 12-445 **1169**

Dimension data can change without notice. Please see our website when dimensions are critical.

FEMALE SWIVEL ELBOW



Part #	Tube O.D. x Female NPTF	A	B	Hex	
20-094S	5/32" x 1/8"	0.76	1.06	0.56	----
20-089S	1/4" x 1/8"	0.98	1.08	0.56	----
20-090S	1/4" x 1/4"	0.98	1.26	0.75	----
20-091S	3/8" x 1/4"	1.07	1.48	0.75	----

FEMALE ELBOW



Part #	Tube O.D. x Female NPTF	A	B	Body Size	Approx. Wt. Lbs.	
20-192	1/8" x 1/8"	0.78	0.82	0.31	0.02	----
20-094	5/32" x 1/8"	0.68	0.82	0.37	0.02	----
20-089	1/4" x 1/8"	0.91	0.75	0.37	0.06	----
20-090	1/4" x 1/4"	1.03	1.03	0.50	0.11	----
20-091	3/8" x 1/4"	0.98	0.95	0.50	0.16	----

AQ70-P **3009**

Life is really simple, but we insist on making it complicated.

- Confucius

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

SWIVEL MALE RUN TEE



Part #	Tube O.D. x Male NPTF	A	B	Hex	Approx. Wt. Lbs.	
20-160	1/8" x 1/8"	0.65	0.86	0.43	0.08	----
20-161	5/32" x 1/8"	0.67	1.04	0.43	0.09	----
20-162	1/4" x 1/8"	0.92	1.04	0.44	0.09	----
20-163	1/4" x 1/4"	0.92	1.13	0.56	0.11	----
20-164	3/8" x 1/4"	0.94	1.19	0.56	0.11	----
20-165	3/8" x 3/8"	0.96	1.24	0.50	0.12	----
20-174	1/2" x 1/4"	1.12	1.18	0.51	0.16	----
20-166	1/2" x 3/8"	1.14	1.31	0.68	0.14	----
20-167	1/2" x 1/2"	1.14	1.61	0.87	0.16	----

AQ71-PS **56440** 3103 **171PL** KQY **12-468** 50-571 **271-OFS** 11715

FIXED MALE RUN TEE



Part #	Tube O.D. x Male NPTF	A	B	Body Size	Approx. Wt. Lbs.	
20-095	1/8" x 1/8"	0.65	0.72	0.31	0.04	----
20-097	3/16" x 1/8"	0.75	0.73	0.37	0.06	----
20-098	1/4" x 1/8"	0.92	0.74	0.37	0.08	----
20-093	1/4" x 1/4"	0.92	0.92	0.43	0.10	----
20-099	3/8" x 1/8"	0.94	0.82	0.50	0.14	----
20-100	3/8" x 1/4"	0.98	0.98	0.50	0.12	----
20-101	3/8" x 3/8"	1.05	1.05	0.62	0.10	----
20-102	1/2" x 3/8"	1.14	1.05	0.62	0.18	----

AQ71-P

SWIVEL MALE BRANCH TEE



Part #	Tube O.D. x Male NPTF	A	B	Hex	Approx. Wt. Lbs.	
20-103	1/8" x 1/8"	0.65	0.81	0.31	0.04	----
20-104*	5/32" x 10-32"*	0.65	0.71	0.31	0.04	----
20-109	5/32" x 1/8"	0.67	0.94	0.37	0.06	----
20-105	1/4" x 1/8"	0.92	0.97	0.37	0.08	----
20-106	1/4" x 1/4"	0.92	1.09	0.55	0.10	----
20-107	3/8" x 1/4"	0.96	1.14	0.56	0.18	----
20-108	3/8" x 3/8"	0.96	1.23	0.69	0.16	----
20-110	1/2" x 3/8"	1.16	1.34	0.69	0.24	----
20-111	1/2" x 1/2"	1.16	1.64	0.87	0.28	----

* Furnished with gaskets

FIXED MALE BRANCH TEE



Part #	Tube O.D. x Male NPTF	A	B	Body Size	Approx. Wt. Lbs.	
20-112	1/8" x 1/8"	0.69	0.72	0.31	0.04	----
20-113	5/32" x 1/8"	0.69	0.65	0.31	0.04	----
20-115	1/4" x 1/8"	0.92	0.74	0.37	0.12	----
20-116	1/4" x 1/4"	0.91	0.91	0.43	0.10	----
20-117	3/8" x 1/8"	0.98	0.80	0.50	0.08	----
20-118	3/8" x 1/4"	0.98	0.97	0.50	0.12	----
20-119	3/8" x 3/8"	0.98	0.97	0.50	0.14	----
20-120	1/2" x 3/8"	1.16	1.05	0.62	0.18	----

AQ72-P

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

UNION "Y"



Part #	Tube O.D. 1 X 2	A	B	Approx. Wt. Lbs.	
20-551	5/32" x 5/32"	1.36	0.81	0.11	----
20-552	1/4" x 1/8"	1.61	1.06	0.12	----
20-553	1/4" x 1/4"	1.81	1.16	0.14	----

BULKHEAD UNION



Part #	Tube O.D. A	B	C	Hex	Approx. Wt. Lbs.	
20-124	1/8"	1.12	7/16-20	0.62	0.03	----
20-125	5/32"	1.12	7/16-20	0.62	0.03	----
20-126	3/16"	1.27	1/2-20	0.68	0.04	----
20-127	1/4"	1.69	1/2-20	0.68	0.06	----
20-128	3/8"	1.69	3/4-16	0.81	0.13	----
20-129	1/2"	1.85	15/16-20	1.12	0.16	----

AQ82-P **6590** 62PLBH **KQE** 12-029 **50-582** 282-OF **1174**

FEMALE BULKHEAD UNION



Part #	Tube O.D. x Female NPTF	A	Hex	Approx. Wt. Lbs.	
20-170	1/4" x 1/8"	1.19	0.68	0.08	----
20-171	1/4" x 1/4"	1.36	0.75	0.10	----
20-172	3/8" x 1/4"	1.71	0.75	0.14	----

AQ86-P **1166BH**

Dimension data can change without notice. Please call us when dimensions are critical.

CROSS



Size	Size	A	B	Body Size	
20-142	1/4"	1.03	2.06	0.37	----
20-143	3/8"	1.06	2.12	0.50	----

REDUCER - NICKEL PLATED - TUBE OD X STUD

Part #	Tube O.D. 1 X 2	A	B	Approx. Wt. Lbs.	
20-510	1/8" x 1/4"	1.38	0.39	0.02	----
20-511	5/32" x 1/4"	1.33	0.35	0.02	----
20-512	1/4" x 3/8"	1.50	0.51	0.04	----

67PPL **286PP**

PLASTIC PLUG



Part #	Tube O.D.	A	Approx. Wt. Lbs.	
20-009	5/32"	1.16	0.01	----
20-010	1/4"	1.40	0.01	----
20-011	3/8"	1.40	0.02	----
20-013	1/2"	1.50	0.02	----

284PP **AQ59** 209-OF **1129** 6900 **639PL** 12-004 **50-526**

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

NICKEL PLATED PUSH-IN FITTINGS
with GLOBAL THREAD

• NPTF • BSPP • BSPT • ISO 7 • ISO 228 • G THREAD • J THREAD

- Saves time and money
- No stripped threads
- No stripped parts
- Reduce inventory
- Completely reusable
- Quick installation
- No pitch identification

Component Parts and Materials	
Body	Brass - Nickel Plated
Thrust Ring	Acetalic Resin/ Glass filled Nylon
Sleeve	Brass - Nickel Plated
Gripper Collet	Stainless Steel
Safety Ring	PA66
Lip Seal (1/8 O-Ring Seal)	NBR 70
Thread Seal	NBR 70

Max Operating Pressure: Vacuum to 290PSI.
Min Temperature: -4°F
Max Temperature: 176°F
Tubing: Nylon, Polyethylene, Polyurethane.
- For best results use 95 Durometer
Media: Compressed air, water, vacuum

• Tolerance
+/- .02 on all dimensions. Dimension data can change without notice. Please call us when dimensions are critical.

GLOBAL THREAD

Works With Inch or Metric Threads

GLOBAL THREAD
NPT • BSPT • RC • NPTF • BSPP • G

"Global Thread" fittings can be assembled with female threads produced to the following standards: **Tapered NPTF**
Parrallel (BSPP, BSP, ISO 7)
Tapered (BSPT, PT, ISO 7, ISO 228)

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

NICKEL PLATED PUSH-IN FITTINGS

UNION CONNECTOR



Part #	Tube O.D.	A	B	Approx. Wt. Lbs.	
20-017N	1/8”	1.06	0.34	0.03	----
20-018N*	5/32”	1.20	0.41	0.03	----
20-016N	5/32" x 1/4"	1.20	0.40	0.04	----
20-019N*	1/4”	1.38	0.49	0.05	----
20-015N*	5/16"	1.46	0.57	0.06	----
20-020N*	3/8”	1.69	0.69	0.06	----
20-022N	3/8" x 1/4"	1.69	0.68	0.06	----
20-021N*	1/2”	1.93	0.81	0.18	----
20-024N	1/2" x 3/8"	1.84	0.80	0.17	----

62PL **88040**

* Available in SS

UNION TEE



Part #	Tube O.D.	A	Body Size	Approx. Wt. Lbs.	
20-025N	1/8”	0.67	0.35	0.04	----
20-026N*	5/32”	0.67	0.35	0.04	----
20-028N*	1/4”	0.83	0.43	0.09	----
20-031N*	5/16”	0.87	0.51	0.10	----
20-029N*	3/8”	1.04	0.63	0.13	----
20-030N*	1/2”	1.20	0.74	0.24	----

164PL **88230**

* Available in SS

UNION ELBOW



Part #	Tube O.D.	A	Body Size	Approx. Wt. Lbs.	
20-150N	1/8”	0.67	0.35	0.02	----
20-151N*	5/32”	0.67	0.35	0.04	----
20-152N*	1/4”	0.83	0.43	0.06	----
20-155N*	5/16”	0.87	0.51	0.08	----
20-153N*	3/8”	1.04	0.63	0.09	----
20-154N*	1/2”	1.20	0.75	0.18	----

165PL **88130**

* Available in SS

FEMALE CONNECTOR



Part #	Tube O.D. x Female NPTF	A	Hex	Approx. Wt. Lbs.	
20-032N	1/8” x 1/8”	0.93	0.51	0.04	----
20-038N	1/8” x 1/4”	1.14	0.63	0.04	----
20-034N	1/4” x 1/8”	1.06	0.51	0.06	----
20-035N	1/4” x 1/4”	1.26	0.63	0.09	----
20-036N	3/8” x 1/4”	1.38	0.71	0.09	----
20-037N	3/8” x 3/8”	1.38	0.79	0.12	----

66PL **88030**

Today is a GOOD day.

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

MALE CONNECTOR



GLOBAL THREAD
NPT • BSPT • RC • NPTF • BSPP • G

• Can be purchased with NPTF threads upon request

* Available in stainless steel

Part #	Tube O.D. x Male Global Thread	A	Hex	Approx. Wt. Lbs.	
20-047N	1/8” x 10-32”	0.75	0.31	0.02	----
20-048N	1/8” x 1/8”	0.77	0.43	0.02	----
20-023N	1/8” x 1/4”	0.97	0.55	0.04	----
20-049N*	5/32” x 10-32”	0.83	0.39	0.02	----
20-050N*	5/32” x 1/8”	0.83	0.43	0.03	----
20-046N*	5/32” x 1/4”	0.98	0.55	0.05	----
20-053N*	1/4” x 10-32”	0.97	0.51	0.03	----
20-054N*	1/4” x 1/8”	0.98	0.51	0.06	----
20-055N*	1/4” x 1/4”	0.98	0.55	0.10	----
20-056N	1/4” x 3/8”	0.98	0.71	0.08	----
20-530N*	5/16” x 1/8”	0.98	0.55	0.05	----
20-531N*	5/16” x 1/4”	1.08	0.55	0.10	----
20-532N	5/16” x 3/8”	1.08	0.71	0.08	----
20-057N	3/8” x 1/8”	1.38	0.67	0.06	----
20-058N*	3/8” x 1/4”	1.32	0.67	0.05	----
20-059N*	3/8” x 3/8”	1.32	0.71	0.08	----
20-062N	3/8” x 1/2”	1.32	0.87	0.08	----
20-841N	1/2" x1/8"	1.03	0.79	0.12	----
20-060N	1/2” x 1/4”	1.54	0.79	0.11	----
20-061N*	1/2” x 3/8”	1.42	0.79	0.12	----
20-063N*	1/2” x 1/2”	1.58	0.87	0.14	----

MALE CONNECTOR WITH INTERNAL HEX



Part #	Tube O.D. x Male Global Thread	A	Hex	Approx. Wt. Lbs.	
20-842N	1/8” x 10-32” UNF	0.71	0.10	0.02	----
20-847N	5/32" x 10-32 UNF	0.79	0.10	0.02	----
20-846N	5/32" x 1/8"	0.71	0.12	0.03	----
20-845N	1/4” x 10-32” UNF	0.93	0.10	0.03	----
20-843N	1/4" x 1/8"	0.93	0.16	0.06	----
20-844N	1/4" x 1/4"	0.85	0.16	0.10	----

68PL **87000**

FIXED MALE ELBOW



Part #	Tube O.D. x Male NPTF	A	B	Body Size	Approx. Wt. Lbs.	
20-068N	1/4” x 1/8”	0.83	0.73	0.43	0.06	----
20-069N	1/4” x 1/4”	0.83	0.91	0.43	0.08	----
20-072N	3/8” x 1/4”	1.04	1.04	0.63	0.09	----
20-073N	3/8” x 3/8”	1.04	1.00	0.63	0.12	----

W169PLNS **8100**

The best and most beautiful things in the world cannot be seen or even touched - they must be felt with the heart.

- Helen Keller

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

SWIVEL MALE ELBOW



GLOBAL THREAD
NPT • BSPT • RC • NPTF • BSPP • G

• Can be purchased with NPTF threads upon request

* Available in stainless steel

Part #	Tube O.D. x Male Global Thread	A	B	Hex	Approx. Wt. Lbs.	
20-079N	1/8” x 1/8”	0.67	0.78	0.51	0.07	----
20-535N	1/8” x 1/4”	0.67	0.95	0.59	0.06	----
20-076N*	5/32” x 10-32”	0.67	0.95	0.59	0.04	----
20-080N*	5/32” x 1/8”	0.67	0.79	0.51	0.05	----
20-848N*	5/32" x 1/4"	0.67	1.00	0.59	0.05	----
20-081N*	1/4” x 1/8”	0.83	0.87	0.51	0.08	----
20-082N*	1/4” x 1/4”	0.83	0.98	0.59	0.10	----
20-086N	1/4” x 3/8”	0.83	1.10	0.67	0.09	----
20-537N*	5/16" x 1/8"	0.91	0.98	0.51	0.06	----
20-538N*	5/16” x 1/4”	0.89	1.02	0.59	0.07	----
20-539N	5/16” x 3/8”	0.87	1.10	0.67	0.08	----
20-087N	3/8” x 1/8”	1.04	1.02	0.51	0.09	----
20-083N*	3/8” x 1/4”	1.04	1.10	0.59	0.10	----
20-084N*	3/8” x 3/8”	1.04	1.18	0.67	0.20	----
20-088N*	3/8” x 1/2”	1.04	1.30	0.83	0.19	----
20-184N	1/2" x 1/4"	1.24	1.30	0.59	0.17	----
20-085N*	1/2” x 3/8”	1.20	1.24	0.59	0.18	----
20-092N*	1/2” x 1/2”	1.20	1.42	0.83	0.24	----

W169PL **87110**

FEMALE SWIVEL ELBOW



Part #	Tube O.D. x Female NPTF	A	B	Hex	
20-094N	5/32" x 1/8"	0.669	0.994	0.354	----
20-089N	1/4" x 1/8"	0.826	1.023	0.433	----
20-090N	1/4" x 1/4"	0.826	1.200	0.433	----
20-762N	3/8" x 1/8"	0.885	1.082	0.511	----
20-091N	3/8" x 1/4"	0.885	1.240	0.511	----

SWIVEL MALE RUN TEE



GLOBAL THREAD
NPT • BSPT • RC • NPTF • BSPP • G

• Can be purchased with NPTF threads upon request

Part #	Tube O.D. x Male Global Thread	A	B	Hex	Approx. Wt. Lbs.	
20-095N	1/8" x 1/8"	0.67	0.81	0.51	0.05	----
20-851N	1/8" x 1/4"	0.67	0.95	0.59	0.06	----
20-852N	5/32" x 1/8"	0.67	0.79	0.51	0.07	----
20-853N	5/32" x 1/4"	0.67	0.95	0.59	0.07	----
20-162N	1/4” x 1/8”	0.83	0.87	0.51	0.09	----
20-163N	1/4” x 1/4”	0.83	0.98	0.59	0.11	----
20-164N	1/4" x 3/8"	0.83	1.10	0.59	0.11	----
20-159N	3/8" x 1/8"	1.04	1.07	0.59	0.12	----
20-168N	3/8" x 1/4"	1.04	1.10	0.59	0.12	----
20-165N	3/8” x 3/8”	1.04	1.18	0.67	0.12	----
20-181N	3/8" x 1/2"	1.20	1.24	0.59	0.15	----
20-174N	1/2” x 1/4”	1.20	1.24	0.59	0.16	----
20-166N	1/2” x 3/8”	1.20	1.30	0.67	0.14	----
20-167N	1/2" x 1/2"	1.20	1.42	0.83	0.17	----

W171PL **87222**

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

NICKEL PLATED PUSH-IN FITTINGS

SWIVEL MALE BRANCH TEE



GLOBAL THREAD
NPT • BSPT • RC • NPTF • BSPP • G

• Can be purchased with NPTF threads upon request

Part #	Tube O.D. x Male Global Thread	A	B	Hex	Approx. Wt. Lbs.	
20-103N	1/8” x 1/8”	0.67	0.78	0.51	0.04	----
20-104N	5/32” x 10-32”	0.67	0.79	0.31	0.04	----
20-109N	5/32" x 1/8"	0.70	0.79	0.51	0.06	----
20-850N	5/32" x 1/4"	0.67	1.00	0.59	0.06	----
20-105N	1/4” x 1/8”	0.83	0.87	0.51	0.08	----
20-106N	1/4” x 1/4”	0.83	0.98	0.59	0.10	----
20-156N	1/4" x 3/8"	1.043	1.10	0.59	0.18	----
20-157N	3/8" x 1/8"	1.04	1.08	0.59	0.18	----
20-107N	3/8” x 1/4”	1.04	1.10	0.59	0.18	----
20-108N	3/8” x 3/8”	1.04	1.18	0.67	0.16	----
20-158N	3/8" x 1/2"	1.04	1.30	0.82	0.18	----
20-112N	1/2" x 1/4"	1.20	1.24	0.59	0.23	----
20-110N	1/2” x 3/8”	1.20	1.30	0.67	0.24	----
20-111N	1/2” x 1/2”	1.20	1.42	0.82	0.28	----

* Available in stainless steel

W172PL **87210**

BULKHEAD UNION



Part #	Tube O.D.	A	Hex	Approx. Wt. Lbs.	
20-124N	1/8"	1.03	0.55	0.04	----
20-125N*	5/32"	1.22	0.67	0.05	----
20-127N*	1/4”	1.38	0.67	0.06	----
20-123N*	5/16”	1.45	0.74	0.08	----
20-128N*	3/8”	1.69	0.94	0.13	----
20-129N*	1/2"	1.93	1.02	0.15	----

* Available in stainless steel

62PLBH **88050**

UNION "Y"



Part #	Tube O.D.	A	B	Approx. Wt. Lbs.	
20-553N	1/4” x 1/4”	1.44	0.53	0.14	----

662PL **88310**

REDUCER

Part #	Tube O.D. 2	Tube O.D. 1	A	
20-510N	1/4"	1/8"	1.142	----
20-511N	1/4"	5/32"	1.181	----
20-512N	3/8"	1/4"	1.496	----
20-513N	1/2"	1/4"	1.693	----
20-514N	1/2"	3/8"	1.693	----

67PPL **88700**

Also available:
- Nylon plug
- Single banjo
- Double banjo
- Push fit cartridges and tools

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

CHROME PLATED BRASS MINI BALL VALVES

- Compact Design
- Max Working Pressure 250 psi
- Optional colors of handle plate for identification

PUSH-IN X PUSH-IN

Part #	Size	Box/Case	Wgt.	
28400	1/8	30/300	.07	----
28401	1/4	30/300	.10	----
28402	3/8	20/200	.21	----

PUSH-IN X MALE PIPE

Part #	Size Tube x MIP	Box/ Case	Wgt.	
28403	5/32 x 1/8	30/300	.08	----
28407	1/4 x 1/8	30/300	.08	----
28404	1/4 x 1/4	30/300	.10	----
28405	3/8 x 3/8	20/200	.17	----

FIP X FIP

Part #	Size	Box/Case	Wgt.	
46650	1/8	30/300	.11	----
46651	1/4	30/300	.10	----
46652	3/8	20/200	.14	----
46653	1/2	15/150	.25	----

MIP X FIP

Part #	Size	Box/Case	Wgt.	
46660	1/8	30/300	.11	----
46661	1/4	30/300	.10	----
46662	3/8	20/200	.14	----
46663	1/2	15/150	.25	----

PANEL MOUNT DESIGN

FIP X FIP ANGLE

Part #	Size	Box/Case	Wgt.	
46670	1/8	20/200	.19	----
46671	1/4	20/200	.20	----
46672	3/8	25/250	.11	----

3-WAY FIP - OPEN CENTER

Part #	Size	Box/Case	Wgt.	
466900	1/8	25/250	.13	----
466901	1/4	20/200	.21	----
466902	3/8	20/200	.21	----

3-WAY FIP - CLOSED CENTER

Part #	Size	Box/Case	Wgt.	
46680	1/8	25/250	.13	----
46681	1/4	20/200	.21	----
46682	3/8	20/200	.21	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

NICKEL PLATED METRIC PUSH-IN FITTINGS

UNION



Part #	Tube O.D. (mm)	Tube O.D. (mm)	A	B	
20-723N	3		1.014	0.332	----
20-600N*	4		1.190	0.410	----
20-724N	5		1.287	0.449	----
20-725N	6	4	1.248	0.488	----
20-601N*	6		1.326	0.488	----
20-726N	8	6	1.365	0.566	----
20-727N*	8		1.404	0.566	----
20-728N	10	8	1.638	0.683	----
20-603N*	10		1.638	0.683	----
20-729N	12	10	1.833	0.800	----
20-604N*	12		1.833	0.800	----
20-730N	14		1.911	0.839	----

* Available in SS

UNION TEE



Part #	Tube O.D. (mm)	A	B	Body Size	
20-741N	3	1.326	0.663	0.351	----
20-610N*	4	1.326	0.663	0.351	----
20-742N	5	1.560	0.780	0.429	----
20-611N*	6	1.638	0.819	0.429	----
20-612N*	8	1.755	0.878	0.507	----
20-613N*	10	2.067	1.034	0.624	----
20-614N*	12	2.379	1.190	0.741	----
20-743N	14	2.379	2.535	0.741	----

* Available in SS

UNION ELBOW



Part #	Tube O.D. (mm)	A	Body Size	
20-738N	3	0.663	0.51	----
20-206N*	4	0.663	0.351	----
20-739N	5	0.780	0.429	----
20-660N*	6	0.780	0.429	----
20-661N*	8	0.878	0.507	----
20-807N*	10	1.034	0.624	----
20-808N*	12	1.190	0.741	----
20-740N	14	1.268	0.741	----

* Available in SS

UNION Y



Part #	Tube O.D. (mm)	B	A	
20-744N	3	0.390	1.131	----
20-813N	4	0.429	1.248	----
20-745N	5	0.527	1.365	----
20-814N	6	0.527	1.424	----
20-815N	8	0.605	1.599	----
20-746N	10	0.728	1.890	----

PLUG



Part #	Tube O.D. (mm)	A	
20-748N	4	0.917	----
20-749N	5	0.956	----
20-750N	6	0.956	----
20-751N	8	1.014	----
20-752N	10	1.112	----
20-753N	12	1.190	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

NICKEL PLATED METRIC PUSH-IN FITTINGS

METRIC TUBE STRAIGHT MALE



GLOBAL THREAD
NPT • BSPT • RC • NPTF • BSPP • G

• Can be purchased with BSPP or BSPT Threads

* Available in SS

Part #	Tube O.D. (mm)	Global Thread	A	Hex	
20-630N*	4	1/8"	0.702	0.429	----
20-631N*	4	1/4"	0.760	0.546	----
20-700N	5	1/8"	0.78	0.429	----
20-701N	5	1/4"	0.78	0.546	----
20-632N*	6	1/8"	0.78	0.546	----
20-633N*	6	1/4"	0.819	0.546	----
20-628N	6	3/8"	0.90	0.546	----
20-629N	6	1/2"	0.92	0.546	----
20-702N*	8	1/8"	0.955	0.546	----
20-634N*	8	1/4"	0.858	0.546	----
20-635N	8	3/8"	0.897	0.663	----
20-703N	8	1/2"	0.897	0.663	----
20-636N*	10	1/4"	1.092	0.663	----
20-637N*	10	3/8"	1.092	0.663	----
20-704N*	10	1/2"	1.014	0.663	----
20-801N	12	1/4"	1.267	0.78	----
20-638N*	12	3/8"	1.267	0.78	----
20-705N*	12	1/2"	1.209	0.78	----
20-706N	14	3/8"	1.287	0.858	----
20-707N	14	1/2"	1.248	0.858	----

METRIC TUBE INTERNAL HEX



Part #	Tube O.D. (mm)	Global Thread	A	Hex	
20-619N	3	M5	0.31	0.31	----
20-620N	4	1/8"	0.71	0.43	----
20-621N*	4	M5	0.39	0.38	----
20-622N	4	M7 x 1"	0.83	0.38	----
20-623N	6	1/4"	0.83	0.55	----
20-624N	6	1/8"	0.85	0.47	----
20-625N*	6	M5	0.47	0.47	----
20-626N	8	1/4"	0.88	0.55	----
20-627N	8	1/8"	0.98	0.55	----

METRIC TUBE SWIVEL MALE ELBOW



GLOBAL THREAD
NPT • BSPT • RC • NPTF • BSPP • G

• Can be purchased with BSPP or BSPT Threads

* Available in SS w BSPP or BSPT Threads

Part #	Tube O.D. (mm)	Global Thread	A	B	Hex	
20-708N*	4	1/8"	0.663	0.780	0.507	----
20-709N*	4	1/4"	0.663	0.936	0.585	----
20-710N	5	1/8"	0.780	0.858	0.507	----
20-642N*	6	1/8"	0.819	0.858	0.507	----
20-803N*	6	1/4"	0.819	0.975	0.585	----
20-711N*	8	1/8"	0.878	0.917	0.507	----
20-805N*	8	1/4"	0.878	1.014	0.585	----
20-655N	8	3/8"	0.878	1.092	0.663	----
20-712N	8	1/2"	0.878	1.404	0.819	----
20-656N*	10	1/4"	1.034	1.092	0.585	----
20-657N*	10	3/8"	1.034	1.170	0.663	----
20-713N*	10	1/2"	1.034	1.287	0.819	----
20-658N*	12	3/8"	1.190	1.287	0.663	----
20-659N*	12	1/2"	1.190	1.404	0.819	----
20-714N	14	3/8"	1.268	1.404	0.663	----
20-715N	14	1/2"	1.268	1.443	0.819	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

METRIC TUBE SWIVEL MALE BRANCH TEE



• Can be purchased with BSPP or BSPT threads

* Available in SS w/BSPP or BSPT threads

Part #	Tube O.D. (mm)	Global Thread	A	B	Hex	
20-680N*	4	1/8"	0.663	0.780	0.507	----
20-716N*	4	1/4"	0.663	0.936	0.585	----
20-717N	5	1/8"	0.78	0.858	0.507	----
20-682N*	6	1/8"	0.819	0.858	0.507	----
20-683N*	6	1/4"	0.819	0.975	0.585	----
20-809N*	8	1/8"	0.877	0.917	0.507	----
20-684N*	8	1/4"	0.877	1.014	0.585	----
20-690N	8	3/8"	0.886	1.024	0.585	----
20-691N	8	1/2"	0.886	1.122	0.585	----
20-686N*	10	1/4"	1.033	1.092	0.585	----
20-687N*	10	3/8"	1.033	1.170	0.663	----
20-810N*	10	1/2"	1.033	1.287	0.819	----
20-688N*	12	3/8"	1.189	1.287	0.663	----
20-689N*	12	1/2"	1.189	1.404	0.819	----
20-718N	14	3/8"	1.267	1.404	0.663	----
20-719N	14	1/2"	1.267	1.443	0.819	----

METRIC TUBE SWIVEL MALE RUN TEE



• Can be purchased with BSPP threads

Part #	Tube O.D. (mm)	Global Thread	A	B	Hex	
20-670N	4	1/8"	0.663	0.780	0.507	----
20-720N	4	1/4"	0.663	0.936	0.585	----
20-721N	5	1/8"	0.780	0.858	0.507	----
20-672N	6	1/8"	0.819	0.858	0.507	----
20-673N	6	1/4"	0.819	0.975	0.585	----
20-811N	8	1/8"	0.819	0.917	0.507	----
20-674N	8	1/4"	0.878	1.014	0.585	----
20-668N	8	3/8"	0.885	1.063	0.585	----
20-669N	8	1/2"	0.885	1.063	0.585	----
20-676N	10	1/4"	0.878	1.092	0.585	----
20-677N	10	3/8"	1.034	1.170	0.663	----
20-722N	10	1/2"	1.034	1.287	0.819	----
20-678N	12	3/8"	1.190	1.287	0.663	----
20-679N	12	1/2"	1.190	1.404	0.819	----

BULKHEAD



* Available in SS

Part #	Tube O.D. (mm)	M	A	Hex	
20-731N	3	M10x1	1.014	0.546	----
20-732N*	4	MI2x1	1.229	0.663	----
20-733N	5	M14x1	1.287	0.663	----
20-734N*	6	M14x1	1.365	0.663	----
20-735N*	8	M16x1	1.443	0.741	----
20-736N*	10	M20x1	1.677	0.936	----
20-737N*	12	M22x1	1.872	1.014	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

Composite Body Push-In Fittings

• For Food Grade,
see page 298-299

Specifications

Fluid admitted	Air
Working pressure range	0-150 PSI (10BAR)
Min. Burst pressure	340PSI (23BAR)
Working Temperature range	0°F ~160°F

Materials of Construction:

1	Body	Composite Polyacetal (hemopolymer,copolymer)
2	Body	Brass
3	Tube Release	Acetal Resin
4	Retainer	Brass
5	Gripper Ring	Stainless Steel
6	Spacer	Brass
7	O-Ring	NBR 70
8	Threads	Brass w/ white sealant

The latest generation of composite material is used in the body construction in addition to brass on threaded components and stainless steel on the tube gripper.

• **Tolerance**
+/- .02 on all dimensions. Dimension data can change without notice. Please call us when dimensions are critical.

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

UNION

Part #	Tube O.D.	Approx. Wt. Lbs.	
20-017C	1/8"	0.01	----
20-018C	5/32"	0.01	----
20-001C	3/16"	0.01	----
20-019C	1/4”	0.01	----
20-015C	5/16"	0.01	----
20-020C	3/8”	0.02	----
20-021C	1/2"	0.03	----
20-016C	1/4" x 5/32"	0.01	----
20-515C	5/16" x 1/4"	0.01	----
20-022C	3/8" x 1/4"	0.01	----
20-516C	3/8" x 5/16"	0.02	----
20-024C	1/2" x 3/8"	0.03	----

PQ62P

UNION TEE

Part #	Tube O.D.	Approx. Wt. Lbs.	
20-025C	1/8"	0.01	----
20-026C	5/32"	0.01	----
20-027C	3/16"	0.02	----
20-028C	1/4”	0.02	----
20-031C	5/16"	0.02	----
20-029C	3/8”	0.02	----
20-030C	1/2"	0.08	----

PQ64P

90° UNION ELBOW

Part #	Tube O.D.	Approx. Wt. Lbs.	
20-150C	1/8"	0.01	----
20-151C	5/32"	0.01	----
20-149C	3/16"	0.01	----
20-152C	1/4”	0.02	----
20-155C	5/16"	0.02	----
20-153C	3/8”	0.02	----
20-154C	1/2"	0.02	----

PQ65P

UNION "Y" CONNECTOR

Part #	Tube O.D.	Approx. Wt. Lbs.	
20-551C	5/32"	0.01	----
20-553C	1/4”	0.02	----
20-182C	5/16"	0.02	----
20-555C	3/8”	0.02	----
20-185C	1/2	0.07	----

PQ89P

FEMALE CONNECTOR

- Brass

Part #	Tube O.D. x Female NPT	Approx. Wt. Lbs.	
20-034C	1/4” x 1/8”	0.02	----
20-035C	1/4” x 1/4”	0.04	----
20-036C	3/8” x 1/4”	0.04	----
20-037C	3/8” x 3/8”	0.06	----

PQ66P

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

MALE CONNECTOR

• Nickel Plated

• See broader range of sizes on page 104
N/P push-in fittings

Part #	Tube O.D. x Male NPT	Approx. Wt. Lbs.	
20-050C	5/32" x 1/8"	0.02	----
20-053C	1/4" x 10-32"	0.02	----
20-054C	1/4” x 1/8”	0.02	----
20-055C	1/4” x 1/4”	0.02	----
20-056C	1/4” x 3/8”	0.04	----
20-530C	5/16" x 1/8"	0.05	----
20-531C	5/16" x 1/4"	0.05	----
20-057C	3/8" x 1/8"	0.05	----
20-058C	3/8” x 1/4”	0.06	----
20-059C	3/8” x 3/8”	0.06	----
20-062C	3/8” x 1/2”	0.08	----
20-060C	1/2” x 1/4”	0.06	----
20-061C	1/2” x 3/8”	0.08	----
20-063C	1/2” x 1/2”	0.10	----

PQ68P

SWIVEL MALE ELBOW

• Swivels for installation only.
• Not a live swivel

* Global Thread

Part #	Tube O.D. x Male NPT	Approx. Wt. Lbs.	
20-079C	1/8" x 1/8"	0.01	----
20-535C*	1/8" x 1/4"	0.01	----
20-517C*	3/16" x 1/4"	0.01	----
20-080C*	5/32" x 1/8"	0.01	----
20-077C*	5/32" x 1/4"	0.01	----
20-049C*	5/32" x 10/32"	0.01	----
20-078C	1/4" x 10-32	0.01	----
20-081C	1/4” x 1/8”	0.02	----
20-082C	1/4” x 1/4”	0.04	----
20-086C	1/4” x 3/8”	0.06	----
20-518C*	1/4" x 1/2"	0.07	----
20-537C	5/16" x 1/8"	0.04	----
20-538C	5/16" x 1/4"	0.04	----
20-539C*	5/16" x 3/8"	0.06	----
20-087C	3/8” x 1/8’	0.04	----
20-083C	3/8” x 1/4”	0.08	----
20-084C	3/8” x 3/8”	0.10	----
20-088C	3/8” x 1/2”	0.12	----
20-184C	1/2" x 1/4"	0.14	----
20-085C	1/2" x 3/8"	0.16	----
20-092C	1/2" x 1/2"	0.18	----

PQ69PS

LONG PATTERN MALE ELBOWS

Part #	Tube O.D. x Thread	Approx. Wt. Lbs.	
20-572C	1/4 X 1/8	0.03	----
20-573C	1/4 X 1/4	0.05	----
20-574C	1/4 X 3/8	0.06	----
20-579C	3/8 X 1/4	0.09	----
20-580C	3/8 X 3/8	0.12	----
20-581C	3/8 X 1/2	0.14	----
20-582C	1/2 X 1/4	0.16	----
20-583C	1/2 X 3/8	0.18	----
20-584C	1/2 X 1/2	0.20	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

FEMALE SWIVEL ELBOWS

Part #	Tube O.D. x Female NPT	Approx. Wt. Lbs.	
20-089C	1/4 X 1/8	0.05	----
20-090C	1/4 X 1/4	0.06	----
20-591C	1/4 X 3/8	0.07	----
20-091C	3/8 X 1/4	0.10	----
20-595C	3/8 X 3/8	0.14	----
20-596C	3/8 X 1/2	0.15	----
20-597C	1/2 X 3/8	0.20	----
20-598C	1/2 X 1/2	0.23	----

45° SWIVELS

Part #	Tube O.D. x Male NPT	Approx. Wt. Lbs.	
20-139C	1/4 X 1/8	0.04	----
20-140C	1/4 X 1/4	0.05	----

SWIVEL MALE RUN TEE

- Swivels for installation only.
- Not a live swivel

* Global Thread

Part #	Tube O.D. x Male NPT	Approx. Wt. Lbs.	
20-160C*	1/8" x 1/8"	0.03	----
20-833C*	1/8" x 1/4"	0.03	----
20-835C*	5/32" x 10-32	0.03	----
20-162C	1/4” x 1/8”	0.04	----
20-163C	1/4” x 1/4”	0.04	----
20-834C*	1/4" x 10-32	0.04	----
20-099C	3/8” x 1/8”	0.06	----
20-100C	3/8” x 1/4”	0.08	----
20-165C	3/8” x 3/8”	0.10	----
20-181C	3/8 x 1/2	0.12	----
20-174C	1/2 x 1/4	0.12	----
20-166C	1/2 x 3/8	0.14	----
20-167C	1/2 x 1/2	0.16	----

PQ71PS

SWIVEL MALE BRANCH TEE

- Swivels for installation only.
- Not a live swivel

* Global Thread

Part #	Tube O.D. x Male NPT	Approx. Wt. Lbs.	
20-103C*	1/8" x 1/8"	0.02	----
20-519C*	1/8" x 1/4"	0.03	----
20-109C*	5/32" x 1/8"	0.02	----
20-135C*	5/32" x 1/4"	0.03	----
20-104C*	5/32" x 10/32"	0.03	----
20-830C*	3/16" x 1/8"	0.03	----
20-105C	1/4” x 1/8”	0.04	----
20-106C	1/4” x 1/4”	0.06	----
20-831C*	1/4" x 10/32"	0.06	----
20-121C	1/4” x 3/8”	0.08	----
20-136C*	5/16" x 1/8"	0.04	----
20-137C*	5/16" x 1/4"	0.05	----
20-832C*	5/16" x 3/8"	0.06	----
20-107C	3/8” x 1/4”	0.10	----
20-108C	3/8” x 3/8”	0.12	----
20-158C	3/8 X 1/2	0.14	----
20-138C	1/2 X 1/4	0.14	----
20-110C	1/2 X 3/8	0.16	----
20-111C	1/2 X 1/2	0.21	----

PQ72PS

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

BULKHEAD UNION

Part #	Tube O.D.	Approx. Wt. Lbs.	
20-127C	1/4”	0.04	----
20-128C	3/8”	0.06	----
20-129C	1/2"	0.10	----

PQ82P

BULKHEAD FEMALES

Part #	Tube O.D. x Thread	Approx. Wt. Lbs.	
20-170C	1/4 X 1/8	0.04	----
20-171C	1/4 X 1/4	0.04	----
20-172C	3/8 X 1/4	0.06	----
20-173C	3/8 X 3/8	0.07	----
20-175C	1/2 X 1/4	0.07	----
20-176C	1/2 X 3/8	0.09	----
20-179C	1/2 X 1/2	0.10	----

SWIVEL "Y" CONNECTOR

• Swivels for installation only. • Not a live swivel

Part #	Tube O.D. x Male NPT	Approx. Wt. Lbs.	
20-187C	1/4 X 1/8	0.02	----
20-557C	1/4” x 1/4”	0.02	----
20-188C	3/8 X 1/4	0.04	----
20-189C	3/8 X 3/8	0.04	----
20-193C	3/8 X 1/2	0.07	----
20-194C	1/2 X 3/8	0.06	----
20-195C	1/2 X 1/2	0.09	----

PQ88PS

IN-LINE NEEDLE VALVE

Part #	Tube O.D.	Approx. Wt. Lbs.	
20-487C	1/4”	0.04	----
20-488C	5/16”	0.05	----
20-489C	3/8”	0.06	----

PQ310C

RIGHT ANGLE FLOW CONTROL METER IN

• Free flow out

Part #	Tube O.D. x Male NPT	Approx. Wt. Lbs.	
20-727C	1/4 X 1/8	0.04	----
20-728C	1/4” x 1/4”	0.04	----
20-780C	3/8 X 1/4	0.06	----
20-781C	3/8 X 3/8	0.06	----
20-782C	1/2 X 1/2	0.10	----

JPQ

RIGHT ANGLE FLOW CONTROL METER OUT

• Free flow in

Part #	Tube O.D. x Male NPT	Approx. Wt. Lbs.	
20-785C	1/4 x 1/8	0.04	----
20-786C	1/4 x 1/4	0.04	----
20-787C	3/8 x 1/4	0.06	----
20-788C	3/8 x 3/8	0.06	----
20-789C	1/2 x 1/2	0.10	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

METRIC COMPOSITE BODY PUSH-IN FITTINGS

Technical Characteristics



PART 1	BODY	COMPOSITE
PART 2	BODY	NICKEL PLATED BRASS
PART 3	TUBE RELEASE	ACETAL RESIN
PART 4	RETAINER	NICKEL PLATED BRASS
PART 5	GRIPPER RING	STAINLESS STEEL
PART 6	SPACER	COMPOSITE
PART 7	THREAD PACKING	NBR 70
PART 8	O-RING	NBR 70
PART 9	THREAD SEAL	NBR70

Operating Range

Pressure: 0 to 220 PSI (15 bar)

Vacuum: 0 to 29hg (-.99 bar)

Temperature

-5^0 F to + 175^0 F (-20^0 C to + 80^0 C)

Media

Compressed air.

Non-toxic fluids (water)

Materials

The latest generation of composite material is used in the body construction in addition to nickel-plated brass on threaded components and stainless steel on the tube gripper.

UNION

Part #	Tube O.D. (mm)	
20-600	4	----
20-601	6	----
20-602	8	----
20-603	10	----
20-604	12	----

UNION TEE

Part #	Tube O.D. (mm)	
20-610	4	----
20-862	5	----
20-611	6	----
20-612	8	----
20-613	10	----
20-614	12	----
20-861	14	----

3104

UNION ELBOW

Part #	Tube O.D. (mm)	
20-806	4	----
20-660	6	----
20-661	8	----
20-807	10	----
20-808	12	----
20-740	14	----

3102

MALE ADAPTER

Part #	Tube OD (mm)	BSPT Thread	
20-630	4	1/8”	----
20-631	4	1/4”	----
20-632	6	1/8”	----
20-633	6	1/4”	----
20-634	8	1/4”	----
20-635	8	3/8”	----
20-636	10	1/4”	----
20-637	10	3/8”	----
20-801	12	1/4”	----
20-638	12	3/8”	----

3175

NOTE: See page 102 for a complete line of male adapters with global thread.

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

SWIVEL ELBOW

Part #	Tube OD (mm)	BSPT Thread	
20-690*	4	M5	----
20-856*	4	1/8"	----
20-855*	4	1/4"	----
20-692*	5	M5	----
20-857*	5	1/8"	----
20-859*	6	M5	----
20-642	6	1/8”	----
20-803	6	1/4”	----
20-698*	6	3/8"	----
20-699*	6	1/2"	----
20-711*	8	1/8"	----
20-805	8	1/4”	----
20-655	8	3/8"	----
20-712*	8	1/2"	----
20-656	10	1/4"	----
20-657	10	3/8"	----
20-713*	10	1/2"	----
20-801	12	1/4"	----
20-658	12	3/8"	----
20-659	12	1/2"	----
20-714*	14	3/8"	----
20-854*	14	1/2"	----

* Global Thread
• BSPP Available

SWIVEL BRANCH TEE

Part #	Tube OD (mm)	BSPT Thread	
20-680*	4	1/8”	----
20-860*	4	1/4"	----
20-717*	5	1/8"	----
20-682	6	1/8”	----
20-683	6	1/4”	----
20-809	8	1/8"	----
20-684	8	1/4"	----
20-685	8	3/8"	----
20-686	10	1/4"	----
20-687	10	3/8"	----
20-810	10	1/2"	----
20-688	12	3/8"	----
20-689	12	1/2"	----
20-718*	14	3/8"	----
20-719*	14	1/2"	----

* Global Thread
• BSPP Available

SWIVEL RUN TEE

Part #	Tube OD (mm)	BSPT Thread	
20-670	4	1/8”	----
20-720*	4	1/4"	----
20-721*	5	1/8"	----
20-672	6	1/8”	----
20-673	6	1/4”	----
20-811	8	1/8"	----
20-674	8	1/4"	----
20-675	8	3/8"	----
20-676	10	1/4"	----
20-677	10	3/8"	----
20-678	12	3/8"	----
20-679	12	1/2"	----

* Global Thread
• BSPP Available

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

UNION WYE

Part #	Tube OD (mm)	
20-813	4	----
20-814	6	----
20-815	8	----
20-746	10	----
20-827	12	----

SWIVEL MALE WYE

Part #	Tube OD (mm)	Global Thread	
20-816	4	1/8"	----
20-821*	4	1/4"	----
20-817*	6	1/8"	----
20-818	6	1/4"	----
20-819*	8	1/8"	----
20-820*	8	1/4"	----
20-822*	8	3/8"	----
20-823*	10	1/4"	----
20-824*	10	3/8"	----
20-825*	10	1/2"	----
20-826*	12	3/8"	----
20-827*	12	1/2"	----

* Global Thread
• BSPP Available

Also available:
• 45° elbow swivel
• 4 position Y
• Manifolds
• Extended swivel elbows
• Bulkhead union
• Plug-in elbows and tees

Affliction comes to us, not to make us sad but sober; not to make us sorry but wise.

- H. G. Wells

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

D.O.T. PUSH-IN TUBE FITTINGS

Meets D.O.T. FMVSS 571.106 SAE J1131 Air Brake System Requirements

Benefits for Cost Savings & Engineering Project

- **Fast assembly:** No tools required. Simply push tubing in. Saves up to 75% of assembly time compared to standard air compression fittings. No loose parts to handle.
- **Fast disconnect:** Hold the collet collar with two fingers and pull out tube. No tools required.
- **Reusable:** Can be connected and disconnected several times.
- **Reliable sealing:** Using recommended tubing, full sealing is guaranteed.
- **Versatility:** Buna N O'ring standard. Viton and others available per request. Secure tube retention. Pulling on tubing only serves to tighten the connection.
- **Pre-Applied Teflon®** based pipe sealant on all male pipe threads, saving customer additional labor.
- **Full Flow Design,** provides more flow area than conventional fittings with internal tube supports even in the swivels.

DOT Fittings are constructed with an all brass captive eyelet which allows for maximum flow. The brass captive eyelet with extended length is floating and has a machined top end radius for easy installation of tubing. All male threads have a pre-applied Teflon® based pipe sealant to provide for easy assembly and leak proof seal.

- **Materials:**
  Brass
  "O" Ring: Buna - Nitrile (90 Durometer)
  EP (Ethylene Propylene)

- **Working Pressures & Temperature Ranges**
  Vacuum to 150 PSI
  -40°F to 200° F (-40°C to +93°C)

Dimension data can change without notice. Please see our website when dimensions are critical.

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

PLUG

Part #	Tube O.D.	Approx. Wt. Lbs.	
595320	5/32”	0.01	----
590400	1/4”	0.02	----
590600	3/8”	0.02	----
590800	1/2”	0.04	----

1829 **DQ59DOT** 639PMT

UNION

Part #	Tube O.D.	Approx. Wt. Lbs.	
620532	5/32”	0.06	----
620400	1/4”	0.06	----
620600	3/8”	0.13	----
620604	3/8" x 1/4"	0.15	----
620800	1/2”	0.19	----
621000	5/8”	0.30	----
621200	3/4”	0.44	----

AQ62DOT **62PMT** 1862 **DQ62DOT**

UNION TEE

Part #	Tube O.D.	Approx. Wt. Lbs.	
640400	1/4”	0.09	----
640600	3/8”	0.16	----
640800	1/2”	0.25	----
641000	5/8"	0.32	----
641200	3/4"	0.36	----

AQ64DOT **164 PMT** 1864 **DQ64DOT**

UNION ELBOW

Part #	Tube O.D.	Approx. Wt. Lbs.	
655320	5/32”	0.03	----
650400	1/4”	0.06	----
650600	3/8”	0.12	----
650800	1/2”	0.18	----

AQ65DOT **165 PMT** 1865 **DQ65DOT**

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

FEMALE CONNECTOR

Part #	Tube O.D. x Female NPTF	Approx. Wt. Lbs.	
660402	1/4” x 1/8”	0.06	----
660404	1/4” x 1/4”	0.10	----
660602	3/8” x 1/8”	0.11	----
660604	3/8” x 1/4”	0.11	----
660606	3/8” x 3/8”	0.17	----
660804	1/2” x 1/4”	0.14	----
660806	1/2” x 3/8”	0.16	----
660808	1/2” x 1/2”	0.25	----

AQ66DOT **66PMT** 1866 **DQ66DOT**

MALE CONNECTOR

Part #	Tube O.D. x Male NPTF	Approx. Wt. Lbs.	
685320	5/32” x 10/32”	0.02	----
685321	5/32” x 1/16”	0.02	----
685322	5/32” x 1/8”	0.02	----
680302	3/16” x 1/8”	0.02	----
680421	1/4" x 1/16"	0.02	----
680402	1/4” x 1/8”	0.03	----
680404	1/4” x 1/4”	0.04	----
680406	1/4” x 3/8”	0.07	----
680602	3/8” x 1/8”	0.06	----
680604	3/8” x 1/4”	0.07	----
680606	3/8” x 3/8”	0.06	----
680608	3/8” x 1/2”	0.13	----
680804	1/2” x 1/4”	0.11	----
680806	1/2” x 3/8”	0.12	----
680808	1/2” x 1/2”	0.14	----
681006	5/8” x 3/8”	0.18	----
681008	5/8” x 1/2”	0.18	----
681208	3/4” x 1/2”	0.20	----
681212	3/4” x 3/4”	0.20	----

AQ68DOT **68PM** 1868 **DQ68DOT** 68PMT

Dimension data can change without notice. Please see our website when dimensions are critical.

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

MALE ELBOW

Forged

Part #	Tube O.D. x Male NPTF	Approx. Wt. Lbs.	
695302	5/32" x 1/16"	0.03	----
695322	5/32" x 1/8"	0.03	----
690302	3/16" x 1/8"	0.03	----
690402	1/4" x 1/8"	0.08	----
690404	1/4" x 1/4"	0.06	----
690406	1/4" x 3/8"	0.11	----
690602	3/8" x 1/8"	0.08	----
690604	3/8" x 1/4"	0.09	----
690606	3/8" x 3/8"	0.11	----
690608	3/8" x 1/2"	0.20	----
690804	1/2" x 1/4"	0.22	----
690806	1/2" x 3/8"	0.22	----
690808	1/2" x 1/2"	0.24	----
691006	5/8" x 3/8"	0.30	----
691008	5/8" x 1/2"	0.32	----
691208	3/4" x 1/2"	0.32	----
691212	3/4" x 3/4"	0.34	----

AQ69DOT **169 PMTNS** 1869 **DQ69DOT**

MALE SWIVEL ELBOW

Forged

Part #	Tube O.D. x Male NPTF	Approx. Wt. Lbs.	
695322S	5/32" x 1/8"	0.07	----
690402S	1/4" x 1/8"	0.06	----
690404S	1/4" x 1/4"	0.10	----
690406S	1/4" x 3/8"	0.10	----
690602S	3/8" x 1/8"	0.10	----
690604S	3/8" x 1/4"	0.11	----
690606S	3/8" x 3/8"	0.12	----
690608S	3/8" x 1/2"	0.20	----
690804S	1/2" x 1/4"	0.16	----
690806S	1/2" x 3/8"	0.18	----
690808S	1/2" x 1/2"	0.26	----
691006S	5/8" x 3/8"	0.28	----
691008S	5/8" x 1/2"	0.30	----
691208S	3/4" x 1/2"	0.50	----
691212S	3/4" x 3/4"	0.56	----

AQ69DOTS **169PMT** 1869 **DQ69DOTS**

Weeds are flowers too, once you get to know them. – A. A. Milne

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

FEMALE ELBOW

Forged

Part #	Tube O.D. x Female NPTF	Approx. Wt. Lbs.	
700402	1/4” x 1/8”	0.06	----
700404	1/4” x 1/4”	0.10	----
700406	1/4” x 3/8”	0.16	----
700602	3/8” x 1/8”	0.15	----
700604	3/8” x 1/4”	0.12	----
700606	3/8” x 3/8”	0.17	----
700806	1/2” x 3/8”	0.26	----
700808	1/2” x 1/2”	0.30	----

AQ70DOTS **1870** DQ70DOTS **170PMTNS**

FEMALE SWIVEL ELBOW

Part #	Tube O.D. x Female NPTF	
700404S	1/4” x 1/4"	----

MALE RUN TEE

Forged

Part #	Tube O.D. x Male NPTF (1 x 3) x 2	Approx. Wt. Lbs.	
710402	1/4” x 1/8”	0.06	----
71040604	(1/4" x 3/8") x 1/4"	0.20	----
710404	1/4” x 1/4”	0.08	----
710604	3/8” x 1/4”	0.20	----
71060404	(3/8" x 1/4") x 1/4"	0.20	----
710606	3/8” x 3/8”	0.17	----
71060406	(3/8" x 1/4") x 3/8"	0.20	----
710608	3/8” x 1/2”	0.14	----
710806	1/2” x 3/8”	0.28	----

AQ71DOT **171PMTNS** 1871 **DQ71DOT**

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

You cannot escape the responsibility of tomorrow by evading it today. - Abraham Lincoln

MALE SWIVEL RUN TEE

Forged

Part #	Tube O.D. x Male NPTF	Approx. Wt. Lbs.	
710402S	1/4" x 1/8"	0.09	----
710404S	1/4" x 1/4"	0.11	----
710604S	3/8" x 1/4"	0.15	----
710606S	3/8" x 3/8"	0.14	----
710804S	1/2" x 1/4"	0.24	----
710806S	1/2" x 3/8"	0.24	----
710808S	1/2" x 1/2"	0.30	----

AQ71DOTS **171PMT** 1871 **DQ71DOTS**

MALE 45° ELBOW

Forged

Part #	Tube O.D. x Male NPTF	Approx. Wt. Lbs.	
540402	1/4" x 1/8"	0.06	----
540404	1/4" x 1/4"	0.06	----
540602	3/8" x 1/8"	0.08	----
540604	3/8" x 1/4"	0.09	----
540606	3/8" x 3/8"	0.11	----
540608	3/8" x 1/2"	0.15	----
540804	1/2" x 1/4"	0.13	----
540806	1/2" x 3/8"	0.16	----
540808	1/2" x 1/2"	0.18	----
541006	5/8" x 3/8"	0.22	----
541008	5/8" x 1/2"	0.21	----
541208	3/4" x 1/2"	0.28	----
541212	3/4" x 3/4"	0.32	----

AQ54DOT **179MTNS** 1880 **DQ54DOT**

MALE 45° SWIVEL ELBOW

Part #	Tube O.D. x Male NPTF	Approx. Wt. Lbs.	
540402S	1/4" x 1/8"	0.06	----
540404S	1/4" x 1/4"	0.09	----
540602S	3/8" x 1/8"	0.10	----
540604S	3/8" x 1/4"	0.11	----
540606S	3/8" x 3/8"	0.13	----
540804S	1/2" x 1/4"	0.14	----
540806S	1/2" x 3/8"	0.16	----
540808S	1/2" x 1/2"	0.18	----
541008S	5/8" x 1/2"	0.24	----

AQ54DOTS **179PMT** 1880 **DQ54DOTS**

MALE BRANCH TEE

Forged

Part #	Tube O.D. x Male NPTF (1 x 2) x 3	Approx. Wt. Lbs.	
720302	3/16" x 1/8"	0.07	----
720402	1/4" x 1/8"	0.10	----
720404	1/4" x 1/4"	0.10	----
720604	3/8" x 1/4"	0.14	----
72060404	(3/8" x 1/4") x 1/4"	0.20	----
720606	3/8" x 3/8"	0.15	----
720804	1/2" x 1/4"	0.20	----
720806	1/2" x 3/8"	0.24	----
720808	1/2" x 1/2"	0.32	----
72100808	(5/8" x 1/2") x 1/2"	0.20	----

AQ72DOT **172PMTNS** 1872 **DQ72DOT**

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

MALE SWIVEL BRANCH TEE

Part #	Tube O.D. x Male NPTF	Approx. Wt. Lbs.	
720402S	1/4” x 1/8”	0.12	----
720404S	1/4” x 1/4”	0.14	----
720602S	3/8" x 1/8"	0.19	----
720604S	3/8” x 1/4”	0.15	----
720606S	3/8” x 3/8”	0.17	----
720804S	1/2” x 1/4”	0.30	----
720806S	1/2” x 3/8”	0.34	----
720808S	1/2” x 1/2”	0.22	----

AQ72DOTS **172PMT** 1872 **DQ72DOTS**

FEMALE BRANCH TEE

(RUN) BRANCH

Part #	(1 & 2) x 3	
770402	1/4” x 1/8"	----
770404	1/4" x 1/4"	----
770604	3/8" x 1/4"	----

GLADHAND BULKHEAD CONNECTOR

TUBE OD x MALE NPTF

Part #	Size	
830808	1/2" x 1/2"	----

BULKHEAD UNION



Part #	Tube O.D.	Approx. Wt. Lbs.	
820400	1/4”	0.16	----
820600	3/8”	0.21	----
820800	1/2”	0.14	----
821000	5/8”	0.30	----

AQ82DOT **62PMTBH** 1874 **DQ82DOT**

FEMALE BULKHEAD UNION

Part #	Tube O.D. x Female NPTF	Approx. Wt. Lbs.	
860402	1/4" x 1/8"	0.08	----
860404	1/4" x 1/4”	0.10	----
860604	3/8” x 1/4”	0.14	----
860606	3/8” x 3/8”	0.31	----
860808	1/2” x 1/2”	0.32	----

• Jam nuts not available separately

AQ86DOT **1873** DQ86DOT **66PMTBH**

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

COMPOSITE BODY DOT AIRBRAKE FITTINGS

WARNING

- Composite DOT push-to-connect fittings are designed only for use in applications where air is utilized as an operating fluid.
- Fittings must be used in accordance with manufacturer and industry specifications.
- They are not intended for use in environments exceeding 145psi or 140 degrees F.
- The Department of Transportation FMVSS 49CFR571-106 prohibits use of this type of fitting for connections between towed and towing vehicles or between a driveshaft and chassis.
- Using Composite DOT fittings in a manner inconsistent with manufacturer specifications may result in serious injury or property damage.
- Under no circumstances shall the supplier be liable to buyer for any consequential or incidental damages of any nature whatsoever arising from nonconformity of goods, defective goods, or delay in shipment or any other breach by seller.

Please feel free to email warning@compdotfitting.com with any questions or concerns.

- One touch connection reduces installation time and cost.
- Rugged ultraviolet and vibration resistant composite body.
- Various shapes and configurations to meet vehicle applications and make installations easier.

Specifications for FMVSS (D.O.T.) and SAE Compliant Fittings

Operating Fluid	Air						
Max. Operating Pressure	145psi (1.0MPa)						
Proof Pressure	Size	5/32"	1/4"	3/8"	1/2"	5/8"	3/4"
	At 75°F (24°C)	1200psi	1200psi	1400psi	950psi	900psi	800psi
	At 200 °F (93°C)	450psi (3.1MPa)					
Recommended Fluid and Ambient Temperature*	-40°F to 140°F (-40°C to 60°C)						
Leak Rate at -40°F (-40°C)	7 Ncm^3/min. or less						
Thread	Thread Portion	ANSI/ASME B1.20.1, 1983 R1992					
	Nut	JIS B 0208 (Unified fine thread) ISO 263					
Thread Sealant	Fluorine/ Acrylic						
Applicable Standards	D.O.T. FMVSS 49 CFR 571.106, SAE J2494-3						
Applicable Tubing	Tubing conforming to both SAE J844 and D.O.T. FMVSS 49 CFR 571.106. Material: Nylon12						
Tube O.D.	5/32", 1/4", 3/8", 1/2", 5/8", 3/4"						



1. Chuck	Stainless steel or Brass
2. Body	Polybutylene Terephthalate (PBT), Brass
3/4. Tube seal, O-Ring	Buna-N, Nitrile Rubber
5. Stud	Brass
6. Sealant	Flourine/ Acrylic
7. Guide	Stainless Steel or Polyacetal (Acetal)
8. Stabilization Ring	Stainless Steel
9. Release Button	Polyacetal, POM (Acetal)
10. Tube support	Stainless Steel/ Brass

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

STRAIGHT UNION

Part #	Tube OD (inch)	Approx. Wt. Lbs.	
620532C	5/32	0.01	----
620400C	1/4	0.01	----
620600C	3/8	0.03	----
620800C	1/2	0.05	----
621000C	5/8	0.08	----

UNION TEE

	Part #	Tube OD (inch)	Approx. Wt. Lbs.	
NEW	645320C	5/32	0.02	----
	640400C	1/4	0.02	----
	640600C	3/8	0.05	----
	640800C	1/2	0.07	----
	641000C	5/8	0.13	----

UNION 90° ELBOW

Part #	Tube OD (inch)	Approx. Wt. Lbs.	
655320C	5/32	0.01	----
650400C	1/4	0.02	----
650600C	3/8	0.04	----
650800C	1/2	0.05	----

FEMALE CONNECTOR

	Part #	Tube OD (inch)	Thread NPT	Approx. Wt. Lbs.	
NEW	665302C	5/32	1/8-27	0.04	----
NEW	665304C	5/32	1/4-18	0.06	----
	660402C	1/4	1/8-27	0.04	----
	660404C	1/4	1/4-18	0.06	----
	660406C	1/4	3/8-18	0.10	----
	660602C	3/8	1/8-27	0.07	----
	660604C	3/8	1/4-18	0.07	----
	660606C	3/8	3/8-18	0.11	----
	660608C	3/8	1/2-14	0.12	----
	660802C	1/2	1/8-27	0.11	----
	660804C	1/2	1/4-18	0.13	----
	660806C	1/2	3/8-18	0.12	----
	660808C	1/2	1/2-14	0.13	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

COMPOSITE BODY D.O.T. PUSH-IN — BRASS FITTINGS

STRAIGHT MALE CONNECTOR

	Part #	App. Tube OD (inch)	Thread NPT	Approx. Wt. Lbs.	
NEW	685301C	5/32	1/16-28	0.02	----
NEW	685302C	5/32	1/8-27	0.02	----
NEW	685304C	5/32	1/4-27	0.03	----
	680402C	1/4	1/8-27	0.02	----
	680404C	1/4	1/4-18	0.03	----
	680406C	1/4	3/8-18	0.05	----
	680602C	3/8	1/8-27	0.05	----
	680604C	3/8	1/4-18	0.06	----
	680606C	3/8	3/8-18	0.06	----
	680608C	3/8	1/2-14	0.09	----
	680804C	1/2	1/4-18	0.09	----
	680806C	1/2	3/8-18	0.09	----
	680808C	1/2	1/2-14	0.09	----
	681006C	5/8	3/8-18	0.15	----
	681008C	5/8	1/2-14	0.13	----
	681208C	3/4	1/2-14	0.38	----

90° MALE ELBOW

• Fixed

	Part #	Tube OD (inch)	Thread NPT	Approx. Wt. Lbs.	
NEW	695322SC	5/32	1/8-27	0.03	----
NEW	690402SC	1/4	1/8-27	0.03	----
	690404SC	1/4	1/4-18	0.04	----
	690406SC	1/4	3/8-18	0.07	----
	690602SC	3/8	1/8-27	0.07	----
	690604SC	3/8	1/4-18	0.06	----
	690606SC	3/8	3/8-18	0.08	----
	690608SC	3/8	1/2-14	0.14	----
	690804SC	1/2	1/4-18	0.07	----
	690806SC	1/2	3/8-18	0.09	----
	690808SC	1/2	1/2-14	0.14	----
	691006SC	5/8	3/8-18	0.14	----
	691008SC	5/8	1/2-14	0.18	----
	691208SC	3/4	1/2-14	0.26	----

90° FEMALE ELBOW

	Part #	Tube OD (inch)	Thread NPT	Approx. Wt. Lbs.	
NEW	705302C	5/32	1/8-27	0.03	----
NEW	705304C	5/32	1/4-18	0.05	----
	700402SC	1/4	1/8-27	0.03	----
	700404SC	1/4	1/4-18	0.05	----
	700406SC	1/4	3/8-18	0.08	----
NEW	700602C	3/8	1/8-27	0.05	----
	700604SC	3/8	1/4-18	0.07	----
	700606SC	3/8	3/8-18	0.09	----
	700608SC	3/8	1/2-14	0.10	----
NEW	700804C	1/2	1/4-18	0.08	----
	700806SC	1/2	3/8-18	0.10	----
	700808SC	1/2	1/2-14	0.11	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

MALE RUN TEE

• Fixed

	Part #	Tube OD (inch)	Thread NPT	Approx. Wt. Lbs.	
NEW	715301C	5/32	1/16	0.05	----
NEW	715302C	5/32	1/8	0.03	----
NEW	715304C	5/32	1/4	0.04	----
	710402SC	1/4	1/8-27	0.04	----
	710404SC	1/4	1/4-18	0.05	----
	710604SC	3/8	1/4-18	0.08	----
	710606SC	3/8	3/8-18	0.10	----
	710608SC	3/8	1/2-14	0.15	----
NEW	710804C	1/2	1/4-8	0.09	----
	710806SC	1/2	3/8-18	0.11	----
	710808C	1/2	1/2-14	0.17	----

MALE BRANCH TEE

• Fixed

	Part #	Tube OD (inch)	Thread NPT	Approx. Wt. Lbs.	
NEW	725301C	5/32	1/16	0.03	----
NEW	725302C	5/32	1/8	0.03	----
NEW	725304C	5/32	1/4	0.05	----
	720402SC	1/4	1/8-27	0.04	----
	720404SC	1/4	1/4-18	0.05	----
	720406SC	1/4	3/8-18	0.08	----
	720604SC	3/8	1/4-18	0.08	----
	720606SC	3/8	3/8-18	0.10	----
NEW	720608C	3/8	1/2-14	0.15	----
NEW	720804C	1/2	1/4-18	0.09	----
	720806SC	1/2	3/8-18	0.11	----
	720808SC	1/2	1/2-14	0.17	----
NEW	721006C	5/8	3/8	0.18	----
NEW	721008C	5/8	1/2	0.21	----

FEMALE BRANCH TEE

	Part #	Tube OD (inch)	Thread NPT	Approx. Wt. Lbs.	
	770402C	1/4	1/8-27	0.06	----
	770404C	1/4	1/4-18	0.08	----
	770604C	3/8	1/4-18	0.08	----
NEW	770806C	1/2	3/8	0.13	----
NEW	771004C	5/8	1/4	0.21	----

45° MALE ELBOW

• Fixed

	Part #	Tube OD (inch)	Thread NPT	Approx. Wt. Lbs.	
NEW	545302C	5/32	1/8-27	0.03	----
	540402SC	1/4	1/8-27	0.03	----
	540404SC	1/4	1/4-18	0.04	----
	540602SC	3/8	1/8-27	0.06	----
	540604SC	3/8	1/4-18	0.06	----
	540606SC	3/8	3/8-18	0.08	----
	540608SC	3/8	1/2-14	0.13	----
NEW	540802C	1/2	1/8-27	0.08	----
	540804SC	1/2	1/4-18	0.08	----
	540806SC	1/2	3/8-18	0.10	----
	540808SC	1/2	1/2-14	0.15	----
	541006SC	5/8	3/8-18	0.14	----
	541008SC	5/8	1/2-14	0.17	----
	541208SC	3/4	1/2-14	0.26	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

UNION "Y"

Part #	A&B Tube OD (inch)	C Tube OD (inch)	Approx. Wt. Lbs.	
620553C	1/4	1/4	0.03	----
620409C	1/4	3/8	0.03	----
620555C	3/8	3/8	0.05	----
620559C	3/8	1/4	0.07	----
620557C	1/2	1/2	0.08	----

MALE BRANCH "Y"

	Part #	Tube OD (inch)	Thread NPT	Approx. Wt. Lbs.	
NEW	880402C	1/4	1/8	0.05	----
NEW	880404C	1/4	1/4	0.06	----
NEW	880406C	1/4	3/8	0.09	----
	620604C	3/8	1/4-18	0.09	----
	620606C	3/8	3/8-18	0.12	----
	620806C	1/2	3/8-18	0.13	----
	620808C	1/2	1/2-14	0.15	----

BULKHEAD UNION

	Part #	Tube OD (inch)	Thread (UNF)	Approx. Wt. Lbs.	
NEW	825320C	5/32	1/2-20	0.07	----
	820400C	1/4	9/16-18	0.07	----
	820600C	3/8	7/8-14	0.19	----
	820800C	1/2	1-12	0.26	----
	821000C	5/8	1 1/8-12	0.42	----

FEMALE BULKHEAD CONNECTOR

	Part #	App. Tube OD (inch)	Thread NPT	T (UNF)	Approx. Wt. Lbs.	
NEW	865304C	5/32	1/4-18	1/2-20	0.08	----
	860402C	1/4	1/8-27	9/16-18	0.01	----
	860404C	1/4	1/4-18	9/16-18	0.08	----
	860604C	3/8	1/4-18	7/8-14	0.20	----
	860606C	3/8	3/8-18	7/8-14	0.20	----
	860806C	1/2	3/8-18	1-12	0.26	----
	860808C	1/2	1/2-14	1-12	0.27	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

D.O.T. AIR BRAKE - NYLON TUBING

Tube O.D	1/4	3/8	1/2	5/8	3/4
Thread Size-B	7/16-24	17/32-24	11/16-20	13/16-18	1-18

•Typical Application
Air brake systems except where temperatures exceed +200^{0}F or where battery acid can drip on tubing.

•Pressure
Maximum operating pressure of 150 PSI.

•Vibration
Fair resistance.

•Temperature Range
-40^{0}F to +200^{0}F (-40^{0}C to +93^{0}C).

•Material
Brass

•Used With
NT Nylon Tubing - SAE J844 Type A and B.

• Tolerance
+/- .02 on all dimensions. Dimension data can change without notice. Please call us when dimensions are critical

•Advantages
Easy to assemble (no tube preparation or flaring required.) Built in tube support. Fittings utilize a ribbed sleeve for compression and positive grip. May be used with copper tubing by replacing nut, sleeve and insert with long nut and spherical sleeve. Insert should be removed for copper tubing use.

•Conformance
Meets specifications and standards of SAE and DOT FMVSS 571,106.

•Assembly Instructions
1- Cut tubing to desired length.
2-Slide nut and then sleeve on tubing. Threaded end of nut "A" must face toward fitting body.
3-Insert tubing into the preassembled fitting. Be sure tubing is bottomed in fitting.
4- Tighten nut to required torque as indicated on chart.

Disassembling: Remove nut and pull tubing out of fitting body. Insert will remain in tubing.
Reassembly: Push tubing and insert into fitting body until it bottoms. Thread nut onto fitting body and torque as in step 4.

Tube Size	Additional Number of Turns from Hand-Tight
1/4	3
3/8, 1/2	4
5/8, 3/4	3-1/2

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

D.O.T. AIR BRAKE - NYLON TUBING

SLEEVE
SAE# 100115

Part #	Tube O.D.	Approx. Wt. Lbs.	
38-000	3/16"		----
38-001	1/4”	0.01	----
38-002	3/8”	0.01	----
38-003	1/2”	0.01	----
38-004	5/8”	0.01	----
38-005	3/4”	0.01	----

60NAB **60NTA** 1460

NUT
SAE# 100110

Part #	Tube O.D.	Approx. Wt. Lbs.	
38-009	3/16"		----
38-010	1/4”	0.02	----
38-011	3/8”	0.03	----
38-012	1/2”	0.05	----
38-013	5/8”	0.06	----
38-014	3/4”	0.09	----

61NAB **61NTA** 1461

UNION
SAE# 100101BA

Part #	Tube O.D.	Approx. Wt. Lbs.	
38-018	3/16"		----
38-019	1/4”	0.07	----
38-020	3/8”	0.11	----
38-021	1/2”	0.20	----
38-022	5/8”	0.25	----
38-023	3/4”	0.40	----

62NAB **62NTA** 1462

BULKHEAD UNION

Part #	Tube O.D.	Approx. Wt. Lbs.	
38-028	1/4”	0.11	----
38-029	3/8”	0.16	----
38-030	1/2”	0.26	----

62NBH **1474** 475

STAINLESS STEEL INSERT
- 300 series stainless

- **For SAE# J844 TUBING**

Part #	Tube O.D.	Approx. Wt. Lbs.	
38-035	1/4”	0.01	----
38-036	3/8”	0.01	----
38-037	1/2”	0.01	----
38-038	5/8”	0.01	----
38-039	3/4”	0.01	----

59A **63NTA**

BRASS INSERT

Part #	Tube O.D.	Approx. Wt. Lbs.	
38-040	1/4”	0.01	----
38-041	3/8”	0.01	----
38-042	1/2”	0.01	----
38-043	5/8”	0.01	----
38-048	3/4”	0.02	----

1484 **463**

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

TEE

SAE# 100401BA

Part #	Tube O.D.	Approx. Wt. Lbs.	
38-044	1/4”	0.12	----
38-045	3/8”	0.19	----
38-046	1/2”	0.36	----
38-047	5/8”	0.48	----

64NAB **264NTA** 1464

REDUCING BRANCH TEE

Part #	Tube O.D. (1&2) x 3	Approx. Wt. Lbs.	
38-049	3/8” x 1/4”	0.24	----
38-057	1/2” x 3/8”	0.30	----

ELBOW

SAE# 100201BA

Part #	Tube O.D.	Approx. Wt. Lbs.	
38-052	1/4”	0.09	----
38-053	3/8”	0.13	----
38-054	1/2”	0.15	----
38-055	5/8”	0.36	----

65NAB **265NTA** 1465

FEMALE ADAPTER

SAE# 100103BA

	Part #	Tube O.D. x Female NPT	Approx. Wt. Lbs.	
	38-060	1/4” x 1/8”	0.06	----
	38-061	1/4” x 1/4”	0.08	----
	38-062	3/8” x 1/8”	0.07	----
	38-063	3/8” x 1/4”	0.10	----
	38-064	3/8” x 3/8”	0.14	----
	38-065	1/2” x 3/8”	0.16	----
	38-066	1/2” x 1/2”	0.20	----
	38-067	5/8” x 3/8”	0.28	----
	38-068	5/8” x 1/2”	0.28	----
NEW	38-059	3/4" x 1/2"	0.31	

66NAB **66NTA** 1466 **66NBH**

Adopt the pace of nature: her secret is patience.

– Ralph Waldo Emerson

Dimension data can change without notice.
Please see our website when dimensions are critical.

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

MALE ADAPTER
SAE# 100102BA

Part #	Tube O.D. x Male NPTF	Approx. Wt. Lbs.	
38-072	1/4" x 1/16"	0.05	----
38-073	1/4" x 1/8"	0.05	----
38-074	1/4" x 1/4"	0.06	----
38-075	1/4" x 3/8"	0.08	----
38-076	3/8" x 1/8"	0.07	----
38-077	3/8" x 1/4"	0.08	----
38-078	3/8" x 3/8"	0.10	----
38-079	3/8" x 1/2"	0.14	----
38-080	1/2" x 1/4"	0.13	----
38-081	1/2" x 3/8"	0.14	----
38-082	1/2" x 1/2"	0.18	----
38-087	1/2" x 3/4"	0.23	----
38-083	5/8" x 3/8"	0.17	----
38-084	5/8" x 1/2"	0.21	----
38-088	5/8" x 3/4"	0.25	----
38-085	3/4" x 1/2"	0.28	----
38-086	3/4" x 3/4"	0.30	----

68NAB **68NTA** 1468

SWIVEL MALE ADAPTER

Part #	Tube O.D. x Male NPTF	Approx. Wt. Lbs.	
38-078S	3/8" x 3/8"	0.18	----
38-081S	1/2" x 3/8"	0.22	----

MALE ELBOW
SAE# 100202BA

Part #	Tube O.D. x Male NPTF	Approx. Wt. Lbs.	
38-091	1/4" x 1/8"	0.06	----
38-092	1/4" x 1/4"	0.08	----
38-093	1/4" x 3/8"	0.13	----
38-094	3/8" x 1/8"	0.09	----
38-095	3/8" x 1/4"	0.11	----
38-090	3/8" x 1/4" LONG	0.14	----
38-101	3/8" x 3/8"	0.14	----
38-102	3/8" x 1/2"	0.20	----
38-103	1/2" x 1/4"	0.16	----
38-104	1/2" x 3/8"	0.20	----
38-109	1/2" x 3/8" LONG	0.26	----
38-105	1/2" x 1/2"	0.29	----
38-106	5/8" x 3/8"	0.26	----
38-107	5/8" x 1/2"	0.32	----
38-110	5/8" x 3/4"	0.40	----
38-108	3/4" x 1/2"	0.43	----
38-111	3/4" x 3/4"	0.51	

269NTA **1469**

SWIVEL MALE ELBOW

Part #	Tube O.D. x Male NPTF	Approx. Wt. Lbs.	
38-101S	3/8" x 3/8"	0.28	----
38-104S	1/2" x 3/8"	0.32	----

FEMALE ELBOW
SAE# 100203BA

Part #	Tube O.D. x Female NPTF	Approx. Wt. Lbs.	
38-113	1/4" x 1/8"	0.08	----
38-114	1/4" x 1/4"	0.12	----
38-115	3/8" x 1/8"	0.14	----
38-116	3/8" x 1/4"	0.10	----
38-117	3/8" x 3/8"	0.12	----
38-118	1/2" x 3/8"	0.23	----
38-119	1/2" x 1/2"	0.36	----
38-120	5/8" x 1/2"	0.38	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

MALE RUN TEE

SAE# 100424BA

Part #	Tube O.D. x Male NPTF x Tube O.D. 1x2x3	Approx. Wt. Lbs.	
38-125	1/4" x 1/8" x 1/4"	0.10	----
38-126	1/4" x 1/4" x 1/4"	0.13	----
38-124	3/8" x 1/4" x 1/4"	0.14	----
38-127	3/8" x 1/4" x 3/8"	0.17	----
38-128	3/8" x 3/8" x 3/8"	0.20	----
38-129	1/2" x 3/8" x 1/2"	0.30	----

71NAB **271NTA** 1471

MALE BRANCH TEE

SAE# 100425BA



Part #	Tube O.D. x Tube O.D. x Male NPTF 1x2x3	Approx. Wt. Lbs.	
38-136	1/4" x 1/4" x 1/8"	0.10	----
38-137	1/4" x 1/4" x 1/4"	0.13	----
38-138	3/8" x 3/8" x 1/8"	0.14	----
38-132	3/8" x 1/4" x 1/4"	0.15	----
38-139	3/8" x 3/8" x 1/4"	0.17	----
38-133	1/2" x 1/2" x 1/4"	0.26	----
38-140	3/8" x 3/8" x 3/8"	0.21	----
38-134	1/2" x 3/8" x 3/8"	0.26	----
38-141	1/2" x 1/2" x 3/8"	0.30	----
38-142	1/2" x 1/2" x 1/2"	0.37	----
38-143	5/8" x 5/8" x 1/2"	0.44	----

72NAB **272NTA** 1472

FEMALE BRANCH TEE



Part #	Tube O.D. x Tube O.D. x Female NPTF 1x2x3	Approx. Wt. Lbs.	
38-144	3/8" x 3/8" x 1/4"	0.21	----
38-146	5/8" x 5/8" x 1/4"	0.48	----

45° ELBOW

SAE# 100302BA

Part #	Tube O.D. x Male NPTF	Approx. Wt. Lbs.	
38-148	1/4" x 1/8"	0.06	----
38-149	1/4" x 1/4"	0.08	----
38-150	3/8" x 1/8"	0.09	----
38-151	3/8" x 1/4"	0.11	----
38-152	3/8" x 3/8"	0.14	----
38-153	3/8" x 1/2"	0.24	----
38-157	1/2" x 1/4"	0.18	----
38-154	1/2" x 3/8"	0.19	----
38-155	1/2" x 1/2"	0.25	----
38-156	5/8" x 1/2"	0.30	----
38-158	3/4" x 1/2"	0.38	----

6945NAB **279NTA** 1480

SWIVEL 45° ELBOW

Part #	Tube O.D. x Male NPTF	Approx. Wt. Lbs.	
38-152S	3/8" x 3/8"	0.20	----
38-154S	1/2" x 3/8"	0.24	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

SLEEVE

SAE# 120115BA

Part #	Tube O.D.	A	Approx. Wt. Lbs.	
38-161	1/4”	0.25	0.01	----
38-162	3/8”	0.31	0.02	----
38-163	1/2”	0.38	0.02	----
38-164	5/8”	0.44	0.02	----
38-165	3/4”	0.50	0.04	----

60AB **1360**

NUT

SAE# 120111BA



Part #	Tube O.D.	A	Hex	Approx. Wt. Lbs.	
38-170	1/4”	0.75	0.56	0.02	----
38-171	3/8”	1.13	0.62	0.04	----
38-172	1/2”	1.25	0.81	0.08	----
38-173	5/8”	1.38	0.94	0.12	----
38-174	3/4”	1.56	1.12	0.18	----

20961 **61AB** 1361

UNION

SAE# 120101BA



Part #	Tube O.D.	A	Hex	Approx. Wt. Lbs.	
38-179	1/4”	0.81	0.44	0.08	----
38-180	3/8”	1.10	0.56	0.14	----
38-181	1/2”	1.07	0.69	0.24	----
38-182	5/8”	1.41	0.81	0.34	----
38-183	3/4"				----

62AB **1362**

TEE

SAE# 120401BA



Part #	Tube O.D.	A	Approx. Wt. Lbs.	
38-188	1/4”	0.62	0.16	----
38-189	3/8”	0.82	0.24	----
38-190	1/2”	0.94	0.48	----
38-191	5/8"			

264AB **1364**

ELBOW

SAE# 120201BA



Part #	Tube O.D.	A	Approx. Wt. Lbs.	
38-196	1/4”	0.62	0.10	----

265AB **1365**

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

FEMALE ADAPTER

SAE# 120103BA



Part #	Tube O.D. x Female NPTF	A	Hex	Approx. Wt. Lbs.	
38-204	1/4" x 1/8"	0.84	0.56	0.08	----
38-205	1/4" x 1/4"	1.07	0.68	0.10	----
38-206	3/8" x 1/8"	1.00	0.56	0.10	----
38-207	3/8” x 1/4”	1.19	0.68	0.12	----
38-208	3/8” x 3/8”	1.18	0.87	0.16	----
38-209	1/2” x 3/8”	1.27	0.87	0.18	----
38-210	1/2' x 1/2"	1.44	1.06	0.20	----
38-211	5/8" x 3/8"	1.31	0.87	0.24	----
38-212	5/8" x 1/2"	0.50	1.06	0.26	----
38-213	3/4" x 1/2"				----

66AB **1366**

MALE ADAPTER

SAE# 120102BA



Part #	Tube O.D. x Male NPTF	A	Hex	Approx. Wt. Lbs.	
38-217	1/4” x 1/8”	0.88	0.43	0.06	----
38-218	1/4” x 1/4”	0.97	0.56	0.08	----
38-221	3/8” x 1/4”	1.09	0.56	0.10	----
38-222	3/8” x 3/8”	1.19	0.69	0.12	----
38-223	3/8” x 1/2”	1.45	0.87	0.18	----
38-224	1/2” x 1/4”	1.32	0.69	0.16	----
38-225	1/2” x 3/8”	1.35	0.69	0.18	----
38-226	1/2” x 1/2”	1.51	0.87	0.24	----
38-227	5/8” x 3/8”	1.39	0.81	0.22	----
38-228	5/8” x 1/2”	1.57	0.87	0.24	----
38-229	3/4” x 1/2”	1.67	1.00	0.34	----

68AB **368**

90° MALE ELBOW

SAE# 120202BA



Part #	Tube O.D. x Male NPTF	A	B	Approx. Wt. Lbs.	
38-235	1/4” x 1/8”	0.64	0.76	0.08	----
38-236	1/4” x 1/4”	0.69	0.88	0.10	----
38-237	1/4” x 3/8”	0.73	0.86	0.14	----
38-239	3/8” x 1/4”	0.80	0.93	0.12	----
38-240	3/8” x 3/8”	0.83	0.90	0.16	----
38-241	3/8" x 1/2"				----
38-243	1/2” x 3/8”	0.92	0.98	0.22	----
38-244	1/2” x 1/2”	1.04	1.19	0.30	----
38-246	5/8” x 1/2”	1.10	1.25	0.36	----

269AB **1369**

MALE BRANCH TEE

SAE# 120425BA



Part #	Tube O.D. x Male NPTF (1&2)x3	A	B	Approx. Wt. Lbs.	
38-278	3/8” x 1/4”	0.78	0.91	0.18	----
38-279	3/8” x 3/8”	0.85	0.92	0.24	----

272AB **1372**

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

D.O.T. AIR BRAKE REUSABLE HOSE/ FITTINGS

•Typical Application
Air Brake hose connections.
Meets SAE & DOT specifications
(FMVCS 10 GAL)

•Pressure
Determined by maximum working pressure for hose size.
Up to 125 psi

Temperature: -40^{0}F to + 120^0 F (-40°C to +48°C)

•Advantages
Can be used for nearly any brake line. Easy to assemble with a good selection of hose end configurations. Brass material offers excellent resistance against corrosion.

• Tolerance
+/- .02 on all dimensions. Dimension data can change without notice. Please call us when dimensions are critical.

•Assembly Instructions
1- Slide nut and sleeve onto hose. Make sure bevel edge of sleeve faces out toward fitting.
2- Push hose into fitting until it bottoms.
3- Screw nut until contact is made with body hex.

NOTE: When reassembling fitting, body and nut should be inspected. Only reuse if in proper condition. Sleeves should never be reused.

SLEEVE
FERRULE

Part #	Hose I.D. Size	Approx. Wt. Lbs.	
38-300	3/8”	0.02	----
38-301	1/2”	0.02	----

#60HC 3380-A 0903610 367 60RB

NUT

Part #	Hose I.D. Size	Approx. Wt. Lbs.	
38-306	3/8”	0.04	----
38-307	1/2”	0.06	----

61RB **#61HC** 369 **3380-B** 0903624

NUT FOR USE WITH SPRING

Part #	Hose I.D. Size	Thread	Approx. Wt. Lbs.	
38-312	3/8”	31/32-20	0.04	----
38-313	1/2”	1-3/32-20	0.06	----

#61HCS **0903613** 3380-D **61RBSG**

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

SPRING

Part #	Hose I.D.	Approx. Wt. Lbs.	
38-351	3/8”	0.20	----
38-352	1/2”	0.22	----

#60SG **0901045** 3380-C **377**

NUT AND SPRING ASSEMBLY

Part #	Hose I.D. Size	Approx. Wt. Lbs.	
38-015	3/8”	0.18	----
38-016	1/2”	0.24	----

379 **67RBSG** 0999999

UNION

Part #	Hose I.D.	Thread	Approx. Wt. Lbs.	
38-318	3/8”	31/32-20	0.32	----
38-319	1/2”	1-1/8-20	0.48	----

#62HC **3380B-Y0** 362

BODY ONLY

Part #	Hose I.D.	Thread	Approx. Wt. Lbs.	
39-318	3/8”	31/32-20	0.32	----
39-319	1/2”	1-1/8-20	0.48	----

FEMALE CONNECTOR HOSE

Part #	Hose I.D. x Female ABS	Approx. Wt. Lbs.	
38-357	3/8” x 3/4-20	0.24	----
38-358	1/2” x 7/8-20	0.39	----

#66ABS **66RBSV** 3380B-Y7 **386**

BODY ONLY

Part #	Hose I.D. x Female ABS	Approx. Wt. Lbs.	
39-357	3/8” x 3/4-20	0.24	----
39-358	1/2” x 7/8-20	0.38	----

MALE CONNECTOR

Part #	Hose I.D. x Male Pipe	Approx. Wt. Lbs.	
38-363	3/8” x 1/4”	0.38	----
38-364	1/2” x 3/8”	0.46	----

#68ABS **09155** 3380B-Y8 **387**

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

ADAPTER FOR SWIVEL TYPE REUSABLE AND CRIMPED ON

Part #	Male ABS x Male Pipe	ABS Thread	Approx. Wt. Lbs.	
38-369	3/8" x 1/4"	3/4-20	0.05	----
38-368	3/8" x 3/8"	3/4-20	0.08	----
38-372	3/8" x 1/2"	3/4-20	0.12	----
38-370	1/2" x 3/8"	7/8-20	0.10	----
38-371	1/2" x 1/2"	7/8-20	0.12	----

#68ABS **1390** 76RB **388**

MALE ADAPTER

Part #	Hose I.D. x Male Pipe	Approx. Wt. Lbs.	
38-333	3/8" x 1/4"	0.22	----
38-334	3/8" x 3/8"	0.24	----
38-335	3/8" x 1/2"	0.26	----
38-336	1/2" x 3/8"	0.33	----
38-337	1/2" x 1/2"	0.36	----

#68HC **368** 3380B-Y2 **68RB**

ADAPTER BODY

Part #	Hose I.D. x Male Pipe	Approx. Wt. Lbs.	
38-324	3/8" x 1/4"	0.12	----
38-325	3/8" x 3/8"	0.14	----
38-326	3/8" x 1/2"	0.20	----
38-327	1/2" x 3/8"	0.18	----
38-328	1/2" x 1/2"	0.20	----

#68B **W1391Z**

MALE ADAPTER

Part #	Hose I.D. x Male Pipe	Approx. Wt. Lbs.	
38-342	3/8" x 1/4"	0.32	----
38-343	3/8" x 3/8"	0.34	----
38-344	3/8" x 1/2"	0.38	----
38-345	1/2" x 3/8"	0.48	----
38-346	1/2" x 1/2"	0.52	----

#68HCS **3380B-Y3** 68RBSG **378**

America was not built on fear. America was built on courage, on imagination and an unbeatable determination to do the job at hand.

- Harry S Truman

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

- 8000 PSI max. pressure
- Exceeds 12hr salt spray

Meets SAE #J-534C
Many types available on special order.

- Assortments also available
- See website for Grease Accesssories

PIPE THREAD — BALL CHECK - 1/8-27 NPTF



Part #	Size	A	B	Hex	Approx. Wt. Lbs.	
36-110	1/8" -27 NPTF	0.66	0.28	0.437	0.01	----
36-110SS	303 SS	0.68	0.29	0.437	0.01	----
36-111	Thread Forming	0.62	0.23	0.437	0.01	----

#610 **1610** 2800 **1720** 5000

PIPE THREAD — BALL CHECK



Part #	Size	A	B	Hex	Approx. Wt. Lbs.	
36-112	1/8" -27 NPTF	1.25	0.22	0.437	0.02	----
36-113	1/8" -27 NPTF	1.75	1.26	0.437	0.02	----

#607 **1607** 2800 **1669** 5003

PIPE THREAD — 30° ANGLE BALL CHECK



Part #	Size	A	B	Hex	Approx. Wt. Lbs.	
36-114	1/8" -27 NPTF	0.90	0.30	0.437	0.01	----

#611 **1611** 2830 **5100**

PIPE THREAD — 45° ANGLE BALL CHECK



Part #	Size	A	B	Hex	Approx. Wt. Lbs.	
36-116	1/8" -27 NPTF	0.88	0.22	0.437	0.01	----
36-116SS	303 SS	0.95	0.29	0.437	0.01	----

#688 **1688** 2845 **5200**

PIPE THREAD — 65° ANGLE BALL CHECK



Part #	Size	A	B	Hex	Approx. Wt. Lbs.	
36-118	1/8" -27 NPTF	0.86	0.30	0.437	0.01	----

#612 **1612** 2865 **5300**

PIPE THREAD — 90° ANGLE BALL CHECK



Part #	Size	A	B	Hex	Approx. Wt. Lbs.	
36-120	1/8" -27 NPTF	0.84	0.30	0.437	0.01	----
36-120SS	303 SS	0.84	0.29	0.437	0.01	----
36-121	1/8" -27 NPTF	1.81	1.25	0.437	0.01	----

#613 **1613** 2890 **5400** 5407

PIPE THREAD — BALL CHECK - 1/4-18 NPTF



Part #	Size	A	B	Hex	Approx. Wt. Lbs.	
36-130	1/4" -18 NPTF	0.84	0.30	0.437	0.02	----
36-130SS	303 SS	0.87	0.42	0.437	0.02	----

#627 **1627** 2900K **5050**

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

PIPE THREAD



65° ANGLE BALL CHECK

Part #	Size	A	B	Hex	Approx. Wt. Lbs.	
36-132	1/4"-18 NPTF	0.97	0.34	0.56	0.02	----

#629 **1629** 2965 **5350**

1/4-28 TAPER THREAD



SHORT BALL CHECK - 1/4-28 NPTF

Part #	Size	A	B	Hex	Approx. Wt. Lbs.	
36-140	1/4"-28 NPTF	0.54	0.18	0.31	0.01	----
36-140SS	303 SS	0.54	0.18	0.31	0.01	----
36-141	Thread Forming	0.55	0.10	0.31	0.01	----

#641 **1641** 2400 **3038** 5010

1/4-28 TAPER THREAD



LONG BALL CHECK

Part #	Size	A	B	Hex	Approx. Wt. Lbs.	
36-142	1/4"-28 Taper Thread	0.69	0.34	0.312	0.01	----

#652 **1652** 2400 **5013**

1/4-28 TAPER THREAD



EXTRA LONG BALL CHECK

Part #	Size	A	B	Hex	Approx. Wt. Lbs.	
36-144	1/4"-28 Taper Thread	0.92	0.60	0.312	0.02	----

#680 **1680** 2400 **5014**

1/4-28 TAPER THREAD



SHORT 45° BALL CHECK

Part #	Size	Angle	A	B	Hex	Approx. Wt. Lbs.	
36-146	1/4"-28 Taper Thread	45°	0.82	0.20	0.375	0.02	----
36-146SS	303 SS	45°	0.81	0.20	0.375	0.02	----
36-147	1/4"-28 Taper Thread	65°	0.78	0.20	0.375	0.02	----

#637 **1637** 2445 **1665** 2465 **3010** 5210

1/4-28 TAPER THREAD



LONG 45° BALL CHECK

Part #	Size	A	B	Hex	Approx. Wt. Lbs.	
36-148	1/4"-28 Taper Thread	0.94	0.30	0.375	0.02	----

#636 **1630** 2445

1/4-28 TAPER THREAD



90° ANGLE BALL CHECK

SAE# A515002

Part #	Size	A	B	Hex	Approx. Wt. Lbs.	
36-150	1/4"-28 Taper Thread	0.75	0.10	0.375	0.02	----
36-150SS	303 SS	0.75	0.20	0.375	0.02	----
36-152	Thread Forming	0.75	0.16	0.375	0.02	----

#911 **1911** 2490 **3054** 5410

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

DRIVE TYPE — BALL CHECK Drive Type



Part #	Size	A	B	Approx. Wt. Lbs.	
36-160	5/16"	0.55	0.25	0.01	----

#608 **1608** 5021

DRIVE TYPE — BALL CHECK



Part #	Size	A	B	Approx. Wt. Lbs.	
36-164	3/16"	0.52	0.25	0.01	----
36-164SS	303 SS	0.51	0.25	0.01	----

#728 **1728** 2316 **5033**

DRIVE TYPE — BALL CHECK



Part #	Size	A	B	Approx. Wt. Lbs.	
36-166	1/4"	0.55	0.23	0.01	----
36-166SS	303 SS	0.55	0.23	0.01	----

#743 **1743** 214 **5029**

METRIC



Part #	Size	A (mm)	B (mm)	Hex (mm)	Approx. Wt. Lbs.	
36-168	6MM x 1	16	3.7	7	0.01	----

(Diameter x Pitch)

#711 **6000** 2106 **2M6** 5175

METRIC — 45° ANGLE



Part #	Size	A (mm)	B (mm)	Hex (mm)	Approx. Wt. Lbs.	
36-170	6MM x 1	21	3.7	9	0.02	----

#712 **6045** 2107 **5176**

METRIC — 90° ANGLE



Part #	Size	A (mm)	B (mm)	Hex (mm)	Approx. Wt. Lbs.	
36-172	6MM x 1	18	3.7	9	0.02	----

#713 **6090** 2108 **ZM906** 5177

METRIC



Part #	Size	A (mm)	B (mm)	Hex (mm)	Approx. Wt. Lbs.	
36-174	8MM x 1	16	3.7	9	0.02	----

#811 **8000** 2103 **ZM58** 5178

METRIC — 45° ANGLE



Part #	Size	A (mm)	B (mm)	Hex (mm)	Approx. Wt. Lbs.	
36-176	8MM x 1	21	3.7	9	0.02	----

#812 **8045** 2104 **ZM458** 5179

METRIC — 90° ANGLE



Part #	Size	A (mm)	B (mm)	Hex (mm)	Approx. Wt. Lbs.	
36-178	8MM x 1	18	3.7	9	0.02	----

#813 **8090** 2105 **ZM908** 5180

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

METRIC



Part #	Size	A (mm)	B (mm)	Hex (mm)	Approx. Wt. Lbs.	
36-180	10MM x 1	16	3.7	11	0.02	----

• Diameter x pitch (extra fine)

#911 **9000** 2109 **ZM510** 5181

METRIC



45° ANGLE

Part #	Size	A (mm)	B (mm)	Hex (mm)	Approx. Wt. Lbs.	
36-182	10MM x 1	21	3.7	11	0.02	----

#912 **9045** 2110 **ZM4510**

METRIC



90° ANGLE

Part #	Size	A (mm)	B (mm)	Hex (mm)	Approx. Wt. Lbs.	
36-184	10MM x 1	18	3.7	11	0.02	----

#913 **9090** 2111 **ZM9010** 5183



Part #	Size	A	B	Hex	Approx. Wt. Lbs.	
36-186	5/16"-24	0.65	0.12	0.375	0.02	----

#711-B **1711** 2500



Part #	Size	A	B	Hex	Approx. Wt. Lbs.	
36-188	3/8"-24	0.65	0.14	0.437	0.01	----

#710-B **1710** 2600

BUTTON HEAD



Part #	Size	A	B	Hex	Approx. Wt. Lbs.	
36-200	1/8"-27 PTF	0.75	0.34	0.625	0.03	----
36-205	1/4"-18 NPT	0.83	0.44	0.625	0.03	----

1184 **1186**

WHIP HOSE - EXCEEDS SAE 100R1-AT - use with hand grease guns only

10,000 PSI Burst Pressure Rubber Hose

1/8" NPT Solid Base
3/16" ID
3,000 PSI Working pressure

Part #	Length	
36-210	12" RUBBER	----
36-212	18" RUBBER	----
36-214	24" RUBBER	----
36-216	36" RUBBER	----

4 JAW GREASE GUN COUPLER

Provides quick, positive, leakproof connection w/ grease fittings.



1/8" NPTF

Part #	A	Hex	Approx. Wt. Lbs.	
36-220	1.50	0.56	0.05	----

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

ADAPTERS FOR GREASE FITTINGS

ADAPTERS

• CARBON STEEL, ZINC COATED

NEW

Part #	Female	Male	L	H	Weight	
36-300	1/8"-27 NPTF	1/4-28" SAE-LT	.75	1/2	0.02	----
36301	1/8"-27 NPTF	1/4-28" SAE-LT	.87	1/2	0.02	----

Part #	Female English to Male English		L	H	Weight	
36-304	1/4"-28 UNF	M6 x 1.0	.43	9mm	0.01	----
36-305	1/4"-28 UNF	M8 x 1.0	.45	3/8	0.01	----
36-306	1/4"-28 UNF	M10 x 1.0	.32	7/16	0.01	----

EXTENSIONS

Part #	Female English to Male English		L	H	Weight	
36-307	1/4"-28 UNF	1/4"-28 SAE-LT	1.34	-	0.01	----
36-308	1/8"-27 NPTF	1/8"-27 NPTF	.75	1/2	0.02	----
36-309*	1/8"-27 NPTF	1/8"-27 NPTF	.82	1/2	0.02	----
36-310	1/8"-27 NPTF	1/8"-27 NPTF	.94	9/16	0.04	----
36-311	1/8"-27 NPTF	1/8"-27 NPTF	1.25	1/2	0.04	----

*BRASS PLATED

45° ANGLE ELBOWS

Part #	Female	Male	L	H	Weight	
36-360	1/8"-27 NPTF	1/4"-28 SAE-LT	.81	1/2	0.02	----
36-362	1/8"-27 NPTF	1/8"-27 PTF SAE Short	1.00	1/2	0.03	----

90° ANGLE ELBOWS

Part #	Female	Male	L	H	Weight	
36-370	1/8"-27 NPTF	1/4"-28 SAE-LT	.81	1/2	0.03	----
36-371	1/8"-27 NPTF	1/4"-28 SAE-LT	1.04	1/2	0.03	----
36-372	1/8"-27 NPTF	1/4"-18 PTF SAE Short	1.19	9/16	0.06	----
36-374	1/8"-27 NPTF	1/8"-27 PTF SAE Short	1.00	1/2	0.03	----
36-375	1/8"-27 NPTF	1/8"-27 NPTF	1.13	1/2	0.03	----
36-377	1/4"-18 NPTF	1/4"-18 NPTF	1.34	11/16	0.08	----
36-376	1/8"-27 NPTF	1/8"-27 NPTF	1.50	5/8	0.07	----
36-373	1/8"-27 PTF SPL Extra Short	1/8"-27 PTF SPL Extra Short	.82	1/2	0.03	----

COUPLING

Part #	Female	Female	L	H	Weight	
36-340	1/4"-28 UNF	1/8"-27 NPTF	.65	1/2	0.02	----

BULKHEAD CONNECTOR

Part #	Female	Male (Female)	L	H	Weight	
36-350	1/8"-27 NPTF	1/8"-27 NPSM (1/4"-28 UNF)	.88	1/2	0.03	----

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

SPECIALTY VALVES AND COCKS

DRAIN COCKS
PAGE 147-148

AIR VALVES

3, 4 AND 6 WAY
PAGE 153-154

NEEDLE
PAGE 150-151

MARINE & ANTI-SIPHON
PAGE 154

PANEL MOUNT BALL VALVES
PAGE 155

TRUCK
PAGE 152

MINI BALL
PAGE 155

SOLID BOTTOM SHUT-OFF
PAGE 152

CHECK
PAGE 156

SPRING BOTTOM SHUT-OFF
PAGE 149

MORE VALVES ON OUR WEBSITE

See our valve section for much, much more!

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

DRAIN COCKS

- For use with low pressure air, water and fluids.
- Designed for a working pressure of 150 psi @ 250°.
- Hand-tightening provides a metal-to-metal seal.
- Not intended for natural gas, LPG, nuclear or aircraft applications.

Install on your tank for easy draining

GASOLINE SHUT OFF w/ SCREEN FILTER



Part #	Barb X Male Pipe	A	B	C	Approx. Wt. Lbs.	
46-064	1/4" x 1/8"	0.55	1.34	0.66	0.06	----

827

DRAIN COCK 150 PSI - Trunk Air Tank



Part #	Male Pipe	A	B	Approx. Wt. Lbs.	
46-066	1/4"	1.73	1.41	0.22	----

DCR601-4

TRUCK DRAIN - 125 P.S.I.G



Part #	Male Pipe	Industry Number	A	B	Hex	Approx. Wt. Lbs.	
46-067	1/8"		1.53	1.95	0.62	0.14	----
46-068	1/4"	W15310	1.53	1.95	0.62	0.18	----

SHUT OFF - 150 P.S.I max.



Part #	Male Pipe x Female Pipe	Industry Number	A	B	Hex 1	Hex 2	Approx. Wt. Lbs.	
46-069	1/4"	W20332	1.96	1.96	0.75	0.62	0.20	----

#60HC **3380-A** 0903610 **367**

LEVER HANDLE



Part #	Male Pipe	Industry Number	A	B	Hex	Approx. Wt. Lbs.	
46-070	1/8"	M-41-P	1.99	1.80	0.62	0.04	----
46-071	1/4"	M-42-P	2.06	1.81	0.62	0.06	----
46-072	3/8"	M-43-P	2.30	2.29	0.81	0.08	----
46-073	1/2"	M-44-P	3.00	2.50	0.87	0.16	----

840 **41D** DC601

- 30 psi

*Valve is closed when handle is in the position of the picture

AIR TANK DRAIN PULL VALVE

Part #	Size	Description	
39595	1/4" male	5ft nylon coated pull cable	----
39596	1/4" male	4ft nylon coated pull cable	----
39597	1/4" male	3ft nylon coated pull cable	----
39600	1/4" male	Air valve only	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

DRAIN COCKS

INTERNAL SEAT



Part #	Male Pipe	Industry Number	A	Hex	Approx. Wt. Lbs.	
46-079	1/8”	6783	1.45	0.55	0.02	----

DC602 **808** 400A **1800A**

INTERNAL SEAT - Wing Nut Handle



Part #	Male Pipe	Industry Number	A	Hex	Approx. Wt. Lbs.	
46-074	1/8”	130	0.92	0.40	0.04	----
46-075	1/4”	140	0.94	0.56	0.06	----
46-077	3/8”	230	1.27	0.68	0.08	----

HB - 5/16 **803** 305A

LONG INTERNAL SEAT



Part #	Size	Ind #	A	Hex	Approx. Wt. Lbs.	
46-078	1/8 MIP	1.85				----
46-076	3/8” Hose I.D.		1.65	0.43	0.02	----

809

PIN HANDLE - Internal Seat



Part #	Male Pipe	Industry Number	A	Hex	Approx. Wt. Lbs.	
46-080	1/8”	M-200-P	1.22	0.50	0.04	----
46-081	1/4”	M-201-P	1.31	0.56	0.06	----
46-082	3/8”	M-202-P	1.53	0.68	0.12	----

DC603 **802**

EXTERNAL SEAT w/ SPOUT



Part #	Male Pipe	Industry Number	A	Hex	Approx. Wt. Lbs.	
46-084*	1/4”	6788	1.56	0.56	0.02	----

* Replaces GM # 511771 & Chrysler #836015

200A **239** DC606 **807**

BIBB VALVE

Part #	Male Pipe	Industry Number	A	B*	C	Approx. Wt. Lbs.	
46-088	1/8”	150	0.82	1.60	0.55	0.04	----
46-089	1/4”	120	0.89	1.59	0.54	0.06	----
46-089A	1/4”	6660	0.55	1.34	0.66	0.06	----

* With valve closed

804 **DC607** 2019 **201DH**

RADIATOR TYPE - External Seat

Part #	Male Pipe	Industry Number	Ind #	A	Hex	Approx. Wt. Lbs.	
46-085	1/8”	M-320-P	135	0.90	0.43	0.02	----
46-086	1/4”	M-321-P	145	1.00	0.56	0.04	----
46-087	3/8”	M-322-P	270	1.25	0.68	0.08	----
46-083	1/2”	108	108	1.48	0.87	0.12	----

320D **240** DC604 **801**

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

- Designed for working pressure of 30 PSI.
- Forged brass bodies and brass handles.
- Instantaneous off-on operation with 360⁰ rotation.
- Not good for gasoline.

COMPRESSION X MALE PIPE



Part #	Comp X Male Pipe	Ind. #	A	B	Hex	Approx. Wt. Lbs.	
46-130	1/4" x 1/8"	27-C	1.87	1.81	0.51	0.14	----
46-131	1/4" x 1/4"	227-C	2.05	1.86	0.62	0.15	----
46-132	5/16" x 1/8"	29-C	2.05	1.90	0.50	0.16	----
46-134	3/8" x 1/4"	57-C	2.05	1.83	0.62	0.15	----

868 **V304C** 2068 **133C** VC206

COMPRESSION X COMPRESSION

* See pg. 73-74 to order nut and sleeve separately.



Part #	Comp X Comp	Ind. #	A	B	Approx. Wt. Lbs.	
46-140	1/4"	28-C	1.82	1.84	0.12	----
46-141	5/16"	30-C	1.84	1.88	0.14	----
46-142	3/8"	58-C	1.87	1.80	0.14	----
46-143	1/2"	68-C	2.21	2.32	0.22	----

V3030F **2062** 134C

FEMALE X FEMALE PIPE



Part #	Female Pipe X Female Pipe	A	B	Hex	Approx. Wt. Lbs.	
46-151	1/8"	1.77	1.79	0.56	0.12	----
46-152	1/4"	2.28	1.82	0.69	0.20	----
46-152T*	1/4"	2.28	2.00	0.68	0.20	----
46-153	3/8"	2.44	2.28	0.81	0.30	----

* 150 PSI

V403P **132C** 875

MALE PIPE X FEMALE



Part #	Male Pipe X Female Pipe	Ind. #	A	B	Hex 1	Hex 2	Approx. Wt. Lbs.	
46-160	1/8"	48-P	2.03	1.84	0.50	0.56	0.14	----
46-161	1/4"	49-P	2.26	1.79	0.69	0.69	0.18	----
46-161T*	1/4"		2.26	1.98	0.69	0.69	0.20	----
46-162	3/8"	50-P	2.33	2.28	0.82	0.82	0.28	----

* 150 PSI

880 **V402P** 130C

MALE PIPE X MALE PIPE



Part #	Male Pipe X Male Pipe	Ind. #	A	B	Hex	Approx. Wt. Lbs.	
46-165	1/8"	76-P	2.15	1.80	0.69	0.12	----
46-166	1/4"	77-P	2.22	1.84	0.70	0.17	----
46-166T*	1/4"		2.23	2.00	0.68	0.18	----
46-167	3/8"	78-P	2.43	2.24	0.82	0.22	----

* 150 PSI

1V401P **890**

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

NEEDLE VALVES

THESE ARE NOT LEAD FREE SEE PAGES 169-182 FOR LEAD FREE PRODUCTS

Made with either pin handle or pressed on handle.
Please specify if you have a preference.

- Used on instrumentation, hydraulic, and pneumatic systems.
- Designed for a maximum working pressure of 150 PSI.
- Provided with steel handles and metal-to-metal seats with fine-thread screwdown.
- Not designed for natural gas, LPG, nuclear or aircraft applications.
- Always install with pressure against the seat.

COMP X MALE PIPE



Part #	Comp X Male Pipe	Ind. #	A	B	Approx. Wt. Lbs.	
46-002	1/4" x 1/8"	**M-101-C**	1.29	1.12	0.07	----
46-003	1/4" x 1/4"	**M-101-C**	1.27	1.14	0.10	----

NV106C **2205** 820 **3068**

COMP X MALE PIPE-ANGLE



Part #	Comp X Male Pipe	Handle	Ind. #	A	B	C	Approx. Wt. Lbs.	
46-011	1/4" x 1/8"	A	**M-103-C**	0.56	1.48	0.93	0.08	----
46-011X	Heavy Pattern	B	**M-103-C**	0.53	1.53	0.83	0.08	----
46-012	1/4" x 1/4"	B	**M-104-C**	0.62	1.67	0.90	0.13	----
46-013	5/16" x 1/8"	B	**M-104-C**	0.63	1.63	0.95	0.10	----
46-016	3/8" x 1/4"	A	**M-303-C**	0.65	1.71	0.92	0.16	----

NV104C **2203** 821 **3069**

COMP X COMP



Part #	Comp X Comp	Handle	Ind. #	A	B	Approx. Wt. Lbs.	
46-020	3/16"	B	**M-105-C**	1.06	0.88	0.08	----
46-021	1/4"	A	**M-106-C**	1.17	1.12	0.10	----
46-022	5/16"	A	**M-107-C**	1.22	1.08	0.12	----
46-023	3/8"	B	**M-113-C**	1.31	1.15	0.13	----

NV105C **3062** 2201 **822**

FLARE X MALE PIPE



Part #	Male Flare X Male Pipe	Handle	Ind. #	A	B	Approx. Wt. Lbs.	
46-028	1/4" x 1/8"	A	**M-104-SAE**	1.35	1.12	0.07	----
46-029	1/4" x 1/4"	B	**M-1040-SAE**	1.38	0.88	0.09	----
46-031	3/8" x 1/4"	B	**M-108-SAE**	1.73	1.22	0.18	----

NV103F **2405** 823 **3048**

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

FLARE X MALE PIPE



Part #	Male Flare X Male Pipe	Ind. #	A	B	C	Approx. Wt. Lbs.	
46-036	1/4" x 1/8"	M-103-SAE	0.68	1.54	0.86	0.08	----
46-038	5/16" x 1/8"	M-203-SAE	0.88	1.59	0.94	0.11	----
46-039	5/16" x 1/4"	M-204-SAE	0.90	1.94	1.00	0.14	----
46-040	3/8" x 1/4"	M-303-SAE	0.95	1.86	0.90	0.17	----

NV101F **2403** 824 **3049**

FLARE X FLARE



Part #	Male Flare X Male Flare	Ind. #	A	B	Approx. Wt. Lbs.	
46-045	1/4"	M-110-SAE	1.48	1.20	0.18	----
46-046	3/8"	M-115-SAE	1.79	1.19	0.20	----

NV102F **3042** 825 **2401**

MULTI-PURPOSE AIR VENT



Part #	Male Pipe	A	Hex	Approx. Wt. Lbs.	
46-048	1/8"	0.78	0.43	0.02	----

705

MALE PIPE TO MALE PIPE



Part #	Male Pipe X Male Pipe	Handle	Ind. #	A	B	Approx. Wt. Lbs.	
46-050	1/8"	A	M-108-P	1.25	1.09	0.08	----
46-051	1/4"	B	M-110-P	1.69	1.00	0.16	----

NV107P **2301** 826 **3122**

FEMALE PIPE X FEMALE PIPE



Part #	Female Pipe X Female Pipe	Ind. #	A	B	Approx. Wt. Lbs.	
46-055*	1/8"	M-304-P	1.18	0.84	0.18	----
46-056	1/4"	M-3044-P	1.60	1.24	0.21	----
46-056P*	1/4" Heavy	M-3044-P	1.62	2.53	0.20	----

* Pressed on handle

6800 **NV109P** 2304 **817** 3103

MALE X FEMALE PIPE



NBR seals -30°C to 120°C

Part #	Male Pipe X Female Pipe	Handle	Ind. #	A	B	Approx. Wt. Lbs.	
46-060	1/8"	A	M-305-P	1.18	1.09	0.10	----
46-061	1/4'	A	M-3055-P	1.60	1.14	0.18	----
46-061L	1/4" Light Pattern	B	M-3055-P	1.88	1.09	0.21	----

NV108P **2305** 818 **3120**

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

BRASS TRUCK VALVES

- Used in heavy duty truck, trailer and mobile markets.
- Used on water, oil and coolant lines.
- Forged brass construction with steel handle.
- Temperature range -40° - 250°
- Max pressure 250 psi
- Metal to metal seats for high heat/fluid compatibility
- Fine thread screw down to afford flow control ability and a positive seal.
- Not intended for natural gas, LPG, Nuclear or aircraft applications

200 PSI

BARB TO MALE PIPE

Part #	Size	
46-450	3/8 x 3/8	----
46-451	5/8 x 3/8	----
46-455	5/8 x 1/2	----
46-457	3/4 x 3/8	----
46-456	3/4 x 1/2	----

404V

FEMALE TO MALE PIPE

Part #	Size	
46-465	3/8 x 3/8	----
46-466	3/8 x 1/2	----
46-467	1/2 x 1/2	----

405V

FLARE TO MALE PIPE

Part #	Size	
46-475	1/2 x 1/2	----
46-476	5/8 x 1/2	----

409V

MIP X FLARE

Part #	Size	
46-485	1/2 x 5/8	----

SOLID BOTTOM VALVES

- Designed for instantaneous on-off operation.
- 360⁰ rotation standard.
- 30 PSI
- Packed with grease.

8875

O-RING SEALED MIP X FIP

Part #	Size	
46-400	1/8	----
46-401	1/4	----
46-402	3/8	----

1035D **M-70-SBV**

- Good for Propane

#M-72-SBV
FIP x FIP

Part #	Size	
46-411	1/4	----

SOLID BOTTOM FUEL VALVES

- Approved for use on Motorcraft fuel lines.
- Pointer lever.
- 90⁰ turn stop mechanism to assure positive location of the on and off positions.
- Corrosion proofed internal construction assures maximum salt atmosphere protection.
- Port hole is 1/4 (.250) diameter.
- UL listed for use in fuel oils no. 1 & no. 2, LP gas and utility gas.

PIPE MALE X FEMALE

Part #	Size	
46-400M	1/8 x 1/8	----
46-401M	1/4 x 1/4	----
46-402M	3/8 x 3/8	----

8980

PIPE
MALE x MALE

Part #	Size	
46-406M	1/4 x 1/4	----

8990

- Good for Propane

FEMALE X FEMALE

Part #	Size	
46-411M	1/4 x 1/4	----

8975

MALE PIPE X FLARE

Part #	Size	
46-429M	1/4 x 3/8	----
46-430M	3/8 x 3/8	----

8948

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

GROUND PLUG SHUT-OFF COCKS

NON-LUBRICATED PLUG VALVES are designed to operate in systems where INSTANTANEOUS PORT SELECTION is desired. Since LUBRICANTS ARE NOT USED, relubrication is not required. There is no lubricant to freeze and lock the valve or to contaminate fine fluids. The O-RING SEALED CAP and STEM eliminate leakage to atmosphere. The mating BRASS BODY and CELCON PLUG produce a fine seal that WILL NOT SEIZE OR GALL.

Designed for PANEL or BRACKET MOUNTING. They are generally recommended for operation in GASOLINE, OIL, AIR, WATER and DETERGENT systems from minus 40^0 to 180^{0}F, at a maximum operating pressure of 30 p.s.i.g. The fluid port size is 9/32 (.281) diameter for 1/8 and 1/4 sizes, 5/16 (.312) diameter for the 3/8 size. **(Consult factory for applications requiring a higher pressure).**



Bracket Mount


PANEL MOUNTING AVAILABLE

Type 1 (Standard)
A pronounced "click" may be felt at each position.

THREE-WAY VALVES (Side Outlet)



- 1-3/8" Stem
- Side Outlet
- Bracket Mounting
- O-Ring Sealed
- 4-way celcon roter standard

LESS CLICK

Part #	A-B-C Female Pipe Thread	Length of Stem	
46-247	1/4	1-3/8"	----
46-248	3/8	1-3/8"	----

M-108-MID WITH CLICK 360^0

Part #	A-B-C Female Pipe Thread	Length of Stem	
46-250	1/8	1-3/8"	----
46-251	1/4	1-3/8"	----
46-252	3/8	1-3/8"	----

V406P 6749

Openings:
Handle Pointer over A.....Valve Open A-C
Handle Pointer over C.....Valve Open B-C
Handle Pointer over B.....Valve "OFF"
Handle Pointer over Bracket.....Valve "OFF"

THREE-WAY VALVES (Bottom Outlet)



- 1-3/8" Stem
- Side Outlet
- Bracket Mounting
- O-Ring Sealed
- 4-way celcon roter standard

LESS CLICK

Part #	A-B-C Female Pipe Thread	Length of Stem	
46-241	1/4	1-3/8"	----

WITH CLICK 360^0

Part #	A-B-C Female Pipe Thread	Length of Stem	
46-243	1/8	1-3/8"	----
46-244	1/4	1-3/8"	----

Openings:
Handle *Pointer* over A.....Valve Open A-C
Handle *Pointer* over B.....Valve Open B-C
Handle *Pointer* over Bracket.....Valve "OFF"

FOUR-WAY VALVES



- Side Outlet
- Bracket Mounting
- O-Ring Sealed
- 4-way celcon roter standard

LESS CLICK

Part #	A-B-C-D Female Pipe Thread	Length of Stem	
46-257	1/4	1-3/8"	----

M-114-MID WITH CLICK (360^0)

Part #	A-B-C-D Female Pipe Thread	Length of Stem	
46-255	1/4	1-3/8"	----
46-256	3/8	1-3/8"	----

WITH 2-3/8" LONG STEM M-115-MID

Part #	A-B-C-D Female Pipe Thread	Length of Stem	
46-260	1/4	2-3/8"	----

V407P

Openings:
Handle *Pointer* over A.....Valve Open A-D
Handle *Pointer* over C.....Valve Open C-D
Handle *Pointer* over B.....Valve Open B-D
Handle *Pointer* over Bracket.....Valve "OFF"

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

MARINE FITTINGS

• Calibrated to support 30" column of gasoline.

BRASS ANTI-SIPHON VALVES

MALE X MALE

Part #	Size	
46-520	1/4 x 1/4	----
46-521	3/8 x 3/8	----
46-522	1/2 x 1/2	----

ALUMINUM

Part #	Size	
46-520A	1/4 x 1/4	----
46-521A	3/8 x 3/8	----

• Flo direction <-

BRASS ANTI-SIPHON VALVES

BARB X NPT

Part #	Size	
46-529	1/4 x 1/4	----
46-530	5/16 x 1/4	----
46-531	3/8 x 1/4	----
46-532	3/8 x 3/8	----
46-533	1/2 x 3/8	----

ALUMINUM

Part #	Size	
46-530A	5/16 x 1/4	----
46-531A	3/8 x 1/4	----
46-532A	3/8 x 3/8	----
46-533A	1/2 x 3/8	----

MINI BALL VALVE - BRASS W/ SS HANDLE AND NUT

Part #	Barb x MIP	
46-986	5/6 x 1/4	----
46-987	3/8 x 1/4	----
46-988	3/8 x 3/8	----
46-989	1/2 x 1/2	----

• NBR O-Ring
• Working temp 180°F
• 3,000 PSI
• Brass or Aluminum
• #316 Ball & Spring

MALE MIP X FEMALE FIP BRASS

Part #	Size	
46-523	1/4	----
46-524	3/8	----

ALUMINUM

Part #	Size	
46-523A	1/4	----
46-524A	3/8	----

FLARE X MIP - BRASS

Part #	Size	
46-526	3/8 x 1/4	----

SIX PORT VALVES



Six port fuel valves are used where 2 tanks supply a single engine, and a return to each supply tank is required.

ABYC H33.9.2 states that fuel system valves must have an independent means of support, so in-line valves are not suitable for fuel system applications

Part #	Ind. #	Female Pipe Thread of 1-2-3 4-5-6	Stem	Length Type	
46-237	SK-1036	1/2 x 3/8	13/16	1	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

BRASS MINIATURE BALL VALVES

- Working Pressure up to 1000 P.S.I.G.
- ASTM B-16 Corrosion Resistant Brass Body.
- Non-Adjusting Viton O-Ring Stem Seal Design Never Needs Tightening.
- Highly Inert Teflon Seats.
- Long Life Nickel Plated Brass Ball.
- Blow-Out Proof Stem for Safety.
- Temperature: -40°F to 300°F
- 1/4 Turn Instantaneous On-Off Operation.
- Quarter Turn Handle Design.
- Water, Oil, and Air Pressure Systems.
- Ideal for tight, confined areas, or when routing aesthetics are desired. Applications include instrumentation, gas sampling systems, high pressure gauges, test stands, hydraulic and pneumatic service lines on capital equipment.
- Not good for steam.
- Good for propane, gas and diesel.

MALE X FEMALE

Part #	Size	
46-900	1/8 x 1/8	----
46-903	1/4 x 1/4	----

MALE X MALE

Part #	Size	
46-910	1/8 x 1/8	----
46-912	1/4 x 1/4	----

MALE PIPE X HOSE BARB

Part #	Size	
47-042	1/8 x 1/4	----
46-980	1/4 x 1/4	----
46-981	1/4 x 3/8	----

FEMALE X FEMALE

Part #	Size	
46-920	1/8 x 1/8	----
46-921	1/8 x 1/4	----
46-922	1/4 x 1/4	----

Part #	Size	
46-922A	1/4 x 1/4	----
46-923	3/8 x 3/8	----

Part #	Size	
46-924	1/2 x 1/2	----
46-925	3/4 x 3/4	----

U.L. TWO WAY VALVES

- Buna-N Seal, Teflon Seat Plated metal handle, plated brass ball.
- 250 PSI Working Pressure

U.L. TWO WAY VALVES FNPT X FNPT

Part #	Size	
46-440	1/4 x 1/4	----

U.L. TWO WAY VALVES MNPT X FNPT

Part #	Size	
46-443	1/4 x 1/4	----

PANEL MOUNT BRASS BALL VALVES

- Working pressure: 1500 psi wog for 1/8" to 1/4", 1000 psi wog for 3/8" to 1/2"
- Vacuum rating: 29.92" Hg
- Working temp: -40°F to +300°F
- Panel mount hole is 9/16" Dia.
- Brass body cap, PTFE ball seats, Viton stem sealing, Brass chrome plated ball

FEMALE X FEMALE

Part #	Size	
46-830	1/8 x 1/8	----
46-832	1/4 x 1/4	----
46-833	3/8 x 3/8	----
46-834	1/2 x 1/2	----

FEMALE X FEMALE

Part #	Size	
46-875	1/8 x 1/8	----
46-878	1/4 x 1/4	----

Part #	Size	
46-951	1/8 FPT	----
46-956	1/4 FPT	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

CHECK VALVES

BRASS CHECK VALVES

- 500 PSI
- 180° temp rating
- 1 PSI Cracking Pressure
- Buna-N Seal for water, air and inert gas
- **Viton Seal for oil, gas and diesel fuel**

FIP X FIP BUNA-N

Part #	Size	
46-560	1/8"	----
46-561	1/4"	----
46-562	3/8"	----
46-563	1/2"	----
46-564	3/4"	----

FIP X FIP VITON

Part #	Size	
46-560V	1/8"	----
46-561V	1/4"	----
46-562V	3/8"	----
46-563V	1/2"	----
46-564V	3/4"	----

FEMALE X MALE BUNA-N

Part #	Size	
46-565	1/8"	----
46-566	1/4"	----
46-567	3/8"	----
46-568	1/2"	----
46-569	3/4"	----



MALE X MALE

Part #	Size	
46-570	1/8"	----
46-571	1/4"	----
46-572	3/8"	----
46-573	1/2"	----

MALE X FEMALE

Part #	Size	
46-575	1/8"	----
46-576	1/4"	----
46-577	3/8"	----
46-578	1/2"	----

HIGH PRESSURE CHECK VALVES

MAX. 2500 PSI
Cracking Pressure 1 PSI

- Opening diameter .187
- 180⁰ max operating temp.
- •SS ball and spring

CV = 0.4

MNPT X MNPT

Part #	Size	Opening Dia.	
46-500	1/4 x 1/4	0.187	----

MAX. 2500 PSI

- Flo direction ->
- Opening diameter .187
- 180⁰ max operating temp.
- Buna Seal
- •SS ball and spring

MNPT X FNPT

Part #	Size	Opening Dia.	
46-505	1/4 x 1/4	0.187	----

MAX. 1200 PSI

- O-Ring poppet seal Bubble tight operation
- 180°F max operating temp.

FNPT X FNPT

Part #	Size	Opening Dia.	
46-510	1/4 x 1/4	0.25	----
46-511	3/8 x 3/8	0.375	----
46-512	1/2 x 1/2	0.437	----

PNEUMATIC CHECK VALVES

- Max Operating Pressure: 220 psi
- Working Pressure: 14.5-145 psi
- Cracking Pressure: 2.8 psi
- Maximum Temperatures: 140° F

Body	Chrome plated Brass
Spring	Steel
O-Ring	NBR Rubber

NPT- Inlet NPSM - Outlet

Part #	Size	Dimensions (In.) A	Dimensions (In.) B	
46-200	1/4	1.97	0.67	----
46-201	3/8	1.97	0.83	----
46-202	1/2	2.48	0.98	----

HIGH PRESSURE CHECK VALVES

- Operates in any position, and is available in mixed or matched end combinations.
- Standard cracking pressure 1 p.s.i with a maximum operating pressure of 3000 p.s.i. and a maximum operating temperature of 180°F using Buna-N seals.
- Buna-N seals standard, other seals available.
- Guided 316 stainless steel ball + spring.
- Fixed ringed seat prevents extrusion of seal.
- Opening diameter .28
- Approximate CV 1.2
- Brass
- Water G.P.M. @ 10 p.s.i. is 4.0
- Good for air

FEMALE X FEMALE

Part #	Size	
46-513	1/4	----
46-517	3/8	----

FEMALE X MALE

Part #	Size	
46-514	1/4	----
46-518	3/8	----

MALE X FEMALE

Part #	Size	
46-516	1/4	----
46-539	3/8	----

MALE X MALE

Part #	Size	
46-515	1/4	----
46-519	3/8	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

LEAD FREE



What is the new lead-free requirement?

In 2011, the Reduction of Lead in Drinking Water Act was signed into law. The Act has reduced the lead content allowed in drinking water system and plumbing materials by changing the definition of "lead-free" in Section 1417of the Safe Drinking Water Act.

*The term "lead-free" has been updated from notmore that 8% lead content to mean "**not more than a weighted average of 0.25% lead when used with respect to the wetted surfaces of pipes, pipe fittings, plumbing fittings and fixtures.**"*

How do I know which products must meet the new lead-free requirement?

The prohibitions on use and introduction into commerce apply to all pipe, pipe fittings, plumbing fittings, and fixtures (henceforth reffered to as "products"), including stocked inventories that have not been installed. This includes coated or uncoated brass or bronze materials. By using the flowchart below as a guide, you can determine if a product must meet the new lead-free requirement:



Lead-Free Requirement Exemptions

(A) The new requirement does not apply to pipes, pipe fittings, plumbing fittings, or fixtures, including backflow preventers, that are used exclusively for nonpotable service such as manufacturing, industrial processing, irrigation, outdoor watering or any other uses where the water is not anticipated to be used for human consumption.

(B) The new requirement does not apply to toilets, bidets, urinals, fill valves, flushometer valves, tub fillers, shower valves, service saddles or water distribution main gate valves 2 inches in diameter or larger.

LEAD FREE

90⁰ FORGED FEMALE ELBOW

Part #		Thread size NPTF	Part #	
28-009LF	----	1/8"	28-001LF	----
28-010LF	----	1/4"	28-002LF	----
28-011LF	----	3/8”	28-003LF	----
28-012LF	----	1/2”	28-004LF	----
28-013LF	----	3/4”	28-005LF	----

UNION FORGED TEE

Part #		Thread size NPTF	Part #	
28-032LF	----	1/8"	28-024LF	----
28-033LF	----	1/4"	28-025LF	----
28-034LF	----	3/8”	28-026LF	----
28-035LF	----	1/2”	28-027LF	----
28-036LF	----	3/4”	28-028LF	----

90⁰ STREET ELBOW

Part #		Thread size NPTF	Part #	
28-165LF	----	1/8”	28-156LF	----
28-166LF	----	1/4”	28-157LF	----
28-167LF	----	3/8"	28-158LF	----
28-168LF	----	1/2”	28-159LF	----
28-169LF	----	3/4"	28-160LF	----

COUPLING

Part #	Thread size NPTF	
28-058LF	1/8"	----
28-059LF	1/4”	----
28-060LF	3/8"	----
28-061LF	1/2”	----

REDUCING COUPLING

	Part #	Thread size NPTF	
NEW	28-181LF	1/4" x 1/8"	----
NEW	28-182LF	3/8" x 1/8"	----
	28-183LF	3/8" x 1/4"	----
NEW	28-180LF	1/2" x 1/8"	----
	28-185LF	1/2” x 3/8”	----
NEW	28-188LF	3/4" x 3/8"	----
	28-189LF	3/4” x 1/2”	----

HEX BUSHING

Part #	Thread size NPTF MxF	
28-102LF	1/4” x 1/8”	----
28-103LF	3/8" x 1/8"	----
28-104LF	3/8” x 1/4”	----
28-105LF	1/2" x 1/8"	----
28-106LF	1/2” x 1/4”	----
28-107LF	1/2” x 3/8”	----
28-108LF	3/4" x 1/8"	----
28-109LF	3/4" x 1/4"	----
28-110LF	3/4" x 3/8"	----
28-111LF	3/4” x 1/2”	----
28-119LF	1 x 1/8	----
28-112LF	1 x 1/4	----
28-114LF	1 x 1/2	----
28-115LF	1" x 3/4"	----

FACE BUSHING

Part #	Thread size NPTF MxF	
28-121LF	1/4” x 1/8”	----
28-122LF	3/8" x 1/8"	----
28-116LF	3/8” x 1/4”	----
28-128LF	1/2” x 1/4”	----
28-117LF	1/2” x 3/8”	----
28-129LF	3/4" x 1/4"	----
28-130LF	3/4" x 3/8"	----
28-118LF	3/4" x 1/2"	----

HEX CAP

	Part #	Thread size NPTF	
	28-075LF	1/8"	----
	28-076LF	1/4"	----
	28-077LF	3/8”	----
	28-078LF	1/2"	----
	28-079LF	3/4”	----
NEW	28-080LF	1"	

SQUARE HEAD PLUG

Part #	Thread size NPTF	
28-084LF	1/8"	----
28-085LF	1/4"	----
28-086LF	3/8"	----
28-087LF	1/2"	----
28-088LF	3/4”	----

COUNTERSUNK HEX PLUG

Part #	Thread size NPTF	
28-093LF	1/8"	----
28-094LF	1/4"	----
28-095LF	3/8”	----
28-096LF	1/2”	----
28-097LF	3/4"	----
28-098LF	1"	----

CORED HEX PLUGS

Part #	Thread size NPTF	
28-201LF	1/8”	----
28-202LF	1/4”	----
NEW 28-203LF	3/8"	----
28-204LF	1/2"	----

CLOSE NIPPLE

Part #	Thread size NPTF	
28-131LF	1/8"	----
28-132LF	1/4”	----
28-133LF	3/8”	----
28-134LF	1/2”	----
28-135LF	3/4”	----

LONG NIPPLE

Part #	Thread size NPTF	
28-141LF	1/8" x 2"	----
28-144LF	1/4" x 1-1/2"	----
28-145LF	1/4" x 2"	----
28-147LF	1/4" x 3"	----
28-148LF	3/8” x 1-1/2"	----
28-149LF	3/8" x 2"	----

HEX NIPPLE

	Part #	Thread size NPTF	
	28-211LF	1/8"	----
	28-212LF	1/4”	----
NEW	28-220LF	1/4" x 1/8"	----
	28-213LF	3/8"	----
	28-222LF	3/8" x 1/4"	----
	28-214LF	1/2”	----
	28-224LF	1/2" x 3/8"	----
	28-215LF	3/4"	----
	28-225LF	3/4" x 1/2"	----

MALE BRANCH TEE

	Part #	Thread size NPTF	
	28-283LF	3/8”	----
NEW	28-284LF	1/2"	

EXTENDER ADAPTER

	Part #	Thread size NPTF FxM	
NEW	28-190LF	1/8" x 1/8"	----
	28-191LF	1/4” x 1/8”	----
	28-192LF	1/4" x 1/4"	----
	28-193LF	3/8" x 1/4"	----
NEW	28-194LF	3/8" x 3/8"	----
NEW	28-199LF	1/2" x 1/4"	----
	28-195LF	1/2" x 3/8"	----
	28-196LF	1/2” x 1/2”	----
NEW	28-207LF	3/4" x 3/8"	----
	28-208LF	3/4" x 1/2"	----

STREET TEE/ SERVICE TEE

NEW

Part #	Thread size NPTF	
28-245LF	1/8"	----
28-246LF	1/4"	----
28-247LF	3/8"	----
28-248LF	1/2"	----

HOSE BARBS

RIGID MALE ADAPTER

	Part #	Hose I.D. x Male NPTF	
	32-001LF	1/8" x 1/8"	----
	32-027LF	1/8" x 1/4"	----
	32-002LF	3/16” x 1/8”	----
	32-003LF	3/16" x 1/4"	----
	32-004LF	1/4” x 1/8”	----
	32-005LF	1/4” x 1/4”	----
	32-006LF	1/4" x 3/8"	----
	32-007LF	1/4" x 1/2"	----
NEW	32-954LF	1/4" x 3/4"	----
	32-008LF	5/16” x 1/8”	----
	32-009LF	5/16” x 1/4”	----
	32-010LF	5/16" x 3/8"	----
	32-011LF	3/8” x 1/8”	----
	32-012LF	3/8” x 1/4”	----
	32-013LF	3/8” x 3/8”	----
	32-014LF	3/8” x 1/2”	----
	32-026LF	3/8" x 3/4"	----
	32-015LF	1/2” x 1/4”	----
	32-016LF	1/2” x 3/8”	----
	32-017LF	1/2” x 1/2”	----
	32-018LF	1/2" x 3/4"	----
	32-019LF	5/8" x 3/8"	----
	32-020LF	5/8” x 1/2”	----
	32-021LF	5/8" x 3/4"	----
	32-306LF	3/4" x 3/8"	----
	32-022LF	3/4” x 1/2”	----
	32-023LF	3/4” x 3/4”	----
	32-024LF	1" x 3/4"	----
	32-025LF	1" x 1"	----

MENDER/ SPLICER

Part #	Hose I.D. x Hose I.D.	
32-091LF	1/8"	----
32-092LF	3/16"	----
32-093LF	1/4”	----
32-094LF	5/16"	----
32-095LF	3/8"	----
32-096LF	1/2”	----
32-097LF	5/8"	----
32-098LF	3/4"	----

RIGID FEMALE ADAPTER

	Part #	Hose I.D. x Female NPTF	
	32-050LF	1/8" x 1/8"	----
	32-317LF	1/8" x 1/4"	----
NEW	32-062LF	3/16" x 1/4"	----
	32-052LF	1/4" x 1/8"	----
	32-053LF	1/4" x 1/4"	----
	32-054LF	1/4" x 3/8"	----
	32-055LF	5/16" x 1/8"	----
	32-056LF	5/16" x 1/4"	----
	32-057LF	3/8" x 1/8"	----
	32-058LF	3/8" x 1/4"	----
	32-059LF	3/8" x 3/8"	----
	32-063LF	3/8" x 1/2"	----
	32-064LF	1/2" x 1/4"	----
	32-060LF	1/2" x 3/8"	----
	32-061LF	1/2" x 1/2"	----
	32-065LF	3/4" x 3/4"	----

FORGED HOSE BARB 90° ELBOW

Part #	Hose I.D. x Male NPTF	
32-038LF	1/4" x 1/8"	----
32-039LF	1/4" x 1/4"	----
32-309LF	1/4" x 3/8"	----
32-036LF	5/16" x 1/8"	----
32-040LF	5/16" x 1/4"	----
32-046LF	3/8" x 1/8"	----
32-041LF	3/8" x 1/4"	----
32-042LF	3/8" x 3/8"	----
32-047LF	3/8" x 1/2"	----
32-048LF	1/2" x 1/4"	----
32-043LF	1/2" x 3/8"	----
32-311LF	1/2" x 1/2"	----
32-313LF	3/4" x 1/2"	----

HOSE BARB TEES

Part #	Hose Barb Size	
32-365LF	1/4"	----
32-126LF	3/8"	----

FEMALE 45° FLARE SWIVEL

Part #		
32-105LF	3/8" x 3/8"	----

LEAD FREE MINI BALL VALVES BARB x BARB

Part #	H.B. x H.B.	
944-142LF	1/4"	----
944-134LF	3/8"	----

PUSH-ON

MALE ADAPTER

Part #	Hose I.D. x Male NPTF	
30-200LF	1/4" x 1/8"	----
30-201LF	1/4" x 1/4"	----
30-203LF	3/8" x 1/4"	----
30-204LF	3/8" x 3/8"	----
30-206LF	1/2" x 3/8"	----
30-207LF	1/2" x 1/2"	----

SAE/JIC DUAL 45°/37° FEMALE SWIVEL

Part #	Hose I.D. x Female 45°/37°	
30-230LF	1/4" x 1/4"	----

GARDEN HOSE

SWIVEL - FGH X FGH

• WASHER INCLUDED

Part #	FGH X FGH	
30-011LF	3/4" x 3/4"	----

SWIVEL - FGH X FEMALE PIPE

NEW

• WASHER INCLUDED

Part #	FGH x Female NPTF	
30-001LF	3/4" x 1/2"	----
30-006LF	3/4" x 3/4"	----

RIGID - FGH X FEMALE PIPE

• WASHER INCLUDED

NEW

Part #	FGH x Female NPTF	
30-083LF	3/4" x 3/4"	----

SWIVEL - FGH X MALE PIPE

• WASHER INCLUDED

Part #	FGH x Male NPTF	
30-047LF	3/4" x 1/4"	----
NEW 30-048LF	3/4" x 3/8"	----
30-049LF	3/4" x 1/2"	----

RIGID - FGH X MALE PIPE

• WASHER INCLUDED

NEW

Part #	FGH x Male NPTF	
30-088LF	3/4" x 1/2"(1/2"SWT)**	----
30-094LF	3/4" x 3/4"(1/2" FIP)	----

RIGID - MGH X FEMALE PIPE

Part #	MGH X Female NPTF	
NEW 30-066LF	3/4" x 1/4"	----
NEW 30-068LF	3/4" x 1/2"	----
30-073LF	3/4" x 3/4"	----

RIGID - MGH X MALE PIPE

Part #	MGH X Male NPTF	
30-052LF	3/4" x 1/4"	----
NEW 30-053LF	3/4" x 3/8"	----
NEW 30-058LF	3/4" x 1/2"	----
30-063LF	3/4" x 3/4" x 1/2"	----

RIGID - MGH X MGH

NEW

Part #	MGH X MGH	
30-098LF	3/4" x 3/4" (1/2" FIP)	----

GARDEN HOSE CAP

NEW

Part #	Size	
30-103LF	3/4" Die Cast	----

RIGID - MGH X FEMALE PIPE

Part #	MGH x Female NPTF	
NEW 30-066LF	3/4" x 1/4"	
NEW 30-068LF	3/4" x 1/2"	
30-073LF	3/4" x 3/4"	----

SHORT ROD NUT

	Part #	Thread Size UNF	
NEW	10-013LF	1/8"	----
NEW	10-014LF	3/16"	----
	10-015LF	1/4"	----
NEW	10-016LF	5/16"	----
	10-017LF	3/8”	----
NEW	10-018LF	7/16"	----
	10-019LF	1/2”	----
NEW	10-020LF	5/8"	----
	10-021LF	3/4"	----

SHORT FORGED NUT

	Part #	Thread Size UNF	
NEW	10-039LF	1/4"	----
	10-041LF	3/8”	----
	10-042LF	1/2”	----

FLARED CAP

	Part #	Thread Size UNF	
	10-075LF	1/4”	----
	10-077LF	3/8”	----
	10-078LF	1/2”	----
	10-079LF	5/8”	----
NEW	10-080LF	3/4"	----

UNION

	Part #	Thread Size UNF	
NEW	10-104LF	1/8"	70404202
NEW	10-105LF	3/16"	70404203
	10-106LF	1/4”	----
NEW	10-107LF	5/16"	70404205
	10-108LF	3/8”	----
	10-118LF	3/8" x 1/4"	----
	10-109LF	1/2”	----
NEW	10-121LF	1/2" x 3/8"	
	10-110LF	5/8”	----
NEW	10-123LF	5/8" x 1/2"	

MALE BRANCH TEE

Part #	Size	
10-204LF	1/4" x 1/8"	----

FEMALE ADAPTER

	Part #	Male Flare x Female NPTF	
NEW	10-228LF	1/4" x 1/8"	
	10-229LF	1/4" x 1/4"	----
NEW	10-230LF	1/4" x 3/8"	
NEW	10-235LF	3/8" x 1/4"	
	10-236LF	3/8” x 3/8”	----
	10-237LF	3/8” x 1/2”	----
	10-240LF	1/2” x 3/8”	----
	10-241LF	1/2” x 1/2”	----
	10-242LF	1/2” x 3/4”	----
NEW	10-244LF	5/8" x 1/2"	
NEW	10-245LF	5/8" x 3/4"	
NEW	10-247LF	3/4" x 3/4"	

MALE ADAPTER

	Part #	Male Flare x Male NPTF	
	10-255LF	1/4” x 1/8”	----
	10-256LF	1/4” x 1/4”	----
	10-257LF	1/4" x 3/8"	----
	10-258LF	1/4” x 1/2”	----
	10-262LF	3/8” x 1/8”	----
	10-263LF	3/8” x 1/4”	----
	10-264LF	3/8” x 3/8”	----
	10-265LF	3/8” x 1/2”	----
NEW	10-266LF	3/8" x 3/4"	----
	10-267LF	1/2" x 1/4"	----
	10-268LF	1/2” x 3/8”	----
	10-269LF	1/2” x 1/2”	----
	10-270LF	1/2” x 3/4”	----
	10-272LF	5/8" x 3/8	----
	10-273LF	5/8" x 1/2"	----
	10-274LF	5/8" x 3/4"	
NEW	10-275LF	3/4" x 1/2"	----
	10-276LF	3/4” x 3/4”	----
NEW	10-278LF	7/8" x 3/4"	

90° MALE ELBOW

Forged Elbow

Part #	Male Flare x Male NPTF	
10-286LF	1/4" x 1/8"	----
10-287LF	1/4" x 1/4"	----
10-288LF	1/4" x 3/8"	----
10-293LF	3/8" x 1/8"	----
10-294LF	3/8" x 1/4"	----
10-295LF	3/8" x 3/8"	----
10-296LF	3/8" x 1/2"	----
10-299LF	1/2" x 3/8"	----
10-300LF	1/2" x 1/2"	----
10-301LF	1/2" x 3/4"	----
10-305LF	3/4" x 1/2"	----
10-306LF	3/4" x 3/4"	----

FORGED MALE RUN TEE

Part #	Male Flare x Male NPTF (1&3) x 2	
10-351LF	3/8" x 3/8"	----
10-355LF	1/2" x 1/2"	----
10-359LF	3/4" x 1/2"	----

FORGED SWIVEL

	Part #	Female Flare UNF	
NEW	10-481LF	1/4"	7407004
	10-483LF	3/8"	----
	10-484LF	1/2"	----
	10-485LF	5/8"	----
	10-487LF	3/8" x 1/4"	----
NEW	10-488LF	1/2" x 3/8"	

TEE

Part #	Size	
10-159LF	1/4"	----
10-161LF	3/8"	----

BRASS SLEEVE

• FERRULES

Part #	Size	
18-002LF	3/16"	----
18-003LF	1/4"	----
18-004LF	5/16"	----
18-005LF	3/8"	----
18-007LF	1/2"	----
18-008LF	5/8"	----
18-009LF	3/4"	----
18-010LF	7/8"	----

60 260

NUT

NEW

BRASS C/P

Part #	Size	
18-035LF	1/4"	70006104
18-037LF	3/8"	70006106
18-039LF	1/2"	70006108
18-040LF	5/8"	70006110

DELRIN SLEEVE

Part #	Size	
18-015	1/4"	----
18-016	5/16"	----
18-017	3/8"	----
18-018	1/2"	----
18-019	5/8"	----

60-P

BRASS INSERT

• SLEEVE

Part #	Size	
22-010LF	1/4"	----
22-011LF	5/16"	----
22-012LF	3/8"	----
22-013LF	1/2"	----
22-014LF	5/8"	----

63-BI 60AE 2030 63PT

CAP

Part #	Size	
18-047LF	1/4”	----
18-048LF	3/8”	----
18-049LF	1/2”	----
18-050LF	5/8”	----

61-CC N5CT

UNION

BRASS C/P

Part #	Size	
18-062LF	1/8”	----
18-063LF	3/16”	----
18-064LF	1/4”	----
18-065LF	5/16”	----
18-066LF	3/8”	----
18-067LF	7/16"	----
18-068LF	1/2”	----
18-069LF	5/8”	----
18-070LF	3/4”	----
18-071LF	7/8”	----

M-62

REDUCING UNION

Part #	Size	
18-076LF	1/4” x 1/8”	----
18-077LF	1/4” x 3/16”	----
18-078LF	5/16” x 1/4”	----
18-079LF	3/8” x 1/4”	----
NEW 18-080LF	3/8" x 5/16"	7000820605
18-081LF	1/2" x 3/8"	----
18-082LF	5/8" x 3/8"	----
18-083LF	5/8" x 1/2"	----

62-R

TEE

Part #	Size	
18-101LF	1/8”	----
18-102LF	3/16"	----
18-103LF	1/4”	----
18-104LF	5/16"	----
18-105LF	3/8”	----
18-106LF	1/2”	----
18-107LF	5/8”	----
18-109LF	7/8”	----

FORGED REDUCING TEE

Part #	Size	
18-115LF	3/8” x 3/8” x 1/4”	----
18-117LF	1/2” x 1/2” x 3/8”	----

64-R

UNION ELBOW

Part #	Size	
18-124LF	1/4”	----
18-125LF	5/16”	----
18-126LF	3/8”	----
18-127LF	1/2”	----
18-128LF	5/8”	----
18-129LF	3/4”	----
18-130LF	7/8”	----

65 BSE2 165C 265C

REDUCING ELBOW - Forged

Part #	Size	
18-135LF	3/8” x 1/4”	----
NEW 18-136LF	1/2" x 3/8"	7000850806
18-137LF	5/8” x 3/8”	----

65-R

COMP X SWEAT ADAPTER

Part #		Comp. X Sweat Adapter		Part #
18-171LF	----	3/8” x 1/2” nom.swt.		31-171

66-S

COMPRESSION

LEAD FREE BRASS FITTINGS

LEAD FREE

FEMALE ADAPTER

	Part #		Comp. X Female NPT	Part # C/P	
	18-142LF	----	1/8” x 1/8”		
	18-143LF	----	3/16” x 1/8”		
	18-145LF	----	1/4” x 1/8”		
	18-146LF	----	1/4” x 1/4”		
	18-147LF	----	1/4” x 3/8”		
	18-148LF	----	1/4” x 1/2”		
	18-150LF	----	5/16” x 1/4”		
	18-151LF	----	5/16” x 3/8”		
	18-152LF	----	3/8” x 1/8”		
	18-153LF	----	3/8” x 1/4”		
	18-154LF	----	3/8” x 3/8”	31-154	
	18-155LF	----	3/8” x 1/2”	31-155	
	18-156LF	----	3/8” x 3/4”		
	18-158LF	----	1/2” x 3/8”		
	18-159LF	----	1/2” x 1/2”	31-159	
	18-160LF	----	1/2” x 3/4”		
NEW	18-161LF		5/8" x 3/8"		
	18-162LF	----	5/8” x 1/2”		
	18-163LF	----	5/8” x 3/4”		
NEW	18-165LF		3/4" x 3/4"		
NEW	18-167LF		7/8" x 1/2"		
	18-166LF	----	7/8” x 3/4”		

66

MALE ELBOW

Forged

Part #	Comp. X Male NPT	
18-220LF	1/8" x 1/8"	
18-221LF	3/16” x 1/8”	----
18-224BLF	1/4" x 1/8"	----
18-225BLF	1/4” x 1/4”	----
18-226BLF	1/4" X 3/8"	----
18-227LF	1/4” x 1/2”	----
18-228LF	5/16” x 1/8”	----
18-229LF	5/16” x 1/4”	----
18-232BLF	3/8” x 1/8”	----
18-233BLF	3/8” x 1/4”	----
18-234BLF	3/8” x 3/8”	----
18-235BLF	3/8” x 1/2”	----
18-236LF	1/2” x 1/4”	----
18-237BLF	1/2” x 3/8”	----
18-238BLF	1/2” x 1/2”	----
18-239LF	1/2” x 3/4”	----
18-240LF	5/8” x 3/8”	----
18-241BLF	5/8” x 1/2”	----
18-242BLF	5/8” x 3/4”	----
18-246LF	7/8” x 3/4”	----

69 269C BSE1 169C

MALE ADAPTER

	Part #		Comp. X Male NPT	Part # C/P	
	18-176LF	----	1/8” x 1/8”		
	18-177LF	----	3/16” x 1/8”		
	18-178LF	----	3/16” x 1/4”		
	18-179LF	----	1/4” x 1/8”		
	18-180LF	----	1/4” x 1/4”		
	18-181LF	----	1/4” x 3/8”		
	18-182LF	----	1/4” x 1/2”		
	18-183LF	----	5/16” x 1/8”		
	18-184LF	----	5/16” x 1/4”		
	18-187LF	----	3/8” x 1/8”		
	18-188LF	----	3/8” x 1/4”		
	18-189LF	----	3/8” x 3/8”	31-189	
	18-190LF	----	3/8” x 1/2”	31-190	
	18-191LF	----	3/8” x 3/4”	31-191	
	18-192LF	----	7/16” x 1/4”		
	18-193LF	----	1/2” x 1/4”		
	18-194LF	----	1/2” x 3/8”		
	18-195LF	----	1/2” x 1/2”		
	18-196LF	----	1/2” x 3/4”		
	18-197LF	----	5/8” x 3/8”		
	18-198LF	----	5/8” x 1/2”		
	18-199LF	----	5/8” x 3/4”		
NEW	18-200LF		3/4" x 1/2"		
	18-201LF	----	3/4” x 3/4”		
	18-202LF	----	7/8” x 1/2”		
	18-203LF	----	7/8” x 3/4”		

FEMALE ELBOW

Forged

	Part #	Comp. X Female NPT	
	18-253LF	1/4” x 1/8”	----
	18-254LF	1/4” x 1/4”	----
	18-267LF	1/4” x 3/8”	----
	18-258BLF	3/8" x 1/4"	----
	18-259BLF	3/8” x 3/8”	----
	18-260LF	3/8” x 1/2”	----
	18-262BLF	1/2” x 3/8”	----
	18-263LF	1/2” x 1/2”	----
NEW	18-269BLF	5/8" x 3/8"	----
	18-264BLF	5/8” x 1/2”	----

70 270C BSE3 170C

COUPLING NUT

	Part #		
NEW	50-032	1/2" IPS	----

NEEDLE VALVES

COMP X MALE PIPE



Part #	Comp x Male Pipe	
46-002LF	1/4" x 1/8"	----
46-003LF	1/4" x 1/4"	----
46-005LF	3/8" x 1/4"	----

COMP X MALE PIPE-ANGLE

Part #	Comp x Male Pipe	
46-011LF	1/4" x 1/8"	----
46-012LF	1/4" x 1/4"	----

COMP X COMP

Part #	Comp x Comp	
46-021LF	1/4"	----
46-023LF	3/8"	----

FEMALE PIPE X FEMALE PIPE

Part #	Female x Female	
46-055LF	1/8" x 1/8"	----
46-056LF	1/4" x 1/4"	----

MALE X FEMALE PIPE

Part #	Male x Female	
46-061LF	1/4" x 1/4" MIP	----

LEAD FREE DISHWASHER TEES

COMP X COMP X SWIVEL FE COMPRESSION

- For adding a water line
- Ice makers, Coffe makers and instant hot water systems



Part #	Male & Fem. compression x Male Comp	
935044LF	3/8 x 1/4	----
935045LF	3/8 x 3/8	----

MISCELLANEOUS

FLARE X FLARE

Part #	Comp x Comp	
46045LF	1/4"	

Ice Maker Kits

ICE MAKER WATER SUPPLY KIT with Poly Tubing



- Lead free fittings
- Bag with Header Card
- 25' 1/4" O.D. Polyethylene Tubing - 979215
- Self Piercing Saddle Valve
- 1/4" O.D. Compression x 1/8" MIP Elbow & Adapter
- 1/4" O.D. Compression Union
- 1/4" Inserts & Sleeves

Part #	Description	
43-265LF	Kit	----
979-215	1/4" OD, 25' Tube	----

ICE-MAKER WATER SUPPLY KIT

- Economy
- 25' Polyethylene Tubing
- Self Piercing Saddle Valve
- 1/4" Compression Union
- 1/4" Inserts & Sleeves



Part #	
43-266LF	----

SELF PIERCING SADDLE VALVES

SELF PIERCING NEEDLE VALVE KIT #M-104-VSP

- **INDIVIDUALLY BAGGED WITH NEEDLE VALVE**
- **SADDLE CLAMP**
- **2 NUTS**
- **2 BOLTS & WASHERS**

Has brass sleeve for copper tube installation & delrin sleeve & brass insert for plastic tube installation.

Part #	Tube O.D.	Min Pkg Qty	
46-090ALF	1/4	1	----

VALVES



VALVES 168-213

LEAD FREE BALL VALVES 169-171
LEAD FREE VALVES 172
BRASS VALVES 173-197
Full Port Ball 173
Locking Handle 174
Butterfly Handle 175
N/P Ball Valve 176
N/P Ball w/SS Trim 177
Italian Ball Valve 178
M X F Ball Valve 179-180
Tee Handle M X F Ball 181
M X F Ball Locking handle 182
Spring Handle Ball Valve 183
Right Angle Ball valve 183
Wye, 3-Way Ball Valve 184
Safety Exhaust Ball Valve 184
Gas Valves 185
Mini Ball Valves 186-189
3-Way Valves 190
Strainer Ball Valve 191
Vacuum Breaker/Hose Bibb 191
Bent Nose Garden Valve 191
Gate Valves 192
Quick Opening Gate 193
Y Strainer 194
Check Valves 195-197

STAINLESS STEEL VALVES

2000# Full Port 198
Standard Port 199
1,000 PSI Full Port 200
SS Mini Ball Valve 201-202
Check Valves 203-207
Y-strainer, Globe,Gate 207

Carbon Steel valves 208-211

2,000# Standard Port 208
2,000 # FP 2-Piece 209
Hi Pressure 2-Way Valves 210
Hi Pressure 3-Way Balves 210
Check valves-5,000# 211

PVC Valves 212-213

LEAD FREE BALL VALVE

5 PSIG C US

• BRASS • 600PSI • STAINLESS STEEL BALL • FULL PORT

LEAD FREE

IAMPO IGC 157 - 2004b

Lead Free Brass Ball Valve NPT,Female*Female
Lead Free and dezincification resistant (DZR) material
IAPMO listed to NSF/ANSI-61, NSF/ANSI-372 ,IGC-157
CSA listed to NSF/ANSI-61, NSF/ANSI-372 ,IGC-157
Vacuum Services 29.92 inches Hg
600 psi (WOG) 150 psi (WSP) Service
Thread conform ANSI B1.20.1
Temperature Range : -40° F to 365° F
Construction:Forging Brass Body
PTFE Ball Seats
Blow Out Proof Brass Stem
Stainless Steel Ball
Steel Handle w/Vinyl Grip
Made in China



• Generic Handles

FIP X FIP LEAD FREE BALL VALVE

Part #	Size	OD	A	B	C	E	F	G	H	Weight	Box/Case	
941151LF	1/4"	0.394	1.73	1.69	3.35	0.453	0.945	2.154	4.331	0.32	10/120	----
941152LF	3/8"	0.394	1.73	1.69	3.35	0.473	0.945	2.154	4.331	0.32	10/120	----
941153LF	1/2"	0.524	1.89	1.73	3.35	0.472	1.083	2.276	4.291	0.36	10/100	----
941154LF	3/4"	0.748	2.28	1.89	3.35	0.563	1.378	2.579	4.488	0.57	10/80	----
941155LF	1"	0.984	2.80	2.14	4.29	0.650	1.772	3.031	5.689	0.94	8/48	----
941156LF	1-1/4"	1.240	3.15	2.32	4.29	0.669	2.165	3.398	5.866	1.30	4/36	----
941157LF	1-1/2"	1.476	3.44	2.66	5.53	0.701	2.50	3.909	7.343	1.92	2/24	----
941158LF	2"	1.949	4.06	3.01	5.53	0.708	3.244	4.638	7.638	3.12	2/12	----



• Generic Handles

SWT X SWT LEAD FREE BALL VALVE

Part #	Size	OD	A	B	C	E	G	H	Weight	WTG	Box/Case	
941163LF	1/2"	0.524	1.945	1.73	3.35	0.504	1.083	2.276	4.319	0.38	10/100	----
941164LF	3/4"	0.748	2.654	1.89	3.35	0.748	1.378	2.579	4.665	0.65	10/80	----
941165LF	1"	0.984	3.315	2.14	4.29	0.909	1.772	3.031	5.949	0.93	8/48	----
941166LF	1-1/4"	1.240	3.741	2.32	4.29	0.968	2.165	3.398	6.165	1.35	4/36	----
941167LF	1-1/2"	1.476	4.252	2.66	5.63	1.091	2.50	3.909	7.756	1.88	2/24	----
941168LF	2"	1.949	5.38	3.01	5.63	1.343	3.244	4.638	8.268	3.62	2/12	----



No	Item	Qty	Material
1	Body	1	Lead Free Brass
2	Seat	2	PTFE
3	Ball	1	Stainless Steel
4	Stem	1	Brass
5	Handle Nut	1	Plated Steel
6	Lock Washer	1	Plated Steel
7	Packing Nut	1	Brass
8	Packing	1	PTFE
9	Handle	1	Plated Steel
10	Cap	1	Lead Free Brass

LEAD FREE

1/2" - 2" Sizes Gas Approved

C US UL842, UL258, UL125,FM

LEAD FREE BALL VALVE W/APPROVALS

• BRASS • 600PSI • FULL PORT

CSA, UL, FM(1/4"-2"), cUPC, NSF/ ANSI 61 & 372

FEATURES

- Leadfree Brass Ball valve NPT, Female * Female
- Lead free and dezincification resistant (DZR) material
- 1/4"-1" Lead Free Brass Ball
- Size 1-1/4" thru 4" with Stainless steel ball
- IAMPO listed to cUPC, NSF/ ANSI 61 & 372, IGC 157
- CSA - 1/4" thru 2": ANSI Z21.15/ CSA 9.1 for 1/2 psig valves ASME B16.44, CGA CR91-002 for 2 & 5 psig valves; CAN/ CGA-3.16, ASME B16.33 (1/2"-2") for 125 psig valves
- UL 125, UL 1477, UL 842 - for size 1/4" thru 4", 250 psig
- UL 258 - for size 1/4" thru 2", 175 psig
- FM - for size 1/4" thru 2"
- ISO 9002 Manufacture
- Suitable for full range of liquids and gases
- Minimal pressure drop due to large full size ports
- Bottom loaded, pressure retaining stem
- Pressure rated for 1/4"-2" at 600psi (42 bars) and 2-1/2"-4" at 400 psi WOG (non-shock) and 150 WSP (10.34 bars) saturated steam. Virgin PTFE stem packing seal, thrust washer and seats
- White vinyl insulator on heavy duty plated carbon steel handles
- Fast 1/4 turn open or close operation
- Low operating torque
- **Adjustable stem packing gland**
- Maximum operating temperature: 302^{0}F (150^0 C)
- Minimum operating temperature: -22^{0}F (-30^{0}C)
- Each valve individually tested
- Forged Brass - for more strength
- Threaded ends to ANSI B1.20.1
- Hard chromium plated solid ball
- Bottom entry, blow-out proof stem
- Deeper threads - for better connections
- Made in China

POS	Components	Materials
1	Body	Lead Free Brass
2	End Cap	Lead Free Brass
3	Ball Seat	PTFE
4	Ball	1/4-1:Lead Free Brass 1 1/4-4:SS316 Hollowball
5	Stem	Brass
6	Stem Padding	PTFE
7	Padding Nut	Brass
8	Lever Handle	Nickel plating steel
9	Stem Nut	Brass plating steel
10	Seal	PTFE

• Generic Handles



Part#	Size	DIMENSIONS A	B	C	D	E	F	G	H	Weight	Box/Case	
940-171LF	1/4"	1.756	1.732	3.543	0.394	0.457	1.012	2.238	4.421	0.34	70/140	----
940-172LF	3/8"	1.756	1.732	3.543	0.394	0.457	1.012	2.238	4.421	0.34	70/140	----
940-173LF	1/2"	2.047	2.040	3.543	0.583	0.520	1.240	2.559	4.567	0.45	50/100	----
940-174LF	3/4"	2.362	2.260	3.780	0.748	0.563	1.492	2.854	4.961	0.69	30/60	----
940-175LF	1"	2.756	2.579	4.528	0.945	0.630	1.791	3.476	5.906	1.11	20/40	----
940-176LF	1-1/4"	3.307	3.050	4.528	1.260	0.709	2.343	4.134	6.181	1.85	12/24	----
940-177LF	1-1/2"	3.661	3.366	5.420	1.575	0.717	2.835	4.783	7.343	2.60	9/18	----
940-178LF	2"	4.181	3.701	5.42	1.969	0.748	3.425	5.413	7.602	3.62	6/12	----
940-179LF	2-1/2"	4.181	4.650	8.870	2.520	1.024	4.331	6.969	11.350	7.93	3/6	----
940-180LF	3"	6.039	4.970	8.870	2.913	1.102	4.921	7.579	11.681	10.40	1/4	----
940-181LF	4"	7.386	6.130	10.85	3.898	1.220	6.430	9.055	13.299	20.99	1/2	----

SWT X SWT LEAD FREE BALL VALVE

FM, cUPC, NSF/ ANSI 61 & 372

Part #	SWT	A	B	C	D	E	F	Weight	Box/Case	
943-612LF	1/2"	2.047	1.839	3.543	0.583	0.512	0.630	0.45	50/100	----
943-613LF	3/4"	2.748	2.14	3.780	0.748	0.748	0.878	0.68	30/60	----
943-614LF	1"	3.228	2.449	4.528	0.945	0.906	1.130	1.08	20/40	----
943-615LF	1-1/4"	3.819	3.04	4.36	1.260	0.972	1.378	1.80	12/24	----
943-616LF	1-1/2"	4.425	3.169	5.39	1.575	1.088	1.630	2.51	9/18	----
943-617LF	2"	5.377	3.488	6.307	1.989	1.346	2.130	3.57	6/12	----

ITALIAN LEAD FREE BRASS BALL VALVE

5 PSIG C US

UL842, UL258, UL125,FM

CSA AGA 3.88 5 PSIG

IAMPO IGC 157 - 2004b

ISO 9002 Manufacturer

FEATURES

600 PSI non-shock cold water, gas, oil - 150 PSI saturated steam

- **SOLID CHROME PLATED BRASS BALL**
- Suitable for full range of liquids and gases
- Minimal pressure drop due to large full size ports
- Bottom loaded, pressure retaining stem
- Pressure rated at 600psi (42 bars) WOG (non-shock) and 150 WSP (10.34 bars) saturated steam. Virgin TFE stem packing seal, thrust washer and seats.
- Blue vinyl insulator on heavy duty plated carbon steel handles.
- Fast 1/4 turn open or close operation
- Low operating torque
- Flow can go both directions
- Adjustable stem packing gland
- Maximum operating temerature: 248^{0}F (120^0 C) at 600 PSI
- Minimum operating temperature: -20^{0}F (-40^{0}C)
- Each valve individually tested
- Forged Brass - for more strength
- Threaded ends to ANSI B1.20.1
- Hard chromium plated solid ball
- Bottom entry, blow-out proof stem
- Deeper threads - for better connections

MADE IN ITALY

FIP X FIP

ANSI/INSF 61-8

- Generic Handles

SWT X SWT

FIP X FIP LEAD FREE FORGED BRASS BALL VALVE

Part #	NPT	DN	A	B	C	D	CH	Weight (lbs)	Box/Case	
943-233LF	1/2"	0.57	2.09	1.57	3.35	0.46	0.98	0.39	20/80	----
943-234LF	3/4"	0.75	2.28	1.77	3.80	0.49	1.22	0.56	14/56	----
943-235LF	1"	0.94	3.04	2.03	3.80	0.59	1.50	0.89	6/24	----
943-236LF	1-1/4"	1.24	3.23	2.32	4.72	0.62	1.85	1.44	4/16	----
943-237LF	1-1/2"	1.49	3.70	2.60	4.72	0.64	2.13	2.19	2/8	----
943-238LF	2"	1.96	4.13	3.27	6.38	0.65	2.64	3.62	1/4	----

SWT X SWT LEAD FREE FORGED BRASS BALL VALVE

Part #	SWT	Ø	DN	A	B	C	D	CH	Weight (lbs)	Box/Case	
940-212LF	1/2"	0.63	0.57	2.40	1.57	3.35	0.42	0.79	0.35	20/80	----
940-213LF	3/4"	0.866	0.75	3.26	1.77	3.80	0.61	1.06	0.55	10/40	----
940-214LF	1"	1.102	0.94	3.68	2.03	3.80	0.73	1.34	0.87	6/24	----
940-215LF	1-1/4"	1.377	1.24	4.23	2.32	4.72	0.91	1.61	1.41	6/24	----
940-216LF	1-1/2"	1.61	1.49	4.96	2.60	4.72	1.06	1.89	2.08	2/8	----
940-217LF	2"	2.125	1.96	5.86	3.27	6.38	1.26	2.40	3.62	1/4	----



POS	Components	Materials
1	Body	CW510L
2	End Connection	CW510L
3	Ball Seal	PTFE
4	Seal	CW510L
5	Stem	CW614N
6	Lower Stem	PTFE
7	O-Ring	NBR70sh
8	Upper Seal	PTFE
9	Brass Ring	CW614N
10	Nut	Steel
11	Handle	Steel P10



LEAD FREE GATE/ CHECK/ Y VALVES

LEAD FREE

BRASS GATE VALVE IPS

- **200 WOG (Cold water, oil, gas)**
- **125 WSP (Saturated Steam)**

- Brass Forged body/bonList- stronger than sand castings.
- Superior quality and finish.
- Each valve individually tested.
- Threaded ends to ANSI B1.20.1, Solder ends to ANSI B16.18
- Non rising stem.
- Cast iron handle.
- Temp. 32°-320°F

BRASS GATE VALVE IPS

Part#	Size	
940-130LF	1/4	74001004
940-131LF	3/8	74001006
940-132LF	1/2	74001008
940-133LF	3/4	74001012
940-134LF	1	74001016
940-135LF	1-1/4	74001020
940-136LF	1-1/2	74001024
940-137LF	2	74001032

BRASS GATE VALVE C X C

Part#	Size	
940-142LF	1/2"	----
940-143LF	3/4"	----
940-144LF	1"	----
940-145LF	1-1/4"	----
940-146LF	1-1/2"	----
940-147LF	2"	----

BRASS CHECK VALVE

NO	Part	Material
1	Cap	C37700
2	Gasket	NBR
3	Spring	Stainless Steel
4	Positioning Seat	BRASS
5	Screw	BRASS
6	Body	C37700

LEAD-FREE

Part #	Size	
944-430LF	1/2	74003408
944-431LF	3/4	74003412
944-432LF	1	74003416
944-433LF	1-1/4	74003420
944-434LF	1-1/2	74003424
944-435LF	2	74003432

CAST BRASS SWING CHECK VALVE IPS SCREWED ENDS

- Working pressure non-shock: 200 psi W.O.G. (cold water, oil, gas) 125 psi WSP (saturated steam)
- Swing type disc.
- Screwed Cap.
- Hard Seat.
- 90^0 Straight Pattern.
- Used to prevent reverse flow in commercial and industrial applications.
- Threaded ends to ANSI B1.20.1
- Integral seat.

Part #	Size	
940-352LF	1/2"	----
940-353LF	3/4"	----
940-354LF	1"	----
940-355LF	1-1/4"	----
940-356LF	1-1/2"	74003024
940-357LF	2"	----

C X C SWING CHECK VALVE

Part #	Size	
940-362LF	1/2	----
940-363LF	3/4	74003212
940-364LF	1	74003216
940-365LF	1-1/4	74003220
940-366LF	1-1/2	----
940-367LF	2	74003232

CLASS 150 BRASS Y-PATTERN STRAINER

LEAD-FREE

Part#	Size	
940-523LF	1/2"	----

FORGED BRASS BALL VALVE

• BRASS • 600WOG • FULL PORT

C US

UL842, UL258, UL125,FM

ISO 9002 Manufacturer

1/4-2" 600 PSI non-shock cold water, gas, oil - 150 PSI saturated steam

2-1/2"- 4" 400 PSI non-shock cold water, gas, oil

Made in China

FEATURES

- Suitable for full range of liquids and gases
- Minimal pressure drop due to large full size ports
- Bottom loaded, pressure retaining stem
- Pressure rated for 1/4"-2" at 600psi (42 bars) and 2-1/2"-4" at 400 psi WOG (non-shock) and 150 WSP (10.34 bars) saturated steam. Virgin PTFE stem packing seal, thrust washer and seats
- Yellow vinyl insulator on heavy duty plated carbon steel handles
- Fast 1/4 turn open or close operation
- Not Lead Free
- Good for gasoline
- Low operating torque
- Adjustable stem packing gland
- Maximum operating temperature: 302^{0}F (150^0 C)
- Minimum operating temperature: -22^{0}F (-30^{0}C)
- Each valve individually tested
- Forged Brass - for more strength
- Threaded ends to ANSI B1.20.1
- Hard chromium plated solid ball
- Bottom entry, blow-out proof stem
- Deeper threads - for better connections

• Generic Handles



Part#	Size	Dimension Inches								
	NPT	DN	A	B	C	E	CH	Weight	Box/Case	
940-171	1/4"	0.39	1.75	1.92	3.54	0.46	0.78	0.34	70/140	4002404
940-172	3/8"	0.41	1.75	1.92	3.54	0.46	0.78	0.30	70/140	4002406
940-173	1/2"	0.58	2.05	2.08	3.54	0.52	0.98	0.44	50/100	4002406
940-174	3/4"	0.75	2.36	2.30	3.78	0.56	1.20	0.67	30/60	4002412
940-175	1"	0.94	2.75	2.68	4.52	0.66	1.50	1.05	20/40	4002416
940-176	1-1/4"	1.26	3.30	3.14	4.52	0.70	1.82	1.50	12/24	4002420
940-177	1-1/2"	1.57	3.66	3.61	5.51	0.72	2.09	2.30	9/18	4002424
940-178	2"	1.97	4.18	3.68	5.51	0.74	2.62	3.38	6/12	4002432
940-179*	2-1/2"	2.52	5.38	4.76	8.66	1.01	3.36	7.61	4/8	4002440
940-180*	3"	2.95	6.04	5.08	8.66	1.11	3.86	11.10	2/4	4002448
940-181*	4"	3.89	7.38	5.86	9.00	1.22	4.89	12.12	1/2	4002460

* 400 PSI

* Add 'H' to part # to order handles *



These are NOT Lead Free
See pages 165 for Lead Free SWT Valves

POS	Components	Materials	N
1	Body	Forged Brass	1
2	End Connection	Forged Brass	1
3	Ball	CP Brass	1
4	Ball Seat	P.T.F.E.	2
5	Stem	Brass	1
6	Gland	Brass	1
7	Nut	Steel	1
8	Spring Inseat	Steel	1
9	Stem Seal	P.T.F.E.	1
10	Handle	Steel	1

• Not Lead Free AB1953 Compliant

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

LOCKING HANDLE BALL VALVE

• BRASS • 600WOG • FULL PORT

5 PSIG

UL842, UL258, UL125,FM

ISO 9002 Manufacturer

FEATURES

1/4-2" 600 PSI non-shock cold water, gas, oil - 150 PSI saturated steam

Made in China

- Suitable for full range of liquids and gases
- Minimal pressure drop due to large full size ports
- Bottom loaded, pressure retaining stem
- Pressure rated for 1/4"-2" at 600psi (42 bars) and 2-1/2"-4" at 400 psi WOG (non-shock) and 150 WSP (10.34 bars) saturated steam. Virgin PTFE stem packing seal, thrust washer and seats
- Yellow vinyl insulator on heavy duty plated carbon steel handles
- Fast 1/4 turn open or close operation
- Not Lead Free
- Locking mechanism works in open and closed position
- Low operating torque
- Adjustable stem packing gland
- Maximum operating temperature: 302^{0}F (150^0 C)
- Minimum operating temperature: -22^{0}F (-30^{0}C)
- Each valve individually tested
- Forged Brass - for more strength
- Threaded ends to ANSI B1.20.1
- Hard chromium plated solid ball
- Bottom entry, blow-out proof stem
- Deeper threads - for better connections



• Generic Handles

Part#	Size	Dimension Inches								
	NPT	DN	A	B	C	E	CH	Weight	Box/Case	
940-171L	1/4"	0.31	1.73	1.84	3.15	0.49	0.71	0.39	70/140	----
940-172L	3/8"	0.39	1.81	1.88	3.86	0.49	0.79	0.35	70/140	----
940-173L	1/2"	0.58	2.23	2.09	3.43	0.61	0.98	0.49	50/100	----
940-174L	3/4"	0.75	2.48	2.24	3.62	0.62	1.20	0.78	30/60	----
940-175L	1"	0.94	2.95	2.67	4.42	0.73	1.50	1.18	20/40	----
940-176L	1-1/4"	1.26	3.42	3.05	4.73	0.77	1.81	1.76	12/24	----
940-177L	1-1/2"	1.57	3.78	3.51	5.18	0.78	2.09	2.53	9/18	----
940-178L	2"	1.97	4.18	3.84	5.24	0.75	2.60	3.53	6/12	----



POS	Components	Materials	N
1	Body	Forged Brass	1
2	End Connection	Forged Brass	1
3	Ball	CP Brass	1
4	Ball Seat	P.T.F.E.	2
5	Stem	Brass	1
6	Gland	Brass	1
7	Nut	Steel	1
8	Spring Inseat	Steel	1
9	Stem Seal	P.T.F.E.	1
10	Handle	Steel	1

• Not Lead FreeAB1953 Compliant

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

BUTTERFLY HANDLE BALL VALVE

• BRASS • 600WOG • FULL PORT

5 PSIG

UL842, UL258, UL125,FM

ISO 9002 Manufacturer

1/4-3/4" 600 PSI non-shock cold water, gas, oil - 150 PSI saturated steam

Made in China

FEATURES

- Suitable for full range of liquids and gases
- Minimal pressure drop due to large full size ports
- Bottom loaded, pressure retaining stem
- Pressure rated for 1/4"-3/4" at 600psi (42 bars) and 150 WSP (10.34 bars) saturated steam. Virgin PTFE stem packing seal, thrust washer and seats
- Fast 1/4 turn open or close operation
- Low operating torque
- Adjustable stem packing gland
- Maximum operating temperature: 302^{0}F (150^0 C)
- Minimum operating temperature: -22^{0}F (-30^{0}C)
- Each valve individually tested
- Forged Brass - for more strength
- Threaded ends to ANSI B1.20.1
- Hard chromium plated solid ball
- Bottom entry, blow-out proof stem
- Deeper threads - for better connections
- Not Lead Free

Part#	Size NPT	A	B	C	D	E	Weight	Box/Case	
940-171T	1/4"	1.75	1.488	1.831	0.315	0.457	0.342	70/140	----
940-172T	3/8"	1.756	1.488	1.831	0.394	0.457	0.31	70/140	----
940-173T	1/2"	2.047	1.756	2.394	0.583	0.520	0.44	50/100	----
940-174T	3/4"	2.362	1.921	2.394	0.748	0.563	0.68	30/60	----



POS	Components	Materials
1	Body	C37700
2	End Cap	C37700
3	Ball Seat	PTFE
4	Ball	C37700
5	Stem	C37700
6	Stem Packing	PTFE
7	Packing Nut	C37700
8	Lever Handle	ZL102
9	Stem Nut	A570

Steel Tee handle option available with extended delivery (1/4" - 4")

• Not Lead Free AB1953 Compliant

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

NICKEL PLATED BALL VALVE

• BRASS • 600WOG • FULL PORT • NO APPROVALS

Vacuum service to 29 inches Hg
600 psi (WOG) 150 psi (WSP) Service
Thread conform ANSI B1.20.1
Temperature Range : -40° F to 365° F
Construction:Forging Brass Body, Nickel plated
PTFE Ball Seats
Blow Out Proof Brass Stem
Steel Handle w/Vinyl Grip
Made in China

• Not Lead Free



• Generic Handles

FIP X FIP NICKEL PLATED BALL VALVE

Part #	Size	OD	A	B	C	E	F	G	H	Weight	Box/Case	
941151NP	1/4"	0.394	1.73	1.69	3.35	0.453	0.945	2.154	4.331	0.32	10/120	----
941152NP	3/8"	0.394	1.73	1.69	3.35	0.473	0.945	2.154	4.331	0.32	10/120	----
941153NP	1/2"	0.524	1.89	1.73	3.35	0.472	1.083	2.276	4.291	0.36	10/100	----
941154NP	3/4"	0.748	2.28	1.89	3.35	0.563	1.378	2.579	4.488	0.57	10/80	----
941155NP	1"	0.984	2.80	2.14	4.29	0.650	1.772	3.031	5.689	0.65	8/48	----
941156NP	1-1/4"	1.240	3.15	2.32	4.29	0.669	2.165	3.398	5.866	1.75	4/36	----
941157NP	1-1/2"	1.476	3.44	2.66	5.63	0.701	2.50	3.909	7.343	2.10	2/24	----
941158NP	2"	1.949	4.06	3.01	5.63	0.708	3.244	4.638	7.638	3.35	2/12	----



No	Item	Qty	Material
1	Body	1	NP Brass
2	Seat	2	PTFE
3	Ball	1	Brass CP
4	Stem	1	Brass/ NP
5	Handle Nut	1	Plated Steel
6	Lock Washer	1	Plated Steel
7	Packing Nut	1	Brass/ NP
8	Packing	1	PTFE
9	Handle	1	Plated Steel
10	Cap	1	Brass/ NP

Gratitude is the sign of noble souls.

- Aesop

WARNING: This product can expose you to chemicals, including Nickel, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

Gas Approved

UL842, UL258, UL125,FM

CSA AGA 3.88 5 PSIG

N/P BALL VALVE W/SS TRIM

• NICKEL PLATED • SS BALL, HANDLE, NUT & STEM

• LOCKING HANDLE • W/APPROVALS

Features

- **Vacuum service to 29 inches Hg**
- Thread Conform ANSI B1.20.1
- Forged Brass Body
- Blow Out Proof Stem Design
- Packing Nut, O-RING & Packing On The Stem Seal
- Stainless Steel Ball, Handle, Nut&Stem
- Handle With Vinyl Grip

Performance rating

- 600 PSI (WOG) 150 PSI (WSP) Service
- Temperature range: -20° F to 300° F
- Made in China
- Not lead free
- No more rusty handles

• Generic Handles

Part#	Size	D	L	H	W	Cv	Wt.(lbs.)	Box/Case	
941-121NP	1/4	0.394	3.22	1.84	1.73	8.23	0.326	10/120	----
941-122NP	3/8	0.394	3.22	1.84	1.73	8.23	0.320	10/120	----
941-123NP	1/2	0.591	3.22	2.02	2.24	18.55	0.474	10/100	----
941-124NP	3/4	0.748	4.04	2.40	2.52	29.76	0.785	10/80	----
941-125NP	1	0.984	4.08	2.20	2.97	51.55	1.155	8/48	----
941-126NP	1-1/4	1.259	5.20	3.05	3.44	84.42	1.797	4/36	----
941-127NP	1 1/2	1.574	5.20	3.18	3.88	131.93	2.447	2/24	----
941-128NP	2	1.941	5.20	3.48	4.33	200.35	3.477	2/12	----



Part Name	Material
Body	Brass/ Nickel Plated
Seat	PTFE
Ball	Stainless Steel
O-ring	Viton
Packing Nut	Brass/ Nickel Plated
Stem	Stainless Steel
Handle Nut	Stainless Steel
Lock Washer	Stainless Steel
Packing	PTFE
Handle	Stainless Steel
Cap	Brass/ Nickel Plated

BRONZE BALL VALVES AVAILABLE WITH UL-MARINE LISTING AND SS TRIM

WARNING: This product can expose you to chemicals, including chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

ITALIAN BALL VALVE

• BRASS • 600WOG • FULL PORT

5 PSIG C US

UL842, UL258, UL125,FM

CSA AGA 3.88 5 PSIG

IAMPO IGC 157 - 2004b

ISO 9002 Manufacturer

FEATURES

- **SOLID CHROME PLATED BRASS BALL**
- Suitable for full range of liquids and gases
- Minimal pressure drop due to large full size ports
- Bottom loaded, pressure retaining stem
- Pressure rated at 600psi (42 bars) WOG (non-shock) and 150 WSP (10.34 bars) saturated steam. Virgin TFE stem packing seal, thrust washer and seats.
- Yellow vinyl insulator on heavy duty plated carbon steel handles.
- Fast 1/4 turn open or close operation
- Low operating torque
- Flow can go both directions
- Generic Handles
- **Adjustable stem packing gland**
- Maximum operating temerature: 248^{0}F (120^0 C) at 600 PSI
- Minimum operating temperature: -20^{0}F (-40^{0}C)
- Each valve individually tested
- Forged Brass - for more strength
- Threaded ends to ANSI B1.20.1
- Hard chromium plated solid ball
- Bottom entry, blow-out proof stem
- Deeper threads - for better connections
- **REVERSIBLE HANDLES**

MADE IN ITALY

Female x Female



Part#	Size	Dimension Inches								
	NPT	DN	A	B	C	D	CH	Weight	Box/Case	
943-200	1/4"	.39	1.96	1.53	3.31	.43	.75	0.36	24/96	----
943-201	3/8"	.39	1.96	1.53	3.31	.43	.86	0.40	24/96	----
943-202	1/2"	.57	2.09	1.57	3.25	.46	.98	0.44	20/80	----
943-203	3/4"	.75	2.28	1.77	3.80	.49	1.22	0.57	14/56	----
943-204	1"	.94	2.80	2.03	3.80	.59	1.50	0.89	6/24	----
943-205	1-1/4"	1.24	3.50	2.32	4.72	0.72	1.85	1.64	4/16	----
943-206	1-1/2"	1.49	3.90	3.02	6.38	0.85	2.13	2.78	2/8	----
943-207	2"	1.96	4.07	3.27	6.38	.65	2.64	3.21	2/8	----
942-208	2-1/2"	2.48	5.80	4.98	7.54	1.06	3.31	6.97	5	----
942-209	3"	2.99	6.85	5.63	8.86	1.14	3.89	10.34	3	----
942-210	4"	3.54	7.67	6.04	8.86	1.22	4.80	18.77	1	----

HANDLE OPTIONS

TEE HANDLES

Part #	Valve Size	
43-200T	1/4" - 3/4"	----
43-204T	1"	----

LOCKING HANDLES

Part #	Valve Size	
43-200L	1/4" - 3/4"	----
43-204L	1"	----
43-206L	1-1/4" - 1-1/2"	----
43-207L	2"	----



POS	Components	Materials	N
1	Body	Forged Brass	1
2	End Connection	Forged Brass	1
3	Ball	CP Brass	1
4	Ball Stems	P.T.F.E.	2
5	Stem Antif. Seat	P.T.F.E.	1
6	Stem Seat	P.T.F.E.	1
7	Brass Ring	Brass	1
8	Stem	Brass	1
9	O-Ring	NBR 80	1
10	Handle	Steel	1
11	Nut	Steel	1
12	Nut	Brass	1

• Not Lead Free AB1953 Compliant

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

MALE X FEMALE BRASS BALL VALVE

• 600WOG • FULL PORT

UL842, UL258

- Solid chrome plated brass ball
- Suitable for full range of liquids and gases.
- Minimal pressure drop due to large full size ports.
- Bottom loaded, pressure retaining stem.
- Pressure rated at 600psi (42 bars) WOG (non-shock) and 150psi (10.34 bars) saturated steam. Virgin TFE stem packing seal, thrust washer and seats.
- Yellow vinyl insulator on heavy duty plated carbon steel handles.
- Fast 1/4 turn open or close operation.
- Flow both directions.
- Low operating torque.
- Adjustable stem packing gland.
- Generic Handles
- Maximum operating temperature: 248^{0}F (120^{0}C)
- Minimum operating temperature: -20^{0}F (-40^{0}C)
- Each valve individually tested.
- Forged Brass - for more strength.
- Threaded ends to ANSI B1.20.1
- Hard chromium plated solid ball
- Bottom entry, blow-out proof stem.
- Made in China

- Not Lead Free

Part#	Size	NPT	A	B	C	D	E	Weight	Box/Case	
948-170	1/4	1/4 - 18	2.016	1.689	2.756	0.315	0.457	0.29	70/140	----
948-171	3/8	3/8 - 18	2.094	1.89	3.543	0.394	0.457	0.33	70/140	----
948-172	1/2	1/2 - 14	2.343	2.05	3.543	0.583	0.520	0.47	50/100	----
948-173	3/4	3/4 - 14	2.618	2.20	3.780	0.748	0.563	0.68	30/60	----
948-174	1	1 - 11.5	3.000	2.579	4.528	0.945	0.630	1.11	20/40	----
948-175	1-1/4	1-1/4 - 11.5	3.563	2.953	4.528	1.260	0.709	1.70	12/24	----
948-176	1-1/2	1-1/2 - 11.5	3.965	3.346	5.512	1.575	0.717	2.50	9/18	----
948-177	2	2 - 11.5	4.496	3.681	5.512	1.969	0.748	3.57	6/12	----



POS	Components	Materials
1	Body	C37700
2	End Cap	CS7700
3	Ball Seat	PTFE
4	Ball	CS7700
5	Stem	CS7700
6	Stem Reducing	PTFE
7	Reducing Nut	CS7700
8	Lever Handle	1008
9	Stem Nut	A570 Gr.A

Locking Handle option
see pg. 182

Tee handle option
see pg. 181

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

ITALIAN MALE X FEMALE BALL VALVE

• BRASS • 600WOG • FULL PORT

Gas Approved

5 PSIG

C US

CSA AGA 3.88 5 PSIG

UL842, UL258, UL125,FM

Made in Italy

ISO 9002 Manufacturer

FEATURES

- Solid chrome plated brass ball
- Suitable for full range of liquids and gases.
- Minimal pressure drop due to large full size ports.
- Bottom loaded, pressure retaining stem.
- Pressure rated at 600psi (42 bars) WOG (non-shock) and 150psi (10.34 bars) saturated steam. Virgin TFE stem packing seal, thrust washer and seats.
- Yellow vinyl insulator on heavy duty plated carbon steel handles.
- Fast 1/4 turn open or close operation.
- Generic Handles
- Low operating torque.
- Adjustable stem packing gland.
- Maximum operating temperature: 248^{0}F (120^{0}C) at 600 p.s.i
- Minimum operating temperature: -20^{0}F (-40^{0}C)
- KV: Pressure drop m^3/h.
- Each valve individually tested.
- Forged Brass - for more strength.
- Threaded ends to ANSI B1.20.1
- Hard chromium plated solid ball
- Bottom entry, blow-out proof stem.
- Deeper threads - for better connections.

MADE IN ITALY

MIP x FIP



Part#	Size	DN	A	B	C	E	E1	CH1	CH2	Weight	Box/Case	
948-101	1/4	.39	2.18	1.53	3.28	.39	.43	.55	.75	0.35	24/96	----
948-102	3/8	.39	2.20	1.53	3.28	.43	.43	.71	.86	0.35	24/96	----
948-103	1/2	.57	2.54	1.57	3.28	.62	.46	.87	.98	0.42	14/56	----
948-104	3/4	.75	2.75	1.77	3.80	.55	.49	1.12	1.22	0.68	12/48	----
948-105	1	.94	3.23	2.03	3.80	.69	.59	1.34	1.50	0.95	6 /24	----
948-106	1-1/4	1.24	3.86	2.32	4.63	.81	.79	1.69	1.90	1.66	4/16	----
948-107	1-1/2	1.49	4.20	2.98	6.28	.85	.64	2.15	2.13	2.83	2/8	----
948-108	2	1.96	4.90	3.27	6.38	.90	.75	2.40	2.64	4.22	1/4	----



POS	Components	Materials	N
1	Body	CW617N Forged Brass	1
2	End Connection	CW617N Forged Brass	1
3	Ball	CW617N CP Brass	1
4	Ball Stems	P.T.F.E.	2
5	Stem Antif. Seat	P.T.F.E.	1
6	Stem Seat	P.T.F.E.	1
7	Brass Ring	CW617N Brass	1
8	Stem	CW617N Brass	1
9	O-Ring	NBR 80	1
10	Handle	UNI EN 10025 Steel	1
11	Nut	UN 5771 Steel	1
12	Nut	CW617N Brass	1

• Not Lead Free

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

TEE HANDLE BALL VALVE - MALE X FEMALE

UL842, UL258

Features
- Thread conform ANSI B1.20.1
- Forged brass body
- Blow out proof stem design
- Packing nut, O-Ring and packing on the stem seal
- Chrome Plated Brass Ball
- Handle with vinyl grip

Performance rating
- 600 PSI (WOG) 150 PSI (WSP) Service
- Temperature range: -20° F to 300° F
- Made in China
- Not lead free

Part#	Size	Dimension Inches							
	NPT	A	B	C	D	E	Weight	Box/Case	
948-170T	1/4"	2.016	1.27	2.67	0.315	0.457	0.26	70/140	----
948-171T	3/8"	2.094	1.213	2.67	0.394	0.457	0.33	70/140	----
948-172T	1/2"	2.343	1.61	3.12	0.583	0.520	0.49	50/100	----
948-173T	3/4"	2.618	1.26	3.12	0.748	0.563	0.66	30/60	----
948-174T	1"	3.000	1.921	3.701	0.945	0.630	1.06	20/40	----
948-176T	1-1/2"	3.965	2.717	4.331	1.575	0.717	2.46	9/18	----



Item	Part	Materials
1	Body	Brass
2	End Cap	Brass
3	Ball Seat	PTFE
4	Ball	C/P Brass
5	Stem	Brass
6	Stem Packing	PTFE
7	Packing Nut	Brass
8	T-Handle	Nickel plating steel
9	Stem Nut	Brass plating steel

It is during our darkest moments that we must focus to see the light. - Aristotle

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

LOCKING HANDLE BALL VALVES - FEMALE X MALE

UL842, UL258

Features
- Thread conform ANSI B1.20.1
- Forged brass body
- Blow out proof stem design
- Packing nut, O-Ring and packing on the stem seal
- Chrome Plated Brass ball
- Handle with vinyl grip

Performance rating
- 600 PSI (WOG) 150 PSI (WSP) Service
- Temperature range: -20° F to 300° F
- Made in China
- Not lead free

Part#	Size	Dimension Inches							
	NPT	A	B	C	D	E	Weight	Box/Case	
948-170L	1/4"	2.016	1.732	3.543	0.315	0.457	0.32	70/140	----
948-171L	3/8"	2.094	1.732	3.543	0.394	0.457	0.37	70/140	----
948-172L	1/2"	2.343	1.941	3.543	0.583	0.520	0.50	50/100	----
948-173L	3/4"	2.618	2.106	3.78	0.748	0.563	0.77	30/60	----
948-174L	1"	3.000	2.579	4.528	0.945	0.630	1.21	20/40	----
948-175L	1-1/4"	3.563	2.961	4.528	1.260	0.709	1.74	12/24	----
948-176L	1-1/2"	3.965	3.366	5.36	1.575	0.717	2.58	9/18	----
948-177L	2"	4.496	3.701	5.36	1.969	0.748	3.73	6/12	----



Item	Part	Materials
1	Body	Brass
2	End Cap	Brass
3	Ball Seat	PTFE
4	Ball	C/P Brass
5	Stem	Brass
6	Stem Packing	PTFE
7	Packing Nut	Brass
8	Lever Handle	Nickel plating steel
9	Stem Nut	Brass plating steel

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

BRASS SPRING HANDLE BALL VALVE

Working pressure:600 PSI for brass
Temperature Range:-40°F to 365°F(-40°C to +185°C)
Material:Brass
Spring Lever Handle w/Vinyl Grip
Made in China
Not lead free



Part #	Part Name	Material
1	Body	Brass
2	Bonnet	Brass
3	Ball	Brass
4	Sealing Seat	PTFE
5	Stem	Stainless Steel
6	Packing Ring	PTFE
7	Gland	Brass
8	Handle	Stainless Steel
9	Bolt	Brass
10	Spring	Stainless Steel

Item#	Size	L	D	DN	H	L3	WTG	Box/Case	
947-103	**1/2"**	2.19	1.24	0.59	1.83	4.24	0.54	10/80	----
947-104	**3/4"**	2.38	1.5	0.75	2.19	4.24	0.72	5/40	----
947-105	**1"**	3.23	1.91	0.98	2.49	4.71	1.32	5/30	----

RIGHT ANGLE BRASS BALL VALVE

Working pressure: 250PSI
Temperature Range -40° to 400°F(-40 °C to +205 °C)
With lever Handle Teflon seats 2-pc,full port Heavy Duty forged Body Steel Handle w/Vinyl Grip-
Made in China
Not lead free



Part #	Part Name	Material
1	Body	Brass
2	Cap	Brass
3	Ball	Brass
4	Seat	PTFE
5	Stem	Brass
6	Stuffing	PTFE
7	Packing Nut	Brass
8	Handle	Steel
9	Nut	Brass

Part #	Size	A	B	C	D	S	DN	L	E	F	WTG	Box/Case	
947-111	1/4	1.59	0.41	1.40	0.64	0.63	0.32	2.60	0.98	0.65	0.34	12/120	----
947-112	3/8	1.59	0.41	1.40	0.73	0.71	0.39	2.60	0.98	0.65	0.36	12/120	----
947-113	1/2	1.73	0.55	1.40	0.79	0.87	0.55	2.60	1.08	0.83	0.47	10/80	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

3-WAY AND SAFETY EXHAUST BALL VALVES

3-WAY WYE BRASS BALL VALVE,VENTED AND UNVENTED

- Max.pressure:W.O.G.(water,oil,inert gas)
  Unvented Valve:600psi@70ºF
  Vented Valve:250psi@70ºF
  W.S.P.(working steam pressure)
  Unvented Valve:150psi@365ºF
  Vented Valve:Not related
- Vacuum Rating:29"Hg
- Temperature Range:-40º to 365ºF
- Ports:Full

Part#	Part Name	Material
1	Body	Brass Nickel Plated
2	Seat	PTFE
3	Ball	Brass,Cr.Plated
4	Cap	Brass Nickel Plated
5	Stem	Brass
6	O-Ring	Viton
7	Handle	Stainless Steel
8	Nut	Steel



Designed for the portable air compressor industry,these valves control the flow of water,oil, and inert gases in two direction and are great for mixing and diverting.They have a single female inlet and two male outlets with two ball valves.Valves are Brass Nickel Plated and have chrome-plated brass balls,brass blow-out proof stems ,PTFE seats and seals,and steel lever handles with vinyl grips.Vented valves has a drilled hole on the two valve balls and body that vents compressed air in the line when valve is closed. Connections:1"NPT female inlet and 3/4"NPT male outlet. • Made in China • Not lead free

NON-VENTED

NOW WITH STAINLESS STEEL HANDLES

VENTED

Part #	Ball	E	F	A	B	C	D	G	WTG	Box/Case	
947-125	Non-vented	1" Female	3/4" Male	5.18"	**2.5"**	2.05"	0.59"	90°	1.43	2/24	----
947-126	Vented								1.48	2/24	----

EXHAUST VALVES

AUTOMATIC DRAIN & LATCH LOCK HANDLE

Full port hot forged brass ball valve, blow-out proof stem, downstream automatic vent with lockable handle in compliance with OSHA requirements.

- Maximum working pressure: 200 PSI (CWP).
- Temperature rating: +15°F through +210°F.
- Made in Italy
- Not lead free

200 PSI



• w/ 10/32 UNP tap for drain. on all sizes

OPEN



Valve - open position. Drain vent shut off.

CLOSED



Part#	Size	
948-131	1/4"	----
948-132	3/8"	----
948-133	1/2"	----
948-134	3/4"	----
948-135	1"	----

Valve - closed and draining occurs. Upstream seat prevents air flow. Downstream system is vented to atmosphere.

SAFETY EXHAUST BALL VALVE

- Threaded - Two Piece Body - Full Port • Vented
- Blow-out Proof Stem - PTFE Seats • 400 PSI WOG
- To Exhaust and Downstream Air in the Closed Position w/ locking lever handle.
- Made in China • Not lead free

Part #	Size	A	B	D	E	
948-141	1/4"	1.756	1.88	0.394	0.457	----
948-142	3/8"	1.756	1.88	0.394	0.457	----
948-143	1/2"	2.047	2.13	0.583	0.520	----
948-144	3/4"	2.362	2.28	0.748	0.563	----



MATERIAL LIST

Item	Part	Material
1	Body	Brass
2	End Cap	Brass
3	Ball Seat	PTFE
4	Ball	Brass
5	Stem	Brass
6	Stem Packing	PTFE
7	Packing Nut	Brass
8	Lever Handle	Nickel plating steel
9	Stem Nut	Nickel plating steel

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

GAS BALL VALVES

5 PSIG
C US
CSA AGA 3.88 5 PSIG

Manual Valve
LISTED
Threaded NPT
UL 842, UL 258, UL 125

ISO 9002 Manufacturer

FEATURES

- Material: C37700
- Forged brass,Regular port,Thread*Flare Thread
- Thread ends in ANSI B1.20.1
- Working temperature:0-65°(32-149°)
- Pressure :1/2PSI;5PSI;
- ASME B16.44/CR91; ANSI Z21.15/CSA9.1
- UL 125 For LP-Gas 125psig
- Made in China



NO.	ITEM	TOTAL	MATERIAL
10	BALL VALVE CAP	1	BRASS
9	HANDLE	1	AL-alloy
8	PACKING	1	PTFE
7	HANDLE NUT	1	PLATED STEEL
6	STEM	1	BRASS
5	PACKING NUT	1	BRASS
4	O-RING	1	NBR
3	BALL	1	BRASS
2	SEALING WASHER	2	PTFE
1	BALL VALVE BODY	1	BRASS

GAS BALL VALVE (2-Piece)

FEMALE x FEMALE

Part#	Size	WTG	Box/Case	
943-311	3/8"	0.35	10/100	4004006
943-312	1/2"	0.44	10/100	4004008
943-313	3/4"	0.62	10/100	4004012

SIZE	⌀D	A	B	C	E	F	G	H
3/8″	0.394	1.752	1.437	1.28	0.472	0.945	1.909	2.146
1/2″	0.394	2.204	1.437	1.28	0.606	1.043	1.961	2.461
3/4″	0.591	2.362	1.535	1.28	0.626	1.299	2.815	2.476

FLARE X FLARE

Part#	Size	
943342	3/8	----
943343	1/2	----
943345	5/8	----
943344	15/16	----

FLARE X MIP

Part#	Size	
943347	3/8 x 1/2	----
943348	1/2 x 1/2	----

FLARE X FIP

Part#	Size	
943331	3/8 x 1/2	----
943332	1/2 x 1/2	----
943351	5/8 x 3/4	----
943350	15/16 x 3/4	400461512

MADE IN ITALY

- For use with natural, manufactured, mixed liquified. petroleum and LP gas-air mixtures.
- Deeper thread connections. Smooth quarter-turn.
- Manufactured to ANSI Z21.15, C.G.A. 9.1-M81, 9.2-M88, 1/2 psig. 372 also to A.G.A.3-8, C.G.A. CR91-002, 2 psig.
- Solid chrome plated brass ball
- Bottom entry
- Blow out proof design.
- Double viton o-rings stem seals
- Teflon seats for durability.
- Forged construction for greater strength.
- Larger ports for increased flow capacity.
- Larger ports for increased flow capacity.
- Red Reversible handle.
- May be used with water 400 WOG.



	Components	Materials
1	Body	Forged Brass
2	End Connection	Forged Brass
3	Ball	Forged Brass
4	Ball Seats	P.T.F.E.
5	Stem	Brass
6	O-Ring	NBR
7	Butterfly	Steel
8	Screw	UNI 5771 Steel

5 PSIG
C US
CSA AGA 3.88 5 PSIG

Manual Valve
LISTED
Threaded NPT
UL 842, UL 258, UL 125



GAS BALL VALVES

FEMALE x FEMALE

Part#	Size	Dimension Inches								
	G	DN	A	B	C	E	CH	PN in psi	WTG	Box/ Case
943-212	1/2"	.47	2.26	1.45	2.28	.55	.98	600	0.33	20/80
943-213	3/4"	.59	2.48	1.57	2.28	.57	1.22	600	0.45	14/56

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

ITALIAN CHROME PLATED BRASS MINI BALL VALVE

ISO 9002 Manufacturer

FEATURES

- Solid chrome plated brass ball
- Max working pressure 235 psi will handle 300psi@75° F
- Longer body style for longer, deeper thread connections
- One piece drawn sand blasted chrome plated body.
- Each valve is seal tested for maximum safety.
- Double seal system allows valve to be operated in both directions making installation easier.
- Blowout-proof brass stem.
- NPT taper ANSI B1.20.1 threads.
- 32°F to +176°F temperature.
- 1/4 Turn Aluminium handle with mechanical stop.
- NSF Approved valves available upon request!
- Not lead free

Female x Female



Made in Italy

Part#	Size		Dimension Inches							
	G	DN	A	B	C	E	CH	WTG	Box/ Case	
46-922I	1/4"	0.31	1.81	1.17	0.9	0.51	0.83	0.24	50/200	----
46-923I	3/8"	0.31	1.85	1.17	0.9	0.51	0.83	0.22	50/200	----
46-924I	1/2"	0.39	2.18	1.26	0.9	0.61	0.98	0.32	30/120	----

Male x Female



Part#	Size		Dimension Inches							
	G	DN	A	B	C	E	CH	WTG	Box/ Case	
46-903I	1/4"	0.31	1.75	1.17	0.9	.40	0.83	0.20	50/200	----
46-904I	3/8"	0.31	1.81	1.17	0.9	.41	0.83	0.20	50/200	----
46-905I	1/2"	0.39	2.14	1.26	0.9	.52	0.98	0.30	40/160	----



POS	Components	Materials	N
1	Body	CW517N Forged Brass	1
2	Ball Seats	P.T.F.E	2
3	Ball	CW517N CP Brass	1
4	Ring Unit	CW614N Brass	1
5	Stem	CW614N Brass	1
6	Screw	UNI 5771 Steel	1
7	Handle	Aluminum	1
8	O-Ring	NBR 80	1



YELLOW BRASS 1/4" MINI MALE X FEMALE VALVE

- **Proprietary seal design extreme for low & high temperature applications**
- **-76° to +248°F temperature.**
- Nominal working pressure 235 psi will handle 300psi@75° F
- One piece drawn sand blasted brass plated body. Solid chrome plate brass ball
- Double seal system allows valve to be operated in both directions making installation easier.
- Blowout-proof brass stem.
- NPT taper ANSI B1.20.1 threads.
- **1/4 TURN BLACK METAL HANDLE WITH MECHANICAL STOP**.

MALE x FEMALE

MADE IN ITALY



Part#	Size		Dimension Inches						
	NPT	DN	A	B	C	E	CH	CASE	
46-903ISB	1/4"	0.315	1.75	1.18	0.91	0.48	0.83	200	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

MINI BALL VALVES

- Chrome plated forged brass body
- Chrome plated brass ball
- NPT taper ANSI B1.20.1 threads*
- 450 PSI working pressure
- At 212°F - 355 PSI
- At 356°F - 142 PSI
- 1/4 Turn Alumzinc handle
- Not lead free
- Made in China

FEMALE X FEMALE - FLAG HANDLE

Part #	Size	Dimensions (In)				Wt lbs	Box/ Case	
		A	D(FLOW)	F	G			
46-934	1/8	1.57	0.24	0.93	1.46	0.21	20/300	----
46-935	1/4	1.57	0.31	0.93	1.46	0.20	20/300	----
46-936	3/8	1.57	0.28	0.93	1.46	0.22	20/300	----
46-937	1/2	1.77	0.35	0.93	1.56	0.24	20/200	----

MINI BALL VALVES W/VITON SEALS

FEMALE X FEMALE - LEVER HANDLE

Part #	Size	Dimensions (In)				Wt lbs	Box/ Case	
		A	D(FLOW)	F	G			
46-934L	1/8	1.57	0.24	1.99	1.50	0.21	20/300	----
46-935L	1/4	1.57	0.31	1.99	1.50	0.20	20/300	----
46-936L	3/8	1.60	0.28	1.99	1.50	0.22	20/300	----
46-937L	1/2	1.77	0.35	1.99	1.59	0.24	20/200	----

FEMALE X FEMALE - TEE HANDLE

Part #	Size	Dimensions (In)				Wt lbs	Box/ Case	
		A	D(FLOW)	Handle	G			
46-934LT	1/8	1.60	0.24	1.34	1.43	0.21	20/300	----
46-935LT	1/4	1.57	0.31	1.34	1.43	0.20	20/300	----
46-936LT	3/8	1.60	0.28	1.34	1.43	0.22	20/300	----
46-937LT	1/2	1.77	0.35	1.34	1.52	0.24	20/200	----

FEMALE X FEMALE - SCREWDRIVER

Part #	Size	Dimensions (In)		Wt lbs	Box/Case	
		A	D(FLOW)			
46-934LS	1/8	1.57	0.24	0.21	20/300	----
46-935LS	1/4	1.57	0.31	0.20	20/300	----
46-936LS	3/8	1.57	0.28	0.22	20/300	----
46-937LS	1/2	1.77	0.35	0.24	20/200	----

- Not lead free



Pos	Components	Materials	N
1	Body	CP Forged Brass	1
2	Ball Seats	P.T.F.E.	2
3	Ball	CP Brass	1
4	Ring Unit	Brass	1
5	Stern	Brass	1
6	O-Ring - flag handle	NBR 80	1
6	O-Ring - all others	Viton	1
7	Handle	Alumzinc	1
8	Screw	Steel	1

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

MINI BALL VALVE

MINI BALL VALVES

- Chrome plated forged brass body
- Chrome plated brass ball
- NPT taper ANSI B1.20.1 threads*
- 450 PSI working pressure
- At 212°F - 355 PSI
- At 356°F - 142 PSI
- 1/4 Turn Alumzinc handle
- Not lead free
- Made in China

MALE X FEMALE - FLAG HANDLE

Part #	Size	Dimensions (In)				Wt lbs	Box/ Case	
		A	D(FLOW)	F	G			
46-930	1/8	1.57	0.24	0.93	1.46	0.17	20/300	----
46-931	1/4	1.57	0.31	0.93	1.46	0.15	20/300	----
46-932	3/8	1.57	0.28	0.93	1.46	0.21	20/300	----
46-933	1/2	1.77	0.35	0.93	1.56	0.24	20/200	----

MINI BALL VALVES W/VITON SEALS

MALE X FEMALE - LEVER HANDLE

Part #	Size	Dimensions (In)				Wt lbs	Box/ Case	
		A	D(FLOW)	F	G			
46-930L	1/8	1.57	0.24	1.99	1.50	0.17	20/300	----
46-931L	1/4	1.57	0.31	1.99	1.50	0.15	20/300	----
46-932L	3/8	1.57	0.28	1.99	1.50	0.21	20/300	----
46-933L	1/2	1.77	0.35	1.99	1.59	0.24	20/200	----

MALE X FEMALE - TEE HANDLE

Part #	Size	Dimensions (In)				Wt lbs	Box/ Case	
		A	D(FLOW)	Handle	G			
46-930T	1/8	1.57	0.24	1.34	1.46	0.17	20/300	----
46-931T	1/4	1.57	0.31	1.34	1.46	0.15	20/300	----
46-932T	3/8	1.57	0.28	1.34	1.40	0.21	20/300	----
46-933T	1/2	1.77	0.35	1.34	1.56	0.24	20/200	----

MALE X FEMALE - SCREWDRIVER

Part #	Size	Dimensions (In)		Wt lbs	Box/ Case	
		A	D(FLOW)			
46-930S	1/8	1.57	0.24	0.17	20/300	----
46-931S	1/4	1.57	0.31	0.15	20/300	----
46-932S	3/8	1.57	0.28	0.21	20/300	----
46-933S	1/2	1.77	0.35	0.24	20/200	----

- Not lead free



Pos	Components	Materials	N
1	Body	CP Forged Brass	1
2	Ball Seats	P.T.F.E.	2
3	Ball	CP Brass	1
4	Ring Unit	Brass	1
5	Stern	Brass	1
6	O-Ring - flag handle	NBR 80	1
6	O-Ring - all others	Viton	1
7	Handle	Alumzinc	1
8	Screw	Steel	1

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

FORGED BRASS MINI-BALL VALVES

- 180^0 operational handle, blow out proof stem. Stem with double "O" Rings
- 200 WOG
- Temp rating -20°F - 250°F
- Generic Handles
- Not lead free

NO	Part Name	Material	QTY
1	Nut	Steel	1
2	Handle	Steel	1
3	Cover	PVC	1
4	O-Ring	NBR	2
5	Stem	Brass	1
6	Body	Brass	1
7	Seat	Teflon	2
8	Ball Disc	Brass	1
9	End Plug	Brass	1



FEMALE x FEMALE

Part #	Size	A	B	C	D	
944-113	1/8	1.53	2.80	0.73	1.42	----
944-116	1/4	1.53	2.80	0.73	1.42	----
944-117	3/8	1.73	2.90	0.87	1.50	----
944-140	1/2	2.20	3.08	0.98	1.45	----

FEMALE x MALE

Part #	Size	A	B	C	D	
944-106	1/8	1.69	3.02	0.73	1.46	----
944-100	1/4X1/8	1.28	2.90	0.66	1.32	----
944-101	1/4	1.70	3.00	0.73	1.46	----
944-103	3/8	1.78	3.02	0.87	1.50	----
944-102	3/8X1/4	1.78	2.50	0.89	1.50	----
944-104	1/2	2.34	3.35	0.98	1.45	----

MALE x MALE

Part #	Size	A	B	C	D	
944-107	1/8	1.70	2.94	0.65	1.42	----
944-109	1/4	1.25	2.66	0.65	1.42	----
944-110	3/8	1.90	2.98	0.73	1.42	----
944-112	1/2	2.56	4.93	1.02	2.21	----

HOSE BARB x MALE

Part #	Size	A	B	C	D	
944-132	1/4X1/8	2.05	2.91	0.73	1.51	----
944-138	1/4X1/4	2.08	2.98	0.73	1.51	----
944-128	3/8X1/4	2.08	3.04	0.73	1.51	----
944-130	3/8X3/8	2.12	3.06	0.73	1.51	----
944-139	1/2X1/2	2.15	3.19	0.73	1.51	----

HOSE BARB x FEMALE

Part #	Size	A	B	C	D	
944-135	1/8X1/8	1.78	2.44	0.62	1.38	----
944-136	1/4X1/4	1.97	2.87	0.73	1.55	----

HOSE BARB x HOSE BARB

Part #	Size	A	B	C	D	
944-142	1/4X1/4	2.47	3.19	0.73	1.55	----
944-134	3/8X3/8	2.47	3.18	0.73	1.55	----

LEAD FREE

Part #	Size	A	B	C	D	
944-142LF	1/4	2.49	3.19	0.73	1.55	----
944-134LF	3/8	2.47	3.18	0.73	1.55	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

SIDE OUTLET 3-WAY BALL VALVE

• BRASS • 600WOG • FULL PORT

- Forged Brass
- 600 WOG
- Temp Rating 0-230°F

• Side outlet





- Full Port
- Blow-out proof stem
- double o-ring stem packing
- PTFE Seal
- Made in China
- Not lead free

Nomenclature & Materials

NO	Part Name	Material	Qty
1	Body	Brass	1
2	End Cap	Brass	1
3	Ball Seat	PTFE	1
4	Ball	Brass	1
5	Stem	Brass	2
6	Seal	PTFE	1
7	Impacted Nut	Brass	1
8	O-Ring	NBR	2
9	Lever Handle	Steel	1
10	Stem Nut	Steel	1

Part#	Size	I	H	D	L	A	WTG	Box/Case	
940-464	1/4"	1.89	1.73	0.39	3.58	0.47	0.51	50/100	----
940-465	3/8"	1.89	1.73	0.39	3.35	0.47	0.57	50/100	----
940-461	1/2"	2.11	1.80	0.50	3.58	0.51	0.65	30/60	----
940-462	3/4"	2.56	2.16	0.74	4.31	0.55	0.99	20/40	----

BOTTOM OUTLET 3 WAY BALL VALVE

- Forged Brass
  Bottom Port is inlet 400 psi
  Side Ports are inlet 100 psi

- Teflon ball seats
- Double O-Ring Stem Seals - primary seal is Viton secondary seal is Aflas
- Blow out proof stem
- Made in USA
- Threaded ports
- Good for propane
- Not lead free
- Great for diesel fuel

• 90° Handle Rotation



• Bottom outlet



• Threaded

Part#	Size	D	G	H	L	Cv	WTG	
940-121	1/4"	.44	3.50	3.12	2.25	5.2	0.76	----
940-122	3/8"	.50	3.50	3.12	2.25	5.5	0.69	----
940-123	1/2"	.50	3.50	3.12	2.25	5.5	1.00	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

BRASS BALL VALVE WITH STRAINER

All-in-One design for economical ,compact and convenient .With stamped stainless Steel Screen . 600PSI WOG Forged brass body,Crome plated ball ,PTFE ball seats and cap seal , and rubber o-ring stem seals. Not lead free

Part #	Part Name	Material
1	Body	Brass
2	Caps	Brass
3	Ball	Brass,Cr.Plated
4	Seat	PTFE
5	Filter	SS
6	Gasket	PTFE
7	Caps	Brass
8	Stem	Brass
9	O-Ring	Viton
10	Handle	Zinc
11	Spring Washer	S.S
12	Nut	Steel



Item#	Size	L	D	W	H	WTG	Box/Case	
947-133	**1/2"x1/2"(MxF)**	3.77"	0.59"	2.00"	1.50"	0.60	8/64	----
947-134	**3/4"x3/4"(MxF)**	4.32"	0.75"	2.40"	1.85"	1.00	8/64	----

VACUUM BREAKER

- *Male hose and female hose threads can be broken off for permanent attachment*
- *Set screw*
- *Vandal proof*
- *Rough brass construction*
- *Prevents back-siphonage on hoses to prevent potable water from getting contaminated*
- *Certified under ASSE Std. 1011*
- *UPC*
- *CSA*

Part #	Size	
947-055	3/4" x 3/4"	4009612
947-055LF	3/4" x 3/4"	

HOSE BIBBS
3/4" Hose Thread Outlet

IPS

Part #	Size	WTG	Box/ Case	
942-170	1/2 (1/2"C)	0.33	10/100	
942-171	3/4	0.35	10/100	

RADIATOR AIR VALVE
COIN SLOT OR LOSSE KEY

Part #	Size	
943-284	1/8" MIP	----
943-287	Key only	----

ANGLE SILLCOCKS
3/4" Hose Thread Outlet

- Notched flange for convenient installation.
- Heavy brass construction.
- Cast Iron handle.
- Not lead free

FEMALE IPS

Part #	Size	Box	
942-142	1/2	12	4009008

BENT NOSE GARDEN VALVES

- Heavy brass construction
- Cast iron handle
- Stuffing box
- Neoprene seal disc

Part #	Size	Box	Case	
942-100	1/2"	12	72	----
942-101	3/4"	12	72	----
942-102	1"	12	72	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

BRASS GATE VALVE

• BRASS • 200WOG • FULL PORT

- 200 WOG (cold water, oil, gas).
- 125 WSP (Saturated Steam).
- Full-port design for a better water flow.
- Screw-in Bonnet - Non-Rising Stem - Solid Wedge
- NPT Threaded ends to ANSI B1.20.1
- Cast iron handle.
- Each valve individually air tested under water.
- Good for diesel fuel.
- Made in Indonesia
- Not lead free
- Temp. 32°-320°F

BRASS GATE VALVES IPS

Part#	Size	L	H	D1	d	T	S1	Weight	Box/Case	
940-130	1/4	1.64	2.91	2.09	0.44	1/4-18 NPT	.85	0.60	10/120	4001004
940-131	3/8	1.71	2.91	2.09	0.48	3/8-18 NPT	.85	0.59	10/120	4001006
940-132	1/2	1.71	2.91	2.09	0.50	1/2-14 NPT	1.03	0.75	10/120	4001008
940-133	3/4	1.71	3.06	2.13	0.74	3/4-14 NPT	1.26	0.83	10/80	4001012
940-134	1	2.13	3.60	2.48	0.97	1-11.5 NPT	1.51	1.24	5/60	4001016
940-135	1-1/4	2.24	4.50	2.66	1.22	1-1/4-11.5 NPT	1.89	1.69	5/40	4001020
940-136	1-1/2	2.44	5.08	3.15	1.45	1-1/2-11.5 NPT	2.17	2.17	5/30	4001024
940-137	2	2.70	5.94	3.52	1.85	2-11.5 NPT	2.60	3.33	2/24	4001032
940-138	2-1/2	3.70	7.87	3.98	2.48	2-1/2-8 NPT	3.27	6.26	1/10	4001040
940-139	3	4.02	8.82	4.37	2.80	3-8 NPT	3.86	8.34	1/6	4001048
940-140	4	4.53	9.88	4.74	3.60	4-8 NPT	4.88	13.09	1/4	4001064



See Lead Free section page 172 for lead free Gate Valves.

See page 207 for SS Gate Valve

NO	Description	Material
1	Body	C85700
2	Disk	C85700
3	Seat	PTFE
4	Cap	C85700
5	Packing	C85700
6	Stem	C85700
7	Rubber Seat	NBR
8	Packing Nut	C85700
9	Handle	Cast Iron
10	Nameplate	AL
11	Stem Nut	SAE 1010R

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

GATE VALVE QUICK OPENING

Features: Bronze Material, Threaded Ends



MATERIAL SPECIFICATION

No.	Part	Bronze
1	BONNET	BRASS (C85700)
2	PACKING	FIBRE
3	ARM	BRASS (C85700)
4	DISC MALE	BRASS (C85700)
5	DISC FEMALE	BRASS (C85700)
6	BODY	BRASS (C85700)
7	STEM	BRASS (C37700)
8	WASHER	BRASS (C37700)
9	PACKING	TEFLON POLYFLON (PTFE M-392)
10	PACKING NUT	BRASS (C37700)
11	HANDLE	CAST IRON (JIS ZZ2202) RUBBER COATING BRASS (C85700)
12	NAME PLATE	ALUMINIUM (A1100)
13	WASHER	HOT ROLLED (SAE 1010R)
14	HANDLE BOLT	HOT ROLLED (SAE 1010R)

Part #	Size	L	L1	L2	H	H1	Box	Case	
941-133	1/2"	45.6	60.6	119	56.8	52.8	10	50	----
941-134	3/4"	51	62	126.3	68	87.5	10	50	----
941-135	1"	58.3	72.3	155	78.7	90.2	10	30	----
941-136	1-1/4"	30.1	78	180.2	89.5	104	5	25	----
941-137	1-1/2"	66.7	85.3	196.6	99.2	131	6	18	----
941-138	2"	76.4	90.3	250.6	119.3	143.7	2	10	----
941-140	3"	101	129.2	305.6	172.2	191.3	2	6	----
941-141	4"	114.5	150.7	378.2	213.5	248.6	1	2	----

Ignorance, the root and stem of all evil. - Plato

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

CLASS 150 BRASS Y-PATTERN STRAINER

- Forged Brass body, size 1/4"-3".
- Pressure rating: 150 WOG (water, oil, gas)/PN25
  150 WSP (Saturated Stem)
- NPT Threaded ends to ANSI B1.20.1
- Protects regulators, pumps, meters and other controls from damage due to sediment scale, metal chips or other foreign materials.
- Screwed cap is threaded & gasketed.
- Tapped drain plug opening in cap.
- 304 stainless steel screen #20 mesh.
- Self cleaning.
- Self cleaning can be accomplished by opening the valve or plug connected to the blow-off outlet.
- Made in Indonesia
- NOT LEAD FREE
- w/20 Mesh Screen
- Temp 180°F

Part#	Size	L	H	C (Plug)	Weight	Box/Case	
940-521	1/4"	2.57	1.95	NPT 3/8	.53	10/100	----
940-522	3/8"	3.23	2.44	NPT 3/8	.71	12/48	----
940-523	1/2"	3.23	2.44	NPT 3/8	.66	12/48	----
940-524	3/4"	3.94	2.78	NPT 3/8	1.10	8/48	----
940-525	1"	4.53	3.19	NPT 1/2	1.71	8/32	----
940-526	1-1/4"	5.33	3.66	NPT 1/2	2.49	6/24	----
940-527	1-1/2"	6.20	3.82	NPT 1/2	3.24	2/16	----
940-528	2"	7.44	4.65	NPT 1/2	5.39	2/8	----
940-529	2-1/2"	9.50	5.39	NPT 3/4	9.56	1/6	----
940-530	3"	9.4	5.67	NPT 3/4	13.49	1/4	----

Add 'S' to part # for replacement screens

See page 172 for 1/2" Lead Free

See page 207 for SS Y Strainer



NO	Name	Material
1	BODY	C85700
2	BONNET	C85700
3	STRAINER	304 S.S.
4	SPRING SEAL	PTFE
5	END CAP	C85700

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

BRASS SWING CHECK VALVES

- Working pressure non-shock: 200 psi W.O.G. (cold water, oil, gas) 125 psi WSP (saturated steam)
- Swing type disc.
- Screwed Cap.
- Hard Seat.
- 90⁰ Straight Pattern.
- Used to prevent reverse flow in commercial and industrial applications.
- Threaded ends to ANSI B1.20.1
- Integral seat.
- Temp range -5° - 150F°
- NOT LEAD FREE
- Cracking pressure 3-5 psi
- Made in Indonesia



NO	Description	Material
1	Body	C85700
2	Disc	C85700
3	Cap	C85700
4	Brass Bar	C85700
5	Screw	C85700
6	Gasket	Fibre H

CAST BRASS SWING CHECK VALVES IPS SCREWED ENDS

Part #	Size	L	H	L1	DN	Weight	Box/Case	
940-352	1/2	2.09	1.42	0.531	0.512	.41	10/100	4003008
940-353	3/4	2.36	1.56	0.579	0.728	.56	10/80	4003012
940-354	1	2.62	1.77	0.748	0.925	.73	5/60	4003016
940-355	1-1/4	3.19	2.07	0.748	1.201	1.36	5/40	4003020
940-356	1-1/2	3.54	2.16	0.846	1.417	1.56	5/30	4003024
940-357	2	4.21	2.74	0.886	1.772	2.58	2/20	4003032
940-358	2-1/2	5.14	3.09	1.063	2.224	4.55	1/15	4003040
940-359	3	5.77	3.80	1.102	2.579	6.53	1/6	4003048
940-360	4	6.84	4.25	1.102	3.602	10.18	1/4	4003064

• See page 172 for Lead Free Brass Swing Check Valves

• See page 207 for SS Swing Check Valves

Y PATTERN BRASS SWING CHECK VALVE SCREWED ENDS

Part #	Size	
940-352B	1/2"	----
940-353B	3/4"	----
940-354B	1"	----
940-355B	1-1/4"	----
940-356B	1-1/2"	----
940-357B	2"	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

BRASS CHECK VALVES

S.S. SPRING LOADED BRONZE POPPET - For positive sealing & self-cleaning. Insures against leakage.

- Inline Lift Type - Resilient Discs - Spring Actuated - Threaded.
- Presure rating: 200 WOG (water, oil, gas) / 125 WSP (Saturated Steam)
- Spring in stainless steel AISI 304. • Resilient washer hold/ disc in brass. • Forged Brass Body for 1/2"-2"
- Corrosion resistant material. • Can be used vertically or horizontally. • Opens & Closes with flow of media.
- No cracking pressure. • NOT LEAD FREE • Made in Indonesia



Temp Range
-10°C - 110°C
14°F - 248°F



Brass Check Valve (Inches)

Part#	Size	Enters Pipe Size	A NPT	B	C	Weight	Box/Case	
944-428	1/4"	-	1/4"	1.00	2.29	.24	24/192	----
944-429	3/8"	-	3/8"	1.00	2.07	.23	10/100	----
944-430	1/2"	1-1/4"	1/2"	1.26	2.40	.42	10/100	4003408
944-431	3/4"	1-1/4"	3/4"	1.45	2.74	.53	10/80	4003412
944-432	1"	2"	1"	1.77	3.23	.80	6/60	4003416
944-433	1-1/4"	2-1/2"	1-1/4"	2.13	3.62	1.18	4/40	4003420
944-434	1-1/2"	3"	1-1/2"	2.29	4.04	1.40	5/30	4003424
944-435	2"	3-1/2"	2"	2.48	5.04	2.70	5/20	4003432

• See page 172 for Lead Free Brass Check Valves

• See page 203-207 for SS Check Valves

IN LINE CHECK VALVES VERTICAL OR HORIZONTAL

- Working Pressure: 250 PSI • Temperature Range: -40° to 450°F(-40°to 230°C)
- Cracking Pressure: 3 PSI • Made in China • Not lead free
- Applications:Air Compressor Discharge Lines, may also used on water or oil lines
- Construction:Cast Bronze Body,Corrosion Resistant Stainless Steel Spring to Ensure Long Life,15% Glass Filled • Teflon Poppet,C360 Machined Brass Cap,1/8 NPT Unloader Port is Standard • Repairable



Part#	Part Name	Material
6	Plug	Brass
5	Body	Bronze
4	Gasket	PTPF
3	Spring	S.Steel
2	O-ring	HNBR
1	Cap	Brass

Part #	Size	W	L	H	WTG	Box/Case	
947-140	1/8"	1/8	1.75	1.34	0.28	20/100	----
947-141	1/4"	1/4	1.75	1.37	0.29	20/100	----
947-142	3/8"	3/8	2.50	2.18	0.62	10/50	----
947-143	1/2"	1/2	2.50	2.13	0.54	10/50	----
947-144	3/4"	3/4	2.88	2.64	1.17	8/40	----
947-145	1"	1	3.61	3.30	1.98	2/20	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

BRASS IN-LINE CHECK VALVES

High Capacity, Size 1/4"-2" 400 WOG, 2 1/2"-4" 175 WOG

- Soft Seat for Bubble Tight Shutoff, Spring Loaded for Fast Seating Action.
- Compact design.
- Low Cracking Pressure 1/2 psi.
- Flow Profile Designed to Minimize Head Loss.
- Perfect Seating both at High and Low Pressure, Wide Temperature Range: +10° to 210°F.
- Polyethermide Disc to ensure the Best Resistance For Corrosion and Abrasion.
- Patented Disc Guide to Prevent Any Side Loading.
- Connection: FNPT x FNPT.
- Made in Italy • Not lead free

NBR for water, oils and general purpose.
With VITON® Seal for fuels and hydrocarbons. Max working TEMPERATURE 325°F/125 psi steam

Add V to part# for Viton®

Brass In-Line Check

Part#		Size	l	psi	Lbs	Case	Viton Part#	
944-401	----	1/4"	0.39	400	0.22	144		
944-402	----	3/8"	0.40	400	0.18	144	944-402V	----
944-403	----	1/2"	0.60	400	0.32	144	944-403V	----
944-404	----	3/4"	0.65	400	0.49	90	944-404V	----
944-405	----	1"	0.66	400	0.71	90	944-405V	----
944-406	----	1-1/4"	0.68	400	1.13	30	944-406V	----
944-407	----	1-1/2"	0.68	400	1.53	30	944-407V	----
944-408	----	2"	0.69	400	2.28	12	944-408V	----
944-409	----	2-1/2"	0.93	175	4.83	4	944-409V	
944-410	----	3"	1.01	175	6.70	4	944-410V	
944-411	----	4"	1.09	175	12.43	2	944-411V	



NO	Part	Material	PCS
1	BODY	BRASS	1
2	END CONNECTION	BRASS	1
3	DISC	POLYETHERIMIDE	1
4	SEAT	100002 NBR	1
		100003 Viton	1
5	SPRING	STAINLESS STEEL	1

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

316 SS 2-PC BALL VALVE, FULL PORT, THREADED END, 2000 PSI

- Investment Castings for body and cap.
- Internal Entry blow-out proof stem.
- Pressure rating: 2000PSI.
- Threaded Ends: ANSI B2,1
- Material: CF8M (316SS)
- Pressure test: API 598
- Generic Handles



LOCKING HANDLE

Part#	Size	D	L	H	W	N.M	lbs/ pc	Case	
949-171	1/4"	0.36	2.13	2.13	4.33	.157	0.64	80	----
949-172	3/8"	0.50	2.13	2.16	4.33	.157	0.58	80	----
949-173	1/2"	0.59	2.24	2.28	4.53	.197	0.71	70	----
949-174	3/4"	0.79	2.76	2.40	4.53	.315	1.18	50	----
949-175	1"	0.98	3.50	3.03	6.04	.394	2.33	30	----
949-176	1-1/4"	1.25	4.12	3.19	6.04	.551	3.48	20	----
949-177	1-1/2"	1.50	4.05	3.54	6.10	.709	4.03	14	----
949-178	2"	1.96	4.90	4.25	6.10	.984	7.50	7	----



NO	Part	Material	QTY
1	BODY	316SS	1
2	BALL SEAT	PTFE	2
3	BALL	316SS	1
4	BODY SEAL	PTFE	1
5	CAP	316SS	1
6	STEM	SS316	1
7	THRUST WASHER	PTFE	1
8	PACKING	PTFE	1
9	GLAND NUT	SS304	1
10	HANDLE	SS304	1
11	WASHER	SS304	1
12	NUT	SS304	1
13	LOCK DEVICE	SS304	1
14	HANDLE COVER	PLASTIC	1

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

ONE PIECE STANDARD PORT BALL VALVE

316 Stainless Steel

1000 PSI

- Manufactured for harsh environments with female NPT threads.
- Locking handle for greater security.
- Standard port has restricted flow.
- Made with corrosion resistant stainless steel materials.
- PTFE seat and seals.
- Investment Castings for Body and Cap.
- Internal Entry Blow-out proof stem.
- Pressure rating: 1000PSI (PN63)
- Threaded Ends: ANSI B2.1
- Material: CF8M
- Pressure Test: API 598
- Generic handles

LOCKING HANDLE

Valves will accept a pad-lock on the handle.

dimensions (inches)

Part#	Size	D	L	H	W	Weight	Case	
949-101	1/4"	0.20	1.53	1.53	3.03	0.19	150	----
949-102	3/8"	0.27	1.74	1.53	3.03	0.23	150	----
949-103	1/2"	0.36	2.24	1.73	3.46	0.41	100	----
949-104	3/4"	0.50	2.32	1.89	3.46	0.63	70	----
949-105	1"	0.59	2.80	2.24	4.29	0.86	50	----
949-106	1-1/4"	0.79	3.07	2.32	4.29	1.34	30	----
949-107	1-1/2"	0.98	3.26	2.76	5.14	2.00	25	----
949-108	2"	1.25	3.94	2.24	6.50	2.88	15	----

Larger sizes available on special order basis



Item	Parts	Material
1	Plastic Cover	Plastic
2	Handle	AISI 304 SS
3	Thrust Washer	PTFE
4	Packing Ring	AISI 304 SS
5	Stem Packing	PTFE
6	Seat	PTFE
7	Seat	AISI 316 SS
8	Stem Nut	AISI 304 SS
9	Ball	316SS ASTM-A351 CF8M
10	Cap	316SS ASTM-A351 CF8M
11	Body	316SS ASTM-A351 CF8M

SS = Stainless Steel

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

316 SS TWO PIECE FULL PORT VALVES

TWO PIECE FULL PORT BALL VALVE

316 Stainless Steel

1000 PSI

Materials: CFM8M (SS316)

Features:

- Quality manufactured for harsh environments.
- Corrrosion resistant.
- Investment Casting body
- Working pressure 1000 psi for W.O.G.
- Adjustable stem packing
- Pure teflon seals and seats
- Temperature range: -60 to 450°F
- Blow-out proof stem and safe pressure-reducing hole
- 100% leakage tested at 100 psi air under water
- Hydrostatic test pressure: 1500 psi
- Locking handle w/ blue generic sleeve
- 125 Steam rated
- Generic Handles

Valves will accept a pad-lock on the handle.

dimensions (inches)

Part#	Size	D	L	H	W	Weight	Case	
949-161	1/4"	0.36	2.13	2.13	4.33	0.51	80	----
949-162	3/8"	0.50	2.13	2.16	4.33	0.49	80	----
949-163	1/2"	0.59	2.24	2.28	4.17	0.69	70	----
949-164	3/4"	0.79	2.68	2.40	4.17	1.03	50	----
949-165	1"	0.98	3.15	2.50	4.88	1.40	30	----
949-166	1-1/4"	1.26	3.58	3.19	5.04	2.17	20	----
949-167	1-1/2"	1.49	4.05	3.54	6.10	3.33	12	----
949-168	2"	1.97	4.88	4.25	6.13	6.02	7	----
949-170	3"	3.15	7.28	5.71	9.06	21.01	2	----
949-180	4"	3.94	8.84	7.28	11.10	36.18	1	----



Dimensions may change without notice. Please see our website if they are critical.

Item	Parts	Material
1	Body	316SS ASTM-A351 CF8M
2	Body Cap	316SS ASTM-A351 CF8M
3	Ball	316SS ASTM-A351 CF8M
4	Seat	Reinforced PTFE
5	Stem	AISI 316 SS
6	Seal	Reinforced PTFE
7	Thrust Washer	Reinforced PTFE
8	Packing	Reinforced PTFE
9	Gland Nut	AISI 304SS
10/11	Nut & Washer	AISI 304SS
12	Handle	AISI 304SS
13	Plastic Cover	Plastic

SS = Stainless Steel

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

STAINLESS STEEL MIN BALL VALVES

- 316 Stainless Steel
- Working pressure 400PSI
- Working Temperature -10°C to 150°C

FEMALE PIPE x FEMALE PIPE

Part#	Size	W	D	H	L	Weight	Case	
46934SS	1/8"	.898	.197	.985	1.693	.18	150	----
46935SS	1/4"	.898	.276	.984	1.693	.21	150	----
46936SS	3/8"	.898	.276	.984	1.693	.19	150	----
46937SS	1/2"	.898	.362	1.114	1.811	.26	100	----

MALE PIPE x FEMALE PIPE

Part#	Size	W	D	H	L	Weight	Case	
46930SS	1/8"	.898	.197	.985	1.693	.18	150	----
46931SS	1/4"	.898	.276	.984	1.693	.18	150	----
46932SS	3/8"	.898	.276	.984	1.693	.19	150	----
46933SS	1/2"	.898	.362	1.114	1.811	.26	100	----



NO	Part	Material	QTY
1	LEVER	ALUMINIUM ALLOY	1
	HANDLES	PLASTIC	
2	BOLT	304	1
3	STEM	304/ 316	1
4	"O" RING	NBR	1~2
5	BALL SEAT (A)	PTFE	1
6	CAP	CF8/ CF8M	1
7	BALL	CF8/ CF8M	1
8	BODY	CF8/ CF8M	1
9	BALL SEAT (B)	PTFE	1

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

316 SS MINI BALL VALVES

MINI STAINLESS STEEL BALL VALVE ,WITH BUTTERFLY HANDLE

1000PSI WOG , 150PSI WSP
Temperature Range: -36°F to + 368°F
Full Port for 1/4" , Standard port for 3/8" and 1/2"
316 Stainless Steel body and Ball
Teflon seats and sealing

- Viton O-Ring
- #316 Stainless Steel
- Made in China

FEMALE PIPE X FEMALE PIPE

Part #	Size	Dimensions in						
	FIP x FIP	d	L	B (Hex)	H	WTG	Box	
46-922SS	1/4"×1/4"	0.314"	2.34"	22.1/0.87"	1.5"	0.33	36	----
46-923SS	3/8"×3/8"	0.314"	2.39"	22.1/0.87"	1.5"	0.39	36	----
46-924SS	1/2"×1/2"	0.314"	2.81"	24.9/0.98"	1.5"	0.43	36	----

MALE PIPE X FEMALE PIPE

Part #	Size	Dimensions in						
	MIP x FIP	d	L	B (Hex)	H	WTG	Box	
46-903SS	1/4"×1/4"	0.314"	2.45"	0.87"	1.5"	0.39	36	----
46-904SS	3/8"×3/8"	0.314"	2.45"	0.87"	1.5"	0.36	36	----
46-905SS	1/2"×1/2"	0.314"	2.81"	0.98"	1.5"	0.41	36	----

MALE PIPE X MALE PIPE

Part #	Size	Dimensions in						
	MIP x MIP	d	L	B (Hex)	H	WTG	Box	
46-912SS	1/4"×1/4"	0.314"	2.59"	0.87"	1.5"	0.33	36	----
46-913SS	3/8"×3/8"	0.314"	2.65"	0.87"	1.5"	0.34	36	----
46-914SS	1/2"×1/2"	0.314"	2.47"	0.98"	1.5"	0.63	36	----





Part #	Part Name	Material
1	Body	S316
2	Seat	PTFE
3	Ball	S316
4	O-Ring	Viton
5	Cap	S316
6	Stem	S316
7	Stem Bottom Seal	PTFE
8	Stem Up Seal	PTFE
9	Nut	Steel
10	Handle	Steel

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

#304 STAINLESS STEEL

CHECK VALVE

- No Lead.
- Water wells need a check valve installed above the pumps between lengths of drop pipes.
- Opens & Closes with flow of media.
- No cracking pressure.
- Working pressure unavailable.
- Made in Taiwan

Dimensions (Inches)

Part#	Size	A NPT	B	C	Box/Case	
949-430	1/2"	1/2"	1.26	2.43	10/100	----
949-431	3/4"	3/4"	1.50	2.72	10/80	----
949-432	1"	1"	1.77	3.23	10/60	----

More sizes available on a special order basis.





FLOW RATE GALLONS PER MINUTE

NO	Part	Material
1	Body	S.S 304
2	Stopper	S.S 304
3	O-Ring	Viton
4	Washer	PE
5	Spring	S.S 304
6	Cap	S.S 304
7	Nut	S.S 304

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

STAINLESS STEEL IN-LINE CHECK VALVE

High Capacity, Size 1/4"-2" 800 WOG

- Soft PTFE Seat for Bubble Tight Shutoff, Spring Loaded for Fast Seating Action
- Low Cracking Pressure 1/2 psi.
- Flow Profile Designed to Minimize Head Loss.
- Perfect Seating both at High and Low Pressure, Wide Temperature Range: +10° to 450°F.
- Corrosion Resistant-Excellent for use on Chemicals.
- ASTM A351-CF8M Investment Casting.
- Connection: FNPT x FNPT.
- 125WSP Saturated Steam.
- ANSI B1.20.1 Threads.
- Dual Guided Stem & Disc.
- Made in Italy

Stainless Steel In-Line Check

Part#	Size	D	L	psi	Lbs	
949-401	1/4"	1.15	2.25	800	0.36	----
949-402	3/8"	1.16	2.25	800	0.34	----
949-403	1/2"	1.35	2.31	800	0.40	----
949-404	3/4"	1.81	2.87	800	0.85	----
949-405	1"	2.13	3.50	800	1.30	----
949-406	1-1/4"	2.46	4.18	800	2.50	----
949-407	1-1/2"	2.88	4.93	800	3.40	----
949-408	2"	3.56	6.00	800	6.0	----



NO	Part	Material	PCS
1	BODY	ASTM A351-CF8M	1
2	SPRING	SS316	1
3	CENTER GUIDE	ASTM A351-CF8M	1
4	DISC	ASTM A351-CF8M	1
5	SEAT	PTFE	1
6	GASKET	PTFE	1
7	END CAP	ASTM A351-CF8M	1

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

SPRING CHECK VALVE

- Working Pressure: 1500PSI (PN100)
- Working Temperature: -10 -150°C
- Opening Pressure: 2~3PSI
- Suitable Medium: W.O.G.
- Threaded End: NPT
- Made in China

FEMALE PIPE x FEMALE PIPE

Part#	Size	L	C	D	B	E	lbs/ pc	Case	
949-451	1/4"	2.165	.217	.748	.699	.394	.19	200	----
949-452	3/8"	2.165	.295	.866	.787	.394	.21	160	----
949-453	1/2"	2.165	.413	1.063	.945	.472	.31	100	----
949-454	3/4"	2.677	.591	1.417	1.26	.472	.71	60	----
949-455	1"	3.268	.787	1.693	1.496	.591	1.14	36	----

MALE PIPE x FEMALE PIPE

Part#	Size	L	C	D	B	E	lbs/ pc	Case	
949-471	1/4"	2.165	.217	.748	.699	.394	.176	200	----
949-472	3/8"	2.165	.295	.866	.787	.394	.22	160	----
949-473	1/2"	2.165	.413	1.063	.945	.472	.27	100	----
949-474	3/4"	2.677	.591	1.417	1.26	.472	.62	65	----
949-475	1"	3.268	.787	1.693	1.496	.591	1.05	40	----

FLOWS MALE -> FEMALE



NO	Part	Material	QTY
1	BODY	316	1
2	RING	Rubber	1
3	SPRING	304	1
4	CAP	CF8M	1
5	SPOOL	304/316	1
6	SPRING RING	304	1

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

Y-SPRING CHECK VALVE

- Working Pressure: 800PSI (PN55)
- Working Temperature: -10 -150°C
- Opening Pressure: 1.5PSI
- Suitable Medium: W.O.G.
- Made in China

Part#	Size	L	H	D	lbs/ pc	Case	
949-481	1/4"	2.559	1.661	.472	.44	70	----
949-482	3/8"	2.559	1.661	.472	.51	70	----
949-483	1/2"	2.559	1.634	.591	.51	100	----
949-484	3/4"	3.15	2.067	.787	.93	80	----
949-485	1"	3.543	2.657	.984	1.25	40	----
949-486	1-1/4"	4.134	2.795	1.26	2.20	30	----
949-487	1-1/2"	4.724	3.169	1.575	3.24	24	----
949-488	2"	5.512	3.74	1.969	5.21	10	----



NO	Part	Material	QTY
1	BODY	CF8M/ CF8	1
2	BOLT	304	1
3	SEAT	Teflon	1
4	DISC	304	1
5	SPRING	304	1
6	GASKET	Teflon	1
7	CAP	CF8M/ CF8	1

2PC BARREL TYPE SPRING CHECK VALVE

- Working Pressure: 300PSI (PN20)
- Working Temperature: -10 -120°C
- Opening Pressure: 2PSI
- Suitable Medium: W.O.G.
- Threaded end: NPT
- Made in China

Part#	Size	L	D	lbs/pc	Case	
949-441	1/4"	2.00	1.142	.27	100	----
949-442	3/8"	2.00	1.142	.24	100	----
949-443	1/2"	2.24	1.28	.36	100	----
949-444	3/4"	2.44	1.594	.54	60	----
949-445	1"	2.95	1.89	.88	30	----
949-446	1-1/4"	3.23	2.362	1.39	18	----
949-447	1-1/2"	3.46	2.756	1.81	25	----
949-448	2"	3.94	3.425	2.86	14	----



NO	Part	Material	QTY
1	BODY	CF8M/ CF8	1
2	BOLT	304	1
3	SEAT	PTFE	1
4	DISC	304	1
5	SPRING	316/ 304	1
6	GASKET	PTFE	1
7	CAP	CF8M/ CF8	1

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

#316 SS Y STRAINER

- Investment Castings for Body
- Pressure Rating: 800PSI (PN40)
- Threaded Ends: ANSI B2.1
- Material: CF8M (#316 SS)
- Pressure Test: API 598
- Made in China



- 40 Mesh screen

	Part	Material	QTY
1	BODY	CF8M	1
2	SCREEN	SS316	1
3	JOINT GASKET	PTFE	1
4	BONNET	CF8M	1

Part #	Size	d	L	H	W	ØA	Lbs	
949-521	1/4"	.38"	2.53	51	1.69	1	0.44	----
949-522	3/8"	.48"	2.53	51	1.69	1	0.38	----
949-523	1/2"	.59"	2.53	51	1.76	1	0.46	----
949-524	3/4"	.79"	3.12	60	2.07	1	0.69	----
949-525	1"	.98"	3.57	72	2.67	1	1.27	----
949-526	1-1/4"	1.26"	4.17	77	2.9	1	1.74	----
949-527	1-1/2"	1.57"	4.71	87	3.23	1	2.38	----
949-528	2"	1.96"	5.49	102	3.88	1	3.57	----

316 SS SWING CHECK VALVE

- 200PSI(PN16)
- Threaded Ends: ANSI B2.1
- Material: CF8M (#316 SS)
- Pressure Test: API 598
- Made in China

	Part	Material	QTY
1	BODY	CF8M	1
2	DISC	CF8M	1
3	PIPE PLUG	CF8	1
4	SCREW	CF8	1
5	SCREW GASKET	PTFE	1
6	CAP	CF8M	1
7	CAP GASKET	PTFE	1



Part #	Size	D	L	W	Lbs	
949-353	1/2"	.59"	2.45	1.66	0.53	----
949-354	3/4"	.79"	2.92	1.82	0.73	----
949-355	1"	.98"	3.41	2.06	1.2	----
949-356	1-1/4"	1.26"	3.93	2.32	1.79	----
949-357	1-1/2"	1.57"	4.54	2.54	2.18	----
949-358	2"	1.96"	5.3	2.78	3.03	----

CF8 = 304SS
CF8M = 316SS

316 SS GLOBE VALVES

- 200PSI(PN16)
- Threaded Ends: ANSI B2.1
- Material: CF8M (#316 SS)
- Pressure Test: API 598
- Made in China

	Part	Material	QTY
1	BODY	CF8M	1
2	DISC	CF8M	1
3	STEM	304SS	1
4	CAP	CF8M	1
5	SEAL	PTFE	1
6	GASKET	304SS	1
7	PACKING	PTFE	1
8	GASKET	CF8	1
9	GLAND	304SS	1
10	NUT	304SS	1
11	SPRING WASHER	CF8	1
12	HANDLE WHEEL	Steel	1



Part #	Size	L	Lbs	
949-303	1/2	2.64	0.89	----
949-304	3/4	3.19	1.3	----
949-305	1	3.46	1.72	----
949-306	1-1/4	3.81	2.33	----
949-307	1-1/2	4.25	3.11	----
949-308	2	5.1	4.38	----

316 SS GATE VALVES

- 200PSI(PN16)
- Threaded Ends: ANSI B2.1
- Material: CF8M (#316 SS)
- Pressure Test: API 598
- Made in China

	Part	Material	QTY
1	BODY	CF8M	1
2	DISC	CF8M	1
3	SEAL	CF8M	1
4	CAP	CF8M	1
5	SEAL	PTFE	1
6	STEM	304SS	1
7	SEAL	PTFE	1
8	GLAND	304SS	1
9	NUT	304SS	1
10	HANDLE WHEEL	Steel	1
11	GASKET	PTFE	1
12	CAP NUT	CF8	1



Part #	Size	L	D	D1	H	Lbs	
949-253	1/2	2.07	2.54	0.55	3.37	0.78	----
949-254	3/4	2.28	2.89	0.74	4.03	0.99	----
949-255	1	2.42	2.89	0.95	4.46	1.25	----
949-256	1-1/4	2.79	3.06	1.18	4.86	1.76	----
949-257	1-1/2	2.92	3.79	1.49	5.53	2.59	----
949-258	2	3.3	4.17	1.85	6.12	3.54	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

STANDARD PORT CARBON STEEL BALL VALVE

- For chemical and industrial applications.
- Blow-out proof stem design.
- 100% air tested under water, at 100 psi, open and closed positions.
- Made in China
- Generic handles

SPECIFICATIONS

- Working Pressure: 1/4" ~ 1" 2000 psi WOG,
  1-1/4" ~ 2" 1500 psi WOG,
- Temperature Range: -60^0 to 450^{0}F
- End types: Threaded
- 1 piece ball valve
- Reinforced PTFE seat





2000 PSI STANDARD PORT

Part #	Size	d	H	E	L	WTG	Box/ Case	
949-121	1/4	.20	1.38	2.95	1.71	0.25	24/96	----
949-122	3/8	.28	1.30	3.27	1.87	0.32	100/200	----
949-123	1/2	.36	2.36	4.53	2.20	0.67	50/100	----
949-124	3/4	.49	2.72	4.53	2.58	1.06	50/100	----
949-125	1	.59	2.95	5.00	3.19	1.17	25/50	----
949-126	1-1/4	.78	3.07	5.29	3.94	3.15	15/30	----
949-127	1-1/2	0.98	3.39	5.29	3.94	2.15	15/30	----
949-128	2	1.26	3.86	5.29	4.49	6.21	10/20	----



Item	Parts	Material
1	Body	ASTM A216 WCB
2	Ball	ASTM A351 CF8
3	Stem	304
4	Ball Seat	PTFE
5	Cap Seal	PTFE
6	Packing	PTFE
7	Handle	SS304
8	Handle Sleeve	Vinyl Grip
9	Thrust Washer	PTFE
10	Gland	SS304
11	Washer	SS304
12	Handle Nut	SS304
13	Stem Nut	SS304

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer.
For more information, visit www.P65Warnings.ca.gov

2000 PSI CARBON STEEL 2PC FULL PORT BALL VALVE

• 2 PIECE

SPECIFICATIONS

- Working Pressure: 2000 PSI (138 Bar)
- Temperature Range: -10° C-150° C
- Suitable medium: WOG
- Threaded End conforms to ANSI B1.20.1
- Made in China
- Generic handle



2000 PSI FULL PORT

Part #	Size	d	L	H	W	WTG	Box/ Case	
949-111	1/4	0.36	2.13	2.13	4.33	0.59	70	----
949-112	3/8	0.50	2.13	2.17	4.33	0.59	70	----
949-113	1/2	0.59	2.24	2.28	4.33	0.75	60	----
949-114	3/4	0.79	2.76	2.40	4.33	1.17	50	----
949-115	1	0.98	3.25	3.03	5.04	1.88	30	----
949-116	1-1/4	1.26	3.58	3.19	5.04	2.45	20	----
949-117	1-1/2	1.50	4.06	3.54	6.10	4.06	20	----
949-118	2	1.97	4.90	4.25	6.10	2.43	7	----



Item	Parts	Material
1	Handle cover	Plastic
2	Body	CF8M
3	Ball seat	PTFE
4	Ball	CF8M
5	Cap	CF8M
6	Joint gasket	PTFE
7	Thrust washer	PTFE
8	Stem packing	PTFE
9	Gland nut	304
10	Spring washer	304
11	Stem nut	304
12	Stem	316
13	Lock device	304
14	Handle	304

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

HIGH PRESSURE FULL PORT 2-WAY VALVES

FULL PORT Two-Way

BKH

Part Number	Thread	Working Pressure	
GE2-14-NPT	1/4" NPT	7250 PSI	----
GE2-38-NPT	3/8" NPT	7250 PSI	----
GE2-12-NPT	1/2" NPT	7250 PSI	----
GE2-34-NPT	3/4" NPT	5800 PSI	----
GE2-1-NPT	1" NPT	5075 PSI	----
GE2-114T-NPT*	1-1/4" NPT	5000 PSI	----
GE2-112T-NPT*	1-1/2" NPT	5000 PSI	----
GE2-2T-NPT	2" NPT	5000 PSI	----

Part Number	Thread	Working Pressure	
GE2-04-SAE	7/16-20 UNF	7250 PSI	----
GE2-06-SAE	9/16-18 UNF	7250 PSI	----
GE2-08-SAE	3/4-16 UNF	7250 PSI	----
GE2-12-SAE	1-1/16-12 UNF	5800 PSI	----
GE2-16-SAE	1-5/16-12 UNF	5000 PSI	----
GB2-20T-SAE+	1-5/8-12 UNF	5000 PSI	----
GB2-24T-SAE+	1-7/8-12 UNF	5000 PSI	----
GB2-32T-SAE+	2-1/2-12 UNF	5000 PSI	----

*** Reduced Port**
+ 'L' flow pattern

Temp Rating = -22° - 212°F

Construction: Steel Body, Ball, Stem
Zinc Chromate Plate
Buna "O" Rings (Viton on request)
Delrin Ball Seats

FULL PORT Three-Way

BK3

Part Number	Thread	Working Pressure	
GE3L-14-NPT	1/4" NPT	5880 PSI	----
GE3L-38-NPT	3/8" NPT	5880 PSI	----
GE3L-12-NPT	1/2" NPT	5145 PSI	----
GE3L-34-NPT	3/4" NPT	5145 PSI	----
GE3L-1-NPT	1" NPT	5145 PSI	----
GE3L-114T-NPT	1 1/4" NPT	4500 PSI	----
GE3L-112T-NPT	1 1/2" NPT	4500 PSI	----
GE3L-2T-NPT	2" NPT	4500 PSI	----

Part Number	Thread	Working Pressure	
GE3L-04-SAE	7/16-20 UNF	5880 PSI	----
GE3L-06-SAE	9/16-18 UNF	5880 PSI	----
GE3L-08-SAE	3/4-16 UNF	5145 PSI	----
GE3L-12-SAE	1-1/16-12 UNF	5145 PSI	----
GE3L-16-SAE	1-5/16-12 UNF	5145 PSI	----
GB3L-20T-SAE+	1-5/8-12 UNF	4500 PSI	----
GB3L-24T-SAE+	1-7/8-12 UNF	4500 PSI	----
GB3L-32T-SAE+	2-1/2-12 UNF	4500 PSI	----

+ 'L' flow pattern

Temp Rating = -22° - 212°F

Construction: Steel Body, Ball, Stem
Zinc Chromate Plate
Buna "O" Rings (Viton on request)
Delrin Ball Seats

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer.
For more information, visit www.P65Warnings.ca.gov

CHECK VALVES - HARD SEAT CARBON STEEL CONSTRUCTION - 5lb Cracking Pressure

• w/ NPT threads



A (NPT Female both ends)

Part #	A Size	B Inches	C Inches	Rated Flow gpm	PSI	
100025	1/4 NPT	2.44	.87	6	5,000	----
100035	3/8 NPT	2.87	.95	10	5,000	----
100045	1/2 NPT	3.76	1.26	18	5,000	----
100065	3/4 NPT	4.30	1.50	30	5,000	----
100085	1 NPT	4.74	1.83	36	5,000	----
1000105	1-1/4 NPT	5.56	2.40	50	3,000	----
1000125	1-1/2 NPT	5.56	2.56	60	3,000	----

CHECK VALVES - HARD SEAT CARBON STEEL CONSTRUCTION - 65lb Cracking Pressure

Part #	A Size	B Inches	C Inches	Rated Flow gpm	PSI	
1000265	1/4NPT	2.45	.87	6	5,000	----
1000365	3/8NPT	2.91	.94	10	5,000	----
1000465	1/2NPT	3.74	1.18	18	5,000	----
1000665	3/4NPT	4.29	1.26	30	5,000	----
1000865	1NPT	5.00	1.81	36	5,000	----
10001065	1-1/4NPT	5.20	2.41	50	3,000	----
10001265	1-1/2NPT	5.20	2.56	60	3,000	----

CHECK VALVES - 5lb Cracking Pressure

• w/ SAE threads

Part #	A Size	B Inches	C Inches	Rated Flow gpm	PSI	
100145	7/16-20 SAE	2.56	.87	6	5,000	----
100165	9/16-18 SAE	2.91	.94	10	5,000	----
100185	3/4-16 SAE	3.74	1.18	18	5,000	----
1001125	1-1/6-12 SAE	4.29	1.50	30	3,000	----
1001165	1-5/16-12 SAE	5.00	1.81	36	3,000	----
1001205	1-5/8-12 SAE	5.20	2.41	50	3,000	----
1001245	1-7/8-12 SAE	5.20	2.56	60	3,000	----

CHECK VALVES - 65lb Cracking Pressure

• w/ SAE threads

Part #	A Size	B Inches	C Inches	Rated Flow gpm	PSI	
1001465	7/16-20 SAE	2.56	.87	6	5,000	----
1001665	9/16-18 SAE	2.91	.94	10	5,000	----
1001865	3/4-16 SAE	3.74	1.18	18	5,000	----
10011265	1-1/6-12 SAE	4.29	1.50	30	3,000	----
10011665	1-5/16-12 SAE	5.00	1.81	36	3,000	----
10012065	1-5/8-12 SAE	5.20	2.41	50	3,000	----
10012465	1-7/8-12 SAE	5.20	2.56	60	3,000	----

Rated Pressure: Sizes 2 thru 8 - 5000 psi / Sizes 10 thru 24 - 3000 psi

• Soft Seat available by special quote

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

WHITE PVC BALL VALVES

•Quarter turn
•Solvent ends comply with ASTM D2466
•Designed for use in residential, commercial & industrial system as well as waste water, chemical, agricultural applications, marine, food processing, swimming pools.
•Corrosion resistant
•EPDM seal • FULL PORT •EPDM O-ring
•Fits both Sch. 40 & 80 pipe
•Rated for 150 PSI at 73°F • Threaded ends comply with ANSI B1.20.1

MOLDED IN PLACE - WHITE PIPE THREADS

Part#	Size	Case	
940-284	1/2"	100	4202008
940-285	3/4"	100	4202012
940-286	1"	100	4202016
940-287	1-1/4"	100	4202020
940-288	1-1/2"	48	4202024
940-289	2"	24	4202032
940-291	3"	12	4202048
940-292	4"	6	4202064

WHITE SOCKET - SLIP X SLIP

Part #	Size	Case	
940-294	1/2"	100	4202208
940-295	3/4"	100	4202212
940-296	1"	100	4202216
940-297	1-1/4"	100	4202220
940-298	1-1/2"	48	4202224
940-299	2"	24	4202232
940-300	2-1/2"	12	4202240
940-301	3"	12	4202248
940-302	4"	6	4202264

GREY PVC BALL VALVES

FEATURES

- Sizes range from 1/2" to 4"
- Excellent flow characteristics
- Leak-tight shut-off
- EPPM O-Ring
- SCH 80
- Test pressure: 225 psi @ 73°F
- Working Pressure: 150 psi @ 73°F

FIP X FIP THREADED BALL VALVE

Part #	Size	Case	
899000	1/2"	100	4202008
899001	3/4"	100	4202012
899002	1"	100	4202016
899003	1-1/4"	100	4202020
899004	1-1/2"	48	4202024
899005	2"	24	4202032

SLIP X SLIP BALL VALVE

Part #	Size	Case	
899050	1/2"	100	4202208
899051	3/4"	100	4202212
899052	1"	100	4202216
899053	1-1/4"	100	4202220
899054	1-1/2"	48	4202224
899055	2"	24	4202232

CPVC BALL VALVE

Part #	Size	
940-281	1/2"	4202808
940-282	3/4"	4202812

WARNING: This product can expose you to chemicals, including Chloroethane, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

INLINE PLASTIC SPRING CHECK VALVE

Socket x Socket

• 200 PSI working pressure @ 77°F .5 PSI to open.

Part#	Size	
940-325	1/2"	4203608
940-326	3/4"	4203612
940-327	1"	4203616
940-328	1-1/4"	4203620
940-329	1-1/2"	4203624
940-330	2"	4203632

INLINE PLASTIC SPRING CHECK VALVE FEMALE THREADED ENDS

• 200 PSI working pressure @ 77°F .5 PSI to open.

Part#	Size	
940-331	1/2"	4203408
940-332	3/4"	4203412
940-333	1"	4203416
940-334	1-1/4"	4203420
940-335	1-1/2"	4203424
940-336	2"	4203432

PLASTIC DRUM FAUCETS

• Pipe threads to ANSI B1.20.1 • Hose threads to ANSI B 1.20.7

The FLO-RITE faucet has been engineered to meet the demand for greater chemical resistance, using linear polyethylene for the stem.

"FLO-RITE" DRUM FAUCET

Part #	Size	
46-277	3/4"	----

DRUM & BARREL FAUCET VALVE

- Die cast body w/ nylon seat and steel spring.
- For use with all petroleum products except trichlorethylene.

G261N

Not suitable for potable water

SELF-CLOSING DRUM & BARREL FAUCET

Part #	Size	
46-270	3/4"	4030012



Part #	Part Name	Material
1	Body	Zinc
2	Bonnet	Zinc
3	Stem	Steel
4	Disc	Plastic
5	Seal	Rubber
6	Spring	Zinc plated steel
7	Handle	Aluminum
8	Rivet	Aluminum

WARNING: This product can expose you to chemicals, including Chloroethane, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

NIPPLES & FITTINGS

BRASS & BRONZE 215-234

Brass Nipples - Sch 40 215-221
EH Sch 80 .....
C/P Brass Nipples 222
Bronze Fittings 223-231
EH Bronze Fittings .....
Lead Free Bronze Fittings 223-230
C/P Fittings 231
Bronze Cleanout Plugs 232
Bronze Drop Ear Elbows 232
Bronze Barbs for PL. Pipe 233
Steel Barbs for PL. Pipe 233
Lead Free Bronze Barbs for PL. Pipe 234
Stainless Steel Barbs for PL. Pipe 234
Stainless Steel Well Couplings 234
Stainless Steel Merchant Couplings 234

STAINLESS STEEL 235

Stainless Nipples 235-240
Sch 80 SS Nipples .....
150# Cast SS Fittings 241-248
1,000# Barstock SS fittings NEW .....
3000# SS Fittings .....

BLACK & GALVANIZED 249-286

Sch. 40 Welded Steel Nipples 250-257
Sch. 80 Seamless Steel nipple 258-263
Sch. XXS Seamless Steel Nipple 264
Groove Nipples 265-266
Merchant Couplings 267
API Line Couplings 268
Malleable Fittings 269-278
Steel Fittings 279-280
300# Malleable 281-282
Forged Steel Fittings .....
Bull Plugs and Swages 283-284
Forged Steel Fanges 285-286

Copper Fittings 287-293

We hereby certify that to the best of our knowledge and belief the CDA 230 alloy seamless Red Brass Pipe from which our nipples are produced meet the requirements of ASTM Specifications B43 and is free of mercury contamination. The chemical analysis is 85% copper, 15% Zinc and conforms to federal Specifications WWN-351. Our brass nipples meet ANSI/ASTM B687-96 and MS51846 for standard brass nipples, and MS51872 for extra heavy brass nipples.

Threads: Nipples are threaded with American Standard taper pipe threads (NPT) in accordance with screw-thread standard for Federal Services Handbook H-58. ANSI B1.20.1

This product is certified by NSF to NSF/ANSI 61 for use in drinking water supplies of pH 6.5 and above.

- ASTM B43
- ANSI B1.20.1, WW-N-351
- ANSI/ ASTM B687-96
- NSF-61 Approved
- MS51846 STD Brass Nipples
- RoHS compliant

STANDARD RED BRASS 85%
PIPE WITH THREADED ENDS SPECIFICATIONS:

Pipe Size in Inches	Dimension in Inches		
	O.D.	I.D.	Wall Thickness
1/8"	.405	.281	.062
1/4"	.540	.376	.082
3/8"	.675	.495	.090
1/2"	.840	.626	.107
3/4"	1.050	.822	.114
1"	1.315	1.063	.126
1-1/4"	1.660	1.368	.146
1-1/2"	1.900	1.600	.150
2"	2.375	2.063	.156
2-1/2"	2.875	2.501	.187
3"	3.500	3.062	.219
3-1/2"	4.000	3.500	.250
4"	4.500	4.000	.250
4-1/2"	5.000	4.500	.250
5"	5.563	5.063	.250
6"	6.625	6.125	.250

Allowable Pressure POUNDS PER SQUARE INCH				
Standard Size (Inches)	@ 100° F	@ 200° F	@ 300° F	@ 400° F
1/8"	370	370	320	140
1/4"	870	870	760	330
3/8"	890	890	780	340
1/2"	900	900	790	340
3/4"	810	810	710	310
1"	630	630	560	240
1-1/4"	690	690	610	260
1-1/2"	630	630	560	240
2"	540	540	480	210
2-1/2"	450	450	390	170
3"	510	510	450	190
3-1/2"	570	570	500	220
4"	510	510	440	190
5"	410	410	360	160
6"	340	340	300	130

No-Lead 125LB seamless Threaded Red Brass Nipples - 2200

LEAD FREE

LEAD FREE

LEAD FREE

1/8" - 27

1/8" DIAMETER SCH 40 SEAMLESS

Part #	Size	Box/Case	Approx. Wt. Lbs.	
40-001	Close (3/4")	25/400	0.02	----
40-002	x 1-1/2"	25/400	0.03	----
40-003	x 2"	25/400	0.04	----
40-004	x 2-1/2"	25/400	0.05	----
40-005	x 3"	25/400	0.06	----
40-006	x 3-1/2"	25/400	0.07	----
40-007	x 4"	25/400	0.08	----
40-008	x 4-1/2"	25/400	0.10	----
40-009	x 5"	25/400	0.11	----
40-010	x 5-1/2"	25/400	0.12	----
40-011	x 6"	25/400	0.13	----
40-012	x 7"	25/400	0.15	----
40-013	x 8"	25/400	0.17	----
40-014	x 9"	25/400	0.19	----
40-015	x 10"	25/400	0.21	----
40-017	x 12"	25/400	0.25	----
40-018	x 14"	1/1	0.29	----
40-019	x 16"	1/1	0.34	----

LEAD FREE

1/4"-18

1/4" DIAMETER SCH 40 SEAMLESS

Part #	Size	Box/Case	Approx. Wt. Lbs.	
40-020	Close (7/8")	25/400	0.03	----
40-021	x 1-1/2"	25/400	0.05	----
40-022	x 2"	25/400	0.07	----
40-023	x 2-1/2"	25/400	0.09	----
40-024	x 3"	25/400	0.11	----
40-025	x 3-1/2"	25/400	0.13	----
40-026	x 4"	25/400	0.14	----
40-027	x 4-1/2"	25/400	0.16	----
40-028	x 5"	25/400	0.18	----
40-029	x 5-1/2"	25/400	0.20	----
40-030	x 6"	25/400	0.22	----
40-031	x 7"	25/200	0.25	----
40-032	x 8"	25/200	0.29	----
40-033	x 9"	25/200	0.33	----
40-034	x 10"	25/200	0.36	----
40-035	x 11"	25/200	0.40	----
40-036	x 12"	25/200	0.43	----

See page 7 for Yellow Brass Nipples

LEAD FREE

3/8"-18

3/8" DIAMETER SCH 40 SEAMLESS

Part #	Size	Box/Case	Approx. Wt. Lbs.	
40-040	Close (1")	25/400	0.05	----
40-041	x 1-1/2"	25/400	0.08	----
40-042	x 2"	25/400	0.10	----
40-043	x 2-1/2"	25/400	0.13	----
40-044	x 3"	25/400	0.16	----
40-045	x 3-1/2"	25/400	0.18	----
40-046	x 4"	25/400	0.21	----
40-047	x 4-1/2"	25/300	0.23	----
40-048	x 5"	25/300	0.26	----
40-049	x 5-1/2"	25/300	0.29	----
40-050	x 6"	25/300	0.31	----
40-051	x 7"	25/200	0.36	----
40-052	x 8"	25/150	0.42	----
40-053	x 9"	25/150	0.47	----
40-054	x 10"	25/100	0.52	----
40-055	x 11"	25/100	0.57	----
40-056	x 12"	25/100	0.62	----

LEAD FREE

1/2" - 14

1/2" DIAMETER SCH 40 SEAMLESS

Part #	Size	Box/Case	Approx. Wt. Lbs.	
40-060	Close (1-1/8")	25/400	0.09	----
40-061	x 1-1/2"	25/400	0.12	----
40-062	x 2"	25/400	0.16	----
40-063	x 2-1/2"	25/300	0.20	----
40-064	x 3"	25/300	0.23	----
40-065	x 3-1/2"	25/300	0.27	----
40-066	x 4"	25/200	0.31	----
40-067	x 4-1/2"	25/200	0.35	----
40-068	x 5"	25/200	0.39	----
40-069	x 5-1/2"	25/200	0.43	----
40-070	x 6"	25/200	0.47	----
40-071	x 7"	25/100	0.55	----
40-072	x 8"	25/100	0.62	----
40-073	x 9"	25/100	0.70	----
40-074	x 10"	25/75	0.78	----
40-075	x 11"	25/75	0.86	----
40-076	x 12"	25/75	0.94	----

SCH 40 SEAMLESS | BRASS NIPPLES

LEAD FREE

3/4" - 14

3/4" DIAMETER SCH 40 SEAMLESS

Part #	Length	Box/Case	Approx. Wt. Lbs.	
40-080	Close (1- 3/8")	25/400	0.15	----
40-081	x 1-1/2"	25/400	0.16	----
40-082	x 2"	25/300	0.21	----
40-083	x 2-1/2"	25/300	0.27	----
40-084	x 3"	25/200	0.32	----
40-085	x 3-1/2"	25/200	0.37	----
40-086	x 4"	25/150	0.43	----
40-087	x 4-1/2"	25/150	0.48	----
40-088	x 5"	25/100	0.53	----
40-089	x 5-1/2"	25/100	0.59	----
40-090	x 6"	25/100	0.64	----
40-091	x 7"	25/75	0.75	----
40-092	x 8"	25/75	0.85	----
40-093	x 9"	25/75	0.96	----
40-094	x 10"	25/50	1.06	----
40-095	x 11"	25/50	1.17	----
40-096	x 12"	25/50	1.28	----
40-097	x 18"	1/1	1.92	----
40-098	x 24"	1/1	2.56	----
40-099	x 36"	1/1	3.84	----

LEAD FREE

1" - 11 1/2

1" DIAMETER SCH 40 SEAMLESS

Part #	Length	Box/Case	Approx. Wt. Lbs.	
40-100	Close (1-1/2")	25/200	0.23	----
40-101	x 2"	25/200	0.30	----
40-102	x 2-1/2"	25/150	0.38	----
40-103	x 3"	25/150	0.45	----
40-104	x 3-1/2"	25/100	0.53	----
40-105	x 4"	25/100	0.60	----
40-106	x 4-1/2"	25/100	0.68	----
40-107	x 5"	25/75	0.75	----
40-108	x 5-1/2"	25/75	0.83	----
40-109	x 6"	25/50	0.94	----
40-110	x 7"	25/50	1.05	----
40-111	x 8"	25/50	1.20	----
40-112	x 9"	25/50	1.35	----
40-113	x 10"	25/50	1.50	----
40-114	x 11"	25/50	1.65	----
40-115	x 12"	20/40	1.80	----

LEAD FREE

1 1/4" - 11 1/2

1-1/4" DIAMETER SCH 40 SEAMLESS

Part #	Length	Box/Case	Approx. Wt. Lbs.	
40-120	Close (1-5/8")	25/100	0.36	----
40-121	x 2"	25/100	0.44	----
40-122	x 2-1/2"	25/100	0.56	----
40-123	x 3"	25/100	0.67	----
40-124	x 3-1/2"	25/100	0.78	----
40-125	x 4"	25/50	0.89	----
40-126	x 4-1/2"	25/50	1.00	----
40-127	x 5"	25/50	1.11	----
40-128	x 5-1/2"	25/50	1.22	----
40-129	x 6"	25/50	1.33	----
40-130	x 7"	25/50	1.56	----
40-131	x 8"	25/50	1.78	----
40-132	x 9"	25/50	2.00	----
40-133	x 10"	25/50	2.22	----
40-134	x 11"	25/50	2.45	----
40-135	x 12"	25/50	2.67	----
40-136	x 18"	1/1	4.00	----

LEAD FREE

1-1/2" - 11 1/2

1-1/2" DIAMETER SCH 40 SEAMLESS

Part #	Length	Box/Case	Approx. Wt. Lbs.	
40-140	Close (1-3/4")	25/100	0.46	----
40-141	x 2"	25/100	0.53	----
40-142	x 2-1/2"	25/50	0.66	----
40-143	x 3"	25/50	0.79	----
40-144	x 3-1/2"	25/50	0.93	----
40-145	x 4"	25/50	1.06	----
40-146	x 4-1/2"	25/50	1.19	----
40-147	x 5"	20/40	1.32	----
40-148	x 5-1/2"	20/40	1.46	----
40-149	x 6"	20/40	1.59	----
40-150	x 7"	20/40	1.85	----
40-151	x 8"	20/40	2.12	----
40-152	x 9"	20/40	2.38	----
40-153	x 10"	20/40	2.65	----
40-154	x 11"	1/40	2.91	----
40-155	x 12"	1/15	3.18	----
40-156	x 18"	1/1	4.77	----

SCH 40 SEAMLESS | BRASS NIPPLES

LEAD FREE

2" - 11 1/2

2" DIAMETER SCH 40 SEAMLESS

Part #	Length	Box/Case	Approx. Wt. Lbs.	
40-160	Close (2")	25/50	0.69	----
40-161	x 2-1/2"	25/50	0.86	----
40-162	x 3"	25/50	1.03	----
40-163	x 3-1/2"	25/50	1.20	----
40-164	x 4"	1/25	1.37	----
40-165	x 4-1/2"	1/25	1.54	----
40-166	x 5"	1/25	1.72	----
40-167	x 5-1/2"	1/25	1.89	----
40-168	x 6"	1/25	2.06	----
40-169	x 7"	1/20	2.40	----
40-170	x 8"	1/18	2.74	----
40-171	x 9"	1/18	3.09	----
40-172	x 10"	1/18	3.43	----
40-173	x 11"	1/18	3.77	----
40-174	x 12"	1/14	4.12	----
40-175	x 18"	1/1	6.18	----
40-176	x 24"	1/1	8.24	----
40-178	x 36"	1/1	12.36	----
40-179	x 48"	1/1	16.48	----

LEAD FREE

2 1/2" - 8

2-1/2" DIAMETER SCH 40 SEAMLESS

Part #	Length	Box/Case	Approx. Wt. Lbs.	
40-180	Close (2-1/2")	1/36	1.26	----
40-181	x 3"	1/36	1.51	----
40-182	x 3-1/2"	1/30	1.76	----
40-183	x 4"	1/30	2.02	----
40-184	x 4-1/2"	1/30	2.27	----
40-185	x 5"	1/20	2.52	----
40-186	x 5-1/2"	1/20	2.77	----
40-187	x 6"	1/20	3.03	----

The best way to find yourself is to lose yourself in the service of others.
- Mahatma Gandhi

See our Valve section for 2-1/2, 3 and 4" Valves

LEAD FREE

3" DIAMETER SCH 40 SEAMLESS

Part #	Length	Box/Case	Approx. Wt. Lbs.	
40-200	Close (2-5/8")	1/24	1.89	----
40-201	x 3"	1/20	2.16	----
40-202	x 3-1/2"	1/18	2.52	----
40-203	x 4"	1/18	2.88	----
40-204	x 4-1/2"	1/18	3.24	----
40-205	x 5"	1/18	3.60	----
40-206	x 5-1/2"	1/18	3.96	----
40-207	x 6"	1/12	4.32	----
40-209	x 8"	1/1	5.76	----
40-213	x 12"	1/1		

LEAD FREE

4" DIAMETER SCH 40 SEAMLESS

Part #	Size	Box/Case	Approx. WT. Lbs.	
40-220	Close (2-7/8)	1/20	2.40	----
40-221	x 3"	1/10	2.72	----
40-222	x 3-1/2"	1/10	3.18	----
40-223	x 4"	1/10	3.71	----
40-224	x 4-1/2"	1/5	4.24	----
40-225	x 5"	1/5	4.77	----
40-226	x 5-1/2"	1/5	5.30	----
40-234	x 6"	1/5	6.36	----

LEAD FREE

6" DIAMETER SCH 40 SEAMLESS

Part #	Size	Box/Case	Approx. WT. Lbs.	
40-254	Close	1/1	4.94	----
40-256	x 4"	1/1	6.54	----
40-259	x 4-1/2"	1/1	7.12	----
40-260	x 5"	1/1	7.91	----
40-261	x 6"	1/1	9.49	----

LEAD FREE

3/8" DIAMETER CHROME PLATED

Part #	Size	Box/Case	Approx. Wt. Lbs.	
41-040	X Close	5/25	0.05	----
41-041	x 1-1/2"	5/25	0.08	----
41-042	x 2"	5/25	0.10	----
41-043	x 2-1/2"	5/25	0.13	----
41-044	x 3"	5/25	0.16	----
41-045	x 3-1/2"	5/25	0.18	----
41-046	x 4"	5/25	0.21	----
41-047	x 4-1/2"	5/25	0.23	----
41-048	x 5"	5/25	0.26	----
41-049	x 5-1/2"	5/25	0.29	----
41-050	x 6"	5/25	0.31	----

LEAD FREE

1/2" DIAMETER CHROME PLATED

Part #	Size	Box/Case	Approx. Wt. Lbs.	
41-060	X Close	5/25	0.09	----
41-061	x 1-1/2"	5/25	0.12	----
41-062	x 2"	5/25	0.16	----
41-063	x 2-1/2"	5/25	0.20	----
41-064	x 3"	5/25	0.23	----
41-065	x 3-1/2"	5/25	0.27	----
41-066	x 4"	5/25	0.31	----
41-067	x 4-1/2"	5/25	0.35	----
41-068	x 5"	5/25	0.39	----
41-069	x 5-1/2"	5/25	0.43	----
41-070	x 6"	5/25	0.47	----
41-074	x 10"	1/1	0.78	----

New Nickel Plated Brass Ball Valve with SS trim see page 177

See page 310 for Brass Cam & Groove Fittings

WARNING: This product can expose you to chemicals, including chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

BRONZE FITTINGS

UL842, UL258, UL125,FM

Class 125 (150) For steam, water, gas, oil and air service

Standard specifications

- UL/ FM Approved
- 1S0 9001:2000
- Not Lead Free
- RoHS Compliant

Materials - ASTM B62-93 (85,5,5,5) C83600
Dimensions - ANSI B 16.15
Threads - ANSI B2.1 or BA 21 and Fed. WW-P-460C, MSS-SP-106, ANSI/ASME B1.20.1

Bronze threaded fittings are manufactured from smooth-cored castings, designed to provide full flow with minimum restriction. All threads are accurately machined and gauged to ensure a perfect fit with the pipe. All fittings are individually tested under water to ensure quality. Bronze provides a tighter seal and is easier to install than other metals. Can be used for water, plumbing, heating, pneumatic and marine applications, able to resist the harmful effects of corrosion when coming into contact with salt water or fresh water polluted with mineral acids or peaty soils.

LEAD FREE BRASS FITTINGS

- Approved to ANSI/NSF 61-4 California AB 1953
- Meets Federal State Drinking Water Act, Lead Free Requirement
- Brass fittings conform to AWWA C800
- Brass castings conform to ASTM B584, UNS Alloy C8933
- Brass fittings dimensions conform to ASME B16.15
- NPT threads on all fittings conform to ASME B1.20.1
- Brass unions conform to specification A-A-59617
- Manufacturing facilities are ISO 9001:2008

WARNING: This product can expose you to chemicals, including Nickel, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov



90° ELBOWS

LEAD FREE

Part #		Approx. Wt. Lbs.	Box/Case	Size	A	Approx. Wt. Lbs.	Part #	
44-100	----	0.08	50/600	1/8”	0.55	0.06	44-100LF	----
44-101	----	0.12	35/420	1/4”	0.72	0.10	44-101LF	----
44-102	----	0.17	90/360	3/8”	0.83	0.15	44-102LF	----
44-103	----	0.24	50/200	1/2”	1.03	0.25	44-103LF	----
44-104	----	0.34	35/105	3/4”	1.19	0.41	44-104LF	----
44-105	----	0.61	20/60	1”	1.43	0.69	44-105LF	----
44-106	----	0.95	20/40	1-1/4”	1.71	1.02	44-106LF	----
44-107	----	1.30	15/30	1-1/2”	1.87	1.36	44-107LF	----
44-108	----	2.07	8/16	2”	2.14	2.14	44-108LF	----
44-109	----	3.80	1/12	2-1/2”	2.74	3.79	44-109LF	
44-110	----	4.76	1/4	3”	3.10	5.21	44-110LF	----
44-112	----	9.71	1/2	4”	3.80	8.59		



90° REDUCING ELBOWS

LEAD FREE

Part #		Approx. Wt. Lbs.	Box/Case	Size	A	B	Approx. Wt. Lbs.	Part #	
44-120				1/4" x 1/8"					
44-123	----	0.44	60/240	1/2" x 1/4"	0.93	0.90	0.19		
44-124	----	0.58	60/240	1/2” x 3/8”	0.93	0.90	0.22	44-124LF	----
44-127	----	0.80	40/160	3/4” x 1/2”	1.08	1.11	0.31	44-127LF	----
44-131	----	1.07	50/100	1” x 3/4”	1.30	1.31	0.56	44-131LF	----
44-134	----	0.80	25/50	1-1/4” x 1”	1.52	1.60	0.81	44-134LF	
44-137	----	1.07	10/40	1-1/2” x 1”	1.56	1.72	1.02	44-137LF	----
				2" x 1"				44-140LF	----



90° STREET ELLS

LEAD FREE

Part #		Approx. Wt. Lbs.	Box/Case	Size	A	B	Approx. Wt. Lbs.	Part #	
44-160	----	0.07	60/720	1/8”	0.55	0.92	0.06	44-160LF	----
44-161	----	0.11	35/420	1/4”	0.72	1.11	0.11	44-161LF	----
44-162	----	0.18	60/240	3/8”	0.83	1.24	0.16	44-162LF	----
44-163	----	0.24	60/180	1/2”	1.03	1.51	0.24	44-163LF	----
44-164	----	0.37	35/105	3/4”	1.19	1.66	0.38	44-164LF	----
44-165	----	0.67	45/90	1”	1.43	1.98	0.66	44-165LF	----
44-166	----	1.00	25/50	1-1/4”	1.71	2.26	0.99	44-166LF	----
44-167	----	1.37	9/27	1-1/2”	1.87	2.46	1.15	44-167LF	----
44-168	----	1.93	8/16	2”	2.14	2.98	2.07	44-168LF	----
44-169	----	4.05	5/10	2-1/2”	2.74	3.92	3.79	44-169LF	
44-170	----	6.16	1/8	3”	3.10	4.45	6.38		

WARNING: This product can expose you to chemicals, including Nickel, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov



45° ELBOWS

Part #		Approx. Wt. Lbs.	Box/Case	Size	A	Approx. Wt. Lbs.	Part #	
44-180	----	0.08	50/600	1/8”	0.43	0.05	44-180LF	----
44-181	----	0.13	30/360	1/4”	0.55	0.09	44-181LF	----
44-182	----	0.17	75/300	3/8”	0.63	0.14	44-182LF	----
44-183	----	0.21	50/200	1/2”	0.79	0.19	44-183LF	----
44-184	----	0.32	40/120	3/4”	0.91	0.36	44-184LF	----
44-185	----	0.52	20/60	1”	1.07	0.59	44-185LF	----
44-186	----	0.86	20/40	1-1/4”	1.23	0.87	44-186LF	----
44-187	----	1.10	10/30	1-1/2”	1.31	1.13	44-187LF	----
44-188	----	1.71	12/24	2”	1.47	1.65	44-188LF	----
44-189	----	3.24	1/12	2-1/2"	1.95	2.69		
44-190	----	4.12	1/10	3"	2.17	3.68		



45° STREET ELBOWS

Part #		Approx. Wt. Lbs.	Box/Case	Size	A	B	Approx. Wt. Lbs.	Part #	
44-200	----	0.06	70/840	1/8”	0.26	0.43	0.06		
44-201	----	0.11	100/400	1/4”	0.35	0.56	0.09	44-201LF	----
44-202	----	0.13	100/400	3/8”	0.37	0.63	0.12	44-202LF	----
44-203	----	0.18	75/225	1/2”	0.45	0.79	0.22	44-203LF	----
44-204	----	0.28	40/120	3/4”	0.52	0.91	0.31	44-204LF	----
44-205	----	0.52	25/75	1”	0.60	1.07	0.52	44-205LF	----
44-206	----	0.77	10/40	1-1/4”	0.67	1.23	0.72	44-206LF	----
44-207	----	0.97	10/30	1-1/2”	0.70	1.31	1.05	44-207LF	----
44-208	----	2.04	12/24	2”	0.76	1.47	2.04	44-208LF	----

CROSSES

Part #		Approx. Wt. Lbs.	Box/Case	Size	A	Approx. Wt. Lbs.	Part #	
44-391	----	0.20	60/240	1/4”	0.72	0.15	44-391LF	----
44-392	----	0.15	50/150	3/8”	0.83	0.25	44-392LF	----
44-393	----	0.45	30/90	1/2”	1.03	0.38	44-393LF	----
44-394	----	0.76	20/60	3/4”	1.19	0.59	44-394LF	----
44-395	----	1.04	15/30	1”	1.19	0.94	44-395LF	----
44-396	----	1.63	10/20	1-1/4”	1.71	1.43	44-396LF	----
44-397	----	2.10	8/16	1-1/2”	1.87	1.89	44-397LF	----
44-398	----	3.28	5/10	2”	2.14	2.95	44-398LF	----

WARNING: This product can expose you to chemicals, including Nickel, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov



TEES

Part #		Approx. Wt. Lbs.	Box/Case	Size	A	Approx. Wt. Lbs.	Part #	
44-250	----	0.11	120/480	1/8”	0.55	0.09	44-250LF	----
44-251	----	0.17	75/300	1/4”	0.72	0.13	44-251LF	----
44-252	----	0.25	45/180	3/8”	0.83	0.21	44-252LF	----
44-253	----	0.31	40/120	1/2”	1.03	0.35	44-253LF	----
44-254	----	0.50	35/70	3/4”	1.19	0.55	44-254LF	----
44-255	----	0.85	20/40	1”	1.43	0.92	44-255LF	----
44-256	----	1.29	14/28	1-1/4”	1.71	1.34	44-256LF	----
44-257	----	1.68	12/24	1-1/2”	1.87	1.82	44-257LF	----
44-258	----	2.70	8/16	2”	2.14	2.80	44-258LF	----
44-259	----	5.14	1/6	2-1/2”	2.74	4.70		
44-260	----	7.59	1/6	3”	3.10	6.69		
				4"			44-261LF	



REDUCING TEES
REDUCING ON THE BRANCH

Part #		Approx. Wt. Lbs.	Box/Case	Size (1 & 2) x 3	A	B	Approx. Wt. Lbs.	Part #	
44-276	----	0.24	40/160	1/2” x 1/4”	0.87	0.87	0.28	44-276LF	----
44-280	----	0.46	40/160	1/2" x 3/4"	2.42	1.155	0.48	44-280LF	----
44-282	----	0.43	25/100	3/4” x 1/4”	1.05	1.08	0.38	44-282LF	----
44-283	----	0.45	25/100	3/4” x 3/8”	1.00	1.00	0.46		
44-286	----	0.53	20/80	3/4” x 1/2”	1.08	1.11	0.40	44-286LF	----
44-291	----	0.60	15/60	1” x 1/2”	1.20	1.24	0.73	44-291LF	----
44-298	----	0.80	12/48	1” x 3/4”	1.30	1.31	0.71	44-298LF	----
44-301	----	0.85	20/40	1-1/4” x 1/2”	1.34	1.53	1.18	44-301LF	----
44-303	----	0.90	20/40	1-1/4” x 3/4”	1.30	1.31	1.08	44-303LF	----
44-306	----	1.21	20/40	1-1/4” x 1”	1.58	1.67	1.23	44-306LF	----
				2" x 1"			1.88	44-330LF	----
				2" x 1-1/4"			2.03	44-334LF	----



REDUCING TEES
REDUCING ON THE RUN

Part #		Size 1x2x3	A	B	C	Box/Case	Approx. Wt. Lbs.	Part #	
44-287	----	3/4” x 1/2” x 1/2”	25/100	1.20	1.22	25/100	0.37	44-287LF	----
		3/4" x 1/2" x 3/4"					0.49	44-288LF	----
44-296	----	1” x 3/4” x 3/4”	15/60	1.37	1.45	10/40	0.71		

WARNING: This product can expose you to chemicals, including Nickel, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

COUPLINGS

Part #		Approx. Wt. Lbs.	Box/Case	Size	A	Approx. Wt. Lbs.	Part #	
44-410	----	0.12	70/840	1/8”	0.80	0.06	44-410LF	----
44-411	----	0.11	40/480	1/4”	0.80	0.09	44-411LF	----
44-412	----	0.15	40/480	3/8”	1.05	0.13	44-412LF	----
44-413	----	0.18	60/240	1/2”	1.29	0.21	44-413LF	----
44-414	----	0.28	50/150	3/4”	1.43	0.32	44-414LF	----
44-415	----	0.45	25/100	1”	1.68	0.53	44-415LF	----
44-416	----	0.63	16/64	1-1/4”	1.86	0.73	44-416LF	----
44-417	----	0.82	18/36	1-1/2”	1.92	0.97	44-417LF	----
44-418	----	1.38	12/24	2”	2.20	1.51	44-418LF	----
44-419	----	2.63	1	2-1/2"	2.88	2.20		
44-420	----	3.80	1	3”	3.18	3.63	44-420LF	----

REDUCING COUPLINGS

Part #		Approx. Wt. Lbs.	Box/Case	Size	A	Approx. Wt. Lbs.	Part #	
44-430	----	0.08	70/840	1/4” x 1/8”	0.88	0.08	44-430LF	----
44-431	----	0.11	35/420	3/8” x 1/8”	0.92	0.10	44-431LF	
44-432	----	0.13	30/360	3/8” x 1/4”	0.92	0.11	44-432LF	----
44-433	----	0.16	75/300	1/2” x 1/8”	1.17	0.14		
44-434	----	0.16	75/300	1/2” x 1/4”	1.17	0.16	44-434LF	----
44-435	----	0.18	60/240	1/2” x 3/8”	1.17	0.17	44-435LF	----
44-436	----	0.23	45/180	3/4” x 1/4”	1.35	0.20	44-436LF	----
44-437	----	0.24	45/180	3/4” x 3/8”	1.35	0.23	44-437LF	----
44-438	----	0.23	60/180	3/4” x 1/2”	1.35	0.26	44-438LF	----
44-440	----	0.40	30/120	1” x 3/8”	1.56	0.40		
44-441	----	0.33	30/120	1” x 1/2”	1.56	0.38	44-441LF	----
44-442	----	0.44	25/100	1” x 3/4”	1.56	0.43	44-442LF	----
44-444	----	0.62	25/75	1-1/4” x 1/2”	1.77	0.60	44-444LF	----
44-445	----	0.64	25/75	1-1/4” x 3/4”	1.77	0.57	44-445LF	----
44-446	----	0.54	15/60	1-1/4” x 1”	1.77	0.65	44-446LF	----
44-447	----	0.80	20/60	1-1/2” x 1/2”	1.80	0.77	44-447LF	
44-448	----	0.83	15/60	1-1/2” x 3/4”	1.80	0.74	44-448LF	----
44-449	----	0.68	25/50	1-1/2” x 1”	1.80	0.83	44-449LF	----
44-450	----	0.99	12/48	1-1/2” x 1-1/4”	1.80	0.87	44-450LF	----
44-458	----	1.28	12/36	2” x 1/2”	2.03	1.07		
44-451	----	0.97	12/36	2” x 3/4”	2.03	1.25	44-451LF	----
44-452	----	1.40	12/36	2” x 1”	2.03	1.19	44-452LF	----
44-453	----	1.09	9/27	2” x 1-1/4”	2.03	1.22	44-453LF	----
44-454	----	3.60	9/27	2” x 1-1/2”	2.03	1.28	44-454LF	----
44-461	----	1.26	1	2-1/2” x 1-1/2”	3.15	1.94		
44-462	----	2.29	1	2-1/2” x 2”	3.15	2.37	44-462LF	----
44-456	----	2.49	1	3” x 2”	3.69	2.46		
44-463	----	3.92	1	3” x 2-1/2”	3.69	3.82		

WARNING: This product can expose you to chemicals, including Nickel, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

LEAD FREE

CAPS

Part #		Approx. Wt. Lbs.	Box/Case	Size	A	Approx. Wt. Lbs.	Part #	
44-470	----	0.04	80/160	1/8”	0.53	0.03	44-470LF	----
44-471	----	0.06	80/960	1/4”	0.58	0.06	44-471LF	----
44-472	----	0.10	60/720	3/8”	0.66	0.09	44-472LF	----
44-473	----	0.13	75/300	1/2”	0.75	0.13	44-473LF	----
44-474	----	0.19	40/160	3/4”	0.87	0.21	44-474LF	----
44-475	----	0.30	25/100	1”	1.03	0.35	44-475LF	----
44-476	----	0.51	20/80	1-1/4”	1.10	0.52	44-476LF	----
44-477	----	0.66	18/54	1-1/2”	1.12	0.65	44-477LF	----
44-478	----	1.00	12/36	2”	1.35	1.14	44-478LF	----
44-480	----	2.74	1	3”	1.83	2.64		

LEAD FREE

UNIONS

Part #		Approx. Wt. Lbs.	Box/Case	Size	A	Approx. Wt. Lbs.	Part #	
44-600	----	0.17	40/160	1/8”	1.18	0.13	44-600LF	----
44-601	----	0.25	40/160	1/4”	1.26	0.27	44-601LF	----
44-602	----	0.37	40/160	3/8”	1.50	0.39	44-602LF	----
44-603	----	0.52	50/100	1/2”	1.57	0.44	44-603LF	----
44-604	----	0.78	35/70	3/4”	1.89	0.59	44-604LF	----
44-605	----	1.18	20/40	1”	2.13	0.90	44-605LF	----
44-606	----	1.64	15/30	1-1/4”	2.36	1.33	44-606LF	----
44-607	----	2.08	10/20	1-1/2”	2.68	1.80	44-607LF	----
44-608	----	3.24	6/12	2”	2.99	2.66	44-608LF	----
44-609	----	5.31	4/8	2-1/2”	3.35	4.80		
44-610	----	6.94	4/8	3”	3.74	6.49		

• Straight Thread

HEX LOCKNUTS

Part #	Box/Case	Size	A	Thickness	Approx. Wt. Lbs.	
44-700	180/720	1/8”	0.50	0.19	0.01	----
44-701	90/540	1/4”	0.66	0.25	0.03	----
44-702	90/540	3/8”	0.77	0.28	0.04	----
44-703	90/360	1/2”	0.97	0.31	0.09	----
44-704	90/360	3/4”	1.23	0.34	0.10	----
44-705	50/150	1”	1.50	0.38	0.17	----
44-706	45/180	1-1/4”	1.86	0.42	0.22	----
44-707	45/135	1-1/2”	2.12	0.47	0.29	----
44-708	25/75	2”	2.63	0.53	0.45	----

WARNING: This product can expose you to chemicals, including Nickel, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

Hex

LEAD FREE

HEX BUSHINGS

Part #		Approx. Wt. Lbs.	Box/Case	Size	A	Hex	Approx. Wt. Lbs.	Part #	
44-500	----	0.02	120/1440	1/4" x 1/8"	0.58	0.66	0.03	44-500LF	----
44-501	----	0.06	75/900	3/8" x 1/8"	0.64	0.72	0.06	44-501LF	----
44-502	----	0.04	75/900	3/8" x 1/4"	0.64	0.75	0.04	44-502LF	----
44-503	----	0.10	150/600	1/2" x 1/8"	0.75	0.92	0.09	44-503LF	----
44-504	----	0.09	150/600	1/2" x 1/4"	0.75	0.93	0.10	44-504LF	----
44-505	----	0.08	150/600	1/2" x 3/8"	0.75	0.92	0.08	44-505LF	----
44-506	----	0.17	75/300	3/4" x 1/8"	0.87	1.15	0.17	44-506LF	----
44-507	----	0.15	75/300	3/4" x 1/4"	0.85	1.14	0.18	44-507LF	----
44-508	----	0.14	75/300	3/4" x 3/8"	0.85	1.14	0.17	44-508LF	----
44-509	----	0.14	75/300	3/4" x 1/2"	0.85	1.15	0.14	44-509LF	----
44-510*	----	0.23	50/200	1" x 1/4"	1.05	1.43	0.28	44-510LF*	----
44-511*	----	0.22	50/200	1" x 3/8"	1.05	1.50	0.26	44-511LF	----
44-512	----	0.25	50/200	1" x 1/2"	1.00	1.40	0.30	44-512LF	----
44-513	----	0.21	50/200	1" x 3/4"	1.00	1.43	0.21	44-513LF	----
44-514	----	0.34	30/120	1-1/4" x 1/4"	1.22	1.10	0.34		
44-515	----	0.35	30/120	1-1/4" x 3/8"	1.19	1.84	0.29		
44-516*	----	0.34	30/120	1-1/4" x 1/2"	1.14	1.33	0.39	44-516LF*	----
44-517	----	0.40	30/120	1-1/4" x 3/4"	1.08	1.75	0.43	44-517LF	----
44-518	----	0.33	30/120	1-1/4" x 1"	1.08	1.76	0.42	44-518LF	----
44-519*	----	0.47	25/75	1-1/2" x 1/4"	1.09	2.12	0.29	44-519LF	----
44-520*	----	0.45	25/75	1-1/2" x 3/8"	1.35	2.16	0.44	44-520LF	----
44-521*	----	0.44	25/75	1-1/2" x 1/2"	1.20	2.10	0.51	44-521LF*	----
44-522*	----	0.48	25/75	1-1/2" x 3/4"	1.20	2.12	0.54	44-522LF*	----
44-523	----	0.53	25/75	1-1/2" x 1"	1.14	2.08	0.57	44-523LF	----
44-524	----	0.45	25/75	1-1/2" x 1-1/4"	1.14	2.12	0.46	44-524LF	----
44-527*	----	0.67	20/60	2" x 1/2"	1.27	1.32	1.10	44-527LF	----
44-528*	----	0.74	20/60	2" x 3/4"	1.27	1.62	0.77	44-528LF	----
44-529*	----	0.76	20/60	2" x 1"	1.29	1.95	0.77	44-529LF*	----
44-530	----	0.86	20/60	2" x 1-1/4"	1.22	2.47	0.88	44-530LF	----
44-531	----	0.83	20/60	2" x 1-1/2"	1.22	2.50	0.71	44-531LF	----
44-532	----	1.16	15/30	2-1/2" x 1"	1.53	1.94	1.19		
44-534	----	1.36	15/30	2-1/2" x 1-1/2"	1.50	2.38	1.15	44-534LF	----
44-535	----	1.13	15/30	2-1/2" x 2"	1.43	2.97	1.12	44-535LF	----
44-537	----	1.82	12/24	3" x 1-1/2"	1.61	2.68	2.44		
44-538	----	2.33	12/24	3" x 2"	1.61	3.70	1.82	44-538LF	----
44-539	----	2.19	12/24	3" x 2-1/2"	1.53	3.70	2.11		
44-541	----	3.51	12/24	4" x 2"			3.86		
44-543	----	4.22	12/24	4" x 3"	2.01	4.62	3.56	44-543LF	----

* INSIDE HEX

WARNING: This product can expose you to chemicals, including Nickel, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov



BRONZE COUNTERSUNK PLUGS

Part #	Size	A	Socket Size	Box/Case	Approx. Wt. Lbs.	
44-633	1/2”	0.57	0.43	120/1440	0.06	----
44-634	3/4”	0.58	0.47	70/840	0.11	----
44-635	1”	0.75	0.59	20/240	0.22	----
44-636	1-1/4”	0.74	0.72	40/120	0.33	----
44-637	1-1/2”	0.79	0.72	30/90	0.50	----
44-638	2”	0.80	0.85	20/60	0.88	----
44-639	2-1/2"	1.08	1.25	1/1	1.56	----
44-640	3"	1.13	1.38	1/1	2.47	----
44-641	4"	1.22	2.12	1/1	3.21	----



LEAD FREE

CORED SQUARE HEAD PLUGS

Part #		Approx. Wt. Lbs.	Box/Case	Size	A	B	C	Approx. Wt. Lbs.	Part #	
44-650	----	0.02	300/3600	1/8”	0.27	0.24	0.28	0.02		
44-651	----	0.04	150/1800	1/4”	0.41	0.28	0.37	0.04	44-651LF	----
44-652	----	0.06	100/1200	3/8”	0.41	0.31	0.43	0.06		
44-653	----	0.10	50/600	1/2”	0.54	0.38	0.56	0.10	44-653LF	----
44-654	----	0.13	30/360	3/4”	0.55	0.44	0.62	0.13	44-654LF	----
44-655	----	0.25	20/240	1”	0.69	0.50	0.81	0.22	44-655LF	----
44-656	----	0.39	40/120	1-1/4”	0.71	0.56	0.93	0.32	44-656LF	----
44-657	----	0.57	30/90	1-1/2”	0.73	0.62	1.12	0.47	44-657LF	----
44-658	----	0.77	20/60	2”	0.76	0.68	1.31	0.68	44-658LF	----
44-659	----	1.25	16/32	2-1/2”	1.07	0.74	1.50	1.26		
44-660	----	2.02	16/32	3”	1.13	0.80	1.68	1.49		
44-662	----	3.20	6/12	4”	1.22	0.92	2.25	3.20		



SOLID SQUARE HEAD PLUGS

Part #		Size	A	B	C	Box/Case	Approx. Wt. Lbs.	Part #	
44-670	----	1/8”	0.27	0.24	0.28	400/4800	0.02	44-670LF	----
44-671	----	1/4”	0.41	0.28	0.37	150/1800	0.04	44-671LF	----
44-672	----	3/8”	0.41	0.31	0.43	120/1440	0.06	44-672LF	----
44-673	----	1/2”	0.54	0.38	0.56	50/600	0.12	44-673LF	----
44-674	----	3/4”	0.55	0.44	0.62	35/420	0.18	44-674LF	----
44-675	----	1”	0.69	0.50	0.81	20/240	0.36	44-675LF	----
44-676	----	1-1/4”	0.71	0.56	0.93	30/120	0.63	44-676LF	----
44-677	----	1-1/2”	0.73	0.62	1.12	30/90	0.84	44-677LF	----
44-678	----	2”	0.76	0.68	1.31	10/60	1.27	44-678LF	----

WARNING: This product can expose you to chemicals, including Nickel, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

HEX NIPPLES



Part #	Size	A	Hex	Box/ Case	Approx. Wt. Lbs.	
44-720	1/8”	1.25	0.50	400/4800	0.05	----
44-721	1/4”	1.25	0.61	150/1800	0.06	----
44-722	3/8"	1.55	0.68	120/1440	0.11	----
44-723	1/2”	1.65	1.03	240/480	0.18	----
44-724	3/4”	1.77	1.21	80/320	0.24	----
44-725	1”	2.06	1.46	50/150	0.36	----
44-726	1-1/4”	2.12	1.81	50/100	0.47	----
44-727	1-1/2”	2.25	2.07	35/70	0.76	----
44-728	2”	2.50	2.41	20/40	1.50	----
44-729	2-1/2”	2.80	3.10	1	2.10	----

REDUCING HEX NIPPLES

Part #	Size	Box/Case	Approx. Wt. Lbs.	
44-740	1/4" x 1/8"	1/1	0.06	----
44-742	1/2" x 3/8"	1/1	0.16	----
44-750	1-1/2" x 1"	1/1	0.64	----
44-753	1-1/2" x 1-1/4"	1/1	0.68	----

See page 239 for Stainless Steel Reducing Hex Nipples

CHROME PLATED 90° ELBOW

LEAD FREE

Part #	Size	
45-102LF	3/8"	----
45-103LF	1/2"	----
45-104LF		

CHROME PLATED 90° ELBOW

LEAD FREE

Part #	Size	
45-163LF	1/2"	----

CHROME PLATED TEE

LEAD FREE

Part #	Size	
45-252LF	3/8"	----
45-253LF	1/2"	----

CHROME PLATED COUPLING



LEAD FREE

Part #	Size	
45-412LF	3/8"	----
45-413LF	1/2"	----

WARNING: This product can expose you to chemicals, including chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

CLEANOUT PLUGS/ DROP EAR ELBOWS

• Southern Code

CAST BRASS SQUARE HEAD CLEANOUT PLUG

Part #	Size	Box/Case	
970-300	1-1/2"	100/200	----
970-301	2"	100/200	----
970-302	2-1/2"	50/200	----
970-303	3"	20/160	----
970-304	3-1/2"	20/120	----
970-305	4"	10/80	----
970-330	5"	10/60	----
970-331	6"	10/40	----
970-332	8"	5/20	----
970-333	10"	1/1	----

• Southern Code

CAST BRASS COUNTERSUNK HEAD CLEANOUT PLUG

Part #	Size	Box/Case	
970-306	1-1/2"	100/200	----
970-307	2"	100/200	----
970-308	2-1/2"	100/200	----
970-309	3"	50/200	----
970-310	3-1/2"	20/160	----
970-311	4"	20/120	----
970-312	5"	10/60	----
970-313	6"	10/40	----
970-314	8"	5/20	----

CAST BRASS COUNTERSUNK CLEANOUT W 1/4-20 TAP

Part #	Size	Box/Case	
970-700	1-1/2"	1/1	----
970-701	2"	1/1	----
970-702	2-1/2"	1/1	----
970-703	3"	1/1	----
970-704	3-1/2"	1/1	----
970-705	4"	1/1	----
970-706	5"	1/1	----
970-707	6"	1/1	----

DROP EAR ELBOWS

• Lead Free Brass

• Lead Free Bronze

Part #	Swt x FIP	
44840LF	1/2 x 1/2 Bronze	----
44841LF	1/2 x 1/2 Brass	----
44842LF	3/4 x 1/2 Brass	----
44843LF	3/4 x 3/4 Brass	----

• Lead Free Brass

Part #	Swt x Swt	
44844LF	1/2 x 1/2	----

• Lead Free Bronze

Part #	Pex x FIP	
44845LF	1/2 x 1/2	----

WARNING: This product can expose you to chemicals, including Nickel, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

BRONZE INSERT FITTINGS

150 PSI Genuine red brass - for plastic pipe
• Not Lead Free

HEX MALE ADAPTERS

(Barb x Male Pipe)

Part #	Barb x Male	
973-925	3/4" x 3/4"	----
973-927	1" x 1"	----
973-930	1" x 1-1/4"	----
973-929	1-1/4" x 1"	----
973-928	1-1/4" x 1-1/4"	----
973-948	1-1/2" x 1-1/2"	----
973-949	2" x 2"	----

BRONZE TEES ALL BARB

Part #	Size	
973-965	3/4"	----
973-966	1"	----
973-967	1-1/4"	----

ELBOWS

(Barb x Male Pipe)

Part #	Size	
973-980	3/4" x 3/4"	----
973-981	1" x 3/4"	----
973-982	1" x 1"	----

ELBOWS

(Barb x Barb)

Part #	Hose Size	
973-975	3/4"	----
973-976	1"	----
973-977	1-1/4" x 1"	----
973-978	1-1/4"	----
973-979	1-1/2"	----

STEEL INSERT FITTINGS FOR PLASTIC PIPE

MALE ADAPTER

• Galvanized

(Barb x Male Pipe)

Part #	Size	Box/Case	
973-906	1/2"	25/100	----
973-907	3/4"	25/10	----
973-908	1"	16/48	----
973-909	1-1/4"	12/36	----
973-910	1-1/2"	6/36	----
973-911	2"	5/25	----
973-912	2-1/2"	1/3	----
973-913	3"	1/3	----
973-914	4"	1/3	----

REDUCING ADAPTER

(Insert x NPT)

Part #	Size	
974-264	3/4 x 1/2	----
974-265	1 x 3/4	----
974-266	1-1/4 x 1	----
974-267	1-1/2 x 1-1/4	----

COUPLINGS

Part #	Size	Box/Case	
973-900	1/2	30/120	----
973-901	3/4	20/100	----
973-902	1	20/100	----
973-903	1-1/4	16/64	----
973-904	1-1/2	12/48	----
973-905	2	5/25	----

WARNING: This product can expose you to chemicals, including Nickel, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

SS & LEAD FREE BRONZE INSERT

STAINLESS STEEL #304

#304 INSERT X MALE PIPE

• For coiled plastic pipe to submersible pump

Part #	Size	
973947SS	1/2 x 1/2	----
973925SS	3/4 x 3/4	----
973926SS	1 x 3/4	----
973927SS	1 x 1	----
973930SS	1 x 1-1/4	----
973928SS	1-1/4 x 1-1/4	----
973948SS	1-1/2 x 1-1/2	----
973949SS	2 x 2	----

#304 INSERT X MIP ELBOW

• Hydrant elbow

Part #	Size	
973980SS	3/4 x 3/4	----
973982SS	1 x 1	----
973985SS	1-1/4 x 1-1/4	----

LEAD FREE BRONZE INSERT FITTINGS

INSERT X INSERT

Part #	Size	
973960LF	1/2	----
973961LF	3/4	----
973962LF	1	----
973963LF	1-1/4	----

INSERT TEE

Part #	Size	
973965LF	3/4	----
973966LF	1	----
973967LF	1-1/4	----

BRONZE FITTINGS

INSERT X MALE BRANCH TEE

Part #	Size	
973969LF	3/4	----
973970LF	1 x 3/4	----
973971LF	1	----

INSERT X INSERT ELBOW

Part #	Size	
973975LF	3/4	----
973976LF	1	----

WELL COUPLINGS

304 SS DROP WELL COUPLINGS STANDARD

Part #	Size	
62415DC	1	----
62416DC	1-1/4	----
62417DC	1-1/2	----
62418DC	2	----

HEAVY WALLED SS 304 DROP WELL COUPLINGS

Part #	Size	
62415HDDC	1	----
62416HDDC	1-1/4	----
62417HDDC	1-1/2	----
62418HDDC	2	----

#304 STAINLESS STEEL MERCHANT COUPLINGS

Part #	Size	
61775	1	----
61776	1-1/4	----
61777	1-1/2	----
61778	2	----

WARNING: This product can expose you to chemicals, including chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

STAINLESS STEEL NIPPLES

SCHEDULE 40 WELDED

Stainless steel pipe nipples are manufactured from stainless steel pipe that conforms to specification ASTM A312/ SA312.

All stainless steel nipples conform to specification ASTM A733. Threads conform to the requirements of ANSI B1.20.1.

SCHEDULE 80 SEAMLESS

- **SEAMLESS FOR UNRESTRICTED FLOW**
- **USE WITH AIR, WATER, OIL, NATURAL GAS, STEAM**
- **FITTINGS: USE THREADED CLASS 3000 HIGH-PRESSURE STAINLESS STEEL.**
- **ASTM A733** • **ASTM A312** • **ANSI/ ASME B1.20.1**
- **PSI 3000**

304

The basic alloy. Type 304 (18-8) is an austenitic steel possessing a minimum of 18% chromium and 8% nickel, combined with a maximum of 0.08% carbon. It is a nonmagnetic steel which cannot be hardened by heat treatment, but instead. must be cold worked to obtain higher tensile strengths.

Because of its ability to withstand the corrosive action of various acids found in fruits, meats, milk, and vegetables, Type 304 is especially suited for all types of dairy equipment piping and valves, the brewing industry, the citrus and fruit juice industry, and in food processing applications. Also used for the dye tanks, pipelines buckets, dippers, etc. that come in contact with the lormic, acetic, and other organic acids used in the dyeing industry.

In the marine environment, because of it slightly higher strength and wear resistance than type 316 it is also used for nuts, bolts, screws, and other fasteners. It is also used for springs, cogs, and other components where both wear and corrosion resistance is needed.

Both #304 and #316 nipples are NSF/ANSI 372 and NSF/ANSI 61 compliant.

316

For severe environments. Of course, there are many industrial processes that require a higher level of resistance to corrosion than Type 304 can offer. For these applications, Type 316 is the answer.

In type 316, the nickel content is increased slightly. What distinguishes Type 316 from Type 304 is the addition of molybdenum up to a maximum of 3%.

Molybdenum increases the corrosion resistance of this chromium-nickel alloy to withstand attack by many industrial chemicals and solvents, and, in particular, inhibits pitting caused by chlorides. As such, molybdenum is one of the single most useful alloying additives in the fight against corrosion.

Type 316 can withstand corrosive attack by sodium and calcium brines, hypochlorite solutions, phosphoric acid; and the sulfite liquors and sulfurous acids used in the paper pulp industry. This alloy, therefore, is specified for industrial equipment that handles the corrosive process chemicals used to produce inks, rayons, photographic chemicals, paper, textiles, bleaches, and rubber. Type 316 is also used extensively for surgical implants within the hostile environment of the body.

Type 316 is the main stainless used in the marine environment, with the exception of fasteners and other items where strength and wear resistance are needed, then Type 304 (18-8) is typically used.

SCH 40 STAINLESS STEEL NIPPLES

STAINLESS STEEL

#304 **#316**

1/8" - 27

1/8" DIAMETER
SCH 40 WELDED

Part # 304 S.S.		Length	Box	Approx. Wt. Lbs.	Part # 316 S.S.	
48-001	----	X Close (3/4")	25	0.01	49-001	----
48-002	----	x 1-1/2"	25	0.03	49-002	----
48-003	----	x 2"	25	0.04	49-003	----
48-004	----	x 2-1/2"	25	0.05	49-004	----
48-005	----	x 3"	25	0.06	49-005	----
48-006	----	x 3-1/2"	25	0.07	49-006	----
48-007	----	x 4"	25	0.07	49-007	----
48-008	----	x 4-1/2"	25	0.09	49-008	----
48-009	----	x 5"	25	0.10	49-009	----
48-010	----	x 5-1/2"	25	0.11	49-010	----
48-011	----	x 6"	25	0.12	49-011	----
48-015	----	x 10"	1	0.19		
		x 12"	1	0.24	49-017	----

1/4"-18

1/4" DIAMETER
SCH 40 WELDED

Part # 304 S.S.		Length	Box	Approx. Wt. Lbs.	Part # 316 S.S.	
48-020	----	X Close (7/8")	25	0.02	49-020	----
48-021	----	x 1-1/2"	25	0.04	49-021	----
48-022	----	x 2"	25	0.06	49-022	----
48-023	----	x 2-1/2"	25	0.07	49-023	----
48-024	----	x 3"	25	0.09	49-024	----
48-025	----	x 3-1/2"	25	0.11	49-025	----
48-026	----	x 4"	25	0.13	49-026	----
48-027	----	x 4-1/2"	25	0.14	49-027	----
48-028	----	x 5"	25	0.16	49-028	----
48-029	----	x 5-1/2"	25	0.18	49-029	----
48-030	----	x 6"	25	0.19	49-030	----
48-031	----	x 7"	1	0.22	49-031	----
48-032	----	x 8"	1	0.25	49-032	----
		x 9"	1	0.31	49-033	----
48-034	----	x 10"	1	0.35	49-034	----
		x 11"	1	0.40	49-035	----
48-036	----	x 12"	1	0.44	49-036	----
		x 14"	1	0.46	49-037	----
		x 16"	1	0.47	49-038	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

#304

3/8"-18

3/8" DIAMETER
SCH 40 WELDED

#316

Part # 304 S.S.		Length	Box	Approx. Wt. Lbs.	Part # 316 S.S.	
48-040	----	X Close (1")	25	0.03	49-040	----
48-041	----	x 1-1/2"	25	0.06	49-041	----
48-042	----	x 2"	25	0.07	49-042	----
48-043	----	x 2-1/2"	25	0.10	49-043	----
48-044	----	x 3"	25	0.12	49-044	----
48-045	----	x 3-1/2"	25	0.15	49-045	----
48-046	----	x 4"	25	0.17	49-046	----
48-047	----	x 4-1/2"	25	0.19	49-047	----
48-048	----	x 5"	25	0.22	49-048	----
48-049	----	x 5-1/2"	25	0.23	49-049	----
48-050	----	x 6"	25	0.26	49-050	----
48-052	----	x 8"	1	0.34	49-052	----
48-053	----	x 9"	1			
48-054	----	x 10"	1	0.43	49-054	----
48-056	----	x 12"	1			

1/2" - 14

1/2" DIAMETER
SCH 40 WELDED

Part # 304 S.S.		Length	Box	Approx. Wt. Lbs.	Part # 316 S.S.	
48-060	----	X Close 1-1/8"	25	0.05	49-060	----
48-061	----	x 1-1/2"	25	0.07	49-061	----
48-062	----	x 2"	25	0.10	49-062	----
48-063	----	x 2-1/2"	25	0.14	49-063	----
48-064	----	x 3"	25	0.18	49-064	----
48-065	----	x 3-1/2"	25	0.20	49-065	----
48-066	----	x 4"	25	0.25	49-066	----
48-067	----	x 4-1/2"	25	0.28	49-067	----
48-068	----	x 5"	25	0.31	49-068	----
48-069	----	x 5-1/2"	25	0.34	49-069	----
48-070	----	x 6"	25	0.39	49-070	----
48-071	----	x 7"	1	0.41		
48-072	----	x 8"	1	0.52	49-072	----
48-073	----	x 9"	1	0.54		
48-074	----	10"	1	0.58	49-074	----
48-075	----	x 11"	1	0.64		
48-076	----	x 12"	1	0.69		

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

SCH 40 STAINLESS STEEL NIPPLES

STAINLESS STEEL

#304

3/4" - 14

3/4" DIAMETER
SCH 40 WELDED

#316

Part # 304 S.S.		Length	Box	Approx. Wt. Lbs.	Part # 316 S.S.	
48-080	----	X Close (1-3/8")	25	0.08	49-080	----
48-081	----	x 1-1/2"	25	0.13	49-081	----
48-082	----	x 2"	25	0.14	49-082	----
48-083	----	x 2-1/2"	25	0.17	49-083	----
48-084	----	x 3"	25	0.22	49-084	----
48-085	----	x 3-1/2"	25	0.27	49-085	----
48-086	----	x 4"	25	0.32	49-086	----
48-087	----	x 4-1/2"	25	0.38	49-087	----
48-088	----	x 5"	25	0.40	49-088	----
48-089	----	x 5-1/2"	25	0.42	49-089	----
48-090	----	x 6"	25	0.48	49-090	----
48-091	----	x 7"	1	0.45		
48-092	----	x 8"	1	0.67	49-092	----
48-094	----	x 10"	1	0.94	49-094	----
48-096	----	x 12"	1	1.03		

1" - 11 1/2

1" DIAMETER
SCH 40 WELDED

Part # 304 S.S.		Length	Box	Approx. Wt. Lbs.	Part # 316 S.S.	
48-100	----	X Close (1-1/2")	25	0.13	49-100	----
48-101	----	x 2"	25	0.20	49-101	----
48-102	----	x 2-1/2"	25	0.25	49-102	----
48-103	----	x 3"	25	0.33	49-103	----
48-104	----	x 3-1/2"	25	0.40	49-104	----
48-105	----	x 4"	25	0.47	49-105	----
48-106	----	x 4-1/2"	25	0.53	49-106	----
48-107	----	x 5"	25	0.55	49-107	----
48-108	----	x 5-1/2"	25	0.60	49-108	----
48-109	----	x 6"	25	0.71	49-109	----
48-110	----	x 7"	1	0.57	49-110	----
48-111	----	x 8"	1	1.02	49-111	----
48-113	----	x 10"	1	1.16	49-113	----
48-115	----	x 12"	1	1.31		

1,000# 2 Piece FP #316 Stainless Steel Ball Valve on page 200

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

1 1/4" - 11 1/2

1-1/4" DIAMETER
SCH 40 WELDED

Part # 304 S.S.		Length	Box	Approx. Wt. Lbs.	Part # 316 S.S.	
48-120	----	X Close (1-5/8")	10	0.17	49-120	----
48-121	----	x 2"	10	0.23	49-121	----
48-122	----	x 2-1/2"	10	0.35	49-122	----
48-123	----	x 3"	10	0.46	49-123	----
48-124	----	x 3-1/2"	10	0.52	49-124	----
48-125	----	x 4"	10	0.65	49-125	----
48-126	----	x 4-1/2"	10	0.53	49-126	----
48-127	----	x 5"	10	0.60	49-127	----
48-128	----	x 5-1/2"	10	0.61	49-128	----
48-129	----	x 6"	10	0.71	49-129	----
48-131	----	x 8"	1	1.34		
48-135	----	x 12"	1	1.54		

1-1/2" - 11 1/2

1-1/2" DIAMETER
SCH 40 WELDED

Part # 304 S.S.		Length	Box	Approx. Wt. Lbs.	Part # 316 S.S.	
48-140	----	X Close x 1-3/4"	10	0.25	49-140	----
48-141	----	x 2"	10	0.32	49-141	----
48-142	----	x 2-1/2"	10	0.41	49-142	----
48-143	----	x 3"	10	0.52	49-143	----
48-144	----	x 3-1/2"	10	0.62	49-144	----
48-145	----	x 4"	10	0.73	49-145	----
48-146	----	x 4-1/2"	10	0.86	49-146	----
48-147	----	x 5"	10	0.95	49-147	----
48-148	----	x 5-1/2"	10	1.01	49-148	----
48-149	----	x 6"	10	1.19	49-149	----
48-151	----	x 8"	1	1.63	49-151	----
48-152	----	x 9"	1	1.88		
48-153	----	x 10"	1	2.28	49-153	----
48-155	----	x 12"	1	2.43		

New SS Mini Ball Valves w/Viton O-Ring on page 202

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

SCH 40 STAINLESS STEEL NIPPLES

STAINLESS STEEL

2" DIAMETER
SCH 40 WELDED

Part # 304 S.S.		Length	Box	Approx. Wt. Lbs.	Part # 316 S.S.	
48-160	----	X Close (2")	10	0.37	49-160	----
48-161	----	x 2-1/2"	10	0.54	49-161	----
48-162	----	x 3"	10	0.65	49-162	----
48-163	----	x 3-1/2"	10	0.88	49-163	----
48-164	----	x 4"	10	1.02	49-164	----
48-165	----	x 4-1/2"	10	1.16	49-165	----
48-166	----	x 5"	10	1.29	49-166	----
48-167	----	x 5-1/2"	10	1.46	49-167	----
48-168	----	x 6"	10	1.57	49-168	----
48-169	----	x 7"	1	1.92	49-169	----
48-170	----	x 8"	1	2.01	49-170	----
48-171	----	x 9"	1	2.55		
48-172	----	x 10"	1	2.69		
48-174	----	x 12"	1	2.89		

2-1/2" DIAMETER
SCH 40 WELDED

Part # 304 S.S.	Length	Box	Approx. Wt. Lbs.	
48-180	X Close (2-1/2")	10	0.64	----
48-181	x 3"			
48-187	x 6"	1	2.37	----
48-193	x 12"	1	4.85	----

3" DIAMETER
SCH 40 WELDED

Part # 304 S.S.		Length	Box	Approx. Wt. Lbs.	Part # 316 S.S.	
48-200	----	X Close (2-5/8")	10	0.95	49-200	----
48-201	----	x 3"	10	1.32	49-201	----
48-203	----	x 4"	10	1.66	49-203	----
48-205	----	x 5"	5	1.72	49-205	----
48-207	----	x 6"	5	1.88	49-207	----
48-209	----	x 8"	1	1.91	49-209	----
48-213	----	x 12"	1	2.12	49-213	----

4" DIAMETER
SCH 40 WELDED

Part # 304 S.S.	List Price	Length	Box	Approx. Wt. Lbs.	Part # 316 S.S.	List Price
48-220	----	X Close (2-7/8")	8	1.15	49-220	----
		x 4"	1	2.98	49-223	----
48-227	----	x 6"	1	4.10	49-234	----
		x 8"	1	5.95	49-236	----
		x 12"	1	9.25	49-240	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

150# 304 & 316 Stainless Steel Fittings

Our high quality standard pattern 150lb rated stainless steel threaded fittings are manufactured to the highest standards. All stainless steel fittings are monitored by our quality control personnel for strict compliance with applicable standards and specifications.

These stainless steel pipe fittings are excellent for uses that involve chemicals or liquids that may be corrosive. Along with fighting corrosion, a stainless steel pipe fitting will prevent contamination making it useful to many professionals.

- Use with air, water, oil, natural gas, steam
- NPT and FNPT threads conform to ASME B1.20.1
- Maximum Pressure: 300 psi @ 72 F;150 psi @ 366 F for steam
- Maximum Steam Pressure: 150 psi
- Material Conforms to ASTM A-351. Class 150 Pressure Ratings
- Manufacturing facility is ISO 9001:2008
- 304 Stainless Steel is economically priced, chromium-nickel material that offers very good corrosion resistance. 316 Stainless Steel has higher nickel content and contains molybdenum for even better corrosion resistance.

HIGH PRESSURE 1000# BARSTOCK

1000#

- Stainless bar stock dimensions conform to MSS SP-114
- NPT threads conform to ASME B1.20.1
- Manufacturing facility is ISO 9001:2008
- Fittings meet applicable chemical & physical properties

HIGH PRESSURE 3000# FORGED

A182 and ANSI/ASME B16.11.

3000#

- Use with air, water, oil, natural gas, steam
- Maximum Pressure:

Type 304 SS: 2,570 psi @ 72°F;
1,965 psi @ 350°F for steam

Type 316 SS: 3,000 psi @ 72°F
2810 psi @ 350°F for steam

- Pipe Nipples and Pipe: Use threaded Schedule 80 thickwall stainless steel

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

304 & 316 150# SS FITTINGS

STAINLESS STEEL

90° ELBOW
304 & 316 150#

Part # 304 S.S		Size	Box	Approx. Wt. Lbs.	Part # 316 S.S.	
62-100	----	1/8”	25	0.06	63-100	----
62-101	----	1/4”	25	0.06	63-101	----
62-102	----	3/8”	25	0.11	63-102	----
62-103	----	1/2”	25	0.13	63-103	----
62-104	----	3/4”	25	0.20	63-104	----
62-105	----	1”	10	0.33	63-105	----
62-106	----	1-1/4”	10	0.55	63-106	----
62-107	----	1-1/2”	5	0.77	63-107	----
62-108	----	2”	5	1.10	63-108	----
62-109	----	2-1/2”	1	2.09	63-109	----
62-110	----	3”	1	2.84	63-110	----
62-112	----	4”	1	5.00	63-112	----

90° STREET ELBOW
304 & 316 150#

Part # 304 S.S		Size	Box	Approx. Wt. Lbs.	Part # 316 S.S.	
62-160	----	1/8”	25	0.04	63-160	----
62-161	----	1/4”	25	0.07	63-161	----
62-162	----	3/8”	25	0.09	63-162	----
62-163	----	1/2”	25	0.15	63-163	----
62-164	----	3/4”	25	0.24	63-164	----
62-165	----	1”	10	0.31	63-165	----
62-166	----	1-1/4”	10	0.51	63-166	----
62-167	----	1-1/2”	5	0.84	63-167	----
62-168	----	2”	5	1.26	63-168	----
62-169	----	3"	1	4.16	63-170	----
		4"	1	7.61	63-171	----

45° ELBOW
304 & 316 150#

Part # 304 S.S	List Price	Size	Box	Approx. Wt. Lbs.	Part # 316 S.S.	
62-180	----	1/8”	25	0.04	63-180	----
62-181	----	1/4”	25	0.07	63-181	----
62-182	----	3/8”	25	0.09	63-182	----
62-183	----	1/2”	25	0.13	63-183	----
62-184	----	3/4”	25	0.20	63-184	----
62-185	----	1”	10	0.33	63-185	----
62-186	----	1-1/4”	10	0.49	63-186	----
62-187	----	1-1/2”	5	0.66	63-187	----
62-188	----	2”	5	1.14	63-188	----
62-189	----	2-1/2"	1	2.82		
62-190	----	3"	1	2.91	63-190	----
62-191	----	4"	1	5.05	63-192	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

TEE
304 & 316 150#

Part # 304 S.S		Size	Box	Approx. Wt. Lbs.	Part # 316 S.S.	
62-250	----	1/8”	25	0.07	63-250	----
62-251	----	1/4”	25	0.07	63-251	----
62-252	----	3/8”	25	0.11	63-252	----
62-253	----	1/2”	25	0.20	63-253	----
62-254	----	3/4”	25	0.29	63-254	----
62-255	----	1”	10	0.42	63-255	----
62-256	----	1-1/4”	5	0.66	63-256	----
62-257	----	1-1/2”	5	0.99	63-257	----
62-258	----	2”	3	1.43	63-258	----
62-259	----	2-1/2"	1	1.43		
62-260	----	3”	1	3.66	63-260	----
		4"	1	7.19	63-261	----

CROSS
304 & 316 150#

Part # 304 S.S		Size	Box	Approx. Wt. Lbs.	Part # 316 S.S.	
		1/8”	25	0.06	63-390	----
62-391	----	1/4”	25	0.09	63-391	----
62-392	----	3/8”	25	0.13	63-392	----
62-393	----	1/2”	25	0.29	63-393	----
62-394	----	3/4”	10	0.44	63-394	----
62-395	----	1”	10	0.74	63-395	----
62-396	----	1-1/4”	5	1.25	63-396	----
62-397	----	1-1/2”	5	1.53	63-397	----
62-398	----	2”	1	2.28	63-398	----
		3"	1	5.46	63-400	----
		4"	1	9.41	63-401	----

HEX NIPPLE
304 & 316 150#

Part # 304 S.S	List Price	Size	Box	Approx. Wt. Lbs.	Part # 316 S.S.	List Price
62-720	----	1/8”	1	0.02	63-720	----
62-721	----	1/4”	1	0.04	63-721	----
62-722	----	3/8”	1	0.07	63-722	----
62-723	----	1/2”	1	0.11	63-723	----
62-724	----	3/4”	1	0.18	63-724	----
62-725	----	1”	1	0.22	63-725	----
62-726	----	1-1/4”	1	0.37	63-726	----
62-727	----	1-1/2”	1	0.46	63-727	----
62-728	----	2”	1	0.61	63-728	----

REDUCING HEX NIPPLE
304 & 316 150#

Part # 304 S.S	List Price	Size	Box	Approx. Wt. Lbs.	Part # 316 S.S.	
62-740	----	1/4" x 1/8"	1	0.04	63-740	----
62-741	----	3/8" x 1/8"	1	0.07	63-741	----
62-742	----	3/8" x 1/4"	1	0.07	63-742	----
62-744	----	1/2" x 1/4"	1	0.09	63-744	----
62-745	----	1/2" x 3/8"	1	0.11	63-745	----
62-747	----	3/4" x 1/4"	1	0.15	63-747	----
62-748	----	3/4" x 3/8"	1	0.15	63-748	----
62-749	----	3/4" x 1/2"	1	0.15	63-749	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

304 & 316 150# SS FITTINGS — STAINLESS STEEL

COUPLING
304 & 316 150#

Part # 304 S.S		Size*	Box	Approx. Wt. Lbs.	Part # 316 S.S.	
62-410	----	1/8"	25	0.03	63-410	----
62-411	----	1/4"	25	0.06	63-411	----
62-412	----	3/8"	25	0.07	63-412	----
62-413	----	1/2”	25	0.13	63-413	----
62-414	----	3/4”	25	0.18	63-414	----
62-415	----	1”	25	0.24	63-415	----
62-416	----	1-1/4”	10	0.44	63-416	----
62-417	----	1-1/2”	10	0.51	63-417	----
62-418	----	2”	5	0.79	63-418	----
62-419	----	2-1/2”	1	1.28	63-419	----
62-420	----	3”	1	1.87	63-420	----
62-421	----	4”	1	2.80	63-421	----

REDUCING COUPLING
304 & 316 150#

Part # 304 S.S		Size	Box	Approx. Wt. Lbs.	Part # 316 S.S.	
62-430	----	1/4” x 1/8”	25	0.04	63-430	----
62-431	----	3/8” x 1/8”	25	0.04	63-431	----
62-432	----	3/8” x 1/4”	25	0.04	63-432	----
62-433	----	1/2” x 1/8”	25	0.09	63-433	----
62-434	----	1/2” x 1/4”	25	0.09	63-434	----
62-435	----	1/2” x 3/8”	25	0.09	63-435	----
62-455	----	3/4” x 1/8”	25	0.13	63-455	----
62-436	----	3/4” x 1/4”	25	0.11	63-436	----
62-437	----	3/4” x 3/8”	25	0.13	63-437	----
62-438	----	3/4” x 1/2”	25	0.15	63-438	----
		1" x 1/4"	25	0.25	63-459	----
62-440	----	1” x 3/8”	25	0.22	63-440	----
62-441	----	1” x 1/2”	25	0.24	63-441	----
62-442	----	1” x 3/4”	25	0.24	63-442	----
62-445	----	1-1/4” x 3/4”	10	0.33	63-445	----
62-446	----	1-1/4” x 1”	10	0.35	63-446	----
62-447	----	1-1/2” x 1/2”	10	0.40	63-447	----
62-448	----	1-1/2” x 3/4”	10	0.42	63-448	----
62-449	----	1-1/2” x 1”	10	0.44	63-449	----
62-450	----	1-1/2” x 1-1/4”	10	0.46	63-450	----
62-451		2" x 3/4"				
62-452	----	2” x 1”	5	0.57	63-452	----
62-453	----	2” x 1-1/4”	5	0.62	63-453	----
62-454	----	2” x 1-1/2”	5	0.62	63-454	----
62-428	----	3" x 1"	1	1.82		
62-456	----	3" x 2"	1	2.25		

OD MACHINED COUPLING
304 & 316 150#



Part # 304 S.S	List Price	Size	A	B	Box	Approx. Wt. Lbs.	Part # 316 S.S.	
62-410B	----	1/8”	0.76	0.56	25	0.04	63-410B	----
62-411B	----	1/4”	0.94	0.71	25	0.04	63-411B	----
62-412B	----	3/8”	0.98	0.84	25	0.07	63-412B	----
62-413B	----	1/2”	1.33	1.01	25	0.09	63-413B	----
62-414B	----	3/4”	1.41	1.27	25	0.16	63-414B	----
62-415B	----	1”	1.69	1.54	10	0.21	63-415B	----
62-416B	----	1-1/4”	1.93	1.90	10	0.31	63-416B	----
62-417B	----	1-1/2”	1.93	2.16	5	0.41	63-417B	----
62-418B	----	2”	1.96	2.66	5	0.68	63-418B	----
62-420B	----	3"	3.23	3.76	1			

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

HALF COUPLING
304 & 316 150#



Part # 304 S.S	List Price	Size	A	B	Box	Approx. Wt. Lbs.	Part # 316 S.S.	
62-770		1/8"						
62-771	----	1/4”	0.39	0.70	25	0.02	63-771	----
62-772	----	3/8”	0.45	0.82	25	0.02	63-772	----
62-773	----	1/2”	0.57	1.02	25	0.09	63-773	----
62-774	----	3/4”	0.67	1.22	25	0.11	63-774	----
62-775	----	1”	0.79	1.47	25	0.13	63-775	----
62-776	----	1-1/4”	0.86	1.88	10	0.24	63-776	----
62-777	----	1-1/2”	0.94	2.10	10	0.26	63-777	----
62-778	----	2”	1.06	2.60	5	0.44	63-778	----

UNION
304 & 316 150#

- Stainless Steel Seat

Part # 304 S.S	List Price	Size	Box	Approx. Wt. Lbs.	Part # 316 S.S.	List Price
62-600	----	1/8”	25	0.09	63-600	----
62-601	----	1/4”	25	0.13	63-601	----
62-602	----	3/8”	25	0.22	63-602	----
62-603	----	1/2”	25	0.26	63-603	----
62-604	----	3/4”	25	0.46	63-604	----
62-605	----	1”	10	0.60	63-605	----
62-606	----	1-1/4”	5	0.90	63-606	----
62-607	----	1-1/2”	5	1.10	63-607	----
62-608	----	2”	1	1.81	63-608	----
62-610	----	3”	1	3.40	63-610	----

CAP - CAST
304 & 316 150#

Part # 304 S.S		Size	Box	Approx. Wt. Lbs.	Part # 316 S.S.	
62-470	----	1/8”	25	0.02	63-470	----
62-471	----	1/4”	25	0.02	63-471	----
62-472	----	3/8”	25	0.04	63-472	----
62-473	----	1/2”	25	0.07	63-473	----
62-474	----	3/4”	25	0.11	63-474	----
62-475	----	1”	10	0.18	63-475	----
62-476	----	1-1/4”	10	0.29	63-476	----
62-477	----	1-1/2”	10	0.40	63-477	----
62-478	----	2”	10	0.60	63-478	----
62-480	----	3”	1	1.28	63-480	----
62-481	----	4"	1	1.54		

HEX CAP - BARSTOCK
304 & 316 150#

Part # 304 S.S		Size	Box	Approx. Wt. Lbs.	Part # 316 S.S.	
62-075	----	1/8”	25	0.04	63-075	----
62-076	----	1/4”	25	0.09	63-076	----
62-077	----	3/8”	25	0.11	63-077	----
62-078	----	1/2”	25	0.13	63-078	----
62-079	----	3/4”	25	0.22	63-079	----
62-080	----	1”	10	0.22	63-080	----
62-081	----	1-1/4”	10	0.29	63-081	----
62-082	----	1-1/2”	5	0.40	63-082	----
62-083	----	2”	5	0.49	63-083	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

HEX BUSHING
304 & 316 150#

Part # 304 S.S		Size M x F	Box	Approx. Wt. Lbs.	Part # 316 S.S.	
62-500	----	1/4” x 1/8”	25	0.04	63-500	----
62-501	----	3/8” x 1/8”	25	0.04	63-501	----
62-502	----	3/8” x 1/4”	25	0.04	63-502	----
62-503	----	1/2” x 1/8”	25	0.09		
62-504	----	1/2” x 1/4”	25	0.09	63-504	----
62-505	----	1/2” x 3/8”	25	0.11	63-505	----
62-506	----	3/4" x 1/8"	25	0.13	63-506	----
62-507	----	3/4” x 1/4”	25	0.15	63-507	----
62-508	----	3/4” x 3/8”	25	0.15	63-508	----
62-509	----	3/4” x 1/2”	25	0.15	63-509	----
62-557	----	1" x 1/8"	25	0.27		
62-510	----	1" x 1/4"	25	0.22	63-510	----
62-511	----	1" x 3/8"	25	0.24	63-511	----
62-512	----	1” x 1/2”	25	0.24	63-512	----
62-513	----	1” x 3/4”	25	0.24	63-513	----
62-515	----	1-1/4” x 3/8”	25	0.37		
62-516	----	1-1/4” x 1/2”	25	0.37	63-516	----
62-517	----	1-1/4” x 3/4”	25	0.37	63-517	----
62-518	----	1-1/4” x 1”	25	0.37	63-518	----
62-521	----	1-1/2” x 1/2”	25	0.44	63-521	----
62-522	----	1-1/2” x 3/4”	25	0.46	63-522	----
62-532	----	1-1/2” x 1”	25	0.49	63-523	----
62-524	----	1-1/2” x 1-1/4”	25	0.46	63-524	----
62-559	----	2" x 1/4"	10	0.95		
62-527	----	2” x 1/2”	10	0.66	63-527	----
62-528	----	2” x 3/4”	10	0.66	63-528	----
62-529	----	2” x 1”	10	0.66	63-529	----
62-530	----	2” x 1-1/4”	10	0.68	63-530	----
62-531	----	2” x 1-1/2”	10	0.68	63-531	----
62-536	----	2-1/2" x 1"	5	1.70		
62-534	----	2-1/2” x 1-1/2”	5	1.23	63-534	----
62-535	----	2-1/2” x 2”	5	1.21	63-535	----
		3" x 1"	5	2.20	63-550	----
62-537		3" x 1-1/2"	5	1.97	63-537	----
62-538	----	3” x 2”	5	1.72	63-538	----
62-539	----	3” x 2-1/2”	5	1.81		
		4" x 1-1/2"	5	3.92	63-540	----
		4" x 2"	1	3.72	63-541	----
62-543	----	4” x 3”	1	2.43	63-543	----

- SEE PAGE 13 FOR STAINLESS STEEL BULKHEAD FITTINGS
- SEE PAGE 230 FOR STAINLESS STEEL:
  - BARBED FOR PLASTIC PIPE
  - WELL COUPLINGS
  - MERCHANT COUPLINGS

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

HEX LOCKNUT
304 & 316 150#

• Straight Thread

Part # 304 S.S		Size	Box	Approx. Wt. Lbs.	Part # 316 S.S.	
62-700	----	1/8"	25	0.02		
62-701	----	1/4”	25	0.05	63-701	----
62-702	----	3/8”	25	0.06	63-702	----
62-703	----	1/2”	25	0.07	63-703	----
62-704	----	3/4”	25	0.11	63-704	----
62-705	----	1”	25	0.15	63-705	----
62-706	----	1-1/4”	25	0.22	63-706	----
62-707	----	1-1/2”	25	0.29	63-707	----
62-708	----	2”	10	0.35	63-708	----

CORED SQUARE HEAD PLUG
304 & 316 150#

Part # 304 S.S		Size	Box	Approx. Wt. Lbs.	Part # 316 S.S.	
62-670	----	1/8”	25	0.02	63-670	----
62-671	----	1/4”	25	0.03	63-671	----
62-672	----	3/8”	25	0.04	63-672	----
62-653	----	1/2”	25	0.06	63-653	----
62-654	----	3/4”	25	0.13	63-654	----
62-655	----	1”	25	0.20	63-655	----
62-656	----	1-1/4”	25	0.32	63-656	----
62-657	----	1-1/2”	10	0.41	63-657	----
62-658	----	2”	10	0.65	63-658	----
62-659	----	2-1/2"	1	1.04		
62-660	----	3”	1	0.88		

CORED HEX HEAD PLUG
304 & 316 150#

Part # 304 S.S		Size	Box	Approx. Wt. Lbs.	Part # 316 S.S.	
62-630	----	1/8”	25	0.02	63-630	----
62-631	----	1/4”	25	0.02	63-631	----
62-632	----	3/8”	25	0.04	63-632	----
62-633	----	1/2”	25	0.07	63-633	----
62-634	----	3/4”	25	0.11	63-634	----
62-635	----	1”	25	0.20	63-635	----
62-636	----	1-1/4”	25	0.31	63-636	----
62-637	----	1-1/2”	10	0.44	63-637	----
62-638	----	2”	10	0.65	63-638	----
		4"	1	2.77	63-641	----

HOSE NIPPLE
304 & 316 150#

HOSE BARB X MALE PIPE

Part # 304 S.S		Hose I.D. x Male Pipe	Box	Approx. Wt. Lbs.	Part # 316 S.S.	
73-951	----	1/4”	1	0.04	973-951	----
73-952	----	3/8”	1	0.07	973-952	----
73-953	----	1/2”	1	0.13	973-953	----
73-954	----	3/4”	1	0.20	973-954	----
73-955	----	1”	1	0.33	973-955	----
73-956	----	1-1/4”	1	0.47	973-956	----
73-957	----	1-1/2”	1	0.67	973-957	----
73-958	----	2”	1	0.88	973-958	----
73-959	----	2-1/2”	1	1.45	973-959	----
73-960	----	3”	1	1.94	973-990	----
73-961	----	4”	1	3.57	973-991	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

304 & 316 150# SS FITTINGS — STAINLESS STEEL

REDUCING HOSE NIPPLE
304 150#

HOSE BARB X MALE PIPE

Part # 304 S.S	Hose I.D. x Male Pipe	Box	Approx. Wt. Lbs.	
73-970	1/4" x 1/8"	1	0.04	----
73-971	3/8" x 1/4"	1	0.07	----
73-972	1/2" x 3/8"	1	0.13	----
73-973	1/2" x 1/4"	1	0.13	----
73-974	3/4" x 1/2"	1	0.20	----
73-975	1" x 3/4"	1	0.33	----
73-976	1" x 1/2"	1	0.33	----
73-977	1-1/4" x 1"	1	0.46	----
73-979	1-1/2" x 1-1/4"	1	0.66	----
73-980	1-1/2" x 1"	1	0.66	----
73-981	2" x 1-1/2"	1	0.88	----
73-982	2" x 1-1/4"	1	0.88	----

SOLID HEX HEAD PLUG
316 150#

Part # 316 S.S	Size	Box	Approx. Wt. Lbs.	
63-660	1/8"	25	0.04	----
63-661	1/4"	25	0.06	----
63-662	3/8"	25	0.08	----
63-663	1/2"	25	0.12	----
63-664	3/4"	25	0.15	----
63-665	1"	25	0.24	----

HEX SOCKET PLUG - BARSTOCK
316 150#

Part # 316 S.S	Size	Box	Approx. Wt. Lbs.	
63-759	1/16"	1	0.03	----
63-760	1/8 "	1	0.05	----
63-761	1/4 "	1	0.07	----
63-762	3/8 "	1	0.10	----
63-763	1/2 "	1	0.14	----
63-764	3/4 "	1	0.21	----
63-765	1"	1	0.24	----

SOLID SQUARE HEAD PLUG
316 150#

Part # 316 S.S	Size	Box	Approx. Wt. Lbs.	
63-680	1/8"	25	0.04	----
63-681	1/4"	25	0.04	----
63-682	3/8"	25	0.05	----
63-683	1/2"	25	0.06	----
63-684	3/4"	25	0.12	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

BLACK AND GALVANIZED STEEL NIPPLES

Product Specifications

Welded steel pipe nipples both galvanized and black in diameters ranging from 1/8" up to 4" in lengths from close to 12" and cut-pipe up to 120". -200°-150° Temp Rating.

Technical Specifications

Standards: Product complies with ASTM A-53, A-733 and ANSI B1.20.1 for threading, dimensions and pipe specifications.

Pipe: Complies with ASTM A-53 mill tested schedule 40 and 80 for both Welded & Seamless Meets ANSI B36.1. All pipe is hydrostatic tested.

Galvanized: Zinc coating applied by hot dipped. Galvanized complying with ASTM A-123, NSF approved, RoHS compliant.

Black: Protected against oxidation with varnish coating.

Cutting Procedure: All pipe is roller cut. A visual inspection of seams, excessive galvanizing, mid-welds, poor galvanizing, bends, roundness, under and over weight of the pipe is made at the time it is cut. This is done for every length of pipe. Pipe lengths are cut to a tolerance of + or - 1/16" of the actual length.

Threading Procedure:

All pipe is chaser thread cut to American Standard Tapered Pipe Thread standards. This is 3/4" taper per foot. Pipe is visually inspected for roundness of threads and other visual faults as it is removed from the threading machine.

SCHEDULE 80 XXS SEAMLESS

XXS SEAMLESS

- ASTM A106 Grade B Seamless Pipe
- ASTM A 53
- WWN 351
- Standard NPT Tapered Pipe Threads as per ANSI B 1.20.1 Specification

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

BLACK & GALVANIZED SCH 40 STEEL NIPPLES

1/8" - 27

Wall Thickness 0.068 - GradeB - Test Pressure 700 PSI - Thread Length 0.39

1/8" DIAMETER
SCH 40 WELDED

Part # Galv		Length	Box/Case	Approx. Wt. Lbs.	Part # Black	
56-001	----	X Close (3/4")	50/600	0.02	57-001	----
56-002	----	x 1-1/2"	50/600	0.03	57-002	----
56-003	----	x 2"	50/500	0.04	57-003	----
56-004	----	x 2-1/2"	100/400	0.06	57-004	----
56-005	----	x 3	50/300	0.07	57-005	----
56-006	----	x 3-1/2"	50/300	0.08	57-006	----
56-007	----	x 4"	50/300	0.09	57-007	----
56-008	----	x 4-1/2"	50/300	0.10	57-008	----
56-009	----	x 5"	50/300	0.11	57-009	----
56-010	----	x 5-1/2"	50/300	0.12	57-010	----
56-011	----	x 6"	50/300	0.13	57-011	----
56-012	----	x 7"	50/300	0.15	57-012	----
56-013	----	x 8"	50/300	0.18	57-013	----
56-014	----	x 9"	50/300	0.21	57-014	----
56-015	----	x 10"	50/300	0.25	57-015	----
56-017	----	x 12"	50/300	0.29	57-017	----

1/4"-18

Wall Thickness 0.068 - GradeB - Test Pressure 700 PSI - Thread Length 0.39

1/4" DIAMETER
SCH 40 WELDED

Part # Galv		Length	Box/Case	Approx. Wt. Lbs.	Part # Black	
56-020	----	X Close (7/8")	50/600	0.04	57-020	----
56-021	----	x 1-1/2"	125/500	0.06	57-021	----
56-022	----	x 2"	125/500	0.06	57-022	----
56-023	----	x 2-1/2"	100/400	0.08	57-023	----
56-024	----	x 3	50/300	0.10	57-024	----
56-025	----	x 3-1/2"	50/300	0.12	57-025	----
56-026	----	x 4"	50/300	0.14	57-026	----
56-027	----	x 4-1/2"	50/300	0.17	57-027	----
56-028	----	x 5"	50/300	0.19	57-028	----
56-029	----	x 5-1/2"	50/300	0.21	57-029	----
56-030	----	x 6"	50/300	0.23	57-030	----
56-031	----	x 7"	50/100	0.27	57-031	----
56-032	----	x 8"	50/100	0.31	57-032	----
56-033	----	x 9"	50/100	0.35	57-033	----
56-034	----	x 10"	50/100	0.40	57-034	----
56-035	----	x 11"	50/100	0.44	57-035	----
56-036	----	x 12"	50/100	0.48	57-036	----
56-038	----	x 18"	50/100	0.54		

See page 208 for Standard port 2,000 Carbon Steel Ball Valve

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

STEEL NIPPLES — BLACK & GALVANIZED SCH 40

3/8" DIAMETER
SCH 40 WELDED

Wall Thickness 0.091 - Grade B - Test Pressure 700 PSI - Thread Length 0.6

Part # Galv		Length	Box/Case	Approx. Wt. Lbs.	Part # Black	
56-040	----	X Close (1")	50/600	0.05	57-040	----
56-041	----	x 1-1/2"	125/500	0.07	57-041	----
56-042	----	x 2"	125/500	0.08	57-042	----
56-043	----	x 2-1/2"	100/400	0.11	57-043	----
56-044	----	x 3"	50/300	0.13	57-044	----
56-045	----	x 3-1/2"	50/300	0.16	57-045	----
56-046	----	x 4"	50/300	0.19	57-046	----
56-047	----	x 4-1/2"	50/200	0.21	57-047	----
56-048	----	x 5"	50/150	0.24	57-048	----
56-049	----	x 5-1/2"	50/150	0.27	57-049	----
56-050	----	x 6"	50/100	0.29	57-050	----
56-051	----	x 7"	50/100	0.35	57-051	----
56-052	----	x 8"	50/100	0.40	57-052	----
56-053	----	x 9"	50/100	0.45	57-053	----
56-054	----	x 10"	50/100	0.51	57-054	----
56-055	----	x 11"	50/100	0.56	57-055	----
56-056	----	x 12"	50/100	0.62	57-056	----
56-430	----	x 18"	5/10	0.71	57-430	----
		x 24"	1/1	1.02	57-431	----
		x 36"	1/1	1.54	57-433	----

1/2" DIAMETER
SCH 40 WELDED

Wall Thickness 0.109 - Grade B - Test Pressure 700 PSI - Thread Length 0.78

Part # Galv		Length	Box/Case	Approx. Wt. Lbs.	Part # Black	
56-060	----	X Close (1-1/8")	50/600	0.08	57-060	----
56-061	----	x 1-1/2"	125/500	0.08	57-061	----
56-062	----	x 2"	125/500	0.12	57-062	----
56-063	----	x 2-1/2"	100/400	0.15	57-063	----
56-064	----	x 3"	50/300	0.19	57-064	----
56-065	----	x 3-1/2"	50/300	0.23	57-065	----
56-066	----	x 4"	50/300	0.27	57-066	----
56-067	----	x 4-1/2"	50/200	0.30	57-067	----
56-068	----	x 5"	50/150	0.34	57-068	----
56-069	----	x 5-1/2"	50/150	0.38	57-069	----
56-070	----	x 6"	50/100	0.42	57-070	----
56-071	----	x 7"	50/100	0.49	57-071	----
56-072	----	x 8"	50/100	0.57	57-072	----
56-073	----	x 9"	50/100	0.65	57-073	----
56-074	----	x 10"	50/100	0.72	57-074	----
56-075	----	x 11"	50/100	0.80	57-075	----
56-076	----	x 12"	40/80	0.87	57-076	----
56-240	----	x 18"	1/3	1.29	57-240	----
56-241	----	x 24"	1/3	1.74	57-241	----
56-242	----	x 30"	1/3	2.16	57-242	----
56-243	----	x 36"	1/3	2.61	57-243	----
56-244	----	x 42"	1/3	3.03	57-244	----
56-245	----	x 48"	1/3	3.48	57-245	----
56-246	----	x 60"	1/3	4.35	57-246	----
56-247	----	x 72"	1/3	5.22	57-247	----

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

BLACK & GALVANIZED SCH 40 STEEL NIPPLES

3/4" DIAMETER
SCH 40 WELDED

Wall Thickness 0.113 - Grade B - Test Pressure 700 PSI - Thread Length 0.79

Part # Galv		Length	Box/Case	Approx. Wt. Lbs.	Part # Black	
56-080	----	X Close (1-3/8")	50/300	0.13	57-080	----
56-081	----	x 1-1/2"	125/250	0.10	57-081	----
56-082	----	x 2"	125/250	0.15	57-082	----
56-083	----	x 2-1/2"	50/250	0.20	57-083	----
56-084	----	x 3"	50/200	0.24	57-084	----
56-085	----	x 3-1/2"	50/150	0.29	57-085	----
56-086	----	x 4"	50/150	0.34	57-086	----
56-087	----	x 4-1/2"	50/150	0.39	57-087	----
56-088	----	x 5"	50/150	0.43	57-088	----
56-089	----	x 5-1/2"	60/120	0.48	57-089	----
56-090	----	x 6"	50/100	0.53	57-090	----
56-091	----	x 7"	50/100	0.63	57-091	----
56-092	----	x 8"	50/100	0.72	57-092	----
56-093	----	x 9"	40/80	0.82	57-093	----
56-094	----	x 10"	40/80	0.91	57-094	----
56-095	----	x 11"	30/60	1.01	57-095	----
56-096	----	x 12"	30/60	1.10	57-096	----
56-250	----	x 18"	1/3	1.63	57-250	----
56-251	----	x 24"	1/3	2.20	57-251	----
56-252	----	x 30"	1/3	2.73	57-252	----
56-253	----	x 36"	1/3	3.30	57-253	----
56-254	----	x 42"	1/3	3.83	57-254	----
56-255	----	x 48"	1/3	4.40	57-255	----
56-256	----	x 60"	1/3	5.50	57-256	----
56-257	----	x 72"	1/3	6.60	57-257	----

See page 209 for Full port 2,000# Carbon Steel Ball Valve

Success consists of going from failure to failure without loss of enthusiasm.

- Winston Churchill

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

1" DIAMETER
SCH 40 WELDED

Wall Thickness 0.133 - Grade B - Test Pressure 700 PSI - Thread Length 0.98

Part # Galv		Length	Box/Case	Approx. Wt. Lbs.	Part # Black	
56-100	----	X Close (1-1/2")	50/200	0.16	57-100	----
56-101	----	x 2"	50/150	0.23	57-101	----
56-102	----	x 2-1/2"	50/150	0.29	57-102	----
56-103	----	x 3"	50/100	0.36	57-103	----
56-104	----	x 3-1/2"	50/100	0.43	57-104	----
56-105	----	x 4"	50/100	0.50	57-105	----
56-106	----	x 4-1/2"	50/100	0.56	57-106	----
56-107	----	x 5"	50/100	0.63	57-107	----
56-108	----	x 5-1/2"	50/100	0.70	57-108	----
56-109	----	x 6"	40/80	0.77	57-109	----
56-110	----	x 7"	25/50	0.90	57-110	----
56-111	----	x 8"	25/50	1.03	57-111	----
56-112	----	x 9"	15/30	1.17	57-112	----
56-113	----	x 10"	15/30	1.30	57-113	----
56-114	----	x 11"	15/30	1.44	57-114	----
56-115	----	x 12"	15/30	1.57	57-115	----
56-260	----	x 18"	1/3	2.34	57-260	----
56-261	----	x 24"	1/3	3.14	57-261	----
56-262	----	x 30"	1/3	3.91	57-262	----
56-263	----	x 36"	1/3	4.71	57-263	----
56-264	----	x 42"	1/3	5.48	57-264	----
56-265	----	x 48"	1/3	6.28	57-265	----
56-266	----	x 60"	1/3	7.85	57-266	----
56-267	----	x 72"	1/3	9.42	57-267	----

High Pressure 7,250 psi Full Port Ball Valves - see page 210

An early-morning walk is a blessing for the whole day.

- Henry David Thoreau

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

BLACK & GALVANIZED SCH 40 STEEL NIPPLES

1-1/4" DIAMETER
SCH 40 WELDED

Wall Thickness 0.14 - Grade B - Test Pressure 1300 PSI - Thread Length 1.01

Part # Galv		Length	Box/Case	Approx. Wt. Lbs.	Part # Black	
56-120	----	X Close (1-5/8")	50/100	0.25	57-120	----
56-121	----	x 2"	50/100	0.32	57-121	----
56-122	----	x 2-1/2"	50/100	0.41	57-122	----
56-123	----	x 3"	50/100	0.50	57-123	----
56-124	----	x 3-1/2"	30/60	0.60	57-124	----
56-125	----	x 4"	30/60	0.69	57-125	----
56-126	----	x 4-1/2"	30/60	0.78	57-126	----
56-127	----	x 5"	25/50	0.87	57-127	----
56-128	----	x 5-1/2"	25/50	0.96	57-128	----
56-129	----	x 6"	25/50	1.06	57-129	----
56-130	----	x 7"	15/30	1.24	57-130	----
56-131	----	x 8"	15/30	1.42	57-131	----
56-132	----	x 9"	15/30	1.61	57-132	----
56-133	----	x 10"	15/30	1.79	57-133	----
56-134	----	x 11"	10/20	1.97	57-134	----
56-135	----	x 12"	10/20	2.16	57-135	----
56-270	----	x 18"	1/3	3.22	57-270	----
56-271	----	x 24"	1/3	4.32	57-271	----
56-272	----	x 30"	1/3	3.22	57-272	----
56-273	----	x 36"	1/3	6.48	57-273	----
56-275	----	x 48"			57-275	----

1-1/2" DIAMETER
SCH 40 WELDED

Wall Thickness 0.145 - Grade B - Test Pressure 1300 PSI - Thread Length 1.03

Part # Galv		Length	Box/Case	Approx. Wt. Lbs.	Part # Black	
56-140	----	X Close (1-3/4")	50/100	0.31	57-140	----
56-141	----	x 2"	40/80	0.37	57-141	----
56-142	----	x 2-1/2"	40/80	0.47	57-142	----
56-143	----	x 3"	40/80	0.58	57-143	----
56-144	----	x 3-1/2"	25/50	0.68	57-144	----
56-145	----	x 4"	25/50	0.78	57-145	----
56-146	----	x 4-1/2"	25/50	0.89	57-146	----
56-147	----	x 5"	25/50	1.10	57-147	----
56-148	----	x 5-1/2"	20/40	1.10	57-148	----
56-149	----	x 6"	15/30	1.20	57-149	----
56-150	----	x 7"	15/30	1.41	57-150	----
56-151	----	x 8"	15/30	1.62	57-151	----
56-152	----	x 9"	15/30	1.83	57-152	----
56-153	----	x 10"	1/20	2.04	57-153	----
56-154	----	x 11"	1/20	2.25	57-154	----
56-155	----	x 12"	1/20	2.46	57-155	----
56-280	----	x 18"	1/3	3.66	57-280	----
56-281	----	x 24"	1/3	4.92	57-281	----
56-282	----	x 30"	1/3	6.12	57-282	----
56-283	----	x 36"	1/3	7.38	57-283	----
56-285	----	x 48"	1/3	9.84	57-285	----
		x 60"			57-286	----

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

2" DIAMETER
SCH 40 WELDED

Wall Thickness 0.154 - Grade B - Test Pressure 2500 PSI - Thread Length 1.06

Part # Galv		Length	Box/Case	Approx. Wt. Lbs.	Part # Black	
56-160	----	X Close (2")	40/80	0.55	57-160	----
56-161	----	x 2-1/2"	25/50	0.70	57-161	----
56-162	----	x 3"	25/50	0.86	57-162	----
56-163	----	x 3-1/2"	1/30	1.01	57-163	----
56-164	----	x 4"	1/30	1.16	57-164	----
56-165	----	x 4-1/2"	1/25	1.31	57-165	----
56-166	----	x 5"	1/30	1.47	57-166	----
56-167	----	x 5-1/2"	1/30	1.62	57-167	----
56-168	----	x 6"	1/20	1.77	57-168	----
56-169	----	x 7"	1/20	2.08	57-169	----
56-170	----	x 8"	1/20	2.39	57-170	----
56-171	----	x 9"	1/10	2.70	57-171	----
56-172	----	x 10"	1/10	3.00	57-172	----
56-173	----	x 11"	1/10	3.31	57-173	----
56-174	----	x 12"	1/10	3.62	57-174	----
56-290	----	x 18"	1/3	5.39	57-290	----
56-291	----	x 24"	1/3	5.26	57-291	----
56-292	----	x 30"	1/3	7.03	57-292	----
56-293	----	x 36"	1/3	10.86	57-293	----
56-294	----	x 42"	1/3	12.63	57-294	----
56-295	----	x 48"	1/3	14.48	57-295	----
56-296	----	x 60"	1/3	18.10	57-296	----
56-297	----	x 72"	1/3	18.10	57-297	----

2-1/2" DIAMETER
SCH 40 WELDED

Wall Thickness 0.203 - Grade B - Test Pressure 2500 PSI - Thread Length 1.57

Part # Galv		Length	Box/Case	Approx. Wt. Lbs.	Part # Black	
56-180	----	X Close (2-1/2")	1/20	1.09	57-180	----
56-181	----	x 3"	1/20	1.33	57-181	----
56-182	----	x 3-1/2"	1/20	1.57	57-182	----
56-183	----	x 4"	1/20	1.82	57-183	----
56-184	----	x 4-1/2"	1/20	2.06	57-184	----
56-185	----	x 5"	1/20	2.30	57-185	----
56-186	----	x 5-1/2"	1/10	2.54	57-186	----
56-187	----	x 6"	1/10	2.78	57-187	----
56-188	----	x 7"	1/10	3.27	57-188	----
56-189	----	x 8"	1/10	3.75	57-189	----
56-190	----	x 9"	1/10	4.24	57-190	----
56-191	----	x 10"	1/8	4.72	57-191	----
56-192	----	x 11"	1/8	5.21	57-192	----
56-193	----	x 12"	1/8	5.69	57-193	----

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

BLACK & GALVANIZED SCH 40 STEEL NIPPLES

3" DIAMETER
SCH 40 WELDED

Wall Thickness 0.216 - Grade B - Test Pressure 2500 PSI - Thread Length 1.64

Part # Galv		Length	Box/Case	Approx. Wt. Lbs.	Part # Black	
56-200	----	X Close (2-5/8")	1/20	1.52	57-200	----
56-201	----	x 3"	1/20	1.76	57-201	----
56-202	----	x 3-1/2"	1/10	2.08	57-202	----
56-203	----	x 4"	1/10	2.39	57-203	----
56-204	----	x 4-1/2"	1/10	2.71	57-204	----
56-205	----	x 5"	1/10	3.03	57-205	----
56-206	----	x 5-1/2"	1/10	3.35	57-206	----
56-207	----	x 6"	1/10	3.66	57-207	----
56-208	----	x 7"	1/8	4.30	57-208	----
56-209	----	x 8"	1/8	4.93	57-209	----
56-210	----	x 9"	1/8	5.57	57-210	----
56-211	----	x 10"	1/5	6.20	57-211	----
56-212	----	x 11"	1/5	7.20	57-212	----
56-213	----	x 12"	1/5	7.47	57-213	----
		x 24"	1	14.94	57-311	----

4" DIAMETER
SCH 40 WELDED

Wall Thickness 0.237 - Grade B - Test Pressure 2210 PSI - Thread Length 1.74

Part # Galv		Length	Box/Case	Approx. Wt. Lbs.	Part # Black	
56-220	----	X Close (2-7/8")	1/10	2.00	57-220	----
56-221	----	3-1/2"	1/8	2.21		
56-223	----	x 4"	1/8	3.41	57-223	----
56-224	----	x 4-1/2"	1/6	3.86	57-224	----
56-225	----	x 5"	1/6	4.31	57-225	----
56-226	----	x 5-1/2"	1/6	4.76	57-226	----
56-227	----	x 6"	1/6	5.21	57-227	----
56-330	----	x 7"	1/5	6.48	57-330	----
56-229	----	x 8"	1/5	7.01	57-229	----
56-331	----	x 9"	1/5	7.54	57-331	----
56-332	----	x 10"	1/5	8.14	57-332	----
56-228	----	x 12"	1/4	8.54	57-228	----

The secret of getting ahead is getting started. – Mark Twain

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

6" DIAMETER
SCH 40 WELDED

Wall Thickness 0.154 - Grade B - Test Pressure 2500 PSI - Thread Length 1.06

Part # Galv		Length	Box/Case	Approx. Wt. Lbs.	Part # Black	
56-300	----	X Close (3-1/8")	1/1	3.80	57-300	----
		x 4"	1/1	5.30	57-304	----
		x 6"	1/1	8.30	57-301	----
		x 8"	1/1	11.30	57-305	----
	—	x 10"			57-306	
		x 12"	1/1	17.20	57-308	----

8" DIAMETER
SCH 40 WELDED

Wall Thickness 0.154 - Grade B - Test Pressure 2500 PSI - Thread Length 1.06

Part #	Length	Box/Case	Approx. Wt. Lbs.	
57-320	X Close (3-1/8")	1/1	5.80	----
57-322	x 6"	1/1	6.50	----
57-324	x 8"	1/1	11.30	----
57-326	x 10"	1/1	19.00	----
57-328	x 12"	1/1	28.55	----

STEEL NIPPLE ASSORTMENTS

B "6" ASSORTMENTS

Black		LENGTH											Wt. Lbs.	Total Pieces	
		Close	1-1/2"	2"	2-1/2"	3"	3-1/2"	4"	4-1/2"	5"	5-1/2"	6"			
973-567	1/2"	6	6	6	6	6	6	6	6	6	6	6	20	66	----
973-568	3/4"	6	6	6	6	6	6	6	6	6	6	6	27	66	----
973-569	1"	6		6	6	6	6	6	6	6	6	6	34	60	----

Galv.		LENGTH											Wt. Lbs.	Total Pieces	
		Close	1-1/2"	2"	2-1/2"	3"	3-1/2"	4"	4-1/2"	5"	5-1/2"	6"			
973-667	1/2"	6	6	6	6	6	6	6	6	6	6	6	20	66	----
973-668	3/4"	6	6	6	6	6	6	6	6	6	6	6	27	66	----
973-669	1"	6		6	6	6	6	6	6	6	6	6	34	60	----

STEEL TOTE TRAYS

Part #	Size	Capacity	
990-781	1/2"	77pcs	----
990-782	3/4"	66pcs	----
990-783	1"	50pcs	----
990-786	1-1/4"	40pcs	----
990-784	1-1/2"	30pcs	----
990-785	2"	27pcs	----

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

EXTRA HEAVY SEAMLESS STEEL PIPE NIPPLES

1/8" - 27

1/8" DIAMETER SCHEDULE 80 SEAMLESS

Wall Thickness 0.094 - GradeB - Test Pressure850 PSI - Thread Length 0.39

Part #	Length	Box/Case	Approx. Wt. Lbs.	
59-001SMLS	x Close	40/480	0.02	----
59-002SMLS	x 1-1/2"	40/480	0.03	----
59-003SMLS	x 2"	100/400	0.05	----
59-004SMLS	2-1/2"	100/400	0.06	----
59-005SMLS	x 3"	40/240	0.08	----
59-006SMLS	x 3-1/2"	40/240	0.09	----
59-007SMLS	x 4"	40/240	0.11	----
59-009SMLS	x 5"	40/120	0.12	----
59-010SMLS	x 5-1/2"	40/120	0.13	----
59-011SMLS	x 6"	40/80	0.16	----

1/4"-18

1/4" DIAMETER SCHEDULE 80 SEAMLESS

Wall Thickness 0.119 - Grade B - Test Pressure 850 PSI - Thread Length 0.59

Part #	Length	Box/Case	Approx. Wt. Lbs.	
59-020SMLS	x Close (7/8")	40 / 480	0.03	----
59-021SMLS	x 1-1/2"	100 / 400	0.06	----
59-022SMLS	x 2"	100 / 400	0.08	----
59-023SMLS	x 2-1/2"	80 / 320	0.10	----
59-024SMLS	x 3"	40 / 240	0.12	----
59-025SMLS	x 3-1/2"	40 / 240	0.15	----
59-026SMLS	x 4"	40 / 240	0.17	----
59-027SMLS	x 4-1/2"	40 / 120	0.19	----
59-028SMLS	x 5"	40 / 120	0.21	----
59-029SMLS	x 5-1/2"	40 / 80	0.24	----
59-030SMLS	x 6"	40 / 80	0.26	----
59-031SMLS	x 7"	40 / 80	0.30	----
59-032SMLS	x 8"	40 / 80	0.35	----
59-033SMLS	x 9"	40 / 80	0.39	----
59-034SMLS	x 10"	40 / 80	0.44	----
59-036SMLS	x 12"	40 / 80	0.53	----

5,000# Carbon Steel Check Valves on page 211

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

3/8"-18

3/8" DIAMETER SCHEDULE 80 SEAMLESS

Wall Thickness 0.126 - Grade B - Test Pressure 850 PSI - Thread Length 0.6

Part #	Length	Box/Case	Approx. Wt. Lbs.	
59-040SMLS	X Close (3/8")	40 / 480	0.05	----
59-041SMLS	x 1-1/2"	100 / 400	0.08	----
59-042SMLS	x 2"	100 / 400	0.11	----
59-043SMLS	x 2-1/2"	80 / 320	0.14	----
59-044SMLS	x 3"	40 / 240	0.17	----
59-045SMLS	x 3-1/2"	40 / 240	0.20	----
59-046SMLS	x 4"	40 / 240	0.23	----
59-047SMLS	x 4-1/2"	40 / 160	0.26	----
59-048SMLS	x 5"	40 / 120	0.29	----
59-049SMLS	x 5-1/2"	40 / 120	0.32	----
59-050SMLS	x 6"	40 / 80	0.35	----
59-052SMLS	x 8"	40/80	0.47	----
59-054SMLS	x 10"	40/80	0.53	----
59-056SMLS	x 12"	40/80	0.65	----

1/2" - 14

1/2" DIAMETER SCHEDULE 80 SEAMLESS

Wall Thickness 0.147 - Grade B - Test Pressure 850 PSI - Thread Length 0.78

Part #	Length	Box/Case	Approx. Wt. Lbs.	
59-060SMLS	X Close (1-1/8")	40 / 480	0.07	----
59-061SMLS	x 1-1/2"	100 / 400	0.11	----
59-062SMLS	x 2"	100 / 400	0.15	----
59-063SMLS	x 2-1/2"	80 / 320	0.20	----
59-064SMLS	x 3"	40 / 240	0.24	----
59-065SMLS	x 3-1/2"	40 / 240	0.29	----
59-066SMLS	x 4"	40 / 240	0.33	----
59-067SMLS	x 4-1/2"	40 / 160	0.38	----
59-068SMLS	x 5"	40 / 120	0.42	----
59-069SMLS	x 5-1/2"	40 / 120	0.47	----
59-070SMLS	x 6"	40 / 80	0.51	----
59-071SMLS	x 7"	40 / 80	0.60	----
59-072SMLS	x 8"	40 / 80	0.69	----
59-073SMLS	x 9"	40/80	0.73	----
59-074SMLS	x 10"	40 / 80	0.88	----
59-075SMLS	x 11"	32/64	0.96	----
59-076SMLS	x 12"	32 / 64	1.06	----

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

3/4" - 14

3/4" DIAMETER SCHEDULE 80 SEAMLESS

Wall Thickness 0.154 - Grade B - Test Pressure 850 PSI - Thread Length 0.79

Part #	Length	Box/Case	Approx. Wt. Lbs.	
59-080SMLS	X Close (1-3/8")	40/240	0.13	----
59-081SMLS	x 1-1/2"	100/200	0.15	----
59-082SMLS	x 2"	100/200	0.21	----
59-083SMLS	x 2-1/2"	40/160	0.27	----
59-084SMLS	x 3"	40/160	0.33	----
59-085SMLS	x 3-1/2"	40/120	0.39	----
59-086SMLS	x 4"	40/120	0.45	----
59-087SMLS	x 4-1/2"	40/120	0.51	----
59-088SMLS	x 5"	40/120	0.57	----
59-089SMLS	x 5-1/2"	48/96	0.64	----
59-090SMLS	x 6"	40/80	0.69	----
59-091SMLS	x 7"	40/80	0.82	----
59-092SMLS	x 8"	40/80	0.94	----
59-094SMLS	x 10"	32/64	1.19	----
59-096SMLS	x 12"	24/48	1.44	----

1" - 11 1/2

1" DIAMETER SCHEDULE 80 SEAMLESS

Wall Thickness 0.179 - Grade B - Test Pressure 850 PSI - Thread Length 0.98

Part #	Length	Box/Case	Approx. Wt. Lbs.	
59-100SMLS	X Close (1-1/2")	40 / 160	0.21	----
59-101SMLS	x 2"	40 / 120	0.30	----
59-102SMLS	x 2-1/2"	40 / 120	0.37	----
59-103SMLS	x 3"	40 / 80	0.47	----
59-104SMLS	x 3-1/2"	40 / 80	0.56	----
59-105SMLS	x 4"	40 / 80	0.65	----
59-106SMLS	x 4-1/2"	40 / 80	0.74	----
59-107SMLS	x 5"	40 / 80	0.83	----
59-108SMLS	x 5-1/2"	40 / 80	0.92	----
59-109SMLS	x 6"	32 / 64	1.01	----
59-110SMLS	x 7"	20 / 40	1.19	----
59-111SMLS	x 8"	20 / 40	1.37	----
59-112SMLS	x 9"	20 / 40	1.55	----
59-113SMLS	x 10"	12 / 24	1.74	----
59-114SMLS	x 11"	12 / 24	1.92	----
59-115SMLS	x 12"	12 / 24	2.10	----

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

1-1/4" DIAMETER SCHEDULE 80 SEAMLESS

Wall Thickness 0.191 - Grade B - Test Pressure 1900 PSI - Thread Length 1.01

Part #	Length	Box/Case	Approx. Wt. Lbs.	
59-120SMLS	X Close (1-5/8")	40 / 80	0.31	----
59-121SMLS	x 2"	40 / 80	0.42	----
59-122SMLS	x 2-1/2"	40 / 80	0.52	----
59-123SMLS	x 3"	40 / 80	0.64	----
59-124SMLS	x 3-1/2"	24 / 48	0.77	----
59-125SMLS	x 4"	24 / 48	0.90	----
59-126SMLS	x 4-1/2"	24 / 48	1.02	----
59-127SMLS	x 5"	20 / 40	1.15	----
59-128SMLS	x 5-1/2"	20 / 40	1.27	----
59-129SMLS	x 6"	20 / 40	1.40	----
59-130SMLS	x 7"	20 / 40	1.65	----
59-131SMLS	x 8"	12 / 24	1.90	----
59-132SMLS	x 9"	12 / 24	2.15	----
59-133SMLS	x 10"	12 / 24	2.40	----
59-134SMLS	x 11"	8 / 16	2.65	----
59-135SMLS	x 12"	8 / 16	2.90	----

1-1/2" DIAMETER SCHEDULE 80 SEAMLESS

Wall Thickness 0.2 - Grade B - Test Pressure 1900 PSI - Thread Length 1.03

Part #	Length	Box/Case	Approx. Wt. Lbs.	
59-140SMLS	X Close (1-3/4")	40 / 80	0.41	----
59-141SMLS	x 2"	32 / 64	0.51	----
59-142SMLS	x 2-1/2"	32 / 64	0.64	----
59-143SMLS	x 3"	32 / 64	0.78	----
59-144SMLS	x 3-1/2"	20 / 40	0.94	----
59-145SMLS	x 4"	20 / 40	1.09	----
59-146SMLS	x 4-1/2"	20 / 40	1.23	----
59-147SMLS	x 5"	20 / 40	1.39	----
59-148SMLS	x 5-1/2"	16 / 32	1.54	----
59-149SMLS	x 6"	12 / 24	1.69	----
59-150SMLS	x 7"	12 / 24	2.00	----
59-151SMLS	x 8"	12 / 24	2.30	----
59-152SMLS	x 9"	12 / 24	2.61	----
59-153SMLS	x 10"	8 / 16	2.90	----
59-154SMLS	x 11"	8 / 16	3.20	----
59-155SMLS	x 12"	8 / 16	3.51	----

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

BLACK SCH 80 SEAMLESS — STEEL NIPPLES

2" DIAMETER SCHEDULE 80 SEAMLESS

Wall Thickness 0.218 - Grade B - Test Pressure 2500 PSI - Thread Length 1.06

Part #	Length	Box/Case	Approx. Wt. Lbs.	
59-160SMLS	X Close (2")	32/64	0.30	----
59-161SMLS	x 2-1/2"	20 / 40	0.80	----
59-162SMLS	x 3"	20 / 40	1.10	----
59-163SMLS	x 3-1/2"	12 / 24	1.31	----
59-164SMLS	x 4"	12 / 24	1.52	----
59-165SMLS	x 4-1/2"	12 / 24	1.72	----
59-166SMLS	x 5"	12 / 24	1.94	----
59-167SMLS	x 5-1/2"	12 / 24	2.15	----
59-168SMLS	x 6"	8 / 16	2.35	----
59-169SMLS	x 7"	8 / 16	2.78	----
59-170SMLS	x 8"	8 / 16	3.19	----
59-171SMLS	x 9"	1 / 8	3.62	----
59-172SMLS	x 10"	1 / 8	4.03	----
59-173SMLS	x 11"	1 / 8	4.44	----
59-174SMLS	x 12"	1 / 8	4.87	----
59-196SMLS	x 18"	1/1	7.22	----
59-197SMLS	x 24"	1/1	9.74	----
59-198SMLS	x 36"	1/1	14.61	----
59-199SMLS	x 48"	1/1	19.48	----

2-1/2" DIAMETER SCHEDULE 80 SEAMLESS

Wall Thickness 0.276 - Grade B - Test Pressure 2500 PSI - Thread Length 1.57

Part #	Length	Box/Case	Approx. Wt. Lbs.	
59-180SMLS	x Close (2-1/2")	1 / 16	1.25	----
59-181SMLS	x 3"	1 / 16	1.57	----
59-182SMLS	x 3-1/2"	1 / 16	1.82	----
59-183SMLS	x 4"	1 / 16	2.15	----
59-184SMLS	x 4-1/2"	1 / 16	1.75	----
59-185SMLS	x 5"	1 / 16	2.78	----
59-186SMLS	x 5-1/2"	1 / 8	2.25	----
59-187SMLS	x 6"	1 / 8	3.41	----
59-188SMLS	x 7"	1 / 8	3.89	----
59-189SMLS	x 8"	1 / 8	4.69	----
59-190SMLS	x 9"	1 / 8	5.34	----
59-191SMLS	x 10"	1 / 6	5.97	----
59-192SMLS	x 11"	1 / 6	4.89	----
59-193SMLS	x 12"	1 / 5	7.26	----

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

3" DIAMETER SCHEDULE 80 SEAMLESS

Wall Thickness 0.3 - Grade B - Test Pressure 2500 PSI - Thread Length 1.64

Part #	Length	Box/Case	Approx. Wt. Lbs.	
59-200SMLS	X Close (2-5/8")	1 / 16	1.79	----
59-201SMLS	x 3"	1 / 16	2.11	----
59-202SMLS	x 3-1/2"	1 / 16	2.55	----
59-203SMLS	x 4"	1 / 8	2.89	----
59-204SMLS	x 4-1/2"	1 / 8	3.30	----
59-205SMLS	x 5"	1 / 8	3.73	----
59-206SMLS	x 5-1/2"	1 / 8	4.17	----
59-207SMLS	x 6"	1 / 8	4.57	----
59-208SMLS	x 7"	1 / 6	5.45	----
59-209SMLS	x 8"	1 / 6	6.29	----
59-210SMLS	x 9"	1 / 6	7.17	----
59-211SMLS	x 10"	1 / 4	8.01	----
59-212SMLS	x 11"	1 / 4	8.85	----
59-213SMLS	x 12"	1 / 4	9.72	----

4" DIAMETER SCHEDULE 80 SEAMLESS

Wall Thickness 0.337 - Grade B - Test Pressure 2800 PSI - Thread Length 1.74

Part #	Length	Box/Case	Approx. Wt. Lbs.	
59-220SMLS	X Close (2-7/8")	1 / 8	2.91	----
59-221SMLS	x 4"	1 / 6	4.26	----
59-223SMLS	x 5"	1 / 5	5.49	----
59-224SMLS	x 5-1/2"			
59-225SMLS	x 6"	1 / 5	6.72	----
59-226SMLS	x 7"	1/3	7.33	----
59-227SMLS	x 8"	1 / 3	9.23	----
59-228SMLS	9"			
59-229SMLS	x 10"	1 / 3	11.73	----
59-231SMLS	x 12"	1 / 3	14.24	----

SCHEDULE 80 SEAMLESS

6" DIAMETER

8" DIAMETER

Part #		Length	Box/Case	Approx. Wt. Lbs.		Part #	
				6"	8"		
59-300SMLS	----	X Close	2	3.57	4.62	59-320SMLS	----
59-301SMLS	----	x 6"	2	14.29	16.91	59-322SMLS	----
59-305SMLS	----	x 8"	2	19.05	22.54	59-324SMLS	----
59-306SMLS	----	x 10"	2	23.81	27.47	59-326SMLS	----
59-308SMLS	----	x 12"	2	28.57	34.18	59-328SMLS	----

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

BLACK EXTRA HEAVY XXS SEAMLESS — STEEL NIPPLES

1/2" DIAMETER BLACK EXTRA HEAVY XXS SEAMLESS

Wall Thickness 0.294 - Grade B - Test Pressure 1000 PSI - Thread Length 0.79

Part #	Length	Box/Case	Approx. Wt. Lbs.	
59-060SMLSXX	x Close	100 / 200	0.31	----
59-062SMLSXX	x 2"	100 / 200	0.58	----
59-064SMLSXX	x 3"	50 / 100	0.62	----
59-066SMLSXX	x 4"	50 / 100	0.66	----
59-070SMLSXX	x 6"	25 / 50	0.75	----

3/4" DIAMETER DIAMETER BLACK EXTRA HEAVY XXS SEAMLESS

Wall Thickness 0.308 - Grade B - Test Pressure 1000 PSI - Thread Length 0.79

Part #	Length	Box/Case	Approx. Wt. Lbs.	
59-080SMLSXX	x Close	40/240	0.55	----
59-082SMLSXX	x 2"	50 / 100	0.62	----
59-086SMLSXX	x 4"	25 / 50	0.68	----
59-090SMLSXX	x 6"	25 / 50	0.71	----

1" DIAMETER DIAMETER BLACK EXTRA HEAVY XXS SEAMLESS

Wall Thickness 0.358 - Grade B - Test Pressure 1000 PSI - Thread Length 0.98

Part #	Length	Box/Case	Approx. Wt. Lbs.	
59-100SMLSXX	x close	50 / 100	0.88	----
59-101SMLSXX	x 2"	50 / 100	1.07	----
59-103SMLSXX	x 3"	20/40	1.10	----
59-105SMLSXX	x 4"	20 / 40	1.14	----
59-109SMLSXX	x 6"	20 / 40	1.75	----
59-111SMLSXX	x 8"	1 / 25	1.88	----
59-115SMLSXX	x 12"	1 / 15	2.15	----

2" DIAMETER DIAMETER BLACK EXTRA HEAVY XXS SEAMLESS

Wall Thickness 0.436 - Grade B - Test Pressure 2500 PSI - Thread Length 1.06

Part #	Length	Box/Case	Approx. Wt. Lbs.	
59-160SMLSXX	x close	1 / 25	1.36	----
59-161SMLSXX	x 2-1/2"	1 / 20	1.67	----
59-162SMLSXX	x 3"	1 / 20	2.09	----
59-163SMLSXX	x 3-1/2"	1 / 12	2.51	----
59-164SMLSXX	x 4"	1 / 12	2.86	----
59-166SMLSXX	x 5"	1/12	3.04	----
59-168SMLSXX	x 6"	1 / 11	3.20	----
59-169SMLSXX	x 7"	1 / 8	4.35	----
59-170SMLSXX	x 8"	1 / 8	5.86	----
59-171SMLSXX	x 9"	1 / 8	6.58	----
59-172SMLSXX	x 10"	1 / 8	7.31	----
59-174SMLSXX	x 12"	1 / 8	9.34	----
59-179SMLSXX	x 24"	1 / 1	14.77	----

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

GROOVE NIPPLES — SCH 40 AND SCH 80

THREAD X GROOVE

SCH 40

SCH 80

2" DIAMETER

Part #	List Price	Box	Wtg	Length	Wtg	Box	Part #	
57162TV	----	50	0.70	x 3	1.03	40	59162TV	----
57164TV	----	30	0.97	x 4	1.40	24	59164TV	----
57168TV	----	20	1.64	x 6	2.41	16	59168TV	----
57170TV	----	20	2.15	x 8	3.20	16	59170TV	----
57172TV	----	10	2.80	x 10	3.65	8	59172TV	----
57174TV	----	10	3.45	x 12	4.01	8	59174TV	----

3" DIAMETER

Part #	List Price	Box	Wtg	Length	Wtg	Box	Part #	
57201TV	----	20	1.26	x 3	2.01	16	59201TV	----
57203TV	----	10	1.80	x 4	3.01	8	59203TV	----
57207TV	----	10	3.17	x 6	4.87	8	59207TV	----
57209TV	----	8	4.13	x 8	5.86	6	59209TV	----
57211TV	----	5	5.48	x 10	6.19	4	59211TV	----
57213TV	----	5	6.24	x 12	6.37	4	59213TV	----

4" DIAMETER

Part #	List Price	Box	Wtg	Length	Wtg	Box	Part #	
57222TV	----	8	2.40	x 3	4.11	6	59222TV	----
57223TV	----	8	2.52	x 4	4.15	6	59221TV	----
57227TV	----	6	4.30	x 6	6.52	5	59225TV	----
57229TV	----	4	5.63	x 8	7.18	3	59229TV	----
57332TV	----	4	7.90	x 10	11.74	3	59231TV	----
57228TV	----	4	8.25	x 12	14.24	3	59227TV	----

Nominal IPS Pipe Size	O.D. Actual	Gasket Seat "A"	Groove Width "B"	Groove Diameter "C"	Actual Groove Depth "D"
2	2.375	0.625	0.312	2.250	0.062
3	3.500	0.625	0.312	3.344	0.078
4	4.500	0.625	0.375	4.334	0.083

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

BLACK SCH 40 AND SCH 80 SEAMLESS | GROOVE NIPPLES

GROOVE X GROOVE

SCH 40



SCH 80

2" DIAMETER

Part #		Box	Wtg	Length	Wtg	Box	Part #	
57162V	----	50	0.70	x 3	1.03	40	59162V	----
57164V	----	30	0.97	x 4	1.40	24	59164V	----
57168V	----	20	1.64	x 6	2.41	16	59168V	----
57170V	----	20	2.15	x 8	3.20	16	59170V	----
57172V	----	10	2.80	x 10	3.65	8	59172V	----
57174V	----	10	3.45	x 12	4.01	8	59174V	----

3" DIAMETER

Part #		Box	Wtg	Length	Wtg	Box	Part #	
57201V	----	20	1.26	x 3	2.01	16	59201V	----
57203V	----	10	1.80	x 4	3.01	8	59203V	----
57207V	----	10	3.17	x 6	4.87	8	59207V	----
57209V	----	8	4.13	x 8	5.86	6	59209V	----
57211V	----	5	5.48	x 10	6.19	4	59211V	----
57213V	----	5	6.24	x 12	6.37	4	59213V	----

4" DIAMETER

Part #		Box	Wtg	Length	Wtg	Box	Part #	
57223V	----	8	2.52	x 4	4.15	6	59221V	----
57227V	----	6	4.35	x 6	6.52	5	59225V	----
57229V	----	4	5.63	x 8	7.18	3	59227V	----
57332V	----	4	7.90	x 10	11.74	3	59229V	----
57228V	----	4	8.25	x 12	14.24	3	59231V	----

Nominal IPS Pipe Size	O.D. Actual	Gasket Seat "A"	Groove Width "B"	Groove Diameter "C"	Actual Groove Depth "D"
2	2.375	0.625	0.312	2.250	0.062
3	3.500	0.625	0.312	3.344	0.078
4	4.500	0.625	0.375	4.334	0.083

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer.
For more information, visit www.P65Warnings.ca.gov

Product Specifications
Welded steel couplings both galvanized and black in diameters from 1/8" up to 4".

Technical Specifications
Standards: Product complies with ASTM A865 and ANSI B1.20.1 for threading, dimensions and pipe specifications. Federal Spec WW-P-404
Pipe: Complies with ASTM A-53 milltested schedule 40 and 80. Meets ANSI B36.1. All pipe is hydrostatic tested.
Galvanized: Zinc coating applied by hot dipping. Galvanized complying with ASTM-A-123.

MERCHANT COUPLINGS



• Straight threads thru 2"

Part # Galv		Size	Part # Black	
64-770	----	1/8"	65-770	----
64-771	----	1/4"	65-771	----
64-772	----	3/8"	65-772	----
64-773	----	1/2"	65-773	----
64-774	----	3/4"	65-774	----
64-775	----	1"	65-775	----
64-776	----	1-1/4"	65-776	----
64-777	----	1-1/2"	65-777	----
64-778	----	2"	65-778	----
64-779	----	2-1/2"	65-779	----
64-780	----	3"	65-780	----
64-781	----	4"	65-781	----
		5"	65-782	----
		6"	65-783	----

HALF MERCHANT COUPLINGS

• Straight threads thru 2"

Part # Galv		Size	Part # Black	
		1/8"	65-770H	
		1/4"	65-771H	----
		3/8"	65-772H	----
64-773H	----	1/2"	65-773H	----
64-774H	----	3/4"	65-774H	----
64-775H	----	1"	65-775H	----
64-776H	----	1-1/4"	65-776H	----
64-777H	----	1-1/2"	65-777H	----
64-778H	----	2"	65-778H	----
		2-1/2"	65-779H	----
64-780H	----	3"	65-780H	----
64-781H	----	4"	65-781H	----

#304 STAINLESS STEEL MERCHANT COUPLINGS

Part #	Size	
61775	1	----
61776	1-1/4	----
61777	1-1/2	----
61778	2	----

Also available:
Extra Heavy Merchant Couplings

MERCHANT COUPLINGS SPECIFICATIONS

Size	Outside Diam.	Length Inches	Weight 100 pcs approx. Pounds	Quantity per box	Threads per Inch	Threads Type
1/8"	.59"	.78	3.5	1000	27	Straight
1/4"	.73"	1.18	7.5	500	18	Straight
3/8"	.86"	1.18"	9	600	18	Straight
1/2"	1.063"	1-9/16"	13.0	100	14	Straight
3/4"	1.313"	1-5/8"	28.3	50	14	Straight
1"	1.576"	2"	40.1	30	11-1/2	Straight
1-1/4"	1.900"	2-1/16"	49.5	25	11-1/2	Straight
1-1/2"	2.200"	2-1/16"	71.48	25	11-1/2	Straight
2"	2.750"	2-1/8"	112.0	20	11-1/2	Straight
2-1/2"	3.250"	3-1/8"	231.2	8	8	Taper Tapped
3"	4.000"	3-1/4"	353.8	5	8	Taper Tapped
4"	5.000"	3-1/2"	471.8	4	8	Taper Tapped
6"	7.32	4"	1000.05	4	8	Taper Tapped

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

A105 BLACK STEEL TAPER TAPPED COUPLINGS

Product Specifications

These couplings are manufactured in accordance with American Petroleum Institute specifications 5L & 5B.
All couplings are phosphated.
All sizes are taper tapped 3/4" per foot on the diameter.

*Certified by the American Petroleum Institute

A105
- **Black Steel**
- **API line API SL**

- Each end has a short, unthreaded recess before the threads start.
- Use with sch 80 & sch. 160 nipples & pipe.
- Max. pressure: 300PSI

API LINE PIPE COUPLINGS

Part #	NPT Size	Threads per Inch	Outside Diameter	Length	Unit Weight	
65770API	1/8"	27	0.563	1-1/16	0.04	----
65771API	1/4"	18	0.719	1-5/8	0.10	----
65772API	3/8"	18	0.875	1-5/8	0.13	----
65773API	1/2"	14	1.063	2-1/8	0.24	----
65774API	3/4"	14	1.313	2-1/8	0.35	----
65775API	1"	11.5	1.576	2-5/8	0.52	----
65776API	1-1/4"	11.5	2.054	2-3/4	1.00	----
65777API	1-1/2"	11.5	2.200	2-3/4	0.88	----
65778API	2"	11.5	2.875	2-7/8	1.83	----
65779API	2-1/2"	8	3.375	4-1/8	3.28	----
65780API	3"	8	4.000	4-1/4	4.09	----
65781API	4"	8	5.200	4-1/2	7.59	----
65783API	6"	8	7.390	4-5/8	12.92	----
65784API	8"	8	9.625	5-3/4	23.18	----

I'm sorry, if you were right, I'd agree with you.
- Robin Williams

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer.
For more information, visit www.P65Warnings.ca.gov

MALLEABLE FITTINGS

- Saturated steam pressure 150 PSI @ 350°F
- Max pressure 300 PSI @ 150°F
- Temp range -20°F to 350°F

ISO 9002 - CERTIFICATE OF QUALITY - UL/FM LISTED

Our quality fittings are made with care and attention to detail. With better molds we can reduce parting lines and rough edges resulting in better fluid flow. By using a low temperature galvanizing process the coating is more durable which means a longer lasting fitting. All Fittings are 100% Pressure Tested to 300# Class.

(Every fitting is subjected to an underwater fitness test to ensure the highest quality)

SPECIFICATIONS

- MATERIAL: ASTM A 197 - Cuppla Malleable Iron, ASTM A 153 - Hot dipped galvanizing • Coating ASTM A164 LS
- DIMENSIONS: ANSI B 16.3 - Malleable Iron threaded fittings, ANSI B 16.14 - Ferrous Pipe Plugs, Bushings etc..., ANSI B 16.39 - Malleable Iron threaded pipe unions.
- THREADS: ANSI B 2.1 or BS 21 ASME B1.20.1 • RoHS Compliant • Tapered Threads
- Pressure - Saturated steam 150 PSI @350°F: Max pressure 300 PSI - 150°F
- Temperature range -20 - 350°F

MALLEABLE IRON - ANSI B 16.3

F°	Class 150 PSIG	Sizes 1/4-1 300#	Sizes 1 1/4-2 300#	Sizes 2 1/4-3 300#
-200-150	300	2000	1500	1000
200	265	1785	1350	910
250	225	1575	1200	825
300	185	1360	1050	735
366*	150	1150	900	650

*Permissible for service temperature up to 366°F, reflecting the temperature of saturated steam at 150 psig.

STEEL FITTINGS

- 1010 Carbon Steel, 3/4 taper threads (see hydraulic section for 7/8 taper threads.)
- Finish or coating • Black Dipped in rust resistant
- Galvanized, Zinc Plated (Inside and Out)

300lb MALLEABLE FITTINGS

Max. pressure: 300 psi WOG @ 72°F; 150 psi WOG saturated steam

- Meet ANSI/ ASME B1.20.1 standards
- Black meet ASTM 197 standards

BULL PLUGS AND SWAGES

FLANGES

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

BLACK & GALVANIZED IRON #150 — MALLEABLE FITTINGS

ELBOWS 90°



Part # Galvanized		Size	A	Box/ Case	Approx. Wt. Lbs.	Part # Black	
64-100	----	1/8”	0.69	50/600	0.07	65-100	----
64-101	----	1/4”	0.81	35/420	0.10	65-101	----
64-102	----	3/8”	0.95	90/360	0.16	65-102	----
64-103	----	1/2”	1.12	50/200	0.23	65-103	----
64-104	----	3/4”	1.31	35/105	0.35	65-104	----
64-105	----	1”	1.50	20/60	0.57	65-105	----
64-106	----	1-1/4”	1.75	20/40	0.86	65-106	----
64-107	----	1-1/2”	1.94	15/30	1.31	65-107	----
64-108	----	2”	2.25	8/16	1.79	65-108	----
64-109	----	2-1/2”	2.70	6/12	3.35	65-109	----
64-110	----	3”	3.08	4/8	5	65-110	----
64-112	----	4”	3.79	1/2	9.02	65-112	----
64-114	----	6”	5.13	1/1	23.68	65-114	----
		8"			41.1	65-115	----

REDUCING ELBOWS 90°



Part # Galvanized		Size	A	B	Box/ Case	Approx. Wt. Lbs.	Part # Black	
64-122	----	3/8” x 1/4”	0.88	0.90	90/360	0.16	65-122	----
64-123	----	1/2” x 1/4”	0.97	0.98	60/240	0.21	65-123	----
64-124	----	1/2” x 3/8”	1.04	1.03	60/240	0.24	65-124	----
64-126	----	3/4” x 3/8”	1.12	1.13	40/160	0.31	65-126	----
64-127	----	3/4” x 1/2”	1.20	1.22	40/160	0.44	65-127	----
64-130	----	1” x 1/2”	1.26	1.40	25/100	0.52	65-130	----
64-131	----	1” x 3/4”	1.37	1.45	50/100	0.58	65-131	----
64-133	----	1-1/4” x 3/4”	1.45	1.62	15/120	0.79	65-133	----
64-134	----	1-1/4” x 1”	1.58	1.67	10/40	0.80	65-134	----
64-136	----	1-1/2” x 3/4”	1.52	1.75	10/40	0.88	65-136	----
64-137	----	1-1/2” x 1”	1.65	1.80	10/40	1.07	65-137	----
64-138	----	1-1/2” x 1-1/4”	1.82	1.88	15/30	1.12	65-138	----
64-140	----	2” x 1”	1.73	2.02	14/28	1.41	65-140	----
64-141	----	2” x 1-1/4”	1.90	2.10	10/20	1.53	65-141	----
64-142	----	2” x 1-1/2”	2.02	2.16	10/20	1.65	65-142	----
64-145	----	2-1/2” x 1-1/2”	2.16	2.51	6/12	2.97	65-145	----
64-146	----	2-1/2” x 2”	2.39	2.60	6/12	3.18	65-146	----
64-148	----	3” x 1-1/2”	2.28	2.83	6/18	4.54	65-148	----
		3” x 2-1/2”	2.83	2.99	4/8	4.39	65-151	----
		3" x 2"	2.52	3.60	4/8	4.22	65-150	----

90° STREET ELBOWS



Part # Galvanized		Size	A	B	Box/ Case	Approx. Wt. Lbs.	Part # Black	
64-160	----	1/8”	0.69	1.00	60/720	.06	65-160	----
64-161	----	1/4”	0.80	1.17	35/420	.10	65-161	----
64-162	----	3/8”	0.95	1.48	40/240	.15	65-162	----
64-163	----	1/2”	1.10	1.59	60/180	.22	65-163	----
64-164	----	3/4”	1.28	1.85	35/105	.39	65-164	----
64-165	----	1”	1.47	2.10	35/105	.60	65-165	----
64-166	----	1-1/4”	1.75	2.57	25/50	.95	65-166	----
64-167	----	1-1/2”	1.90	2.63	9/27	1.37	65-167	----
64-168	----	2”	2.21	3.19	8/16	2.25	65-168	----
64-169	----	2-1/2”	2.65	3.78	5/10	3.32	65-169	----
64-170	----	3”	3.02	4.42	4/8	5.27	65-170	----
64-171	----	4”	3.72	5.57	2/4	8.94	65-171	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

ELBOWS 45°



Part # Galvanized		Size	A	Box/ Case	Approx. Wt. Lbs.	Part # Black	
64-180	----	1/8”	0.63	50/600	.07	65-180	----
64-181	----	1/4”	0.73	30/360	.10	65-181	----
64-182	----	3/8”	0.80	75/300	.14	65-182	----
64-183	----	1/2”	0.88	50/200	.21	65-183	----
64-184	----	3/4”	0.98	40/120	.33	65-184	----
64-185	----	1”	1.12	20/60	.50	65-185	----
64-186	----	1-1/4”	1.29	20/40	.74	65-186	----
64-187	----	1-1/2”	1.43	10/30	1.01	65-187	----
64-188	----	2”	1.68	12/24	1.53	65-188	----
64-189	----	2-1/2”	1.95	9/18	2.78	65-189	----
64-190	----	3”	2.17	1/10	4.49	65-190	----
64-191	----	4”	2.61	2/4	7.44	65-191	----
64-192	----	6”	3.46	1/1	18.63	65-192	----
		8"			26.40	65-194	----

45° STREET ELBOWS



Part # Galvanized		Size	A	B	Box/ Case	Approx. Wt. Lbs.	Part # Black	
64-200	----	1/8”	0.63	0.83	70/840	.05	65-200	----
64-201	----	1/4”	0.73	0.94	40/480	.09	65-201	----
64-202	----	3/8”	0.80	1.03	100/400	.14	65-202	----
64-203	----	1/2”	0.86	1.30	75/225	.19	65-203	----
64-204	----	3/4”	0.96	1.48	40/120	.28	65-204	----
64-205	----	1”	1.10	1.69	25/75	.48	65-205	----
64-206	----	1-1/4”	1.26	1.87	10/40	.71	65-206	----
64-207	----	1-1/2”	1.40	2.05	10/30	1.02	65-207	----
64-208	----	2”	1.65	2.38	12/24	1.68	65-208	----
64-209	----	2-1/2”	1.95	2.72	6/12	2.69	65-209	----
64-210	----	3”	2.17	3.16	3/6	4.61	65-210	----
64-211	----	4”	2.61	3.90	2/4	7.74	65-211	----

CROSSES



Part # Galvanized		Size	A	Box/ Case	Approx. Wt. Lbs.	Part # Black	
64-390	----	1/8”	0.65	50/600	.14	65-390	----
64-391	----	1/4”	0.80	60/240	.17	65-391	----
64-392	----	3/8”	0.95	50/150	.26	65-392	----
64-393	----	1/2”	1.12	30/90	.42	65-393	----
64-394	----	3/4”	1.31	20/60	.64	65-394	----
64-395	----	1”	1.50	15/30	.98	65-395	----
64-396	----	1-1/4”	1.75	10/20	1.45	65-396	----
64-397	----	1-1/2”	1.94	8/16	1.90	65-397	----
64-398	----	2”	2.25	5/10	2.96	65-398	----
64-399	----	2-1/2”	2.71	4/8	5.49	65-399	----
64-400	----	3”	3.06	2/4	7.71	65-400	----
		4"		1/1	14.77	65-401	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

BLACK & GALVANIZED IRON #150 — MALLEABLE FITTINGS

TEES



Part # Galvanized		Size	A	Box/Case	Approx. Wt. Lbs.	Part # Black	
64-250	----	1/8”	0.69	120/480	.11	65-250	----
64-251	----	1/4”	0.81	75/300	.15	65-251	----
64-252	----	3/8”	0.95	45/180	.22	65-252	----
64-253	----	1/2”	1.12	40/120	.36	65-253	----
64-254	----	3/4”	1.31	35/70	.48	65-254	----
64-255	----	1”	1.50	20/40	.83	65-255	----
64-256	----	1-1/4”	1.75	14/28	1.29	65-256	----
64-257	----	1-1/2”	1.94	12/24	1.66	65-257	----
64-258	----	2”	2.26	8/16	2.50	65-258	----
64-259	----	2-1/2”	2.70	4/8	4.45	65-259	----
64-260	----	3”	3.08	1/6	6.72	65-260	----
64-261	----	4”	3.79	1/2	11.31	65-261	----
64-262	----	6”	5.13	1/1	30.75	65-262	----
		8"			37.85	65-264	----

REDUCING TEES

(SAME SIZE ON RUN, REDUCING ON BRANCH)



Part # Galvanized		Size (1&2) x 3	A	B	Box/ Case	Approx. Wt. Lbs.	Part # Black	
64-273	----	3/8” x 1/4”	0.81	0.90	25/300	.18	65-273	----
64-276	----	1/2” x 1/4”	0.97	0.98	40/160	.24	65-276	----
64-279	----	1/2” x 3/8”	1.04	1.03	40/160	.35	65-279	----
64-282	----	3/4” x 1/4”	1.05	1.08	25/100	.43	65-282	----
64-283	----	3/4” x 3/8”	1.12	1.13	25/100	.39	65-283	----
64-286	----	3/4” x 1/2”	1.20	1.18	20/80	.49	65-286	----
64-268	----	1” x 1/4”	1.11	1.22	20/80	.51	65-268	----
64-269	----	1” x 3/8”	1.18	1.27	15/60	.55	65-269	----
64-291	----	1” x 1/2”	1.26	1.40	15/60	.63	65-291	----
64-298	----	1” x 3/4”	1.37	1.45	12/48	.71	65-298	----
64-301	----	1-1/4” x 1/2”	1.34	1.45	20/40	.91	65-301	----
64-303	----	1-1/4” x 3/4”	1.45	1.62	20/40	.99	65-303	----
64-306	----	1-1/4” x 1”	1.58	1.66	20/40	1.07	65-306	----
64-721		1-1/2" x 1/2"				1.12	65-721	----
64-316	----	1-1/2” x 3/4”	1.41	1.75	15/30	1.23	65-316	----
64-318	----	1-1/2” x 1”	1.65	1.88	10/30	1.33	65-318	----
64-322	----	1-1/2” x 1-1/4”	1.65	1.88	12/24	1.52	65-322	----
64-327	----	2” x 1/2”	1.49	1.88	10/20	1.64	65-327	----
64-328	----	2” x 3/4”	1.60	1.97	10/20	1.71	65-328	----
64-330	----	2” x 1”	1.73	2.02	10/20	1.88	65-330	----
64-334	----	2” x 1-1/4”	1.86	2.06	8/16	2.03	65-334	----
64-336	----	2” x 1-1/2”	1.98	2.12	8/16	2.22	65-336	----
		2-1/2" x 1"				2.85	65-342	----
64-343	----	2-1/2” x 1-1/2”	2.16	2.51	5/10	2.97	65-343	----
64-729	----	3" x 1"	2.00	2.00	3/6	4.15		
		3" x 1-1/2"				5.19	65-359	----
64-351	----	3” x 2”	2.52	2.89	3/6	5.35	65-351	----

Quick Disconnects - see pages 348-355

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

BULLHEAD TEES



Part #		Size (1&2) x 3	A	B	Box/ Case	Approx. Wt. Lbs.	Part # Black	
64-280	----	1/2" x 3/4"	1.22	1.20	30/120	.4	65-280	----
64-733	----	1/2" x 1"	1.36	1.26	25/100	.50	65-733	----
64-289	----	3/4" x 1"	1.45	1.37	20/120	.60	65-289	----
64-299	----	1" x 1-1/4"	1.67	1.58	15/30	.96	65-299	----
64-300	----	1" x 1-1/2"	1.80	1.65	9/36	1.11	65-300	----
64-317	----	1-1/4" x 1-1/2"	1.88	1.82	12/24	1.07	65-317	----
64-319	----	1-1/2" x 2"	2.12	1.98	8/32	2.10	65-319	----

REDUCING TEES
REDUCING ON RUN



Part # Black	Size 1 x 2 x 3	A	B	C	Box/Case	Approx. Wt. Lbs.	
65-287	3/4" x 1/2" x 1/2"	1.18	1.18	1.20	25/100	0.39	----
65-288	3/4" x 1/2" x 3/4"	1.28	1.20	1.28	20/80	0.49	----
65-292	1" x 1/2" x 1/2"	1.31	1.22	1.31	20/80	0.51	----
65-293	1" x 1/2" x 3/4"	1.22	1.37	1.45	20/80	0.53	----
65-294	1" x 1/2" x 1"	1.40	1.50	1.50	15/60	0.54	----
65-295	1" x 3/4" x 1/2"	1.20	1.26	1.40	20/80	0.58	----
65-296	1" x 3/4" x 3/4"	1.34	1.28	1.42	15/60	0.63	----
65-297	1" x 3/4" x 1"	1.45	1.50	1.50	15/60	0.62	----
65-347	1-1/4" x 3/4" x 3/4"	1.31	1.45	1.64	10/40	0.66	----
65-305	1-1/4" x 3/4" x 1-1/4"	1.62	1.75	1.75	10/40	1.14	----
65-309	1-1/4" x 1"x 1"	1.55	1.47	1.63	20/40	1.00	----
65-346	1-1/4" x 3/4" x 1/2"	1.31	1.45	1.64	20/40	1.05	----
65-349	1-1/4" x 1" x 1/2"	1.26	1.34	1.53	20/40	1.10	----
65-350	1-1/4" x 1" x 3/4"						
65-310	1-1/4" x 1" x 1-1/4"	1.30	1.36	1.44	15/30	1.21	----
65-372	1-1/2" x 1" x 1"	1.50	1.65	1.78	15/30	1.28	----
65-375	1-1/2" x 1-1/4" x 3/4"	1.43	1.52	1.25	15/30	1.30	----
65-377	1-1/2" x 1-1/4" x 1-1/4"	1.75	1.82	1.88	15/30	1.35	----
65-267	2" x 3/4" x 2"						
65-312	2" x 1-1/2" x 1-1/4"	1.82	1.90	2.10	10/30	1.21	----
65-313	2" x 1-1/2" x 1-1/2"	1.94	2.02	2.16	10/30	1.79	----

MALLEABLE SERVICE TEE (STREET TEE)



Part # Galvanized		Size	A	B	Box/ Case	Approx. Wt. Lbs.	Part # Black	
64-363	----	1/2"	1.12	1.62	40/12	0.31	65-363	----
64-364	----	3/4"	1.31	1.89	25/75	0.49	65-364	----

SIDE OUTLET TEES



Part # Galvanized		Size	A	Box/ Case	Approx. Wt. Lbs.	Part # Black	
64-383	----	1/2"	1.12	25/100	.39	65-383	----
64-384	----	3/4"	1.31	15/60	.58	65-384	----
64-385	----	1"	1.50	20/40	.88	65-385	----
64-386	----	1-1/4"	1.75	12/24	1.32	65-386	----
		1-1/2"	1.97	1/1	1.56	65-387	----
		2"	2.29	1/1	1.81	65-388	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

BLACK & GALVANIZED IRON #150 — MALLEABLE FITTINGS

COUPLINGS

Part # Galvanized		Size	A	Box/ Case	Approx. Wt. Lbs.	Part # Black	
64-410	----	1/8”	0.96	70/840	.07	65-410	----
64-411	----	1/4”	1.06	40/480	.09	65-411	----
64-412	----	3/8”	1.16	40/480	.13	65-412	----
64-413	----	1/2”	1.34	60/240	.19	65-413	----
64-414	----	3/4”	1.52	50/150	.28	65-414	----
64-415	----	1”	1.67	25/100	.45	65-415	----
64-416	----	1-1/4”	1.93	16/64	.66	65-416	----
64-417	----	1-1/2”	2.15	18/36	.84	65-417	----
64-418	----	2”	2.54	12/24	1.39	65-418	----
64-419	----	2-1/2”	2.88	8/16	2.42	65-419	----
64-420	----	3”	3.18	1/12	3.49	65-420	----
64-421	----	4”	3.69	3/6	5.81	65-421	----
64-422	----	6”	4.23	1/2	28.62	65-422	----

REDUCING COUPLINGS

Part # Galvanized		Size	A	Box/ Case	Approx. Wt. Lbs.	Part # Black	
64-430	----	1/4” x 1/8”	1.00	50/600	.07	65-430	----
64-431	----	3/8” x 1/8”	1.13	35/420	.09	65-431	----
64-432	----	3/8” x 1/4”	1.13	30/360	.11	65-432	----
64-433	----	1/2” x 1/8”	1.25	75/300	.13	65-433	----
64-434	----	1/2” x 1/4”	1.25	75/300	.11	65-434	----
64-435	----	1/2” x 3/8”	1.25	60/240	.15	65-435	----
64-439	----	3/4” x 1/8”	1.44	60/240	.18	65-439	----
64-436	----	3/4” x 1/4”	1.44	45/18	.19	65-436	----
64-437	----	3/4” x 3/8”	1.44	45/18	.21	65-437	----
64-438	----	3/4” x 1/2”	1.44	60/180	.25	65-438	----
64-459	----	1” x 1/4”	1.69	45/135	.34	65-459	----
64-440	----	1” x 3/8”	1.69	30/120	.35	65-440	----
64-441	----	1” x 1/2”	1.69	30/120	.36	65-441	----
64-442	----	1” x 3/4”	1.69	25/100	.39	65-442	----
64-460	----	1-1/4” x 3/8”	2.06	25/75	.55	65-460	----
64-444	----	1-1/4” x 1/2”	2.06	25/75	.53	65-444	----
64-445	----	1-1/4” x 3/4”	2.06	25/75	.57	65-445	----
64-446	----	1-1/4” x 1”	2.06	15/60	.61	65-446	----
64-443	----	1-1/2” x 3/8”	2.31	20/60	.71	65-443	----
64-447	----	1-1/2” x 1/2”	2.31	20/60	.69	65-447	----
64-448	----	1-1/2” x 3/4”	2.31	15/60	.71	65-448	----
64-449	----	1-1/2” x 1”	2.31	25/50	.78	65-449	----
64-450	----	1-1/2” x 1-1/4”	2.31	12/48	.87	65-450	----
64-458	----	2” x 1/2”	2.81	12/36	1.14	65-458	----
64-451	----	2” x 3/4”	2.81	12/36	1.14	65-451	----
64-452	----	2” x 1”	2.81	12/36	1.21	65-452	----
64-453	----	2” x 1-1/4”	2.81	9/27	1.19	65-453	----
64-454	----	2” x 1-1/2”	2.81	9/27	1.38	65-454	----
64-461	----	2-1/2” x 1-1/2”	3.25	20/40	2.07	65-461	----
64-462	----	2-1/2” x 2”	3.25	7/14	2.23	65-462	----
64-486	----	3” x 1-1/2”	3.69	6/12	3.23	65-486	----
64-456	----	3” x 2”	3.69	6/12	3.30	65-456	----
64-463	----	3” x 2-1/2”	3.69	5/10	3.55	65-463	----
64-464	----	4” x 2”	4.38	3/6	5.55	65-464	----
64-465	----	4” x 2-1/2”	4.38	3/6	5.90	65-465	----
64-457	----	4” x 3”	4.38	3/6	6.05	65-457	----
		6” x 4”	4.24	1/2	10.86	65-491	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

HEX BUSHING

* INSIDE HEX

Part # Galvanized		Size M x F	A	Hex	Box/ Case	Approx. Wt. Lbs.	Part # Black	
64-500	----	*1/4" x 1/8"	0.79	0.67	1/25	.03	65-500	----
64-501	----	*3/8" x 1/8"	0.79	0.75	1/25	.06	65-501	----
64-502	----	*3/8" x 1/4"	0.79	0.75	1/25	.05	65-502	----
64-503	----	1/2" x 1/8"	0.84	1.03	150/600	.09	65-503	----
64-504	----	1/2" x 1/4"				.08	65-504	----
64-505	----	1/2" x 3/8"	0.75	1.03	150/600	.07	65-505	----
64-506	----	3/4" x 1/8"	0.85	1.15	75/300	.14	65-506	----
64-507	----	3/4" x 1/4"	0.85	1.15	75/300	.13	65-507	----
64-508	----	3/4" x 3/8"	0.85	1.15	75/300	.12	65-508	----
64-509	----	3/4" x 1/2"	0.93	1.15	75/300	.10	65-509	----
64-510*	----	1" x 1/4"	1.13	1.12	50/200	.20	65-510*	----
64-511*	----	1" x 3/8"	1.13	1.12	50/200	.18	65-511*	----
64-512	----	1" x 1/2"	1.10	1.42	50/200	.21	65-512	----
64-513	----	1" x 3/4"	1.10	1.42	50/200	.17	65-513	----
64-514*	----	1-1/4" x 1/4"	1.24	1.12	30/120	.29	65-514*	----
64-515*	----	1-1/4" x 3/8"	1.24	1.12	30/120	.29	65-515*	----
64-516*	----	1-1/4" x 1/2"	1.24	1.24	30/120	.31	65-516*	----
64-517	----	1-1/4" x 3/4"	1.08	1.76	30/120	.35	65-517	----
64-518	----	1-1/4" x 1"	1.08	1.76	30/120	.29	65-518	----
64-519*	----	1-1/2" x 1/4"	1.30	1.12	25/75	.40	65-519*	----
64-520*	----	1-1/2" x 3/8"	1.30	1.12	25/75	.38	65-520*	----
64-521*	----	1-1/2" x 1/2"	1.30	1.34	25/75	.38	65-521*	----
64-522*	----	1-1/2" x 3/4"	1.30	1.44	25/75	.40	65-522*	----
64-523	----	1-1/2" x 1"	1.23	2.00	25/75	.45	65-523	----
64-524	----	1-1/2" x 1-1/4"	1.23	2.00	25/75	.34	65-524	----
64-526	----	2" x 1/4"	1.29	1.12	20/60	.57	65-526	----
64-525*	----	2" x 3/8"	1.28	1.12	20/60	.57	65-525*	----
64-527*	----	2" x 1/2"	1.39	1.34	20/60	.57	65-527*	----
64-528*	----	2" x 3/4"	1.39	1.63	20/60	.63	65-528*	----
64-529*	----	2" x 1"	1.39	1.77	20/60	.66	65-529*	----
64-530	----	2" x 1-1/4"	1.50	2.48	20/60	.74	65-530	----
64-531	----	2" x 1-1/2"	1.50	2.48	20/60	.61	65-531	----
64-546*	----	2-1/2" x 1/2"	1.51	1.34	15/30	.97	65-546*	----
64-547*	----	2-1/2" x 3/4"	1.51	1.63	15/30	.91	65-547*	----
64-532*	----	2-1/2" x 1"	1.51	1.95	15/30	.97	65-532*	----
64-533*	----	2-1/2" x 1-1/4"	1.51	2.39	15/30	1.03	65-533*	----
64-534	----	2-1/2" x 1-1/2"	1.51	2.98	15/30	1.16	65-534	----
64-535	----	2-1/2" x 2"	1.54	2.98	15/30	1.01	65-535	----
64-550	----	3" x 1"	1.61	1.95	12/24	1.41	65-550	----
64-549*	----	3" x 1-1/4"	1.61	2.39	12/24	1.42	65-549*	----
64-537*	----	3" x 1-1/2"	1.61	2.68	12/24	1.51	65-537*	----
64-538	----	3" x 2"	1.61	3.86	12/24	1.71	65-538	----
64-539	----	3" x 2-1/2"	1.61	3.86	12/24	1.68	65-539	----
		3-1/2" x 3"	1.86	4.20	5/10	2.17	65-555	----
64-551	----	4" x 3/4"	2.15	4.90	5/10	3.88	65-551	----
64-553*	----	4" x 1"	2.00	4.75	5/10	3.79	65-553*	----
64-552	----	4" x 1-1/4"	1.82	2.39	5/10	2.39	65-552	----
64-540	----	4" x 1-1/2"	1.82	2.68	5/10	2.39	65-540	----
64-541*	----	4" x 2"	1.82	3.31	5/10	2.52	65-541*	----
64-542*	----	4" x 2-1/2"	2.06	3.87	5/10	2.87	65-542*	----
64-543	----	4" x 3"	2.17	4.96	5/10	2.95	65-543	----
		5" x 4"	2.16	5.34	2/4	6.80	65-544	----
64-545*	----	6" x 4"	2.33	5.79	2/4	7.11	65-545*	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

UNIONS

• Brass Seat

Part # Galvanized		Size	A	Box/ Case	Approx. Wt. Lbs.	Part # Black	
64-600	----	1/8”	1.26	60/240	.17	65-600	----
64-601	----	1/4”	1.44	20/240	.25	65-601	----
64-602	----	3/8”	1.61	40/160	.37	65-602	----
64-603	----	1/2”	1.72	50/100	.52	65-603	----
64-604	----	3/4”	1.94	35/70	.78	65-604	----
64-605	----	1”	2.06	20/40	1.18	65-605	----
64-606	----	1-1/4”	2.26	15/30	1.64	65-606	----
64-607	----	1-1/2”	2.41	10/20	2.08	65-607	----
64-608	----	2”	2.75	6/12	3.24	65-608	----
64-609	----	2-1/2”	3.22	4/8	5.31	65-609	----
64-610	----	3”	3.50	4/8	6.94	65-610	----
64-611	----	4”	3.85	2/4	12.02	65-611	----

SQUARE HEAD PLUGS



• Cored

Part # Galvanized		Size	A	B	C	Box/ Case	Approx. Wt. Lbs.	Part # Black	
		*1/8"	0.41	0.23	0.30	1/25	.02	65-650	----
64-651	----	*1/4”	0.48	0.28	0.38	1/25	.03	65-651	----
64-652	----	*3/8”	0.53	0.31	0.43	1/25	.04	65-652	----
64-653	----	1/2”	0.58	0.38	0.56	50/600	.08	65-653	----
64-654	----	3/4”	0.65	0.44	0.63	30/360	.13	65-654	----
64-655	----	1”	0.75	0.50	0.82	20/240	.22	65-655	----
64-656	----	1-1/4”	0.82	0.56	0.94	40/120	.33	65-656	----
64-657	----	1-1/2”	0.85	0.62	1.13	30/90	.41	65-657	----
64-658	----	2”	0.91	0.68	1.31	20/60	.68	65-658	----
64-659	----	2-1/2”	1.26	0.74	1.50	16/64	.89	65-659	----
64-660	----	3”	1.16	0.80	1.69	16/32	1.68	65-660	----
64-661	----	4”	1.22	1.00	2.28	6/12	3.02	65-661	----
		6"	1.85	1.13	5.97	5/10	11.41	65-662	----
		8"				1/1		65-664	----

CAPS

Part # Galvanized		Size	A	Box/ Case	Approx. Wt. Lbs.	Part # Black	
64-470	----	1/8"	0.55	1/25	.03	65-470	----
64-471	----	1/4"	0.62	80/960	.07	65-471	----
64-472	----	3/8”	0.74	60/720	.08	65-472	----
64-473	----	1/2”	0.87	75/300	.13	65-473	----
64-474	----	3/4”	0.97	40/160	.18	65-474	----
64-475	----	1”	1.16	25/100	.30	65-475	----
64-476	----	1-1/4”	1.28	20/80	.47	65-476	----
64-477	----	1-1/2”	1.33	18/54	.66	65-477	----
64-478	----	2”	1.45	12/36	.99	65-478	----
64-479	----	2-1/2”	1.70	20/40	1.58	65-479	----
64-480	----	3”	1.80	12/24	2.51	65-480	----
64-481	----	4”	2.08	6/12	4.09	65-481	----
64-482	----	6”	2.55	2/4	5.18	65-482	----

* Use steel fittings for smaller sizes. See page 279-280 for Galvanized and Black Steel Fittings.

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

LATERAL Ys



Part #	Size	A	B	Case	Weight	
65-963	1/2	2.32	1.71	120	.35	----
65-964	3/4	2.77	2.05	60	.58	----
65-965	1	3.28	2.42	40	.97	----
65-966	1-1/4	3.94	2.92	24	1.44	----
65-967	1-1/2	4.38	3.28	16	1.93	----
65-968	2	5.41	3.98	8	3.12	----
65-969	2-1/2	6.25	4.73	4	5.61	----
65-970	3	7.26	5.55	2	8.36	----
65-971	4	8.98	6.97	2	14.88	----

LOCKNUTS

Part # Galv		Size	A Hex	Thickness	Box/ Case	Weight	Part # Black	
64-703	----	1/2		0.31	150/600	0.08	65-703	----
64-704	----	3/4		0.34	90/360	0.13	65-704	----
64-705	----	1		0.38	60/240	0.19	65-705	----
64-706	----	1-1/4		0.42	45/180	0.27	65-706	----
64-707	----	1-1/2		0.47	45/135	0.47	65-707	----
64-708	----	2		0.53	25/75	0.56	65-708	----

RIGHT & LEFT COUPLINGS



Part # Galv		Size	A	Case	Weight	Part # Black	
64-573	----	1/2	1.34	240	0.19	65-573	----
64-574	----	3/4	1.52	150	0.28	65-574	----
64-575	----	1	1.67	100	0.45	65-575	----
64-576	----	1-1/4	1.93	64	0.66	65-576	----
64-577	----	1-1/2	2.15	36	0.84	65-577	----
64-578	----	2	2.53	24	1.39	65-578	----

SIDE OUTLET ELBOW



Part # Galv		Size	A	B	Case	Part # Black	
64-583	----	1/2	1.10		135	65-583	----
64-584	----	3/4	1.30		80	65-584	----
64-585	----	1	1.50		40	65-585	----
64-586	----	1-1/4	1.77		30	65-586	----
64-587	----	1-1/2	1.97		24	65-587	----
64-588	----	2	2.29		10	65-588	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

FLOOR FLANGES



Part # Galvanized		Size	A	Thickness	Hole Size	Box/ Case	Approx. Wt. Lbs.	Part # Black	
64-692	----	1/2”	3.50	0.50	0.25	25/100	.63	65-692	----
64-693	----	3/4”	3.50	0.63	0.25	15/45	.73	65-693	----
64-694	----	1”	4.00	0.69	0.25	15/45	1.02	65-694	----
64-695	----	1-1/4”	4.00	0.75	0.25	15/30	1.00	65-695	----
64-696	----	1-1/2”	4.50	0.87	0.31	8/24	1.37	65-696	----
64-697	----	2”	5.50	1.00	0.31	8/16	2.11	65-697	----

EXTENSION FIP X MIP

Part #	Size	Approx. WT. Lbs.	Box/Case	
65-621	1/2"	0.12	75 / 300	----
65-622	3/4"	0.23	40 / 160	----
65-623	1"	0.32	30 / 90	----

MUSHROOM VENT CAP

Cast Iron Galvanized Threaded Cap. 30 Mesh screen. Protects against driving rain, snow, sleet and insects.

Part #	Size	
21-174	3/4"	----
21-175	1"	----
21-176	1-1/2"	----
21-177	1-1/2"	----
21-178	2"	----
21-179	3"	----
21-180	4"	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

STEEL FITTINGS — BLACK & GALVANIZED

This will certify that the material was manufactured in accordance with ASME B16.14 - 1991 Standards. All Threads are Dryseal (NPTF) - 3/4 inch taper per foot and are made of Carbon Steel 12L14. Pressure rating: 150/300 PSI

• Clear Zinc plating specifications ASTM B633-07 • Federal Specification QQ-Z-325 (Zinc Plate)
• Type III with supplemental clear Trivalent chromate • .00015" Zinc (Minimum) • ROHS Compliant • Lead Free

HEX BUSHINGS

Part # Zinc		Size M x F	A	Hex	Approx. Wt. Lbs.	Part # Black	
66-500	----	1/4” x 1/8”	0.63	0.62	0.02	67-500	----
66-501	----	3/8” x 1/8”	0.66	0.68	0.04	67-501	----
66-502	----	3/8” x 1/4”	0.66	0.68	0.02	67-502	----
66-503	----	1/2” x 1/8”	0.80	0.87	0.10	67-503	----
66-504	----	1/2” x 1/4”	0.80	0.87	0.08	67-504	----
66-505	----	1/2” x 3/8”	0.80	0.87	0.06	67-505	----
66-506	----	3/4” x 1/8”	0.94	1.06	0.18	67-506	----
66-507	----	3/4” x 1/4”	0.94	1.06	0.14	67-507	----
66-508	----	3/4” x 3/8”	0.94	1.06	0.14	67-508	----
66-509	----	3/4” x 1/2”	0.94	1.06	0.10	67-509	----
66-510	----	1” x 1/4”	1.00	1.31	0.16	67-510	----
66-511	----	1” x 3/8”	1.00	1.31	0.26	67-511	----
66-512	----	1” x 1/2”	1.00	1.31	0.22	67-512	----
66-513	----	1” x 3/4”	1.00	1.31	0.14	67-513	----
		1-1/4" x 1/8"	1.08	1.31	0.16	67-514	----

FACE BUSHING

Part # Zinc		Size M x F	A	Approx. Wt. Lbs.	Part # Black	
66-700	----	1/4” x 1/8”	0.44	0.01	67-700	----
66-701	----	3/8” x 1/8”	0.48	0.02	67-701	----
66-702	----	3/8” x 1/4”	0.48	0.02	67-702	----
		1/2” x 1/8”	0.56	0.04	67-703	----
66-704	----	1/2” x 1/4”	0.56	0.04	67-704	----
66-705	----	1/2” x 3/8”	0.56	0.04	67-705	----
		3/4” x 1/4”	0.62	0.12	67-707	----
66-708	----	3/4” x 3/8”	0.62	0.10	67-708	----
66-709	----	3/4” x 1/2”	0.62	0.10	67-709	----
		1” x 3/8”	0.75	0.18	67-711	----
66-712	----	1” x 1/2”	0.75	0.16	67-712	----
66-713	----	1” x 3/4”	0.75	0.16	67-713	----

CAPS

Part # Zinc		Size NPTF	A	Hex	Approx. Wt. Lbs.	Part # Black	
66-470	----	1/8”	0.53	0.56	0.02	67-470	----
66-471	----	1/4”	0.63	0.62	0.04	67-471	----
66-472	----	3/8”	0.69	0.81	0.06	67-472	----
66-473	----	1/2”	0.87	1.00	0.12	67-473	----
66-474	----	3/4”	0.97	1.18	0.16	67-474	----
66-475	----	1”	1.16	1.50	0.30	67-475	----
66-476	----	1-1/4"	1.28	2.00	0.68	67-476	----
66-477	----	1-1/2"	1.35	2.25	0.83	67-477	----
66-478	----	2"	1.45	2.625	1.36		

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

This will certify that the plugs are dimensional per SAE J531 MAY 95 Standards. All threads are Dryseal (NPTF) - 3/4"Taper per foot and are made of SAE J403 Low Carbon Steel 1010 Cold headed.

SQUARE HEAD PLUGS

• Solid



Part # Zinc		Size NPTF	A	B	C	Approx. Wt. Lbs.	Part # Black	
		1/16”	0.33	0.18	0.22	0.01	67-669	----
66-670	----	1/8”	0.33	0.24	0.28	0.01	67-670	----
66-671	----	1/4”	0.45	0.28	0.37	0.02	67-671	----
66-672	----	3/8”	0.50	0.31	0.43	0.04	67-672	----
66-653	----	1/2”	0.59	0.38	0.55	0.12	67-653	----
66-654	----	3/4”	0.63	0.44	0.62	0.18	67-654	----
66-655	----	1"	0.75	0.5	0.81	0.34	67-655	----
66-656	----	1-1/4"	0.80	0.56	0.93	0.62	67-656	----
66-657	----	1-1/2"	0.83	0.62	1.12	0.82	67-657	----
66-658	----	2"	0.88	0.68	1.31	1.36	67-658	----

HEX HEAD PLUGS

• Solid

Hex

Part # Zinc		Size NPTF	A	Hex	Approx. Wt. Lbs.	Part # Black	
66-770	----	1/8”	0.55	0.43	0.01	67-770	----
66-771	----	1/4”	0.74	0.56	0.04	67-771	----
66-772	----	3/8”	0.67	0.68	0.06	67-772	----
66-773	----	1/2”	0.80	0.70	0.12	67-773	----
66-774	----	3/4”	0.94	1.06	0.18	67-774	----
66-775	----	1”	1.00	1.31	0.22	67-775	----
66-776	----	1-1/4"	1.17	1.75	0.7	67-776	----
66-777	----	1-1/2"	1.51	2.00	1.2	67-777	----
66-778	----	2"	1.65	2.50	2.06	67-778	----

COUNTERSUNK PLUG - Square Socket

Part # Zinc		Size NPTF	A	Socket Size	Approx. Wt. Lbs.	Part # Black	
66-630	----	1/8”	0.29	0.19	0.01	67-630	----
66-631	----	1/4”	0.45	0.25	0.02	67-631	----
66-632	----	3/8”	0.45	0.31	0.04	67-632	----
66-633	----	1/2”	0.59	0.38	0.08	67-633	----
66-634	----	3/4”	0.60	0.50	0.12	67-634	----
66-635	----	1”	0.75	0.50	0.16	67-635	----
66-636	----	1-1/4"	0.80	0.75	0.32	67-636	----
66-637	----	1-1/2"	0.83	0.75	0.45	67-637	----
66-638	----	2"	0.88	0.875	2.06	67-638	----

COUNTERSUNK PLUG - Hex Socket

Part # Zinc		Size NPTF	A	Socket Size	Approx. Wt. Lbs.	Part # Black	
66-760	----	1/16”	0.29	0.15	0.01	67-760	----
66-761	----	1/8”	0.29	0.18	0.01	67-761	----
66-762	----	1/4”	0.44	0.25	0.02	67-762	----
66-763	----	3/8”	0.44	0.31	0.04	67-763	----
66-764	----	1/2”	0.59	0.37	0.08	67-764	----
66-765	----	3/4”	0.60	0.56	0.14	67-765	----
66-766	----	1”	0.75	0.625	0.22	67-766	----
66-767	----	1-1/4"	0.80	0.75	0.37	67-767	----
66-768	----	1-1/2"	0.83	1.0	0.45	67-768	----
66-769	----	2"	0.88	1.0	0.86	67-769	----

• Slotted and Flush plugs available upon request

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

MALLEABLE FITTINGS — BLACK EXTRA HEAVY 300# IRON

90° ELBOW

Part #	Size	
69-101	1/4"	----
69-102	3/8"	----
69-103	1/2"	----
69-104	3/4"	----
69-105	1"	----
69-106	1-1/4"	----
69-107	1-1/2"	----
69-108	2"	----

45° ELBOW

Part #	Size	
69-181	1/4"	----
69-182	3/8"	----
69-183	1/2"	----
69-184	3/4"	----
69-185	1"	----
69-186	1-1/4"	----
69-187	1-1/2"	----
69-188	2"	----

90° STREET ELBOW

Part #	Size	
69-161	1/4"	----
69-162	3/8"	----
69-163	1/2"	----
69-164	3/4"	----
69-165	1"	----
69-166	1-1/4"	----
69-167	1-1/2"	----
69-168	2"	----

TEE

Part #	Size	
69-252	3/8"	----
69-253	1/2"	----
69-254	3/4"	----
69-255	1"	----
69-256	1-1/4"	----
69-257	1-1/2"	----
69-258	2"	----

COUPLING

Part #	Size	
69-411	1/4"	----
69-412	3/8"	----
69-413	1/2"	----
69-414	3/4"	----
69-415	1"	----
69-416	1-1/4"	----
69-417	1-1/2"	----
69-418	2"	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

BLACK EXTRA 300# IRON — MALLEABLE FITTINGS

REDUCING COUPLING

Part #	Size	
69-432	3/8 x 1/4"	----
69-434	1/2 x 1/4"	----
69-435	1/2 x 3/8"	----
69-438	3/4 x 1/2"	----
69-441	1 x 1/2"	----
69-442	1 x 3/4"	----

CAP

Part #	Size	
69-471	1/4"	----
69-472	3/8"	----
69-473	1/2"	----
69-474	3/4"	----
69-475	1"	----
69-476	1-1/4"	----
69-477	1-1/2"	----
69-478	2"	----

UNION

• Brass Seat

Part #	Size	
69-600	1/8"	----
69-601	1/4"	----
69-602	3/8"	----
69-603	1/2"	----
69-604	3/4"	----
69-605	1"	----
69-606	1-1/4"	----
69-607	1-1/2"	----
69-608	2"	----

STEEL MAGNETIC PLUGS

Steel Magnetic Drain Plugs - NPT Threaded

Magnetic Drain Plugs are similar to standard pipe or straight thread drain plugs with one important difference - a permanent magnet is fastened to the plug body. This magnet attracts and holds abrasive, ferrous metal particles preventing their circulation through the lubrication or hydraulic system.

These abrasive, ferrous metal particles appear in lubricating or hydraulic systems as a result of the following conditions:
• The constant flaking effect of normal wear of moving parts.
• Particles not removed by flushing operations after boring or machining.
• Chipping due to sub-surface casting flaws.
• Minute component breakdown caused by stress usage.

Magnetic Drain Plugs prevent excessive wear to the system's components.

Magnetic Plugs are used by numerous manufacturers of gear boxes, transmissions, engines, and hydraulic systems for the automotive, aircraft, agricultural and machinery industries.
Typical applications include:
• Outboard Engines
• Earthmoving Equipment
• Combines
• Balers
• Crawler Tractors
• Lift Trucks
• Mining Equipment
• Military Vehicles
• Turbine Engines
• Truck Axles
• Heavy-Duty Transmissions



Part	Size "A"	Head Width "C"	Recess Dia. "H"	O/L Length "L"	
28-996	3/8 - 18	.428 - .440	.435 - .445	.805 - .860	----
28-997	1/2 - 14	.553 - 565	.560 - .570	.970 -1.04	----
28-998	3/4 - 14	.615 - .627	.725 - .735	1.120 - 1.170	----
28-999	1-11 1/2	.803 - 815	.895 - .905	1.25 - 1.33	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm.
For more information, visit www.P65Warnings.ca.gov

STANDARD BULL PLUG

- Sch 40 150#
- Zinc plated

Part #	Description	
91-008	2"	----
91-007	2" w/ 1/2" TAP	----
91-009	2-1/2"	----
91-010	3"	----
91-011	4"	----

XH BULL PLUG

- Made from sch. 80 pipe.
- Zinc plated
- Hollow

Part #	Description	
90-001	1/4"	----
90-002	3/8"	----
90-003	1/2"	----
90-004	3/4"	----
90-005	1"	----
90-006	1-1/4"	----
90-007	1-1/2"	----
90-008	2"	----
93-001*	2"	----
90-213	2" w/ 1/4" TAP	----
90-212	2" w/ 1/2" TAP	----
93-212*	2"XXH w/1/2" TAP	----
90-009	2-1/2"	----
90-010	3"	----
90-215	3" w/ 1/2" TAP	----
90-011	4"	----

* XXH

STANDARD SCH. 40 SWAGE

MIP X MIP

- Zinc plated

Part #	Description	
93-113	1-1/4" x 1"	----
93-121	2" x 1"	----
93-122	2" x 1-1/4"	----
93-123	2" x 1-1/2"	----
93-124	2-1/2" x 2"	----
93-125	3" x 1"	----
93-127	3" x 1-1/2"	----
93-128	3" x 2"	----
93-129	3" x 2-1/2"	----
93-130	4" x 2"	----
93-131	4" x 3"	----
93-139	6" x 3"	----

Pressure Ratings: Due to the wide variation in service conditions, temperature, vibrations, etc...We can make no recommendations as to allowable working pressure of swage nipples and bull plugs. There are a number of working pressure formulas from which the end user may choose to determine the required wall thickness of the piping system. It is our responsibility only to furnish a fitting with end dimensions equal to those of the pipe size and schedule ordered.

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

SWAGES

SCH 80 XH SWAGES
MIP X MIP

* Hex Style

Part #	Description	
90-100*	1/4" x 1/8"	----
90-102*	1/2" x 1/4"	----
90-103*	1/2" x 3/8"	----
90-104*	3/8" x 1/4"	----
90-105*	3/4" x 1/4"	----
90-106*	3/4" x 3/8"	----
90-107*	3/4" x 1/2"	----
90-108*	1" x 1/4"	----
90-109*	1" x 3/8"	----
90-110*	1" x 1/2"	----
90-111*	1" x 3/4"	----
90-140	1-1/4" x 3/4"	----
90-141	1-1/4" x 1"	----
90-114	1-1/2" x 1/2"	----
90-115	1-1/2" x 3/4"	----
90-116	1-1/2" x 1"	----
90-117	1-1/2" x 1-1/4"	----
90-118	2" x 1/4"	----
90-119	2" x 1/2"	----
90-120	2" x 3/4"	----
90-121	2" x 1"	----
90-122	2" x 1-1/4"	----
90-123	2" x 1-1/2"	----
90-124	2-1/2" x 2"	----
90-125	3" x 1"	----
90-126	3" x 1-1/4"	----
90-127	3" x 1-1/2"	----
90-128	3" x 2"	----
90-129	3" x 2-1/2"	----
90-133	4" x 1"	----
90-130	4" x 2"	----
90-131	4" x 3"	----
90-132	6" x 4"	----
90-150	6" x 2"	----
90-152	6" x 3"	----

XXH SWAGE

Part #	Description	
92-102*	1/2" x 1/4"	----
92-107*	3/4" x 1/2"	----
92-108*	1" x 1/4"	----
92-109*	1" x 3/8"	----
92-110*	1" x 1/2"	----
92-111*	1" x 3/4"	----
92-114	1-1/2" x 1/2"	----
92-115	1-1/2" x 3/4"	----
92-116	1-1/2" x 1"	----
92-119	2" x 1/2"	----
92-120	2" x 3/4"	----
92-121	2" x 1"	----
92-122	2" x 1-1/4"	----
92-123	2" x 1-1/2"	----
92-128	3" x 2"	----

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer.
For more information, visit www.P65Warnings.ca.gov

ASTMA105
ASME SA105
ANSI B16.5

Forged Steel Flanges

• A105 Forged Steel • CLASS 150

(1-1/2 thru 6" available in #316 Stainless Steel add SS to part#)



SLIP-ON 1/16" RAISED FACE FORGED STEEL FLANGE

Part #	Size	
107-020	1/2"	----
107-021	3/4"	----
107-022	1"	----
107-023	1-1/4"	----
107-024	1-1/2"	----
107-025	2"	----
107-026	2-1/2"	----
107-027	3"	----
107-029	4"	----
107-031	6"	----
107-032	8"	----
107-033	10"	----
107-034	12"	----



THREADED 1/16" RAISED FACE FORGED STEEL FLANGE

Part #	Size	
107-060	1/2"	----
107-061	3/4"	----
107-062	1"	----
107-063	1-1/4"	----
107-064	1-1/2"	----
107-065	2"	----
107-066	2-1/2"	----
107-067	3"	----
107-069	4"	----
107-071	6"	----
107-072	8"	----
107-073	10"	----
107-074	12"	----

Nominal Pipe Size	Depth of Socket in.	DRILLING			BOLTING				APPROXIMATE WEIGHT		
		Bolt Circle Diameter	Number of Holes	Diameter of Holes	Diameter of Bolts (inch)	Machine Bolt Length	Stud Bolt Length		Welding Neck	Slip-on and Threaded	Blind
						Raised Face	Raised Face	Ring Joint			
	Y								LBS	LBS	LBS
1/2	.382	2.382	4	.618	1/2	2.00	2.252	-	1.146	1.036	1.036
3/4	.441	2.752	4	.618	1/2	2.00	2.50	-	2.028	1.653	1.389
1	.500	3.118	4	.618	1/2	2.252	2.50	3.00	2.425	1.893	2.094
1-1/4	.559	3.50	4	.618	1/2	2.252	2.752	3.252	3.086	3.086	3.086
1-1/2	.618	3.882	4	.618	1/2	2.50	2.752	3.252	3.99	3.109	3.571
2	.689	4.752	4	.752	5/8	2.752	3.252	3.752	6.173	4.982	5.82
2-1/2	.752	5.5	4	.752	5/8	3.00	3.50	4.00	9.436	7.562	8.951
3	.811	6.0	4	.752	5/8	3.00	3.50	4.00	11.42	8.818	11.023
4	.941	7.50	8	.752	5/8	3.00	3.50	4.00	16.138	12.677	16.535
6	1.059	9.50	8	.882	3/4	3.252	4.00	4.50	24.824	17.196	26.455
8	1.252	11.752	8	.882	3/4	3.50	4.252	4.752	39.683	28.66	44.092
10	1.311	14.252	12	1.00	7/8	4.00	4.50	5.00	55.116	37.699	66.139
12	1.559	17	12	1.00	7/8	4.00	4.752	5.252	85.936	61.024	97.003

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

ASTMA105
ASME SA105
ANSI B16.5

Forged Steel Flanges

- **A105 Forged Steel**
- **CLASS 150**

(1-1/2 thru 6" available in #316 Stainless Steel add SS to part#)



WELD NECK FORGED STEEL FLANGE

Part #	Size	
107-000	1/2"	----
107-001	3/4"	----
107-002	1"	----
107-003	1-1/4"	----
107-004	1-1/2"	----
107-005	2"	----
107-006	2-1/2"	----
107-007	3"	----
107-009	4"	----
107-011	6"	----
107-012	8"	----
107-013	10"	----
107-014	12"	----



BLIND 1/16" RAISED FACE FORGED STEEL FLANGE

Part #	Size	
107-040	1/2"	----
107-041	3/4"	----
107-042	1"	----
107-043	1-1/4"	----
107-044	1-1/2"	----
107-045	2"	----
107-046	2-1/2"	----
107-047	3"	----
107-049	4"	----
107-051	6"	----
107-052	8"	----
107-053	10"	----
107-054	12"	----

Nominal Pipe Size	Outside Diameter	O.D of Raised Face	Diameter at Base of Hub	Thickness	BORE	LENGTH THRU HUB	
					Welding Neck Socket Welding	Welding Neck	Slip-on Threaded Socket Welding
	D	G	X	T	B1	T1	T2
1/2	3.504	1.382	1.189	.441	.618	1.882	.618
3/4	3.898	1.689	1.50	.50	.819	2.059	.618
1	4.252	2.00	1.941	.559	1.051	2.189	.689
1-1/4	4.606	2.50	2.311	.618	1.382	2.252	.811
1-1/2	5.00	2.882	2.559	.689	1.610	2.441	.882
2	5.984	3.618	3.059	.752	2.071	2.50	1.00
2-1/2	7.008	4.118	3.559	.882	2.469	2.752	1.118
3	7.52	5.00	4.252	.941	3.071	2.752	1.189
4	9.016	6.189	5.311	.941	4.031	3.00	1.311
6	10.984	8.50	7.559	1.00	6.071	3.50	1.559
8	13.504	10.618	9.689	1.118	7.980	4.00	1.752
10	15.984	12.752	12.00	1.189	10.02	4.00	1.941
12	19.016	15.00	14.382	1.252	12.00	4.50	2.189

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

COPPER FITTINGS

SYMBOL OF JOINT ENDS

C Solder joint fitting end made to receive copper tube diameter
Ftg. Solder joint fitting end made to copper tube diameter
F Internal ANSI Standard Taper Pipe Thread-Female
M External ANSI Standard Taper Pipe Thread-Male
Threaded ends ANSI/ ASME B1. Solder ends ASTM B88

- Temp range 32° to 200°F
- Pressure @100° - 1/8-1 : 500 PSI
  - 1-1/4-2 : 400 PSI
  - 2-1/2 - 3: 300 PSI

NSF - 61 CERTIFIED
ALLOY C12200

THE ABOVE CONFORMS TO ASTM B 88 & ASTM B 306, A 306



MALE (FITTING)



FEMALE (COPPER)

Nominal Size	Joint Ends										Metal Thickness T (in)	Inside Diameter O (in)
	Male End					Female End						
	Outside Diameter (A) in	Average Tolerance (mm)	Actual MIN in	O.D. MAX in	Length (Min) H (in)	Inside Diameter F (in)	Average Tolerance (mm)	Actual MIN in	O.D. MAX in	Length (Min) G (in)		
1/8	2/8	0.03	2/8	2/8	3/8	2/8	0.03	2/8	2/8	3/8	0	2/8
1/4	3/8		3/8	3/8	3/8	3/8		3/8	3/8	3/8	0	2/8
3/8	4/8		4/8	4/8	3/8	4/8		4/8	4/8	3/8	0	3/8
1/2	5/8		5/8	5/8	4/8	5/8		5/8	5/8	3/8	0	4/8
5/8	6/8		6/8	6/8	5/8	6/8		6/8	6/8	5/8	0	4/8
3/4	7/8		7/8	7/8	6/8	7/8		7/8	7/8	5/8	0	5/8
1	1-1/8	0.04	1-1/8	1-1/8	7/8	1-1/8	0.04	1-1/8	1-1/8	7/8	0	7/8
1-1/4	1-3/8		1-3/8	1-3/8	1	1-3/8		1-3/8	1-3/8	1	0	1-1/8
1-1/2	1-5/8	0.05	1-5/8	1-5/8	1-1/8	1-5/8	0.05	1-5/8	1-5/8	1-1/8	0	1-3/8
2	2-1/8		2-1/8	2-1/8	1-3/8	2-1/8		2-1/8	2-1/8	1-2/8	0	1-6/8
2-1/2	2-5/8		2-5/8	2-5/8	1-4/8	2-5/8		2-5/8	2-5/8	1-4/8	1/8	2-1/8
3	3-1/8		3-1/8	2-1/8	1-6/8	3-1/8		3-1/8	3-1/8	1-5/8	1/8	2-5/8
4	4-1/8		4-1/8	4-1/8	2-1/8	4-1/8		4-1/8	4-1/8	2-1/8	1/8	3-4/8



90° ELL C X C

Part#	Nominal (ID)	OD	Approx Net Wt.	Ind #	
77-100	1/8"	1/4"	0.01	W 02003	----
77-101	1/4"	3/8"	0.01	W 02009	----
77-102	3/8"	1/2"	0.03	W 02017	----
77-104	1/2"	5/8"	0.04	W 02022	----
77-107	5/8"	3/4"	0.07	W 02028	----
77-108	3/4"	7/8"	0.09	W 02034	----
77-110	1"	1-1/8"	0.17	W 02047	----
77-113	1-1/4"	1-3/8"	0.27	W 02077	----
77-114	1-1/2"	1-5/8"	0.41	W 02085	----
77-116	2"	2-1/8"	0.73	W 02086	----

WE-500-R 607-R 107-C

90° STREET ELL FTG. X C

77-124	1/4"	3/8"	0.01	W 02312	----
77-125	3/8"	1/2"	0.03	W 02321	----
77-126	1/2"	5/8"	0.05	W 01652	----
77-127	5/8"	3/4"	0.07	W 02330	----
77-128	3/4"	7/8"	0.12	W 01654	----
77-129	1"	1-1/8"	0.22	W 02344	----
77-130	1-1/4"	1-3/8"	0.33	W 02384	----
77-131	1-1/2"	1-5/8"	0.45	W 02385	----
77-132	2"	2-1/8"	0.87	W 02386	----

90° LONG TURN ELL C X C

77-139	1/8"	1/4"	0.01	W 02715	----
77-140	1/4"	3/8"	0.02	W 02716	----
77-141	5/16"		0.03		----
77-142	3/8"	1/2"	0.04	W 02717	----
77-143	1/2"	5/8"	0.06	W 02722	----
77-144	5/8"	3/4"	0.10	W 02728	----
77-145	3/4"	7/8"	0.15	W 02734	----

WE-500-L 607-LT 107-L

90° LONG TURN ST. ELL FTG. X C

77-154	3/8"	1/2"	0.04	W 02817	----
77-155	1/2"	5/8"	0.06	W 02822	----
77-156	5/8"	3/4"	0.11		----
77-157	3/4"	7/8"	0.15		----
77-158	1"	1-1/8"	0.33		----
77-159	1-1/4"	1-3/8"	0.46	W 02828	----
77-160	1-1/2"	1-5/8"	0.64	W 02834	----

WE-503-L 607-2LT

45° ELL C X C

Part#	Nominal	Approx Net Wt.	Ind #	
77-161	1/8"	0.01	W 03005	----
77-162	1/4"	0.01	W 03012	----
77-163	3/8"	0.02	W 03021	----
77-164	1/2"	0.04	W 03026	----
77-165	5/8"	0.06	W 03030	----
77-166	3/4"	0.10	W 03034	----
77-167	1"	0.19	W 03044	----
77-168	1-1/4"	0.27	W 03050	----
77-169	1-1/2"	0.39	W 03055	----
77-170	2"	0.75	W 03059	----

WE-504 606 106

STREET 45° FTG. X C

77-177	1/4"	0.01	W 03312	----
77-178	3/8"	0.02	W 03321	----
77-179	1/2"	0.06	W 03326	----
77-180	5/8"	0.06	W 03330	----
77-181	3/4"	0.10	W 03334	----
77-182	1"	0.18	W 03344	----
77-183	1-1/4"	0.27	W 03350	----
77-184	1-1/2"	0.38	W 03355	----
77-185	2"	0.75	W 03359	----

WE-505 606-2

COUPLING (SOCKET) W/ ROLLED UP TUBE STOP C X C

77-201	1/8"	0.01	W 01003	----
77-202	1/4"	0.01	W 01009	----
77-203	3/8"	0.02	W 01017	----
77-204	1/2"	0.03	W 01022	----
77-205	5/8"	0.04	W 01028	----
77-206	3/4"	0.06	W 01034	----
77-207	1"	0.10	W 01047	----
77-208	1-1/4"	0.15	W 01055	----
77-209	1-1/2"	0.22	W 01063	----
77-210	2"	0.39	W 01072	----

WC-400 100

COUPLING (SOCKET) LESS TUBE STOP C X C

77-219	1/8"	0.01	W 01900	----
77-220	1/4"	0.01	W 01901	----
77-222	1/2"	0.03	W 01903	----
77-223	3/4"	0.06	W 01905	----
77-224	1"	0.10	W 01906	----
77-225	1-1/4"	0.15	W 01907	----
77-226	1-1/2"	0.22	W 01908	----
77-227	2"	0.39	W 01909	----

WC-400NS 601

See page 169-171 for SWT x SWT LF Ball Valves

WROT SOLDER JOINT — COPPER FITTINGS

COUPLING (SOCKET) W/ DIMPLED TUBE STOP C X C

Part#	Nominal	Approx Net Wt.	Ind #	
77-238	1/2"	0.03		----
77-240	3/4"	0.06		----
77-241	1"	0.10		----
77-242	1-1/4"	0.15		----
77-244	2"	0.39		----

WC-400S

REDUCER COUPLING W/ STOP C X C

77-252	1/4" x 1/8"	0.01	W 01011	----
77-254	3/8" x 1/8"			----
77-253	3/8" x 1/4"	0.02	W 01019	----
77-256	1/2" x 1/4"	0.03	W 01023	----
77-255	1/2" x 3/8"	0.03	W 01021	----
77-258	5/8" x 1/2"	0.04	W 01025	----
77-263	3/4" x 3/8"	0.06	W 01036	----
77-262	3/4" x 1/2"	0.06	W 01029	----
77-267	1"x1/2"	0.10	W 01049	----
77-265	1"x3/4"	0.12	W 01038	----
77-270	1 -1/4" x 1/2"	0.14	W 01058	----
77-269	1 -1/4" x 3/4"	0.17	W 01056	----
77-268	1-1/4" x 1"	0.17	W 01051	----
77-273	1 -1/2" x 3/4"	0.25	W 01065	----
77-272	1-1/2" x1"	0.24	W 01064	----
77-271	1-1/2" x 1-1/4"	0.24	W 01060	----
77-277	2" x 1"	0.48	W 01074	----
77-276	2 x 1-1/4"	0.46	W 01073	----
77-275	2" x 1-1/2"	0.42	W 01069	----
77-280	2-1/2"x2"	0.79	W 01075	----

WC-400R 600-R

FITTING REDUCER FTG. C X C

77-292	3/8" x 1/8"	0.01	W 01314	----
77-291	3/8" x 1/4"	0.02	W 01312	----
77-294	1/2" x 1/4"	0.03	W 01317	----
77-293	1/2" x 3/8"	0.03	W01315	----
77-295	5/8" X 1/2"	0.03	W 01320	----
77-298	3/4" x 3/8"	0.05	W 01327	----
77-297	3/4" x 1/2"	0.06	W 01326	----
77-296	3/4" x 5/8"	0.08	W 01325	----
77-352	1" x 1/2"	0.10	W 01265	----
77-300	1"x3/4"	0.11	W 01337	----
77-355	1 -1/4" x 3/4"	0.15	W 01345	----
77-354	1-1/4" x1"	0.17	W 01343	----
77-360	1 -1/2" x 1/2"	0.21	W 01355	----
77-359	1 -1/2" x 3/4"	0.21	W 01353	----
77-358	1-1/2"x1"	0.22	W 01351	----
77-357	1 -1/2" X 1-1/4"	0.21	W 01350	----
77-365	2" x 1/2"	0.44	W 01364	----
77-363	2" x 1"	0.40	W 01360	----
77-361	2" x 1-1/2"	0.39	W 01358	----

WC-403 600-2

MALE ADAPTER
C X M



Part#	Nominal	Approx Net Wt.	Ind #	
77-393	1/8"	0.02		----
77-394	1/4"	0.04		----
77-398	3/8"	0.06	W 01125	----
77-401	1/2"	0.08	WB01131	----
77-306	3/4"	0.14	WB01146	----
77-309	1"	0.24	WB01163	----
77-314	1-1/4"	0.41	W 01171	----
77-318	1-1/2"	0.50	W 01179	----
77-322	2"	0.87	W 01187	----
77-395	1/4" x 1/2"	0.09	W 01113	----
77-311	1/2" x 3/8"	0.18		----
77-303	1/2" x 3/4"	0.16	W 01130	----
77-308	3/4" x 1/2"	0.31		----
77-307	3/4" x 1"	0.29	W 01145	----
77-312	1" x 3/4"	0.18	W 01164	----

• 14 more reducing sizes available

WC-401 604

FTG. MALE ADAPTER
FTG. X M

77-331	1/2"	0.09	W 01431	----
77-333	3/4"	0.15	W 01446	----
77-334	1"	0.15	W 01463	----
77-335	1-1/4"	0.41	W 01471	----
77-336	1-1/2"	0.41	W 0147X9	----
77-337	2"	0.86	W 01487	----

WC-404 604-2

COPPER TUBING

SEE COPPER TUBING FOR REFRIGERATION AND DRINKING WATER ON PAGE 341

Well done is better than well said. - Benjamin Franklin

FEMALE ADAPTERS
C X F

Part#	Nominal	Approx Net Wt.	Ind #	
77-343	1/2"	0.10	WB01231	----
77-349	3/4"	0.14	WB01246	----
77-402	1"	0.24	WB01263	----
77-406	1-1/4"	0.43	W 01271	----
77-410	1-1/2"	0.58	W 01279	----
77-413	2"	0.74	W 01287	----
77-341	3/8" x 1/2"	0.10	W 01224	----
77-347	1/2" x 1/4"	0.05	W 01233	----
77-346	1/2"x3/8"	0,70	W 01232	----
77-345	1/2" x 3/4"	0.15	WB01230	----

FEMALE FTG.
ADAPT. FTG. X F

77-419	3/8"	0.05	W 01525	----
77-420	1/2"	0.11	W 01531	----
77-423	3/4"	0.19	W 01546	----
77-424	1			----

• More sizes available

WC402 603 WC402R 603R

CAP

77-429	1/4"	0.01	W 07004	----
77-430	3/8"	0.01	W 07006	----
77-431	1/2"	0.02	WB07007	----
77-432	5/8"	0.03	W 07008	----
77-433	3/4"	0.04	WB07009	----
77-434	1"	0.08	WB07011	----
77-435	1-1/4"	0.11	W 07012	----
77-436	1-1/2"	0.18	W 07013	----
77-437	2"	0.30	W 07014	----

WC405 603-2 WC405R 603R

UNIONS C X C

• LF = Lead Free

77-453	1/4"	0.11	W 08001	----
77-454	3/8"	0.11	W 08002	----
77-455LF	1/2"	0.17	W 08003	----
77-456LF	3/4"	0.37	W 08004	----
77-457LF	1"	0.51	W 08005	----
77-606LF	1-1/4"	0.98	W08006	----
77-607LF	1-1/2"	1.21	W08007	----
77-608LF	2"		W08008	----

WC-415 617

U-TYPE STRAP

77-461	1/2"	0.03	A 02529	----
77-462	3/4"	0.03	A 02574	----
77-463	1"	0.04	A 02614	----
77-464	1-1/4"	0.04	A 02650	----

WC-407

WS-1100

TEE
C X C X C

Part#	Nominal 1 x 2 x 3	Approx Net Wt.	Ind #	
77-467	1/8"	0.02	W 40306	----
77-468	1/4"	0.03	W 04000	----
77-470	3/8"	0.05	W 04001	----
77-473	1/2"	0.08	WB04006	----
77-481	5/8"	0.12	W 04017	----
77-483	3/4"	0.18	WB04031	----
77-490	1"	0.35	WB04048	----
77-504	1-1/4"	0.58	W 04068	----
77-519	1-1/2"	0.72	W 04084	----
77-543	2"	1.35	W 40102	----
77-489	3/4"x1/2"x1/2"	0.15	WB04043	----
77-488	3/4" x 1/2" x 3/4"	0.19	WB04041	----
77-486	3/4" x 3/4" x 1/2"	0.15	WB04033	----
77-485	3/4"x3/4"x1"	0.25	W 04065	----
77-501	1"x1/2"x1"	0.34	W 04061	----
77-499	1"x3/4"x3/4"	0.31	W 04056	----
77-498	1"x3/4"x1"	0.38	W 04055	----
77-496	1"x1"x1/2"	0.24	WB04051	----
77-493	1"x1"x3/4"	0.29	WB04049	----
77-518	1 -1 /4"x 1/2" x 1-1/4"	0.58	W 04083	----
77-514	1 -1/4" x 3/4" x 1-1/4"	0.63	W 04078	----
77-508	1-1/4" x 1-1/4" x 3/4"	0.39	W 04070	----
77-507	1-1/4"x1-1/4"x1"	0.47	W 04069	----
77-506	1 -1/4" x1 -1/4" x 1-1/2"	0.79	W 40100	----
77-523	1 -1/2" x 1-1/2" x 3/4"	0.51	W 04087	----
77-522	1-1/2" x 1-1/2" x1"	0.60	W 04086	----
77-549	2"x2"x1/2"	0.77	W 40107	----
77-548	2" x 2" x 3/4"	0.90	W 40106	----
77-547	2"x2"x1"	0.99	W 40105	----

DROP EAR ELBOWS

• Lead Free Bronze • Lead Free Brass

Part #	SWT x FIP	
44840LF	1/2 x 1/2 Bronze	----
44841LF	1/2 x 1/2 Brass	----
44842LF	3/4 x 1/2 Brass	----
44843LF	3/4 x 3/4 Brass	----

• Lead Free Brass

Part #	SWT x SWT	
44844LF	1/2 x 1/2	----

• Lead Free Bronze

Part #	Pex x FIP	
44845LF	1/2 x 1/2	----

WARNING: This product can expose you to chemicals, including Nickel, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

Sometimes the road less traveled is less traveled for a reason. - *Jerry Seinfeld*

PLASTIC FITTINGS

PIPE FITTINGS

- Nylon
- Polyethylene
- Polypropylene

HOSE BARB FITTINGS

- Nylon
- Polyethylene
- Polypropylene

GARDEN HOSE FITTINGS

- Nylon

NYLON & POLYPROPYLENE COMPRESSION FITTINGS

Machined Schedule 80 PVC nipples comply fully with ASTM D2464,

POLYPROPYLENE PUSH-IN TUBE FITTINGS AND VALVES

- NSF 61 certified for use with drinking (potable) water
- Max Temperature: 140°F
- Max Pressure: Not Rated

SCH 80 PVC NIPPLES

Machined Schedule 80 PVC nipples comply fully with ASTM D2464, threads conform to ASTM F1498, and the pipe is extruded from PVC 1120-1220 meeting ASTM D1784 and meets ASTM D1785, products standard 21-70

SCH 40 PVC FITTINGS

- NSF 61 certified for use with drinking (potable) water
- Max Temperature: 140°F
- Max Pressure: Not Rated

Resistant to corrosion, strong and rigid - commonly used in low pressure plumbing applications. ASTM D1784 and D2466.

SCH 80 PVC FITTINGS

PVC Material is Type 1 according to the American Society for Testing Materials (ASTM) D-1784. Fittings conform to ASTM D-2464 & ASTM D-2467. Temperature rating is 140°F. PSI is based on water at 73°F. Derate 50% at 110°F and 78% at 140°F. Not recommended for use in compressed air or gas systems.

AVAILABLE IN THREE TYPES OF PLASTIC

(W) White Nylon

Made from virgin grade formulated to resist physical stress and abrasion. This material meets F.D.A. requirements of Code of Federal Regulation part 177.1500 and is therefore suitable for food contact surfaces.

Temperature Range: -40^{0}F to 200^0 F

Working Pressure: 125 PSI maximum.

(B) Black Polyethylene

Made from a high molecular weight linear polyethylene formulated for chemical compatibility and high impact resistance at lower temeratures. Polyethylene is NSF approved for potable water.

Temperature Range: -65^{0}F to 190^{0}F

Working Pressure: 125 PSI maximum.

(P) Polypropylene

Made from the finest polypropylene resins. Polypropylene is used for its resistance to a wide range of chemicals. Working pressures decrease as temperatures increase.

- **NSF-approved materials**
- **FDA-approved materials**

Note: Do not use with compressed air or gas.

- 10% Fiberglass fill for extra strength

ELBOW

P

POLYPROPYLENE ELBOWS

Part #	Size	
28-702P	3/8"	----
28-704P	3/4"	----

W

NYLON ELBOWS

Part #	Size	
28-701W	1/4"	----
28-703W	1/2"	----
28-704W	3/4"	----
28-705W	1"	----
28-706W	1-1/4"	----
28-707W	1-1/2"	----
28-708W	2"	----

TEE

P

POLYPROPYLENE TEES

Part #	Size	
28-741P	1/4"	----
28-742P	3/8"	----
28-743P	1/2"	----
28-744P	3/4"	----

W

NYLON TEES

Part #	Size	
28-741W	1/4"	----
28-743W	1/2"	----
28-744W	3/4"	----
28-745W	1"	----
28-746W	1-1/4"	----
28-747W	1-1/2"	----
28-748W	2"	----

STREET ELBOW

P

POLYPROPYLENE STREET ELBOW

Part #	Size	
28-819P	1/8"	----
28-723P	1/2"	----
28-820P	2"	----
28-821P	3"	----

W

NYLON STREET ELBOW

Part #	Size	
28-819W	1/8"	----
28-720W	1/4"	----
28-721W	3/8"	----
28-723W	1/2"	----
28-724W	3/4"	----
28-725W	1"	----
28-726W	1-1/4"	----
28-727W	1-1/2"	----
28-820W	2"	----

HEX HEAD PLUGS

- Cored

B

POLYETHYLENE PLUGS

Part #	Size	
28-601B	1/8"	----
28-602B	1/4"	----
28-603B	3/8"	----
28-604B	1/2"	----
28-605B	3/4"	----

W

NYLON PLUGS

Part #	Size	
28-601W	1/8"	----
28-602W	1/4"	----
28-603W	3/8"	----
28-604W	1/2"	----
28-605W	3/4"	----
28-606W	1"	----
28-607W	1-1/4"	----
28-608W	1-1/2"	----
28-609W	2 "	----

PLASTIC PIPE

PLASTIC FITTINGS

HEX BUSHING

P

POLYPROPYLENE BUSHINGS

Part #	Size	
28-659P	1/4 x 1/8"	----
28-660P	3/8 x 1/8"	----
28-661P	3/8 x 1/4"	----
28-811P	1/2 x 1/8"	----
28-663P	1/2 x 1/4"	----
28-664P	1/2 x 3/8"	----
28-666P	3/4 x 1/4"	----
28-668P	3/4 x 1/2"	----
28-812P	1 x 3/8"	----
28-671P	1 x 1/2"	----
28-672P	1 x 3/4"	----
28-675P	1-1/4" x 1"	----
28-814P	1-1/2" x 1/2"	----
28-678P	1-1/2 x 3/4"	----
28-680P	1-1/2 x 1-1/4"	----
28-816P	2 x 1-1/4"	----
28-818P	3 x 2"	----

W

NYLON BUSHINGS

Part #	Size	
28-659W	1/4 x 1/8"	----
28-660W	3/8 x 1/8"	----
28-661W	3/8 x 1/4"	----
28-811W	1/2 x 1/8"	----
28-663W	1/2 x 1/4"	----
28-664W	1/2 x 3/8"	----
28-665W	3/4 x 1/8"	
28-666W	3/4 x 1/4"	----
28-667W	3/4 x 3/8"	----
28-668W	3/4 x 1/2"	----
28-671W	1 x 1/2"	----
28-672W	1 x 3/4"	----
28-674W	1-1/4 x 3/4"	----
28-675W	1-1/4 x 1"	----
28-678W	1-1/2 x 3/4"	----
28-679W	1-1/2 x 1"	----
28-680W	1-1/2 x 1-1/4"	----
28-815W	2" x 1/2"	----
28-682W	2 x 3/4"	----
28-683W	2 x 1"	----
28-685W	2 x 1-1/2"	----
28-818W	3" x 2"	----

HEX NIPPLES

B

POLYETHYLENE HEX NIPPLES

Part #	Size	
28-611B	1/8"	----
28-612B	1/4"	----
28-613B	3/8"	----
28-614B	1/2"	----

P

POLYPROPYLENE HEX NIPPLES

Part #	Size	
28-612P	1/4"	----
28-613P	3/8"	----
28-614P	1/2"	----
28-615P	3/4"	----
28-619P	2"	----

W

NYLON HEX NIPPLES

Part #	Size	
28-611W	1/8"	----
28-612W	1/4"	----
28-613W	3/8"	----
28-614W	1/2"	----
28-615W	3/4"	----
28-616W	1"	----
28-617W	1 1/4 "	----
28-618W	1 1/2"	----
28-619W	2"	----

REDUCER NIPPLES

B

POLYETHYLENE HEX NIPPLES

Part #	Size	
28-623B	1/2 x 1/4"	----
28-624B	1/2 x 3/8"	----
28-628B	3/4 x 3/8"	----
28-625B	3/4 x 1/2"	----

W



NYLON REDUCING HEX NIPPLES

Part #	Size	
28-620W	1/4 x 1/8"	----
28-621W	3/8 x 1/8"	----
28-622W	3/8 x 1/4"	----
28-623W	1/2 x 1/4"	----
28-624W	1/2 x 3/8"	----
28-628W	3/4 x 3/8"	----
28-625W	3/4 x 1/2"	----
28-663W	1-1/4 x 1"	36100804

P = Polypropylene
W = White Nylon
B = Black Polyethylene

COUPLING

P

POLYETHYLENE COUPLINGS

Part #	Size	
28-761P	1/4"	----
28-762P	3/8"	----
28-763P	1/2"	----
28-764P	3/4"	----

W

NYLON COUPLINGS

Part #	Size	
28-761W	1/4"	----
28-762W	3/8"	----
28-763W	1/2"	----
28-764W	3/4"	----
28-765W	1"	----
28-803W	1-1/4"	----
28-767W	1-1/2"	----
28-768W	2"	----

Thank you... motion sensor hand towel machine. You never work, so I just end up looking like I'm waving hello to a wall robot.

-Jimmy Fallon

PIPE CAP

W

NYLON CAPS

Part #	Size	
28-640W	1/4"	----
28-641W	3/8"	----
28-642W	1/2"	----
28-643W	3/4"	----

PLASTIC BULKHEAD FITTINGS

P

20% Glass Filled Polypropylene w/ Santoprene Gasket

Part #	Fpt	Hole	
28-693P	1/2"	1-3/8"	----
28-694P	3/4"	1-3/8"	----
28-695P	1"	1-3/4"	----
28-696P	1-1/4"	2"	----
28-697P	1-1/2"	3"	----
28-698P	2"	3"	----
28-699P	3"	4-1/2"	----

P = Polypropylene
W = White Nylon
B = Black Polyethylene

MALE ADAPTERS

B

POLYETHYLENE BARB X MALE PIPE

Part #	Size	
33-002B	3/16 x 1/8"	----
33-003B	3/16 x 1/4"	----
33-004B	1/4 x 1/8"	----
33-005B	1/4 x 1/4"	----
33-006B	1/4 x 3/8"	----
33-007B	1/4 x 1/2"	----
33-008B	5/16 x 1/8"	----
33-009B	5/16 x 1/4"	----
33-012B	3/8 x 1/4"	----
33-013B	3/8 x 3/8"	----
33-014B	3/8 x 1/2"	----
33-026B	3/8 x 3/4"	----
33-015B	1/2 x 1/4"	----
33-016B	1/2 x 3/8"	----
33-017B	1/2 x 1/2"	----
33-018B	1/2 x 3/4"	----
33-019B	5/8 x 3/8"	----
33-020B	5/8 x 1/2"	----
33-021B	5/8 x 3/4"	----
33-022B	3/4 x 1/2"	----
33-023B	3/4 x 3/4"	----
33-024B	1 x 3/4"	----
33-025B	1 x 1"	----

P

POLYPROPYLENE HOSE BARB
Hose ID x MIP

Part #	Size	
33-012P	3/8 x 1/4"	----
33-013P	3/8 x 3/8"	----
33-014P	3/8 x 1/2"	----
33-015P	1/2 x 1/4"	----
33-016P	1/2 x 3/8"	----
33-017P	1/2 x 1/2"	----
33-018P	1/2 x 3/4"	----
33-303P	1/2" x 1"	----
33-020P	5/8 x 1/2"	----
33-022P	3/4 x 1/2"	----
33-023P	3/4 x 3/4"	----
33-000P	3/4 x 1"	----
33-024P	1 x 3/4"	----
33-025P	1 x 1"	----
33-323P	3" x 3"	----

PLASTIC BARBS

W

NYLON BARB MALE ADAPTERS
Hose ID x MIP

Part #	Size	
33-002W	3/16 x 1/8"	----
33-003W	3/16 x 1/4"	----
33-004W	1/4 x 1/8"	----
33-005W	1/4 x 1/4"	----
33-006W	1/4 x 3/8"	----
33-007W	1/4 x 1/2"	----
33-380W	1/4 x 3/4"	----
33-008W	5/16 x 1/8"	----
33-009W	5/16 x 1/4"	----
33-010W	5/16 x 3/8"	----
33-011W	3/8 X 1/8"	----
33-012W	3/8 x 1/4"	----
33-013W	3/8 x 3/8"	----
33-014W	3/8 x 1/2"	----
33-026W	3/8 x 3/4"	----
33-015W	1/2 x 1/4"	----
33-016W	1/2 x 3/8"	----
33-017W	1/2 x 1/2"	----
33-018W	1/2 x 3/4"	----
33-303W	1/2" x 1"	----
33-019W	5/8 x 3/8"	----
33-020W	5/8 x 1/2"	----
33-021W	5/8 x 3/4"	----
33-306W	3/4" x 3/8"	----
33-022W	3/4 x 1/2"	----
33-023W	3/4 x 3/4"	----
33-000W	3/4 x 1"	----
33-318W	3/4" x 1-1/4"	----
33-319W	3/4" x 1-1/2"	----
33-307W	1" x 1/2"	----
33-024W	1 x 3/4"	----
33-025W	1 x 1"	----
33-029W	1 x 1-1/4"	----
33-320W	1" x 1-1/2"	----
33-349W	1-1/4" x 3/4"	----
33-028W	1-1/4 x 1"	----
33-030W	1-1/4 x 1-1/4"	----
33-032W	1-1/4 x 1-1/2"	----
33-321W	1-1/2" x 1-1/4"	----
33-033W	1-1/2 x 1-1/2"	----
33-322W	2" x 1-1/2"	----
33-035W	2 x 2"	----

ELBOWS

B

POLYETHYLENE ELBOWS
Hose ID x MALE PIPE

Part #	Size	
33-308B	3/16 x 1/8	----
33-038B	1/4 x 1/8	----
33-039B	1/4 x 1/4	----
33-309B	1/4 x 3/8	----
33-046B	3/8 x 1/8	----
33-041B	3/8 x 1/4	----
33-042B	3/8 x 3/8	----
33-047B	3/8 x 1/2	----
33-043B	1/2 x 3/8	----
33-311B	1/2 x 1/2	----
33-385B	1/2 x 3/4	----
33-044B	5/8 x 3/8	----
33-045B	5/8 x 1/2	----
33-312B	5/8 x 3/4	----
33-313B	3/4 x 1/2	----
33-314B	3/4 x 3/4	----
33-316B	1 x 1	----

P

POLYPROPYLENE BARB ELBOW

Part #	Size	
33-048P	1/2 x 1/4	----
33-311P	1/2 x 1/2	----
33-385P	1/2 x 3/4	----
33-313P	3/4 x 1/2	----
33-314P	3/4 x 3/4	----
33-316P	1 x 1	----
33-334P	1-1/4 x 1	----
33-461P	1-1/4 x 1-1/4	----
33-463P	1-1/2 x 1-1/2	----

W

NYLON BARB X MIP ELBOWS

Part #	Size	
33-381W	3/16 x 1/4	----
33-038W	1/4 x 1/8	----
33-039W	1/4 x 1/4	----
33-309W	1/4 x 3/8	----
33-351W	1/4 x 1/2	----
33-040W	5/16 x 1/4	----
33-310W	5/16 x 3/8	----
33-046W	3/8 x 1/8	----
33-041W	3/8 x 1/4	----
33-042W	3/8 x 3/8	----
33-047W	3/8 x 1/2	----
33-384W	3/8 x 3/4	----
33-048W	1/2 x 1/4	----
33-043W	1/2 x 3/8	----
33-311W	1/2 x 1/2	----
33-385W	1/2 x 3/4	----
33-044W	5/8 x 3/8	----
33-045W	5/8 x 1/2	----
33-312W	5/8 x 3/4	----
33-329W	5/8" x 1"	----
33-313W	3/4 x 1/2	----
33-314W	3/4 x 3/4	----
33-315W	3/4 x 1	----
33-386W	1x3/4	----
33-316W	1 x 1	----
33-460W	1 x 1-1/4	----
33-461W	1-1/4 x 1-1/4	----
33-462W	1-1/2 x 1-1/4	----
33-463W	1-1/2 x 1-1/2	----
33-464W	2 x 2	----

P = Polypropylene
W = White Nylon
B = Black Polyethylene

HOSE BARB X FE ADAPTERS

B

POLYETHYLENE ADAPTER
Hose ID x FIP

Part #	Size	
33-053B	1/4 x 1/4"	----

W

NYLON ADAPTER
Barb x FIP

Part #	Size	
33-052W	1/4 x 1/8"	----
33-053W	1/4 x 1/4"	----
33-058W	3/8 x 1/4"	----
33-059W	3/8 x 3/8"	----
33-060W	3/8 x 1/2"	----
33-442W	3/8 x 3/4"	----
33-066W	1/2 x 1/4"	----
33-062P	1/2 x 3/8"	----
33-061W	1/2 x 1/2"	----
33-067W	1/2 x 3/4"	----
33-068W	5/8 x 1/2"	----
33-063W	5/8 x 3/4"	----
33-064W	3/4 x 1/2"	----
33-065W	3/4 x 3/4"	----

HOSE BARB X FE ELBOW

P

W

NYLON ELBOW
Hose ID x Female Pipe

Part #	Size	
33-342W	3/8 x 1/2"	----
33-402W	1/2 x 3/8"	----
33-403W	1/2 x 3/4"	----
33-343P	1/2 x 1/2"	----
33-343W	1/2 x 1/2"	----
33-344P	5/8 x 3/4"	----
33-344W	5/8 x 3/4"	----
33-470W	5/8 x 1/2"	----
33-345W	3/4 x 1/2"	----
33-471W	3/4 x 3/4"	----
33-471P	3/4 x 3/4"	----

UNION ELBOWS

B

POLYETHYLENE ELBOW

Part #	Size	
33-390B	1/4	----
33-391B	3/8	----
33-394B	1/2	----
33-395B	5/8	----
33-396B	3/4	----

W

NYLON ELBOW

Part #	Size	
33-390W	1/4	----
33-391W	3/8	----
33-394W	1/2	----
33-395W	5/8	----
33-396W	3/4	----
33-397W	1	----
33-398W	1-1/4	----
33-399W	1-1/2	----
33-389W	2	----

SPLICERS

B

POLYETHYLENE SPLICER

Part #	Size	
33-091B	1/8	----
33-092B	3/16	----
33-093B	1/4	----
33-095B	3/8	----
33-096B	1/2	----
33-097B	5/8	----
33-098B	3/4	----

POLYPROPYLENE SPLICER

Part #	Size	
33-095P	3/8	----
33-096P	1/2	----
33-098P	3/4	----
33-099P	1	----

SPLICERS

W

NYLON SPLICES

Part #	Size	
33-091W	1/8	----
33-092W	3/16	----
33-093W	1/4	----
33-094W	5/16	----
33-095W	3/8	----
33-096W	1/2	----
33-097W	5/8	----
33-098W	3/4	----
33-099W	1	----
33-480W	1-1/4	----
33-481W	1-1/2	----
33-482W	2	----

REDUCING SPLICERS

B

POLYETHYLENE SPLICES

Part #	Size	
33-406B	3/8 x 1/4	----
33-407B	1/2 x 1/4	----
33-408B	1/2 x 3/8	----
33-410B	5/8 x 1/2	----

W

NYLON SPLICES

Part #	Size	
33-079W	1/4 x 1/8	----
33-347W	1/4 x 3/16	----
33-406W	3/8 x 1/4	----
33-348W	3/8 x 5/16	----
33-407W	1/2 x 1/4	----
33-408W	1/2 x 3/8	----
33-409W	5/8 x 3/8	----
33-410W	5/8 x 1/2	----
33-089W	3/4 x 1/2	----

PLASTIC BARBS

TEES BARBED ON ALL SIDES

B

POLYETHYLENE TEE

Part #	Size	
33-415B	1/8	----
33-418B*	3/16	----
33-420B	3/16	----
33-422B	1/4	----
33-426B	5/16	----
33-429B	3/8	----
33-433B	1/2	----
33-436B	5/8	----
33-437B	3/4	----
33-438B	1	----

P

POLYPROPYLENE TEE

Part #	Size	
33-429P	3/8	----
33-440P	1-1/2	----

ALL HOSE BARB "Y"

P

POLYPROPYLENE WYE

Part #	Size	
33-300P*	1/4"	----
33-301P*	3/8"	----
33-302P*	1/2"	----

**Natural Polypro*

W

NYLON WYE

Part #	Size	
33-301W	3/8"	----

W

NYLON TEE

Part #	Size	
33-415W	1/8	----
33-417W	5/32	----
33-420W	3/16	----
33-422W	1/4	----
33-426W	5/16	----
33-429W	3/8	----
33-433W	1/2	----
33-436W	5/8	----
33-437W	3/4	----
33-438W	1	----
33-439W	1-1/4	----
33-440W	1-1/2	----
33-441W	2	----

REDUCING TEES

B

POLYETHYLENE TEE

Part #	Size	
33-423B	3/8 x 3/8 x 1/4	----
33-430B	1/2 x 1/2 x 3/8	----
33-432B	3/8 x 3/8 x 1/2	----
33-434B	1/2 x 1/2 x 5/8	----
33-435B	3/4 x 3/4 x 1/2	----

W



NYLON TEE

Part #	Size	
33-430W	1/2 x 1/2 x 3/8	----
33-431W	5/8 x 5/8 x 3/8	----
33-432W	3/8 x 3/8 x 1/2	----
33-435W	3/4 x 3/4 x 1/2	----

MALE BRANCH TEE

W

NYLON BRANCH TEE

Part #	Size	
33-448W	1/4 x 1/4	----
33-450W	3/8 x 1/4	----
33-451W	3/8 x 3/8	----
33-453W	1/2 x 1/4	----
33-454W	1/2 x 3/8	----
33-455W	1/2 x 1/2	----
33-458W	5/8" x 3/4"	----
33-456W	3/4 x 3/4	----

Thank you, hard taco shells, for surviving the long journey from factory, to supermarket, to my plate and then breaking the moment I put something inside you. Thank you.

- Jimmy Fallon

PLASTIC GARDEN HOSE FITTINGS

FITTINGS WITH GARDEN HOSE THREAD

GARDEN HOSE CAP

- Washer not included

- White Nylon

P

Part #	Size	
30-103P	3/4"	----

GARDEN HOSE THREAD ADAPTERS

BARB X MALE GARDEN HOSE

- White Nylon

Part #	Size	
31-038	1/4"	----
31-039	3/8"	----
31-040	1/2"	----
31-041	5/8"	----
31-042	3/4"	----

Victorious warriors win first and then go to war, while defeated warriors go to war first and then seek to win.

- Sun Tzu

GARDEN HOSE ADAPTER INSERTS

- for assembly with 31-022

- White Nylon

Part #	Size	
31-030	1/4"	----
31-031	3/8"	----
31-032	1/2"	----
31-033	5/8"	----
31-034	3/4"	----
31-035	1/2" MPT	----

GARDEN HOSE NUT

- White Nylon

Part #	Size	
31-022	3/4"	----
31-023	3/4" FIP	----

MALE GARDEN HOSE X FEMALE PIPE

- White Nylon

Part #	Size	
31-067	MGH X 1/4	----
31-068	MGH X 1/2 FIP	----
31-069	MGH X 3/4	----

FEMALE GARDEN HOSE X MALE PIPE

- White Nylon

Part #	Size	
31-093	FGH X 3/4 MPT	----
31-095	FGH X 3/4 MGH	----

FEMALE GARDEN HOSE X FEMALE PIPE

- White Nylon

Part #	Size	
31-096	FGH X 1/2 FIP	----
31-097	FGH X 3/4 FIP	----

MALE GARDEN HOSE X MALE PIPE

- White Nylon

Part #	Size	
31-055	GHT X 3/8 MPT	----
31-058	GHT X 1/2 MPT	----
31-063	GHT X 3/4 MPT	----
31-064	GHT X 1 MPT	----

PLASTIC COMPRESSION

PLASTIC COMPRESSION FITTINGS

Corrosion resistant thermoresins designed to resist vibration, provide good electrical insulation, low flow resistance, and resistance to scale buildup.

The letter on the end of part no. denotes the type.

N = Nylon
P = Polypropylene

Standard nut and sleeves will be provided (sleeve is integral part of nut). Other sizes available upon request.

FDA and NSF Listed

UNION & REDUCING UNION CONNECTORS

P

Part #	Size	
17-064P	1/4"	----
17-066P	3/8"	----
17-079P	3/8" x 1/4"	----
17-068P	1/2"	----
17-081P	1/2" x 3/8"	----

• Nylon

Part #	Size	
17-064N	1/4"	----
17-065N	5/16"	----
17-078N	5/16" x 1/4"	----
17-066N	3/8"	----
17-079N	3/8" x 1/4"	----
17-068N	1/2"	----

BULKHEAD UNIONS

• Nylon

Part #	Size	
17-088N	1/4"	----
17-090N	3/8"	----
17-091N	1/2"	----

UNION TEES

• Nylon

Part #	Size	
17-103N	1/4"	----
17-105N	3/8"	----
17-106N	1/2"	----

UNION ELBOWS

P

Part #	Size	
17-124P	1/4"	----
17-126P	3/8"	----
17-127P	1/2"	----

• Nylon

Part #	Size	
17-124N	1/4"	----
17-126N	3/8"	----

FEMALE CONNECTORS

P

Part #	Size	
17-145P	1/4 x 1/8	----
17-153P	3/8 x 1/4	----
17-154P	3/8 x 3/8	----
17-158P	1/2 x 3/8	----
17-159P	1/2 x 1/2	----

• Nylon

Part #	Size	
17-146N	1/4 x 1/4	----
17-153N	3/8 x 1/4	----
17-154N	3/8 x 3/8	----

MALE CONNECTORS

P

Part #	Size	
17-179P	1/4 x 1/8	----
17-180P	1/4 x 1/4	----
17-188P	3/8 x 1/4	----
17-189P	3/8 x 3/8	----
17-190P	3/8 x 1/2	----
17-193P	1/2 x 1/4	----
17-194P	1/2 x 3/8	----
17-195P	1/2 x 1/2	----

• Nylon

Part #	Size	
17-176N	1/8 x 1/8"	
17-179N	1/4 x 1/8	----
17-180N	1/4 x 1/4	----
17-188N	3/8 x 1/4	----
17-189N	3/8 x 3/8	----
17-190N	3/8 x 1/2	----
17-193N	1/2 x 1/4	----
17-194N	1/2 x 3/8	----
17-195N	1/2 x 1/2	----

MALE ELBOWS

P

Part #	Size	
17-225P	1/4 x 1/4	----
17-233P	3/8 x 1/4	----
17-234P	3/8 x 3/8	----
17-237P	1/2 x 3/8	----
17-238P	1/2 x 1/2	----

• Nylon

Part #	Size	
17-224N	1/4 x 1/8	----
17-225N	1/4 x 1/4	----
17-233N	3/8 x 1/4	----
17-234N	3/8 x 3/8	----
17-237N	1/2 x 3/8	----
17-238N	1/2 x 1/2	----

PLASTIC PUSH-IN TUBE FITTINGS

Manufactured from safe, non-toxic materials meeting the requirements of the US FDA, WRAS, ANSI/NSF-51, 61, and SK Zert. Our products are widely used in water purification, food/beverage and pneumatic systems.

- Function & Quality : provides quick and convenient assembly - saving time & expense. Our ISO9001, 14001 registered quality system ensures our customers a superior level of product quality. Defects are easily detectable and maintenance is easy with its easy dismantling for access.
- Collet Design : Unique oval collet design is superior and more practical.
- Applications : Beyond water and food use, fittings can be used with air, gases, vacuum, & liquids. And all connections can be assembled & disassembled repeatedly.
- Material : Grey Acetal Copolymer, also known as POM. Highly durable and resistant to fatigue and creep. It has high resistance to a wide range of organic & inorganic chemicals and detergents. Not recommended for use with strong acids or repeated exposure to strong oxidizers. (polypropylene may be subbed)

SIZE / Temperature	Small Size						Large Size				
	5/32"	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	7/8"			28mm
	4mm	5mm	6mm	8mm	10mm	12mm	15mm	16mm	18mm	22mm	
1°C (34°F)	16bar (230PSI)				11bar (170PSI)		11bar (170PSI)				
20°C (68°F)	16bar (230PSI)				11bar (170PSI)		11bar (170PSI)				
65°C (150°F)	10bar (150PSI)				7bar (100PSI)		7bar (100PSI)				

- Fittings are not recommended for use with liquids other than water and food or beverage products.
- Do not use pipe dope or other liquid thread sealers. Use only Teflon tape to seal threaded connections.
- After assembling a tube connection, tug with moderate force to check for proper gripping of the tube.
- Before disassembling tube connections, always verify that pressure has been removed from the system.

UNION CONNECTOR

Part #	Tube OD	
20-018P	5/32"	----
20-702P	3/16"	----
20-019P	1/4"	----
20-020P	3/8"	----
20-021P	1/2"	----

UNION TEE

Part #	Tube OD	
20-028P	1/4"	----
20-029P	3/8"	----
20-030P	1/2"	----

REDUCING ELBOW

Part #	Tube OD	Tube OD	
20-733P	3/8"	3/16"	----
20-734P	3/8"	1/4"	----
20-736P	1/2"	3/8"	----

REDUCING UNION

Part #	Tube OD	Tube OD	
20-750P	1/4"	3/16"	----
20-754P	3/8"	3/16"	----
20-755P	3/8"	1/4"	----
20-756P	3/8"	5/16"	----
20-758P	1/2"	3/8"	----

REDUCING BRANCH TEE

Part #	Tube OD	Tube OD	
20-725P	3/8"	1/4"	----
20-724P	1/2"	3/8"	----

FEMALE CONNECTOR

Part #	Tube OD	Thread NPTF	
20-993P	1/4"	1/8"	----
20-035P	1/4"	1/4"	----
20-944P	3/8"	1/8"	----
20-036P	3/8"	1/4"	----

BULKHEAD UNION

Part #	Tube OD	
20-127P	1/4"	----
20-128P	3/8"	----
20-129P	1/2"	----

UNION ELBOW

Part #	Tube OD	
20-152P	1/4"	----
20-153P	3/8"	----
20-154P	1/2"	----

PLASTIC PUSH-IN

MALE CONNECTOR

Part #	Tube OD	Thread NPTF	
20-050P	5/32"	1/8"	----
20-054P	1/4"	1/8"	----
20-055P	1/4"	1/4"	----
20-056P	1/4"	3/8"	----
20-057P	3/8"	1/8"	----
20-058P	3/8"	1/4"	----
20-059P	3/8"	3/8"	----
20-062P	3/8"	1/2"	----
20-061P	1/2"	3/8"	----
20-063P	1/2"	1/2"	----

STEM ADAPTER

Part #	Tube OD	Thread NPTF	
20-524P	1/4"	1/8"	----
20-525P	1/4"	1/4"	----
20-528P	3/8"	1/4"	----
20-529P	3/8"	3/8"	----

REDUCER

Part #	Tube OD	Tube OD	
20-512P	3/8"	1/4"	----
20-763P	3/8"	5/16"	----
20-514P	1/2"	3/8"	----

FIXED ELBOW

Part #	Tube OD	Thread NPTF	
20-068P	1/4"	1/8"	----
20-069P	1/4"	1/4"	----
20-070P	1/4"	3/8"	----
20-072P	3/8"	1/4"	----
20-073P	3/8"	3/8"	----

PLUG-IN ELBOW

Part #	Tube OD	Tube OD	
20-740P	5/32"	5/32"	----
20-742P	1/4"	1/4"	----
20-745P	3/8"	1/4"	----
20-747P	3/8"	3/8"	----
20-748P	1/2"	1/2"	----

2-WAY DIVIDER

Part #	Tube OD	List Price
20-776P	5/16"	----
20-777P	3/8"	----

PLUG

Part #	Tube OD	
20-876P	5/32"	----
20-878P	1/4"	----
20-880P	3/8"	----
20-881P	1/2"	----

TUBE END STOP

Part #	Tube OD	
20-925P	1/4"	----
20-927P	3/8"	----

PL X PL

Part #	Tube OD	
20-900P	1/4"	----
20-901P	3/8"	----

PL X MALE NPTF

Part #	Tube OD	Thread NPTF	
20-904P	1/4"	1/4"	----
20-905P	3/8"	3/8"	----

CHECK VALVE

Part #	Tube OD	
20-779P	3/8"	----

See Polyethylene Tubing on pages 332

HOSE ACCESSORIES

HOSE ACCESSORIES

CAM AND GROOVE

ALUMINIUM

POLYPROPLYENE

STAINLESS STEEL

BRASS

COMBINATION HOSE NIPPLES

FIRE HOSE FITTINGS

UNIVERSAL/ GROUND JOINT COUPLINGS



WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

ALUMINUM

SEE PAGES 332 FOR JUMP SIZES IN ALUMINUM

MALE ADAPTER X FEMALE NPT

TYPE A

Part#	Size	
61-911	3/4"	----
61-912	1"	----
61-913	1-1/4"	----
61-914	1-1/2"	----
61-915	2"	----
61-916	2-1/2"	----
61-917	3"	----
61-918	4"	----
61-919	5”	----
61-920	6”	----
61-910	8”	----

FEMALE COUPLER X MALE NPT

TYPE B

Part#	Size	
61-921	3/4"	----
61-922	1"	----
61-923	1-1/4"	----
61-924	1-1/2"	----
61-925	2"	----
61-926	2-1/2"	----
61-927	3"	----
61-928	4"	----
61-929	5”	----
61-930	6”	----

FEMALE COUPLER X HOSE SHANK

TYPE C

Part#	Size	
61-931	3/4"	----
61-932	1"	----
61-933	1-1/4"	----
61-934	1-1/2"	----
61-935	2"	----
61-936	2-1/2"	----
61-937	3"	----
61-938	4"	----
61-939	5”	----
61-940	6"	----
61-907	8"	----

FEMALE COUPLER X FEMALE NPT

TYPE D

Part#	Size	
61-941	3/4"	----
61-942	1"	----
61-943	1-1/4"	----
61-944	1-1/2"	----
61-945	2"	----
61-946	2-1/2"	----
61-947	3"	----
61-948	4"	----
61-950	5”	----
61-949	6”	----
61-904	8"	----

MALE ADAPTER X HOSE SHANK

TYPE E

Part#	Size	
61-951	3/4"	----
61-952	1"	----
61-953	1-1/4"	----
61-954	1-1/2"	----
61-955	2"	----
61-956	2-1/2"	----
61-957	3"	----
61-958	4"	----
61-959	5”	----
61-905	6”	----
61-906	8"	----

MALE ADAPTER X MALE NPT

TYPE F

Part#	Size	
61-961	3/4"	----
61-962	1"	----
61-963	1-1/4"	----
61-964	1-1/2"	----
61-965	2"	----
61-966	2-1/2"	----
61-967	3"	----
61-968	4"	----
61-970	5”	----
61-969	6”	----
61-999	8”	----

DUST CAP

TYPE DC

Part#	Size	
61-971	3/4"	----
61-972	1"	----
61-973	1-1/4"	----
61-974	1-1/2"	----
61-975	2"	----
61-976	2-1/2"	----
61-977	3"	----
61-978	4"	----
61-980	5”	----
61-979	6”	----
61-998	8”	----

DUST PLUG

TYPE DP

Part#	Size	
61-981	3/4"	----
61-982	1"	----
61-983	1-1/4"	----
61-984	1-1/2"	----
61-985	2"	----
61-986	2-1/2"	----
61-987	3"	----
61-988	4"	----
61-909	5”	----
61-908	6”	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

ALUMINUM JUMP SIZES

MALE ADAPTER X MALE ADAPTER

ALUMINUM SPOOL ADAPTER

Part#	Size	
61-872	1”	----
61-873	1-1/2”	----
61-874	2”	----
61-875	2” x 3”	----
61-876	2-1/2”	----
61-877	3”	----
61-878	3” x 4”	----
61-879	4”	----

FEMALE COUPLER X FEMALE COUPLER

ALUMINUM TYPE DD

Part#	Size	
619-440	1-1/2”	----
619-450	2”	----
619-470	3”	----
619-480	4”	----

FEMALE COUPLER X MALE ADAPTER

ALUMINUM TYPE DA

Part#	Size	
619-001	1-1/2” x 1”	----
619-002	1-1/2” x 2”	----
619-003	2” x 1-1/2”	----
619-004	2” x 3”	----
619-005	2” x 4”	----
619-006	3” x 1-1/2”	----
619-007	3” x 2”	----
619-008	3” x 4”	----
619-009	4” x 2”	----
619-010	4” x 3”	----
619-011	4” x 6”	----
619-012	6” x 4”	----

MALE ADAPTER X FEMALE NPT

ALUMINUM JUMP SIZE A

Part#	Size	
61-851	2” x 3”	----
61-853	3” x 4”	----
61-854	4” x 3”	----

FEMALE COUPLER X MALE NPT

ALUMINUM JUMP SIZE B

Part#	Size	
61-859	3” x 2”	----
61-860	3” x 4”	----
61-861	4” x 3”	----

FEMALE COUPLER X FEMALE NPT

ALUMINUM JUMP SIZE D

Part#	Size	
61-867	3” x 2”	----
61-868	4” x 3”	----

MALE ADAPTER X MALE NPT

ALUMINUM JUMP SIZE F

Part#	Size	
61-870	3” x 2”	----
61-871	3” x 4”	----

TYPE A MALE COUPLER X FIP
TYPE B FEMALE COUPLER X MIP
TYPE C FEMALE COUPLER X HOSE SHANK
TYPE D FEMALE COUPLER X FIP
TYPE E MALE COUPLER X HOSE SHANK
TYPE F MALE COUPLER X MIP
TYPE DC DUST CAP
TYPE DP DUST PLUG

TEMPERATURE RATINGS								
Gasket Material	Temperature Range in °F							
	500	400	300	275	250	200	150	0
Buna N				x				-40
Neoprene					x			-65
*Vitron A		x						-40
Silicone	x							-30
*Teflon	x							-40
Nat. Rubber						x		-60
Butyl			x					-40
Hypalon					x			-65
EPDM							x	

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

POLYPROPYLENE

MALE ADAPTER X FEMALE NPT

TYPE A

Part#	Size	
35-910	1/2"	----
35-911	3/4"	----
35-912	1"	----
35-913	1-1/4"	----
35-914	1-1/2"	----
35-915	2"	----
35-917	3"	8.47

FEMALE COUPLER X MALE NPT

TYPE B

Part#	Size	
35-920	1/2"	----
35-921	3/4"	----
35-922	1"	----
35-923	1-1/4"	----
35-924	1-1/2"	----
35-925	2"	----
35-927	3"	----

FEMALE COUPLER X HOSE SHANK

TYPE C

Part#	Size	
35-930	1/2"	----
35-931	3/4"	----
35-932	1"	----
35-933	1-1/4"	----
35-934	1-1/2"	----
35-935	2"	----
35-937	3"	----

FEMALE COUPLER X FEMALE NPT

TYPE D

Part#	Size	
35-940	1/2"	----
35-941	3/4"	----
35-942	1"	----
35-943	1-1/4"	----
35-944	1-1/2"	----
35-945	2"	----
35-947	3"	----

MALE ADAPTER X HOSE SHANK

TYPE E

Part#	Size	
35-950	1/2"	----
35-951	3/4"	----
35-952	1"	----
35-953	1-1/4"	----
35-954	1-1/2"	----
35-955	2"	----
35-957	3"	----

MALE ADAPTER X MALE NPT

TYPE F

Part#	Size	
35-960	1/2"	----
35-961	3/4"	----
35-962	1"	----
35-963	1-1/4"	----
35-964	1-1/2"	----
35-965	2"	----
35-967	3"	----

DUST CAP

TYPE DC

Part#	Size	
35-970	1/2"	----
35-971	3/4"	----
35-972	1"	----
35-973	1-1/4"	----
35-974	1-1/2"	----
35-975	2"	----
35-977	3"	----

DUST PLUG

TYPE DP

Part#	Size	
35-980	1/2"	----
35-981	3/4"	----
35-982	1"	----
35-983	1-1/4"	----
35-984	1-1/2"	----
35-985	2"	----
35-987	3"	----

316 STAINLESS STEEL

MALE ADAPTER X FEMALE NPT

TYPE A

Part#	Size	
63-911	3/4"	----
63-912	1"	----
63-913	1-1/4"	----
63-914	1-1/2"	----
63-915	2"	----
63-916	2-1/2"	----
63-917	3"	----
63-918	4"	----
63-919	5”	----

FEMALE COUPLER X MALE NPT

TYPE B

Part#	Size	
63-921	3/4"	----
63-922	1"	----
63-923	1-1/4"	----
63-924	1-1/2"	----
63-925	2"	----
63-926	2-1/2"	----
63-927	3"	----
63-928	4"	----
63-929	5”	----

FEMALE COUPLER X HOSE SHANK

TYPE C

Part#	Size	
63-931	3/4"	----
63-932	1"	----
63-933	1-1/4"	----
63-934	1-1/2"	----
63-935	2"	----
63-936	2-1/2"	----
63-937	3"	----
63-938	4"	----
63-939	5”	----

FEMALE COUPLER X FEMALE NPT

TYPE D

Part#	Size	
63-941	3/4"	----
63-942	1"	----
63-943	1-1/4"	----
63-944	1-1/2"	----
63-945	2"	----
63-946	2-1/2"	----
63-947	3"	----
63-948	4"	----
63-949	5”	----
63-950	6”	----

MALE ADAPTER X HOSE SHANK

TYPE E

Part#	Size	
63-951	3/4"	----
63-952	1"	----
63-953	1-1/4"	----
63-954	1-1/2"	----
63-955	2"	----
63-956	2-1/2"	----
63-957	3"	----
63-958	4"	----
63-959	5”	----
63-960	6”	----

MALE ADAPTER X MALE NPT

TYPE F

Part#	Size	
63-961	3/4"	----
63-962	1"	----
63-963	1-1/4"	----
63-964	1-1/2"	----
63-965	2"	----
63-966	2-1/2"	----
63-967	3"	----
63-968	4"	----
63-969	5”	----
63-999	6”	----

DUST CAP

TYPE DC

Part#	Size	
63-971	3/4"	----
63-972	1"	----
63-973	1-1/4"	----
63-974	1-1/2"	----
63-975	2"	----
63-976	2-1/2"	----
63-977	3"	----
63-978	4"	----
63-979	5”	----
63-980	6”	----

DUST PLUG
TYPE DP

Part#	Size	
63-981	3/4"	----
63-982	1"	----
63-983	1-1/4"	----
63-984	1-1/2"	----
63-985	2"	----
63-986	2-1/2"	----
63-987	3"	----
63-988	4"	----
63-989	6”	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

BRASS

MALE ADAPTER X FEMALE NPT

TYPE A

Part#	Size	
44-911	3/4"	----
44-912	1"	----
44-913	1-1/4"	----
44-914	1-1/2"	----
44-915	2"	----
44-916	2-1/2"	----
44-917	3"	----
44-918	4"	----
44-919	5”	----
44-920	6”	----

FEMALE COUPLER X MALE NPT

TYPE B

Part#	Size	
44-921	3/4"	----
44-922	1"	----
44-923	1-1/4"	----
44-924	1-1/2"	----
44-925	2"	----
44-926	2-1/2"	----
44-927	3"	----
44-928	4"	----
44-929	5”	----
44-930	6”	----

FEMALE COUPLER X HOSE SHANK

TYPE C

Part#	Size	
44-931	3/4"	----
44-932	1"	----
44-933	1-1/4"	----
44-934	1-1/2"	----
44-935	2"	----
44-936	2-1/2"	----
44-937	3"	----
44-938	4"	----
44-939	5”	----
44-940	6”	----

FEMALE COUPLER X FEMALE NPT

TYPE D

Part#	Size	
44-941	3/4"	----
44-942	1"	----
44-943	1-1/4"	----
44-944	1-1/2"	----
44-945	2"	----
44-946	2-1/2"	----
44-947	3"	----
44-948	4"	----
44-949	5”	----
44-950	6”	----

MALE ADAPTER X HOSE SHANK

TYPE E

Part#	Size	
44-951	3/4"	----
44-952	1"	----
44-953	1-1/4"	----
44-954	1-1/2"	----
44-955	2"	----
44-956	2-1/2"	----
44-957	3"	----
44-958	4"	----
44-959	5”	----
44-960	6”	----

MALE ADAPTER X MALE NPT

TYPE F

Part#	Size	
44-961	3/4"	----
44-962	1"	----
44-963	1-1/4"	----
44-964	1-1/2"	----
44-965	2"	----
44-966	2-1/2"	----
44-967	3"	----
44-968	4"	----
44-969	5”	----
44-970	6”	----

DUST CAP

TYPE DC

Part#	Size	
44-971	3/4"	----
44-972	1"	----
44-973	1-1/4"	----
44-974	1-1/2"	----
44-975	2"	----
44-976	2-1/2"	----
44-977	3"	----
44-978	4"	----
44-979	5”	----
44-980	6”	----

DUST PLUG

TYPE DP

Part#	Size	
44-981	3/4"	----
44-982	1"	----
44-983	1-1/4"	----
44-984	1-1/2"	----
44-985	2"	----
44-986	2-1/2"	----
44-987	3"	----
44-988	4"	----
44-989	5”	----
44-990	6”	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

STAINLESS STEEL AND BRASS JUMP SIZES

MALE ADAPTER X MALE ADAPTER

316 SS SPOOL ADAPTER

Part#	Size	
63-850	1”	----
63-851	1-1/2”	----
63-852	1-1/2” x 2”	----
63-853	2”	----
63-854	2” x 3”	----
63-855	3”	----
63-856	3” x 4”	----
63-857	4”	----

FEMALE COUPLER X FEMALE COUPLER

316 SS TYPE DD

Part#	Size	
639-440	1-1/2”	----
639-450	2”	----
639-470	3”	----
639-480	4”	----

FEMALE COUPLER X MALE ADAPTER

316 SS TYPE DA

Part#	Size	
639-001	2” x 1-1/2”	----
639-002	3” x 2”	----
639-003	4” x 3”	----
639-004	6” x 4”	----

MALE ADAPTER X MALE ADAPTER

BRASS SPOOL ADAPTER

Part#	Size	
44-212	1-1/2”	----
44-213	2”	----
44-214	2-1/2”	----
44-215	3”	----
44-216	4”	----

FEMALE COUPLER X MALE ADAPTER

BRASS TYPE DA

Part#	Size	
449-450	2” x 3”	----
449-470	3” x 2”	----
449-480	4” x 2”	----
449-481	4” x 3”	----
449-482	6” x 4”	----

INVESTMENT CAST STAINLESS STEEL HANDLE, RING & PIN

Part#	Size	
61-447	3/4”	----
61-448	1”	----
61-449	1-1/4” - 2-1/2”	----
61-452	3” & 4”	----
61-454	6”	----

FORGED BRASS HANDLE - RING & PIN STEEL

Part#	Size	
61-455	3/4”	----
61-450	1”	----
61-451	1-1/4” - 2-1/2”	----
61-453	3” & 4”	----
61-457	6”	----

SAFETY CLIP

Part #	Size	
66-015	1-1/4" - 2-1/2"	----

BUNA-N GASKET

Part#	Size	
BG-50	1/2”	----
BG-75	3/4”	----
BG-100	1”	----
BG-125	1-1/4”	----
BG-150	1-1/2”	----
BG-200	2”	----
BG-250	2-1/2”	----
BG-300	3”	----
BG-400	4”	----
BG-500	5”	----
BG-600	6”	----
BG-800	8”	----

SILICONE GASKET

Part#	Size	
SG300	3"	----
SG400	4"	----

VITON GASKET

Part#	Size	
VG100	1"	----
VG150	1-1/2"	----
VG200	2"	----
VG250	2-1/2"	----
VG300	3"	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

KING NIPPLES

STEEL HOSE NIPPLES

• Black

(Barb x Male Pipe)

Part #	Hose Size	
973-850	1/2"	----
973-851	3/4"	----
973-852	1"	----
973-853	1-1/4"	----
973-854	1-1/2"	----
973-855	2"	----
973-856	2-1/2"	----
973-857	3"	----
973-858	4"	----
973-861	8"	

ZINC PLATED STEEL

Part #	Size	
973-870	1/2"	----
973-871	3/4"	----
973-872	1"	----
973-873	1-1/4"	----
973-874	1-1/2"	----
973-875	2"	----
973-876	2-1/2"	----
973-877	3"	----
973-878	4"	----
973-879	5"	----
973-880	6"	----
973-881	8"	----

ZINC PLATED STEEL EXPANDER & REDUCER

NEW

Hose x MIP

Part #	Size	
973-862	3/4 x 1	----
973-884	1 x 3/4	----
973-863	1 x 1-1/4	----
973-885	1-1/4 x 1	----
973-886	1-1/4 x 1-1/2	----
973-887	1-1/2 x 1-1/4	----
973-864	1-1/2 x 2	----
973-888	2 x 1-1/2	----
973-859	2 x 2-1/2	----
973-869	2-1/2 x 2	----
973-865	2-1/2 x 3	----
973-867	3 x 2-1/2	----
973-866	3 x 4	----
973-868	4 x 3	----

316 STAINLESS STEEL

Part #	Size	
973-700	1/2"	----
973-701	3/4"	----
973-702	1"	----
973-703	1-1/4"	----
973-704	1-1/2"	----
973-705	2"	----
973-706	2-1/2"	----
973-707	3"	----
973-708	4"	----

BRASS

• Lead Free

Part #	Size	
973-600	1/2"	----
973-601	3/4"	----
973-602	1"	----
973-603	1-1/4"	----
973-604	1-1/2"	----
973-605	2"	----
973-606	2-1/2"	----
973-607	3"	----

ALUMINUM

Part #	Size	
973-620	1/2"	----
973-621	3/4"	----
973-622	1"	----
973-623	1-1/4"	----
973-624	1-1/2"	----
973-625	2"	----
973-626	2-1/2"	----
973-627	3"	----
973-628	4"	----

MENDERS

STEEL HOSE MENDERS

Part #	Hose Size	
973-890	1/2"	----
973-891	3/4"	----
973-892	1"	----
973-893	1-1/4"	----
973-894	1-1/2"	----
973-895	2"	----

PLATED STEEL MENDER

• Zinc

Part #	Size	
973-650	3/8"	----
973-651	1/2"	----
973-652	3/4"	----
973-653	1"	----
973-654	1-1/4"	----
973-655	1-1/2"	----
973-656	2"	----
973-657	2-1/2"	----
973-658	3"	----
973-659	4"	----

316 STAINLESS STEEL HOSE MENDER

Part #	Size	
73-670	3/4"	----
73-671	1"	----
73-672	1-1/4"	----
73-673	1-1/2"	----
73-674	2"	----

• Lead Free

BRASS HOSE MENDER

Part #	Size	
73-983	3/4"	----
73-984	1"	----
73-985	1-1/4"	----
73-986	1-1/2"	----
73-987	2"	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

MALE NPT ENDS

• Twist claw/ universal/ chicago

• Malleable iron
• ISO PSI

* Safety clip included

Part #	Size	
66005	3/8"	----
66006	1/2"	----
66007	3/4"	----
66008	1"	----

WASHER

Part #	
66000	----

FEMALE NPT ENDS

* Safety clip included

Part #	Size	
66009	3/8"	----
66010	1/2"	----
66011	3/4"	----
66012	1"	----

HOSE END

* Safety clip included

Part #	Size	
66001	3/8"	----
66002	1/2"	----
66003	3/4"	----
66004	1"	----

SAFETY CLIP

Part #	Size	
66-015	1-1/4" - 2-1/2"	----

TRIPLE CONNECTIONS

Part #	
66013	----

FOR SHOP USE ONLY,
NOT FOR STEAM OR
HYDRAULIC APPLICATIONS

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

GROUND JOINT COUPLINGS

For high pressure air and water service, steam, sanitary, high pressure spray, LPG and anhydrous ammonia service, petroleum products and chemicals: All parts plated malleable iron. Insert and spud may be either steel or malleable iron. NPT Male and Female spud. Female wing nut-to-spud connection is NPSM ground joint.

HEAVY DUTY COUPLINGS - GROUND JOINT TYPE - PLATED

HOSE STEM W/ WING NUT AND FEMALE SPUD

Part #	Size	
73-003	1/2"	----
73-004	3/4"	----
73-005	1"	----
73-006	1-1/4"	----
73-007	1-1/2"	----
73-008	2"	----
73-009	2-1/2"	----
73-010	3"	----
73-011	4"	----

HOSE STEM ONLY

Part #	Size	
73-023	1/2"	----
73-024	3/4"	----
73-025	1"	----
73-026	1-1/4"	----
73-027	1-1/2"	----
73-028	2"	----
73-029	2-1/2"	----
73-030	3"	----
73-031	4"	----

WING NUT ONLY

Part #	Size	
73-033	1/2"	----
73-035	1"	----
73-036	1-1/4"	----
73-037	1-1/2"	----
73-038	2"	----
73-039	2-1/2"	----
73-040	3"	----
73-041	4"	----

FEMALE SPUD ONLY

Part #	Size	
73-063	1/2"	----
73-064	3/4"	----
73-065	1"	----
73-066	1-1/4"	----
73-067	1-1/2"	----
73-068	2"	----
73-069	2-1/2"	----
73-070	3"	----
73-071	4"	----

MALE PIPE STEM ONLY (NPT)

Part #	Size	
73-043	1/2"	----
73-044	3/4"	----
73-045	1"	----
73-046	1-1/4"	----
73-047	1-1/2"	----
73-048	2"	----
73-049	2-1/2"	----
73-050	3"	----
73-051	4"	----

2, 4, 6 BOLT CLAMPS

Part #	Size	# Bolts	
73-056	3/4"	2	----
73-057	1"	4	----
73-058	1-1/2"	4	----
73-059	2"	4	----
73-060	3"	4	----

Danger: Failure or improper selection or improper use of hose couplings or related accessories can cause death, personal injury and property damage. Possible consequences of failure or improper selection or improper use of hose couplings or related accessories include but are not limited to:

- Coupling or parts thrown off at high speed.
- High velocity fluid discharge.
- Explosion or burning of the conveyed fluid.
- Contact with suddenly moving or falling objects that are to be held in position or moved by the conveyor fluid.
- Dangerously whipping hose.
- Contact with conveyed fluids that may be hot, cold, toxic or otherwise injurious.
- Sparking or explosion while paint or flammable liquid spraying.

Before selecting or using any of our products, it is important to check with our offices for more detailed specifications regarding use.

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

HYDRANT ADAPTERS - BRASS

FEMALE X MALE

Part #	Description	
444-011	1-1/2" NST x 3/4" GHT	----
444-000	2-1/2" NST x 3/4" GHT	----
444-001	2-1/2" NST x 3/4" NPT	----
444-002	2-1/2" NST x 1" NPT	----
444-005	2-1/2" NST x 1-1/2" NPT	----
444-007	2-1/2" NST x 2" NPSH	----
444-008	2-1/2" NST x 2" NPT	----
444-006	2-1/2" NST x 1-1/2" NST	----

FEMALE TO MALE HEX ADAPTER - BRASS

FEMALE X MALE

Part #	Description	
444-021	1-1/2" NST x 1-1/2" NPSH	----
444-023	1-1/2" NPT x 1-1/2" NPSH	----
444-020	1-1/2" NST x 1-1/2" NPT	----
444-318	2 NPT x 2-1/2" NST	----

DOUBLE MALE HEX NIPPLE - BRASS

Part #	Description	
444-042	1-1/2" NPT x 1-1/2" NPSH	----
444-040	1-1/2" NPT x 1-1/2" NST	----
444-048	2" NPT x 2-1/2" NST	----
444-095	2-1/2" NST x 1-1/2" NST	----
444-045	2-1/2" NPT x 2-1/2" NST	----
444-049	3" NPT x 2-1/2" NST	----

MALE SWIVEL ADAPTER - BRASS W/LUGS

Part #	Description Female x Male	
444-111	2-1/2" NST x 2" NPT	----
444-112	2-1/2" NST x 2-1/2" NPT	----
444-113	2-1/2" NST x 3" NPT	----

CAP - BRASS

Part #	Description	
444-062	2-1/2" NST	----
444-313	4-1/2" NST	----
444-320	2-1/2" NST PLUG	----
444-060	1-1/2" NST	

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

HOSE CLAMPS

HOSE CLAMPS

WORM GEAR
PAGE 317-320

QUICK RELEASE
PAGE 321

T-BOLT
PAGE 322

SPRING LOADED T-BOLT
PAGE 323

CONSTANT TORQUE
PAGE 324

V-BAND
PAGE 324

MUFFLER
PAGE 325

EXHAUST
PAGE 326

1 EAR, 2 EAR, GAPLESS
PAGE 327-328

PRE-FORMED
PAGE 329-330

TOOLS
PAGE 331

NON-PERFORATED OR LINED BAND
PAGE 332

RUBBER LINED
PAGE 333

HOSE FERRULES
PAGE 334

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

MINIATURE CLAMPS - 5/16" BAND

Stainless Steel band with Carbon Steel Housing and Screw

5/16" band, 1/4" screw

Part #	Dia. Range		Box/Case	
	Min.	Max.		
300-0004	7/32"	5/8"	200/2400	----
300-005	7/16"	11/16"	200/2400	----
300-0006	5/16"	7/8"	200/2400	----
300-0008	7/16"	1"	200/1200	----
300-010	1/2"	1-1/16"	200/1200	----
300-012	9/16"	1-1/4"	200/1200	----
300-016	11/16"	1-1/2"	200/1200	----
300-0020	7/8"	1-3/4"	200/1200	----

300 Series

- 1/4" Hex Slotted Carbon Steel Screw
- 5/16" Wide 301 Stainless Steel Band
- Carbon Steel Housing

Applications: For marine, agricultural, industrial and automotive uses. Corrosion resistance varies with stainless components.

Mechanically interlocked, 3 piece construction for service sealing pressure without spot welding.

1/2" BAND CLAMPS

Stainless Steel band with Carbon Steel Housing and Screw

1/2" band, 5/16" screw

Part #	#	Dia. Range		Bag/Case	
		Min.	Max.		
600-006	6	3/8"	7/8"	100/600	----
600-008	8	7/16"	1"	100/600	----
600-010	10	9/16"	1-1/16"	100/600	----
600-012	12	9/16"	1-1/4"	100/600	----
600-016	16	11/16"	1-1/2"	100/600	----
600-020	20	3/4"	1-3/4"	100/300	----
600-024	24	1-1/16"	2"	100/300	----
600-028	28	1-5/16"	2-1/4"	100/300	----
600-032	32	1-9/16"	2-1/2"	100/300	----
600-036	36	1-13/16"	2-3/4"	50/200	----
600-040	40	2-1/16"	3"	50/200	----
600-044	44	2-5/16"	3-1/4"	50/200	----
600-048	48	2-9/16"	3-1/2"	50/200	----
600-052	52	2-13/16"	3-3/4"	25/100	----
600-056	56	3-1/16"	4"	25/100	----
600-060	60	3-5/16"	4-1/4"	25/100	----
600-064	64	2-1/2"	4-1/2"	25/100	----
600-072	72	3"	5"	25/100	----
600-080	80	3-1/2"	5-1/2"	10/100	----
600-088	88	4"	6"	10/100	----
600-096	96	4-1/2"	6-1/2"	10/100	----
600-104	104	5"	7"	10/100	----

600 Series

- 5/16" Hex Slotted Carbon Steel Screw
- 1/2" Wide 201 Stainless Steel Band
- Carbon Steel Housing

Applications: A general purpose clamp for automobiles, plumbing, home and garden general clamping applications, with anti-corrosive properties varying with the number of components made from stainless steel.

- No PSI Rating
- 50lb/ Inch Torque Rating Die Set Function

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

325 & 611 WORM GEAR CLAMPS | HOSE CLAMPS

MINIATURE CLAMPS - 5/16" BAND

325 Series

- 1/4" Hex Slotted Carbon Steel Screw
- 5/16" Wide 301 Stainless Steel Band
- 301 Stainless Steel Housing

Stainless Steel band and housing with Carbon Steel Screw

5/16" band, 1/4" screw

Part #	Dia. Range		Box/Case	
	Min.	Max.		
325-004	7/32"	5/8"	200/2400	----
325-005	7/16"	11/16"	200/2400	----
325-006	5/16"	7/8"	200/2400	----
325-008	7/16"	1"	200/1200	----
325-010	1/2"	1-1/16"	200/1200	----
325-012	9/16"	1-1/4"	200/1200	----
325-016	11/16"	1-1/2"	200/1200	----
325-020	7/8"	1-3/4"	200/1200	----

Lightweight, low profile, compact design allows ease of installation in restricted applications. The 5/16 band width generates significant sealing pressure with relatively low installationi torque levels. 300 series stainless band and housing

Applications: For agricultural, industrial and automotive uses. Corrosion resistance varies with stainless components.

Mechanically interlocked, 3 piece construction for service sealing pressure without spot welding.

1/2" BAND CLAMPS

611 Series

- 5/16" Hex Slotted Carbon Steel Screw
- 1/2" Wide 201 Stainless Steel Band
- 301 Stainless Steel Housing

Applications: The perfect clamp for automobiles, plumbing, home and garden general clamping applications, with anti-corrosive properties varying with the number of components made from stainless steel.

- No PSI Rating
- 50lb/ Inch Torque Rating Die Set Function

Stainless Steel band and housing with Carbon Steel Screw

1/2" band, 5/16" screw

Part #	#	Dia. Range		Bag/Case	
		Min.	Max.		
611-006	6	3/8"	7/8"	100/600	----
611-008	8	7/16"	1"	100/600	----
611-010	10	9/16"	1-1/16"	100/600	----
611-012	12	9/16"	1-1/4"	100/600	----
611-016	16	11/16"	1-1/2"	100/600	----
611-020	20	3/4"	1-3/4"	100/300	----
611-024	24	1-1/16"	2"	100/300	----
611-028	28	1-5/16"	2-1/4"	100/300	----
611-032	32	1-9/16"	2-1/2"	100/300	----
611-036	36	1-13/16"	2-3/4"	50/200	----
611-040	40	2-1/16"	3"	50/200	----
611-044	44	2-5/16"	3-1/4"	50/200	----
611-048	48	2-9/16"	3-1/2"	50/200	----
611-052	52	2-13/16"	3-3/4"	25/100	----
611-056	56	3-1/16"	4"	25/100	----
611-060	60	3-5/16"	4-1/4"	25/100	----
611-064	64	2-1/2"	4-1/2"	25/100	----
611-072	72	3"	5"	25/100	----
611-080	80	3-1/2"	5-1/2"	10/100	----
611-088	88	4"	6"	10/100	----
611-096	96	4-1/2"	6-1/2"	10/100	----
611-104	104	5"	7"	10/100	----
611-116	116	5-3/4"	7-3/4"	100/100	----
611-128	128	6-1/2"	8-1/2"	100/100	----
611-152	152	2"	10"	100/100	----
611-164	164	1-3/4"	10-3/4"	100/100	----
611-176	176	9-1/4"	11-1/4"	100/100	----
611-188	188	2-1/16"	12-1/4"	100/100	----
611-200	200	11"	13"	100/100	----
611-212	212	11-3/4"	13-3/4"	100/100	----
611-224	224	12-1/2"	14-1/2"	100/100	----
611-248	248	10-3/4"	16"	100/100	----
611-270	270	15-3/8"	17-3/8"	100/100	----
611-312	312	18"	20"	100/100	----
611-332	332	19-1/8"	21-1/4"	100/100	----
611-390	390	22-7/8"	24-7/8"	100/100	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

MINIATURE CLAMPS - 5/16" BAND

350 Series

- 1/4" Hex Slotted 410 Stainless Steel Screw
- 5/16" Wide 301 Stainless Steel Band
- 301 stainless Steel Housing
- 6mm thick

All Stainless Steel

5/16" band, 1/4" screw

Part #	Dia. Range		Box/Case	
	Min.	Max.		
350-004	7/32"	5/8"	200/2400	----
350-005	7/16"	11/16"	200/2400	----
350-006	5/16"	7/8"	200/2400	----
350-008	7/16"	1"	200/1200	----
350-010	1/2"	1-1/16"	200/1200	----
350-012	9/16"	1-1/4"	200/1200	----
350-016	11/16"	1-1/2"	200/1200	----
350-020	7/8"	1-3/4"	200/1200	----

Applications: For agricultural, industrial and automotive uses. Corrosion resistance varies with stainless components.

Mechanically interlocked, 3 piece construction for service sealing pressure without spot welding.

1/2" WIDE BAND CLAMPS (12.70mm)

620 Series

- 5/16" Hex Slotted 305 Stainless Steel Screw
- 1/2" Wide 301 Stainless Steel Band
- 301 Stainless Steel Housing

- 60mm Thickness
- Use for underground and other high corrosive applications.
- For a sure grip application.
- Especially suited to industrial applications

All Stainless Steel

1/2" band, 5/16" screw

Part #	#	Dia. Range		Box/Case	
		Min.	Max.		
620-006	6	3/8"	7/8"	100/600	----
620-008	8	7/16"	1"	100/600	----
620-010	10	9/16"	1-1/16"	100/600	----
620-012	12	9/16"	1-1/4"	100/600	----
620-016	16	11/16"	1-1/2"	100/600	----
620-020	20	3/4"	1-3/4"	100/300	----
620-024	24	1-1/16"	2"	100/300	----
620-028	28	1-5/16"	2-1/4"	100/300	----
620-032	32	1-9/16"	2-1/2"	100/300	----
620-036	36	1-13/16"	2-3/4"	50/200	----
620-040	40	2-1/16"	3"	50/200	----
620-044	44	2-5/16"	3-1/4"	50/200	----
620-048	48	2-9/16"	3-1/2"	50/200	----
620-052	52	2-13/16"	3-3/4"	25/100	----
620-056	56	3-1/16"	4"	25/100	----
620-060	60	3-5/16"	4-1/4"	25/100	----
620-064	64	2-1/2"	4-1/2"	25/100	----
620-072	72	3"	5"	25/100	----
620-080	80	3-1/2"	5-1/2"	10/100	----
620-088	88	4"	6"	10/100	----
620-096	96	4-1/2"	6-1/2"	10/100	----
620-104	104	5"	7"	10/100	----
620-116	116	5-3/4"	7-3/4"	100/100	----
620-128	128	6-1/2"	8-1/2"	100/100	----
620-152	152	2"	10"	100/100	----
620-164	164	1-3/4"	10-3/4"	100/100	----
620-176	176	9-1/4"	11-1/4"	100/100	----
620-188	188	9.9"	12-1/4"	100/100	----
620-200	200	11"	13"	100/100	----
620-212	212	11-3/4"	13-3/4"	100/100	----
620-224	224	12-1/2"	14-1/2"	100/100	----
620-248	248	10-3/4"	16"	100/100	----
620-270	270	15-3/8"	17-3/8"	100/100	----
620-312	312	18"	20"	100/100	----
620-332	332	19-1/8"	21-1/4"	100/100	----
620-390	390	22-7/8"	24-7/8"	100/100	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

#316 MARINE WORM GEAR CLAMPS | HOSE CLAMPS

MINIATURE CLAMPS - 5/16" BAND

All #316 SS for Marine Environments

5/16" band, 1/4" screw

Part #	Dia. Range		Box/Case	
	Min.	Max.		
350-004SS	7/32"	5/8"	200/2400	----
350-005SS	7/16"	11/16"	200/2400	----
350-006SS	5/16"	7/8"	200/2400	----
350-008SS	7/16"	1"	200/1200	----
350-010SS	1/2"	1-1/16"	200/1200	----
350-012SS	9/16"	1-1/4"	200/1200	----
350-016SS	11/16"	1-1/2"	200/1200	----
350-020SS	7/8"	1-3/4"	200/1200	----

350SS Series

- 1/4" Hex Slotted 316 Stainless Steel Screw
- 316 Stainless Steel Band
- 8mm wide
- 60 mm thick
- 316 stainless Steel Housing

Applications: For marine, agricultural, industrial and automotive uses. Corrosion resistance varies with stainless components.

Mechanically interlocked, 3 piece construction for service sealing pressure without spot welding.

1/2" WIDE BAND CLAMPS (12.70mm)

All #316 SS for Marine Environments

1/2" band, 5/16" screw

All 316SS Part #	#	Dia. Range		Box/Case	
		Min.	Max.		
620-006SS	6	3/8"	7/8"	100/600	----
620-008SS	8	7/16"	1"	100/600	----
620-010SS	10	9/16"	1-1/16"	100/600	----
620-012SS	12	9/16"	1-1/4"	100/600	----
620-016SS	16	11/16"	1-1/2"	100/600	----
620-020SS	20	3/4"	1-3/4"	100/300	----
620-024SS	24	1-1/16"	2"	100/300	----
620-028SS	28	1-5/16"	2-1/4"	100/300	----
620-032SS	32	1-9/16"	2-1/2"	100/300	----
620-036SS	36	1-13/16"	2-3/4"	50/200	----
620-040SS	40	2-1/16"	3"	50/200	----
620-044SS	44	2-5/16"	3-1/4"	50/200	----
620-048SS	48	2-9/16"	3-1/2"	50/200	----
620-052SS	52	2-13/16"	3-3/4"	25/100	----
620-056SS	56	3-1/16"	4"	25/100	----
620-060SS	60	3-5/16"	4-1/4"	25/100	----
620-064SS	64	2-1/2"	4-1/2"	25/100	----
620-072SS	72	3"	5"	25/100	----

620SS Series

- 5/16" Hex Slotted 316 Stainless Steel Screw
- 1/2" Wide 316 Stainless Steel Band
- 316 Stainless Steel Housing

- 60mm Thickness
- Use for marine, underground and other high corrosive applications.

Yesterday is not ours to recover, but tomorrow is ours to win or lose. - *Lyndon B. Johnson*

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

QUICK RELEASE 500/550 SERIES

These clamps feature a unique quick release design between the one piece housing and band allowing for quick and easy installation in restricted or difficult areas.

Applications: Quick release action permits easy installation in applications where clamp must be opened to be applied. Quick release clamps are used extensively in the telecommunications industry on cable enclosures where open air application demands durability.



Open/Close design allows easy installation.

500 Series
- 5/16" Hex Slotted Carbon Steel Screw
- 1/2" 301 Stainless Steel band
- 301 Stainless Steel Housing
- 410 Stainless Steel Bridge

550 Series
- 5/16" Hex Slotted 410 Stainless Steel Screw
- 1/2" 301 Stainless Steel band
- 301 Stainless Steel Housing
- 410 Stainless Steel Bridge

Part #		#	Dia. Range		Part #	
			Min.	Max.		
500-012	----	12	1/2"	1-1/4"	550-012	----
500-020	----	20	3/4"	1-3/4"	550-020	----
500-028	----	28	1"	2-1/4"	550-028	----
500-036	----	36	1"	2-3/4"	550-036	----
500-048	----	48	1-1/2"	3-1/2"	550-048	----
500-056	----	56	1"	4"	550-056	----
500-072	----	72	2"	5"	550-072	----
500-088	----	88	2-1/16"	6"	550-088	----
500-104	----	104	1-3/4"	7"	550-104	----
500-128	----	128	1-3/4"	8-9/16"	550-128	----
500-152	----	152	2"	10"	550-152	----
500-188	----	188	2-1/16"	12-5/16"	550-188	----
500-216	----	216	10-3/16"	14"	550-216	----
500-248	----	248	10-3/4"	16"	550-248	----
500-280	----	280	14-1/4"	18"	550-280	----
		312	14"	20"	550-312	----

I believe if you keep your faith, you keep your trust, you keep the right attitude, if you're grateful, you'll see God open up new doors.

-Joel Osteen

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

T-Bolt Clamps

- All designs meet SAE J1508 specifications.
- .025" Band Thickness
- 3/4" Wide Band
- Band Material: 301 Series Stainless Steel
- Bolt Material: 304 Series Stainless Steel
- Nut Material: 304 Series Stainless Steel
- Nuts are Self-locking
- Torque Rating 75 in/lb

Opens 1/16" above and tightens 1/8" smaller then nominal I.D. for a total of 3/16" range for clamps sizes 150 through 250. Opens 1/16" above and tightens 7/32" smaller then nominal I.D. for clamps sizes 256 through 750.

Purpose: To provide a quick, yet effective means of clamping a variety of fittings to a wide range of hose. T-Bolts can be applied with a standard 7/16" socket wrench. They provide 360^0 sealing surface by using a shoe or formed bridge.

Services: The T-Bolt clamp is a high strength, reliable clamp with numerous applications in both the commercial and industrial markets including hose and ductwork connections for air, oil, water, other types of low pressure fluid lines, engine air intake, exhaust, hose and filters.

ALL STAINLESS STEEL

Nominal Size	O.D. Range		Part#	
	From:	To:		
1-1/4	1-5/32"	1-15/32"	840-131	----
1-1/2	1-3/8"	1-9/16"	840-150	----
1-3/4	1-5/8"	1-13/16"	840-175	----
1-7/8	1-3/4"	1-15/16"	840-188	----
2	1-7/8"	2-1/16"	840-200	----
2-1/4	2-1/8"	2-5/16"	840-225	----
2-3/8	2-1/4"	2-7/16"	840-238	----
2-1/2	2-3/8"	2-9/16"	840-250	----
2-9/16	2-11/32"	2-5/8"	840-256	----
2-5/8	2-13/32"	2-11/16"	840-263	----
2-3/4	2-17/32"	2-13/16"	840-275	----
2-7/8	2-21/32"	2-15/16"	840-288	----
3	2-25/32"	3-1/16"	840-300	----
3-1/8	2-29/32"	3-3/16"	840-312	----
3-1/4	3-1/32"	3-5/16"	840-325	----
3-1/2	3-9/32"	3-9/16"	840-350	----
3-3/4	3-17/32"	3-13/16"	840-375	----
3-53/64	3-19/32"	3-7/8"	840-382	----
4	3-25/32"	4-1/16"	840-400	----
4-1/4	4-1/32"	4-5/16"	840-425	----
4-1/2	4-9/32"	4-9/16"	840-450	----
4-3/4	4-17/32"	4-13/16"	840-475	----
5	4-25/32"	5-1/16"	840-500	----
5-1/4	5-1/32"	5-5/16"	840-525	----
5-1/2	5-9/32"	5-9/16"	840-550	----
5-3/4	5-17/32"	5-13/16"	840-575	----
6	5-25/32"	6-1/16"	840-600	----
6-1/4	6-1/32"	6-5/16"	840-625	----
6-1/2	6-9/32"	6-9/16"	840-650	----
6-3/4	6-17/32"	6-13/16"	840-675	----
7	6-25/32"	7-1/16"	840-700	----
7-1/2	7-9/32"	7-9/16"	840-750	----
8	7-25/32"	8-1/16"	840-800	----
8-1/4	8-9/32"	8-9/16"	840-850	----
8-7/8	8-21/32"	8-15/16"	840-888	----
10-7/8	10-21/32"	10-15/16"	840-1088	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

Spring Loaded T-Bolt Hose Clamp

- Per SAE standard J1508 Type "SLTB"
- .025 Band Thickness
- 3/4 (19mm) band width
- Heavy duty springs
- Band Material: 300 stainless
- T-bolt: Carbon steel w/ zinc plating
- Housing (Bridge): 300 Stainless
- Hex nut: Carbon Steel, Nylon insert
- Torque rating: 150 in-lbs (8.5 mm)

Purpose: To provide constant tension performance to compensate for the expansion and contraction when temperatures fluctuate. Provides high strength and a 360° seal. Tighten with a 7/16" wrench or hex nutdriver.

Services: Designed for use in high vibration and large diameter applications common in heavy trucks, industrial machinery, off road equipment, agricultural irrigation and machinery, for air intake and coolant adapter

Part #	SAE #	Min - Max	WGT	Box Qty	
844-213	40	2.13 - 2.44	0.170	100	----
844-225	44	2.25 - 2.56	0.174	100	----
844-238	48	2.38 - 2.69	0.179	100	----
844-250	52	2.50 - 2.81	0.181	100	----
844-263	56	2.63 - 2.94	0.183	100	----
844-275	60	2.75 - 3.06	0.185	100	----
844-300	68	3 - 3.31	0.187	100	----
844-306	70	3.06 - 3.38	0.190	100	----
844-313	72	3.13 - 3.44	0.192	100	----
844-325	76	3.25 - 3.56	0.194	100	----
844-338	80	3.38 - 3.69	0.196	100	----
844-350	84	3.50 - 3.81	0.196	100	----
844-356	86	3.56 - 3.88	0.196	100	----
844-363	88	3.63 - 3.94	0.198	100	----
844-375	92	3.75 - 4.06	0.198	100	----
844-406	102	4.06 - 4.38	0.203	100	----
844-413	104	4.13 - 4.44	0.209	100	----
844-425	108	4.25 - 4.56	0.214	100	----
844-456	118	4.56 - 4.88	0.216	100	----
844-500	132	5 - 5.31	0.218	100	----
844-525	140	5.25 - 5.56	0.220	100	----
844-600	164	6 - 6.31	0.223	100	----
844-625	172	6.25 - 6.56	0.225	100	----

Automatically adjust diameter for hose expansioin and contraction due to temperature changes.

Always turn a negative situation into a positive situation.

– Michael Jordan

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

Constant Torque Hose Clamps

- All designs meet SAE J1508 specifications type "SLHD"
- .028 Band thickness
- Band material: 304 thickness
- Band width: 9/16" for 45in-lb
  5/8" for 90in-lb
- Band material: 304 stainless
- Housing: 304 stainless steel
- Bridge: 410 stainless steel
- Hex screw: 410 stainless steel

Purpose: To eliminate leaks by automatically incerasing or decreasing the clamps diameter, decreasing the need for retightening. Constant torque clamps have an extended tail on the band to protect soft hose or tube from being cut.

Services: Constant torque clamps are an excellent choice for fluctuating and extreme temperature applications and thermal compensation.

Part #	Clamping Range	Band Width	Torque	Screw Size	WGT	Box Qty	
842-010	9/16" - 1 1/16"	9/16"	72 in-lb	5/16"	0.106	100	----
842-012	11/16" - 1 1/4"	9/16"	72 in-lb	5/16"	0.108	100	----
842-016	13/16" - 1 1/2"	9/16"	72 in-lb	5/16"	0.112	100	----
842-020	13/16" - 1 3/4"	9/16"	72 in-lb	5/16"	0.119	100	----
842-024	1 1/16" - 2"	9/16"	72 in-lb	5/16"	0.121	100	----
842-200	1 1/4" - 2 1/8"	5/8"	130 in-lb High	3/8"	0.207	100	----
842-250	1 3/4" - 2 5/8"	5/8"	130 in-lb High	3/8"	0.216	100	----
842-300	2 1/4" - 3 1/8"	5/8"	130 in-lb High	3/8"	0.220	100	----
842-350	2 3/4" - 3 5/8"	5/8"	130 in-lb High	3/8"	0.225	100	----
842-400	3 1/4" - 4 1/8"	5/8"	130 in-lb High	3/8"	0.231	100	----
842-450	3 3/4" - 4 5/8"	5/8"	130 in-lb High	3/8"	0.238	100	----
842-500	4 1/4" - 5 1/8"	5/8"	130 in-lb High	3/8"	0.256	100	----

V-Band Hose Clamps

- Band thickness: see chart
- Band width: see chart
- Band material: 300 stainless
- Trunnion: 300 stainless
- 1/4" T-bolt: 300 stainless
- 7/16" Hex nut: 300 stainless



Purpose: to provide a fast, secure cupling for connecting flanged joints.

Services: V-Band clamps feature high strength and positive sealing integrity for applications including: heavy duty diesel engine exhaust and turbochargers, filter housings, emissions and general industrial applications.

Part#	Nominal Diameter	V-Insert Sections			Bands		WGT	Box Qty	
		A	B	C	D	E			
843-321	3.21	0.050	0.262	0.141	0.035	0.750	0.525	100	----
843-382	3.82	0.077	0.207	0.281	0.040	0.875	0.531	100	----
843-388	3.88	0.050	0.400	0.281	0.040	0.875	0.536	100	----
843-450	4.50	0.077	0.207	0.281	0.040	0.875	0.547	100	----
843-461	4.61	0.050	0.156	0.281	0.035	0.750	0.549	100	----
843-475	4.75	0.050	0.400	0.281	0.040	0.875	0.553	100	----
843-525	5.25	0.050	0.262	0.141	0.035	0.750	0.567	100	----
843-588	5.88	0.050	0.400	0.281	0.040	0.875	0.575	100	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

MUFFLER CLAMPS

Muffler Clamps are designed with elongated and tapered holes that pulls the legs around the pipe as the nuts tighten, making a tight seal. Other clamps legs do not wrap around the pipe, they stay straight and the clamp only connects at two points.

- Carbon steel band, housing and bridge
- All muffler clamps are zinc plated for superior corrosion resistance
- Heavy duty U-Bolt and band construction
- 3/8 U-bolt
- Base 2.4mm

SADDLE

Part #	Size	WGT	Box Qty	
841-175	1-3/4"	0.335	50	----
841-200	2"	0.410	50	----
841-250	2-1/2"	0.448	50	----
841-300	3"	0.582	50	----
841-350	3-1/2"	0.741	50	----
841-400	4"	0.847	25	----
841-450	4-1/2"	1.023	25	----
841-500	5"	1.067	25	----

FLAT BAND

Part #	Size	WGT	Box Qty	
841-004	4"	0.847	25	----
841-005	5"	1.093	25	----

GUILLOTINE - provides a complete 360° heavy duty seal

Part #	Size	WGT	Box Qty	
841-040	4"	0.820	25	----
841-045	4-1/2"	0.847	25	----
841-050	5"	0.988	25	----

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

EXHAUST CLAMPS

Complete with:
- One metal band - 76mm width
- One spacer
- Two bolts
- Two reaction blocks
- Individually boxed

- Pre-attached hardware for easy and accurate installation.

- Conforms to pipe and flex tubing to create the best seal available without distorting any pipes.

ALUMINIZED STEEL BUTT CLAMPS

- .7mm band thickness
- 76mm band width

Part #	Size	WGT	Box Qty	
845-200	2"	0.970	50	----
845-300	3"	1.058	50	----
845-350	3.50"	1.102	50	----
845-400	4"	1.146	50	----
845-500	5"	1.235	50	----
845-600	6"	1.323	50	----
845-500SS*	5"	1.190	50	----

*Light pattern .5mm band thickness

ALUMINIZED STEEL LAP CLAMPS

- .7mm band thickness
- 76mm band width

Part #	Size	WGT	Box Qty	
846-200	2"	0.970	50	----
846-250	2.50"	1.014	50	----
846-275	2.75"	1.036	50	----
846-300	3"	1.058	50	----
846-350	3.50"	1.102	50	----
846-400	4"	1.146	50	----
846-500	5"	1.235	50	----

STAINLESS STEEL LAP CLAMPS

- .5mm band thickness
- 76mm band width

Part #	Size	WGT	Box Qty	
847-200	2"	0.926	50	----
847-250	2.50"	0.970	50	----
847-275	2.75"	0.992	50	----
847-300	3"	1.014	50	----
847-350	3.50"	1.058	50	----
847-400	4"	1.102	50	----
847-500	5"	1.190	50	----
847-600	6"	1.279	50	----

STAINLESS STEEL EASY-FORM CLAMPS

- .5mm band thickness
- 76mm band width

Part #	Size	WGT	Box Qty	
848-200	2"	0.926	50	----
848-225	2.25"	0.948	50	----
848-250	2.50"	0.970	50	----
848-275	2.75"	0.992	50	----
848-300	3"	1.014	50	----
848-350	3.50"	1.058	50	----
848-400	4"	1.102	50	----
848-500	5"	1.190	50	----
848-600	6"	1.279	50	----
848-700	7"	1.367	50	----

WARNING: This product can expose you to chemicals, including chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

CARBON STEEL 1-EAR CLAMPS

1-Ear Clamps are intended for low pressure applications such as automotive (not fuel lines), appliances, industrial machinery, underground irrigation systems and beverage dispensing equipment. They are specifically designed for mass production applications where inexpensive clamps are needed.

Pressure:

As a guideline, 1-Ear Clamps have held
30 bar - 441 psi.
This was done using a static water pressure test.

- 100 PER BAG

Material:

Hot dipped galvanized carbon steel band - G90

Part #	Ref#	Nominal Size	Inches		
			Close	Open	
1050000	105	3/8"	0.350	0.414	----
1050001	113	7/16"	0.381	0.444	----
1050002	123	15/32"	0.394	0.486	----
1050003	133	1/2"	0.453	0.524	----
1050006	140	35/64"	0.472	0.551	----
1050007	145	9/16"	0.496	0.571	----
1050008	157	5/8"	0.543	0.618	----
1050009	170	11/16"	0.594	0.669	----
1050010	185	23/32"	0.618	0.728	----
1050011	198	3/4"	0.669	0.779	----
1050012	210	13/16"	0.716	0.827	----
1050013	226	7/8"	0.779	0.890	----
1050014	241	15/16"	0.839	0.949	----
1050015	256	1"	0.898	1.008	----
1050016	271	1-1/16"	0.945	1.067	----
1050017	286	1-1/8"	1.004	1.126	----
1050018	301	1-3/16"	1.063	1.185	----
1050020	331	1-5/16"	1.181	1.303	----
1050021	346	1-3/8"	1.240	1.362	----
1050023	376	1-15/32"	1.358	1.480	----
1050025	396	1-9/16"	1.437	1.559	----
1050026	410	1-5/8"	1.492	1.614	----
1050029	455	1-3/4"	1.669	1.791	----
1050030	470	1-16/16"	1.728	1.850	----
1050032	500	1-15/16"	1.846	1.968	----
1050033	515	2"	1.905	2.028	----

The art of communication is the language of leadership. - James Humes

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

2-EAR CLAMPS

2-Ear Clamps are especially suited for industrial use and with heavily vibrating equipment.

This is a medium pressure clamp and is widely used for maintenace and OEM applications. Rubber hose, plastic tubing, coaxial and electrical cable, rope, etc. are all easily clamped. These clamps are installed on air, fluid, gas and steam lines. The one piece design offers a positive, tamper-proof seal without damaging the hose.

PRESSURE:

As a guideline, 2-Ear Clamps successfully seal at 54 bar - 800 psi with 35 pulsating strokes a minute.

MATERIAL:

Zinc plated carbon steel
SAE 1008/1010 or DIN 1.0338
Stainless steel tubing
UNS S30400 or DIN 1.4301

• 100 PER BAG

Note: When ordering your 2-Ear Clamps select nominal clamp size nearest to, but always larger than, O.D. of material to be clamped after insert has been fitted.

ZINC PLATED CARBON STEEL

Part #	Nominal Size	Inches Close	Inches Open	
1010002	3/16"	0.134	0.197	----
1010008	5/16"	0.276	0.354	----
1010011	3/8"	0.319	0.433	----
1010016	1/2"	0.425	0.512	----
1010019	9/16"	0.492	0.591	----
1010022	19/32"	0.551	0.669	----
1010024	5/8"	0.591	0.709	----
1010027	3/4"	0.638	0.787	----

STAINLESS STEEL

Part #	Nominal Size	Inches Close	Inches Open	
1510003	1/4"	0.197	0.276	----
1510004	5/16"	0.276	0.354	----
1510023	3/8"	0.319	0.433	----
1510006	1/2"	0.425	0.512	----
1510007	9/16"	0.492	0.591	----
1510008	19/32"	0.551	0.669	----
1510009	5/8"	0.591	0.709	----
1510010	3/4"	0.638	0.787	----
1510011	13/16"	0.709	0.866	----
1510012	7/8"	0.748	0.906	----
1510013	15/16"	0.827	0.984	----
1510014	1"	0.886	1.063	----
1510016	1-1/8"	1.035	1.221	----
1510019	1-9/16"	1.260	1.457	----
1510020	1-1/2"	1.378	1.575	----

Minimum QTYs may apply

GAPLESS EAR CLAMPS

Features

•Assured clamping seal
• For low durometer and/ or thin-walled hose/ tubing
• Perfect for silicon, vinyl, polyurethane or other high tech materials used in all industries.
• Once installed, smooth inner band circumference prevents damage to the hose while the unique tongue-in-groove design provides a 360° seal
• There are no steps or gaps inside clamp

Material

- Stainless steel tubing UNS S30400 or DIN 1.4301

• 100 PER BAG

Part #	Nominal Size	Band Width	Inches Close	Inches Open	
16700001	9/32"	5mm	0.228	0.276	----
16700004	3/8"	5mm	0.307	0.374	----
16700007	7/16"	5mm	0.378	0.445	----
16700010	1/2"	7mm	0.425	0.524	----
16700012	35/64"	7mm	0.453	0.551	----
16700013	9/16"	7mm	0.472	0.571	----
16700016	5/8"	7mm	0.520	0.618	----
16700017	11/16"	7mm	0.571	0.669	----
16700022	3/4"	7mm	0.654	0.780	----
16700024	13/16"	7mm	0.701	0.827	----

obstacles are things a person sees when he takes his eyes off his goal.

– E. Joseph Cossman

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

HOSE CLAMPS PERFORMED

TO ORDER the correct size Fast Lok Clamps, measure the outside diameter of the hose or article and then select the next larger inside diameter clamp by catalog number.
• Minimum Qty may apply

Preformed Clamps are double wrapped and formed to a given diameter. Used primarily where one end of the hose or article is free to allow the clamps to be slid over the hose end before the fitting is inserted. All clamps may be pulled down to a smaller diameter but cannot be adjusted to a larger diameter.

PREFORMED CLAMPS
(3/8" AND 5/8" (NOMINAL) WIDTH) - 100/BOX

Catalog Number Galv	Band Width & Thick-ness		Clamp I.D. Inches	Catalog Number SS	Band Width & Thick-ness	
F-3	3/8 x .025	----	13/16			----
F-311	3/8 x .025	----	1 3/8			----
F-4	5/8 x .025	----	1	FS-4	5/8 x .022	----
F-5	5/8 x .025	----	1 1/4	FS-5	5/8 x .022	----
F-6	5/8 x .031	----	1 1/2	FS-6	5/8 x .022	----
F-7	5/8 x .031	----	1 3/4	FS-7	5/8 x .022	----
F-8	5/8 x .031	----	2	FS-8	5/8 x .022	----
F-9	5/8 x .031	----	2 1/4	FS-9	5/8 x .022	----

WITH STAINLESS STEEL LOK - 50/BOX

F-10	5/8 x .031	----	2 1/2	FS-10	5/8 x .022	----
F-11	5/8 x .031	----	2 3/4	FS-11	5/8 x .022	----
F-12	5/8 x .031	----	3	FS-12	5/8 x .022	----
F-14	5/8 x .031	----	3 1/2	FS-14	5/8 x .022	----
25/ BOX						
F-16	5/8 x .031	----	4	FS-16	5/8 x .022	----
F-18	5/8 x .031	----	4 1/2	FS-18	5/8 x .022	----
F-20	5/8 x .031	----	5	FS-20	5/8 x .022	----
	5/8 x .031		6	FS-24	5/8 x .022	----
	5/8 x .031		7	FS-28	5/8 x .022	----

Double-wrapped, Triple Punched, Holds Permanently

Galvanized Preformed Clamps 2 1/2 inch I.D. and above, and 5/8" wide open end clamps have a stainless steel lock for greater strength and rigidity.

K-CLAMP PREFORMED HOSE CLAMPS

Each clamp is a double wrapped metal band formed to a given diameter. The clamp is designed to be slid over the hose end before the fitting is inserted. A punch-type or fold-up tool is then used to apply the clamp.

Punch Indentation for ease of center punching

Heavy Duty Lock for greater strength and rigidity



Heavy Duty Clamp

K-Clamps may be secured by either a punch or fold-up method. (See cross sectioned views)

• Minimum Qty may apply

Center Punched

Less tension loss. Patented hole in inner band gives better internal mechanical locking after punching

Fold-up





PREFORMED CLAMPS
(3/8" AND 5/8" (NOMINAL) WIDTH) - 100/BOX

GALVANIZED STEEL — **STAINLESS STEEL TYPE 301**

Catalog Number		Clamp I.D. Inches	Band Width & Thickness	Catalog Number	
K-3	----	13/16"	3/8" x .025	KS-3	----
K-311	----	1-3/8"	3/8" x .025	KS-311	----
K-4	----	1"	5/8" x .030	KS-4	----
K-5	----	1-1/4"	5/8" x .030	KS-5	----
K-6	----	1-1/2"	5/8" x .030	KS-6	----
K-7	----	1-3/4"	5/8" x .030	KS-7	----
K-8	----	2"	5/8" x .030	KS-8	----
K-9	----	2-1/4"	5/8" x .030	KS-9	----
50/BOX					
K-10	----	2-1/2"	5/8" x .030	KS-10	----
K-11	----	2-3/4"	5/8" x .030	KS-11	----
K-12	----	3"	5/8" x .030	KS-12	----
K-14	----	3-1/2"	5/8" x .030	KS-14	----
25/BOX					
K-16	----	4"	5/8" x .030	KS-16	----
K-18	----	4-1/2"	5/8" x .030	KS-18	----
K-20	----	5"	5/8" x .030	KS-20	----
K-24	----	6"	5/8" x .030		
K-28	----	7"	5/8" x .030		

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

TO ORDER the correct size Fast Lok Clamps, measure the outside diameter of the hose or article and then select the next larger inside diameter clamp by catalog number.

STAINLESS STEEL

FLJS-Clamp

SMOOTH I.D. CLAMPS

• Minimum Qty may apply

FLJS - Clamps are double wrapped clamps with a more smooth inside diameter, intended for your thermoplastic and other thinner wall hose clamping applications. The JS series clamps slide on the hose prior to inserting the fitting.

Preformed JS - Clamps are available in 5/8" and 3/4" widths, 1" I.D. to 8" I.D. in 1/4" increments.

The FLJS - Clamp is intended to be applied with a KS001 tool or other comparable fold-up locking tool.

5/8" (NOMINAL WIDTH) - 100/BOX

Catalog #	Clamp I.D. Inches	Band Width & Thickness	
FLJS-203	1"	5/8" x .030	----
FLJS-204	1-1/4"	5/8" x .030	----
FLJS-205	1-1/2"	5/8" x .030	----
FLJS-207	2"	5/8" x .030	----
FLJS-208	2-1/4"	5/8" x .030	----
FLJS-209	2-1/2"	5/8" x .030	----

100' CLAMP-IT STRAPPING

Catalog #	Width	Thickness	Material 100'/CTN.	
SS-3751	3/8"	.025	301 Stainless	----
SS-5001	1/2"	.030	301 Stainless	----
SS-6251	5/8"	.030	301 Stainless	----
SS-7501	3/4"	.030	301 Stainless	----
SG-5000	1/2"	.030	Galvanized	----

CLAMP-IT

The multi-sized clamps all rolled up in one..for your unknown requirements for 1 inch to 30 feet, be they round or otherwise. Clamp-It products will fill your needs. This Strapping in widths of 3/8", 1/2", 5/8", and 3/4" stainless or galvanized steel, as are the clamps (buckles).

CLAMPS (BUCKLES)

Catalog #	Width	Material	Qty per box	
CS-3751	3/8"	301 Stainless	100	----
CS-5001	1/2"	301 Stainless	100	----
CS-6251	5/8"	301 Stainless	100	----
CS-7501	3/4"	301 Stainless	50	----

Be the attitude you want to be around. -Tim DeTellis

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

Model 1098 I
Standard Jaw Pincers

Part #		
1410118		----

SIDE JAW PINCERS

This dual purpose, side jaw design allows clamps to be applied or removed in confined areas with pincers held parallel to the hose. Also used like standard Pincers.

Part #		
1410083	Model 1099 I	----

HOSE CRIMPER

HOSE RULE CRIMPING TOOL
Tool is equipped with mounting holes for permanent installation or may be used as a portable tool assembly in the field.

IMPORTANT! BEFORE USING THIS TOOL
Make sure the crimping arm is in the closed (down) position and then set the adjusting screw so it touches the end stop.

OPERATION:
A. FERRULE - The proper ferrule should fit easily over the hose. It is better to use a slightly oversized ferrule as an undersized ferrule may make inserting the barbed fitting difficult.
B. BARBED FITTING - Dip the ferrule end of the hose into soapy water. Insert the chosen barbed fitting into the hose with a fair amount of force. A barbed fitting that slides into a hose too easily will not crimp properly.
C. CRIMPING DIE - To find the proper crimping die find the smallest die opening which the hose will just pass through freely. Use the next smallest die and depress the crimping arm fully, keep fingers free from the crimper. Open the crimper and rotate the hose one quarter turn and repeat to finish the crimp.

• Provides production capability and "big tool" crimping advantages at just a fraction of the cost of other tools offering comparable results.

HOSE CRIMPER COMES WITH 5 DIES

Die Sizes = 5/8", 37/64", 12/32", 31/64", 11/16"

Part #		
308-070	Hose Crimper	----

LOKING TOOL

Part #		
F-38	Portable hand tool used to apply punch Type 3/8 & 5/8 Clamps	----

LOKING TOOL

Part #		
F-40		----

Used to apply Punch Type 3/8 & 5/8 clamps. Order mallet separately

LOKING TOOL

Part #		
F-100	Used to apply Punch Type 3/8 & 5/8 clamps. Order mallet separately	----

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

LINED BAND CLAMPS

Features unique one-piece housing, rolled-up band edges and a non-perforated (embossed) band that protects the hose. For added corrosion resistance, the band in the 12mm Standard is made of Aluzinc which gives three times the protection offered by conventional galvanized steel.
• Features high clamping force and high durability torque.
• Stainless: All parts in AISI 304 Stainless Steel.
A non-perforated band with rolled up edges eliminates hose damage while increasing clamping force.
Per SAE standard J1508 Type "FEO"

GENERAL PURPOSE EMBOSSED WORM-GEAR HOSE CLAMPS

• Minimum Qty may apply

Part # Aluzinc		SAE Size	Clamping Range Inches	Clamping Range mm	Bag	Part# 304 SS	
88-024	----	8	5/8-1	15-24	1000	89-024	----
88-028	----	10	3/4-1-1/8	19-28	500	89-028	----
88-032	----	12	7/8-1-1/4	22-32	500	89-032	----
88-038	----	16	1-1/16-1-1/2	26-38	500	89-038	----
		20	1-1/4-1-3/4	32-44	500	89-044	----
88-050	----	24	1-1/2-2	38-50	500	89-050	----
88-056	----	28	1-3/4-2-1/4	44-56	500	89-056	----
88-065	----	32	2-2-9/16	50-65	200	89-065	----
88-075	----	40	2-5/16-3	58-75	200	89-075	----
88-085	----	44	2-11/16-3-3/8	68-85	200	89-085	----
88-095	----	52	3-3-3/4	77-95	200	89-095	----
88-112	----	64	3-7/16-4-7/16	87-112	200	89-112	----

MINI CLAMPS

Sure seal for small, thin walled hoses. The nut is secured to the clamp, making installation easier and the hexagonal head can be tightened with a socket wrench or screw driver. Bandwidth is 9mm.

PAINTED ALUZINC STANDARD MINI CLAMPS

Part # Aluzinc	Clamping Range Inches	Clamping Range mm	Qty per Bag	
92-010	.36-.41	9-10.5	1000	----
92-011	.37-.45	9.5-11.5	900	----
92-012	.41-.49	10.5-12.5	800	----
92-013	.45-.53	11.5-13.5	800	----
92-014	.49-.57	12.5-14.5	700	----
92-015	.53-.61	13.5-15.5	600	----
92-016	.55-.65	14-16.5	500	----
92-017	.59-.69	15-17.5	500	----

HOSE CLAMPS

MARINE - EMBOSSED NON-PERFORATED WORM GEAR CLAMPS

• Meets the DIN 3017 Standard
• Replaces the Ultra Clamps 316 stainless steel
• 12mm band widths
• Installation torque 60lbs
• General purpose non perforated band especially suited for most hoses and soft silicone hoses.
• Band edges rolled to protect soft hoses from shearing and fraying
• Common applications include: vehicular, industrial, mechanical engineering, plumbing and marine.
• ROLLED EDGES
• BAND WILL NOT DAMAGE SOFT HOSES

ALL #316 SS MATERIAL

12MM WIDE EMBOSSED ALL 316 BAND CLAMPS

Part #	Range of Adjust (in mm)	Range of Adjust (inches)	
96022	12-22	.469-.859	
96027	16-27	.625-1.06	----
96032	20-32	.787-1.26	----
96040	25-40	.984-1.575	----
96050	35-50	1.26-1.969	----
96060	40-60	1.575-2.362	----
96070	50-70	1.969-2.756	----
96080	60-80	2.362-3.15	----
96090	70-90	2.756-3.543	----
96100	80-100	3.15-3.937	----
96110	90-110	3.543-4.33	----
96120	100-120	3.937-4.724	----
96130	110-130	4.33-5.118	----
96140	120-140	4.72-5.512	----
96150	130-150	5.118-5.906	----
96160	140-160	5.512-6.299	----

MINI CLAMPS

304 SS MINI CLAMPS

Part # 304 SS	Clamping Range Inches	Clamping Range mm	Qty per Bag	
93-008	.30-.34	7.5-8.5	1000	----
93-009	.34-.37	8.5-9.5	1000	----
93-011	.41-.47	10.5-12	900	----
93-013	.49-.55	12.5-14	800	----
93-014	.53-.59	13.5-15	700	----
93-016	.59-.67	15-17	1000	----
93-017	.63-.71	16-18	500	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

RUBBER LINED CLAMPS

Multiple uses for holding cable, wire, pipe and hose. The rubber cushion absorbs vibration, provides protection against scratching and is made of black EPDM type rubber.

Rubber cushion clamps are used in a variety of industries and applications including automotive, truck, hydraulics and pneumatics, ship building, refrigeration, large equipmetnt packaging etc.

Bandwidths and mounting hose sizes vary by diameter and material.

- Aluzinc clamps have a .26 hole diameter
- Stainless Steel .20 diameter

Part # Aluzinc	Qty per Bag		Clamping Range		Part# 304 SS	Qty per Bag	
			Inches	mm			
95-300	100	----	1/8	3			
95-301	100	----	3/16	5	96-301	1000	----
95-302	100	----	1/4	6	96-302	200	----
95-303	100	----	5/16	8	96-303	1000	----
95-304	100	----	3/8	10	96-304	100	----
95-305	100	----	7/16	11	96-305	1000	----
95-306	100	----	1/2	13	96-306	100	----
95-307	100	----	9/16	14	96-307	100	----
95-308	100	----	5/8	16	96-308	100	----
95-309	50	----	11/16	18			
95-310	50	----	3/4	19	96-310	500	----
95-311	50	----	13/16	21			
95-312	50	----	7/8	22	96-312	500	----
95-313	50	----	15/16	24			
95-314	50	----	1	25	96-314	500	----
95-315	50	----	1-1/16	27			
95-316	50	----	1-1/8	29	96-316	500	----
95-317	50	----	1-3/16	30			
95-318	50	----	1-1/4	32	96-318	500	----
95-319	50	----	1-5/16	33			
95-320	50	----	1-3/8	35	96-320	500	----
95-321	50	----	1-7/16	36			
95-322	500	----	1-1/2	38	96-322	100	----
95-326	50	----	1-5/8	41			
95-323	25	----	1-3/4	45	96-323	500	----
95-328	25	----	1-7/8	47			
95-324	25	----	2	51			
95-325	25	----	2-1/8	54			
95-329	25	----	2-3/8	60			
95-327	25	----	2-1/2	65			
95-330	15	----	2-15/16	74			
95-331	10	----	4-5/16	110			

RUBBER CUSHIONED CLAMP, ZINC PLATED STEEL

Part #	Mounting Dia	Clamp Dia	
95402	3/8"	1/4"	----
95404	3/8"	3/8"	----
95406	3/8"	1/2"	----
95408	3/8"	5/8"	----
95410	3/8"	3/4"	----
95414	3/8"	1"	----
95418	3/8"	1 1/4"	----
95422	3/8"	1 1/2"	----
95424	3/8"	2"	----
95427	3/8"	2 1/2"	----
95432	3/8"	3"	----
95433	3/8"	4"	----
95434	3/8"	5"	----

GALVANIZED STEEL VINYL COATED CLAMP

Part #	Mounting Dia	Clamp Dia	
95504	1/4"	3/8"	----
95506	1/4"	1/2"	----
95508	1/4"	5/8"	----
95510	1/4"	3/4"	----
95512	1/4"	7/8"	----
95514	1/4"	1"	----
95516	1/4"	1 1/8"	----
95518	1/4"	1 1/4"	----
95522	1/4"	1 1/2"	----
95523	1/4"	1 3/4"	----
95524	1/4"	2"	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

HOSE FERRULES

SMOOTH BRASS HOSE FERRULES

Brass Hose Ferrules offer an alternative to hose clamps. After crimping, the ferrule will provide a permanent clamping force on both the hose and fitting.

I.D. Pierce/ Hole

• ASTMB36 Alloy 268

Part #	Ferrule #	I.D.	Length	Pierce	Gauge	
32-500	6231	0.330	0.49	0.250	0.020	----
32-501	833	0.358	0.500	0.265	0.020	----
32-503	833B	0.375	0.718	0.265	0.025	----
32-502	622	0.380	0.500	0.265	0.020	----
32-550	619	0.400	0.47	0.27	0.020	----
32-504	620	0.410	0.500	0.265	0.020	----
32-551	769R	0.450	0.562	0.343	0.020	----
32-552	4750	0.478	0.687	0.328	0.025	----
32-553	624R	0.500	0.500	0.343	0.020	----
32-506	7322A	0.500	1.000	0.343	0.025	----
32-554	7322	0.500	1.000	0.328	0.025	----
32-555	625	0.525	0.47	0.36	0.020	----
32-517	625A	0.525	0.56	0.360	0.020	----
32-556	7323	0.525	1.000	0.375	0.025	----
32-521	9974	0.525	1.000	0.437	0.025	----
32-557	7324	0.531	1.000	0.375	0.025	----
32-558	626	0.550	0.484	0.375	0.020	----
32-507	3588	0.56	0.75	0.375	0.020	----
32-559	7325	0.56	1.000	0.437	0.025	----
32-561	7326	0.593	1.000	0.437	0.025	----
32-563	JJ	0.600	0.500	0.500	0.020	----
32-526	II	0.625	0.500	0.500	0.020	----
32-564	7327	0.625	1.000	0.437	0.025	----
32-565	HH	0.650	0.500	0.500	0.020	----
32-566	7328	0.656	1.000	0.437	0.025	----
32-567	GG	0.675	0.515	0.500	0.020	----
32-568	7329	0.69	1.000	0.500	0.025	----

Part #	Ferrule #	I.D.	Length	Pierce	Gauge	
32-570	7330	0.718	1.000	0.500	0.025	----
32-508	7330A	0.718	1.000	0.625	0.025	----
32-571	EE	0.725	0.530	0.500	0.020	----
32-572	DD	0.750	0.531	0.500	0.020	----
32-510	7331B	0.75	1.00	0.500	0.025	----
32-573	7331	0.750	1.000	0.625	0.025	----
32-574	CC	0.775	0.531	0.500	0.020	----
32-533	7332B	0.781	1.000	0.500	0.025	----
32-575	7332	0.781	1.000	0.625	0.025	----
32-576	BB	0.800	0.546	0.562	0.020	----
32-577	7333	0.812	1.000	0.625	0.025	----
32-578	AA	0.825	0.546	0.562	0.020	----
32-535		0.85	0.968	0.687	0.025	----
32-579	7244	0.875	0.843	0.687	0.025	----
32-539	5029A	0.900	0.875	0.687	0.025	----
32-580	7113	0.925	0.968	0.750	0.025	----
32-543	5028A	0.975	0.843	0.687	0.025	----
32-545	5235A	1.000	0.843	0.687	0.025	----
32-549	7145A	1.050	0.843	0.687	0.025	----
32-584	5027	1.100	0.843	0.812	0.025	----
32-586	7104A	1.15	0.843	0.875	0.025	----
32-588	7088A	1.175	0.875	0.875	0.025	----
32-590	875L	1.200	0.843	0.875	0.025	----
32-591	7291	1.225	0.968	0.875	0.025	----
32-592	7255	1.25	0.968	1.000	0.04	----
32-596	8000	1.425	0.875	1.062	0.025	----
32-597	1500	1.50	0.875	1.125	0.025	----

STAINLESS STEEL FERRULES

Part #	Cross #	I.D.	Length	Hole	Metal Thickness	
32552SS	x4750	.478	.687	.328	.020	----
32557SS	7324	.531	1.00	.438	.020	----
32559SS	7325	.56	1.00	.437	.020	----
32561SS	7326	.593	1.00	.437	.020	----
32564SS	7327	.625	1.00	.437	.020	----
32566SS	7328	.656	1.00	.437	.020	----
32568SS	7329	.69	1.00	.50	.020	----
32570SS	7330	.718	1.00	.625	.020	----
32575SS	7332	.781	1.00	.625	.020	----
32577SS	7333	.812	1.00	.625	.020	----
32588SS	7088A	1.175	.844	.875	.020	----

MORE SIZES AVAILABLE

AVAILABLE IN ALUMINUM AND STEEL ALSO

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

TUBING

POLYURETHANE

POLYETHYLENE

Sold individually boxed

Natural, Black, Blue, Green, Red, Yellow, Orange

NYLON

Sold individually boxed

PVC

- Clear

Sold individually boxed

COPPER AND ALUMINUM



TYPE L AND REFRIGERATION

ALUMINUM



POLYURETHANE TUBING

POLYURETHANE NSF 51®

NSF 51® polyurethane (PUR) Shore A 98 tubing is made from the highest quality raw materials available. it is etherbased to provide excellent hydrolysis, oil and cold resistance. Polyurethane NSF 51® is strong and flexible and offers superior kink resistance compared to other tubing. It is 5 to 10 times more wear resistant and lighter in weight than any rubber hose.

Polyurethane NSF 51® tubing has an outside diameter made to extremely tight tolerances. It is ideal for use with push-to-connect fittings, as well as barb-type and compression fittings for simple installation.

Features

- Strong
- Lightweight
- Flexible
- Abrasion Resistant
- Heat & Cold Resistant
- Chemical Resistant
- Kink Resistant
- NSF 51® Certified
- Meets NSF 61® Requirements

Specifications

Temperature Range: -40°F to +160°F

Hardness: Shore A 98

Vacuum Rating:

To 28" Hg

Tolerances:

1/8"-1/2" O.D. +/- .005

9/16"-3/4" O.D. +/- .006

RoHS Compliant

Applications

Pneumatic Tools
Pneumatic Piping
Vacuum
Laboratories
Robotics
Motion Control
Instrumentation
Agriculture
Lube Lines
Painting Systems
Food & Beverages

100' FOOT LENGTHS

CLEAR

Part #	O.D. (IN)	I.D. (IN)	Wall Thickness (IN)	Bend Radius (IN)	W.P. @70°F (PSI)	W.P. @150°F (PSI)	3:1 Burst Pressure	Package Weight (lbs)	
973-341	4mm, 5/32	.093	.031	.250	200	85	600	.70	----
973-343	.250	.156	.047	.476	180	70	540	1.50	----
973-345	.375	.250	.063	1.000	150	70	450	3.40	----
973-346	.500	.328	.086	1.102	150	70	450	5.60	----

BLACK

Part #	O.D. (IN)	I.D. (IN)	Wall Thickness (IN)	Bend Radius (IN)	W.P. @70°F (PSI)	W.P. @150°F (PSI)	3:1 Burst Pressure	Package Weight (lbs)	
73-341B	4mm, 5/32	.093	.031	.250	200	85	600	.70	----
73-343B	.250	.156	.047	.476	180	70	540	1.50	----
73-345B	.375	.250	.063	1.000	150	70	450	3.40	----
73-346B	.500	.328	.086	1.102	150	70	450	5.60	----

BLUE

Part #	O.D. (IN)	I.D. (IN)	Wall Thickness (IN)	Bend Radius (IN)	W.P. @70°F (PSI)	W.P. @150°F (PSI)	3:1 Burst Pressure	Package Weight (lbs)	
73-341U	4mm, 5/32	.093	.031	.250	200	85	600	.70	----
73-343U	.250	.156	.047	.476	180	70	540	1.50	----
73-345U	.375	.250	.063	1.000	150	70	450	3.40	----
73-346U	.500	.328	.086	1.102	150	70	450	5.60	----

RED

Part #	O.D. (IN)	I.D. (IN)	Wall Thickness (IN)	Bend Radius (IN)	W.P. @70°F (PSI)	W.P. @150°F (PSI)	3:1 Burst Pressure	Package Weight (lbs)	
73-341R	4mm, 5/32	.093	.031	.250	200	85	600	.70	----
73-343R	.250	.156	.047	.476	180	70	540	1.50	----
73-345R	.375	.250	.063	1.000	150	70	450	3.40	----
73-346R	.562	.375	.093	1.142	140	60	420	5.60	----

OD Sizes Available

.125, .187, 1/4(1/8), 8mm(5/16)
.562, .625 and .750

Other sizes, Lengths and Colors available

- Available in longer lengths upon request
- Other colors available

LINEAR LOW DENSITY POLYETHYLENE TUBING (LLDPE)

Features

- Chemically Inert
- Chemical Resistant
- Lightweight & Flexible
- Good Dielectric Properties
- Impermeable to Gases
- Meets FDA Requirements
- Multiple Colors Available
- Vacuum rating to 28" Hg

Polyethylene is made from 100% non-toxic ingredients. It's inert nature and FDA compliant status makes it perfect for food, water and beverage piping. It is ideal for use in pneumatic, drain piping, lab use and chemical transfer applications which require an inexpensive tubing

Polyethylene is highly-resistant to stress cracking from chemicals, aging and ultraviolet exposure. For use with barb-type, push-to-connect or compression-style fittings.

Specifications

Temperature Range: -50°F to +140°F

Hardness: Shore A 93A
Shore D 45D

Applications

Food & Beverage
Pneumatic Tools
Pneumatic Piping
Electrical Jacketing
Drain Lines
Instrumentation
Chemical Transfer
Process Control
Laboratories

100' LENGTH

500' LENGTH

1000' LENGTH

100' LENGTH - Natural

Part #	Tube O.D.	Tube ID	Tube Wall	Working Pressure	
973-200	1/8"	0.08	0.022	250	----
973-201	4mm/5/32"	0.106	0.025	180	----
973-203	1/4"	0.17	0.040	150	----
973-204	1/4"	0.125	0.0625	350	----
973-205	8mm/5/16"	0.236	0.038	150	----
973-206	3/8"	0.25	0.0625	150	----
973-207	1/2"	0.375	0.0625	125	----
973-208	5/8"	0.50	0.0625	100	----
973-211	3/4"	0.625	0.0625	100	----
973-210	1"	0.75	0.125	150	----

500' LENGTH

Part #	Tube O.D.	Tube ID	Tube Wall	Working Pressure	
73-200N5	1/8"	0.085	0.020	250	----
73-203N5	1/4"	0.17	0.040	150	----
73-204N5	1/4"	0.125	0.0625	350	----
73-206N5	3/8"	0.25	0.0625	150	----
73-207N5	1/2"	0.375	0.0625	125	----

1000' LENGTH

Part #	Tube O.D.	Tube ID	Tube Wall	Working Pressure	
73-203N1	1/4"	0.17	0.040	150	----
73-206N1	3/8"	0.25	0.0625	150	----

LLDPE POLYETHYLENE TUBING - COLORS

BLACK

- 100'
- 500'
- 1000'

Part #	Color	Length	Nominal O.D.	
73-200B	Black	100'	1/8"	----
73-201B	Black	100'	5/32"	----
73-203B	Black	100'	1/4"	----
73-204B	Black	100'	1/4"	----
73-205B	Black	100'	5/16"	----
73-206B	Black	100'	3/8"	----
73-207B	Black	100'	1/2"	----
73-208B	Black	100'	5/8"	----
73-203B5	Black	500'	1/4"	----
73-205B5	Black	500'	5/16"	----
73-206B5	Black	500'	3/8"	----
73-207B5	Black	500'	1/2"	----
73-203B1	Black	1000'	1/4"	----
73-206B1	Black	1000'	3/8"	----

GREEN

- 100'
- 500'
- 1000'

Part #	Color	Length	Nominal O.D.	
73-201G	Green	100'	5/32"	----
73-203G	Green	100'	1/4"	----
73-204G	Green	100'	1/4"	----
73-205G	Green	100'	5/16"	----
73-206G	Green	100'	3/8"	----
73-207G	Green	100'	1/2"	----
73-203G5	Green	500'	1/4"	----
73-203G1	Green	1000'	1/4"	----

WHITE

- 100'
- 500'

Part #	Color	Length	Nominal O.D.	
73-203W	White	100'	1/4"	----
73-206W	White	100'	3/8"	----
73-207W	White	100'	1/2"	----
73-207W5	White	500'	1/2"	----

BLUE

- 100'
- 500'
- 1000'

Part #	Color	Length	Nominal O.D.	
73-200U	Blue	100'	1/8"	----
73-201U	Blue	100'	5/32"	----
73-203U	Blue	100'	1/4"	----
73-204U	Blue	100'	1/4"	----
73-205U	Blue	100'	5/16"	----
73-206U	Blue	100'	3/8"	----
73-207U	Blue	100'	1/2"	----
73-203U5	Blue	500'	1/4"	----
73-206U5	Blue	500'	3/8"	----
73-203U1	Blue	1000'	1/4"	----

RED

- 100'
- 500'
- 1000'

Part #	Color	Length	Nominal O.D.	
73-203R	Red	100'	1/4"	----
73-205R	Red	100'	5/16"	----
73-206R	Red	100'	3/8"	----
73-207R	Red	100'	1/2"	----
73-203R5	Red	500'	1/4"	----
73-206R5	Red	500'	3/8"	----
73-203R1	Red	1000'	1/4"	----

YELLOW

- 100'

Part #	Color	Length	Nominal O.D.	
73-203Y	Yellow	100'	1/4"	----
73-204Y	Yellow	100'	1/4"	----
73-205Y	Yellow	100'	5/16"	----
73-206Y	Yellow	100'	3/8"	----
73-207Y	Yellow	100'	1/2"	----

ORANGE

Part #	Color	Length	Nominal O.D.	
73-203O	Orange	100'	1/4"	----

NYLON 12 TUBING

Nylon 12 tubing is recognized as an industry standard for applications which require higher working pressures and higher heat and/or chemical resistance. It is ideal for outdoor use applications because of its superior stress crack resistance. Nylon 12 is strong, lightweight and has a very low moisture absorption rate compared to other nylons. By not absorbing moisture, Nylon 12 remains more flexible, which in turn extends it's service life. Nylon 12 tubing can be used with standard push-to-connect fittings and compression fittings for simple installation.

Because of it's semi-rigid properties, a thinner tube wall provides higher flow rates and working pressure.

Features

- Strong
- Lightweight
- Flexible
- Abrasion Resistant
- Heat Resistant
- Chemical Resistant
- Heat/ Light Stabilized
- Black - UV Rated

Specifications

Temperature Range: -60°F to +200°F
Hardness: Rockwell 78 R
Shore D 70
Vacuum Rating: To 28" Hg
Higher Flow Rates & Working Pressure
Tolerances: 1/8'-1/4" +/- .004
3/4"-1/2" +/- .006

Applications

Pneumatic Tools
Pneumatic Piping
Instrumentation
Lube Lines
Coolants
Refrigeration
Chemical Transfer
Vacuum
Process Control
Fuel Lines
Paint Supply Lines
Laboratories

Part #'s shown are for natural. 500' and 1000' reels available on request.

100' LENGTH

BLACK TUBING & MISC.

METRIC LENGTH

100' LENGTH

Part #	Tube O.D.	Tube ID	Tube Wall	Working Pressure	
973-230	1/8"	0.08	.022	420	----
973-231	5/32"	0.106	.025	350	----
973-232	1/4"	0.18	.035	290	----
973-238	1/4"	0.15	.05	800	----
973-226	5/16"				
973-233	3/8"	0.275	.050	250	----
973-234	1/2"	0.375	.062	240	----

BLACK TUBING & MISC.

Part #	O.D.	Tube ID	Wall	Working Pressure	
73-230B	1/8	0.08	0.022	420	----
73-231B	5/32	0.106	0.025	350	----
73-232B	1/4	0.18	0.035	290	----
73-238B	1/4	0.15	0.05	800	----
73-233B	3/8	0.275	0.05	250	----
73-232N5*	1/4	0.18	0.035	290	----
73-238U**	1/4	0.15	0.075	800	----

• 500' Natural **Blue

*METRIC LENGTH - 100 ft. coils

• available in natural color only

Part #	MM O.D.	MM I.D.	MM Wall	Working Pressure	
973-323	4	2.7	0.65	350	----
973-326	6	3.5	1.25	350	----
973-325	6	4	1	340	----
973-327	8	6	1	250	----
973-329	10	8	1	225	----
973-332	12	10	1	200	----
973-334	14	11	1.5	175	----

PVC TUBING AND TUBING CUTTERS

PVC POLYVINYLCHLORIDE TUBING - NSF61

PVC is suited for general, low-pressure, industrial applications for the conveyance of liquids and solids of suitable granular size. Made from a PVC compound that complies with FDA regulations. Although it is primarily intended for applications where pressure is not essential, it will withstand the pressures shown.

The clear PVC Tubing provides good chemical resistance, is lightweight, flexible and economically priced.

Features

- Lightweight
- Flexible
- Food Grade
- Clear Color/ Blue tint

Specifications

Temperature Range: +25°F to +150°F
Hardness: Shore A 75 PVC
Meets FDA requirements
NSF 61 Certified
USP Class VI rated materials
RoHS Compliant

Applications

Beverage Dispensing
Drain Tubing
Potable Water
Laboratory Tubing
Wine Transfer
Low Pressure Air Line
Distilled Water Transfer
Light Vacuum
Wire Harness
3:1 Burst Pressure

Colors Available: Clear

Package Lengths: 100'

100' LENGTH

Part #	Tube I.D.	Tube O.D.	Tube Wall	Working Pressure	
973-224	1/8 (.125)	1/4 (.25)	1/16 (.032)	50	----
973-223	3/16 (.187)	5/16 (.313)	1/16 (.062)	55	----
973-215	1/4 (.25)	3/8 (.375)	1/16 (.062)	55	----
973-252	5/16 (.312)	7/16 (.438)	1/16 (.062)	50	----
973-253	5/16 (.312)	1/2 (.500)	3/32 (.094)	55	----
973-216	3/8 (.375)	1/2 (.500)	1/16 (.062)	45	----
973-255	3/8 (.375)	5/8 (.625)	1/8 (.125)	55	----
973-262	3/8 (.375)	9/16 (.563)	3/32 (.094)	50	----
973-217	1/2 (.500)	5/8 (.625)	1/16 (.062)	30	----
973-219	3/4 (.750)	1 (1.00)	1/8 (.125)	35	----
973-221	1 (1.00)	1-1/4 (1.25)	1/8 (.125)	25	----

TUBING ACCESSORIES

MINI-TUBING CUTTER

• Great for tight places

Part #	Size	
990-571	3mm-22mm (1/8"-7/8")	----

TUBING CUTTER

Part #	Size	
990-570	1/8"-1-1/8"	----

PLASTIC TUBE CUTTER

Range: 1/8" - 3/8" I.D. (3mm-10mm)

Part #	Description	
91-707	Cutter w/Blade	----

MOUNTING RACKS

- Route and secure multiple tubing lines
- Mounting versatility
  - Racks can be easily hand separated down to single holders.
  - Thru holes provided (all sizes)
- Standard color is BLACK.

Other colors available on special request.

NOTE: MOUNTING SCREWS NOT PROVIDED

Part #	Tubing OD	Description	Channels	
28-988	1/4	non-adhesive	10	----
28-989	1/4	adhesive	10	----
28-990	3/8	non-adhesive	7	----
28-991	1/2	non-adhesive	5	----

ALUMINUM TUBING - EASY BEND

Alloy 3003-0 ASTM B-483



Material to ASTM B-483

900 PSI max
3700 Burst PSI

Bend this tubing into the shape you need without special tools or elbow fittings. It is also known as Alloy 3003. Tubing has seamless construction, which provides a smooth interior and allows it to be flared without splitting. Use with water, air, alcohol and oil. Tubing meets ASTM B483 and has a soft (annealed) temper. OD tolerance is ±0.004"

ALUMINUM VERSATUBE 50' COILS

Part #	O.D.	Wall Thick	ID	Max PSI @ 100°F	Case	50' Coils
972-190	1/8	.025	.075"	2,300	10 coils	----
972-191	3/16	.028	.132"	1,600	10 coils	----
972-192	1/4	.032	.186"	1,400	10 coils	----
972-193	5/16	.035	.243"	1,200	10 coils	----
972-194	3/8	.035	.305"	1,000	10 coils	----
972-195	1/2	.035	.43"	740	10 coils	----

COPPER TUBING - REFRIGERATION TUBING

ASTMB280

- Temp range: 32° to 400°F
- Bend with a bending tool
- Use with copper solder-connect fittings

This copper Alloy 122 tube comes cleaned and capped to prevent moisture and dirt from contaminating the inside. It's often called refrigeration and air conditioning tubing. Use with water, natural gas, oil and R22 refrigerant. Tubing meets ASTM B280. It has seamless construction, which provides a smooth interior. Tubing has a soft (annealed) temper.

REFRIGERATION COPPER TUBE 50' COILS

Part #	Tube Size	OD	Wall	ID	Max PSI @ 100°F	Weight per 50' Coil	50' Coils
972-180	-	1/8	.030	.065"	3,000	1.74	----
972-181	-	3/16	.030	.128"	1,900	2.88	----
972-182	1/8	1/4	.030	.19"	1,400	4..02	----
972-183	-	5/16	.032	.248"	1,100	5.45	----
972-184	1/4	3/8	.032	.311"	980	6.70	----
972-185	3/8	1/2	.032	.436"	720	9.10	----
972-186	1/2	5/8	.035	.555"	610	12.55	----
972-187	5/8	3/4	.035	.68'	510	15.25	----

COPPER TUBING - DRINKING WATER

For residential water lines

- Temp range: 32° to 180°F
- Bend with a bending tool
- Use with copper solder-connect fittings

NSF 61 certified for drinking (potable) water, this copper Alloy 122 tubing is also called type L. Tubing meets ASTM B88. It has seamless construction, which porovides a smooth interior. Coils - Have a soft (annealed) temper.

• Water service • Natural, liquified and petroleum gases • Fire protection • Solar • Fuel/ Fuel oil • HVAC • Snow melting - Air Brake

TYPE L SOFT COPPER TUBING 60' COILS

Part #	TUBE SIZE	OD	WALL	ID	Max PSI @ 100°F	Weight per 60' Coil	60' Coils
972-171	1/4	3/8"	.03"	.315"	910	7.56	----
972-172	3/8	1/2	.035"	.43"	770	11.88	----
972-173	1/2	5/8"	.04"	.545"	720	17.10	----

WARNING: This product can expose you to chemicals, including Lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

HIGH PRESSURE SPRAYERS

STRAIGHT THROUGH QDS

FITTINGS AND SWIVELS



NOZZLES

SPRAY GUNS AND WANDS

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

QUICK DISCONNECT NOZZLE

0-degree red tip nozzle, 15-degree yellow tip nozzle, 25-degree green tip nozzle, 40-degree white tip nozzle, and 65-degree black tip detergent nozzle. All nozzles are 4000 PSI and stainless steel, except for detergent nozzle, which is 600 PSI and brass. All Nozzles are rated for temperatures up to 300°F. Nozzles attach with ¼" quick disconnect plug.

Part #	Degree of Spray	GPM @ 4000PSI	
DX250030	0	3.0	----
DX251530	15	3.0	----
DX252530	25	3.0	----
DX254030	40	3.0	----
DX250040	0	4.0	----
DX251540	15	4.0	----
DX252540	25	4.0	----
DX254040	40	4.0	----
DX250050	0	5.0	----
DX251550	15	5.0	----
DX252550	25	5.0	----
DX254050	40	5.0	----
DX250060	0	6.0	----
DX251560	15	6.0	----
DX252560	25	6.0	----
DX254060	40	6.0	----
DX256500	65		----

MEG NOZZLE

Available in 0-degree nozzle, 15-degree nozzle, 25-degree nozzle, or 40-degree nozzle. Nozzle sizes 3.0, 4.0, 5.0, 6.0 or 7.0. All nozzles are 7250 PSI 300°F, stainless steel and ¼" male pipe thread.

Part #	Degree of Spray	GPM @ 4000PSI	
DX140030MG	0	3.0	----
DX141530MG	15	3.0	----
DX142530MG	25	3.0	----
DX144030MG	40	3.0	----
DX140040MG	0	4.0	----
DX141540MG	15	4.0	----
DX142540MG	25	4.0	----
DX144040MG	40	4.0	----
DX140050MG	0	5.0	----
DX141550MG	15	5.0	----
DX142550MG	25	5.0	----
DX144050MG	40	5.0	----
DX140060MG	0	6.0	----
DX141560MG	15	6.0	----
DX142560MG	25	6.0	----
DX144060MG	40	6.0	----
DX140070MG	0	7.0	----
DX141570MG	15	7.0	----
DX142570MG	25	7.0	----
DX144070MG	40	7.0	----

QUICK DISCONNECT NOZZLE 5-PIECE KIT

Part #	GPM @ 4000PSI	
DX259520	2.0	----
DX259530	3.0	----
DX259540	4.0	----
DX259550	5.0	----
DX259560	6.0	----
DX259570	7.0	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

OFFERED EXCLUSIVELY THROUGH MFG

DREXEL PRESSURE

RUBBER-TIP TURBO NOZZLE

Rubber tip, rotating turbo nozzle, ¼" NPT with steel male quick disconnect plug adaptor, rated for temperatures up to 300°F.

Part #	PSI	GPM @ 4000PSI	
DX722530	2500	3.0	----
DX722540	2500	4.0	----
DX722550	2500	5.0	----
DX722560	2500	6.0	----
DX723230	3200	3.0	----
DX723240	3200	4.0	----
DX723250	3200	5.0	----
DX723260	3200	6.0	----
DX724030	4000	3.0	----
DX724040	4000	4.0	----
DX724050	4000	5.0	----
DX724060	4000	6.0	----
DX725030	5000	3.0	----
DX725040	5000	4.0	----
DX725050	5000	5.0	----
DX725060	5000	6.0	----

STAINLESS STEEL LIVE SWIVEL

MxF straight through live swivel, NBR or Viton seal, 416 SS, 10.6 gpm, 180F max, 3500 PSI

Part #	Seal	Size	
DX60021	NBR	1/4"	----
DX60022	NBR	3/8"	----
DX60023	NBR	1/2"	----
DX60021V	Viton	1/4"	----
DX60022V	Viton	3/8"	----
DX60023V	Viton	1/2"	----

THERMAL RELIEF VALVE

140F Thermal Relief Valve, Brass, 300 PSI

Part #	Size	
DX35TR25	1/4"	----
DX35TR38	3/8"	----

90° BOOM SWIVEL

Male x Female 90° Boom swivel, Stainless Steel, 5000 PSI, 7GPM, 300°F

Part #	Size	
DX60092	3/8"	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

OFFERED EXCLUSIVELY THROUGH MFG

CHROMED STEEL WAND

1/4" MNPT x 1/4" Extension Wands, 10.5 GPM, 300F



Part #	Size	Grip	
DX4324	24"	No Grip	----
DX4336	36"	No Grip	----
DX4424	24"	Molded Grip	----
DX4436	36"	Molded Grip	----
DX4524VG	24"	Vented Grip	----
DX4536VG	36"	Vented Grip	----

SPRAY GUN

Rear entry spray gun, 4000 PSI, 7 GPM, 212F max

Part #	Pressure	Flow	Temperature	
DX5090	4000	7	212	----
DX5022	4000	6.6	300	----
DX5005	5075	10.5	300	----

WEEPING SPRAY GUN

Rear entry spray gun, weeping, 5000 PSI, 10.5 GPM, 300F

Weep style spray guns allow for a continuous flow of water by way of a small hole in the bottom of the gun that produces a slight leak, or a weeping effect. This helps prevent lines freezing in cold weather or scalding water temperatures in hot weather that could damage the pumps.

Part #	
DX5006	----

SPRAY GUN WITH EXTENSION

Rear entry spray gun with 12” extension, 4000psi, 7gpm, 300F max

Part #	
DX5190	----

SPRAY GUN WITH EXTENSION

Rrear entry spray gun with 12” extension, 5075psi, 10.5gpm, 300F max

Part #	
DX5197	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

COUPLERS/ PLUGS

STRAIGHT THROUGH STYLE

- Brass couplers have brass bodies and brass valves, 8 steel locking balls, Buna-N seal, and stainless steel springs
- Stainless steel couplers have stainless steel bodies, 8 stainless steel locking balls, Buna-N seal, and stainless steel springs
- Plugs are steel with green blue zinc plating or stainless steel
- Straight through design means there is no positive shut-off after disconnect
- Fully interchangeable with Parker, Hansen, Foster and Adams
- Use with liquids, hydraulic service, compressed air, gases, water and vacuum
- Ideal for applications such as high pressure water, steam washers, and carpet cleaners
- Max. Temp. 212°F for Couplers/ 300°F for Plugs • Max Flow: 10.5 GPM

MALE BRASS COUPLERS

Part #	Body Size	Thread Size	PSI	
86-030	1/4	1/4	4000	----
86-031	3/8	3/8	4000	----
86-032	1/2	1/2	4000	----

MALE STEEL PLUGS

Part #	Body Size	Thread Size	PSI	
86-040	1/4	1/4	4000	----
86-041	3/8	3/8	4000	----
86-042	1/2	1/2	4000	----

FEMALE BRASS COUPLERS

Part #	Body Size	Thread Size	PSI	
86-035	1/4	1/4	4000	----
86-036	3/8	3/8	4000	----
86-037	1/2	1/2	4000	----

FEMALE STEEL PLUGS

Part #	Body Size	Thread Size	PSI	
86-045	1/4	1/4	4000	----
86-046	3/8	3/8	4000	----
86-047	1/2	1/2	4000	----

MALE STAINLESS STEEL COUPLERS

Part #	Body Size	Thread Size	PSI	
86-030SS	1/4	1/4	6000	----
86-031SS	3/8	3/8	6000	----

MALE STAINLESS STEEL PLUGS

Part #	Body Size	Thread Size	PSI	
86-040SS	1/4	1/4	6000	----
86-041SS	3/8	3/8	6000	----

FEMALE STAINLESS STEEL COUPLERS

Part #	Body Size	Thread Size	PSI	
86-035SS	1/4	1/4	6000	----
86-036SS	3/8	3/8	6000	----

FEMALE STAINLESS STEEL PLUGS

Part #	Body Size	Thread Size	PSI	
86-045SS	1/4	1/4	6000	----
86-046SS	3/8	3/8	6000	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

MOLDED GRIP MALE BRASS COUPLER

Part #	Thread Size	Thread Size	PSI	
86-030RG	1/4	1/4	4000	----
86-031RG	3/8	3/8	4000	----

MOLDED GRIP FEMALE BRASS COUPLER

Part #	Thread Size	Plug	PSI	
86-035RG	1/4	1/4	4000	----
86-036RG	3/8	3/8	4000	----

M22 SCREW TYPE X MNPT

Part #	Thread Size	Male	PSI	
86-001	M22	1/4	4000	----
86-002	M22	3/8	4000	----

M22 SCREW TYPE X FNPT

Part #	Thread Size	Female Size	PSI	
86-005	M22	1/4	4000	----
86-006	M22	3/8	4000	----

INSUALTED KNOB

M22 INSULATED KNOB X MNPT

Part #	Thread Size	Male Size	PSI	
86-012	M22	1/4	4000	----
86-013	M22	3/8	4000	----

M22 INSULATED KNOB X FNPT



Part #	Thread Size	Female Size	PSI	
86-017	M22	1/4	4000	----
86-018	M22	3/8	4000	----

M22 X M22 FNPT

Part #	Thread Size	Thread Size	PSI	
86-022	M22	M22	4000	----

M22 INSULATED KNOB X QC PLUG

Part #	Thread Size	Plug	PSI	
86-020	M22	3/8	4000	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

PNEUMATICS

PNEUMATICS

1/4" 3/8" 1/2" 1/4" 1/4" 3/8" 1/4" 1/4" 3/8"
INDUSTRIAL INTERCHANGE ARO AUTO AUTO LINCOLN STRAIGHT THRU STRAIGHT THRU

QUICK DISCONNECTS

- Universal
- ARO 210
- Lincoln
- Industrial
- Automotive
- ST Series - High Flow

BREATHER VENTS, MUFFLERS

- Mufflers
- Snubbers
- In-line filters
- Breather vents
- Control valves
- Manifolds

PNEUMATIC ACCESSORIES

- Kits NEW
- Tire gauge
- Tank and vent valves
- Blow guns
- Air chucks
- Inflators

GAUGES

- Liquid filled & Dry
- Lower mount & center mount
- Water test
- Syphons

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

INDUSTRIAL INTERCHANGE

• Couplers are brass or plated steel body with brass or steel valves, 6 steel locking balls, NBR seal and stainless steel springs

6 Steel locking balls (1/2" body size has 8 steel locking balls)

• Plugs are brass or steel with green blue zinc plating

• Industry standard design for compressed air, water, grease, paint, limited vacuum and limited gases

• Manual retract for connecting and disconnecting

• Maximum working pressure is 250 PSI

BRASS FEMALE COUPLER

Part#	Body Size	Thread Size	
28-540	1/4"	1/4"	----
28-541	1/4"	3/8"	----

BRASS MALE COUPLER

Part#	Body Size	Thread Size	
28-552	1/4"	1/4"	----
28-553	1/4"	3/8"	----

STEEL FEMALE COUPLER

Part#	Body Size	Thread Size	
28-540S	1/4"	1/4"	----
28-541S	1/4"	3/8"	----
98-810	3/8"	1/4"	----
98-811	3/8"	3/8"	----
98-812	3/8"	1/2"	----
99-812	1/2"	1/2"	----
99-813	1/2"	3/4"	----

STEEL MALE COUPLER

Part#	Body Size	Thread Size	
28-552S	1/4"	1/4"	----
28-553S	1/4"	3/8"	----
98-823	3/8"	1/4"	----
98-824	3/8"	3/8"	----
98-825	3/8"	1/2"	----
99-825	1/2"	1/2"	----
99-826	1/2"	3/4"	----

BRASS HOSE ID COUPLER

Part#	Body Size	Barb Size	
28-562	1/4"	1/4"	----
28-564	1/4"	3/8"	----

STEEL HOSE ID COUPLER

Part#	Body Size	Barb Size	
28-562S	1/4"	1/4"	----
28-564S	1/4"	3/8"	----
98-840	3/8"	1/4"	----
98-841	3/8"	3/8"	----
99-841	1/2"	3/8"	----
99-843	1/2"	1/2"	----

BRASS PUSH-ON HOSE COUPLER

Part#	Body Size	Barb Size	
28-565	1/4"	1/4"	----
28-566	1/4"	3/8"	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

INDUSTRIAL — QUICK DISCONNECTS

STEEL PUSH-ON HOSE COUPLER

Part#	Body Size	Barb Size	
28-565S	1/4"	1/4"	----
28-566S	1/4"	3/8"	----
98-842	3/8"	3/8"	----

STEEL MALE PLUG

Part#	Body Size	Thread Size	
28-545	1/4"	1/8"	----
28-546	1/4"	1/4"	----
28-547	1/4"	3/8"	----
98-814	3/8"	1/4"	----
98-815	3/8"	3/8"	----
99-816	1/2"	1/2"	----
99-817	1/2"	3/4"	----

STEEL FEMALE PLUG

Part#	Body Size	Thread Size	
28-533	1/4"	1/8"	----
28-534	1/4"	1/4"	----
28-535	1/4"	3/8"	----
98-801	3/8"	1/4"	----
98-802	3/8"	3/8"	----
99-803	1/2"	1/2"	----
99-804	1/2"	3/4"	----

BRASS MALE PLUG

Part#	Body Size	Thread Size	
28-546B	1/4"	1/4"	----

BRASS FEMALE PLUG

Part#	Body Size	Thread Size	
28-534B	1/4"	1/4"	----

STEEL HOSE ID PLUG

Part#	Body Size	Barb Size	
28-557	1/4"	1/4"	----
28-559	1/4"	3/8"	----
98-828	3/8"	3/8"	----
99-828	1/2"	3/8"	----
99-830	1/2"	1/2"	----

STEEL PUSH-ON HOSE PLUG

Part#	Body Size	Barb Size	
28-558	1/4"	1/4"	----
28-561	1/4"	3/8"	----
98-830	3/8"	3/8"	----

STEEL SWIVEL MALE PLUG

Part#	Body Size	Thread Size	
320-065	1/4"	1/4"	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

UNIVERSAL SERIES COUPLERS

• Automatic Coupler means flow will cut off automatically at time of disconnect
• Brass Couplers have brass body and brass sleeve with brass valve, 6 steel locking balls, NBR seal and 6 stainless steel springs.
• Stainless Steel Couplers have stainless steel body and stainless steel sleeve with stainless steel valve, 6 steel locking balls, FKM seal, and stainless steel springs
• Coupler compatible with ARO 210, Parker Interchange and Industrial Interchange plugs
• Maximum working pressure is 250 PSI

BRASS MALE COUPLER

Part#	Body Size	Thread Size	
28-579	1/4"	1/4"	----
28-589	1/4"	3/8"	----

BRASS FEMALE COUPLER

Part#	Body Size	Thread Size	
28-560	1/4"	1/4"	----

BRASS HOSE ID COUPLER

Part#	Body Size	Barb Size	
28-690	1/4"	1/4"	----
28-691	1/4"	3/8"	----

STAINLESS STEEL MALE COUPLER

Part#	Body Size	Thread Size	
28-579SS	1/4"	1/4"	----

STAINLESS STEEL FEMALE COUPLER

Part#	Body Size	Thread Size	
28-560SS	1/4"	1/4"	----

STAINLESS STEEL INDUSTRIAL MALE PLUG

Part#	Body Size	Thread Size	
28-546SS	1/4"	1/4"	----

STAINLESS STEEL INDUSTRIAL FEMALE PLUG

Part#	Body Size	Thread Size	
28-534SS	1/4"	1/4"	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

ARO 210 INTERCHANGE

• Couplers have brass bodies and brass valves, 6 steel locking balls, NBR seal, and stainless steel springs
• Plugs are steel with green blue zinc plating
• Couplers have a full opening tubular valve for maximum flow and a built-in sleeve guard to minimize accidental disconnect
• Maximum working pressure is 250 PSI

MALE COUPLER

Part#	Body Size	Thread Size	
28-592	1/4"	1/8"	----
28-593	1/4"	1/4"	----
28-594	1/4"	3/8"	----

MALE PLUG

Part#	Body Size	Thread Size	
28-586	1/4"	1/8"	----
28-587	1/4"	1/4"	----

FEMALE COUPLER

Part#	Body Size	Thread Size	
28-583	1/4"	1/8"	----
28-584	1/4"	1/4"	----
28-585	1/4"	3/8"	----

FEMALE PLUG

Part#	Body Size	Thread Size	
28-578	1/4"	1/4"	----

HOSE ID COUPLER

Part#	Body Size	Barb Size	
28-601	1/4"	1/4"	----
28-603	1/4"	3/8"	----

HOSE ID PLUG

Part#	Body Size	Barb Size	
28-595	1/4"	1/4"	----
28-597	1/4"	3/8"	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

AUTOMOTIVE/ PARKER INTERCHANGE (Tru-Flate)

- Brass couplers are brass bodies with brass valves, 6 steel locking balls, NBR seal, and stainless steel springs. Steel couplers are steel bodies with steel valves, 6 stainless steel locking balls, NBR seal, and stainless steel springs.
- Plugs are brass or steel with green blue zinc plating
- Unique design has been field proven as a long-lasting, high performance coupling especially when used with pneumatic tools
- Maximum working pressure is 300 PSI

BRASS MALE COUPLER

Part#	Body Size	Thread Size	
28-515	1/4"	1/8"	----
28-516	1/4"	1/4"	----
28-517	1/4"	3/8"	----

BRASS FEMALE COUPLER

Part#	Body Size	Thread Size	
28-507	1/4"	1/4"	----
28-508	1/4"	3/8"	----

STEEL MALE COUPLER

Part#	Body Size	Thread Size	
28-516S	1/4"	1/4"	----
28-514S	3/8"	1/4"	----
28-519S	3/8"	3/8"	----

STEEL FEMALE COUPLER

Part#	Body Size	Thread Size	
28-507S	1/4"	1/4"	----
28-525S	3/8"	1/4"	----
28-526S	3/8"	3/8"	----

BRASS MALE PLUG

Part#	Body Size	Thread Size	
28-510B	1/4"	1/4"	----

BRASS FEMALE PLUG

Part#	Body Size	Thread Size	
28-501B	1/4"	1/4"	----

STEEL MALE PLUG

Part#	Body Size	Thread Size	
28-509	1/4"	1/8"	----
28-510	1/4"	1/4"	----
28-511	1/4"	3/8"	----
28-512	3/8"	1/4"	----
28-513	3/8"	3/8"	----

STEEL FEMALE PLUG

Part#	Body Size	Thread Size	
28-500	1/4"	1/8"	----
28-501	1/4"	1/4"	----
28-502	1/4"	3/8"	----
28-503	3/8"	1/4"	----
28-504	3/8"	3/8"	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

AUTOMOTIVE/ PARKER INTERCHANGE — QUICK DISCONNECTS

HOSE ID COUPLER

Part#	Body Size	Barb Size	
28-528	1/4"	1/4"	----
28-530	1/4"	3/8"	----
28-536	3/8"	1/4"	----
28-538	3/8"	3/8"	----

HOSE ID PLUG

Part#	Body Size	Barb Size	
28-518	1/4"	1/4"	----
28-520	1/4"	3/8"	----
28-523	3/8"	1/4"	----
28-524	3/8"	3/8"	----

PUSH-ON HOSE COUPLER

Part#	Body Size	Barb Size	
28-531	1/4"	1/4"	----
28-532	1/4"	3/8"	----

PUSH-ON HOSE PLUG

Part#	Body Size	Barb Size	
28-521	1/4"	1/4"	----
28-522	1/4"	3/8"	----

LINCOLN INTERCHANGE

- Couplers have brass bodies with steel sleeves, Acetal valves, 6 steel locking balls, Nitrile seal and stainless steel springs
- Plugs are steel with green blue zinc plating
- Manual style
- Unique design includes long nose and short ball groove
- Maximum working pressure is 250 PSI

MALE COUPLER

Part#	Body Size	Thread Size	
28-683	1/4"	1/4"	----

STEEL MALE PLUG

Part#	Body Size	Thread Size	
28-685	1/4"	1/8"	----
28-686	1/4"	1/4"	----

FEMALE COUPLER

Part#	Body Size	Thread Size	
28-684	1/4"	1/4"	----

STEEL FEMALE PLUG

Part#	Body Size	Thread Size	
28-687	1/4"	1/4"	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

ST SERIES...HIGH FLOW

SPECIFICATIONS

Brass - Coupler & Steel Plug

Temperature Range	-40° to 250°	
Rated Pressure	4650	2350

- Non-valved couplings for applications where maximum flow is required. Ideal for applications such as high pressure water and steam washers, carpet cleaners and mold coolant lines. They are often used in food processing, on fluid and dye transfer lines.
- Standard seals are Buna-N (Nitrile).

MALE PIPE COUPLER

BRASS

Part #	Body & Thread Size	
28-667	1/8"	----
28-665	1/4"	----
28-666	3/8"	----
28-668	1/2"	----
28-669	3/4"	----
28-670	1"	----

FEMALE PIPE COUPLER

BRASS

Part #	Body & Thread Size	
28-671	1/8"	----
28-651	1/4"	----
28-652	3/8"	----
28-672	1/2"	----
28-673	3/4"	----

MALE PLUG

STEEL

Part #	Size	
28-675	1/8"	----
28-639	1/4"	----
28-640	3/8"	----
28-676	1/2"	----
28-677	3/4"	----

FEMALE PLUG

STEEL

Part #	Size	
28-688	1/8"	----
28-619	1/4"	----
28-620	3/8"	----
28-679	1/2"	----
28-680	3/4"	----
28-681	1"	----

MOLD COOLANT-LINE QUICK COUPLERS

OPERATING PRESSURE:
200 PSIG (14.06 Kg/sq. cm)
Standard Seal:
SILICONE: -90°F to 400°F (-68°C to + 205°C)

- Our coolant couplers are engineered for optimum speed and performance in connecting coolant lines to molds used for thermoplastic, thermosetting, blow molding, diecasting and on other types of tooling and equipment utilizing a constant fluid flow pumped through cooling channels.



MALE PLUG (BRASS)

1/4" BASIC SIZE

Part #	Size	A	B	
29-900	1/8"	0.69	0.69	----
29-901	1/4"	0.84	0.94	----
29-902	3/8"	1.00	0.97	----

3/8" BASIC SIZE

Part #	Size	A	B	
29-906	1/4"	1.00	0.94	----
29-907	3/8"	1.00	1.13	----
29-908	1/2"	1.81	1.25	----

1/2" BASIC SIZE

Part #	Size	A	B	
29-911	1/2"	1.25	1.50	----
29-912	3/4"	1.50	1.56	----

FEMALE PLUG (STEEL)

1/4" BASIC SIZE

Part #	Size	
29-903	1/8"	----
29-904	1/4"	----
29-905	3/8"	----

3/8" BASIC SIZE

Part #	Size	
29-909	1/4"	----
29-910	3/8"	----

1/2" BASIC SIZE

Part #	Size	
29-913	1/2"	----
29-914	3/4"	----

MINI TYPE QUICK DISCONNECTS

MALE COUPLER

Part #	Size	
28-605	1/8"	----

FEMALE PLUG

Part #	Size	
28-608	1/8"	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

BRASS MUFFLERS

Materials:
Body: Brass
Element: Sintered Bronze
Max Operating Pressure: 300PSI
Temperature: 35° to 300°F
• Application: Designed to diffuse Air & Muffler noise to acceptable levels within OSHA noise requirements.
• Used on exhaust ports, valves, cylinders and air tools.
• Construction: Porous sintered bronze 40 micron filter element secured to a brass body

Part #	Size	
300-020	10/32"	----
300-021	1/8"	----
300-022	1/4"	----
300-023	3/8"	----
300-024	1/2"	----
300-026	3/4"	----
300-028	1"	----

40 Micron element

STAINLESS MUFFLERS



Materials:
Body: 303 Grade Stainless Steel
Element: 316 Grade Stainless Steel
Max Operating Pressure: 300PSI
Temperature: 35° to 392°F

Part #	Size	
300-031	10/32"	----
300-032	1/8"	----
300-033	1/4"	----
300-034	3/8"	----
300-035	1/2"	----
300-036	3/4"	----
300-037	1"	----

BRASS BREATHER VENT

Materials:
Body: Brass
Element: Sintered Bronze
Max Operating Pressure: 150PSI
Temperature: 35° to 300°F
• Application: Prevents Dirt and Foreign Particles from Entering Ports Open to Atmosphere. Typically used on Acting Cylinders
• Additional Use is Vacuum Relief or Pressure Equalization on Storage Vessels or Tanks
• Construction: Porous Sintered Bronzed 40 Micron Filter Element Secured to a brass body

Part #	Size	
300-000	10-32"	----
300-001	1/8"	----
300-002	1/4"	----
300-003	3/8"	----
300-004	1/2"	----
300-006	3/4"	----
300-008	1"	----

40 Micron element

STAINLESS BREATHER VENT



Materials:
Body: 303 Grade Stainless Steel
Element:316 Grade Stainless Steel
Max Operating Pressure: 150PSI
Temperature: 35° to 390°F

Part #	Size	
300-014	1/8"	----
300-015	1/4"	----
300-017	3/8"	----
300-018	1/2"	----
300-019	3/4"	----
300-007	1"	----

PRESSURE SNUBBER



Materials:
Body: Brass
Element: Sintered Bronze
Max Operating Pressure: 9000PSI
Temperature: 35° to 300°F
• Applications: Protect pressure instruments from sudden pressure surges and fluctuations providing more accurate gauge readings
• Construction: Solid brass housing with porous bronze element
• Can be used for mini in-line filters
• 5 different porosity elements per package, allows each user to adjust snubbing capacity for the specific application

Part #	Size	Porosity	
28-354	1/4"	40 um	----
28-353	1/4"	30 um	----
28-352	1/4"	25 um	----
28-351	1/4"	20 um	----
28-350	1/4"	10 um	----

Recommended Element Porosity Rating		
Rating	Color	Recommended Application
40 um	None	Viscous Fluids (over 500 ssu)
30 um	Black	Med. Type Oils (225 to 500 ssu)
25 um	Brown	Water & LT. Oils (30 to 25 ssu)
20 um	Green	Low Viscosity Fluids Fluids (under 30 ssu)
10 um	Red	Air and Other Gases
5 um	Purple	

SPEED CONTROL VALVE



Materials:
Body: Brass
Element: 40 Micron Sintered Bronze
Max Operating Pressure: 300PSI
Temperature: 35° to 300°F
• Application: Provide infinite variation of metering air flow at acceptable sound levels on air valve exhaust ports with complete safety
• The speed of an operating cylinder or air tool may be increased or decreased with the adjusting screw, the final position is locked in place by a lock nut
• Objectionable exhaust air noise is eliminated by the surrounding sleeve - 40 µm sintered bronze
• Brass Body
• Max operating pressure: 300PSI
• Operating temperature: 35° F to 300° F

Part #	Size	
940-800	1/8"	----
940-801	1/4"	----
940-803	3/8"	----
940-804	1/2"	----
940-805	3/4"	----
940-806	1"	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

STAINLESS SPEED CONTROL VALVE



70 Micron filter element

Materials:
Body: 303 Grade Stainless Steel
Element: 316 Grade Stainless Steel
Max Operating Pressure: 300PSI
Temperature: 35° to 392°F

Part #	Size	
940-810	1/8"	----
940-811	1/4"	----
940-812	3/8"	----
940-813	1/2"	----
940-814	3/4"	----
940-815	1"	----

MUFFLER W/ FLOW ADJUSTMENT



Materials:
Body: Brass
Element: Sintered Bronze
Max Operating Pressure: 300PSI
Temperature: 35° to 300°F

Part #	Size	
28-379	1/8"	----
28-380	1/4"	----
28-381	3/8"	----
28-382	1/2"	----

HIGH FLOW ALUMINUM MUFFLER

• hole pattern



Materials:
Body: Aluminum
Element: 50 Mesh Stainless Steel
Max Operating Pressure: 300PSI
Temperature: 35° to 160°F

Part #	Size	
940-822	1/8"	----
940-823	1/4"	----
940-824	3/8"	----
940-825	1/2"	----
940-826	3/4"	----
940-827	1"	----

HIGH FLOW STEEL MUFFLER



Materials:
Body: Steel
Element: 50 Mesh Stainless Steel
Max Operating Pressure: 300PSI
Temperature: 35° to 160°F

Part #	Size	
28-373	1/8"	----
28-374	1/4"	----
28-375	3/8"	----
28-376	1/2"	----
28-377	3/4"	----
28-378	1"	----

ALUMINUM HIGH FLOW MUFFLER

Materials:
Body: Aluminum
Element: 50 Mesh Stainless Steel
Max Operating Pressure: 300PSI
Temperature: 35° to 160°F
• Slit pattern
• Application: Used exhaust ports of Pneumatic valves or manifolds to reduce work area noise
• Construction: Aluminum body, 50 mesh self cleaning stainless steel screen corrosion resistant aluminum shell
• High flow & minimal back pressure

Part #	Size	
28-367	1/8"	----
28-368	1/4"	----
28-369	3/8"	----
28-370	1/2"	----
28-371	3/4"	----
28-372	1"	----

PLASTIC HIGH FLOW MUFFLER



Materials:
Body: Black Nylon
Element:50 Mesh Stainless Steel
Max Operating Pressure: 150PSI
Temperature: 35° to 120°F

Part #	Size	
28-363	1/8"	----
28-364	1/4"	----
28-365	3/8"	----
28-366	1/2"	----

NIPPLE INLINE FILTER



Materials:
Body: Brass
Element: 40 Micron Sintered Bronze
Max Operating Pressure: 300PSI
Temperature: 35° to 300°F

Part #	Size	
940-845	1/8"	----
940-846	1/4"	----
940-847	3/8"	----
940-848	1/2"	----

REPAIRABLE AIR/ OIL INLINE FILTER



Materials:
Body: Anodized Aluminum
Element: 40 Micron Sintered Bronze
Max Operating Pressure: 300PSI
Temperature: 35° to 200°F
• Application: Protect small air tools i.e. impact wrench grinders, screwdrivers and low pressure hydraulic applications
• Construction: All anodized, lightweight aluminum housing
• Can be installed directly before the air tool
• Features cleanable or replaceable 40 micron filter element

Part #	Size	
940-840	1/8"	----
940-841	1/4"	----
940-842	3/8"	----
940-843	1/2"	----
940-844	3/4"	----

I have never let my schooling interfere with my education.

– Mark Twain

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

CHROME PLATED BRASS MANIFOLDS

NEW

• 1/4" inlet and outlets

Part #	Description	
28-444	2 Port	----
28-445	3 Port	----
28-446	4 Port	----

• 1/4" Inlet on each end

MANIFOLDS - Aluminum with Black Anodizing

Materials:
Aluminum with black anodizing for corrosion resistance.
Specifications:
Max Operating Pressure: 1000PSI
Temperature: -10° to 200°F
Media: Air and liquids compatible with materials of construction.
• Ports column = # of ports in top of manifold



THREADED PORTS

Part #	Ports		A - out NPT	B - in NPT	C	D	E	F	G	H	J	K	M	R
28-450	4	----	1/8"	1/4"	1.00	0.50	0.75	1.5	0.17	3.25	0.70	0.50	0.88	0.15
28-452	6	----						3.00		4.75				
28-456	10	----						6.00		7.75				
28-457	2	----	1/4"	3/8"	1.25	0.63	0.88		0.20		0.89	0.63	1.06	0.18
28-458	3	----						0.88		3.00				
28-460	5	----						2.63		4.75				
28-464	9	----						6.13		8.25				
28-465	10	----						7.00		9.13				
28-467	3	----	3/8"	3/8"	1.25	1.00	1.13	1.13	0.20	4.25	0.89	0.63	1.56	0.18
28-468	4	----						2.25		5.38				
28-469	5	----						3.38		6.50				
28-470	6	----						4.50		7.63				

3 IN 1 ALUMINUM AIR MANIFOLD

No need to connect and disconnect every time you want to change tools. Supply 3 air tools from one outlet. These manifolds have one inlet with three 1/4 outlets.

Part #	Size	
320-120	1/4" Inlet	----
320-121	3/8" Inlet	----
320-122	1/2" Inlet	----

three 1/4" Outlets

AIR REGULATOR

• Rated for Inlet Pressrue up to 140PSI(10bar).
• Ambient and Fluid Tempreature:5~60°C(41~140°F)
• Port Threads:NPT
• Flow Capacity:See Below,at 0.7Mpa Inlet Pressure and set at 0.5Mpa.
• Assembly Bracket is included.

Part #	Size	Gauge Port	Regulating Range	
AR2	1/4"	1/8	0.05~0.85Mpa(0.5~8.5kgf/cm2)(7.25psi~123psi)	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

ASME CODED SAFETY VALVES

• Valves are manufactured to ASME standards and certified by the national board of boiler and pressure vessel inspectors.
• Bubble tight to 10% of set pop-off pressure.
• ASME safety valves are interchangeable with all other ASME valves of same size and pressure.
• Brass construction. Marked ASME, NB
• 1/ Blister card.

Part #	Male NPT	Pop-off Pressure	Air Flow	
87001	1/4"	70 PSI	70 CFM	----
87002	1/4"	125 PSI	120 CFM	----
87003	1/4"	150 PSI	140 CFM	----
87004	1/4"	200 PSI	170 CFM	----

Note: Valve resets after pressure drops 50%

NON-CODED SAFETY RELIEF VALVES

• Non-coded safety valves are constructed of the same materials as the AMSE safety valves but are not national board certified and cannot be used on applications requiring ASME components.
• Valves are equipped with a lift ring for instant relief and are staked at the factory at the pre set pop-off pressure.
• Marked ASME, UV, NB

Part #	Male NPT	Pop-off Pressure	
87008	1/4"	125 PSI	----
87009	1/4"	150 PSI	----

Warning: These valves are not to be used on compressors with a capacity over 15 CFM or 3 HP or 12 gallon storage tank.

COMPRESSOR TANK CHECK VALVES

• Used in compressor tanks to prevent air volume and pressure from escaping back into compressor heads while the compressor is not operating.
• Brass body with Teflon poppet.
• 1/8" Female NPT side port for pressure switch application.
• Maximum working pressure: 450 PSI
• Maximum temperature: 400°F

Part #	Tank Bung Hole Size	Compressor Air Line Size	SCFM	
87020	1/2" NPT Male	3/8" Tube Compression male	20	----
87021	1/2" NPT Male	1/2" Tube Compression male	20	----
87023	1/2" NPT Male	1/2" NPT Female	20	----

The memories we make with our family is everything.– Candace Cameron Bure

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

MULTI-PURPOSE AIR VENT

Part #	Size	
46-048	1/8"	----
46-048S*	1/8" SS	----

#303 SS

705

BRASS BICYCLE PUMP FITTING

Screw on swivel chuck for most hand operated tire pumps.
Buna-N-Seal • Deflator

INT x 3/16 Barb

Part #	Size	
32-782	3/16"	----

INFLATOR

INT x 3/16

Part #	Size	
32-783	3/16"	----

PNEUMATIC SLIDE VALVE

- Max Operating Pressure: 200 psig
- Temperatures:-20°F to +200°F

Manually operated slide valves provide simple on/off airflow control. They can be mounted horizontally, vertically or at any angle.

Open Position

MALE X FEMALE

Part #	Size	L	Hex	
20-780	1/8"	2.15	9/16"	----

INT = Inflation needle thread .305 in. OD x 32 threads per inch
(see page 371)

TANK & VENT VALVE

Three standard styles of valve bodies, complete with short core, for air lifts, water pumps, vacuum, pressurized containers, air jacks, and other pneumatic devices.
REGULAR: 300 PSI and cracking pressure 80 PSI

1/8" NPT - .9" LONG SPRING CORE

7/16" Hex

1/8 x INT

Part #	Size	
46-620	1/8	----

1/8" NPT 1.207"LONG SPRING CORE

7/16" Hex

1/8 x INT

Part #	Size	
46-621	1/8	----

1/4" NPT 1.46" LONG SPRING CORE

9/16" Hex

w/ Black cap

1/4 x INT

Part #	Size	
46-622	1/4	----

TANK VALVE ACCESSORIES

BLACK PLASTIC CAP

No gasket

Inflation needle theads

Part #	
46-630	----

SHORT NICKEL PLATED DOME CAP

Dome skirted type

Inflation needle thead

Part #	
46-631	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

COMPACT BLOW GUN W/RUBBER TIP

- Includes One Rubber Tip and One Safety Tip
- Zinc Alloy Body
- 1/4" FPT Inlet
- Maximum 150 psi (Recommended Working Pressure 90-120 psi)
- Safety Tip Limits Air Pressure to 30 psi When Dead-Ended per OSHA requirement
- Maximum 87 dba
- 1/8" Outlet

Part #	Size	
320-053	1/4"	----

SAFETY BLOW GUN

- Heavy-Duty Design
- Internal Safety Valve that Limits Air Pressure to Less than 30 psi When dead-ended per OSHA
- Aluminium Alloy Body
- 1/4" FPT Inlet
- Maximum 150 psi (Recommended Working Pressure 90-120 psi)
- Safety Tip Limits Air Pressure to 30 psi When Dead-Ended per OSHA Requirement
- Maximum 87 dba
- 1/8" Outlet

Part #	Size	
320-054	1/4"	----

SAFETY BLOW GUN

- N/P steel handle with plastic sleeve
- Brass Valve
- Zinc body
- Aluminum nozzle

90 PSI

1/8" Outlet

Part #	Size	
320-050	1/4" Inlet	----

5114 51-124 401 20430AD S148 D204-30 6475

COMPACT BLOW GUN

- With standard tip and safety tip
- Zinc Alloy Body
- 1/4" FPT Inlet
- Maximum 150 psi (Recommended Working Pressure 90-120 psi)
- Safety Tip Limits Air Pressure to 30 psi When Dead-Ended per OSHA Requirement
- Maximum 87 dba

Part #	Size	
320-055	1/4"	----

PISTOL GRIP BLOW GUN

- Lightweight, Ergonomic Design
- Delrin® Body
- Trigger Air Flow Control
- 1/4" FPT Inlet
- 3" Nozzle Ideal for Tight Spaces
- Recommended Working Pressure 90-120 psi
- Maximum 87 Dba

Part #	Size	
320-036	1/4"	----

PISTOL GRIP BLO-GUN

Material

150 PSI

- Body: POM (engineering plastic)
- Nozzle: nickel plated carbon steel
- Blue Handle Color

Features

- Simple construction, economic
- Global thread connection
- Durable and versatile applications
- 4 inch nozzle



Part #	Size	
320-035	1/4"	----

RUBBER TIPPED NOZZLE

Makes positive seal between gun and fuel line or other openings. Use only on air line regulated to 30 PSI or less.

Part #	Thread Size	
320-070	1/8 - 27	----

51-521 2058 D201RT 411R

HIGH FLOW SAFETY NOZZLE

Meets OSHA regulations of 30 PSI maximum outlet pressure when line pressure is 150 PSI or less. Has an air pressure bypass which prevents build up of tip pressure even if nozzle is blocked. Adapts to any blow gun with a 1/8" NPT nozzle port

Part #	Size	
320-075	1/8 MIP x Female Neelde Thread	----

51-338 SST10 411BT 2056

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

TIRE GAUGES

POCKET TIRE GAUGES

M - TIRE GAUGE

320-021

HEAVY DUTY DUAL FOOT TIRE GAUGE

320-022

DUEL ANGLE FOOT TRUCK PENCIL GAUGE

320-023

Part #	Pressure Range	Increment	Head	Body	Bar(psi/kPa)	
320-021	20-120psi	2 psi	Metal	Metal	4 sided plastic	----
320-022	10-120psi	2 psi	Plastic	Metal	4 sided plastic	----
320-023	20-120psi	2 psi	Metal	Metal	4 sided plastic	----

INFLATION NEEDLE

• See thread note below

Part #	
320-095	----

1 PIECE BLOW GUN TAPERED NOZZLE

Part #	Size	
320-076	NT	----

1 PIECE BLOW GUN STANDARD NOZZLE

Part #	Size	
320-077		----

VOLUME REGULATOR

Part #	FIP X MIP	
46-615	1/4	----

What size thread is an inflation needle (INT)?
Metric: 7.7mm OD, thread reoot diameter is 6.9mm x 0.794 pitch
English: 0.305 OD, threadroot diameter 0.302 in x 32 tpi (threads per inch)

1 PIECE DIAL TIRE GAUGE

Part #	
320-410	----

1 PIECE EXTENSION

Part #	Size	
320-080	NT	----

1 PIECE BLOW GUN ADAPTER

Part #	Size	
320-078	Female NT x 1/8 MPT	----

NYLON COIL AIR HOSE

- 200 psi working pressure
- 4:1 Safety factor (burst vs working pressure)
- Spring end sleeves to prevent kinking
- 1/4 MPT Brass fittings on both ends
- Temperature range 32°F to 120°F
- Packaged for retail sale

Part #	Description	Size	
307-030	25'	1/4" NPT	----
307-031	50'	1/4" NPT	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

HEX BALL FOOT CHUCK

Part #		
46-600	1/4 FPT Live Air	----

MALE BALL FOOT CHUCK

Part #		
46-605	1/4 MIP Live Air	----

BALL FOOT CHUCK W/ 1/4 ID HOSE BARB

Part #		
46-607	1/4 ID Live Air	----

DUAL HEAD STRAIGHT AIR CHUCK

Dual Head Air Chuck 1/4"FNPT,the length is 6.08",the head is Zinc-alloy,and the nut is brass with chrome plated.

Part #		
320-000	1/4	----

DUAL HEAD ANGLE FOOT AIR CHUCK

Dual Head Straight Foot Air Chuck 1/4"FNPT For inner duals;both ends lock on valve core threads,the length is 6.66",the head is Zinc-alloy,and the nut is brass with chrome plated.

Part #		
320-005	1/4	----

INFLATORS WITH GAUGE

INFLATOR/ GAUGE

- Rugged Zinc Cast Body with Brass Internals for long life
- Solid Brass Gauge Bar
- Built-in Air Relief Valve
- 6"Dual-Foot Air Chuck

320-010

INFLATOR/ GAUGE

- Rugged Zinc Cast Body with Brass Internals for Long Life
- Easy to View Built-In Sight Gauge
- Full Swivel Hose Fittings
- Protective Rubber Bumper
- Built-in Air Relief Valve
- 6"Dual-Foot Air Chuck

320-011

Part #	Pressure Range	Increment	Inlet	Hose Length	
320-010	10-120 psi	2 psi	1/4 FPT	12"	----
320-011	10-120 psi	2 psi	1/4 FPT	12"	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

AIR ACCESSORY SET

16PCS-AIR ACCESSORY SET

PART# 87-400

LIST PRICE: —

Contents of blister card package

Components and part#'s		Page #
1pc-1/4"FNPT industrial coupler	28-540	349
2pcs-1/4"FNPT industrial plugs	28-534	350
2pcs-1/4"MNPT industrial plugs	28-546	350
1pc-1/4" male connector	28-212	8
1pc-1/4" double female connector	28-059	3
1pc-ball foot chuck	46-600	363
1pc-blow gun	320-050	361
1pc-dial tire gauge	320-410	362
1pc-tapered rubber tip	320-070	361
1pc-blow gun safety nozzle	320-075	361
1pc-blow gun tapered nozzle	320-076	362
2pcs-inflation needles	320-095	362
1pc-25ft. nylon recoil hose	307-030	362

10PCS-AIR ACCESSORY SET

PART# 87-402

LIST PRICE: —

Contents of blister card package

Components and part#'s		Page #
1pc-1/4"female connector	28-059	3
1pc-blow gun safety nozzle	320-075	361
1pc-blow gun tapered nozzle	320-076	362
1pc-ball foot chuck	46-605	363
1pc-blow gun	320-050	361
1pc-1/4"FNPT industrial coupler	28-540	349
1pc-1/4" FNPT industrial plug	28-534	350
1pc-1/4"MNPT industrial plug	28-546	350
2pcs-inflation needles	320-095	362

7PCS-AIR ACCESSORY SET

PART# 87-404

LIST PRICE: —

Contents of blister card package

Components and part#'s		Page #
1pc-blow gun rubber tip	320-070	361
1pc-blow gun safety nozzle	320-075	361
1pc-blow gun tapered nozzle	320-076	362
1pc-extension	320-080	362
1pc-blow gun	320-050	361
2pcs-inflation needles	320-095	362

11PCS-AIR ACCESSORY SET

PART# 87-406

LIST PRICE: —

Contents of blister card package

Components and part#'s		Page #
1pc-blow gun rubber tip	320-070	361
1pc-blow gun safety nozzle	320-075	361
1pc-blow gun tapered nozzle	320-076	362
1pc-blow gun standard nozzle	320-077	362
1pc-blow gun adapter	320-078	362
1pc-hose&chuck assembly	320-414	362
1pc-blow gun	320-050	362
1pc-inflation needle	320-095	362
1pc-1/4"FNPT industrial coupler	28-540	349
1pc-1/4" FNPT industrial plug	28-534	350
1pc-1/4"MNPT industrial plug	28-546	350

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

17PCS-AIR ACCESSORY SET

PART# 87-408

LIST PRICE: —

Contents of blister card package

Components and part#'s		Page #
1pc-1/4" double female connector	50004	409
2pcs-1/4" double male connectors	54044	409
1pc-blow gun safety nozzle	320-075	361
1pc-blow gun tapered nozzle	320-076	362
1pc-dual-foot tire chuck	320-005	363
1pc-tire gauge	320-021	362
1pc-blow gun	320-050	361
1pc-1/4" FNPT industrial coupler	28-540S	349
2pcs-1/4" FNPT industrial plug	28-534	350
4pcs-1/4" MNPT industrial plug	28-546	350
2pcs-inflation needles	320-095	362

12PCS-AIR ACCESSORY SET

PART# 87-410

LIST PRICE: —

Contents of blister card package

Components and part#'s		Page #
1pc-blow gun safety nozzle	320-075	361
1pc-blow gun tapered nozzle	320-076	362
1pc-blow gun rubber nozzle	320-070	361
1pc-ball foot tire chuck	46-600	363
1pc-blow gun	320-050	361
1pc-1/4"FNPT industrial coupler	28-540	349
1pc-1/4" MNPT industrial coupler	28-552	349
2pcs-1/4"FNPT industrial plug	28-534B	350
2pcs-1/4"MNPT industrail plug	28-546B	350
1pc-inflation needle	320-095	362

20PCS-AIR ACCESSORY SET

PART# 87-412

LIST PRICE: —

Contents of blister card package

Components and part#'s		Page #
1pc-dual-foot tire chuck	320-005	363
1pc-tire gauge	320-021	362
1pc-blow gun rubber nozzle	320-070	361
1pc-blow gun adapter	320-078	362
1pc-1/4" double male connector	54044	409
1pc-1/4" double female connector	50004	409
1pc-blow gun safety nozzle	320-075	361
1pc-blow gun tapered nozzle	320-076	362
1pc-thread seal tape	982-107	370
1pc-blow gun	320-050	361
2pcs-1/4"FNPT industrial coupler	28-540S	349
2pcs-1/4"FNPT industrial plug	28-534	350
3pcs-1/4"MNPT industrial plug	28-546	350
2pcs-inflation needles	320-095	362
1pc-1/4"x 25Ft coil Nylon hose	307-030	362

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

1/4" X 1/4" NPT INDUSTRIAL 7PCS
PART# 87-414

LIST PRICE: —

Contents of blister card package

Components and part#'s		Page #
2pc-1/4"x1/4" FNPT T I/M coupler	28-540S	345
2pcs-1/4"x1/4" FNPT I/M plugs	28-534	350
2pcs-1/4"x1/4"MNPT I/M plugs	28-546	350
1pc-double 1/4" MNPT fitting	54044	409

1/4" X 1/4" NPT INDUSTRIAL 5PCS
PART# 87-416

LIST PRICE: —

Contents of blister card package

Components and part#'s		Page #
1pc-1/4"x1/4"FNPT I/M coupler	28-540S	349
4pc-1/4"X1/4" MNPT I/M plug	28-546	350

1/4" X 1/4" NPT INDUSTRIAL 5PCS
PART# 87-418

LIST PRICE: —

Contents of blister card package

Components and part#'s		Page #
1pc-1/4"x1/4"FNPT I/M coupler	28-540S	349
1pc-1/4"x1/4"FNPT I/M plug	28-534	350
1pc-1/4"X1/4" MNPT I/M plug	28-546	350
1pc-double 1/4" MNPT fitting	54-044	409

1/4" X 1/4" NPT INDUSTRIAL 3PCS
PART# 87-420

LIST PRICE: —

Contents of blister card package

Components and part#'s		Page #
1pc-1/4"x1/4" FNPT I/M coupler	28-540S	349
1pc-1/4"x1/4" FNPT I/M plug	28-534	350
1pc-1/4"x1/4" MNPT I/M plug	28-546	350

3/8" X 1/4" NPT AUTOMOTIVE 5PCS KIT
PART# 87-422

LIST PRICE: —

Contents of blister card package

Components and part#'s		Page #
1pc-3/8"x1/4" FNPT Automotive coupler	28-525S	353
2pcs-3/8"x1/4"MNPT Automotive plugs	28-512	353
1pc-double 1/4"MNPT fitting	28-212	8
1pc-double 1/4"FNPT fitting	28-059	3

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

STANDARD DRY GAUGES

STEEL CASE

All the gauges supplied by us are designed for long, reliable service under rugged conditions.
Typical applications include compressors, filter regulators, water pumps, beverage dispensing equipment, hydraulic and pneumatic systems, and other applications, where the media does not corrode brass. ALL CONNECTIONS ARE BRASS.

LOWER MOUNT

• Plastic lens (window)

1-1/2" FACE
1/8" NPT LOWER MOUNT

Part #	PSI	
80-501	0-15	----
80-502	0-30	----
80-503	0-60	----
80-504	0-100	----
80-505	0-160	----
80-506	0-200	----

2" FACE
1/4" LOWER MOUNT

Part #	PSI	
80-001	0-15	----
80-002	0-30	----
80-003	0-60	----
80-004	0-100	----
80-005	0-160	----
80-006	0-200	----
80-007	0-300	----
80-020	30-0 Vacuum	----

2-1/2" FACE
1/4" LOWER MOUNT

Part #	PSI	
80-031	0-15	----
80-032	0-30	----
80-033	0-60	----
80-034	0-100	----
80-035	0-160	----
80-036	0-200	----

CENTER BACK MOUNT

1-1/2" FACE
1/8" NPT CENTER BACK MOUNT

Part #	PSI	
80-511	0-15	----
80-512	0-30	----
80-513	0-60	----
80-514	0-100	----
80-515	0-160	----
80-516	0-200	----

2" FACE
1/4" CENTER BACK MOUNT

Part #	PSI	
80-301	0-15	----
80-302	0-30	----
80-303	0-60	----
80-304	0-100	----
80-305	0-160	----
80-306	0-200	----
80-307	0-300	----

2-1/2" FACE
1/4" CENTER BACK MOUNT

Part #	PSI	
80-331	0-15	----
80-332	0-30	----
80-333	0-60	----
80-334	0-100	----
80-335	0-160	----
80-336	0-200	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

LIQUID FILLED GAUGES

STAINLESS CASE

Liquid filled gauges enhance the reliability and integrity of the measuring system for long periods. The glycerine filling helps dampen the effects of vibration and pulsation. It also lubricates the movement which extends the life of the gauge. ALL CONNECTIONS ARE BRASS.

1-1/2" FACE
1/8" LOWER MOUNT

Part #	PSI	
80-601	0-15	----
80-602	0-30	----
80-603	0-60	----
80-604	0-100	----
80-605	0-160	----
80-606	0-200	----

Keep your mind open to change all the time. Welcome it. Court it. It is only by examining and re-examining your opinions and ideas that you can progress.

-Dale Carnegie

- Liquid Filled Gauges with a stainless case are used for protection in harsh environments.
- Stainless Steel Case
- Copper Alloy Wetted parts
- Polycarbonate window
- ± 1.5% of span accuracy
- Temp. Range -104°F to 158°F

2-1/2" FACE
1/4" LOWER MOUNT

Part #	PSI	
80-061	0-15	----
80-062	0-30	----
80-063	0-60	----
80-064	0-100	----
80-065	0-160	----
80-066	0-200	----
80-067	0-300	----
80-068	0-400	----
80-069	0-600	----
80-100	0-1000	----
80-101	0-1500	----
80-102	0-2000	----
80-103	0-3000	----
80-104	0-5000	----
80-105	0-10000	----
80-080	30-0 Vacuum	----
80-081	-30 to +30	----

4" FACE
1/4" LOWER MOUNT

Part #	PSI	
80-463	0-100	----

CENTER BACK MOUNT

1-1/2" FACE
1/8" CENTER BACK MOUNT

Part #	PSI	
80-611	0-15	----
80-612	0-30	----
80-613	0-60	----
80-614	0-100	----
80-615	0-160	----
80-616	0-200	----

2-1/2" FACE
1/4" CENTER BACK MOUNT

Part #	PSI	
80-201	0-15	----
80-202	0-30	----
80-204	0-60	----
80-203	0-160	----
80-205	0-100	----
80-206	0-200	----
80-207	0-300	----
80-208	0-400	----
80-209	0-600	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

Water Test Gauge

0-300 PSI DIAL
3/4" FEMALE HOSE CONNECTION

Part #	Face Size	
991-249	2"	----
991-250	2-1/2"	----

Water Test Gauge w/Lazy Hand (Maximum pointer)

2-1/2" GAUGE
0-300 PSI DIAL
3/4" FEMALE HOSE CONNECTION

Regular pressure hand pushes LAZY hand to peak operating or surge pressure point where it remains until you manually reset it. Excellent to determine if P/T valve is leaking from failure or if leaking is caused by surge of excessive pressures. (Attach gauge to Boiler Drain Valve overnight.) LAZY hand operates over entire gauge range of 0-300psi

Part #	
991-251	----

GAS TEST GAUGE

Pressure test residential and commerical pipe systems

Part #	Face Size	
GT15	0-15	----
GT30	0-30	----
GT60	0-60	----

BODY ONLY

Part #	Face Size	
991-259	3/4" FIP x 1/4" TAP	----

SYPHON

BRASS

Syphons protect instruments from effects of hot pressure media commonly used in steam applications

Part #	Size	
995-210	1/4" 90°	----
995-211	1/4" 180°	----
995-212	1/4" 270°	----
995-213	1/4" 360°	----

STEEL

Syphons protect instruments from effects of hot pressure media commonly used in steam applications

Part #	Size	
995-214	1/4" 90°	----
995-215	1/4" 180°	----
995-216	1/4" 270°	----
995-217	1/4" 360°	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

TAPES/ SEALANT

PTFE THREAD SEAL TAPE

- Density 0.4
- Thickness 3.5 MIL
- Meets MIL specs T-27730A

Part #	Size	Case Qty	
982-107	1/2" x 260"	500	----
982-108	1/2" x 520"	500	----
982-109	3/4" x 260"	350	----
982-110	3/4" x 520"	350	----

POP OUT COVERED SPOOL

GREY STAINLESS STEEL

- Density 1.2
- Thickness 4MIL
- Meets MIL specs T-27730A & CID A-A 58092

Part #	Size	Case Qty	
982-135	1/2" x 260"	250	----
982-136	1/2" x 520"	150	----
982-137	3/4" x 260"	150	----
982-138	3/4" x 520"	150	----

GREEN OXYGEN TAPE

- Density 1.2
- Thickness 3.5MIL
- Meets MIL specs T-27730A & CID A-A 58092

Part #	Size	Case Qty	
982-130	1/2" x 260"	250	----
982-131	1/2" x 520"	150	----
982-132	3/4" x 520"	150	----

PTFE BLUE SEAL TAPE

- Professional grade top -450 to +450°F
- Super long roll
- Twice the density of standard tape for less passes, lasts longer
- Density 0.8
- Thickness 3.5 MIL
- Meets MIL Spec T-27730A

Part #	Size	Case Qty	
982-120	1/2" x 1368"	250	----
982-121	3/4" x 1368"	150	----
982-122	1" x 1296"	150	----

YELLOW GAS LINE TAPE

- Density 0.9
- Thickness 4MIL
- Meets MIL specs T-27730A

Part #	Size	Case Qty	
982-125	1/2" x 260"	250	----
982-126	1/2" x 520"	150	----
982-127	3/4" x 520"	150	----

PVC ELECTRICAL TAPE

Rated to 176 degrees fahrenheit
Suitable for use up to 600V
UL Listed
Individually wrapped in cellophane

Part #	Size	
982140	3/4" X 60' Black	----

THREAD SEALANT

GASOILA SOFT-SET THREAD SEALANT WITH PTFE

Part#	Size	Units per case	
983100	1/4 pt. Brush	24	----
983101	1/2 pt. Brush	24	----
983102	1 pt. Brush	12	----

PLS 2 PREMIUM THREAD AND GASKET SEALER

Part#	Size	Units per case	
983110	1/4 pt. Brush	12	----
983111	1 pt. Brush	6	----

GASOILA NT NON-PTFE THREAD SEALANT

Part#	Size	Units per case	
983120	1/2 pt. Brush	12	----
983121	1 pt. Brush	6	----

JC-30 GASOILA HIGH-FILL

Part#	Size	Units per case	
983115	1/4 pt. Brush	12	----
983116	1 pt. Brush	6	----

FREE ALL DEEP PENETRATING OIL

Part#	Size	Units per case	
983125	6 oz. Aerosol	12	----
983126	11 oz. Aerosol	12	----

LUBE-IT ALL DEEP LUBRICATING OIL

Part#	Size	Units per case	
983130	6 oz. Aerosol	12	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

TRUCK AND TRAILER

INDUSTRY GRADE NYLON AIR COIL ASSEMBLY - SET

- Each kit contains one Emergency (Red) and one service (Blue) 1/2" O.D. nylon tubing assembly.
- 1/2" -14 NPTF end fitting with heavy gauge spring.
- Assemblies meet SAE J844 and DOT FMVSS 106 requirements.
- Temp rating -40° - +208°

Part #	Length	Pigtail Length Tractor end	Pigtail Length Trailer end	
39404	12'	6"	6"	----
39400	15'	12"	12"	----
39402	15'	40"	12"	----
39406	20'	12"	12"	----

FIFTH WHEEL SLIDER COIL

- Temperatures range -40 to 208°F
- 150 psi max pressure rating
- Meets SAE J844 and DOT FMVSS 106 requirements.
- (2) ¼" OD fittings assembled

Part #	Description	Length	Fittings	
39839	5th Wheel slider coil	up to 54"	(2) 1/4" MPT	----
39838	5th Wheel slider coil	up to 72"	(2) 1/4" MPT	----

3-IN-1 AND 4-IN-1 COMBINATION AIRLINE CABLE

- (2) 3/8" ID SAE J1402 rubber service and emergency with blue (service) and red (emergency) gladhand grip handle
- Color-coded grip helps to minimize incorrect tractor/trailer connections have glad handle with Vibraseal
- ABS power line (green) – meets SAE J2222 requirements
- Auxiliary power line (yellow) – fitted with SAESS60 plugs that have an inverted (male) ground pin 4-in-1 only
- SAE J560 Plugs with sleeves for superior corrosion protection and strain relief
- Corrosion resistant all brass fittings 1/2" male NPT w/ Vibraseal
- Tapered grip flexes with airline during tight turns for kink protection
- Temp rating -40 - 208°F

Part #	Description	
39825	Combo 3 in 1 assembly 15 ft.	----
39962	Combo 4 in 1 assembly 15 ft.	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

AIRBRAKE HOSE REPAIR KIT

- Fittings to repair hose with a minimum 3/4" OD
- Meets DOT 106 SAE j1402
- Brass sleeve and barb
- Pre-applied sealant

Part #	Description	
39855	3/8" Quick fix hose fitting	----
*39856	3/8" Quick fix hose kit- clam pack	----
39857	1/2" Quick fix hose fitting	----

*Supplied with hex tool

POGO STICKS CANNISTER STYLE

39425 39426

- Large diameter housing eliminates spring binding
- Increased resistance to sagging and bending
- Thick gauge heavy duty spring
- Used for all nylon and rubber air brake hose
- Forged steel mounting stud 7/16-20 thread
- All Pogo Sticks include Eyebolt and Nut

Part #	Size	Description	
39425	40"	Chrome finish	----
39426	40"	Zinc Plated Steel	----



39409 39410

HOSE HOLDERS



39411 39413



39416 39412

- ABS Plastic
- 2, 3 and 4 Hold

Part #	Size	Description	
39409	1/2"	2-Hose Holder Hex Head	----
39410	1/2"	2-Hose Holder	----
39411	1/2"	3-Hose Holder	----
39413	1/2"	3-Hose Hex Head w Cable tie	----
39416	1/2"	4-Hose V Bolt w Cable Tie	----
39412	1/2"	4-Hose Holder	----

HOSE SEPARATORS



39415 39418

- ABS Plastic

Part #	Size	Description	
39414	3/8"	2-Hose Separator	----
39415	3/8"	4-Hose Separator	----
39418	1/2"	2-Hose Separator	----
39419	1/2"	4-Hose Separator	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

TENDER KIT COMPONENTS

Part #	Description	
39411	3 hole holder	----
39469	Clip Carabiner	----
39472	1-1/2" ID Hanger Bracket	----
39473	Yoke	----

• Sold individually



SPRING WITH TANDEM FRAME CLIP

- Steel spring and clip - yellow dichromate finish
- 3/4" OD
- Beam clip

Part #	Description	
39477	Frame Clip with Cable Tie	----

Part #	Length	Description	
39463	6“ Spring	Tandem frame clip	----
39464	3“ Spring	Tandem frame clip	----
39471	Frame clip only		----

CLIPS

Part #	Description	
95631	ABS Clip for 1/2" Air Hose	----
95640	5" Axle Clip	----
95641	5-3/4" Axle Clip	----

Success is no accident. It is hard work, perseverance, learning, studying, sacrifice and most of all, love of what you are doing or learning to do.

– *Pele*

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

TENDER KIT

Complete Tender Kit includes:

- Large snap Clip
- Heavy duty spring
- Protective tube

Part #	Spring & Tube Length/ #pcs	One Clip	3 Hole Clamp	Yoke	
39442	16" / 1pc	1pc	1pc		----
39444	16" / 2 pcs	1pc	1pc	2pcs	----
39446	20"/ 1pc	1pc	1pc		----
39448	20"/ 2pcs	1pc	1pc	2pcs	----
39452	25" / 1pc	1pc	1pc		----
39453	25" / 2pcs	1pc	1pc	2pcs	----

HYDRAULIC TENDER KIT

Part #	Spring & Tube Length/ #pcs	Large Clip	Hanger Bracket	Yoke	
39457	25" / 2pcs	1pcs	1pc	2pcs	----

SLIDER BAR KITS

Part #	Spring & Tube Length/ #pcs	Large Clip	3 Hole Clamp	Slider Bar Length	Yoke	
39437	16" / 1pc	1pc	1pc	43"		----
39438	16" / 2pcs	1pc	1pc	43"	2pcs	----
39459	20"/ 2pcs	1pc	1pc	43"	2pcs	----
39460	25" / 1pc	1pc	1pc	43"		----
39461	25" / 2pcs	1pc	1pc	43"	2pcs	----
39470	16" / 1pc	1pc	1pc	38"		----
39462	16" / 2pcs	1pc	1pc	38"	2pcs	----
39451	25" / 1pc	1pc	1pc	38"		----
39454	25" / 2pcs	1pc	1pc	38"	2pcs	----

Spring & Tube



Slider Bar

BARS, SPRINGS, TUBES

Part #	Spring & Tube Length/ #pcs	
39443	16" Tube only	----
39447	20" Tube only	----
39436	25" Tube only	----
39466	16" Spring only	----
39467	20" Spring only	----
39468	25" Spring only	----
39474	38" Slider Bar	----
39475	43" Slider Bar	----

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

ALUMINUM GLADHANDS

- ½ " FPT port
- Aluminum Casting
- Permanent Clamp Screw
- Black rubber seals
- Stainless Steel filter
- Meet SAE J318 requirements

Part #	Description	Material	Seal	Filter	Port A	
39870	Universal	Aluminum	Blk Rubber	No	1/2"	----
39871	Universal with filter	Aluminum	Blk Rubber	Yes	1/2"	----
39877	Emergency Red	Aluminum	Blk Rubber	No	1/2"	----
39878	Emergency with filter	Aluminum	Blk Rubber	Yes	1/2"	----
39874	Service Blue	Aluminum	Blk Rubber	No	1/2"	----
39875	Service with filter	Aluminum	Blk Rubber	Yes	1/2"	----

PLATED ALUMINUM GLADHANDS

Part #	Description	Material	Seal	Filter	Port A	
39832	Universal Standard	Plated Aluminum	Blk Rubber	No	1/2"	----
39833	Service - Blue	Plated Aluminum	Blk Rubber	No	1/2"	----
39834	Emergency - Red	Plated Aluminum	Blk Rubber	No	1/2"	----
39828	Service 38 degree	Plated Aluminum	Blk Rubber	No	1/2"	----
39829	Emergency 38 drgree	Plated Aluminum	Blk Rubber	No	1/2"	----
39830	Service 38 degree	Plated Aluminum	Blk Rubber	No	3/8"	----
39831	Emergency 38 drgree	Plated Aluminum	Blk Rubber	No	3/8"	----

CAST IRON GLADHANDS



- ½ " FPT port
- One-piece casting eliminates problems with clamp separation
- "Positive-stop" post, assures a perfect connection
- Polyurethane seal resist oils, chemicals & provide improved sealing & service life
- Gladhands meet SAE J318 requirements including breakaway requirement.

Part #	Description	Material	Seal	Filter	Port A	
39506	Universal	Cast Iron	Black Polyurethane	No	1/2"	----
39507	Emergency	Cast Iron	Red Polyurethane	No	1/2"	----
39508	Service	Cast Iron	Blue Polyurethane	No	1/2"	----

ANGLE MOUNT ALUMINUM GLADHANDS

- For use in trailer mounting locations
- Dual port provides connection options
- Powder-coated clamp plates are color coded for easy identification
- Port "A" comes standard as unplugged
- (2) 3/8 inch FPT Ports (one plugged).
- (2) 11/32 inch diameter mounting holes.
- Available with Port "B" plugged or unplugged (plug is included, loose in bag)
- Meet SAE J318

Part #	Type	Material	Seal	Filter	Port A	Port B	
39511	Emergency	Aluminum	Blk Rubber	No	Unplugged	Plugged	----
39512	Service	Aluminum	Blk Rubber	No	Unplugged	Plugged	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

POWDER COATED IRON GLADHAND

- Tough powder coating improves wear & corrosion resistance
- Vividly colored to provide improved identification of service & emergency lines
- Stainless steel plate eliminates corrosion of the mating surface
- Polyurethane seal resist oil, chemicals, provide improved sealing & service life
- Meet or exceeds SAE J318 standard

Part #	Description	Filter	Port A	
39509	Service with blue poly seal	Yes	1/2"	----
39510	Emergency with red poly seal	Yes	1/2"	----

BRACKET MOUNT SWING AWAY GLADHAND

- Bracket allows 180° rotation allowing for easy hookups, eliminating the need to twist lines during connections
- Helps protect rear-trailer gladhands when not in use
- Filter and closed seal are recommended
- Spring design provides consistent tension throughout rotation
- Design provides both back port and bottom port capabilities
  Gladhand mount - 1/2" Male Thread

Part #	Description	Material	Seal	Filter	
39515	Service (Blue)	Aluminum	Blk Rubber	yes	----
39516	Emergency (Red)	Aluminum	Blk Rubber	yes	----

KNOB STYLE SHUTOFF GLADHAND

- Economical trailer shutoff gladhand
- Centered low-profile “snap-stop” knob
- Full face rubber seal
- Available with assembled or separate fittings.
- Meets SAE J318

Part #	Description	Material	Seal	Filter	
39520	1/2" Service (Blue)	Aluminum	Blk Rubber	No	----
39521	3/8" Service (Blue)	Aluminum	Blk Rubber	No	----
39522	1/2" Emergency (Red)	Aluminum	Blk Rubber	No	----
39524	3/8" Emergency (Red)	Aluminum	Blk Rubber	No	----

LEVER STYLE SHUTOFF GLADHAND



- Flange mount
- Metel handle shutoff
- Full face rubber seal
- Tough metal Ball valve
- Color coded
- Meets SAE J318

Part #	Description	Material	Seal	Filter	Port A NPT	Port B NPT	
39531	Emergency (Red)	Aluminum	Blk Rubber	No	3/8"	1/4"	----
39530	Service (Blue)	Aluminum	Blk Rubber	No	3/8"	1/4"	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

GLADHAND GRIPS

1/2" NPTF.

- Comes with hardware and sealant
- Color-coded red and blue for easy air line identification - clamshell
- Handles are heat, oil and UV-resistant.
- Meet SAE J318

Part #	Description	
39535	Poly grip hardware	----

ALUMINUM GLADHAND GRIPS

- 1/2" NPTF
- Each pack contains (1) red and (1) blue - clamshell
- One piece design
- No screws or plastic parts
- Easy to install
- Class II anodized coating provides greater corrosion resistance

Part #	Description	
39537	Sure grip	----

GLADHAND PACIFIER SEAL

- Seals Gladhand from moisture, dirt and debris

Part #	Description	
39566	Gladhand pacifier	----

GLADHAND SEALS

Seal Options:

- Rubber
- Polyurethane
- With screen filter
- Double lip
- Filter screen only

Part #	Description	
39541	Blue, Polyurethane	----
39542	Red, Polyurethane	----
39543	Black, Polyurethane	----
39556	Blue with a screen filter Polyurethane	----
39557	Red with a screen filter Polyurethane	----
39558	Black with a screen filter Polyurethane	----
39550	Blue Double lip, Polyurethane	----
39551	Red Double Lips, Polyurethane	----
39552	Double Lip, Polyurethane	----
39544	Grey, Closed Style, Polyurethane	----
39560	Filter, Screen, Gladhand	----
39559	Filter, Screen, Gladhand	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

39565

DUMMY GLADHAND COUPLING KIT

• 6 ½" coupling length

Part #	Connection	Vent	Material	
39563	Chain	Yes	Steel Yellow Zinc plated	----
39564	Chain	No	Steel Yellow Zinc plated	----
39565	Cable	N/A	Aluminum	----

NYLON GLADHAND AND PLUG HOLDER

39574 39575

• Stores Gladhand and electrical hook ups at a 45° angle.
• Can accept heavy ABS plug
• Standard mounting holes to install on back of cab.
• Glass-filled nylon, non-corrosive construction.

Part #	Description	
39574	1 plug slot	----
39575	2 plug slot	----

GLADHAND HOLDER KIT



• Steel - Zinc Yellow Dichromate
• Holds gladhands when disconnected

Part #	Description	
39573	Holder Kit	----
39572	Bracket only	----

GLADHAND LOCK

• Red molded plastic
• Prevents unwanted connections with trailers
• Protects idle units
• Universal for Aluminum and Iron Gladhands
• Supplied with 2-keys

Part #	Description	
39570	Gladhand Lock w/ 2 keys	----

**** Not an Anti theft device***

KING PIN LOCK-ANTI HOOK UP

• Cast, Zinc plated
• Anti-tractor, trailer hook-up
• Supplied with 2 keys

Part #	Description	
39860	King Pin Lock w/ 2 keys	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

AIR CYLINDER

- 300 series stainless steel cylinder shafts provide excellent corrosion resistance and extended cycle life -cylinders tested to over 500,000 cycles.
- Lightweight, corrosion resistant aluminum tube with die cast aluminum end caps.
- Rear clevis cast as integral part of the rear cover for improved durability and mounting integrity.
- Double acting, Emralon-coated piston cup assures smooth long lasting operation even in cold weather conditions to (- 40°F).
- Front end cap assembly includes pressure seal, dirt seal and oil impregnated bronze bushing.
- Cylinder tube imprinted with part number and date code for quick identification.
- All cylinders are factory pressure and leak tested prior to shipping.
- Front Cover Kit-Includes front cover with bushing and seals installed and two cylinder gaskets.
- Rear Cover Kit-Includes rear cover with two cylinder gaskets.
- Piston Cup Kit-Includes piston cup, lock nut and two cylinder gaskets.
- Shaft Kit-Includes shaft, lock nut and two cylinder gaskets.

Part #	Size	Stroke	Retracted	Extended	Type	
39672	2 1/2"	4.0"	9.89"	13.89"	push/pull	----
39673	2 1/2"	6.0"	11.89"	17.89"	push/pull	----
39674	2 1/2"	8.0"	13.89"	21.89"	push/pull	----
39675	2 1/2"	6.0"	13.75"	19.75"	Spring return	----
39676	3 1/2"	8.0"	15.60"	24.28"	push/pull	----
39677	3 1/2"	10.0"	16.92"	26.95"	push/pull	----

HIGH LIFT AIR CYLINDERS

- Aluminum tube with 16 RMS finish
- Temp rating -40 to 185°F
- Recommended working pressure 150 psi
- Minimum bursting pressure 150 psi
- 1275 lb. thrust at 100 psi
- 1158 lb. draw at 100 psi

Part #	Dia.	Stroke	Retracted	Extended	Type	
39654	4"	24"	34.5"	58.5"	push/pull	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

TAILGATE AIR CYLINDERS

39657 39660

- Die cast aluminum with mount hole for ½" pin and ¼" NPT port
- Molded piston cup
- Stainless steel piston rod with 5/8" – 18 thread
- 10 PSI – 120 PSI
- 10 psi min-120 psi max

Part #	Dia.	Stroke	Length	Type	
39655	2-1/2"	4.0"	13.37	Push/Pull	----
39656	2-1/2"	6.0"	17.37	Push/Pull	----
39657	2-1/2"	8.0"	21.37	Push/Pull	----
39658	2-1/2"	4.0"	14.71	Spring Ret	----
39659	2-1/2"	6.0"	19.75	Spring Ret	----
39660	3-1/2"	6.0"	20.23	Push/Pull	----
39661	3-1/2"	8.0"	24.23	Push/Pull	----
39662	3-1/2"	8.0"	26.98	Push/Pull	----
39663	3-1/2"	10.0"	28.98	Push/Pull	----

TAILGATE AIR CYLINDERS

39665 39667

- Machined aluminum, 5/8" diameter ,stainless steel shaft with 5/8" - 18 threads, "O" rings and a UHMW polyethylene wear band
- Direct replacements to Haldex and MGM
- Standard operating pressure 100 psi
- 90psi min to 150 psi max

Part #	Dia.	Stroke	Bracket	Type	
39665	6"	3"	Yes	Spring Ret	----
39667	6"	4.38"	No	Spring Ret	----

FIFTH WHEEL AIR CYLINDER

- 1/4" FPT port cast aluminum front and rear
- 2-1/2" Bore
- 6-3/4" stroke
- Front and rear mounting hole for 17/32" clevis,
- 100 psi
- Gold anodized tube for corrosion resistance

Part #	Description	
39669	Fifth Wheel Air Cylinder	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

AIR TANK DRAIN PULL VALVE

Part #	Size	Description	
39595	1/4" male	5ft nylon coated pull cable	----
39596	1/4" male	4ft nylon coated pull cable	----
39597	1/4" male	3ft nylon coated pull cable	----
39600	1/4" male	Air valve only	----

AIR TANK CHECK VALVE

- Single check valves allow air to pass from a single source to its destination, and prevent air travel in the opposite direction.

Part #	Male x Female	
39604	1/4"	----
39605	3/8"	----
39606	1/2"	----

D-2 STYLE AIR BRAKE GOVERNOR

- Opening and closing pressures of 100 to 120 psi
- High temperature O-ring construction
- Gasket and plugs included
- Replaces Bendix 275491 & KN18530

Part #	Thread	Description	
39592	6-1/8" NPT	Air Brake Governors D-2 style	----

IN-LINE QUICK RELEASE VALVE

- Quick release for the air break system
- 3/8” female exhaust port
- 2-3/8” female delivery port
- Cracking pressure: 1 PSI
- Helps meet the FMVSS -121 requirement for timing

Part #	Description	
39610*	3/8" NPT In-Line quick release valve	----
39611**	1/2" NPT In-Line quick release valve	----

* Replaces Bendix 229859, 288351 & KN32005
** Replaces Bendix 229860 & KN32011

R-12 RELAY VALVE

- ¼” Relay Valve with multiple delivery ports

Replaces Bendix 102166, 102626, 103009

Part #	Supply Port	Delivery Port	Description	
39613	1/2" NPT	4, 1/2"NPT	4 psi no Bracket	----
39614	1/2" NPT	4, 1/2"NPT	4 psi Relay Valve	----
39615	3/4" NPT	2, 1/2" NPT	4 psi Relay Valve	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

R-14 RELAY VALVE

- ¼" Relay Valve with two delivery and supply ports
- Replaces Bendix 103010

Part #	Supply Port	Delivery Port	Description	
39616	2-3/4"NPT	2-1/2"NPT	4 psi Relay Valve	----

THREE WAY SOLENOID

- Operates a minimum GF 50,000 cycles
- Inlet port normally closed
- Must be mounted vertically with the air inlet port facing up
- 1/4" female NPT ports
- 12 Volts
- 100-120 psi operating pressure
- Attached mounting bracket with two 9/32" diameter mounting holes on 2-1/2" centers

Part #	Supply Port	Description	
39684	2, 1/4" FPT	Three way Solenoid	----

UNIVERSAL SOLENOID

- Operates a minimum of 50,000 cycles.
- 125 amps at 12 volts.
- Continuous voltage.
- One on/off circuit
- 5/16 inch side studs, No. 10 top stud(s).
- 2 1/8 on Center
- 5/16 x 19/32
- Hardware included.
- Normally open

Part #	Description	
39687	4 stud Solenoid	----
39688	3 stud Solenoid	----

AIR SOLENOID VALVE

- Operates a minimum of 50,000 cycles.
- 100 psi max pressure.
- 1/4" Thread
- 10 Watts, 12 VDC
- Replaces Neway 90054075

Part #	Description	
39689	12V Closed	----
39690	12V Open	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

SEVEN-WAY COILED CABLE ASSEMBLIES

- ABS assemblies are heavy duty to power trailers
- HD Green gives clear ABS identification
- Resists abrasion, great coil retention
- Heavy duty plugs with spring guards
- ABS Cable meets SAE J2394
- Operating temperature range of -55° to +185°F

Pin Location	Color code	Gauge	Circuit
1	White	8	Ground
2	Black	12	Clearance, side and ID lamps
3	Yellow	12	Left turn and Hazard
4	Red	10	Stop lamp and Anti-lock
5	Green	12	Right turn and Hazard
6	Brown	12	Tail and Plate lamp
7	Blue	10	ABS Power Aux



ABS

Part #	Length	Description	
39736	12'	Coiled Electrical Cord, ABS w/12 in lead, w/plugs, Green	----
39737	15'	Coiled Electrical Cord, ABS w/12 in lead, w/plugs, Green	----

SEVEN-WAY COILED CABLE BLACK

- This high quality, durable construction is recommended for single-trailer configurations using standard lighting on non-ABS vehicles.
- Durable black outer jacket with heavy duty zinc die cast plugs and two spring guards included.

Pin	Color code	HD Gauge	Eco Gauge	Circuit
1	White	10	12	Ground
2	Black	12	14	Clearance, side and ID lamps
3	Yellow	12	14	Left turn and Hazard
4	Red	12	14	Stop lamp and Anti-lock
5	Green	12	14	Right turn and Hazard
6	Brown	12	14	Tail and Plate lamp
7	Blue	12	14	ABS Power Aux



STANDARD - HEAVY DUTY

Part #	Length	Description	
39738	12'	Coiled Electrical Cord, w/12 in lead, w/plugs, Black	----
39739	15'	Coiled Electrical Cord, w/15 in lead, w/plugs, Black	----

STANDARD - ECONOMY

Part #	Length	Description	
39740	12'	Coiled Electrical Cord, w/12 in lead, w/plugs, Black	----
39741	15'	Coiled Electrical Cord, w/12 in lead, w/plugs, Black	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

SIX WAY COILED ELECTRIC CABLE ASSEMBLY

- 6', 8', 12' Length
- Includes 2 Thermoseal 6-way plugs
- For light duty towing applications such as boats and utility trailers
- Plugs are molded for moisture and corrosion resistance
- 4/14 Gauge cable
- Flexible from -55°F to 150°F (-66°C to 66°C)

Part #	Description	
39752	6ft, 14awg w/12" Lead at 2 ends	----
39753	8 ft, 14awg w/12" Lead at 2 ends	----
39754	12ft,14awg w/12" Lead at 2 ends	----

FOUR WAY COILED ELECTRIC CABLE ASSEMBLY

- 4/14 Gauge cable
- 12' & 15' length
- Includes 2 Thermoseal 4-way plugs
- For light duty towing applications such as boats and utility trailers
- Plugs are molded for moisture and corrosion resistance
- Flexible from -55°F to 150°F (-66°C to 66°C)

Part #	Description	
39748	12' with 12" Lead, both ends 4/14awg	----
39749	15' with 12" Lead, both ends 4/14awg	----

DUEL POLE COILED ELECTRIC CABLE ASSEMBLY

- Black Jacket
- 12' & 15' length
- 200 Amp at 12 VDC.
- Zinc die cast plugs.
- 4 gauge cable.

Part #	Description	
39744	12' Coil With 12" Lead at 2 ends 4awg	----
39745	15' Coil With 12" Lead at 2 ends 4awg	----

SINGLE POLE COILED ELECTRIC CABLE ASSEMBLY

- Black Jacket
- 12' & 15' length
- For applications that require direct electrical power to trailer lift gates.
- Rated at 265 amps on/off service (30 seconds on/50 seconds off).
- Zinc die cast plugs with spring guards included.
- 4 gauge cable.

Part #	Description	
39742	12' Coil With 12" Lead both ends 4awg	----
39743	15' Coil With 12" Lead both ends 4awg	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

7 WAY PLUGS AND SOCKETS

39758

39757

39772

- Heavy-duty, nickel-plated zinc die cast housings
- Brass terminal pins for maximum current carrying ability
- Field repairable with standard tools
- Fully interchangeable with other SAE-type, 7-way connectors
- ATA marked wire terminals.
- Internal clamp holds cable securely in place.
- Standard seven-way plugs meet ATA and SAE J560 requirements
- ISO plugs meet ISO 3731:1997 requirements.
- ISO socket prevents connections with Non-ISO plugs - Used in tractor/ trailer systems
- ISO color-coded yellow, non-corrosive reinforced nylon housing.

PLUGS

Part #	Description	
39757	7-Way Single Grip Plug w/Spring Guard	----
39758	7-Way Single Grip Plug NO Spring.	----
39772	7-Way Double Grip Plug w/Spring.	----
39773	7-Way Double Grip Plug NO Spring Guard	----
39788	7-way ISO plug	----

SOCKETS

Part #	Description	
39774	Solid Pin 7-Way Metal Socket	----
39775	Split Pin 7-Way Metal Socket	----
39789	7-way, ISO socket	----

7 WAY DOUBLE GRIP PLUG

- T-Grip weather guard
- Plastic grip

Part #	Description	
39818	7-Way Double Grip Plug, Plastic	----

6 AND 7 WAY ADAPTER

Part #	Description	
39786	Seven way plug to Six Way Socket Adapter	----
39787	Six way plug to Seven Way socket Adapter	----

RV 7-WAY PLUG

- Primarily used in RV applications.
- Constructed of molded PVC for impact resistance
- Blade Style Pin

Part #	Description	
39819	7-way Plastic plug	----

RV 7-WAY SOCKET

- RV Screw-type socket
- 6-24 VDC.
- Mounting 2-1/4" inch on center .
- Constructed of molded PVC

Part #	Description	
39820	7-way socket	----

WARNING: This product can expose you to chemicals, including Nickel, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

6 - WAY PLUGS AND SOCKETS

Part #	Description	
39782	6-Way Double Grip Metal Plug w/Spring Guard.	----
39783	6-Way Metal Socket.	----

4 WAY PLUGS AND SOCKETS

- Heavy-duty zinc die cast housings on plugs and sockets.
- Plug locking system works with socket door to ensure proper hookup and prevent unintentional disconnections.
- Spring guard supports and protects cable.

4 - WAY

Part #	Description	
39778	4-Way Double Grip Metal Plug w/Spring Guard.	----
39779	4-Way Metal Socket.	----

2 POLE PLUGS AND SOCKETS

- 200 amp 4 gauge wire capacity.
- Heavy-duty zinc die cast housing.
- Internal ground.
- Spring guard supports and protects cable.

Part #	Description	
39768	2 Pole Double Grip Metal Plug w/Spring Guard.	----
39769	2 Pole Metal Socket	----

SINGLE POLE PLUGS AND SOCKETS

- Used to provide power to heavy draw auxiliary trailer equipment.
- Heavy-duty zinc die cast housings.
- Power and ground terminals hold up to 1/0 gauge wire.

Part #	Description	
39764	1-Way Double Grip Plug w/Spring Guard.	----
39765	1-Way Double Grip Plug w/Spring Guard and Ground Kit	----
39766	1-Way Metal Socket	----
39767	1-Way Metal Socket and Ground Kit	----

GROUND KIT

Part #	Description	
39809	Ground Kit (Bolt, Nut and Wire Lug) for 1-Way Plug or Socket	----

PROTECTOR BOOT FOR PLUG

- Protective rubber boot seals out moisture and contaminants

Part #	Description	
39807	Protector Boot	----

WARNING: This product can expose you to chemicals, including Nickel, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

7 WAY SOCKET WITH CIRCUIT BREAKER

- Non-corrosive, reinforced nylon housing for added durability.
- Designed for No. 8 ring terminals.
- ATA color-coded contacts.
- Solid brass split pins are zinc-plated for corrosion resistance.
- Each socket includes automatic reset circuit breakers with positive snap action to eliminate arcing (unless otherwise noted).
- Mounting holes are 4 1/2 inch on center and include steel bushings for added housing protection.
- Adhesive-backed mounting gasket included.
- Circuit breaker sockets meet SAE J560 requirements.

Part #	Description	
39792	No circuit breakers	----
39793	15amp Plastic with circuit breakers	----
39794	20amp Plastic with circuit breakers	----
39795	30amp Plastic with circuit breakers	----

7 WAY CIRCUIT CHASER

- Instantly finds short or faulty circuits
- Portable

Part #	Description	
39805	7 way circuit	----

CIRCUIT BREAKERS - PLASTIC

- Colored Battery molded Stud
- 12 Volt
- Meets SAE j553 requirements
- Nuts included

Part #	Description	
39800	15 AMP	----
39801	20 AMP	----
39802	25 AMP	----
39803	30 AMP	----

NOSE BOX - DEEP

- Zinc - extra deep

Part #	Description	
39814	Deep Nose Box	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

BATTERY GROUND STRAP

- 4 gauge wire.
- Molded zinc-plated steel lugs and tin-plated copper stranding.
- 7/16 inch diameter bolt hole.
- 12" Long

Part #	Description	
39712	12", 4 Gauge ground strap	----

STAINLESS STEEL BATTERY NUT

Part #	Type	
39713	3/8"	----

RUBBER GROMMET

- Black Rubber

Part #	ID	OD	
95450	5/16"	9/16"	----
95451	5/8"	1 1/4"	----
95452	3/4"	1 3/4"	----

Put your heart, mind, and soul into even your smallest acts. This is the secret of success.

–Swami Sivananda

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

DEER WHISTLES

- Produces two separate and unique frequencies
- High output airflow activated
- Can be removed from base for cleaning and car washes
- Mounts with high bond tape **(included)**
- Lowers risk for vehicle-animal collisions

Part #	Description	
39465	2 pack whistle	----

CABLE TIE STRAPS - NYLON

- Used to secure and bundle
- CSA Certified
- RoHs Compliant
- UV or Standard

STANDARD

Part #	Length	Strength	Package Qty	
95601	7 1/2"	50lb	100	----
95602	11"	50 lb	100	----
95603	14.5"	50 lb	100	----
95604	24"	175 lb	50	----
95605	36"	175lb	50	----
95606	48"	175 lb	50	----

UV BLACK

Part #	Length	Strength	Package Qty	
95610	7 1/2"	50lb	100	----
95611	14"	50 lb	100	----
95612	24"	175lb	50	----
95613	36"	175lb	50	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

CONSPICUITY TAPE

95620



Tape is designed for trucks, trailers, and other vehicles for easy nighttime vehicle recognition and increased road safety. It is a high quality, durable microprismatic retroreflective material with a pressure sensitive adhesive. The solid construction does not require edge sealing. Conspicuity tape provides superior reflectivity and may help reduce accidents.

- DOT -C2 Certified
- Meets or exceeds NHTSA, FMVSS 108 & ASTM D4956
- Meets Canada TSD 108
- 10 year durability

Part #	Description	App. Wt.	
95620	2" x 150' Roll of 11" Red / 7" White	0.32	----
95621	2" x 150' Roll of 6" Red / 6" White	0.32	----
95622	2" x 150' Roll of solid white	0.32	----
95623	2" x 18", kiss cut strip, white	0.03	----
95624	2" x 18" kiss cut strip of 11" Red / 7" White	0.03	----

95625



95627

- Meets or exceeds ANSI/ASAE S279, ANSI/ASAE S276 & ASTM D-4956
- 7 year durability

Part #	Description	App. Wt.	
95625	1" X 150' Roll of solid yellow	0.17	----
95626	2" X 150' Roll of solid yellow	0.32	----
95627	3" round all plastic reflector, Red	0.06	----
95628	3 3/4" x 6 1/2" American flag, type IV HIP	0.02	----

95628

TARP STRAPS

- Heavy Duty EPDM tarp straps
- Longer lasting than rubber
- Greater stretch length
- Ozone and weather resilient
- Made in the USA

Part #	Strap Length	Material	Description	Qty	
990790	10"	EPDM	Tarp strap with S hook	50	----
990791	15"	EPDM	Tarp strap with S hook	50	----
990792	21"	EPDM	Tarp strap with S hook	50	----
990793	31"	EPDM	Tarp strap with S hook	50	----
990794	41"	EPDM	Tarp strap with S hook	50	----

NYLON DOT AIR BRAKE TUBING

- Air Brake Tubing available from inventory in a large variety of colors and sizes
- Superior cold weather flexibility and abrasion resistance
- UV and ozone resistant nylon
- Meets or exceeds SAEJ844 (Type A - non-reinforced & Type B - reinforced)
- Meets or exceeds DOT requirements for use with compression fittings (NOTE: SAE does not recognize 1/8", 5/32" or 3/16" O.D. tubing for use with air brake systems)
- Air Brake Tubing identified per SAE J844 & FMVSS No. 106 Brake Hoses, 49 CFR 571.106
- Conforms to our own rigorous qualification and inspection testing which exceeds SAE and DOT requirements
- Designed to operate at up to 150 psi in air brake systems
- Resistant to attack by gasoline, diesel fuel and commonly used road and cleaning chemicals
- Air Brake Tubing available on bulk spools or by packages
- Operating range: -40°- 200°F - Not made for fuel

Part Number	Color	Length	Nominal O.D.	Nominal Wall	
38-950B2	Black	2000'	1/8"	0.023"	----
38-950	Black	100'	1/8"	0.023"	----
38-95BA	Black	50'	1/8"	0.023"	----
38-951B1	Black	1000'	5/32"	0.032"	----
38-951	Black	100'	5/32"	0.032"	----
38-951BA	Black	50'	5/32"	0.032"	----
38-953B1	Black	1000'	3/16"	0.035"	----
38-953	Black	100'	3/16"	0.035"	----
38-953BA	Black	50'	3/16"	0.035"	----
38-9523	Black	1000'	1/4"	0.040"	----
38-9522	Black	500'	1/4"	0.040"	----
38-952	Black	100'	1/4"	0.040"	----
38-952BA	Black	50'	1/4"	0.040"	----
38-952U1	Blue	1000'	1/4"	0.040"	----
38-952U	Blue	100'	1/4"	0.040"	----
38-952UA	Blue	50'	1/4"	0.040"	----
38-952O	Orange	100'	1/4"	0.040"	----
38-952OA	Orange	50'	1/4"	0.040"	----
38-952G1	Green	1000'	1/4"	0.040"	----
38-952G	Green	100'	1/4"	0.040"	----
38-952GA	Green	50'	1/4"	0.040"	----
38-952R1	Red	1000'	1/4"	0.040"	----
38-952R	Red	100'	1/4"	0.040"	----
38-952RA	Red	50'	1/4"	0.040"	----
38-952Y1	Yellow	1000'	1/4"	0.040"	----
38-952Y	Yellow	100'	1/4"	0.040"	----
38-952YA	Yellow	50'	1/4"	0.040"	----
38-954B5	Black	500'	5/16"	0.040"	----
38-954	Black	100'	5/16"	0.040"	----
38-954BA	Black	50'	5/16"	0.040"	----
38-960B5	Black	500'	3/8"	0.062"	----
38-960	Black	100'	3/8"	0.062"	----
38-960BA	Black	50'	3/8"	0.062"	----
38-960U5	Blue	500'	3/8"	0.062"	----
38-960U	Blue	100'	3/8"	0.062"	----
38-960UA	Blue	50'	3/8"	0.062"	----
38-960O5	Orange	500'	3/8"	0.062"	----
38-960O	Orange	100'	3/8"	0.062"	----
38-960OA	Orange	50'	3/8"	0.062"	----
38-960G5	Green	500'	3/8"	0.062"	----
38-960G	Green	100'	3/8"	0.062"	----
38-960GA	Green	50'	3/8"	0.062"	----
38-960R5	Red	500'	3/8"	0.062"	----
38-960R	Red	100'	3/8"	0.062"	----
38-960RA	Red	50'	3/8"	0.062"	----

Part Number	Color	Length	Nominal O.D.	Nominal Wall	
38-960Y5	Yellow	500'	3/8"	0.062"	----
38-960Y	Yellow	100'	3/8"	0.062"	----
38-960YA	Yellow	50'	3/8"	0.062"	----
38-965B5	Black	500'	1/2"	0.062"	----
38-965	Black	100'	1/2"	0.062"	----
38-965BA	Black	50'	1/2"	0.062"	----
38-965U5	Blue	500'	1/2"	0.062"	----
38-965U	Blue	100'	1/2"	0.062"	----
38-965UA	Blue	50'	1/2"	0.062"	----
38-965O5	Orange	500'	1/2"	0.062"	----
38-965O	Orange	100'	1/2"	0.062"	----
38-965OA	Orange	50'	1/2"	0.062"	----
38-965G5	Green	500'	1/2"	0.062"	----
38-965G	Green	100'	1/2"	0.062"	----
38-965GA	Green	50'	1/2"	0.062"	----
38-965R5	Red	500'	1/2"	0.062"	----
38-965R	Red	100'	1/2"	0.062"	----
38-965RA	Red	50'	1/2"	0.062"	----
38-965Y5	Yellow	500'	1/2"	0.062"	----
38-965Y	Yellow	100'	1/2"	0.062"	----
38-965YA	Yellow	50'	1/2"	0.062"	----
38-970BC	Black	250'	5/8"	0.092"	----
38-970	Black	100'	5/8"	0.092"	----
38-970BA	Black	50'	5/8"	0.092"	----
38-970GC	Green	250'	5/8"	0.092"	----
38-970G	Green	100'	5/8"	0.092"	----
38-970GA	Green	50'	5/8"	0.092"	----
38-970RC	Red	250'	5/8"	0.092"	----
38-970R	Red	100'	5/8"	0.092"	----
38-970RA	Red	50'	5/8"	0.092"	----
38-975BC	Black	250'	3/4"	0.092"	----
38-975	Black	100'	3/4"	0.092"	----
38-975BA	Black	50'	3/4"	0.092"	----
38-975GC	Green	250'	3/4"	0.092"	----
38-975G	Green	100'	3/4"	0.092"	----
38-975GA	Green	50'	3/4"	0.092"	----

FUEL LINE AND VAPOR EMISSION



•SAE 30R7
•Nitrile tube w/ spiral synthetic cord, hypalon cover.
•50 p.s.i. working pressure. 1/2 -35 PSI
•-40^0 F to + 257^0 F temperature range.
•Low pressure/ high temperature fuel for cars, light trucks, and small engines.
• Meets SAE J1402

Part #	ID	OD	Length	
38-920	3/16	13/32	25'	----
38-926	5/16	9/16	25'	----
38-923	1/4	1/2	25'	----
38-927	3/8	5/8	50'	----

AIR BRAKE HOSE

• Black

•Spiral synthetic cord reinforcement with neoprene cover.
•-40^0 F to +200^0 F temperature range.
•Max opperating pressure 255 psi
•Max burst pressure 900 psi
• Meets SAE J1402

Part #	ID	OD	Length	
38-910	3/8	3/4	50'	----
38-915	1/2	7/8	50'	----

Work hard, stay positive, and get up early. It's the best part of the day.

– George Allen, Sr.

HYDRAULIC ADAPTERS & ACCESSORIES

STEEL ADAPTERS

Technical information ... 394
Profile size chart 400
Steel Pipe Swivels 402
37° JIC Flare Straights 404
37° JIC Flare Shapes 406
Bulkhead Adapters 407
Steel Pipe Fittings 409
O-Ring Adapters Straight . 413
JIC Swivels 415
O-Ring Adapters 417
O-Ring Face Seal 420
BSPT/ BSPP Adapters 423
Metric Adapters 425

HYDRAULIC QUICK DISCONNECTS

Thread to Connect - Wing 427
ISO A Interchange 427
ISO B Interchange 427
Flush Face ISO 428
VEP Series 428
AG Interchange 429
Hydraulic Jack Q/D 429

HYDRAULIC VALVES & ACCESSORIES

Flow Control Valve 430
Variable Flow Control 431
Air Breathers 431

PLATING SPECIFICATION

Our standard Trivalent, Cr^{+3} plating performs at nearly double the S.A.E. corrosion resistance requirement. The plating meets ASTM B633, Fe/Zn 5. The thickness is 5um-13um. This plating is silver in appearance and has been testing at 96 hours to white rust and 120 hours to red rust.

WORKING PRESSURE

The tables on the following pages list the recommended working pressure for a variety of hydraulic fittings made in accordance with certain industry standards. Many factors such as impulse, vibration, mechanical shock, and improper assembly may affect the integrity of the fitting connection.

We recommends sufficient testing be conducted to ensure that performance levels will be safe and satisfactory, especially if installed in systems operating at elevated pressures or in severe conditions. Working pressure ratings are capable of a 4 to 1 minimum burst. All steel fittings meet or exceed the minimum SAE pressure ratings. Always consider application and maximum pressure requirements when selecting fittings.

METHODS FOR INSTALLING FITTINGS

There are three methods for installing a fitting:

- Torque wrench
- Flats From Wrench Resistance
- Turns From Finger Tight

For Flare and NPSM Fittings, recommends the flats from wrench resistence method be used whenever possible.

The differences in material, plating, and surface finish impacts the coefficient of friction when installing or connecting fittings. To minimize these variances, We recommends that fitting connections are lubricated when installed. Connections that are lubricated provide a more accurate installation torque, which results in fewer leaks.

USING A TORQUE WRENCH

The torque values given in the tables on the following pages are for reference purposes only based on industry standard practice and for low carbon steel mating with steel/iron components. Actual torque values may need to be adjusted due to variances described above.

SAE recommends always making a wet (lubricated) installation or connection to reduce friction on moving parts, O-rings, and variances in material and plating. The torque values in these tables are based off SAE values using a .17 coefficient of friction as per SAE J2593. Many hydraulic leaks are a result of over-torque, which causes excessive deformation of material or exceeds the yield strength of the material, which may reduce the load or clamping force between seal contacts.

If more than one value or range is given, use the lower value first and increase only if required. Over-torquing can damage a fitting or mating component.

SAE O-Ring Boss Port Specifications

O-ring Boss ports (ORB) provide a seal by trapping the fitting's O-ring inside a port cavity. When a fitting is installed into the port, the O-ring is trapped between the fitting body hex or washer and port cavity.

Straight fittings include a hex, and sometimes an additional cylindrical shoulder below the hex and above the threads, to trap the O-ring in the port cavity.

Elbow and Tee fittings require a backup washer and a locknut above the O-ring on the threaded stud to permit a 360° orientation of the fitting around the port.



Straight SAE ORB



Adustable SAE ORB

The following table lists the specifications for SAE O-Ring Boss Ports.

SAE O-Ring Boss Specifications								
Dash Size	Tube Size	Thread	SAE-ORB to JIC and Pipe Fittings*			SAE-ORB to ORFS Fittings**		
			Torque	Working Pressure		Torque	Working Pressure	
			Adjustable & Non- Adjustable	Adjustable	Non-Adjustable	Adjustable & Non- Adjustable	Adjustable	Non- Adjustable
			(ft-lbs) +25% -0%	*(psi)*	*(psi)*	*(ft-lbs) +25% -0%*	*(psi)*	*(psi)*
02	*1/8*	*5/16-24*	*6*	*4500*	*4500*	-	-	-
03	*3/16*	*3/8-24*	*7*	*4500*	*4500*	*7*	*5800*	*9100*
04	*1/4*	*7/16-20*	*13*	*4500*	*4500*	*15*	*5800*	*9100*
05	*5/16*	*1/2-20*	*18*	*4500*	*4500*	*18*	*5800*	*9100*
06	*3/8*	*9/16-18*	*22*	*3600*	*4500*	*26*	*5800*	*9100*
08	*1/2*	*3/4-16*	*37*	*3600*	*4500*	*52*	*5800*	*9100*
10	*5/8*	*7/8-14*	*44*	*2900*	*3600*	*74*	*5800*	*9100*
12	*3/4*	*1-1/16-12*	*70*	*2900*	*3600*	*125*	*5800*	*5800*
14	*7/8*	*1-3/16-12*	*92*	*2300*	*2900*	*158*	*5800*	*5800*
16	*1*	*1-5/16-12*	*111*	*2300*	*2900*	*199*	*4500*	*5800*
20	*1 1/4*	*1-5/8-12*	*147*	*1800*	*2300*	*210*	*3600*	*3600*
24	*1 1/2*	*1-7/8-12*	*155*	*1800*	*2300*	*273*	*2900*	*3600*
32	*2*	*2-1/2-12*	*221*	*1450*	*1800*	-	-	-
* = Light duty studs included on JIC, NPTF and NPSM fittings per SAE J1926/3 & J514 ** = Heavy duty studs included on ORFS fittings per SAE J1926/2 & J1453								
Note: Torque values are for wet torque and are allowed up to 25% the listed value according to SAE J2593.								

JIC Adapter Specifications

Male flared fittings include a conical nose with external threads for clamping.

A flared fitting or tube assembly is tightened against the cone with a swivel nut. By forcing the flare against the cone during the torquing process, the nose cone is slightly deformed and meshes to create a metal to metal seal between the flare and the cone.



The following table lists the specifications for JIC adapters.

JIC Specifications							
Dash Size	Tube Size	Thread	Working Pressure		Torque		
			Male	Female Swivel Nut	JIC Rigid	JIC Swivel	Bulkhead Locknut
			(psi)	(psi)	(FFWR)	(FFWR)	(ft-lbs) +25% -0%
02	1/8	5/16-24	5000	5000	1/4 - 1/2	2	4
03	3/16	3/8-24	5000	5000	1/4 - 1/2	2	6
04	1/4	7/16-20	5000	4500	1/4 - 1/2	2	10
05	5/16	1/2-20	5000	4000	1/4 - 1/2	2	13
06	3/8	9/16-18	5000	4000	1/4 - 1/2	2	16
08	1/2	3/4-16	4500	4000	1/4 - 1/2	2	27
10	5/8	7/8-14	3500	3000	1/4 - 1/2	1 1/2	32
12	3/4	1-1/16-12	3500	3000	1/4 - 1/2	1 1/2	52
14	7/8	1-3/16-12	3000	2500	1/4 - 1/2	1 1/2	66
16	1	1-5/16-12	3000	2500	1/4 - 1/2	1 1/2	85
20	1 1/4	1-5/8-12	2500	2000	1/4 - 1/2	1	111
24	1 1/2	1-7/8-12	2000	1500	1/4 - 1/2	1	114
32	2	2-1/2-12	1500	1125	1/4 - 1/2	1	162
Values are per SAE J514							

It has been my observation that most people get ahead during the time that others waste. -*Henry Ford*

Pipe & Pipe Swivel Adapter Specifications

NPSM fittings include an inverted 60° cone inside an internally threaded swivel union nut. Male NPTF fittings that have a 30° internal chamfer that make a 60° inverted cone, will mate with NPSM swivel unions.

NOTE: THE MATING MALE THREADS MUST INCLUDE AN INSIDE CHAMFER ON THE END OF THE FITTING THAT MATES WITH THE INVERTED CONE. THREADS ARE FOR CLAMPING FORCE ONLY AND THE SEALING OCCURS ON A SMALL RADIAL SECTION BETWEEN THE MALE FITTING INTERNAL CHAMFER AND THE SWIVEL UNION INVERTED CONE.



Fi F & NPSM Union



Fi & NPTF Assembly

N NPT and NPTF pipe threads seal by wedging the tapered threads through deformation into each other. Both t of these threads require thread sealants to complete a seal.

The following table lists the specifications for NPT, NPTF, and NPSM Pipe adapters.

NPT, NPTF, and NPSM Pipe Specifications						
Dash Size	Thread Size	Major OD* (inch)	Working Pressure		Torque	
			NPT, NPTF Male and Female	NPSM Female Swivel Nut	NPT, NPTF	NPSM Swivel Union
			(psi)	*(psi)*	*(TFFT)*	*(FFWR)*
02	*1/8-27*	*.405*	*5000*	*5000*	*2-3*	*2*
04	*1/4-18*	*.540*	*4000*	*5000*	*2-3*	*2*
06	*3/8-18*	*.675*	*3000*	*4000*	*2-3*	*2*
08	*1/2-14*	*.84*	*3000*	*3500*	*2-3*	*2*
12	*3/4-14*	*1.050*	*2500*	*2250*	*2-3*	*2*
16	*1-11 1/2*	*1.315*	*2000*	*2000*	*1 1/2 - 2 1/2*	*1 1/2*
20	*1 1/4-11 1/2*	*1.660*	*1150*	*1625*	*1 1/2 - 2 1/2*	*1 1/2*
24	*1 1/2-11 1/2*	*1.900*	*1000*	*1250*	*1 1/2 - 2 1/2*	*1 1/2*
32	*2-11 1/2*	*2.375*	*1000*	*1125*	*1 1/2 - 2 1/2*	*1 1/2*
Values are per SAE J514 & J2593						

Ta , NPTF, and NPSM Pipe Specifications

Folks who never do any more than they are paid for, never get paid for any more than they do.

-Elebert Hubbard

O-ring Face Seal Adapter Specifications

O-ring face seal fittings include a precision groove in the face of the male fitting. Sealing occurs when an O-ring is trapped in the groove by a smooth flat flange that is clamped against the face with a nut or nut and sleeve. The flat flange may be formed or brazed onto the end of a tube, or is machined on a fitting.

There are two SAE groove types:
- Type A: The original style A O-ring has no retaining ledge.
- Type B: The Type B groove has a retaining ledge (half dovetail) that improves O-ring retention. The Type B style is more commonly found and is a design improvement over the Type A.



e 9 : ORFS Fitting Assembly



: 10: Detail View of Cross Section of Groove Type A



11 : View of Groove Type B

The following table lists the specifications for O-ring Face Seal adapters.

ORFS Specifications								
Dash Size	Tube Size	Thread Size	Working Pressure		Torque			
			Male	Female Swivel Nut	Male & Female	Bulkhead Locknut	Tube Nuts	Swivel Nuts
			(psi)	*(psi)*	*(ft-lbs) +25% -0%*	*(ft-lbs) +25% -0%*	*FWR*	*FWR*
04	*1/4*	*9/16-18*	*6000*	*6000*	*18*	*16*	*1/4-1/2*	*1/2-3/4*
06	*3/8*	*11/16-16*	*6000*	*6000*	*29*	*22*	*1/4-1/2*	*1/2-3/4*
08	*1/2*	*13/16-16*	*6000*	*6000*	*41*	*29*	*1/4-1/2*	*1/2-3/4*
10	*5/8*	*1-14*	*6000*	*6000*	*44*	*44*	*1/4-1/2*	*1/2-3/4*
12	*3/4*	*1-3/16-12*	*6000*	*6000*	*66*	*66*	*1/4-1/2*	*1/3-1/2*
16	*1*	*1-7/16-12*	*6000*	*5000*	*92*	*92*	*1/4-1/2*	*1/3-1/2*
20	*1 1/4*	*1-11/16-12*	*4000*	*4000*	*125*	*111*	*1/4-1/2*	*1/3-1/2*
24	*1 1/2*	*2-12*	*4000*	*3000*	*147*	*125*	*1/4-1/2*	*1/3-1/2*
Note: Values are per SAE J2593 & J1453								
Torque values are for wet installation of steel components. Reduce torque values for softer material components.								

.e 4 : ORFS Specifications

BSPT, BSPP and Metric Adapter Specifications

BSPT and Metric tapered threads install and work in the same manner as NPT and NPTF.

Male BSPP fittings include an inverted 60° cone inside an internally threaded swivel union nut. Male BSPP fittings that have a 30° internal chamfer that make a 60° inverted cone, will mate with Female BSPP swivel unions.

NOTE: THE MATING MALE THREADS MUST INCLUDE AN INSIDE CHAMFER ON THE END OF THE FITTING THAT MATES WITH THE INVERTED CONE. THREADS ARE FOR CLAMPING FORCE ONLY AND THE SEALING OCCURS ON A SMALL RADIAL SECTION BETWEEN THE MALE FITTING INTERNAL CHAMFER AND THE SWIVEL UNION INVERTED CONE.

DIN swivel unions have a 24° inverted cone and may be installed into DIN bite-ring compression fittings. To provide enhanced performance, an O-ring is sometimes included in the cone of some DIN swivel unions.

British Standard Pipe Parallel (BSPP) and Metric Parallel threaded ports do not include a port cavity like the O-ring Boss or ISO 6149 port. Instead, an O-ring sits on top of the spot face or external surface and is surrounded by a metal retaining ring or other retaining component to trap the O-ring between the fitting hex, body, and spot face.

Elbow and Tee fittings have a locknut, backup washer, O-ring and retaining washer to permit 360° orientation around the axis of the port.

The following table lists the specifications for **BSPP & BSPT Adapters**

BSPP & BSPT Specifications				
Dash Size	BSPT & BSPP		Torque	
	THREAD SIZE	MAJOR OD* (inch)	BSPP Swivel Union	BSPT
02	1/8-28	0.383	2	2-3
04	1/4-19	0.518	2	2-3
06	3/8-19	0.656	2	2-3
08	1/2-14	0.825	2	2-3
10	5/8-14	0.929	2	2-3
12	3/4-14	1.041	2	2-3
16	1-11	1.309	1 1/2	1 1/2 - 2 1/2
20	1 1/4-11	1.650	1 1/2	1 1/2 - 2 1/2
24	1 1/2-11	1.882	1 1/2	1 1/2 - 2 1/2
32	2-11	2.347	1 1/2	1 1/2 - 2 1/2

The following table lists the specifications for **Metric Adapters**

Metric DIN 3852-1 Threads	
Dash Size	THREAD SIZE (mm)
08	8 x 1.0
10	10 x 1.0
12	12 x 1.5
14	14 x 1.5
16	16 x 1.5
18	18 x 1.5
20	20 x 1.5
22	22 x 1.5
24	24 x 1.5
26	26 x 1.5
27	27 x 2.0
30	30 x 2.0
33	33 x 2.0
39	39 x 2.0
42	42 x 2.0
48	48 x 2.0
60	60 X 2.0
Values are from DIN 3852-1	

PROFILE SIZE CHART

MALE JIC/ MALE O-RING BOSS



O-RING FACE SEAL



MALE PIPE





AG INTERCHANGE - NV SERIES



ISO 7241 - 1 - ISO A - ANV SERIES



ISO 16028 - FF SERIES



ISO 7241 - 1 ISO B - HNV SERIES

FEMALE PIPE SWIVELS

STEEL PIPE SWIVEL ADAPTERS

MALE PIPE SWIVEL ADAPTER

SAE 140130

Part #	Male Pipe 1	Female NPSM 2	
1404-2-2	1/8	1/8	----
1404-4-2	1/4	1/8	----
1404-4-4	1/4	1/4	----
1404-6-6	3/8	3/8	----
1404-6-8	3/8	1/2	----
1404-8-4	1/2	1/4	----
1404-8-6	1/2	3/8	----
1404-8-8	1/2	1/2	----
1404-12-8	3/4	1/2	----
1404-12-12	3/4	3/4	----
1404-12-16	3/4	1	----
1404-16-12	1	3/4	----
1404-16-16	1	1	----
1404-20-16	1-1/4	1	----
1404-20-20	1-1/4	1-1/4	----
1404-24-24	1-1/2	1-1/2	----
1404-32-32	2	2	----

1404 2045R 1210 9205R 0107

FEMALE PIPE SWIVEL ADAPTER

SAE 140131

Part #	Female Pipe 1	Female NPSM 2	
1405-2-2	1/8	1/8	----
1405-4-4	1/4	1/4	----
1405-6-4	3/8	1/4	----
1405-6-6	3/8	3/8	----
1405-6-8	3/8	1/2	----
1405-8-4	1/2	1/4	----
1405-8-8	1/2	1/2	----
1405-12-12	3/4	3/4	----
1405-16-12	1	3/4	----
1405-16-16	1	1	----
1405-20-20	1-1/4	1-1/4	----
1405-24-24	1-1/2	1-1/2	----
1405-32-32	2	2	----

1405 2046R 1212 9255 C207

MALE PIPE ELBOW SWIVEL ADAPTER

SAE 140230

Part #	Male Pipe 1	Female NPSM 2	
1501-2-2	1/8	1/8	----
1501-4-2	1/4	1/8	----
1501-4-4	1/4	1/4	----
1501-6-4	3/8	1/4	----
1501-6-6	3/8	3/8	----
1501-8-6	1/2	3/8	----
1501-8-8	1/2	1/2	----
1501-12-8	3/4	1/2	----
1501-12-12	3/4	3/4	----
1501-16-12	1	3/4	----
1501-16-16	1	1	----
1501-20-20	1-1/4	1-1/4	----
1501-32-32	2	2	----

1501 2047R 1218 9405 2107

FEMALE UNION ELBOW SWIVEL ADAPTER

SAE 140231

Part #	Female Pipe 1	Female NPSM 2	
1502-2-2	1/8	1/8	----
1502-4-4	1/4	1/4	----
1502-6-4	3/8	1/4	----
1502-6-6	3/8	3/8	----
1502-6-8	3/8	1/2	----
1502-8-6	1/2	3/8	----
1502-8-8	1/2	1/2	----
1502-12-12	3/4	3/4	----
1502-16-16	1	1	----
1502-20-20	1-1/4	1-1/4	----
1502-24-24	1-1/2	1-1/2	----

1502 2207 1216 94SSR

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer.
For more information, visit www.P65Warnings.ca.gov

MALE 45° PIPE ELBOW SWIVEL ADAPTER

SAE 140330



Part #	Male Pipe 1	Female NPSM 2	
1503-2-2	1/8	1/8	----
1503-4-4	1/4	1/4	----
1503-6-4	3/8	1/4	----
1503-6-6	3/8	3/8	----
1503-8-6	1/2	3/8	----
1503-8-8	1/2	1/2	----
1503-12-8	3/4	1/2	----
1503-12-12	3/4	3/4	----
1503-16-12	1	3/4	----
1503-16-16	1	1	----

1503 2049R 3107 1214 9355R

FEMALE 45° UNION ELBOW SWIVEL ADAPTER

SAE 140331



Part #	Female Pipe 1	Female NPSM 2	
1504-2-2	1/8	1/8	----
1504-4-4	1/4	1/4	----
1504-6-6	3/8	3/8	----
1504-8-8	1/2	1/2	----
1504-12-12	3/4	3/4	----
1504-16-16	1	1	----

1504 2050R 1249 9385R

MALE SWIVEL BRANCH TEE

Part #	Female NPSM 1 & 2	Male Pipe 3	
1601-2-2	1/8	1/8	----
1601-4-4	1/4	1/4	----
1601-6-6	3/8	3/8	----
1601-8-8	1/2	1/2	----
1601-12-12	3/4	3/4	----
1601-16-16	1	1	----

1601 2254R 1258 9406R

FEMALE SWIVEL TEE

Part #	Female NPSM 1 & 2	Female Pipe 3	
1602-4-4	1/4	1/4	----
1602-6-6	3/8	3/8	----
1602-8-8	1/2	1/2	----
1602-12-12	3/4	3/4	----
1602-16-16	1	1	----

1602 2253R 1259 9456R

FEMALE SWIVEL UNION TEE

Part #	Female NPSM 1,2 & 3	
1603-4-4	1/4	----
1603-6-6	3/8	----
1603-8-8	1/2	----
1603-12-12	3/4	----
1603-16-16	1	----

1603 2255 1223 9705R

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

STRAIGHTS STEEL JIC FLARE 37°

LONG JIC TUBE NUT

SAE 070111

Part #	Tube O.D	JIC Thread Size	
0304-4	1/4	7/16-20	----
0304-6	3/8	9/16-18	----
0304-8	1/2	3/4-16	----
0304-10	5/8	7/8-14	----
0304-12	3/4	1-1/16-12	----
0304-16	1	1-5/16-12	----

304 221000 0304 C5115

JIC CAP

SAE 070112
MS 51532

Part #	Tube O.D.	JIC Thread Size	
0304-C-2	1/8	5/16-24	----
0304-C-3	3/16	3/8-24	----
0304-C-4	1/4	7/16-20	----
0304-C-5	5/16	1/2-20	----
0304-C-6	3/8	9/16-18	----
0304-C-8	1/2	3/4-16	----
0304-C-10	5/8	7/8-14	----
0304-C-12	3/4	1-1/16-12	----
0304-C-14	7/8	1-3/16-12	----
0304-C-16	1	1-5/16-12	----
0304-C-20	1-1/4	1-5/8-12	----
0304-C-24	1-1/2	1-7/8-12	----
0304-C-32	2	2-1/2-12	----

820 304 210292 FNTX 1329 C5129

JIC TUBE NUT (SLEEVE REQUIRED)

SAE 070110
MS 51531

Part #	Tube O.D	JIC Thread Size	
0318-2	1/8	5/16-24	----
0318-3	3/16	3/8-24	----
0318-4	1/4	7/16-20	----
0318-5	5/16	1/2-20	----
0318-6	3/8	9/16-18	----
0318-8	1/2	3/4-16	----
0318-10	5/8	7/8-14	----
0318-12	3/4	1-1/16-12	----
0318-14	7/8	1-3/16-12	----
0318-16	1	1-5/16-12	----
0318-20	1-1/4	1-5/8-12	----
0318-24	1-1/2	1-7/8-12	----
0318-32	2	2-1/2-12	----

318 1290 BTX 1311 C5105

JIC TUBE SLEEVE

SAE 070115
MS 51533

Part #	Tube O.D	
0319-2	1/8	----
0319-3	3/16	----
0319-4	1/4	----
0319-5	5/16	----
0319-6	3/8	----
0319-8	1/2	----
0319-10	5/8	----
0319-12	3/4	----
0319-14	7/8	----
0319-16	1	----
0319-20	1-1/4	----
0319-24	1-1/2	----
0319-32	2	----

319 900605 TX 1253 C5165

JIC TUBE UNION

SAE 070101
MS 51501

1 2

Part #	JIC Thread Size 1	JIC Thread Size 2	
2403-2-2	5/16-24	5/16-24	----
2403-3-3	3/8-24	3/8-24	----
2403-4-4	7/16-20	7/16-20	----
2403-5-5	1/2-20	1/2-20	----
2403-6-6	9/16-18	9/16-18	----
2403-6-4	9/16-18	7/16-20	----
2403-8-8	3/4-16	3/4-16	----
2403-8-6	3/4-16	9/16-18	----
2403-10-10	7/8-14	7/8-14	----
2403-10-8	7/8-14	3/4-16	----
2403-12-12	1-1/16-12	1-1/16-12	----
2403-12-8	1-1/16-12	3/4-16	----
2403-12-10	1-1/16-12	7/8-14	----
2403-14-14	1-3/16-12	1-3/16-12	----
2403-16-16	1-5/16-12	1-5/16-12	----
2403-16-12	1-5/16-12	1-1/16-12	----
2403-20-20	1-5/8-12	1-5/8-12	----
2403-24	1-7/8-12	1-7/8-12	----
2403-32	2-1/2-12	2-1/2-12	----

2403 2027 HTX 1204 C5305

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

JIC MALE CONNECTOR

SAE 070102
MS 51500

Part #	JIC Thread Size 1	MalePipe Thread 2	
2404-2-2	5/16-24	1/8	----
2404-4-2	7/16-20	1/8	----
2404-4-4	7/16-20	1/4	----
2404-4-6	7/16-20	3/8	----
2404-4-8	7/16-20	1/2	----
2404-6-2	9/16-18	1/8	----
2404-6-4	9/16-18	1/4	----
2404-6-6	9/16-18	3/8	----
2404-6-8	9/16-18	1/2	----
2404-8-4	3/4-16	1/4	----
2404-8-6	3/4-16	3/8	----
2404-8-8	3/4-16	1/2	----
2404-8-12	3/4-16	3/4	----
2404-8-16	3/4-16	1	----
2404-10-8	7/8-14	1/2	----
2404-10-12	7/8-14	3/4	----
2404-12-6	1-1/16-12	3/8	----
2404-12-8	1-1/16-12	1/2	----
2404-12-12	1-1/16-12	3/4	----
2404-12-16	1-1/16-12	1	----
2404-16-12	1-5/16-12	3/4	----
2404-16-16	1-5/16-12	1	----
2404-20-16	1-5/8-12	1	----
2404-20-20	1-5/8-12	1-1/4	----
2404-24-16	1-7/8-12	1	----
2404-24-20	1-7/8-12	1-1/4	----
2404-24-24	1-7/8-12	1-1/2	----
2404-32-24	2-1/2-12	1-1/2	----
2404-32-32	2-1/2-12	2	----

2404 2021R FTX 1202R C5205 816

My dream is of a place and a time where America will once again be seen as the last best hope of earth.

- Abraham Lincoln

JIC FEMALE CONNECTOR

SAE 070103
MS 51503

Part #	JIC Thread Size 1	Female Pipe Size 2	
2405-2-2	5/16-24	1/8	----
2405-3-2	3/8-24	1/8	----
2405-4-2	7/16-20	1/8	----
2405-4-4	7/16-20	1/4	----
2405-6-4	9/16-18	1/4	----
2405-6-6	9/16-18	3/8	----
2405-8-4	3/4-16	1/4	----
2405-8-6	3/4-16	3/8	----
2405-8-8	3/4-16	1/2	----
2405-10-6	7/8-14	3/8	----
2405-10-8	7/8-14	1/2	----
2405-12-8	1-1/16-12	1/2	----
2405-12-12	1-1/16-12	3/4	----
2405-16-12	1-5/16-12	3/4	----
2405-16-16	1-5/16-12	1	----
2405-20-20	1-5/8-12	1-1/4	----
2405-24-24	1-7/8-12	1-1/2	----
2405-32-32	2-1/2-12	2	----

2405 2022R GTX 1230R C5255

JIC REDUCER/ EXPANDER

SAE 070123

Part #	Female JIC Thread Size 1	Male JIC Thread Size 2	
2406-6-4	9/16-18	7/16-20	----
2406-6-8	9/16-18	3/4-16	----
2406-8-4	3/4-16	7/16-20	----
2406-8-6	3/4-16	9/16-18	----
2406-8-12	3/4-16	1-1/16-12	----
2406-10-4	7/8-14	7/16-20	----
2406-10-6	7/8-14	9/16-18	----
2406-10-8	7/8-14	3/4-16	----
2406-12-4	1-1/16-12	7/16-20	----
2406-12-6	1-1/16-12	9/16-18	----
2406-12-8	1-1/16-12	3/4-16	----
2406-12-10	1-1/16-12	7/8-14	----
2406-16-4	1-5/16-12	7/16-20	----
2406-16-12	1-5/16-12	1-1/16-12	----
2406-16-20	1-5/16-12	1-5/8-12	----
2406-20-12	1-5/8-12	1-1/16-12	----
2406-20-16	1-5/8-12	1-5/16-12	----
2406-24-16	1-7/8-12	1-5/16-12	----
2406-32-24	2-1/2-12	1-7/8-12	----

2406 C5015 2215 TRTX 1246

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

STRAIGHTS STEEL JIC FLARE 37°

PLUG

SAE 070109
MS 51518

Part #	Tube O.D.	JIC Thread Size	
2408-2	1/8	5/16-24	----
2408-3	3/16	3/8-24	----
2408-4	1/4	7/16-20	----
2408-5	5/16	1/2-20	----
2408-6	3/8	9/16-18	----
2408-8	1/2	3/4-16	----
2408-10	5/8	7/8-14	----
2408-12	3/4	1-1/16-12	----
2408-14	7/8	1-3/16-12	----
2408-16	1	1-5/16-12	----
2408-20	1-1/4	1-5/8-12	----
2408-24	1-1/2	1-7/8-12	----
2408-32	2	2-1/2-12	----

2408 430549 PNTX 1254 C5229

JIC UNION ELBOW

SAE 070201
MS 51505

Part #	JIC Thread Size 1	JIC Thread Size 2	
2500-2-2	5/16-24	5/16-24	----
2500-4-4	7/16-20	7/16-20	----
2500-5-5	1/2-20	1/2-20	----
2500-6-6	9/16-18	9/16-18	----
2500-6-4	9/16-18	7/16-20	----
2500-8-8	3/4-16	3/4-16	----
2500-8-6	3/4-16	9/16-18	----
2500-10-10	7/8-14	7/8-14	----
2500-12-12	1-1/16-12	1-1/16-12	----
2500-16-16	1-5/16-12	1-5/16-12	----
2500-20-20	1-5/8-12	1-5/8-12	----
2500-24-24	1-7/8-12	1-7/8-12	----
2500-32-32	2-1/2-12	2-1/2-12	----

2500 2039 1234 C5505 821

STEEL 37° JIC FLARE SHAPES

JIC MALE ELBOW

SAE 070202
MS 51504

Part #	JIC Thread Size 1	Male Pipe Size 2	
2501-4-2	7/16-20	1/8	----
2501-4-4	7/16-20	1/4	----
2501-4-8	7/16-20	1/2	----
2501-6-2	9/16-18	1/8	----
2501-6-4	9/16-18	1/4	----
2501-6-6	9/16-18	3/8	----
2501-6-8	9/16-18	1/2	----
2501-8-4	3/4-16	1/4	----
2501-8-6	3/4-16	3/8	----
2501-8-8	3/4-16	1/2	----
2501-8-12	3/4-16	3/4	----
2501-10-6	7/8-14	3/8	----
2501-10-8	7/8-14	1/2	----
2501-12-8	1-1/16-12	1/2	----
2501-12-12	1-1/16-12	3/4	----
2501-12-16	1-1/16-12	1	----
2501-16-12	1-5/16-12	3/4	----
2501-16-16	1-5/16-12	1	----
2501-16-20	1-5/16-12	1-1/4	----
2501-20-20	1-5/8-12	1-1/4	----
2501-24-24	1-7/8-12	1-1/2	----
2501-32-32	2-1/2-12	2	----

1208R C5405 2501 2024R CTX 822

JIC FEMALE ELBOW

SAE 070203
MS 51506



Part #	JIC Thread Size 1	Female Pipe Size 2	
2502-4-2	7/16-20	1/8	----
2502-4-4	7/16-20	1/4	----
2502-6-4	9/16-18	1/4	----
2502-6-6	9/16-18	3/8	----
2502-8-6	3/4-16	3/8	----
2502-8-8	3/4-16	1/2	----
2502-12-12	1-1/16-12	3/4	----
2502-16-16	1-5/16-12	1	----
2502-20-20	1-5/8-12	1-1/4	----

2502 2025R DTX 1240R C5455

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer.
For more information, visit www.P65Warnings.ca.gov

JIC MALE 45° ELBOW

SAE 070302
MS 51508

Part #	JIC Thread Size 1	Male Pipe Size 2	
2503-2-2	5/16-24	1/8	----
2503-4-4	7/16-20	1/4	----
2503-6-4	9/16-18	1/4	----
2503-6-6	9/16-18	3/8	----
2503-6-8	9/16-18	1/2	----
2503-8-6	3/4-16	3/8	----
2503-8-8	3/4-16	1/2	----
2503-10-8	7/8-14	1/2	----
2503-12-12	1-1/16-12	3/4	----
2503-12-16	1-1/16-12	1	----
2503-16-16	1-5/16-12	1	----
2503-16-20	1-5/16-12	1-1/4	----
2503-20-16	1-5/8-12	1	----
2503-20-20	1-5/8-12	1-1/4	----

2503 2023R VTX 1206R C5355 823

JIC MALE BRANCH TEE

Part #	JIC Thread Size 1&2	Pipe Thread Size 3	
2601-4-4	7/16-20	1/4	----
2601-6-6	9/16-18	3/8	----
2601-8-8	3/4-16	1/2	----
2601-12-12	1-1/16-12	3/4	----

2601 2030R STX 1221R C5605

JIC FEMALE BRANCH TEE

SAE 070427
MS 51513

Part #	JIC Thread Size 1 & 2	Female Pipe Size 3	
2602-4-4	7/16-20	1/4	----
2602-6-6	9/16-18	3/8	----
2602-8-8	3/4-16	1/2	----

2602 2031R OTX 1228R C6566

JIC UNION TEE

SAE 070401
MS 51510

Part #	JIC Thread Size 1 & 2	JIC Thread Size 3	
2603-2-2	5/16-24	5/16-24	----
2603-3-3	3/8-24	3/8-24	----
2603-4-4	7/16-20	7/16-20	----
2603-6-6	9/16-18	9/16-18	----
2603-8-8	3/4-16	3/4-16	----
2603-10-10	7/8-14	7/8-14	----
2603-12-12	1-1/16-12	1-1/16-12	----
2603-16-16	1-5/16-12	1-5/16-12	----

2603 2033 JTX 1220 C5705

STEEL BULKHEAD FITTINGS

LOCK NUT

SAE 070118
MS 51860

*** Lock Nut no longer included on fittings**

Part #	Thread Size	
0306-2	5/16-24	----
0306-4	7/16-20	----
0306-5	1/2-20	----
0306-6	9/16-18	----
0306-8	3/4-16	----
0306-10	7/8-14	----
0306-12	1-1/16-12	----
0306-14	1-3/16-12	----
0306-16	1-5/16-12	----
0306-20	1-5/8-12	----

1306 894 210212 WLN 1332 C5624

JIC BULKHEAD UNION

SAE 070601
MS 51520

Part #	JIC Thread Size 1	JIC Thread Size 2	
2700-2-2	5/16-24	5/16-24	----
2700-4-4	7/16-20	7/16-20	----
2700-5-5	1/2-20	1/2-20	----
2700-6-6	9/16-18	9/16-18	----
2700-8	3/4-16	3/4-16	----
2700-10	7/8-14	7/8-14	----
2700-12	1-1/16-12	1-1/16-12	----
2700-14	1-3/16-12	1-3/16-12	----
2700-16	1-5/16-12	1-5/16-12	----

2700 2041R WTX 1260 C5325

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

STEEL BULKHEAD FITTINGS

HYDRAULIC ADAPTERS

JIC BULKHEAD UNION ELBOW

SAE 070701
MS 51507



Part #	JIC Thread Size 1	JIC Bulkhead Thread 2	
2701-4	7/16-20	7/16-20	----
2701-5	1/2-20	1/2-20	----
2701-6	9/16-18	9/16-18	----
2701-8	3/4-16	3/4-16	----
2701-10	7/8-14	7/8-14	----
2701-12	1-1/16-12	1-1/16-12	----
2701-16	1-5/16-12	1-5/16-12	----
2701-20	1-5/8-12	1-5/8-12	----

2701 2043R WETX 1262 C5525

JIC BULKHEAD UNION 45° ELBOW

SAE 070801
MS 51509

Part #	JIC Thread Size 1	JIC Thread Size 2	
2702-4	7/16-20	7/16-20	----
2702-6	9/16-18	9/16-18	----
2702-8	3/4-16	3/4-16	----
2702-10	7/8-14	7/8-14	----
2702-12	1-1/16-12	1-1/16-12	----
2702-16	1-5/16-12	1-5/16-12	----

2702 2042 WNTX 1261 C5375

JIC BULKHEAD BRANCH TEE

SAE 070959
MS 51515

Part #	JIC Thread Size 1&2	JIC Thread Size 3	
2703-4	7/16-20	7/16-20	----
2703-6	9/16-18	9/16-18	----
2703-8	3/4-16	3/4-16	----
2703-10	7/8-14	7/8-14	----
2703-12	1-1/16-12	1-1/16-12	----
2703-16	1-5/16-12	1-5/16-12	----

2703 203002 WJT 1283 C5725

JIC BULKHEAD RUN TEE

SAE 070958
MS 51516



Part #	JIC Thread Size 1&3	JIC Thread Size 2	
2704-4	7/16-20	7/16-20	----
2704-6	9/16-18	9/16-18	----
2704-8	3/4-16	3/4-16	----
2704-10	7/8-14	7/8-14	----
2704-12	1-1/16-12	1-1/16-12	----
2704-16	1-5/16-12	1-5/16-12	----

2704 203008 WJJT 1284 C5726

JIC TO FEMALE PIPE BULKHEAD

Part #	JIC Thread	Female Pipe Size 2	
2705-4-4	7/16-20	1/4	----
2705-6-6	9/16-18	3/8	----
2705-8-8	3/4-16	1/2	----
2705-12-12	1-1/16-12	3/4	----
2705-16-16	1-5/16-12	1	----
2705-20-20	1-5/8-12	1-1/4	28.45

2705 2239 WGTX C5275

JIC TO MALE PIPE BULKHEAD

Part #	JIC Thread Size 1	Pipe Thread Size 2	
2706-4-4	7/16-20	1/4	----
2706-6-6	9/16-18	3/8	----
2706-8-8	3/4-16	1/2	----
2706-12-12	1-1/16-12	3/4	----
2706-16-16	1-5/16-12	1	----

2706 2240

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

** Lock Nuts sold separately - pg. 403*

PIPE COUPLING

910

SAE 140138

Part #	Female Pipe 1	Female Pipe 2	
5000-2	1/8	1/8	----
5000-4-2	1/4	1/8	----
5000-4	1/4	1/4	----
5000-6-4	3/8	1/4	----
5000-6-6	3/8	3/8	----
5000-8-4	1/2	1/4	----
5000-8-6	1/2	3/8	----
5000-8	1/2	1/2	----
5000-12-12	3/4	3/4	----
5000-16-12	1	3/4	----
5000-16	1	1	----
5000-20-20	1-1/4	1-1/4	----
5000-24	1-1/2	1-1/2	----
5000-32	2	2	----

5000 2096 GG 1273 C3309

HEX PIPE NIPPLES

SAE 140137

Part #	Male Pipe 1	Male Pipe 2	
5404-2	1/8	1/8	----
5404-4-2	1/4	1/8	----
5404-4	1/4	1/4	----
5404-6-2	3/8	1/8	----
5404-6-4	3/8	1/4	----
5404-6	3/8	3/8	----
5404-8-4	1/2	1/4	----
5404-8-6	1/2	3/8	----
5404-8	1/2	1/2	----
5404-12-6	3/4	3/8	----
5404-12-8	3/4	1/2	----
5404-12	3/4	3/4	----
5404-16-12	1	3/4	----
5404-16	1	1	----
5404-20-16	1-1/4	1	----
5404-20	1-1/4	1-1/4	----
5404-24-20	1-1/2	1-1/4	----
5404-24	1-1/2	1-1/2	----
5404-32-24	2	1-1/2	----
5404-32	2	2	----

5404 2083 FF 1252 C3069 911

EXPANDING PIPE ADAPTER

SAE 140139

Part #	Male Pipe 1	Female Pipe 2	
5405-2-2	1/8	1/8	----
5405-2-4	1/8	1/4	----
5405-4-2	1/4	1/8	----
5405-4-4	1/4	1/4	----
5405-6-4	3/8	1/4	----
5405-6-6	3/8	3/8	----
5405-6-8	3/8	1/2	----
5405-8-8	1/2	1/2	----
5405-8-12	1/2	3/4	----
5405-12-12	3/4	3/4	----
5405-16-16	1	1	----
5405-16-20	1	1-1/4	----
5405-20-20	1-1/4	1-1/4	----
5405-20-24	1-1/4	1-1/2	----
5405-24-24	1-1/2	1-1/2	----

920 5405 2040 FG-(R) 1274 C3209(R)

HEX REDUCER BUSHING

SAEF1
140140

Part #	Male Pipe	Female Pipe	
5406-4-2	1/4	1/8	----
5406-6-2	3/8	1/8	----
5406-6-4	3/8	1/4	----
5406-8-2	1/2	1/8	----
5406-8-4	1/2	1/4	----
5406-8-6	1/2	3/8	----
5406-12-4	3/4	1/4	----
5406-12-6	3/4	3/8	----
5406-12-8	3/4	1/2	----
5406-16-4	1	1/4	----
5406-16-6	1	3/8	----
5406-16-8	1	1/2	----
5406-16-12	1	3/4	----
5406-20-16	1-1/4	1	----
5406-24-20	1-1/2	1-1/4	----
5406-32-20	2	1-1/4	----
5406-32-24	2	1-1/2	----

5406 2081 PTR 1250 C3109 912

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

STEEL PIPE FITTINGS

HYDRAULIC ADAPTERS

HEX HEAD PLUG

SAE 130109E

Part #	Male Pipe	
5406-P-2	1/8	----
5406-P-4	1/4	----
5406-P-6	3/8	----
5406-P-8	1/2	----
5406-P-12	3/4	----
5406-P-16	1	----
5406-P-20	1-1/4	----
5406-P-24	1-1/2	----
5406-P-32	2	----

933 5406P 2082 HP 1251 C3159

HOLLOW HEX PLUG

SAE 130109

Part #	Male Pipe	
5406-HHP-2	1/8	----
5406-HHP-4	1/4	----
5406-HHP-6	3/8	----
5406-HHP-8	1/2	----
5406-HHP-12	3/4	----
5406-HHP-16	1	----
5406-HHP-20	1-1/4	----
5406-HHP-24	1-1/2	----

C3169 2222

FLUSH HOLLOW HEX PLUG W/ 7/8 TAPER

Part #	Male Pipe	
5406-FLP-2	1/8	----
5406-FLP-4	1/4	----
5406-FLP-6	3/8	----
5406-FLP-8	1/2	----
5406-FLP-12	3/4	----

SQUARE HEAD PLUG

SAE 130109A

Part #	Male Pipe	
5406-SHP-2	1/8	----
5406-SHP-4	1/4	----
5406-SHP-6	3/8	----
5406-SHP-8	1/2	----
5406-SHP-12	3/4	----
5406-SHP-16	1	----
5406-SHP-20	1-1/4	----
5406-SHP-24	1-1/2	----
5406-SHP-32	2	----

C3179

PIPE CAP

Part #	Female Pipe	
5406-C-2	1/8	----
5406-C-4	1/4	----
5406-C-6	3/8	----
5406-C-8	1/2	----
5406-C-12	3/4	----
5406-C-16	1	----

HPC

MALE ELBOW

SAE 140237

Part #	Male Pipe 1	Male Pipe 2	
5500-2	1/8	1/8	----
5500-4	1/4	1/4	----
5500-6	3/8	3/8	----
5500-8-4	1/2	1/4	----
5500-8	1/2	1/2	----
5500-12-8	3/4	1/2	----
5500-12-12	3/4	3/4	----
5500-16	1	1	----
5500-16-12	1	3/4	----
5500-20-20	1-1/4	1-1/4	----

919 5500 2085 CR 1275 C3529

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

45° MALE ELBOW

Part #	Male Pipe 1	Male Pipe 2	
5501-2-2	1/8	1/8	----
5501-4-4	1/4	1/4	----
5501-6-6	3/8	3/8	----
5501-8	1/2	1/2	----
5501-12-12	3/4	3/4	----
5501-16-16	1	1	----

5501 2247

90° STREET ELBOW

SAE 140239

Part #	Male Pipe 1	Female Pipe 2	
5502-2	1/8	1/8	----
5502-4	1/4	1/4	----
5502-6-4	3/8	1/4	----
5502-6	3/8	3/8	----
5502-8-4	1/2	1/4	----
5502-8-6	1/2	3/8	----
5502-8-8	1/2	1/2	----
5502-12	3/4	3/4	----
5502-16-16	1	1	----
5502-20	1-1/4	1-1/4	----
5502-24	1-1/2	1-1/2	----

5502 2089 CD 1234R C3409 914

45° STREET ELBOW

SAE 140339

Part #	Male Pipe 1	Female Pipe 2	
5503-2	1/8	1/8	----
5503-4	1/4	1/4	----
5503-6	3/8	3/8	----
5503-8	1/2	1/2	----
5503-12-12	3/4	3/4	----
5503-16	1	1	----

5503 CD45 1244

FEMALE ELBOW

SAE 140238

Part #	Female Pipe 1	Female Pipe 2	
5504-2	1/8	1/8	----
5504-4	1/4	1/4	----
5504-6	3/8	3/8	----
5504-8-6	1/2	3/8	----
5504-8	1/2	1/2	----
5504-12	3/4	3/4	----
5504-16	1	1	----
5504-20	1-1/4	1-1/4	----
5504-24	1-1/2	1-1/2	----

5504 2087 DD 1245 C3509 916

45° FEMALE ELBOW

SAE 140338



Part #	Female Pipe 1	Female Pipe 2	
5505-4	1/4	1/4	----
5505-6	3/8	3/8	----
5505-8	1/2	1/2	----
5505-12	3/4	3/4	----
5505-16	1	1	----
5505-20	1-1/4	1-1/4	----

5505 DD45 1241 C3559

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

STEEL PIPE FITTINGS

HYDRAULIC ADAPTERS

MALE PIPE TEE

SAE 140437



Part #	Male Pipe 1 & 2	Male Pipe 3	
5600-2-2	1/8	1/8	----
5600-4-4	1/4	1/4	----
5600-6-6	3/8	3/8	----
5600-8-8	1/2	1/2	----
5600-12	3/4	3/4	----
5600-16	1	1	----

5600 2257 RRS

FEMALE RUN PIPE TEE

SAE 1404276



Part #	Male Pipe 1 & 3	Female Pipe 2	
5603-2-2	1/8	1/8	----
5603-4-4	1/4	1/4	----
5603-6-6	3/8	3/8	----
5603-8-8	1/2	1/2	----
5603-12	3/4	3/4	----
5603-16	1	1	----

5603 2093 MMO 1277

FEMALE BRANCH PIPE TEE

SAE 140427

Part #	Male Pipe 1 & 2	Female Pipe 3	
5601-2-2	1/8	1/8	----
5601-4-4	1/4	1/4	----
5601-6-6	3/8	3/8	----
5601-12	3/4	3/4	----
5601-16	1	1	----

901 5601 2256

MALE BRANCH PIPE TEE

Part #	Female Pipe 1 & 2	Male Pipe 3	
5604-2-2	1/8	1/8	----
5604-4-4	1/4	1/4	----
5604-6-6	3/8	3/8	----
5604-8-8	1/2	1/2	----
5604-12	3/4	3/4	----
5604-16	1	1	----

904 5604 2091 MMS 1278 C3609

STREET PIPE TEE

SAE 140424

Part #	Male Pipe 1	Female Pipe 2 & 3	
5602-2-2	1/8	1/8	----
5602-4-4	1/4	1/4	----
5602-6-6	3/8	3/8	----
5602-8-8	1/2	1/2	----
5602-12	3/4	3/4	----
5602-16	1	1	----

902 5602 2092 MRO 1276 C3759

FEMALE PIPE TEE

SAE 140438

Part #	Female Pipe	
5605-2-2	1/8	----
5605-4-4	1/4	----
5605-6-6	3/8	----
5605-8	1/2	----
5605-12	3/4	----
5605-16	1	----
5605-20	1-1/4	----

917 5605 2090 1225 C3709

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

JIC TO O-RING CONNECTOR

SAE 070120
MS 51525

Part #	JIC Thread Size 1	O-Ring Thread 2	
6400-2	5/16-24	5/16-24	----
6400-4	7/16-20	7/16-20	----
6400-4-2	7/16-20	5/16-24	----
6400-4-6	7/16-20	9/16-18	----
6400-4-8	7/16-20	3/4-16	----
6400-5	1/2-20	1/2-20	----
6400-6	9/16-18	9/16-18	----
6400-6-4	9/16-18	7/16-20	----
6400-6-8	9/16-18	3/4-16	----
6400-6-10	9/16-18	7/8-14	----
6400-6-12	9/16-18	1-1/16-12	----
6400-8	3/4-16	3/4-16	----
6400-8-4	3/4-16	7/16-20	----
6400-8-6	3/4-16	9/16-18	----
6400-8-10	3/4-16	7/8-14	----
6400-8-12	3/4-16	1-1/16-12	----
6400-10	7/8-14	7/8-14	----
6400-10-8	7/8-14	3/4-16	----
6400-10-12	7/8-14	1-1/16-12	----
6400-12	1-1/16-12	1-1/16-12	----
6400-12-8	1-1/16-12	3/4-16	----
6400-12-10	1-1/16-12	7/8-14	----
6400-12-14	1-1/16-12	1-3/16-12	----
6400-12-16	1-1/16-12	1-5/16-12	----
6400-16	1-5/16-12	1-5/16-12	----
6400-16-12	1-5/16-12	1-1/16-12	----
6400-16-20	1-5/16-12	1-5/8-12	----
6400-20	1-5/8-12	1-5/8-12	----
6400-20-24	1-5/8-12	1-7/8-12	----
6400-24-32	1-7/8-12	2-1/2-12	----

6400 202702R F50X 1231 C5315

O-RING HEX NIPPLE UNION

Part #	O-Ring Thread 1	O-Ring Thread 2	
6403-O-6	9/16-18	9/16-18	----
6403-O-8	3/4-16	3/4-16	----
6403-O-12	1-1/16-12	1-1/16-12	----

O-RING TO PIPE ADAPTER

Part #	O-Ring Thread 1	Male Pipe Thread 2	
6401-4-4	7/16-20	1/4	----
6401-6-4	9/16-18	1/4	----
6401-6-6	9/16-18	3/8	----
6401-8-6	3/4-16	3/8	----
6401-8-8	3/4-16	1/2	----
6401-10-8	7/8-14	1/2	----
6401-12-8	1-1/16-12	1/2	----
6401-12-12	1-1/16-12	3/4	----
6401-16-16	1-5/16-12	1	----
6401-20-20	1-5/8-12	1-1/4	----

6401 F5X 1264R C3249

O-RING TO 37° JIC - SWIVEL ADAPTER

Part #	O-Ring Thread 1	JIC Thread Size 2	
6402-O-4-4	7/16-20	7/16-20	----
6402-O-6-6	9/16-18	9/16-18	----
6402-O-8-8	3/4-16	3/4-16	----
6402-O-10-10	7/8-14	7/8-14	----
6402-O-12-12	1-1/16-12	1-1/16-12	----

6402 2266 F65X 1213 9316

FEMALE O-RING TO MALE PIPE ADAPTER

Part #	O-Ring Thread 1	Male Pipe Thread 2	
6404-4-4	7/16-20	1/4	----
6404-6-4	9/16-18	1/4	----
6404-6-6	9/16-18	3/8	----
6404-6-8	9/16-18	1/2	----
6404-8-8	3/4-16	1/2	----
6404-10-8	7/8-14	1/2	----
6404-12-12	1-1/16-12	3/4	----

6404 2246R 1267R C3239 FHG5

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

STEEL O-RING ADAPTERS

O-RING TO FEMALE PIPE ADAPTER

Part #	O-Ring Thread 1	Female Pipe Thread 2	
6405-O-4-2	7/16-20	1/8	----
6405-O-4-4	7/16-20	1/4	----
6405-O-6-4	9/16-18	1/4	----
6405-O-6-6	9/16-18	3/8	----
6405-O-8-6	3/4-16	3/8	----
6405-O-8-8	3/4-16	1/2	----
6405-O-10-6	7/8-14	3/8	----
6405-O-10-8	7/8-14	1/2	----
6405-O-12-8	1-1/16-12	1/2	----
6405-O-12-12	1-1/16-12	3/4	----
6405-O-16-12	1-5/16-12	3/4	----
6405-O-16-16	1-5/16-12	1	----
6405-O-20-20	1-5/8-12	1-1/4	----
6405-O-24-24	1-7/8-12	1-1/2	----
6405-O-32-32	2-1/2-12	2	----

6405 2216R F50G 1268R C3269

O-RING HEX HEAD PLUG

SAE 090109A

***Not all sizes are solid**

Part #	O-Ring Thread	
6408-O-2	5/16-24	----
6408-O-4	7/16-20	----
6408-O-5	1/2-20	----
6408-O-6	9/16-18	----
6408-O-8	3/4-16	----
6408-O-10	7/8-14	----
6408-O-12	1-1/16-12	----
6408-O-14	1-3/16-12	----
6408-O-16	1-5/16-12	----
6408-O-20	1-5/8-12	----
6408-O-24	1-7/8-12	----

6408 900598 P50N 1265 7237

O-RING HOLLOW - HEX HEAD PLUG

SAE 090109B

Part #	O-Ring Thread	
6408-H-O-2	5/16-24	----
6408-H-O-4	7/16-20	----
6408-H-O-5	1/2-20	----
6408-H-O-6	9/16-18	----
6408-H-O-8	3/4-16	----
6408-H-O-10	7/8-14	----
6408-H-O-12	1-1/16-12	----
6408-H-O-14	1-3/16-12	----
6408-H-O-16	1-5/16-12	----
6408-H-O-20	1-5/8-12	----
6408-H-O-24	1-7/8-12	----
6408-H-O-32	2-1/2-12	----

6408HHP FF2138 HP50N 1256 7238 6409

O-RING PORT REDUCER/EXPANDER

Part #	O-Ring Thread 1	O-Ring Thread 2	
6410-O-8-4	3/4-16	7/16-20	----
6410-O-8-6	3/4-16	9/16-18	----
6410-O-8-8	3/4-16	3/4-16	----
6410-O-12-8	1-1/16-12	3/4-16	----

6410 FF1010 F50G5 1270 7033

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer.
For more information, visit www.P65Warnings.ca.gov

JIC SWIVEL NUT ELBOW

SAE 070221
MS 51521

Part #	JIC Thread Size 1	JIC Thread Size 2	
6500-4	7/16-20	7/16-20	----
6500-6	9/16-18	9/16-18	----
6500-8	3/4-16	3/4-16	----
6500-10	7/8-14	7/8-14	----
6500-12	1-1/16-12	1-1/16-12	----
6500-16	1-5/16-12	1-5/16-12	----
6500-24	1-7/8-12	1-7/8-12	----

6500 2071R C6X 1236 G5506

JIC SWIVEL TO MALE PIPE ELBOW

Part #	JIC Thread Size 1	Male Pipe Thread 2	
6501-4-4	7/16-20	1/4	----
6501-6-6	9/16-18	3/8	----
6501-8-8	3/4-16	1/2	----
6501-10-8	7/8-14	1/2	----
6501-12-12	1-1/16-12	3/4	----
6501-16-16	1-5/16-12	1	----

6501 2250 1247R TF5406

JIC SWIVEL 45° ELBOW

SAE 070321
MS 51522

Part #	JIC Thread	JIC Thread Size 2	
6502-4	7/16-20	7/16-20	----
6502-6	9/16-18	9/16-18	----
6502-8	3/4-16	3/4-16	----
6502-10	7/8-14	7/8-14	----
6502-12	1-1/16-12	1-1/16-12	----
6502-16	1-5/16-12	1-5/16-12	----

6502 2070R V6X 1237 C5356

JIC SWIVEL TO FEMALE - PIPE ELBOW

Part #	JIC Thread Size 1	Female Pipe Thread 2	
6503-4-4	7/16-20	1/4	----
6503-6-6	9/16-18	3/8	----
6503-8-8	3/4-16	1/2	----
6503-12-12	1-1/16-12	3/4	----

JIC SWIVEL CONNECTOR

Part #	JIC Thread	JIC Thread Size 2	
6504-4-4	7/16-20	7/16-20	----
6504-6-6	9/16-18	9/16-18	----
6504-8-8	3/4-16	3/4-16	----
6504-10-10	7/8-14	7/8-14	----
6504-12-12	1-1/16-12	1-1/16-12	----
6504-16-16	1-5/16-12	1-5/16-12	----
6504-20-20	1-5/8-12	1-5/8-12	----

6504 1205

JIC SWIVEL TO MALE - PIPE ADAPTER

Part #	JIC Thread Size 1	Male Pipe Thread 2	
6505-4-2	7/16-20	1/8	----
6505-4-4	7/16-20	1/4	----
6505-4-6	7/16-20	3/8	----
6505-6-4	9/16-18	1/4	----
6505-6-6	9/16-18	3/8	----
6505-8-6	3/4-16	3/8	----
6505-8-8	3/4-16	1/2	----
6505-12-12	1-1/16-12	3/4	----
6505-16-16	1-5/16-12	1	----
6505-24-24	1-7/8-12	1-1/2	----

6505 2018 F6X 1211 9100R

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

FEMALE SWIVELS

JIC SWIVEL TO FEMALE PIPE ADAPTER

Part #	JIC Thread Size 1	Female Pipe Thread 2	
6506-4-2	7/16-20	1/8	----
6506-4-4	7/16-20	1/4	----
6506-6-4	9/16-18	1/4	----
6506-6-6	9/16-18	3/8	----
6506-6-8	9/16-18	1/2	----
6506-8-6	3/4-16	3/8	----
6506-8-8	3/4-16	1/2	----
6506-10-6	7/8-14	3/8	----
6506-12-12	1-1/16-12	3/4	----
6506-16-16	1-5/16-12	1	----
6506-20-20	1-5/8-12	1-1/4	----

6506 2242 1215

JIC SWIVEL BRANCH TEE

SAE 070433
MS 51524



Part #	JIC Thread Size 1 & 2	JIC Female Thread 3	
6600-4-4	7/16-20	7/16-20	----
6600-6-6	9/16-18	9/16-18	----
6600-8-8	3/4-16	3/4-16	----
6600-10	7/8-14	7/8-14	----
6600-12	1-1/16-12	1-1/16-12	----
6600-16	1-5/16-12	1-5/16-12	----
6600-20	1-5/8-12	1-5/8-12	----

6600 203101R 55X 1227 C5707

NWO = Nut, Washer & O-Ring

HYDRAULIC ADAPTERS

JIC SWIVEL RUN TEE

SAE 070432
MS 51523

Part #	JIC Thread Size 1 & 3	JIC Female Thread 2	
6602-4	7/16-20	7/16 -20	----
6602-5	1/2-20	1/2-20	----
6602-6	9/16-18	9/16-18	----
6602-8	3/4-16	3/4-16	----
6602-12	1-1/16-12	1-1/16-12	----
6602-16	1-5/16-12	1-5/16-12	----
6602-24	1-7/8-12	1-7/8-12	----

6602 203102R R6X 1248 C5706

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer.
For more information, visit www.P65Warnings.ca.gov

JIC TO O-RING ELBOW CONNECTOR

SAE 070220
MS 51527

Part #	JIC Thread Size 1	O-Ring Thread Size 2	
6801-NWO-4	7/16-20	7/16-20	----
6801-NWO-4-6	7/16-20	9/16-18	----
6801-NWO-6	9/16-18	9/16-18	----
6801-NWO-6-4	9/16-18	7/16-20	----
6801-NW0-6-8	9/16-18	3/4-16	
6801-NWO-8	3/4-16	3/4-16	----
6801-NWO-8-6	3/4-16	9/16-18	----
6801-NWO-8-10	3/4-16	7/8-14	----
6801-NWO-8-12	3/4-16	1-1/16-12	----
6801-NWO-10	7/8-14	7/8-14	----
6801-NWO-10-8	7/8-14	3/4-16	----
6801-NWO-12	1-1/16-12	1-1/16-12	----
6801-NWO-12-10	1-1/16-12	7/8-14	----
6801-NWO-12-16	1-1/16-12	1-5/16-12	----
6801-NWO-16	1-5/16-12	1-5/16-12	----
6801-NWO-20	1-5/8-12	1-5/8-12	----

6801 2062R C50X 1238L C5515

JIC TO O-RING 45° ELBOW

SAE 070320
MS 51528

Part #	JIC Thread Size 1	O-Ring Thread Size 2	
6802-NWO-2	5/16-24	5/16-24	----
6802-NWO-4	7/16-20	7/16-20	----
6802-NWO-6	9/16-18	9/16-18	----
6802-NWO-8	3/4-16	3/4-16	----
6802-NWO-8-6	3/4-16	9/16-18	----
6802-NWO-8-10	3/4-16	7/8-14	----
6802-NWO-10	7/8-14	7/8-14	----
6802-NWO-10-8	7/8-14	3/4-16	----
6802-NWO-12	1-1/16-12	1-1/16-12	----
6802-NWO-16	1-5/16-12	1-5/16-12	----
6802-NWO-20	1-5/8-12	1-5/8-12	----

6802 2061 V50X 1240R C5365

JIC TO O-RING - BRANCH TEE

SAE 070429
MS 51529



Part #	JIC Thread Size 1 & 2	O-Ring Thread Size 3	
6803-NWO-4	7/16-20	7/16-20	----
6803-NWO-6	9/16-18	9/16-18	----
6803-NWO-8	3/4-16	3/4-16	----
6803-NWO-10	7/8-14	7/8-14	----
6803-NWO-12	1-1/16-12	1-1/16-12	----
6803-NWO-16	1-5/16-12	1-5/16-12	----

6803 203003X S50X 1265R C5715

JIC TO O-RING RUN TEE

SAE 070428
MS 51530



Part #	JIC Thread Size 1 & 3	O-Ring Thread Size 2	
6804-NWO-4	7/16-20	7/16-20	----
6804-NWO-6	9/16-18	9/16-18	----
6804-NWO-8	3/4-16	3/4-16	----
6804-NWO-10	7/8-14	7/8-14	----
6804-NWO-12	1-1/16-12	1-1/16-12	----
6804-NWO-16	1-5/16-12	1-5/16-12	----

6804 203005R R50X 1266R C5716

O-RING TO - FEMALE PIPE ELBOW

Part #	O-Ring Thread Size 1	Pipe Thread Size 2	
6805-NWO-4-4	7/16-20	1/4	----
6805-NWO-6-6	9/16-18	3/8	----
6805-NWO-8-8	3/4-16	1/2	----
6805-NWO-10-8	7/8-14	1/2	----
6805-NWO-12-8	1-1/16-12	1/2	----
6805-NWO-12-12	1-1/16-12	3/4	----
6805-NWO-16-16	1-5/16-12	1	----

6805 206801R AE0G 1264 C3459

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

STEEL O-RINGS

HYDRAULIC ADAPTERS

O-RING TO MALE PIPE ELBOW

Part #	O-Ring Thread Size 1	Pipe Thread Size 2	
6806-NWO-4-4	7/16-20	1/4	----
6806-NWO-6-6	9/16-18	3/8	----
6806-NWO-8-8	3/4-16	1/2	----
6806-NWO-12-12	1-1/16-12	3/4	----
6806-NWO-16-16	1-5/16-12	1	----

6806 1263 TF3569

O-RING TO 37° JIC SWIVEL NUT TO O-RING ELBOW

Part #	O-Ring Thread Size 1	JIC Thread Size 2	
6809-NWO-4-4	7/16-20	7/16-20	----
6809-NWO-6-6	9/16-18	9/16-18	----
6809-NWO-8-8	3/4-16	3/4-16	----
6809-NWO-12-12	1-1/16-12	1-1/16-12	----

FEMALE O-RING TO MALE O-RING ELBOW

Part #	O-Ring Thread Size 1	O-Ring Thread Size 2	
6815-NWO-4-4	7/16-20	7/16-20	----
6815-NWO-6-6	9/16-18	9/16-18	----
6815-NWO-8-8	3/4-16	3/4-16	----
6815-NWO-10-10	7/8-14	7/8-14	----
6815-NWO-12-12	1-1/16-12	1-1/16-12	----

MALE O-RING SWIVEL ADAPTER

SAE 140157

Part #	O-Ring Thread Size 1	Female NPSM Size 2	
6900-O-4-2	7/16-20	1/8	----
6900-O-4-4	7/16-20	1/4	----
6900-O-6-4	9/16-18	1/4	----
6900-O-6-6	9/16-18	3/8	----
6900-O-6-8	9/16-18	1/2	----
6900-O-8-6	3/4-16	3/8	----
6900-O-8-8	3/4-16	1/2	----
6900-O-8-12	3/4-16	3/4	----
6900-O-10-8	7/8-14	1/2	----
6900-O-10-12	7/8-14	3/4	----
6900-O-12-8	1-1/16-12	1/2	----
6900-O-12-12	1-1/16-12	3/4	----
6900-O-16-16	1-5/16-12	1	----

6900 2066R 1235 9315

90° O-RING SWIVEL ADAPTER

SAE 140257

Part #	O-Ring Thread Size 1	Female NPSM Size 2	
6901-NWO-4-4	7/16-20	1/4	----
6901-NWO-6-4	9/16-18	1/4	----
6901-NWO-6-6	9/16-18	3/8	----
6901-NWO-6-8	9/16-18	1/2	----
6901-NWO-8-4	3/4-16	1/4	----
6901-NWO-8-6	3/4-16	3/8	----
6901-NWO-8-8	3/4-16	1/2	----
6901-NWO-8-12	3/4-16	3/4	----
6901-NWO-10-6	7/8-14	3/8	----
6901-NWO-10-8	7/8-14	1/2	----
6901-NWO-12-6	1-1/16-12	3/8	----
6901-NWO-12-8	1-1/16-12	1/2	----
6901-NWO-12-12	1-1/16-12	3/4	----
6901-NWO-16-12	1-5/16-12	3/4	----
6901-NWO-16-16	1-5/16-12	1	----
6901-NWO-20-20	1-5/8-12	1-1/4	----

6401 2068R 1271 9515

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

45° O-RING SWIVEL ADAPTER

SAE 140357

Part #	O-Ring Thread Size 1	Female NPSM Size 2	
6902-NWO-4-4	7/16-20	1/4	----
6902-NWO-6-4	9/16-18	1/4	----
6902-NWO-6-6	9/16-18	3/8	----
6902-NWO-8-8	3/4-16	1/2	----
6902-NWO-10-8	7/8-14	1/2	----
6902-NWO-12-8	1-1/16-12	1/2	----
6902-NWO-12-12	1-1/16-12	3/4	----
6902-NWO-16-16	1-5/16-12	1	----

6902 2067R 1272 9365

O-RINGS

VITON 75 SAE BOSS O-RING

Fluorocarbon

Part #	O-Ring Thread	
4001-2-2	5/16-24	----
4001-4-4	7/16-20	----
4001-6-6	9/16-18	----
4001-8-8	3/4-16	----
4001-10	7/8-14	----
4001-12	1-1/16-12	----
4001-16	1-5/16-12	----
4001-20	1-5/8-12	----
4001-24	1-7/8-12	----
4001-32	2-1/2-12	----

NITRILE 90 SAE BOSS O-RING

Part #	O-Ring Thread	
4000-2-2	5/16-24	----
4000-4-4	7/16-20	----
4000-6-6	9/16-18	----
4000-8-8	3/4-16	----
4000-10	7/8-14	----
4000-12	1-1/16-12	----
4000-14	1-3/16-12	----
4000-16	1-5/16-12	----
4000-20	1-5/8-12	----
4000-24	1-7/8-12	----
4000-32	2-1/2-12	----

BRAZE TUBE NUT (SLEEVE REQUIRED)

SAE 520110

Part #	Tube O.D.	Braze Tube O.D.	
FSO318-4	1/4	.25	----
FSO318-6	3/8	.38	----
FSO318-8	1/2	.50	----
FSO318-10	5/8	.62	----
FSO318-12	3/4	.72	----
FSO318-16	1	1.00	----
FSO318-20	1 1/4	1.25	----
FSO318-24	1 1/2	1.50	----

FF318 FF1311

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

O-RING FACE SEAL ADAPTERS

BRAZE TUBE SLEEVE

SAE 520115

Part #	Tube O.D.	
FSO319-4	1/4	----
FSO319-6	3/8	----
FSO319-8	1/2	----
FSO319-10	5/8	----
FSO319-12	3/4	----
FSO319-16	1	----
FSO319-20	1-1/4	----
FSO319-24	1-1/2	----

FF319 FF3019

See Page 414 for JIC Nut and Sleeve

CAP

SAE 520112

• Two Piece Nut/ Insert

Part #	Tube O.D.	Face Seal Thread	
FSO304-C-4	1/4	9/16-18	----
FSO304-C-6	3/8	11/16-16	----
FSO304-C-8	1/2	13/16-16	----
FSO304-C-10	5/8	1-14	----
FSO304-C-12	3/4	1-3/16-12	----
FSO304-C-16	1	1-7/16-12	----
FSO304-C-20	1-1/4	1-11/16-12	----
FSO304-C-24	1-1/2	2-12	----

FF304C

BULKHEAD LOCKNUT

SAE 520118

Part #	Thread Size	
FSO306-4	9/16-18	----
FSO306-6	11/16-16	----
FSO306-8	13/16-16	----
FSO306-12	1-3/16-12	----
FSO306-16	1-7/16-12	----

FF403

MALE UNION CONNECTOR

SAE 520102

Part #	Tube O.D.	Face Seal Thread 1&2	
FSO2403-4-4	1/4	9/16-18	----
FSO2403-6-6	3/8	11/16-16	----
FSO2403-8-8	1/2	13/16-16	----
FSO2403-12-12	3/4	1-3/16-12	----
FSO2403-16-16	1	1-7/16-12	----

FF2403 FF1203

MALE O-RING FACE SEAL ADAPTER

Part #	Face Seal Thread 1	Male Pipe Size 2	
FSO2404-4-4	9/16-18	1/4-18	----
FSO2404-6-4	11/16-16	1/4-18	----
FSO2404-6-6	11/16-16	3/8-18	----
FSO2404-8-4	13/16-16	1/4-18	----
FSO2404-8-8	13/16-16	1/2-14	----
FSO2404-12-12	1-3/16-12	3/4-14	----
FSO2404-16-16	1-7/16-12	1-11-1/2	----

FF2404 4205 FLO

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

FEMALE ORFS TO MALE ORFS REDUCER

Part #	Female Face Seal Size 1	Male Face Seal Thread 2	
FSO2406-6-4	11/16-16	9/16-18	----
FSO2406-8-4	13/16-16	9/16-18	----
FSO2406-10-6	1-14	11/16-16	----
FSO2406-10-8	1-14	13/16-16	----
FSO2406-12-6	1-3/16-12	11/16-16	----

FF2406 TRLON

PLUG

SAE 520109

Part #	Tube O.D.	Face Seal Thread	
FSO2408-4	1/4	9/16-18	----
FSO2408-6	3/8	11/16-16	----
FSO2408-8	1/2	13/16-16	----
FSO2408-10	5/8	1-14	----
FSO2408-12	3/4	1-3/8-12	----
FSO2408-16	1	1-7/16-12	----
FSO2408-20	1-1/4	1-11/16-12	----
FSO2408-24	1-1/2	2-12	----

FF2408 FF1254 4229 PNLO

ORFS UNION ELBOW 90°

Part #	Face Seal Thread 1	Face Seal Thread 2	
FS2500-4-4	9/16-18	9/16-18	----
FS2500-6-6	11/16-16	11/16-16	----
FS2500-10-10	1-14	1-14	----
FS2500-12-12	1-3/16-12	1-3/16-12	----
FS2500-16-16	1-7/16-12	1-7/16-12	----

FF2500 4505 ELO

ORFS TO MALE ELBOW

SAE 520202

Part #	Face Seal Thread 1	Male Pipe Thread 2	
FS2501-4-4	9/16-18	1/4	----
FS2501-6-4	11/16-16	1/4	----
FS2501-6-6	11/16-16	3/8	----
FS2501-8-6	13/16-16	3/8	----
FS2501-8-8	13/16-16	1/2	----
FS2501-12-12	1-3/8-12	3/4	----
FS2501-16-16	1-7/16-12	1	----
FS2501-20-20	1-11/16-12	1-1/4	----

FF2501 FF1208 4405 CLO

ORFS TO PIPE ELBOW 45°

Part #	Face Seal Thread 1	Male Pipe Thread 2	
FS2503-4-4	9/16-18	1/4	----
FS2503-6-6	11/16-16	3/8	----
FS2503-8-8	13/16-16	1/2	----
FS2503-12-12	1-3/16-12	3/4	----
FS2503-16-16	1-7/16-12	1	----

FF2503 4355 VLO

ORFS UNION TEE

Part #	Face Seal Thread 1+2+3	
FS2603-4-4	9/16-18	----
FS2603-6-6	11/16-16	----
FS2603-8-8	13/16-16	----
FS2603-12-12	1-3/16-12	----

FF2603 4705 JLO

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

O-RING FACE SEAL ADAPTERS

MALE ORFS TO ORB CONNECTOR

SAE 520120

Part #	Face Seal Thread 1	O-Ring Thread 2	
FS6400-O-4-4	9/16-18	7/16-20	----
FS6400-O-4-6	9/16-18	9/16-18	----
FS6400-O-6-4	11/16-16	7/16-20	----
FS6400-O-6-6	11/16-16	9/16-18	----
FS6400-O-6-8	11/16-16	3/4-16	----
FS6400-O-8-6	13/16-16	9/16-18	----
FS6400-O-10-8	1-14	3/4-16	----
FS6400-O-10-10	1-14	7/8-14	----
FS6400-O-12-8	1-3/16-12	3/4-16	----
FS6400-O-12-10	1-3/16-12	7/8-14	----
FS6400-O-12-12	1-3/16-12	1-1/16-12	----
FS6400-O-12-16	1-3/16-12	1-5/16-12	----
FS6400-O-16-12	1-7/16-12	1-1/16-12	----
FS6400-O-16-16	1-7/16-12	1-5/16-12	----
FS6400-O-20-20	1-11/16-12	1-5/8-12	----
FS6400-O-24-24	2-12	1-7/8-12	----

4315 FF6400 FF1231

MALE FLAT FACE TO FEMALE 37 ° SWIVEL

Part #	Face Seal Thread 1	JIC Thread 2	
FS6402-4-4	9/16-18	7/16-20	----
FS6402-6-6	11/16-16	9/16-18	----
FS6402-8-8	13/16-16	3/4-16	----
FS6402-10-10	1-14	7/8-14	----
FS6402-12-12	1-3/16-12	1-1/16-12	----

FF6402 FF1294

SWIVEL NUT ELBOW

Part #	Face Seal Thread 1	Face Seal Thread 2	
FS6500-4-4	9/16-18	9/16-18	----
FS6500-6-6	11/16-16	11/16-16	----
FS6500-8-8	13/16-16	13/16-16	----
FS6500-12-12	1-3/16-12	1-3/16-12	----

FF6500 FF1236

MALE JIC 37° FLARE TO FEMALE FLAT FACE SWIVEL

Part #	JIC Thread Size 1	Face Seal Thread 2	
FS6504-4-4	7/16-20	9/16-18	----
FS6504-6-6	9/16-18	11/16-16	----
FS6504-8-8	3/4-16	13/16-16	----
FS6504-10-10	7/8-14	1-14	----
FS6504-16-16	1-5/16-12	1-7/16-12	----

FF6504 FF1296

O-RING ELBOW CONNECTOR

Part #	Face Seal Thread 1	O-Ring Thread 2	
FS6801-4-4	9/16-18	7/16-20	----
FS6801-6-6	11/16-16	9/16-18	----
FS6801-8-6	13/16-16	9/16-18	----
FS6801-8-8	13/16-16	3/4-16	----
FS6801-12-12	1-3/16-12	1-1/16-12	----
FS6801-16-16	1-7/16-12	1-5/16-12	----
FS6801-20-20	1-11/16-12	1-5/8-12	----

FF6801 FF1238 4515

ORFS TO O-RING ELBOW 45°

Part #	Face Seal Thread 1	O-Ring Size 2	
FS6802-4-4	9/16-18	7/16-20	----
FS6802-6-6	11/16-16	9/16-18	----
FS6802-8-8	13/16-16	3/4-16	----
FS6802-10-10	1-14	7/8-14	----
FS6802-12-12	1-3/16-12	1-1/16-12	----
FS6802-16-16	1-7/16-12	1-5/16-12	----
FS6802-20-20	1-11/16-12	1-5/8-12	----

FF6802 4365 V5OLO

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

STEEL BSPT ADAPTERS

STRAIGHT THREAD SWIVEL NUT ELBOW

Part #	O-Ring Thread 1	Face Seal Thread 2	
FS6809-4-4	7/16-20	9/16-18	----
FS6809-6-6	9/16-18	11/16-16	----
FS6809-8-8	3/4-16	13/16-16	----
FS6809-12-12	1-1/16-12	1-3/16-12	----

FF6809 FF1239 4535 AOELC

STEEL BSPT ADAPTERS

JIC MALE CONNECTOR BSPT

Part #	JIC Thread Size 1	Male BSPT 2	
7000-4-2	7/16-20	1/8-28	----
7000-4-4	7/16-20	1/4-19	----
7000-6-4	9/16-18	1/4-19	----
7000-6-6	9/16-18	3/8-19	----
7000-6-8	9/16-18	1/2-14	----
7000-8-6	3/4-16	3/8-19	----
7000-8-8	3/4-16	1/2-14	----
7000-8-12	3/4-16	3/4-14	----
7000-10-8	7/8-14	1/2-14	----
7000-10-12	7/8-14	3/4-14	----
7000-12-8	1-1/16-12	1/2-14	----
7000-12-12	1-1/16-12	3/4-14	----
7000-16-16	1-5/16-12	1-11	----
7000-20-20	1-5/8-12	1-1/4-11	----

3404 3O5

JIC MALE ELBOW BSPT

Part #	JIC Thread Size 1	Male BSPT 2	
7200-4-2	7/16-20	1/8-28	----
7200-4-4	7/16-20	1/4-19	----
7200-6-4	9/16-18	1/4-19	----
7200-6-6	9/16-18	3/8-19	----
7200-6-8	9/16-18	1/2-14	----
7200-8-6	3/4-16	3/8-19	----
7200-8-8	3/4-16	1/2-14	----
7200-12-12	1-1/16-12	3/4-14	----
7200-16-16	1-5/16-12	1-11	----

3501 315

BSPT HEX NIPPLE

Part #	Male BSPT 1	Male BSPT 2	
7520-2-2	1/8-28	1/8-28	----
7520-4-4	1/4-19	1/4-19	----
7520-6-6	3/8-19	3/8-19	----
7520-8-8	1/2-14	1/2-14	----
7520-10-10	5/8-14	5/8-14	----
7520-12-12	3/4-14	3/4-14	----

3520 MBT

BSPT PLUG

Part #	BSPT	
9508-2	1/8-28	----
9508-4	1/4-19	----
9508-6	3/8-19	----
9508-8	1/2-14	----
9508-12	3/4-14	----
9508-16	1-11	----

100B-Y KA-RM MHL 296

STEEL BSPP ADAPTERS

BSPP HEX NIPPLE

Part #	Male BSPP 1	Male BSPP 2	
7420-2-2	1/8-28	1/8-28	----
7420-4-2	1/4-19	1/8-28	----
7420-6-4	3/8-19	1/4-19	----
7420-6-6	3/8-19	3/8-19	----
7420-8-6	1/2-14	3/8-19	----
7420-8-8	1/2-14	1/2-14	----
7420-10-8	5/8-14	1/2-14	----
7420-12-8	3/4-14	1/2-14	----
7420-12-12	3/4-14	3/4-14	----
7420-16-12	1-11	3/4-14	----
7420-16-16	1-11	1-11	----

3420 MB 9022

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

STEEL BSPP ADAPTERS

HYDRAULIC ADAPTERS

BSPP COUPLING

Part #	BSPP	
7425-2	1/8-28	----
7425-4	1/4-19	----
7425-8	1/2-14	----
7425-10	5/8-14	----
7425-12	3/4-14	----
7425-16	1-11	----

3425 FB

JIC TO FEMALE BSPP STRAIGHT SWIVEL

Part #	JIC Thread Size 1	Female BSPP Swivel 2	
7240-4	7/16-20	1/4-19	----
7240-6	9/16-18	3/8-19	----
7240-8	3/4-16	1/2-14	----
7240-10	7/8-14	5/8-14	----
7240-12	1-1/16-12	3/4-14	----
7240-16	1-5/16-12	1-11	----

3240 MJFBS

JIC TO BSPP MALE ELBOW

Part #	JIC Thread Size 1	Male BSPP 2	
7202-NWO-4-2	7/16-20	1/8-28	----
7202-NWO-4-4	7/16-20	1/4-19	----
7202-NWO-6-4	9/16-18	1/4-19	----
7202-NWO-6-6	9/16-18	3/8-19	----
7202-NWO-6-8	9/16-18	1/2-14	----
7202-NWO-8-6	3/4-16	3/8-19	----
7202-NWO-8-8	3/4-16	1/2-14	----
7202-NWO-8-12	3/4-16	3/4-14	----
7202-NWO-10-8	7/8-14	1/2-14	----
7202-NWO-12-12	1-1/16-12	3/4-14	----
7202-NWO-12-16	1-1/16-12	1-11	----
7202-NWO-16-16	1-5/16-12	1-11	----

3801 315

JIC TO BSPP 45° ELBOW

Part #	JIC Thread Size 1	Male BSPP 2	
7802-4	7/16-20	1/4-19	----
7802-6	9/16-18	3/8-19	----
7802-8	3/4-16	1/2-14	----
7802-12	1-1/16-12	3/4-14	----
7802-16	1-5/16-12	1-11	----

3802 35J

BSPP TO MALE PIPE NIPPLE

Part #	Male BSPP Size 1	Male Pipe Thread Size 2	
7825-2	1/8-28	1/8	----
7825-4	1/4-19	1/4	----
7825-6	3/8-19	3/8	----
7825-8	1/2-14	1/2	----
7825-12	3/4-14	3/4	----
7825-16	1-11	1	----

MBMP 3825

JIC TO BSPP MALE CONNECTOR

Part #	JIC Thread Size 1	Male BSPP 2	
7002-4-2	7/16-20	1/8-28	----
7002-4-4	7/16-20	1/4-19	----
7002-4-6	7/16-20	3/8-19	----
7002-4-8	7/16-20	1/2-14	----
7002-6-4	9/16-18	1/4-19	----
7002-6-6	9/16-18	3/8-19	----
7002-6-8	9/16-18	1/2-14	----
7002-8-6	3/4-16	3/8-19	----
7002-8-8	3/4-16	1/2-14	----
7002-8-12	3/4-16	3/4-14	----
7002-10-8	7/8-14	1/2-14	----
7002-12-12	1-1/16-12	3/4-14	----
7002-12-16	1-1/16-12	1-11	----
7002-16-16	1-5/16-12	1-11	----

30J 3800

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

STEEL BSPP ADAPTERS

JIC TO BSPP STRAIGHT SWIVEL

Part #	JIC Thread Size 1	Male BSPP 2	
7022-4-2	7/16-20	1/8-28	----
7022-4-4	7/16-20	1/4-19	----
7022-6-6	9/16-18	3/8-19	----
7022-8-8	3/4-16	1/2-14	----
7022-10-8	7/8-14	1/2-14	----
7022-12-12	1-1/16-12	3/4-14	----
7022-16-16	1-5/16-12	1-11	----

3402 3055

HEX HEAD PLUG BSPP

Part #	Male BSPP	
9522-P-2	1/8-28	----
9522-P-4	1/4-19	----
9522-P-6	3/8-19	----
9522-P-8	1/2-14	----
9522-P-12	3/4-14	----
9522-P-16	1-11	----

3408

HOLLOW HEX PLUG BSPP

Part #	Male BSPP	
9522-H-2	1/8-28	----
9522-H-4	1/4-19	----
9522-H-6	3/8-19	----
9522-H-8	1/2-14	----
9522-H-12	3/4-14	----
9522-H-16	1-11	----

3408 HHP

FEMALE ADAPTER BSPP

Part #	Female Pipe 1	Male BSPP 2	
7042-2-2	1/8	1/8-28	----
7042-4-2	1/4	1/8-28	----
7042-4-4	1/4	1/4-19	----
7042-6-6	3/8	3/8-19	----
7042-8-8	1/2	1/2-14	----
7042-12-12	3/4	3/4-14	----
7042-16-16	1	1-11	----

3455 MMFP

STEEL METRIC ADAPTERS

MALE CONNECTOR

Part #	JIC Thread Size 1	Metric Thread 2	
7005-4-10	7/16-20	10x1.0	----
7005-4-12	7/16-20	12x1.5	----
7005-4-14	7/16-20	14x1.5	----
7005-4-18	7/16-20	18x1.5	----
7005-5-12	1/2-20	12x1.5	----
7005-5-14	1/2-20	14x1.5	----
7005-6-14	9/16-18	14x1.5	----
7005-6-16	9/16-18	16x1.5	----
7005-6-18	9/16-18	18x1.5	----
7005-8-16	3/4-16	16x1.5	----
7005-8-18	3/4-16	18x1.5	----
7005-8-22	3/4-16	22x1.5	----
7005-10-18	7/8-14	18x1.5	----
7005-10-20	7/8-14	20x1.5	----
7005-10-22	7/8-14	22x1.5	----
7005-12-22	1-1/16-12	22x1.5	----
7005-12-27	1-1/16-12	27x1.5	----

Port-seal crush washer and O-ring included 7400 30J (R) 7011

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

STEEL METRIC ADAPTERS

MALE ELBOW

Part #	JIC Thread Size 1	Metric Thread 2	
7205-NWO-4-10	7/16-20	10x1.0	----
7205-NWO-4-12	7/16-20	12x1.5	----
7205-NWO-4-14	7/16-20	14x1.5	----
7205NWO-5-12	1/2-20	12x1.5	----
7205-NWO-6-14	9/16-18	14x1.5	----
7205-NWO-6-16	9/16-18	16x1.5	----
7205-NWO-8-16	3/4-16	16x1.5	----
7205-NWO-8-18	3/4-16	18x1.5	----
7205-NWO-8-22	3/4-16	22x1.5	----
7205-NWO-10-18	7/8-14	18x1.5	----

Port-seal crush washer and O-ring included

7801 315 (R)

STRAIGHT SWIVEL

Part #	JIC Thread Size 1	Metric Thread 2	
7025-4-10	7/16-20	10x1.0	----
7025-4-12	7/16-20	12x1.5	----
7025-5-12	1/2-20	12x1.5	----
7025-6-14	9/16-18	14x1.5	----
7025-6-16	9/16-18	16x1.5	----
7025-8-16	3/4-16	16x1.5	----
7025-10-22	7/8-14	22x1.5	----
7025-12-27	1-1/16-12	27x2.0	----
7025-16-33	1-5/16-12	33x2.0	----

7402 30JS (R)

HEX HEAD PLUG METRIC PARALLEL

Part #	Metric Thread	
8555-P-10	10x1.0	----
8555-P-12	12x1.5	----
8555-P-14	14x1.5	----
8555-P-16	16x1.5	----
8555-P-18	18x1.5	----
8555-P-20	20x1.5	----
8555-P-22	22x1.5	----
8555-P-26	26x1.5	----
8555-P-30	30x1.5	----

7408

HYDRAULIC ADAPTERS

HOLLOW HEX HEAD PLUG METRIC PARALLEL

Part #	Metric Thread	
8555-H-10	10x1.0	----
8555-H-12	12x1.5	----
8555-H-14	14x1.5	----
8555-H-16	16x1.5	----
8555-H-18	18x1.5	----
8555-H-20	20x1.5	----
8555-H-22	22x1.5	----
8555-H-26	26x1.5	----
8555-H-30	30x1.5	----

7408 HHP

FEMALE ADAPTER

Part #	Female Pipe Thread 1	Metric Thread 2	
7045-2-10	1/8	10x1.0	----
7045-4-12	1/4	12x1.5	----
7045-4-14	1/4	14x1.5	----
7045-6-12	3/8	12x1.5	----
7045-6-16	3/8	16x1.5	----
7045-6-18	3/8	18x1.5	----
7045-8-16	1/2	16x1.5	----
7045-8-18	1/2	18x1.5	----
7045-8-22	1/2	22x1.5	----
7045-12-27	3/4	27x2.0	----
7045-16-33	1	33x2.0	----

MMFP (R)

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

THREAD TO CONNECT, DRYBREAK NO-SPILL QUICK CONNECT

- Brass Body
- Steel Wing Nut
- Buna-Seal (-40° to +250°F)

Aeroquip 5100
Parker 6100
Snaptite B78

- Bonded Face Seal
- External ORing Alleviates Full Connection

Part #	Body Size	Female NPT	Max PSI	
61-150	3/4	1/2	3000	----
61-152	3/4	3/4	3000	----
61-153	1	1	3000	----
61-154	1-1/4	1-1/4	2750	----
61-155	1-1/2	1-1/2	2500	----

Part #	Body Size	Female NPT	Max PSI	
61-050	3/4	1/2	3000	----
61-052	3/4	3/4	3000	----
61-053	1	1	3000	----
61-054	1-1/4	1-1/4	2750	----
61-055	1-1/2	1-1/2	2500	----

FEATURES - **ISO A and ISO B**

- Poppet valves to prevent uncoupled leakage
- Critical parts are induction hardened for durability
- Dependable ball-locking mechanism holds the maling halves together
- Socket and plug are precision machined from solid barstock
- Standard nitrile seals temp range -40°F to +250°F

ISO 7241-1 ISO-A Interchange (Connected)				
Body Size	*Steel Coupler/ Plug*			
	Maximum Working		*Burst*	
	PSI	Bar	PSI	Bar
1/4"	5,000	345	18,270	1,200
3/8"	4,000	275	18,270	1,200
1/2"	4,000	275	16,500	1,100
3/4"	4,000	275	14,800	1,000
1"	4,000	275	12,400	850

INTERCHANGE DATA:

- Parker 6600, Aeroquip/ Eaton FD56, Dixon 'K' Series.
- Hansen HA 15000, Safeway S56

ISO-A FEMALE PIPE COUPLER

Part #	Body Size	NPT	
ANV-14-F	1/4"	1/4"	----
ANV-38-F	3/8"	3/8"	----
ANV-12-F	1/2"	1/2"	----
ANV-34-F	3/4"	3/4"	----
ANV-1-F	1"	1"	----

ISO-A FEMALE PIPE PLUG

Part #	Body Size	NPT	
ANV-14-M	1/4"	1/4"	----
ANV-38-M	3/8"	3/8"	----
ANV-12-M	1/2"	1/2"	----
ANV-34-M	3/4"	3/4"	----
ANV-1-M	1"	1"	----

ISO 7241-1 Series B ISO-B Interchange (Connected)								
Body Size	*Steel Coupler/ Plug*				*Brass Coupler/ Plug*			
	Max. Working		*Burst*		*Max. Working*		*Burst*	
	PSI	Bar	PSI	Bar	PSI	Bar	PSI	Bar
1/4"	5,000	345	22,500	1,550	3,000	200	15,000	1,000
3/8"	4,000	275	16,500	1,150	2,500	175	12,000	800
1/2"	4,000	275	16,000	1,100	2,500	175	11,500	750
3/4"	4,000	275	16,500	1,150	2,000	150	12,000	800
1"	4,000	275	16,000	1,100	1,500	100	8,500	800

INTERCHANGE DATA:

- Parker 60 Series, Snap-tite 72 series, Dixon 'H' series
- Hansen HK - series, Aeroquip/ Eaton FDH5

B=BRASS

BRASS - HNV SERIES PLUG

BRASS - HNV SERIES COUPLER

ISO-B FEMALE PIPE COUPLER

Part #	Body Size	NPT	
HNV-14-F	1/4"	1/4"	----
HNV-14-F-B	1/4"	1/4"	----
HNV-38-F	3/8"	3/8"	----
HNV-38-F-B	3/8"	3/8"	----
HNV-12-F	1/2"	1/2"	----
HNV-12-F-B	1/2"	1/2"	----
HNV-34-F	3/4"	3/4"	----
HNV-34-F-B	3/4"	3/4"	----
HNV-1-F	1"	1"	----
HNV-1-F-B	1"	1"	----

ISO-B FEMALE PIPE PLUG

Part #	Body Size	NPT	
HNV-14-M	1/4"	1/4"	----
HNV-14-M-B	1/4"	1/4"	----
HNV-38-M	3/8"	3/8"	----
HNV-38-M-B	3/8"	3/8"	----
HNV-12-M	1/2"	1/2"	----
HNV-12-M-B	1/2"	1/2"	----
HNV-34-M	3/4"	3/4"	----
HNV-34-M-B	3/4"	3/4"	----
HNV-1-M	1"	1"	----
HNV-1-M-B	1"	1"	----

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

QUICK DISCONNECT — HYDRAULIC ADAPTERS

FEATURES
• Steel construction, zinc plated trivalent finish. Hardened Nipples and sleeves and solid barstock construction for maximum resistance to damage from hydraulic and mechanical shock.
• This Anti-Blowout Nitrile/ PTFE bonded seal is designed to prevent blow out or damage during servere service conditions.
• Durable ball-locking mechanism assures reliable connection everytime.
• Temp Range -65° to +250°

ISO 16028

FLUSH FACE

Body Size	Steel Coupler/ Plug Coupled			
	Maximum Working		Burst	
	PSI	Bar	PSI	Bar
1/4"	5,000	345	18,270	1,200
3/8"	4,000	275	18,270	1,200
1/2"	4,000	275	16,500	1,100
5/8"	4,000	275	14,800	1,000
3/4"	4,000	275	12,400	850
1"	3,000	200	12,600	850

FF Series
HTMC
74C

FEMALE PIPE COUPLER

Part #	Body Size	NPT	
FF-14-F	1/4"	1/4"	----
FF-38-F	3/8"	3/8"	----
FF-12-F	1/2"	1/2"	----
FF-3812-F	3/8"	1/2"	----
FF-1234-F	1/2"	3/4"	----
FF-1012F	5/8"	3/4"	
FF-3416-F	3/4"	1"	----
FF-34-F	3/4"	3/4"	----
FF-1-F	1"	1"	----

FF Series
HTMN
74N

FEMALE PIPE PLUG

Part #	Body Size	NPT	
FF-14-M	1/4"	1/4"	----
FF-38-M	3/8"	3/8"	----
FF-12-M	1/2"	1/2"	----
FF-3812-M	3/8"	1/2"	----
FF-1234-M	1/2"	3/4"	----
FF-3416-M	3/4"	1"	----
FF-34-M	3/4"	3/4"	----
FF-1-M	1"	1"	----

FLAT FACE THREAD LOCK - VEP QUICK COUPLING

SPECIFICATIONS

Body Size (in)	1/2(12)	3/4(34)	1(1)	1-1/2(24)
Rated Pressure (PSI)	7000	7000	6000	5000
Rated Flow (GPM)	12	50	88	152
Temperature Range	-20°C +120°C			

Standard seal material is **NBR**

Test Fluid-Oil = 200 SUS

APPLICATIONS
• Widely used in public equipment
• Portable construction equipment.
• Hydraulic tools
• Vehicles

FEATURES
• New valve design provides better resistance from high flow and the pressure of impulse, thus providing advanced performance.
• Special nipple design for connecting under pressure, allows connection and disconnection with high residual pressures.
• The LSQ-VEP series employs a threaded sleeve locking mechanism, mates with matching male threads on the coupler.
• New plating treatment provides advanced anti-rust performance.
• LSQ-VEP series couplings employ flush valving when connecting or disconnecting, therefore only a small amount of fluid can be lost during disconnecting or air inclusion during reconnection.
• The Anti-Blowout bonded seal is designed to prevent blow-out or damage during severe service conditions.
• Machined form solid steel barstock for durability. Compatible with most other VEP series.

• O-Ring SAE Boss Thread available with import lead time (same list price)



FEMALE COUPLER

Part #	LS	D	A	NPT	
LSQ-VEP-12-SF	4.09	1.13	0.67	1/2	----
LSQ-VEP-34-SF	4.49	2.13	0.79	3/4	----
LSQ-VEP-1-SF	5.28	2.33	0.83	1	----
LSQ-VEP-20-SF	5.71	2.72	0.83	1-1/4	----
LSQ-VEP-24-SF	7.41	3.63	0.83	1-1/2	----



FEMALE PLUG

Part #	LS	D	A	NPT	
LSQ-VEP-12-PF	4.09	1.13	0.67	1/2	----
LSQ-VEP-34-PF	4.49	2.13	0.79	3/4	----
LSQ-VEP-1-PF	5.28	2.33	0.83	1	----
LSQ-VEP-20-PF	5.71	2.72	0.83	1-1/4	----
LSQ-VEP-24-PF	7.41	3.63	0.83	1-1/2	----

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

AG - Series Agricultural Interchange (Connected)				
Nominal Size	*Steel Coupler/ Plug*			
	Maximum Working		*Burst*	
	PSI	Bar	PSI	Bar
1/4"	4,000	275	21,000	1,500
3/8"	4,000	275	23,100	1,600
1/2"	4,000	275	16,500	1,100
3/4"	3,000	200	10,300	700
1"	3,000	200	13,000	900

Snap-Tite 60 Series

FEMALE PIPE COUPLER

Part #	Body Size	NPT	
NV-14-F	1/4"	1/4"	----
NV-38-F	3/8"	3/8"	----
NV-12-F	1/2"	1/2"	----
NV-34-F	3/4"	3/4"	----
NV-1-F	1"	1"	----

FEMALE PIPE PLUG

Part #	Body Size	NPT	
NV-14-M	1/4"	1/4"	----
NV-38-M	3/8"	3/8"	----
NV-12-M	1/2"	1/2"	----
NV-34-M	3/4"	3/4"	----
NV-1-M	1"	1"	----

FEATURES

- Heavy duty heat treated poppet: valves are standard with rugged, specially-designed seals made of nitrite for leak-free performance in the toughest application.
- High-strength steel valve guides designed for high flow rates and made extra tough for agricultural service.
- Dependable hardened chrome alloy steel locking balls. Heat treated plugs and sleeves.
- Standard seals temp range -40°F to +250°F

THREAD LOCK HYDRAULIC JACK COUPLING

APPLICATIONS

- Thread lock couplings with their threaded union locking system and precision ball-type check valves are designed for extreme high pressure applications such as portable hydraulic jacks.
- **Ball Type.**





SPECIFICATIONS

Body Size	1/4(14)	3/8(38)
Rated Pressure	10.000	
Rated Flow (GPM)	3	6
Temperature Range	-20°C +120°C	

Standard seal material is **NBR**

MALE COUPLER

Part #	LS	D	Hex	A	NPT	
KZE-B-14-SM	2.40	1.14	0.87	0.55	1/4	----
KZE-B-38-SM	2.91	1.38	0.98	0.57	3/8	----

FEMALE COUPLER

Part #	LS	D	Hex	A	NPT	
KZE-B-14-PF	1.30	0.44	0.75	0.51	1/4	----
KZE-B-38-PF	1.38	0.63	1.26	0.55	3/8	----

WARNING: This product can expose you to chemicals, including Cobalt, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov

MM-FC SERIES FLOW CONTROL VALVES

FEATURES:
• Micrometer adjustment knob for accurate valve setting.
• Rugged construction.
TECHNICAL DATA:
• Materials

Body:	Carbon steel w/ black oxide plating
Handle:	Zinc Alloy
Set Screw:	Steel
Packing:	Buna O-Ring/ PTFE stem packing
Maximum Pressure:	5000PSI
Temperature Ratings:	-4°F to 176°F (-20°C to 80°C)
Flow Rate: 0-42 GPM	

INLET

<< FREE FLOW





Part#	B	D1	D2	D3	H1	H2	H3	L1	L2	WEIGHT (lbs)	
MMFC4NPT	1.10	0.76	1.18	1/4 NPT	0.55	2.41	2.67	1.54	2.52	0.90	----
MMFC6NPT	1.10	0.76	1.18	3/8 NPT	0.55	2.41	2.67	1.69	2.75	0.90	----
MMFC8NPT	1.50	0.95	1.46	1/2 NPT	0.75	3.07	3.41	2.05	3.27	2.00	----
MMFC12NPT	1.50	0.95	1.46	3/4 NPT	0.75	3.08	3.41	2.19	3.50	2.00	----
MMFC16NPT	1.89	1.38	1.89	1 NPT	0.94	4.03	4.50	2.79	4.60	4.20	----
MMFC20NPT	2.38	1.96	2.28	1-1/4 NPT	1.18	5.25	5.88	3.39	6.07	9.55	----

MM-NV SERIES NEEDLE VALVES

FEATURES:
• Micrometer adjustment knob for accurate valve setting.
• Rugged construction.
TECHNICAL DATA:
• Materials

Body:	Carbon steel w/ black oxide plating
Handle:	Zinc Alloy
Set Screw:	Steel
Packing:	Buna O-Ring/ PTFE stem packing
Maximum Pressure:	5000PSI
Temperature Ratings:	-4°F to 176°F (-20°C to 80°C)
Flow Rate: 0-42 GPM	

▪ FULL SHUT-OFF





Part#	B	D1	D2	D3	H1	H2	H3	L1	L2	WEIGHT (lbs)	
MMNV4NPT	1.10	0.76	1.18	1/4 NPT	0.55	2.41	2.67	1.07	2.13	0.90	----
MMNV6NPT	1.10	0.76	1.18	3/8 NPT	0.55	2.41	2.67	1.07	2.13	0.90	----
MMNV8NPT	1.50	0.95	1.46	1/2 NPT	0.75	3.07	3.41	1.34	2.38	2.00	----
MMNV12NPT	1.50	0.95	1.46	3/4 NPT	0.75	3.08	3.41	1.54	3.09	2.00	----
MMNV16NPT	1.89	1.38	1.89	1 NPT	0.94	4.03	4.50	1.81	3.62	4.20	----

WARNING: This product can expose you to chemicals, including cobalt, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

PRESSURE COMPENSATING VARIABLE FLOW CONTROL

FEATURES:

MFC-51 model is a full range pressure compensating variable flow control. It is designed so that the orifice area varies as the lever is rotated. The outlet flw is smooth and constant regardless of the pressure on the control flow or excess flow ports. An adjustable ball spring relief allows for pressure compensated flow up to the pressure setting on the relief. Relief valves are preset at 1500 PSI and field adjustable from 750 to 3000 PSI.

- Materials: Cast Iron Body, Heat Treated Compensator Spool, Stainless Steel Rotary Spool, Buna N "O" Rings (Standard)
- **ALL ARE STANDARD FLOW CONTROL**
- **ALL HAVE ADJUSTABLE BALL SPRING RELIEF**
- **SAE PORT AVAILABLE. MINIMUM ORDER REQUIRED**





Part#	Size	Flow	
MFC-38-N	3/8" - NPT	0-8 gpm	----
MFC-12-N	1/2" - NPT	0-16 gpm	----
MFC-34-N	3/4" - NPT	0-30 gpm	----

SCREW-ON TYPE AIR BREATHERS

• Chrome Plated Steel • 1/4 To 1 Inch NPT • 40 Micron Breather

Part Number	Flow cfm	NPT	
MB40-04	10	1/4	----
MB40-06	10	3/8	----
MB40-08	10	1/2	----
MB40-12	25	3/4	----
MB40-16	25	1	----

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

Part#	Page	Part#	Page	Part#	Page	Part#	Page	Part#	Page	Part#	Page
0304-10	404	100045	211	10-046	51	10-108LF	163	10-212	55	10-259L	56
0304-12	404	1000465	211	10-047	51	10-109	53	10-213	55	10-260	56
0304-16	404	10-005	50	10-048	51	10-109L	53	10-214	55	10-260L	56
0304-4	404	10-006	50	10-049	51	10-109LF	163	10-215	55	10-261	56
0304-6	404	100065	211	10-051	51	10-110	53	10-216	55	10-262	56
0304-8	404	1000665	211	10-052	51	10-110L	53	10-217	55	10-262LF	163
0304-C-10	404	10-007	50	10-053	51	10-110LF	163	10-218	55	10-263	56
0304-C-12	404	10-008	50	10-054	51	10-111	53	10-219	55	10-263L	56
0304-C-14	404	100085	211	10-055	51	10-112	53	10-220	55	10-263LF	163
0304-C-16	404	1000865	211	10-056	51	10-115	54	10-221	55	10-264	56
0304-C-2	404	1001125	211	10-058	51	10-116	54	10-227	55	10-264L	56
0304-C-20	404	10011265	211	10-062	52	10-117	54	10-228	55	10-264LF	163
0304-C-24	404	1001165	211	10-063	52	10-118	54	10-228L	55	10-265	56
0304-C-3	404	10011665	211	10-064	52	10-118LF	163	10-228LF	163	10-265L	56
0304-C-32	404	1001205	211	10-065	52	10-119	54	10-229	55	10-265LF	163
0304-C-4	404	10012065	211	10-066	52	10-120	54	10-229L	55	10-266	56
0304-C-5	404	1001245	211	10-067	52	10-121	54	10-229LF	163	10-266LF	163
0304-C-6	404	10012465	211	10-068	52	10-121LF	163	10-230	55	10-267	56
0304-C-8	404	10-013	50	10-069	52	10-122	54	10-230LF	163	10-267LF	163
0306-10	407	10-013	88	10-073	52	10-123	54	10-231	55	10-268	56
0306-12	407	10-013LF	163	10-074	52	10-123LF	163	10-232	55	10-268L	56
0306-14	407	10-014	50	10-075	52	10-126	54	10-233	55	10-268LF	163
0306-16	407	100145	211	10-075EH	52	10-127	54	10-234	55	10-269	56
0306-2	407	1001465	211	10-075LF	163	10-131	53	10-235	55	10-269L	56
0306-20	407	10-014LF	163	10-076	52	10-132	53	10-235L	55	10-269LF	163
0306-4	407	10-015	50	10-077	52	10-133	53	10-235LF	163	10-270	56
0306-5	407	10-015L	50	10-077LF	163	10-135	60	10-236	55	10-270LF	163
0306-6	407	10-015LF	163	10-078	52	10-136	60	10-236L	55	10-271	56
0306-8	407	10-016	50	10-078LF	163	10-137	60	10-236LF	163	10-272	56
0318-10	404	100165	211	10-079	52	10-138	60	10-237	55	10-272L	56
0318-12	404	1001665	211	10-079LF	163	10-139	60	10-237L	55	10-272LF	163
0318-14	404	10-016LF	163	10-080	52	10-157	54	10-237LF	163	10-273	56
0318-16	404	10-017	50	10-080LF	163	10-158	54	10-238	55	10-273L	56
0318-2	404	10-017L	50	10-081	52	10-159	54	10-239	55	10-273LF	163
0318-20	404	10-017LF	163	10-082	52	10-159LF	164	10-240	55	10-274	56
0318-24	404	10-018	50	10-084	52	10-160	54	10-240L	55	10-274LF	163
0318-3	404	100185	211	10-085	52	10-161	54	10-240LF	163	10-275	56
0318-32	404	1001865	211	10-086	52	10-161LF	164	10-241	55	10-275LF	163
0318-4	404	10-018LF	163	10-087	52	10-162	54	10-241L	55	10-276	56
0318-5	404	10-019	50	10-088	52	10-163	54	10-241LF	163	10-276LF	163
0318-6	404	10-019L	50	10-089	52	10-164	54	10-242	55	10-277	56
0318-8	404	10-019LF	163	10-090	52	10-165	54	10-242L	55	10-278	56
0319-10	404	10-020	50	10-094	53	10-170	54	10-242LF	163	10-278LF	163
0319-12	404	10-020L	50	10-095	53	10-171	54	10-243	55	10-279	56
0319-14	404	10-020LF	163	10-097	53	10-172	54	10-244	55	10-280	56
0319-16	404	10-021	50	10-098	53	10-173	54	10-244L	55	10-283	57
0319-2	404	10-021LF	163	10-099	53	10-174	54	10-244LF	163	10-283B	57
0319-20	404	10-022	50	10-100	53	10-175	54	10-245	55	10-284	57
0319-24	404	10-023	50	1010002	328	10-176	54	10-245LF	163	10-284B	57
0319-3	404	10-024	50	1010008	328	10-178	54	10-246	55	10-285	57
0319-32	404	10-025	50	1010011	328	10-179	54	10-247	55	10-286	57
0319-4	404	10-026	50	1010016	328	10-180	54	10-247LF	163	10-286B	57
0319-5	404	10-028	51	1010019	328	10-181	54	10-248	55	10-286L	57
0319-6	404	10-030	51	1010022	328	10-182	54	10-253	56	10-286LF	164
0319-8	404	10-031	51	1010024	328	10-187	54	10-254	56	10-287	57
10-001	50	10-032	51	1010027	328	10-188	54	10-255	56	10-287B	57
1000105	211	10-033	51	10-104	53	10-189	54	10-255EH	56	10-287LF	164
10001065	211	10-038	51	10-104LF	163	10-197	54	10-255L	56	10-288	57
1000125	211	10-039	51	10-105	53	10-203	55	10-255LF	163	10-288LF	164
10001265	211	10-039LF	163	10-105LF	163	10-204	55	10-256	56	10-289	57
10-002	50	10-040	51	10-106	53	10-204LF	163	10-256L	56	10-290	57
100025	211	10-041	51	10-106EH	53	10-205	55	10-256LF	163	10-290B	57
1000265	211	10-041LF	163	10-106L	53	10-206	55	10256WC	53	10-291	57
10-003	50	10-042	51	10-106LF	163	10-207	55	10-257	56	10-291B	57
100035	211	10-042LF	163	10-107	53	10-208	55	10-257LF	163	10-292	57
1000365	211	10-043	51	10-107LF	163	10-209	55	10-258	56	10-293	57
10-003L	50	10-044	51	10-108	53	10-210	55	10-258LF	163	10-293B	57
10-004	50	10-045	51	10-108L	53	10-211	55	10-259	56	10-293LF	164

Part#	Page
10-294	57
10-294B	57
10-294LF	164
10-295	57
10-295B	57
10-295L	57
10-295LF	164
10-296	57
10-296LF	164
10-297	57
10-298	57
10-298B	57
10-299	57
10-299B	57
10-299LF	164
10-300	57
10-300B	57
10-300LF	164
10-301	57
10-301LF	164
10-302	57
10-302B	57
10-303	57
10-303B	57
10-303L	57
10-304	57
10-305	57
10-305LF	164
10-306	57
10-306B	57
10-306B	58
10-306LF	164
10-307	57
10-308	57
10-309	57
10-311	57
10-312	58
10-313	58
10-313B	58
10-314	58
10-314B	58
10-315	58
10-316	58
10-317	58
10-318	58
10-319	58
10-319B	58
10-320	58
10-320B	58
10-321	58
10-321L	58
10-322	58
10-323	58
10-324	58
10-324B	58
10-325	58
10-325L	58
10-326	58
10-327	58
10-328	58
10-329	58
10-330	58
10-331	58
10-333	58
10-340	58
10-343	58
10-344	58
10-344B	58
10-345	58
10-347	58
10-348	58
10-350	58
10-351	58
10-351LF	164
10-352	58
10-353	58
10-354	58
10-355	58
10-355LF	164
10-357	58
10-359	58
10-359LF	164
10-360	58
10-361	58
10-373	59
10-374	59
10-375	59
10-376	59
10-382	59
10-383	59
10-404	59
10-405	59
10-406	59
10-406B	59
10-407	59
10-408	59
10-409	59
10-409B	59
10-410	59
10-411	59
10-412	59
10-416	59
10-419	59
10-421	59
10-440	60
10-441	60
10-442	60
10-443	60
10-444	60
10-448	60
10-448B	60
10-449	60
10-450	60
10-451	60
10-452	60
10-452B	60
10-453	60
10-454	60
10-455	60
10-455B	60
10-456	60
10-457	60
10-458	60
10-459	60
10-460	60
10-461	60
10-462	60
10-463	60
10-464	60
10-467	60
10-468	60
10-469	60
10-470	60
10-471	60
10-473	60
10-481	61
10-481LF	164
10-482	61
10-483	61
10-483L	61
10-483LF	164
10-484	61
10-484L	61
10-484LF	164
10-485	61
10-485LF	164
10-486	61
10-487	61
10-487LF	164
10-488	61
10-488LF	164
10-489	61
10-493	61
10-494	61
10-495	61
10-496	61
10-497	61
1050000	327
1050001	327
1050002	327
1050003	327
1050006	327
1050007	327
1050008	327
1050009	327
1050010	327
1050011	327
1050012	327
1050013	327
1050014	327
1050015	327
1050016	327
1050017	327
1050018	327
1050020	327
1050021	327
1050023	327
1050025	327
1050026	327
1050029	327
1050030	327
1050032	327
1050033	327
10-600	61
10-602	61
10-611	61
10-612	61
10-613	61
10-614	61
10-615	61
10-616	61
10-617	61
10-618	61
10-619	61
10-620	61
10-621	61
10-622	61
107-000	286
107-001	286
107-002	286
107-003	286
107-004	286
107-005	286
107-006	286
107-007	286
107-009	286
107-011	286
107-012	286
107-013	286
107-014	286
107-020	285
107-021	285
107-022	285
107-023	285
107-024	285
107-025	285
107-026	285
107-027	285
107-029	285
107-031	285
107-032	285
107-033	285
107-034	285
107-040	286
107-041	286
107-042	286
107-043	286
107-044	286
107-045	286
107-046	286
107-047	286
107-049	286
107-051	286
107-052	286
107-053	286
107-054	286
107-060	285
107-061	285
107-062	285
107-063	285
107-064	285
107-065	285
107-066	285
107-067	285
107-069	285
107-071	285
107-072	285
107-073	285
107-074	285
12-000	69
12-001	69
12-002	69
12-003	69
12-004	69
12-005	69
12-006	69
12-007	69
12-008	69
12-009	69
12-010	69
12-011	69
12-012	69
12-013	69
12-014	69
12-015	69
12-016	69
12-017	69
12-018	69
12-022	70
12-023	70
12-024	70
12-025	70
12-026	70
12-027	70
12-028	70
12-029	70
12-030	70
12-031	70
12-032	70
12-033	70
12-034	70
12-035	70
12-036	70
12-037	70
12-038	70
12-039	70
12-040	70
12-041	70
12-042	70
12-043	70
12-044	70
12-045	70
12-046	70
12-047	70
12-048	70
12-049	70
12-050	70
12-051	70
12-052	70
12-053	70
12-054	71
12-055	70
12-056	71
12-057	71
12-058	71
12-059	71
12-060	71
12-061	71
12-062	71
12-063	71
12-064	71
12-065	71
12-066	71
12-067	71
12-068	71
12-069	71
12-070	71
12-072	71
12-073	71
12-074	71
12-075	71
12-076	71
12-077	71
12-079	71
12-080	71
12-081	71
12-082	71
12-083	69
12-084	69
12-085	71
12-086	71
12-087	71
12-088	71
12-089	71
12-090	71
12-091	72
12-092	72
12-093	72
12-094	72
12-095	72
12-096	72
12-097	72
12-098	72
12-099	70
12-100	72
12-101	72
12-102	72
12-103	72
12-104	70
12-105	70
12-107	70
12-108	70
12-110	72
12-111	72
12-112	72
12-114	71
12-115	71
12-118	72
12-119	72
12-120	72
12-121	72
12-127	73
12-129	73
12-130	73
12-144	73
12-145	73
12-146	73
12-147	73
12-148	73
12-149	73
12-150	73
12-151	73
12-200	73
12-202	73
12-205	75
12-206	74
12-207	74
12-208	74
12-209	74
12-210	74
12-211	74
12-212	74
12-213	74
12-214	74
12-215	74
12-216	74
12-217	74
12-218	74
12-220	74
12-221	74
12-222	74
12-224	74
12-230	74
12-250	75
12-252	75
12-254	75
12-256	75
12-257	75
12-260	69
12-261	69
12-262	69
12-263	69
12-264	69
12-265	69
12-266	69
12-267	69
12-268	69
12-269	69

Part#	Page
12-270	69
12-271	69
12-272	69
12-273	69
12-274	69
12-275	69
12-310	74
12-326	75
12-327	75
12-328	75
12-329	75
12-330	75
12-335	75
12-336	75
12-337	75
12-339	75
12-341	75
12-342	75
12-343	75
12-344	75
12-345	75
14-001	62
14-011	62
14-016	62
14-017	62
14-018	62
14-025	62
1404-12-12	402
1404-12-16	402
1404-12-8	402
1404-16-12	402
1404-16-16	402
1404-20-16	402
1404-20-20	402
1404-2-2	402
1404-24-24	402
1404-32-32	402
1404-4-2	402
1404-4-4	402
1404-6-6	402
1404-6-8	402
1404-8-4	402
1404-8-6	402
1404-8-8	402
1405-12-12	402
1405-16-12	402
1405-16-16	402
1405-20-20	402
1405-2-2	402
1405-24-24	402
1405-32-32	402
1405-4-4	402
1405-6-4	402
1405-6-6	402
1405-6-8	402
1405-8-4	402
1405-8-8	402
1410083	331
1410118	331
1501-12-12	402
1501-12-8	402
1501-16-12	402
1501-16-16	402
1501-20-20	402
1501-2-2	402
1501-32-32	402
1501-4-2	402
1501-4-4	402
1501-6-4	402
1501-6-6	402
1501-8-6	402
1501-8-8	402
1502-12-12	402
1502-16-16	402
1502-20-20	402
1502-2-2	402
1502-24-24	402
1502-4-4	402
1502-6-4	402
1502-6-6	402
1502-6-8	402
1502-8-6	402
1502-8-8	402
1503-12-12	403
1503-12-8	403
1503-16-12	403
1503-16-16	403
1503-2-2	403
1503-4-4	403
1503-6-4	403
1503-6-6	403
1503-8-6	403
1503-8-8	403
1504-12-12	403
1504-16-16	403
1504-2-2	403
1504-4-4	403
1504-6-6	403
1504-8-8	403
1510003	328
1510004	328
1510006	328
1510007	328
1510008	328
1510009	328
1510010	328
1510011	328
1510012	328
1510013	328
1510014	328
1510016	328
1510019	328
1510020	328
1510023	328
16-001	86
16-002	86
16-003	86
16-004	86
16-005	86
16-006	86
16-007	86
16-009	86
16-010	86
16-011	86
16-012	86
16-013	86
1601-12-12	403
1601-16-16	403
1601-2-2	403
1601-4-4	403
1601-6-6	403
1601-8-8	403
1602-12-12	403
1602-16-16	403
1602-4-4	403
1602-6-6	403
1602-8-8	403
1603-12-12	403
1603-16-16	403
1603-4-4	403
1603-6-6	403
1603-8-8	403
16-090	86
16-117	86
16-118	86
16-119	86
16-120	86
16-121	86
16-122	86
16-123	86
16-125	86
16-127	86
16-128	86
16-129	86
16-130	86
16-131	86
16-133	86
16700001	328
16700004	328
16700007	328
16700010	328
16700012	328
16700013	328
16700016	328
16700017	328
16700022	328
16700024	328
17-064N	302
17-064P	302
17-065N	302
17-066N	302
17-066P	302
17-068N	302
17-068P	302
17-078N	302
17-079N	302
17-079P	302
17-081P	302
17-088N	302
17-090N	302
17-091N	302
17-103N	302
17-105N	302
17-106N	302
17-124N	302
17-124P	302
17-126N	302
17-126P	302
17-127P	302
17-145P	302
17-146N	302
17-153N	302
17-153P	302
17-154N	302
17-154P	302
17-158P	302
17-159P	302
17-176N	302
17-179N	302
17-179P	302
17-180N	302
17-180P	302
17-188N	302
17-188P	302
17-189N	302
17-189P	302
17-190N	302
17-190P	302
17-193N	302
17-193P	302
17-194N	302
17-194P	302
17-195N	302
17-195P	302
17-224N	302
17-225N	302
17-225P	302
17-233N	302
17-233P	302
17-234N	302
17-234P	302
17-237N	302
17-237P	302
17-238N	302
17-238P	302
18-001	77
18-002	77
18-002LF	164
18-003	77
18-003LF	164
18-004	77
18-004LF	164
18-005	77
18-005LF	164
18-006	77
18-007	77
18-007LF	164
18-008	77
18-008LF	164
18-009	77
18-009LF	164
18-010	77
18-010LF	164
18-011	77
18-015	88
18-015	164
18-016	88
18-016	164
18-017	88
18-017	164
18-018	88
18-018	164
18-019	88
18-019	164
18-020	88
18-028	84
18-029	84
18-030	84
18-031	84
18-032	84
18-033	77
18-034	77
18-035	77
18-035L	77
18-035LF	164
18-036	77
18-037	77
18-037L	77
18-037LF	164
18-038	77
18-039	77
18-039L	77
18-039LF	164
18-040	77
18-040L	77
18-040LF	164
18-041	77
18-042	77
18-043	77
18-047	84
18-047LF	165
18-048	84
18-048LF	165
18-049	84
18-049LF	165
18-050	84
18-050LF	165
18-062	77
18-062LF	165
18-063	77
18-063LF	165
18-064	77
18-064L	77
18-064LF	165
18-065	77
18-065LF	165
18-066	77
18-066L	77
18-066LF	165
18-067	77
18-067LF	165
18-068	77
18-068L	77
18-068LF	165
18-069	77
18-069L	77
18-069LF	165
18-070	77
18-070LF	165
18-071	77
18-071L	77
18-071LF	165
18-072	77
18-076	78
18-076LF	165
18-077	78
18-077LF	165
18-078	78
18-078LF	165
18-079	78
18-079LF	165
18-080	78
18-080LF	165
18-081	78
18-081LF	165
18-082	78
18-082LF	165
18-083	78
18-083LF	165
18-084	78
18-085	78
18-086	78
18-087	85
18-088	85
18-089	85
18-090	85
18-091	85
18-092	85
18-093	85
18-094	85
18-096	85
18-101	78
18-101B	78
18-101LF	165
18-102	78
18-102B	78
18-102LF	165
18-103	78
18-103B	78
18-103LF	165
18-104	78
18-104B	78
18-104LF	165
18-105	78
18-105B	78
18-105LF	165
18-106	78
18-106B	78
18-106LF	165
18-107	78
18-107LF	165
18-108	78
18-109	78
18-109LF	165
18-110	78
18-111	78
18-114	78
18-115	78
18-115LF	165
18-116	78
18-117	78
18-117LF	165
18-118	78
18-119	78
18-122B	79
18-123	79
18-124	79
18-124LF	165
18-125	79
18-125LF	165
18-126	79
18-126LF	165
18-127	79
18-127LF	165
18-128	79
18-128LF	165
18-129	79
18-129LF	165
18-130	79
18-130LF	165
18-135	79
18-135LF	165
18-136	79
18-136LF	165
18-137	79
18-137LF	165
18-142	79
18-142LF	166
18-143	79
18-143LF	166
18-144	79
18-145	79
18-145L	79
18-145LF	166
18-146	79
18-146L	79
18-146LF	166
18-147LF	166

Part#	Page
18-148	79
18-148LF	166
18-149	79
18-150	79
18-150LF	166
18-151LF	166
18-152	79
18-152LF	166
18-153	79
18-153L	79
18-153LF	166
18-154	79
18-154L	79
18-154LF	166
18-155	79
18-155LF	166
18-156	79
18-156LF	166
18-157	79
18-158	79
18-158L	79
18-158LF	166
18-159	79
18-159L	79
18-159LF	166
18-160	79
18-160LF	166
18-161LF	166
18-162	79
18-162L	79
18-162LF	166
18-163	79
18-163LF	166
18-164	79
18-165	79
18-165LF	166
18-166	79
18-166LF	166
18-167	79
18-167LF	166
18-171LF	165
18-175	80
18-176	80
18-176LF	166
18-177	80
18-177LF	166
18-178	80
18-178LF	166
18-179	80
18-179L	80
18-179LF	166
18-180	80
18-180L	80
18-180LF	166
18-181	80
18-181LF	166
18-182	80
18-182LF	166
18-183	80
18-183LF	166
18-184	80
18-184L	80
18-184LF	166
18-185	80
18-186	80
18-187	80
18-187L	80
18-187LF	166
18-188	80
18-188L	80
18-188LF	166
18-189	80
18-189L	80
18-189LF	166
18-190	80
18-190L	80
18-190LF	166
18-191	80
18-191LF	166
18-192	80
18-192LF	166
18-193	80
18-193L	80
18-193LF	166
18-194	80
18-194L	80
18-194LF	166
18-195	80
18-195L	80
18-195LF	166
18-196	80
18-196LF	166
18-197	80
18-197LF	166
18-198	80
18-198LF	166
18-199	80
18-199LF	166
18-200	80
18-200LF	166
18-201	80
18-201LF	166
18-202	80
18-202LF	166
18-203	80
18-203LF	166
18-204	80
18-205	80
18-206	80
18-207	80
18-208	85
18-209	85
18-210	85
18-211	85
18-212	85
18-213	85
18-214	85
18-215	85
18-216	80
18-219	81
18-220	81
18-220B	81
18-220LF	166
18-221	81
18-221B	81
18-221LF	166
18-223	81
18-223B	81
18-224	81
18-224B	81
18-224BLF	166
18-225	81
18-225B	81
18-225BLF	166
18-226	81
18-226BLF	166
18-227	81
18-227LF	166
18-228	81
18-228B	81
18-228LF	166
18-229	81
18-229B	81
18-229LF	166
18-230	81
18-231	81
18-232	81
18-232B	81
18-232BLF	166
18-233	81
18-233B	81
18-233BLF	166
18-234	81
18-234B	81
18-234BLF	166
18-235	81
18-235B	81
18-235BLF	166
18-236	81
18-236B	81
18-236LF	166
18-237	81
18-237B	81
18-237BLF	166
18-238	81
18-238B	81
18-238BLF	166
18-239	81
18-239LF	166
18-240	81
18-240LF	166
18-241	81
18-241B	81
18-241BLF	166
18-242	81
18-242BLF	166
18-243	81
18-245	81
18-246	81
18-246LF	166
18-247	81
18-248	81
18-248B	81
18-250	82
18-251	82
18-251B	82
18-252	82
18-252B	82
18-253	82
18-253B	82
18-253LF	166
18-254	82
18-254B	82
18-254LF	166
18-255	82
18-256	82
18-257	82
18-258	82
18-258BLF	166
18-259	82
18-259BLF	166
18-260	82
18-260LF	166
18-261	82
18-262	82
18-262BLF	166
18-263	82
18-263LF	166
18-264	82
18-264BLF	166
18-265	82
18-266	82
18-267	82
18-267LF	166
18-268	82
18-269	82
18-269BLF	166
18-270	82
18-272	82
18-273	82
18-273B	82
18-274	82
18-274B	82
18-275	82
18-276	82
18-277	82
18-278	82
18-279	82
18-280	82
18-281	82
18-282	82
18-283	82
18-284	82
18-290	83
18-291	83
18-291B	83
18-292	83
18-293	83
18-294	83
18-295	83
18-296	83
18-297	83
18-298	83
18-299	83
18-299B	83
18-300	83
18-301	83
18-302	83
18-303	83
18-304	83
18-307	83
18-314	83
18-316	83
18-321	84
18-322	84
18-323	84
18-324	84
18-325	84
18-326	84
18-327	84
18-328	84
18-329	84
18-330	84
18-331	84
18-332	84
18-333	84
18-334	84
18-335	84
18-336	84
18-338	84
18-339	84
18-534	21
20-001C	112
20-009	101
20-010	101
20-011	101
20-012	97
20-013	101
20-015C	112
20-015N	103
20-016C	112
20-016N	103
20-017	97
20-017C	112
20-017N	103
20-018	97
20-018C	112
20-018N	103
20-018P	303
20-019	97
20-019C	112
20-019N	103
20-019P	303
20-020	97
20-020C	112
20-020N	103
20-020P	303
20-021	97
20-021C	112
20-021N	103
20-021P	303
20-022	97
20-022C	112
20-022N	103
20-023	98
20-023N	104
20-024C	112
20-024N	103
20-025	97
20-025C	112
20-025N	103
20-026	97
20-026C	112
20-026N	103
20-027	97
20-027C	112
20-028	97
20-028C	112
20-028N	103
20-028P	303
20-029	97
20-029C	112
20-029N	103
20-029P	303
20-030	97
20-030C	112
20-030N	103
20-030P	303
20-031	97
20-031C	112
20-031N	103
20-032	97
20-032N	103
20-034	97
20-034C	112
20-034N	103
20-035	97
20-035C	112
20-035N	103
20-035P	303
20-036	97
20-036C	112
20-036N	103
20-036P	303
20-037	97
20-037C	112
20-037N	103
20-038	97
20-038N	103
20-039	98
20-045	98
20-046	98
20-046N	104
20-047	98
20-047N	104
20-048	98
20-048N	104
20-049	98
20-049C	113
20-049N	104
20-050	98
20-050C	113
20-050N	104
20-050P	304
20-051	98
20-052	98
20-053	98
20-053C	113
20-053N	104
20-054	98
20-054C	113
20-054N	104
20-054P	304
20-055	98
20-055C	113
20-055N	104
20-055P	304
20-056	98
20-056C	113
20-056N	104
20-056P	304
20-057	98
20-057C	113
20-057N	104
20-057P	304
20-058	98
20-058C	113
20-058N	104
20-058P	304
20-059	98
20-059C	113
20-059N	104
20-059P	304
20-060	98
20-060C	113
20-060N	104
20-061	98
20-061C	113
20-061N	104
20-061P	304
20-062	98
20-062C	113
20-062N	104
20-062P	304
20-063	98
20-063C	113
20-063N	104
20-063P	304

Part#	Page
20-064	99
20-065	99
20-066	99
20-067	99
20-068	99
20-068N	104
20-068P	304
20-069	99
20-069N	104
20-069P	304
20-070	99
20-070P	304
20-071	99
20-072	99
20-072N	104
20-072P	304
20-073	99
20-073N	104
20-073P	304
20-074	99
20-075	99
20-076	98
20-076N	105
20-077	98
20-077C	113
20-078	98
20-078C	113
20-079	98
20-079C	113
20-079N	105
20-080	98
20-080C	113
20-080N	105
20-081	98
20-081C	113
20-081N	105
20-082	98
20-082C	113
20-082N	105
20-083	98
20-083C	113
20-083N	105
20-084	98
20-084C	113
20-084N	105
20-085	98
20-085C	113
20-085N	105
20-086	98
20-086C	113
20-086N	105
20-087	98
20-087C	113
20-087N	105
20-088	98
20-088C	113
20-088N	105
20-089	99
20-089C	114
20-089N	105
20-089S	99
20-090	99
20-090C	114
20-090N	105
20-090S	99
20-091	99
20-091C	114
20-091N	105
20-091S	99
20-092	98
20-092C	113
20-092N	105
20-093	100
20-094	99
20-094N	105
20-094S	99
20-095	100
20-095N	105
20-097	100
20-098	100
20-099	100
20-099C	114
20-100	100
20-100C	114
20-101	100
20-102	100
20-103	100
20-103C	114
20-103N	106
20-104	100
20-104C	114
20-104N	106
20-105	100
20-105C	114
20-105N	106
20-106	100
20-106C	114
20-106N	106
20-107	100
20-107C	114
20-107N	106
20-108	100
20-108C	114
20-108N	106
20-109	100
20-109C	114
20-109N	106
20-110	100
20-110C	114
20-110N	106
20-111	100
20-111C	114
20-111N	106
20-112	100
20-112N	106
20-113	100
20-115	100
20-116	100
20-117	100
20-118	100
20-119	100
20-120	100
20-121C	114
20-123N	106
20-124	101
20-124N	106
20-125	101
20-125N	106
20-126	101
20-127	101
20-127C	115
20-127N	106
20-127P	303
20-128	101
20-128C	115
20-128N	106
20-128P	303
20-129	101
20-129C	115
20-129N	106
20-129P	303
20-135C	114
20-136C	114
20-137C	114
20-138C	114
20-139C	114
20-140C	114
20-142	101
20-143	101
20-149C	112
20-150	97
20-150C	112
20-150N	103
20-151	97
20-151C	112
20-151N	103
20-152	97
20-152C	112
20-152N	103
20-152P	303
20-153	97
20-153C	112
20-153N	103
20-153P	303
20-154	97
20-154C	112
20-154N	103
20-154P	303
20-155	97
20-155C	112
20-155N	103
20-156N	106
20-157N	106
20-158C	114
20-158N	106
20-159N	105
20-160	100
20-160C	114
20-161	100
20-162	100
20-162C	114
20-162N	105
20-163	100
20-163C	114
20-163N	105
20-164	100
20-164N	105
20-165	100
20-165C	114
20-165N	105
20-166	100
20-166C	114
20-166N	105
20-167	100
20-167C	114
20-167N	105
20-168N	105
20-170	101
20-170C	115
20-171	101
20-171C	115
20-172	101
20-172C	115
20-173C	115
20-174	100
20-174C	114
20-174N	105
20-175C	115
20-176C	115
20-179C	115
20-181C	114
20-181N	105
20-182C	112
20-184C	113
20-184N	105
20-185C	112
20-187C	115
20-188C	115
20-189C	115
20-192	99
20-193C	115
20-194C	115
20-195C	115
20-200	91
20-201	94
20-203	94
20-204	94
20-205	94
20-206	94
20-206N	108
20-207	94
20-208	94
20-211	91
20-212	91
20-213	91
20-214	91
20-218	94
20-219	94
20-220	94
20-221	94
20-222	94
20-223	94
20-227	94
20-228	94
20-229	94
20-230	94
20-231	94
20-232	94
20-235	91
20-237	91
20-240	91
20-241	91
20-242	91
20-243	91
20-244	91
20-245	91
20-248	92
20-249	92
20-250	92
20-251	92
20-252	92
20-253	92
20-256	92
20-257	92
20-259	92
20-260	92
20-261	92
20-262	92
20-263	92
20-265	92
20-268	92
20-269	92
20-270	92
20-271	92
20-272	92
20-273	92
20-274	92
20-275	92
20-276	92
20-277	92
20-278	92
20-279	92
20-282	92
20-287	92
20-288	92
20-289	92
20-290	92
20-291	92
20-292	92
20-293	92
20-294	92
20-295	92
20-296	92
20-300	93
20-301	93
20-302	93
20-303	93
20-304	93
20-305	93
20-308	93
20-309	93
20-310	93
20-311	93
20-312	93
20-313	93
20-314	93
20-317	93
20-318	93
20-319	93
20-320	93
20-321	93
20-322	93
20-323	93
20-324	93
20-327	93
20-328	93
20-330	92
20-333	91
20-334	91
20-337	91
20-338	91
20-339	91
20-487C	115
20-488C	115
20-489C	115
20-510	101
20-510N	106
20-511	101
20-511N	106
20-512	101
20-512N	106
20-512P	304
20-513N	106
20-514N	106
20-514P	304
20-515C	112
20-516C	112
20-517C	113
20-518C	113
20-519C	114
20-524P	304
20-525P	304
20-528P	304
20-529P	304
20-530	98
20-530C	113
20-530N	104
20-531	98
20-531C	113
20-531N	104
20-532	98
20-532N	104
20-535	98
20-535C	113
20-535N	105
20-537C	113
20-537N	105
20-538	98
20-538C	113
20-538N	105
20-539	98
20-539C	113
20-539N	105
20-551	101
20-551C	112
20-552	101
20-553	101
20-553C	112
20-553N	106
20-555C	112
20-557C	115
20-572C	113
20-573C	113
20-574C	113
20-579C	113
20-580C	113
20-581C	113
20-582C	113
20-583C	113
20-584C	113
20-591C	114
20-595C	114
20-596C	114
20-597C	114
20-598C	114
20-600	116
20-600N	108
20-601	116
20-601N	108
20-602	116
20-603	116
20-603N	108
20-604	116
20-604N	108
20-610	116
20-610N	108
20-611	116
20-611N	108
20-612	116
20-612N	108
20-613	116
20-613N	108
20-614	116
20-614N	108
20-619N	109
20-620N	109
20-621N	109
20-622N	109

Part#	Page
20-623N	109
20-624N	109
20-625N	109
20-626N	109
20-627N	109
20-628N	109
20-629N	109
20-630	116
20-630N	109
20-631	116
20-631N	109
20-632	116
20-632N	109
20-633	116
20-633N	109
20-634	116
20-634N	109
20-635	116
20-635N	109
20-636	116
20-636N	109
20-637	116
20-637N	109
20-638	116
20-638N	109
20-642	117
20-642N	109
20-655	117
20-655N	109
20-656	117
20-656N	109
20-657	117
20-657N	109
20-658	117
20-658N	109
20-659	117
20-659N	109
20-660	116
20-660N	108
20-661	116
20-661N	108
20-668N	110
20-669N	110
20-670	117
20-670N	110
20-672	117
20-672N	110
20-673	117
20-673N	110
20-674	117
20-674N	110
20-675	117
20-676	117
20-676N	110
20-677	117
20-677N	110
20-678	117
20-678N	110
20-679	117
20-679N	110
20-680	117
20-680N	110
20-682	117
20-682N	110
20-683	117
20-683N	110
20-684	117
20-684N	110
20-685	117
20-686	117
20-686N	110
20-687	117
20-687N	110
20-688	117
20-688N	110
20-689	117
20-689N	110
20-690	117
20-690N	110
20-691N	110
20-692	117
20-698	117
20-699	117
20-700N	109
20-701N	109
20-702N	109
20-702P	303
20-703N	109
20-704N	109
20-705N	109
20-706N	109
20-707N	109
20-708N	109
20-709N	109
20-710N	109
20-711	117
20-711N	109
20-712	117
20-712N	109
20-713	117
20-713N	109
20-714	117
20-714N	109
20-715N	109
20-716N	110
20-717	117
20-717N	110
20-718	117
20-718N	110
20-719	117
20-719N	110
20-720	117
20-720N	110
20-721	117
20-721N	110
20-722N	110
20-723N	108
20-724N	108
20-724P	303
20-725N	108
20-725P	303
20-726N	108
20-727C	115
20-727N	108
20-728C	115
20-728N	108
20-729N	108
20-730N	108
20-731N	110
20-732N	110
20-733N	110
20-733P	303
20-734N	110
20-734P	303
20-735N	110
20-736N	110
20-736P	303
20-737N	110
20-738N	108
20-739N	108
20-740	116
20-740N	108
20-740P	304
20-741N	108
20-742N	108
20-742P	304
20-743N	108
20-744N	108
20-745N	108
20-745P	304
20-746	118
20-746N	108
20-747P	304
20-748N	108
20-748P	304
20-749N	108
20-750N	108
20-750P	303
20-751N	108
20-752N	108
20-753N	108
20-754P	303
20-755P	303
20-756P	303
20-758P	303
20-762N	105
20-763P	304
20-776P	304
20-777P	304
20-779P	304
20-780	360
20-780C	115
20-781C	115
20-782C	115
20-785C	115
20-786C	115
20-787C	115
20-788C	115
20-789C	115
20-801	116
20-801	117
20-801N	109
20-803	117
20-803N	109
20-805	117
20-805N	109
20-806	116
20-807	116
20-807N	108
20-808	116
20-808N	108
20-809	117
20-809N	110
20-810	117
20-810N	110
20-811	117
20-811N	110
20-813	118
20-813N	108
20-814	118
20-814N	108
20-815	118
20-815N	108
20-816	118
20-817	118
20-818	118
20-819	118
20-820	118
20-821	118
20-822	118
20-823	118
20-824	118
20-825	118
20-826	118
20-827	118
20-827	118
20-830C	114
20-831C	114
20-832C	114
20-833C	114
20-834C	114
20-835C	114
20-841N	104
20-842N	104
20-843N	104
20-844N	104
20-845N	104
20-846N	104
20-847N	104
20-848N	105
20-850N	106
20-851N	105
20-852N	105
20-853N	105
20-854	117
20-855	117
20-856	117
20-857	117
20-859	117
20-860	117
20-861	116
20-862	116
20-876P	304
20-878P	304
20-880P	304
20-881P	304
20-900P	304
20-901P	304
20-904P	304
20-905P	304
20-925P	304
20-927P	304
20-944P	303
20-993P	303
21-003	26
21-007	26
21-009	26
21-021	26
21-023	26
21-025	26
21-027	26
21-043	26
21-046	26
21-049	26
21-082	26
21-083	26
21-084	26
21-095	26
21-097	26
21-099	26
21-109	26
21-111	26
21-113	26
21-115	26
21-117	26
21-119	26
21-121	26
21-133	26
21-151	26
21-153	26
21-155	26
21-159	26
21-161	26
21-174	278
21-175	278
21-176	278
21-177	278
21-178	278
21-179	278
21-180	278
21-193	26
21-195	26
21-197	26
21-207	26
22-008	88
22-008A	88
22-009	88
22-009A	88
22-010	88
22-010A	88
22-010B	88
22-010LF	164
22-011	88
22-011A	88
22-011LF	164
22-012	88
22-012LF	164
22-013	88
22-013LF	164
22-014	88
22-014LF	164
22-015	88
24-002	88
24-003	88
24-004	88
24-005	88
24-006	88
24-007	88
24-008	88
2403-10-10	404
2403-10-8	404
2403-12-10	404
2403-12-12	404
2403-12-8	404
2403-14-14	404
2403-16-12	404
2403-16-16	404
2403-20-20	404
2403-2-2	404
2403-24	404
2403-32	404
2403-3-3	404
2403-4-4	404
2403-5-5	404
2403-6-4	404
2403-6-6	404
2403-8-6	404
2403-8-8	404
2404-10-12	405
2404-10-8	405
2404-12-12	405
2404-12-16	405
2404-12-6	405
2404-12-8	405
2404-16-12	405
2404-16-16	405
2404-20-16	405
2404-20-20	405
2404-2-2	405
2404-24-16	405
2404-24-20	405
2404-24-24	405
2404-32-24	405
2404-32-32	405
2404-4-2	405
2404-4-4	405
2404-4-6	405
2404-4-8	405
2404-6-2	405
2404-6-4	405
2404-6-6	405
2404-6-8	405
2404-8-12	405
2404-8-16	405
2404-8-4	405
2404-8-6	405
2404-8-8	405
2405-10-6	405
2405-10-8	405
2405-12-12	405
2405-12-8	405
2405-16-12	405
2405-16-16	405
2405-20-20	405
2405-2-2	405
2405-24-24	405
2405-3-2	405
2405-32-32	405
2405-4-2	405
2405-4-4	405
2405-6-4	405
2405-6-6	405
2405-8-4	405
2405-8-6	405
2405-8-8	405
2406-10-4	405
2406-10-6	405
2406-10-8	405
2406-12-10	405
2406-12-4	405
2406-12-6	405
2406-12-8	405
2406-16-12	405
2406-16-20	405
2406-16-4	405
2406-20-12	405
2406-20-16	405
2406-24-16	405
2406-32-24	405
2406-6-4	405
2406-6-8	405
2406-8-12	405
2406-8-4	405
2406-8-6	405
2408-10	406
2408-12	406
2408-14	406
2408-16	406

Part#	Page
2408-2	406
2408-20	406
2408-24	406
2408-3	406
2408-32	406
2408-4	406
2408-5	406
2408-6	406
2408-8	406
25-001	87
2500-10-10	406
2500-12-12	406
2500-16-16	406
25-002	87
2500-20-20	406
2500-2-2	406
2500-24-24	406
25-003	87
2500-32-32	406
2500-4-4	406
2500-5-5	406
2500-6-4	406
2500-6-6	406
2500-8-6	406
2500-8-8	406
2501-10-6	406
2501-10-8	406
2501-12-12	406
2501-12-16	406
2501-12-8	406
2501-16-12	406
2501-16-16	406
2501-16-20	406
2501-20-20	406
2501-24-24	406
2501-32-32	406
2501-4-2	406
2501-4-4	406
2501-4-8	406
2501-6-2	406
2501-6-4	406
2501-6-6	406
2501-6-8	406
2501-8-12	406
2501-8-4	406
2501-8-6	406
2501-8-8	406
2502-12-12	406
2502-16-16	406
2502-20-20	406
2502-4-2	406
2502-4-4	406
2502-6-4	406
2502-6-6	406
2502-8-6	406
2502-8-8	406
2503-10-8	407
2503-12-12	407
2503-12-16	407
2503-16-16	407
2503-16-20	407
2503-20-16	407
2503-20-20	407
2503-2-2	407
25-033	87
2503-4-4	407
2503-6-4	407
2503-6-6	407
2503-6-8	407
2503-8-6	407
2503-8-8	407
25-062	87
25-064	87
25-175	87
25-176	87
25-177	87
25-179	87
25-219	87
25-220	87
25-221	87
25-224	87
26-001	89
26-002	89
26-003	89
26-004	89
26-005	89
26-007	89
26-008	89
26-011	89
2601-12-12	407
26-014	89
2601-4-4	407
2601-6-6	407
2601-8-8	407
26-021	89
26-023	89
2602-4-4	407
2602-6-6	407
2602-8-8	407
2603-10-10	407
2603-12-12	407
2603-16-16	407
2603-2-2	407
2603-3-3	407
2603-4-4	407
2603-6-6	407
2603-8-8	407
26-062	89
26-063	89
26-064	89
26-065	89
26-066	89
26-068	89
26-069	89
26-079	89
26-102	89
26-103	89
26-105	89
26-142	89
26-145	89
26-146	89
26-153	89
26-175	89
26-176	89
26-177	89
26-179	89
26-180	89
26-180L	89
26-181	89
26-182	89
26-183	89
26-184	89
26-188	89
26-189	89
26-190	89
26-194	89
26-195	89
26-198	89
26-220	89
26-220B	89
26-221	89
26-221B	89
26-224	89
26-224B	89
26-225	89
26-225B	89
26-228	89
26-229	89
26-232	89
26-233	89
26-233B	89
26-234	89
26-235	89
26-237	89
26-238	89
26-291	89
26-292	89
26-293	89
26-296	89
27-001	88
2700-10	407
2700-12	407
2700-14	407
2700-16	407
27-002	88
2700-2-2	407
27-003	88
2700-4-4	407
27-005	88
2700-5-5	407
27-006	88
2700-6-6	407
2700-8	407
2701-10	408
2701-12	408
2701-16	408
2701-20	408
2701-4	408
2701-5	408
2701-6	408
2701-8	408
2702-10	408
2702-12	408
2702-16	408
2702-4	408
2702-6	408
2702-8	408
2703-10	408
2703-12	408
2703-16	408
2703-4	408
2703-6	408
2703-8	408
2704-10	408
2704-12	408
2704-16	408
2704-4	408
2704-6	408
2704-8	408
2705-12-12	408
2705-16-16	408
2705-4-4	408
2705-6-6	408
2705-8-8	408
2706-12-12	408
2706-16-16	408
2706-4-4	408
2706-6-6	408
2706-8-8	408
28-001	2
28-002	2
28-003	2
28-004	2
28-005	2
28-009	2
28-009LF	158
28-010	2
28-010LF	158
28-011	2
28-011LF	158
28-012	2
28-012LF	158
28-013	2
28-013LF	158
28-014	2
28-015	2
28-015B	2
28-016	2
28-016B	2
28-017	2
28-018	2
28-019	2
28-020	2
28-021B	2
28-022	2
28-023	2
28-024	2
28-025	2
28-026	2
28-027	2
28-028	2
28-029	3
28-030	3
28-031	3
28-032	2
28-032LF	158
28-033	2
28-033LF	158
28-034	2
28-034LF	158
28-035	2
28-035LF	158
28-036	2
28-036LF	158
28-038	3
28-039	3
28-041	3
28-042	3
28-043	3
28-044	3
28-045	3
28-046	3
28-047	3
28-048	3
28-049	3
28-050	3
28-051	3
28-052	3
28-053B	2
28-057	3
28-058	3
28-058L	3
28-058LF	158
28-059	3
28-059L	3
28-059LF	158
28-060	3
28-060L	3
28-060LF	158
28-061	3
28-061L	3
28-061LF	158
28-062	3
28-062L	3
28-063	3
28-067	4
28-068	4
28-069	4
28-070	4
28-071	4
28-075	4
28-075LF	159
28-076	4
28-076LF	159
28-077	4
28-077LF	159
28-078	4
28-078LF	159
28-079	4
28-079LF	159
28-080	4
28-080LF	159
28-084	6
28-084LF	159
28-085	6
28-085LF	159
28-086	6
28-086LF	159
28-087	6
28-087LF	159
28-088	6
28-088LF	159
28-089	6
28-090	6
28-091	5
28-092	6
28-093	6
28-093LF	159
28-094	6
28-094LF	159
28-095	6
28-095LF	159
28-096	6
28-096LF	159
28-097	6
28-097LF	159
28-098LF	159
28-102	5
28-102L	5
28-102LF	158
28-103	5
28-103LF	158
28-104	5
28-104L	5
28-104LF	158
28-105	5
28-105L	5
28-105LF	158
28-106	5
28-106L	5
28-106LF	158
28-107	5
28-107L	5
28-107LF	158
28-108	5
28-108LF	158
28-109L	5
28-109LF	158
28-110L	5
28-110LF	158
28-111	5
28-111L	5
28-111LF	158
28-112	5
28-112LF	158
28-113	5
28-114	5
28-114LF	158
28-115	5
28-115LF	158
28-116	6
28-116LF	158
28-117	6
28-117LF	158
28-118	6
28-118LF	158
28-119	6
28-119LF	158
28-120	6
28-121	6
28-121LF	158
28-122	6
28-122LF	158
28-123	7
28-124	7
28-125	7
28-126	7
28-127	7
28-128	6
28-128LF	158
28-129	6
28-129LF	158
28-130	6
28-130LF	158
28-131	7
28-131LF	159
28-132	7
28-132LF	159
28-133	7
28-133LF	159
28-134	7
28-134LF	159
28-135	7
28-135LF	159
28-136	7
28-140	7
28-141	7
28-141LF	159
28-142	7
28-143	7
28-144	7
28-144LF	159
28-145	7
28-145LF	159
28-146	7
28-147	7
28-147LF	159
28-148	7

Part#	Page	Part#	Page	Part#	Page	Part#	Page	Part#	Page	Part#	Page
28-148LF	159	28-194LF	160	28-225	8	28300SS	13	28-372	357	28-517	353
28-149	7	28-195	9	28-225L	8	28-301	12	28-373	357	28-518	354
28-149LF	159	28-195L	9	28-225LF	159	28-301	12	28-374	357	28-519S	353
28-150	7	28-195LF	160	28-227	8	28301SS	13	28-375	357	28-520	354
28-151	7	28-196	9	28-230	8	28-302	12	28-376	357	28-521	354
28-152	7	28-196L	9	28-231	8	28-302	12	28-377	357	28-522	354
28-153	7	28-196LF	160	28-232	8	28-303	12	28-378	357	28-523	354
28-154	7	28-197	9	28-233	8	28-303	12	28-379	357	28-524	354
28-155	7	28-198	9	28-234	8	28303SS	13	28-380	357	28-525S	353
28-156	4	28-199	9	28-238	8	28-304	12	28-381	357	28-526S	353
28-156S	4	28-199LF	160	28-239	8	28-304	12	28-382	357	28-528	354
28-157	4	28-200	6	28-240	8	28304SS	13	28400	107	28-530	354
28-157S	4	28-201	6	28-245	9	28-306	13	28401	107	28-531	354
28-158	4	28-201LF	159	28-245LF	160	28-307	13	28402	107	28-532	354
28-159	4	28-201S	7	28-246	9	28-308	13	28403	107	28-533	350
28-160	4	28-202	6	28-246LF	160	28-309	13	28404	107	28-534	350
28-161	4	28-202LF	159	28-247	9	28-310	13	28405	107	28-534B	350
28-165	5	28-202S	7	28-247LF	160	28-311	12	28407	107	28-534SS	351
28-165LF	158	28-203	6	28-248	9	28-312	13	28-415	17	28-535	350
28-166	5	28-203LF	159	28-248LF	160	28-313	12	28-424	9	28-536	354
28-166LF	158	28-203S	7	28-249	9	28-313	12	28-425	9	28-538	354
28-167	5	28-204	6	28-253	9	28-315	12	28-426	9	28-540	349
28-167LF	158	28-204LF	159	28-254	9	28-316	12	28-427	9	28-540S	349
28-168	5	28-204S	7	28-255	9	28-317	12	28-440	11	28-541	349
28-168LF	158	28-205	6	28-256	9	28-317	12	28-441	11	28-541S	349
28-169	5	28-205LF	159	28-257	9	28-318	12	28-442	11	28-545	350
28-169LF	158	28-205S	7	28-259	5	28-318	12	28-443	11	28-546	350
28-174	6	28-206	6	28-260	5	28-319	12	28-444	358	28-546B	350
28-175	6	28-206LF	159	28-261	5	28-319	12	28-445	358	28-546SS	351
28-176	6	28-206S	7	28-261B	5	28-320	13	28-446	358	28-547	350
28-177	6	28-207	9	28-262	5	28-321	12	28-450	358	28-552	349
28-178	4	28-207LF	160	28-263	5	28-321	12	28-452	358	28-552S	349
28-179	4	28-208	9	28-264	5	28-322	12	28-456	358	28-553	349
28-180	4	28-208L	9	28-265	5	28-322	12	28-457	358	28-553S	349
28-180LF	158	28-208LF	160	28-265B	5	28-325	13	28-458	358	28-557	350
28-181	4	28-209	9	28-266	10	28-328	11	28-460	358	28-558	350
28-181L	4	28-210	8	28-266B	10	28-329	11	28-464	358	28-559	350
28-181LF	158	28-211	8	28-267	10	28-330	11	28-465	358	28-560	351
28-182	4	28-211L	8	28-267B	10	28-331	11	28-467	358	28-560SS	351
28-182LF	158	28-211LF	159	28-268	10	28-332	11	28-468	358	28-561	350
28-183	4	28-212	8	28-268B	10	28-333	11	28-469	358	28-562	349
28-183L	4	28-212L	8	28-269	10	28-335	11	28-470	358	28-562S	349
28-183LF	158	28-212LF	159	28-269B	10	28-336	11	28-475	7	28-564	349
28-184	4	28-213	8	28-270B	10	28-337	11	28-481	7	28-564S	349
28-184L	4	28-213L	8	28-274	10	28-338	11	28-487	7	28-565	349
28-185	4	28-213LF	159	28-275	10	28-339	11	28-493	7	28-565S	350
28-185L	4	28-214	8	28-276	10	28-340	11	28-497	7	28-566	349
28-185LF	158	28-214L	8	28-276B	10	28-345	13	28-498	7	28-566S	350
28-186	4	28-214LF	159	28-281	10	28-346	12	28-499	7	28-578	352
28-187	4	28-215	8	28-281F	10	28-346	12	28-500	353	28-579	351
28-188	4	28-215L	8	28-282	10	28-347	12	28-501	353	28-579SS	351
28-188LF	158	28-215LF	159	28-282F	10	28-347	12	28-501B	353	28-583	352
28-189	4	28-216	8	28-283	10	28-348	12	28-502	353	28-584	352
28-189LF	158	28-216L	8	28-283LF	160	28-348	12	28-503	353	28-585	352
28-190	9	28-218	8	28-284	10	28-350	356	28-504	353	28-586	352
28-190L	9	28-220	8	28-284LF	160	28-351	356	28-507	353	28-587	352
28-190LF	160	28-220L	8	28-285	10	28-352	356	28-507S	353	28-589	351
28-191	9	28-220LF	159	28-290	11	28-353	356	28-508	353	28-592	352
28-191L	9	28-221	8	28-291	11	28-354	356	28-509	353	28-593	352
28-191LF	160	28-221L	8	28-292	11	28-363	357	28-510	353	28-594	352
28-192	9	28-222	8	28-293	11	28-364	357	28-510B	353	28-595	352
28-192L	9	28-222L	8	28-294	11	28-365	357	28-511	353	28-597	352
28-192LF	160	28-222LF	159	28-295	11	28-366	357	28-512	353	28-601	352
28-193	9	28-223	8	28-296	11	28-367	357	28-513	353	28-601B	295
28-193L	9	28-223L	8	28-298	11	28-368	357	28-514S	353	28-601W	295
28-193LF	160	28-224	8	28-299	12	28-369	357	28-515	353	28-602B	295
28-194	9	28-224L	8	28-300	12	28-370	357	28-516	353	28-602W	295
28-194L	9	28-224LF	159	28-300	12	28-371	357	28-516S	353	28-603	352

Part#	Page
28-603B	295
28-603W	295
28-604B	295
28-604W	295
28-605	355
28-605B	295
28-605W	295
28-606W	295
28-607W	295
28-608	355
28-608W	295
28-609W	295
28-611B	296
28-611W	296
28-612B	296
28-612P	296
28-612W	296
28-613B	296
28-613P	296
28-613W	296
28-614B	296
28-614P	296
28-614W	296
28-615P	296
28-615W	296
28-616W	296
28-617W	296
28-618W	296
28-619	355
28-619P	296
28-619W	296
28-620	355
28-620W	296
28-621W	296
28-622W	296
28-623B	296
28-623W	296
28-624B	296
28-624W	296
28-625B	296
28-625W	296
28-628B	296
28-628W	296
28-639	355
28-640	355
28-640W	297
28-641W	297
28-642W	297
28-643W	297
28-651	355
28-652	355
28-659P	296
28-659W	296
28-660P	296
28-660W	296
28-661P	296
28-661W	296
28-663P	296
28-663W	296
28-663W	296
28-664P	296
28-664W	296
28-665	355
28-665W	296
28-666	355
28-666P	296
28-666W	296
28-667	355
28-667W	296
28-668	355
28-668P	296
28-668W	296
28-669	355
28-670	355
28-671	355
28-671P	296
28-671W	296
28-672	355
28-672P	296
28-672W	296
28-673	355
28-674W	296
28-675	355
28-675P	296
28-675W	296
28-676	355
28-677	355
28-678P	296
28-678W	296
28-679	355
28-679W	296
28-680	355
28-680P	296
28-680W	296
28-681	355
28-682W	296
28-683	354
28-683W	296
28-684	354
28-685	354
28-685W	296
28-686	354
28-687	354
28-688	355
28-690	351
28-691	351
28-693P	297
28-694P	297
28-695P	297
28-696P	297
28-697P	297
28-698P	297
28-699P	297
28-701	66
28-701W	295
28-702	66
28-702P	295
28-703	66
28-703W	295
28-704	66
28-704P	295
28-704W	295
28-705	66
28-705W	295
28-706	66
28-706W	295
28-707	66
28-707W	295
28-708	66
28-708W	295
28-709	66
28-710	66
28-711	66
28-712	66
28-713	66
28-714	66
28-715	66
28-716	66
28-717	66
28-718	66
28-719	66
28-720W	295
28-721W	295
28-722F	67
28-723P	295
28-723W	295
28-724F	67
28-724W	295
28-725W	295
28-726W	295
28-727W	295
28-728F	67
28-729F	67
28-731F	67
28-733F	67
28-734F	67
28-736F	67
28-738F	67
28-740F	67
28-741P	295
28-741W	295
28-742F	67
28-742P	295
28-743P	295
28-743W	295
28-744P	295
28-744W	295
28-745W	295
28-746W	295
28-747W	295
28-748	66
28-748W	295
28-749	66
28-752	66
28-753	66
28-754	66
28-756	66
28-760F	67
28-761P	297
28-761W	297
28-762F	67
28-762P	297
28-762W	297
28-763P	297
28-763W	297
28-764P	297
28-764W	297
28-765W	297
28-766F	67
28-767W	297
28-768F	67
28-768W	297
28-770F	67
28-772F	67
28-773F	67
28-774F	67
28-777F	67
28-778F	67
28-780F	67
28-781F	67
28-783F	67
28-784F	67
28-786F	67
28-803W	297
28-811P	296
28-811W	296
28-812P	296
28-814P	296
28-815W	296
28-816P	296
28-818P	296
28-818W	296
28-819P	295
28-819W	295
28-820P	295
28-820W	295
28-821P	295
28-957	66
28-958	66
28-959	66
28-960	66
28-961	66
28-962	66
28-963	66
28-964	66
28-966	66
28-969	66
28-970	66
28-971	66
28-972	66
28-973	67
28-974	67
28-975	67
28-988	340
28-989	340
28-990	340
28-991	340
28-996	282
28-997	282
28-998	282
28-999	282
29-900	355
29-901	355
29-902	355
29-903	355
29-904	355
29-905	355
29-906	355
29-907	355
29-908	355
29-909	355
29-910	355
29-911	355
29-912	355
29-913	355
29-914	355
30-000	38
300-000	356
300-0004	317
300-0006	317
300-0008	317
300-001	356
300-002	356
300-0020	317
300-003	356
300-004	356
300-005	317
300-006	356
300-007	356
300-008	356
30-001	38
300-010	317
300-012	317
300-014	356
300-015	356
300-016	317
300-017	356
300-018	356
300-019	356
300-020	356
300-021	356
300-022	356
300-023	356
300-024	356
300-026	356
300-028	356
300-031	356
300-032	356
300-033	356
300-034	356
300-035	356
300-036	356
300-037	356
30-006	38
30-011	38
30-012	38
30-013	38
30-016	38
30-017	38
30-018	38
30-019	38
30-020	38
30-021	40
30-022	40
30-025	43
30-026	41
30-027	43
30-027SS	43
30-028	43
30-028SS	43
30-029	43
30-029SS	43
30-030	43
30-031	43
30-032	43
30-032SS	43
30-033	43
30-033SS	43
30-034	43
30-034SS	43
30-035	43
30-039	43
30-040	43
30-040SS	43
30-041	43
30-041SS	43
30-042	43
30-042SS	43
30-043	43
30-044	43
30-045	43
30-046	43
30-047	39
30-048	39
30-049	39
30-050	42
30-051	42
30-052	42
30-053	40
30-054	40
30-055	39
30-056	39
30-058	40
30-063	40
30-063BE	40
30-063S	40
30-064	40
30-065	40
30-066	40
30-066LF	162
30-067	40
30-068	40
30-068LF	162
30-073	40
30-073LF	162
30-074	40
30-075	40
30-078	39
30-083	39
30-087	39
30-088	39
30-093	39
30-093L	39
30-094	39
30-098	40
30-099	40
30-100	40
30-101	40
30-103	41
30-103B	41
30-103P	301
30-123	42
30-128	42
30-133	42
30-135	42
30-136	42
30-137	42
30-138	42
30-139	42
30-140	47
30-142	41
30-149	42
30-150	41
30-150B	41
30-150R	41
30-151	41
30-160	47
30-161	46
30-162	46
30-163	47
30-180	41
30-180F	41
30-181	39
30-182	39
30-183	39
30-184	39
30-200	31
30-200LF	161
30-200SS	36
30-201	31
30-201LF	161
30-201SS	36
30-202	31
30-203	31
30-203LF	161
30-203SS	36
30-204	31
30-204LF	161

Part#	Page	Part#	Page	Part#	Page	Part#	Page	Part#	Page	Part#	Page
30-204SS	36	30-269SS	36	30-389	31	30-543	45	320-005	363	32-016	15
30-205	31	30-270	34	30-390	31	30-545	45	32-001	15	32-016LF	160
30-206	31	30-271	33	30-391	32	30-546	45	320-010	363	32-016SS	27
30-206LF	161	30-275	34	30-392	31	30-547	45	320-011	363	32-017	15
30-206SS	36	30-276	34	30-393	32	30-548	45	32-001LF	160	32-017LF	160
30-207	31	30-277	34	30-394	32	30-550	45	32-001SS	27	32-017SS	27
30-207LF	161	30-279	34	30-395	32	30-551	45	32-002	15	32-018	15
30-207SS	36	30-280	34	30-396	32	30-552	45	320-021	362	32-018LF	160
30-208	31	30-282	34	30-397	32	30-553	45	320-022	362	32-018SS	27
30-209	31	30-283	34	30-398	32	30-560	45	320-023	362	32-019	15
30-210	31	30-284	34	30-399	32	30-561	45	32-002LF	160	32-019LF	160
30-210SS	36	30-286	34	30-400	32	30-562	45	32-002SS	27	32-019SS	27
30-211	31	30-290	33	30-401	25	30-563	45	32-003	15	32-020	15
30-212	31	30-291	33	30-402	32	30-565	45	320-035	361	32-020LF	160
30-213	31	30-292	33	30-403	32	30-566	45	320-036	361	32-020SS	27
30-214	31	30-293	33	30-406	25	30-567	45	32-003LF	160	32-021	15
30-215	31	30-294	33	30-410	25	30-568	45	32-003SS	27	32-021LF	160
30-215SS	36	30-295	22	30-411	25	30-570	45	32-004	15	32-021SS	27
30-216	31	30-297	33	30-413	25	30-571	45	32-004LF	160	32-022	15
30-217	31	30-298	33	30-420	25	30-572	45	32-004SS	27	32-022LF	160
30-218	31	30-299	33	30-421	25	30-573	45	32-005	15	32-022SS	27
30-219	31	30-300	32	30-422	31	30-600	48	320-050	361	32-023	15
30-220	32	30-301	32	30-423	31	30-609	48	320-053	361	32-023LF	160
30-221	32	30-302	32	30-424	31	30-620	48	320-054	361	32-023SS	27
30-222	32	30-303	32	30-426	33	30-626	47	320-055	361	32-024	15
30-223	32	30-304	32	30-427	33	30-627	47	32-005LF	160	32-024LF	160
30-224	32	30-305	32	30-428	33	30-629	47	32-005SS	27	32-024SS	27
30-225	32	30-306	32	30-429	34	30-630	48	32-006	15	32-025	15
30-226	32	30-310	35	30-430	35	30-631	46	320-061	9	32-025LF	160
30-227	32	30-311	35	30-450	42	30-637	48	320-065	350	32-026	15
30-229	32	30-312	35	30-451	42	30-638	48	32-006LF	160	32-026LF	160
30-230	33	30-313	35	30-452	42	30-640	48	32-006SS	27	32-027	15
30-230LF	161	30-314	35	30-453	44	307-030	362	32-007	15	32-027LF	160
30-230SS	36	30-315	35	30-454	44	307-031	362	320-070	361	32-028	15
30-231	33	30-316	35	30-455	44	308-070	331	320-075	361	32-029	15
30-232	33	30-340	35	30-457	44	31-022	301	320-076	362	32-030	21
30-233	33	30-341	35	30-458	44	31-023	301	320-077	362	32-031	21
30-234	33	30-342	35	30-459	44	31-030	301	320-078	362	32-032	21
30-234SS	36	30-343	35	30-464	44	31-031	301	32-007LF	160	32-033	21
30-235	33	30-344	35	30-466	44	31-032	301	32-008	15	32-034	21
30-236	33	30-345	35	30-467	44	31-033	301	320-080	362	32-036	18
30-237	33	30-346	35	30-468	44	31-034	301	32-008LF	160	32-036B	19
30-238	31	30-349	35	30-469	44	31-035	301	32-008SS	27	32-036LF	161
30-240	33	30-358	31	30-471	44	31-038	301	32-009	15	32-038	18
30-241	33	30-359	31	30-472	44	31-039	301	320-095	362	32-038B	19
30-243	33	30-360	31	30-473	44	31-040	301	32-009LF	160	32-038LF	161
30-245	33	30-361	31	30-480	35	31-041	301	32-009SS	27	32-038SS	27
30-246	33	30-362	31	30-482	35	31-042	301	32-010	15	32-039	18
30-247	33	30-363	31	30-483	35	31-055	301	32-010LF	160	32-039B	19
30-249	33	30-366	31	30-484	35	31-058	301	32-010SS	27	32-039LF	161
30-250	34	30-370	32	30-486	35	31-063	301	32-011	15	32-039SS	27
30-251	34	30-371	32	30-505	44	31-064	301	32-011LF	160	32-040	18
30-252	34	30-372	32	30-506	44	31-067	301	32-011SS	27	32-040B	19
30-253	34	30-373	32	30-507	44	31-068	301	32-012	15	32-040LF	161
30-254	34	30-374	32	30-508	44	31-069	301	320-120	358	32-041	18
30-255	34	30-375	32	30-510	44	31-093	301	320-121	358	320-410	362
30-257	34	30-376	32	30-511	44	31-095	301	320-122	358	32-041B	19
30-258	34	30-377	32	30-512	44	31-096	301	32-012LF	160	32-041LF	161
30-259	34	30-378	32	30-513	44	31-097	301	32-012SS	27	32-041SS	27
30-260	34	30-379	32	30-516	44	31-137	79	32-013	15	32-042	18
30-261	34	30-381	32	30-517	44	31-154	166	32-013LF	160	32-042B	19
30-264	34	30-382	32	30-518	44	31-155	166	32-013SS	27	32-042LF	161
30-265	34	30-383	32	30-526	46	31-159	166	32-014	15	32-042SS	27
30-266	34	30-384	32	30-527	46	31-171	165	32-014LF	160	32-043	18
30-266SS	36	30-385	31	30-530	46	31-189	166	32-014SS	27	32-043B	19
30-267	34	30-386	31	30-540	45	31-190	166	32-015	15	32-043LF	161
30-268	34	30-387	31	30-541	45	31-191	166	32-015LF	160	32-043SS	27
30-269	34	30-388	31	30-542	45	320-000	363	32-015SS	27	32-044	18

Part#	Page
32-045	18
32-046	18
32046B	19
32-046LF	161
32-047	18
32047B	19
32-047LF	161
32-048	18
32048B	19
32-048LF	161
32-049	17
32-050	17
32-050LF	161
32-051	17
32-052	17
32-052LF	161
32-053	17
32-053LF	161
32-054	17
32-054LF	161
32-055	17
32-055LF	161
32-056	17
32-056LF	161
32-057	17
32-057LF	161
32-058	17
32-058LF	161
32-059	17
32-059LF	161
32-060	17
32-060LF	161
32-061	17
32-061LF	161
32-062	17
32-062LF	161
32-063	17
32-063LF	161
32-064	17
32-064LF	161
32-065	17
32-065LF	161
32-066	21
32-067	21
32-068	21
32-069	21
32-070	21
32-071	21
32-072	21
32-073	21
32-074	21
32-075	21
32-076	21
32-077	21
32-078	21
32-079	16
32-080	16
32-081	21
32-082	21
32-083	21
32-084	21
32-085	21
32-086	21
32-087	16
32-088	16
32-089	16
32-090	16
32-091	16
32-091LF	160
32-091SS	27
32-092	16
32-092LF	160
32-093	16
32-093LF	160
32-093SS	27
32-094	16
32-094LF	160
32-094SS	27
32-095	16
32-095LF	160
32-095SS	27
32-096	16
32-096	42
32-096LF	160
32-096SS	27
32-097	16
32-097	42
32-097LF	160
32-098	16
32-098	42
32-098LF	160
32-098SS	27
32-099	16
32-099	42
32-100	22
32-101	22
32-102	22
32-103	22
32-104	22
32-105	22
32-105C	22
32-105LF	161
32-106	22
32-107	22
32-107C	22
32-109	20
32-110	20
32-111	20
32-112	20
32-113	20
32-114	20
32-115	20
32-116	20
32-117	18
32-118	18
32-119	18
32-120	18
32-121	18
32-122	18
32-123	18
32-124	18
32-125	18
32-126	19
32-126LF	161
32-128	19
32-129	18
32-130	18
32-131	18
32-132	18
32-133	18
32-150	26
32-151	26
32-153	26
32-159	26
32-160	26
32-170	26
32-171	26
32176	24
32177	24
32178	24
32179	24
32180	24
32181	24
32182	24
32183	24
32184	24
32185	24
32-186	24
32-187	24
32-188	24
32-189	24
32-190	24
32-191	24
32-192	24
32-194	24
32-195	24
32-200	16
32-201	16
32-202	16
32-300	15
32-301	15
32-302	15
32-303	15
32-304	15
32-305	15
32-306	15
32-306LF	160
32-307	15
32-308	18
32-309	18
32-309B	19
32-309LF	161
32-310	18
32310B	19
32-311	18
32311B	19
32-311LF	161
32-311SS	27
32-312	18
32-313	18
32-313LF	161
32-314	18
32314B	19
32-314SS	27
32-315	18
32-316	15
32-317	17
32-317LF	161
32-318	17
32-319	18
32-320	17
32-321	17
32-322	21
32-326	22
32-327	22
32-328	22
32-329	16
32-330	18
32-331	16
32-332	16
32-334	22
32-335	22
32-336	22
32-336C	22
32-337	22
32-337C	22
32-338	22
32-338C	22
32-338SS	22
32-339	22
32-340	22
32-341	22
32-341C	22
32-342	22
32-345	20
32-346	20
32-349	16
32-350	19
32-351	16
32-352	19
32-353	19
32-354	18
32-355	16
32-356	16
32-357	16
32-359	21
32-360	16
32-361	19
32-362	21
32-363	19
32-364	21
32-365	19
32-365LF	161
32-366	19
32-367	19
32-368	19
32-375	16
32-376	16
32-377	24
32-379	16
32-380	16
32-381	24
32-382	24
32-383	24
32-384	24
32-385	24
32-386	16
32-387	24
32-388	24
32-389	21
32-390	15
32-391	18
32-392	21
32-394	22
32-397	22
32-400	19
32-401	20
32-402	20
32-403	20
32-404	20
32-405	20
32-406	20
32-407	20
32-409	20
32-410	20
32-411	20
32-412	19
32-413	19
32-414	19
32-415	19
32-416	19
32-417	19
32-418	19
32-419	19
32-420	19
32-425	19
32-429	19
32-433	19
32-434	19
32-435	19
32-436	19
32-437	25
32-438	25
32-439	25
32-440	25
32-441	17
32-442	17
32-443	17
32-444	17
32-445	17
32-446	17
32-447	17
32-448	17
32-449	17
32-450	16
32-451	16
32-452	16
32-453	16
32-454	16
32-455	16
32-456	16
32-457	16
32-458	16
32-460	21
32-461	21
32-462	21
32-463	21
32-470	17
32-472	17
32-473	17
32-475	17
32-476	17
32-500	334
325-004	318
325-005	318
325-006	318
325-008	318
32-501	334
325-010	318
325-012	318
325-016	318
32-502	334
325-020	318
32-503	334
32-504	334
32-506	334
32-507	334
32-508	334
32-510	334
32-517	334
32-521	334
32-526	334
32-533	334
32-535	334
32-539	334
32-543	334
32-545	334
32-549	334
32-550	334
32-551	334
32-552	334
32552SS	334
32-553	334
32-554	334
32-555	334
32-556	334
32-557	334
32557SS	334
32-558	334
32-559	334
32559SS	334
32-561	334
32561SS	334
32-563	334
32-564	334
32564SS	334
32-565	334
32-566	334
32566SS	334
32-567	334
32-568	334
32568SS	334
32-570	334
32570SS	334
32-571	334
32-572	334
32-573	334
32-574	334
32-575	334
32575SS	334
32-576	334
32-577	334
32577SS	334
32-578	334
32-579	334
32-580	334
32-584	334
32-586	334
32-588	334
32588SS	334
32-590	334
32-591	334
32-592	334
32-596	334
32-597	334
32-608	20
32-609	20
32-610	20
32-725	23
32-726	23
32-727	23
32-728	23
32-741	23
32-742	23
32-744	23
32-746	23
32-747	23
32-749	23
32-750	23
32-751	23
32-752	23
32-753	23
32-754	23
32-755	23
32-756	23
32-758	23
32-759	23
32-760	23

Part#	Page	Part#	Page	Part#	Page	Part#	Page	Part#	Page	Part#	Page
32-761	23	33-017P	297	33-089W	299	33-384W	298	33-453W	300	34-567T	29
32-770	23	33-017W	298	33-091B	299	33-385B	298	33-454W	300	34-568	29
32-771	23	33-018B	297	33-091W	299	33-385P	298	33-455W	300	34-568T	29
32-772	23	33-018P	297	33-092B	299	33-385W	298	33-456W	300	34-572	28
32-773	23	33-018W	298	33-092W	299	33-386W	298	33-458W	300	34-572T	28
32-774	23	33-019B	297	33-093B	299	33-389W	299	33-460W	298	34-574	28
32-775	23	33-019W	298	33-093W	299	33-390B	299	33-461P	298	34-574T	28
32-781	17	33-020B	297	33-094W	299	33-390W	299	33-461W	298	34-579	28
32-782	360	33-020P	297	33-095B	299	33-391B	299	33-462W	298	34-580	28
32-783	360	33-020W	298	33-095P	299	33-391W	299	33-463P	298	34-581	28
32-900	33	33-021B	297	33-095W	299	33-394B	299	33-463W	298	34-583	28
32-901	33	33-021W	298	33-096B	299	33-394W	299	33-464W	298	34-584	28
32-902	33	33-022B	297	33-096P	299	33-395B	299	33-470W	299	34-585	28
32-903	33	33-022P	297	33-096W	299	33-395W	299	33-471P	299	34-586	28
32-905	33	33-022W	298	33-097B	299	33-396B	299	33-471W	299	34-587	28
32-906	33	33-023B	297	33-097W	299	33-396W	299	33-480W	299	34-588	28
32-907	33	33-023P	297	33-098B	299	33-397W	299	33-481W	299	34-589	28
32-912	15	33-023W	298	33-098P	299	33-398W	299	33-482W	299	34-590	28
32-915	15	33-024B	297	33-098W	299	33-399W	299	34-001	63	34-591	28
32-950	15	33-024P	297	33-099P	299	33-402W	299	34-011	63	34-592	28
32-951	15	33-024W	298	33-099W	299	33-403W	299	34-012	63	34-595	28
32-952	15	33-025B	297	33-300P	300	33-406B	299	34-016	63	34-597	28
32-953	15	33-025P	297	33-301P	300	33-406W	299	34-022	63	34-600	29
32-954	15	33-025W	298	33-301W	300	33-407B	299	34-031	63	34-601	29
32-954LF	160	33-026B	297	33-302P	300	33-407W	299	34-041	63	34-610	29
32-955	15	33-026W	298	33-303P	297	33-408B	299	34-046	63	34-611	29
32-956	15	33-028W	298	33-303W	298	33-408W	299	34-051	63	34-612	29
32-957	15	33-029W	298	33-306W	298	33-409W	299	34-130	63	34-613	29
32-958	15	33-030W	298	33-307W	298	33-410B	299	34-131	63	34-621T	29
32-960	16	33-032W	298	33-308B	298	33-410W	299	34-141	63	34622T	29
32-961	16	33-033W	298	33-309B	298	33-415B	300	34-501	28	34-625	28
32-962	21	33-035W	298	33-309W	298	33-415W	300	34-502	28	34-626	28
33-000P	297	33-038B	298	33-310W	298	33-417W	300	34-504	28	34-633	29
33-000W	298	33-038W	298	33-311B	298	33-418B	300	34-510	28	34-633T	29
33-002B	297	33-039B	298	33-311P	298	33-420B	300	34-525	29	34-635T	29
33-002W	298	33-039W	298	33-311W	298	33-420W	300	34-526	29	34-638T	29
33-003B	297	33-040W	298	33-312B	298	33-422B	300	34-529	29	34-650T	29
33-003W	298	33-041B	298	33-312W	298	33-422W	300	34-531	29	34-652T	29
33-004B	297	33-041W	298	33-313B	298	33-423B	300	34-532	28	34-658	29
33-004W	298	33-042B	298	33-313P	298	33-426B	300	34-533	28	34-661	29
33-005B	297	33-042W	298	33-313W	298	33-426W	300	34-533T	28	34-71?	28
33-005W	298	33-043B	298	33-314B	298	33-429B	300	34-534	28	34-710	28
33-006B	297	33-043W	298	33-314P	298	33-429P	300	34-535	28	34-711	28
33-006W	298	33-044B	298	33-314W	298	33-429W	300	34-535T	28	34-712	28
33-007B	297	33-044W	298	33-315W	298	33-430B	300	34-536	28	34-713	28
33-007W	298	33-045B	298	33-316B	298	33-430W	300	34-537	28	34-714	28
33-008B	297	33-045W	298	33-316P	298	33-431W	300	34-538	28	34-715	28
33-008W	298	33-046B	298	33-316W	298	33-432B	300	34-539	28	34-716	28
33-009B	297	33-046W	298	33-318W	298	33-432W	300	34-540	28	34-717	28
33-009W	298	33-047B	298	33-319W	298	33-433B	300	34-540T	28	34-718	28
33-010W	298	33-047W	298	33-320W	298	33-433W	300	34-541T	28	34-720	28
33-011W	298	33-048P	298	33-321W	298	33-434B	300	34-543	28	34-721	28
33-012B	297	33-048W	298	33-322W	298	33-435B	300	34-543T	28	34-722	28
33-012P	297	33-052W	299	33-323P	297	33-435W	300	34-550	29	34-723	28
33-012W	298	33-053B	299	33-329W	298	33-436B	300	34-551	29	34-724	28
33-013B	297	33-053W	299	33-334P	298	33-436W	300	34-551T	29	34-725	28
33-013P	297	33-058W	299	33-342W	299	33-437B	300	34-552	29	34-726	28
33-013W	298	33-059W	299	33-343P	299	33-437W	300	34-552T	29	34-727	28
33-014B	297	33-060W	299	33-343W	299	33-438B	300	34-553T	29	34-728	28
33-014P	297	33-061W	299	33-344P	299	33-438W	300	34-561	29	350-004	319
33-014W	298	33-062W	299	33-344W	299	33-439W	300	34-562	29	350-004SS	320
33-015B	297	33-063W	299	33-345W	299	33-440P	300	34-562T	29	350-005	319
33-015P	297	33-064W	299	33-347W	299	33-440W	300	34-563	29	350-005SS	320
33-015W	298	33-065W	299	33-348W	299	33-441W	300	34-563T	29	350-006	319
33-016B	297	33-066W	299	33-349W	298	33-442W	299	34-564T	29	350-006SS	320
33-016P	297	33-067W	299	33-351W	298	33-448W	300	34-565	29	350-008	319
33-016W	298	33-068W	299	33-380W	298	33-450W	300	34-565T	29	350-008SS	320
33-017B	297	33-079W	299	33-381W	298	33-451W	300	34-567	29	350-010	319

Part#	Page
350-010SS	320
350-012	319
350-012SS	320
350-016	319
350-016SS	320
350-020	319
350-020SS	320
35-130	62
35-131	62
35-132	62
35-133	62
35-134	62
35-135	62
35-136	62
35-142	62
35-186	62
35-910	308
35-911	308
35-912	308
35-913	308
35-914	308
35-915	308
35-917	308
35-920	308
35-921	308
35-922	308
35-923	308
35-924	308
35-925	308
35-927	308
35-930	308
35-931	308
35-932	308
35-933	308
35-934	308
35-935	308
35-937	308
35-940	308
35-941	308
35-942	308
35-943	308
35-944	308
35-945	308
35-947	308
35-950	308
35-951	308
35-952	308
35-953	308
35-954	308
35-955	308
35-957	308
35-960	308
35-961	308
35-962	308
35-963	308
35-964	308
35-965	308
35-967	308
35-970	308
35-971	308
35-972	308
35-973	308
35-974	308
35-975	308
35-977	308
35-980	308
35-981	308
35-982	308
35-983	308
35-984	308
35-985	308
35-987	308
36-110	141
36-110SS	141
36-111	141
36-112	141
36-113	141
36-114	141
36-116	141
36-116SS	141
36-118	141
36-120	141
36-120SS	141
36-121	141
36-130	141
36-130SS	141
36-132	142
36-140	142
36-140SS	142
36-141	142
36-142	142
36-144	142
36-146	142
36-146SS	142
36-147	142
36-148	142
36-150	142
36-150SS	142
36-152	142
36-160	143
36-164	143
36-164SS	143
36-166	143
36-166SS	143
36-168	143
36-170	143
36-172	143
36-174	143
36-176	143
36-178	143
36-180	144
36-182	144
36-184	144
36-186	144
36-188	144
36-200	144
36-205	144
36-210	144
36-212	144
36-214	144
36-216	144
36-220	144
36-300	145
36301	145
36-304	145
36-305	145
36-306	145
36-307	145
36-308	145
36-309	145
36-310	145
36-311	145
36-340	145
36-350	145
36-360	145
36-362	145
36-370	145
36-371	145
36-372	145
36-373	145
36-374	145
36-375	145
36-376	145
36-377	145
38-000	132
38-001	132
38-002	132
38-003	132
38-004	132
38-005	132
38-009	132
38-010	132
38-011	132
38-012	132
38-013	132
38-014	132
38-015	139
38-016	139
38-018	132
38-019	132
38-020	132
38-021	132
38-022	132
38-023	132
38-028	132
38-029	132
38-030	132
38-035	132
38-036	132
38-037	132
38-038	132
38-039	132
38-040	132
38-041	132
38-042	132
38-043	132
38-044	133
38-045	133
38-046	133
38-047	133
38-048	132
38-049	133
38-052	133
38-053	133
38-054	133
38-055	133
38-057	133
38-059	133
38-060	133
38-061	133
38-062	133
38-063	133
38-064	133
38-065	133
38-066	133
38-067	133
38-068	133
38-072	134
38-073	134
38-074	134
38-075	134
38-076	134
38-077	134
38-078	134
38-078S	134
38-079	134
38-080	134
38-081	134
38-081S	134
38-082	134
38-083	134
38-084	134
38-085	134
38-086	134
38-087	134
38-088	134
38-090	134
38-091	134
38-092	134
38-093	134
38-094	134
38-095	134
38-101	134
38-101S	134
38-102	134
38-103	134
38-104	134
38-104S	134
38-105	134
38-106	134
38-107	134
38-108	134
38-109	134
38-110	134
38-111	134
38-113	134
38-114	134
38-115	134
38-116	134
38-117	134
38-118	134
38-119	134
38-120	134
38-124	135
38-125	135
38-126	135
38-127	135
38-128	135
38-129	135
38-132	135
38-133	135
38-134	135
38-136	135
38-137	135
38-138	135
38-139	135
38-140	135
38-141	135
38-142	135
38-143	135
38-144	135
38-146	135
38-148	135
38-149	135
38-150	135
38-151	135
38-152	135
38-152S	135
38-153	135
38-154	135
38-154S	135
38-155	135
38-156	135
38-157	135
38-158	135
38-161	136
38-162	136
38-163	136
38-164	136
38-165	136
38-170	136
38-171	136
38-172	136
38-173	136
38-174	136
38-179	136
38-180	136
38-181	136
38-182	136
38-183	136
38-188	136
38-189	136
38-190	136
38-191	136
38-196	136
38-204	137
38-205	137
38-206	137
38-207	137
38-208	137
38-209	137
38-210	137
38-211	137
38-212	137
38-213	137
38-217	137
38-218	137
38-221	137
38-222	137
38-223	137
38-224	137
38-225	137
38-226	137
38-227	137
38-228	137
38-229	137
38-235	137
38-236	137
38-237	137
38-239	137
38-240	137
38-241	137
38-243	137
38-244	137
38-246	137
38-278	137
38-279	137
38-300	138
38-301	138
38-306	138
38-307	138
38-312	138
38-313	138
38-318	139
38-319	139
38-324	140
38-325	140
38-326	140
38-327	140
38-328	140
38-333	140
38-334	140
38-335	140
38-336	140
38-337	140
38-342	140
38-343	140
38-344	140
38-345	140
38-346	140
38-351	139
38-352	139
38-357	139
38-358	139
38-363	139
38-364	139
38-368	140
38-369	140
38-370	140
38-371	140
38-372	140
38-711	87
38-715	87
38-718	87
38-732	87
38-761	87
38-769	87
38-770	87
38-800	24
38-802	24
38-806	24
38-808	24
38-810	24
38-828	24
38-830	24
38-832	24
38-834	24
38-836	24
38-860	24
38-862	24
38-864	24
38-866	24
38-868	24
38-873	25
38-874	25
38-910	392
38-915	392
38-920	392
38-923	392
38-926	392
38-927	392
38-950	391
38-950B2	391
38-951	391
38-951B1	391
38-951BA	391
38-952	391
38-9522	391
38-9523	391
38-952BA	391
38-952G	391
38-952G1	391
38-952GA	391
38-952O	391
38-952OA	391
38-952R	391
38-952R1	391
38-952RA	391

Part#	Page
38-952U	391
38-952U1	391
38-952UA	391
38-952Y	391
38-952Y1	391
38-952YA	391
38-953	391
38-953B1	391
38-953BA	391
38-954	391
38-954B5	391
38-954BA	391
38-95BA	391
38-960	391
38-960B5	391
38-960BA	391
38-960G	391
38-960G5	391
38-960GA	391
38-960O	391
38-960O5	391
38-960OA	391
38-960R	391
38-960R5	391
38-960RA	391
38-960U	391
38-960U5	391
38-960UA	391
38-960Y	391
38-960Y5	391
38-960YA	391
38-965	391
38-965B5	391
38-965BA	391
38-965G	391
38-965G5	391
38-965GA	391
38-965O	391
38-965O5	391
38-965OA	391
38-965R	391
38-965R5	391
38-965RA	391
38-965U	391
38-965U5	391
38-965UA	391
38-965Y	391
38-965Y5	391
38-965YA	391
38-970	391
38-970BA	391
38-970BC	391
38-970G	391
38-970GA	391
38-970GC	391
38-970R	391
38-970RA	391
38-970RC	391
38-975	391
38-975BA	391
38-975BC	391
38-975G	391
38-975GA	391
38-975GC	391
39-318	139
39-319	139
39-357	139
39-358	139
39400	371
39402	371
39404	371
39406	371
39409	372
39410	372
39411	372
39411	373
39412	372
39413	372
39414	372
39415	372
39416	372
39418	372
39419	372
39425	372
39426	372
39436	374
39437	374
39438	374
39442	374
39443	374
39444	374
39446	374
39447	374
39448	374
39451	374
39452	374
39453	374
39454	374
39457	374
39459	374
39460	374
39461	374
39462	374
39463	373
39464	373
39465	389
39466	374
39467	374
39468	374
39469	373
39470	374
39471	373
39472	373
39473	373
39474	374
39475	374
39477	373
39506	375
39507	375
39508	375
39509	376
39510	376
39511	375
39512	375
39515	376
39516	376
39520	376
39521	376
39522	376
39524	376
39530	376
39531	376
39535	377
39537	377
39541	377
39542	377
39543	377
39544	377
39550	377
39551	377
39552	377
39556	377
39557	377
39558	377
39559	377
39560	377
39563	378
39564	378
39565	378
39566	377
39570	378
39572	378
39573	378
39574	378
39575	378
39592	381
39595	147
39595	381
39596	147
39596	381
39597	147
39597	381
39600	147
39600	381
39604	381
39605	381
39606	381
39610	381
39611	381
39613	381
39614	381
39615	381
39616	382
39654	379
39655	380
39656	380
39657	380
39658	380
39659	380
39660	380
39661	380
39662	380
39663	380
39665	380
39667	380
39669	380
39672	379
39673	379
39674	379
39675	379
39676	379
39677	379
39684	382
39687	382
39688	382
39689	382
39690	382
39712	388
39713	388
39736	383
39737	383
39738	383
39739	383
39740	383
39741	383
39742	384
39743	384
39744	384
39745	384
39748	384
39749	384
39752	384
39753	384
39754	384
39757	385
39758	385
39764	386
39765	386
39766	386
39767	386
39768	386
39769	386
39772	385
39773	385
39774	385
39775	385
39778	386
39779	386
39782	386
39783	386
39786	385
39787	385
39788	385
39789	385
39792	387
39793	387
39794	387
39795	387
39800	387
39801	387
39802	387
39803	387
39805	387
39807	386
39809	386
39814	387
39818	385
39819	385
39820	385
39825	371
39828	375
39829	375
39830	375
39831	375
39832	375
39833	375
39834	375
39838	371
39839	371
39855	372
39856	372
39857	372
39860	378
39870	375
39871	375
39874	375
39875	375
39877	375
39878	375
39962	371
40-001	216
4000-10	419
4000-12	419
4000-14	419
4000-16	419
40-002	216
4000-20	419
4000-2-2	419
4000-24	419
40-003	216
4000-32	419
40-004	216
4000-4-4	419
40-005	216
40-006	216
4000-6-6	419
40-007	216
40-008	216
4000-8-8	419
40-009	216
40-010	216
40-011	216
4001-10	419
4001-12	419
4001-16	419
40-012	216
4001-20	419
4001-2-2	419
4001-24	419
40-013	216
4001-32	419
40-014	216
4001-4-4	419
40-015	216
4001-6-6	419
40-017	216
40-018	216
4001-8-8	419
40-019	216
40-020	216
40-021	216
40-022	216
40-023	216
40-024	216
40-025	216
40-026	216
40-027	216
40-028	216
40-029	216
40-030	216
40-031	216
40-032	216
40-033	216
40-034	216
40-035	216
40-036	216
40-040	217
40-041	217
40-042	217
40-043	217
40-044	217
40-045	217
40-046	217
40-047	217
40-048	217
40-049	217
40-050	217
40-051	217
40-052	217
40-053	217
40-054	217
40-055	217
40-056	217
40-060	217
40-061	217
40-062	217
40-063	217
40-064	217
40-065	217
40-066	217
40-067	217
40-068	217
40-069	217
40-070	217
40-071	217
40-072	217
40-073	217
40-074	217
40-075	217
40-076	217
40-080	218
40-081	218
40-082	218
40-083	218
40-084	218
40-085	218
40-086	218
40-087	218
40-088	218
40-089	218
40-090	218
40-091	218
40-092	218
40-093	218
40-094	218
40-095	218
40-096	218
40-097	218
40-098	218
40-099	218
40-100	218
40-101	218
40-102	218
40-103	218
40-104	218
40-105	218
40-106	218
40-107	218
40-108	218
40-109	218
40-110	218
40-111	218
40-112	218
40-113	218
40-114	218
40-115	218
40-120	219
40-121	219
40-122	219
40-123	219
40-124	219
40-125	219
40-126	219
40-127	219
40-128	219
40-129	219
40-130	219
40-131	219

Part#	Page
40-132	219
40-133	219
40-134	219
40-135	219
40-136	219
40-140	219
40-141	219
40-142	219
40-143	219
40-144	219
40-145	219
40-146	219
40-147	219
40-148	219
40-149	219
40-150	219
40-151	219
40-152	219
40-153	219
40-154	219
40-155	219
40-156	219
40-160	220
40-161	220
40-162	220
40-163	220
40-164	220
40-165	220
40-166	220
40-167	220
40-168	220
40-169	220
40-170	220
40-171	220
40-172	220
40-173	220
40-174	220
40-175	220
40-176	220
40-178	220
40-179	220
40-180	220
40-181	220
40-182	220
40-183	220
40-184	220
40-185	220
40-186	220
40-187	220
40-200	221
40-201	221
40-202	221
40-203	221
40-204	221
40-205	221
40-206	221
40-207	221
40-209	221
40-213	221
40-220	221
40-221	221
40-222	221
40-223	221
40-224	221
40-225	221
40-226	221
40-234	221
40-254	221
40-256	221
40-259	221
40-260	221
40-261	221
41-040	222
41-041	222
41-042	222
41-043	222
41-044	222
41-045	222
41-046	222
41-047	222
41-048	222
41-049	222
41-050	222
41-060	222
41-061	222
41-062	222
41-063	222
41-064	222
41-065	222
41-066	222
41-067	222
41-068	222
41-069	222
41-070	222
41-074	222
43-200L	178
43-200T	178
43-204L	178
43-204T	178
43-206L	178
43-207L	178
43-265LF	167
43-266LF	167
44-100	224
44-100LF	224
44-101	224
44-101LF	224
44-102	224
44-102LF	224
44-103	224
44-103LF	224
44-104	224
44-104LF	224
44-105	224
44-105LF	224
44-106	224
44-106LF	224
44-107	224
44-107LF	224
44-108	224
44-108LF	224
44-109	224
44-110	224
44-110LF	224
44-112	224
44-120	224
44-123	224
44-124	224
44-124LF	224
44-127	224
44-127LF	224
44-131	224
44-131LF	224
44-134	224
44-134LF	224
44-137	224
44-137LF	224
44-140LF	224
44-160	224
44-160LF	224
44-161	224
44-161LF	224
44-162	224
44-162LF	224
44-163	224
44-163LF	224
44-164	224
44-164LF	224
44-165	224
44-165LF	224
44-166	224
44-166LF	224
44-167	224
44-167LF	224
44-168	224
44-168LF	224
44-169	224
44-170	224
44-180	225
44-180LF	225
44-181	225
44-181LF	225
44-182	225
44-182LF	225
44-183	225
44-183LF	225
44-184	225
44-184LF	225
44-185	225
44-185LF	225
44-186	225
44-186LF	225
44-187	225
44-187LF	225
44-188	225
44-188LF	225
44-189	225
44-190	225
44-200	225
44-201	225
44-201LF	225
44-202	225
44-202LF	225
44-203	225
44-203LF	225
44-204	225
44-204LF	225
44-205	225
44-205LF	225
44-206	225
44-206LF	225
44-207	225
44-207LF	225
44-208	225
44-208LF	225
44-212	311
44-213	311
44-214	311
44-215	311
44-216	311
44-250	226
44-250LF	226
44-251	226
44-251LF	226
44-252	226
44-252LF	226
44-253	226
44-253LF	226
44-254	226
44-254LF	226
44-255	226
44-255LF	226
44-256	226
44-256LF	226
44-257	226
44-257LF	226
44-258	226
44-258LF	226
44-259	226
44-260	226
44-276	226
44-276LF	226
44-280	226
44-280LF	226
44-282	226
44-282LF	226
44-283	226
44-286	226
44-286LF	226
44-287	226
44-287LF	226
44-288LF	226
44-291	226
44-291LF	226
44-296	226
44-298	226
44-298LF	226
44-301	226
44-301LF	226
44-303	226
44-303LF	226
44-306	226
44-306LF	226
44-330LF	226
44-334LF	226
44-391	225
44-391LF	225
44-392	225
44-392LF	225
44-393	225
44-393LF	225
44-394	225
44-394LF	225
44-395	225
44-395LF	225
44-396	225
44-396LF	225
44-397	225
44-397LF	225
44-398	225
44-398LF	225
444-000	315
444-001	315
444-002	315
444-005	315
444-006	315
444-007	315
444-008	315
444-011	315
444-020	315
444-021	315
444-023	315
444-040	315
444-042	315
444-045	315
444-048	315
444-049	315
444-060	315
444-062	315
444-095	315
44-410	227
44-410LF	227
44-411	227
444-111	315
444-112	315
444-113	315
44-411LF	227
44-412	227
44-412LF	227
44-413	227
44-413LF	227
44-414	227
44-414LF	227
44-415	227
44-415LF	227
44-416	227
44-416LF	227
44-417	227
44-417LF	227
44-418	227
44-418LF	227
44-419	227
44-420	227
44-420LF	227
44-430	227
44-430LF	227
44-431	227
444-313	315
444-318	315
44-431LF	227
44-432	227
444-320	315
44-432LF	227
44-433	227
44-434	227
44-434LF	227
44-435	227
44-435LF	227
44-436	227
44-436LF	227
44-437	227
44-437LF	227
44-438	227
44-438LF	227
44-440	227
44-441	227
44-441LF	227
44-442	227
44-442LF	227
44-444	227
44-444LF	227
44-445	227
44-445LF	227
44-446	227
44-446LF	227
44-447	227
44-447LF	227
44-448	227
44-448LF	227
44-449	227
44-449LF	227
44-450	227
44-450LF	227
44-451	227
44-451LF	227
44-452	227
44-452LF	227
44-453	227
44-453LF	227
44-454	227
44-454LF	227
44-456	227
44-458	227
44-461	227
44-462	227
44-462LF	227
44-463	227
44-470	228
44-470LF	228
44-471	228
44-471LF	228
44-472	228
44-472LF	228
44-473	228
44-473LF	228
44-474	228
44-474LF	228
44-475	228
44-475LF	228
44-476	228
44-476LF	228
44-477	228
44-477LF	228
44-478	228
44-478LF	228
44-480	228
44-500	229
44-500LF	229
44-501	229
44-501LF	229
44-502	229
44-502LF	229
44-503	229
44-503LF	229
44-504	229
44-504LF	229
44-505	229
44-505LF	229
44-506	229
44-506LF	229
44-507	229
44-507LF	229
44-508	229
44-508LF	229
44-509	229
44-509LF	229
44-510	229
44-510LF	229
44-511	229
44-511LF	229
44-512	229
44-512LF	229
44-513	229
44-513LF	229
44-514	229
44-515	229
44-516	229
44-516LF	229

Part#	Page	Part#	Page	Part#	Page	Part#	Page	Part#	Page	Part#	Page
44-517	229	44-651	230	44844LF	293	44-971	310	46-061L	151	46-400M	152
44-517LF	229	44-651LF	230	44845LF	232	44-972	310	46-061LF	167	46-401	152
44-518	229	44-652	230	44845LF	293	44-973	310	46-064	147	46-401M	152
44-518LF	229	44-653	230	44-911	310	44-974	310	46-066	147	46-402	152
44-519	229	44-653LF	230	44-912	310	44-975	310	46-067	147	46-402M	152
44-519LF	229	44-654	230	44-913	310	44-976	310	46-068	147	46-406M	152
44-520	229	44-654LF	230	44-914	310	44-977	310	46-069	147	46-411	152
44-520LF	229	44-655	230	44-915	310	44-978	310	46-070	147	46-411M	152
44-521	229	44-655LF	230	44-916	310	44-979	310	46-071	147	46-429M	152
44-521LF	229	44-656	230	44-917	310	44-980	310	46-072	147	46-430M	152
44-522	229	44-656LF	230	44-918	310	44-981	310	46-073	147	46-440	155
44-522LF	229	44-657	230	44-919	310	44-982	310	46-074	148	46-443	155
44-523	229	44-657LF	230	44-920	310	44-983	310	46-075	148	46-450	152
44-523LF	229	44-658	230	44-921	310	44-984	310	46-076	148	46-451	152
44-524	229	44-658LF	230	44-922	310	44-985	310	46-077	148	46-455	152
44-524LF	229	44-659	230	44-923	310	44-986	310	46-078	148	46-456	152
44-527	229	44-660	230	44-924	310	44-987	310	46-079	148	46-457	152
44-527LF	229	44-662	230	44-925	310	44-988	310	46-080	148	46-465	152
44-528	229	44-670	230	44-926	310	44-989	310	46-081	148	46-466	152
44-528LF	229	44-670LF	230	44-927	310	44-990	310	46-082	148	46-467	152
44-529	229	44-671	230	44-928	310	45-102LF	231	46-083	148	46-475	152
44-529LF	229	44-671LF	230	44-929	310	45-103LF	231	46-084	148	46-476	152
44-530	229	44-672	230	44-930	310	45-104FF	231	46-085	148	46-485	152
44-530LF	229	44-672LF	230	44-931	310	45-163LF	231	46-086	148	46-500	156
44-531	229	44-673	230	44-932	310	45-252LF	231	46-087	148	46-505	156
44-531LF	229	44-673LF	230	44-933	310	45-253LF	231	46-088	148	46-510	156
44-532	229	44-674	230	44-934	310	45-412LF	231	46-089	148	46-511	156
44-534	229	44-674LF	230	44-935	310	45-413LF	231	46-089A	148	46-512	156
44-534LF	229	44-675	230	44-936	310	46-002	150	46-090ALF	167	46-513	156
44-535	229	44-675LF	230	44-937	310	46-002LF	167	46-130	149	46-514	156
44-535LF	229	44-676	230	44-938	310	46-003	150	46-131	149	46-515	156
44-537	229	44-676LF	230	44-939	310	46-003LF	167	46-132	149	46-516	156
44-538	229	44-677	230	44-940	310	46-005LF	167	46-134	149	46-517	156
44-538LF	229	44-677LF	230	44-941	310	46-011	150	46-140	149	46-518	156
44-539	229	44-678	230	44-942	310	46-011LF	167	46-141	149	46-519	156
44-541	229	44-678LF	230	44-943	310	46-011X	150	46-142	149	46-520	154
44-543	229	44-700	228	44-944	310	46-012	150	46-143	149	46-520A	154
44-543LF	229	44-701	228	44-945	310	46-012LF	167	46-151	149	46-521	154
44-600	228	44-702	228	449-450	311	46-013	150	46-152	149	46-521A	154
44-600LF	228	44-703	228	44-946	310	46-016	150	46-152T	149	46-522	154
44-601	228	44-704	228	44-947	310	46-020	150	46-153	149	46-523	154
44-601LF	228	44-705	228	449-470	311	46-021	150	46-160	149	46-523A	154
44-602	228	44-706	228	44-948	310	46-021LF	167	46-161	149	46-524	154
44-602LF	228	44-707	228	449-480	311	46-022	150	46-161T	149	46-524A	154
44-603	228	44-708	228	449-481	311	46-023	150	46-162	149	46-526	154
44-603LF	228	44-720	231	449-482	311	46-023LF	167	46-165	149	46-529	154
44-604	228	44-721	231	44-949	310	46-028	150	46-166	149	46-530	154
44-604LF	228	44-722	231	44-950	310	46-029	150	46-166T	149	46-530A	154
44-605	228	44-723	231	44-951	310	46-031	150	46-167	149	46-531	154
44-605LF	228	44-724	231	44-952	310	46-036	151	46-200	156	46-531A	154
44-606	228	44-725	231	44-953	310	46-038	151	46-201	156	46-532	154
44-606LF	228	44-726	231	44-954	310	46-039	151	46-202	156	46-532A	154
44-607	228	44-727	231	44-955	310	46-040	151	46-237	154	46-533	154
44-607LF	228	44-728	231	44-956	310	46-045	151	46-241	153	46-533A	154
44-608	228	44-729	231	44-957	310	46045LF	167	46-243	153	46-539	156
44-608LF	228	44-740	231	44-958	310	46-046	151	46-244	153	46-540	12
44-609	228	44-742	231	44-959	310	46-048	151	46-247	153	46-541	12
44-610	228	44-750	231	44-960	310	46-048	360	46-248	153	46-560	156
44-633	230	44-753	231	44-961	310	46-048S	360	46-250	153	46-560V	156
44-634	230	44840LF	232	44-962	310	46-050	151	46-251	153	46-561	156
44-635	230	44840LF	293	44-963	310	46-051	151	46-252	153	46-561V	156
44-636	230	44841LF	232	44-964	310	46-055	151	46-255	153	46-562	156
44-637	230	44841LF	293	44-965	310	46-055LF	167	46-256	153	46-562V	156
44-638	230	44842LF	232	44-966	310	46-056	151	46-257	153	46-563	156
44-639	230	44842LF	293	44-967	310	46-056LF	167	46-260	153	46-563V	156
44-640	230	44843LF	232	44-968	310	46-056P	151	46-270	213	46-564	156
44-641	230	44843LF	293	44-969	310	46-060	151	46-277	213	46-564V	156
44-650	230	44844LF	232	44-970	310	46-061	151	46-400	152	46-565	156

Part#	Page
46-566	156
46-567	156
46-568	156
46-569	156
46-570	156
46-571	156
46-572	156
46-573	156
46-575	156
46-576	156
46-577	156
46-578	156
46-600	363
46-605	363
46-607	363
46-615	362
46-620	360
46-621	360
46-622	360
46-630	360
46-631	360
46650	107
46651	107
46652	107
46653	107
46660	107
46661	107
46662	107
46663	107
46670	107
46671	107
46672	107
46680	107
46681	107
46682	107
466900	107
466901	107
466902	107
46-830	155
46-832	155
46-833	155
46-834	155
46-875	155
46-878	155
46-900	155
46-903	155
46-903I	186
46-903ISB	186
46-903SS	202
46-904I	186
46-904SS	202
46-905I	186
46-905SS	202
46-910	155
46-912	155
46-912SS	202
46-913SS	202
46-914SS	202
46-920	155
46-921	155
46-922	155
46-922A	155
46-922I	186
46-922SS	202
46-923	155
46-923I	186
46-923SS	202
46-924	155
46-924I	186
46-924SS	202
46-925	155
46-930	188
46-930L	188
46-930S	188
46930SS	201
46-930T	188
46-931	188
46-931L	188
46-931S	188
46931SS	201
46-931T	188
46-932	188
46-932L	188
46-932S	188
46932SS	201
46-932T	188
46-933	188
46-933L	188
46-933S	188
46933SS	201
46-933T	188
46-934	187
46-934L	187
46-934LS	187
46-934LT	187
46934SS	201
46-935	187
46-935L	187
46-935LS	187
46-935LT	187
46935SS	201
46-936	187
46-936L	187
46-936LS	187
46-936LT	187
46936SS	201
46-937	187
46-937L	187
46-937LS	187
46-937LT	187
46937SS	201
46-951	155
46-956	155
46-980	155
46-981	155
46-986	154
46-987	154
46-988	154
46-989	154
47-042	155
48-001	236
48-002	236
48-003	236
48-004	236
48-005	236
48-006	236
48-007	236
48-008	236
48-009	236
48-010	236
48-011	236
48-015	236
48-020	236
48-021	236
48-022	236
48-023	236
48-024	236
48-025	236
48-026	236
48-027	236
48-028	236
48-029	236
48-030	236
48-031	236
48-032	236
48-034	236
48-036	236
48-040	237
48-041	237
48-042	237
48-043	237
48-044	237
48-045	237
48-046	237
48-047	237
48-048	237
48-049	237
48-050	237
48-052	237
48-053	237
48-054	237
48-056	237
48-060	237
48-061	237
48-062	237
48-063	237
48-064	237
48-065	237
48-066	237
48-067	237
48-068	237
48-069	237
48-070	237
48-071	237
48-072	237
48-073	237
48-074	237
48-075	237
48-076	237
48-080	238
48-081	238
48-082	238
48-083	238
48-084	238
48-085	238
48-086	238
48-087	238
48-088	238
48-089	238
48-090	238
48-091	238
48-092	238
48-094	238
48-096	238
48-100	238
48-101	238
48-102	238
48-103	238
48-104	238
48-105	238
48-106	238
48-107	238
48-108	238
48-109	238
48-110	238
48-111	238
48-113	238
48-115	238
48-120	239
48-121	239
48-122	239
48-123	239
48-124	239
48-125	239
48-126	239
48-127	239
48-128	239
48-129	239
48-131	239
48-135	239
48-140	239
48-141	239
48-142	239
48-143	239
48-144	239
48-145	239
48-146	239
48-147	239
48-148	239
48-149	239
48-151	239
48-152	239
48-153	239
48-155	239
48-160	240
48-161	240
48-162	240
48-163	240
48-164	240
48-165	240
48-166	240
48-167	240
48-168	240
48-169	240
48-170	240
48-171	240
48-172	240
48-174	240
48-180	240
48-181	240
48-187	240
48-193	240
48-200	240
48-201	240
48-203	240
48-205	240
48-207	240
48-209	240
48-213	240
48-220	240
48-227	240
49-001	236
49-002	236
49-003	236
49-004	236
49-005	236
49-006	236
49-007	236
49-008	236
49-009	236
49-010	236
49-011	236
49-017	236
49-020	236
49-021	236
49-022	236
49-023	236
49-024	236
49-025	236
49-026	236
49-027	236
49-028	236
49-029	236
49-030	236
49-031	236
49-032	236
49-033	236
49-034	236
49-035	236
49-036	236
49-037	236
49-038	236
49-040	237
49-041	237
49-042	237
49-043	237
49-044	237
49-045	237
49-046	237
49-047	237
49-048	237
49-049	237
49-050	237
49-052	237
49-054	237
49-060	237
49-061	237
49-062	237
49-063	237
49-064	237
49-065	237
49-066	237
49-067	237
49-068	237
49-069	237
49-070	237
49-072	237
49-074	237
49-080	238
49-081	238
49-082	238
49-083	238
49-084	238
49-085	238
49-086	238
49-087	238
49-088	238
49-089	238
49-090	238
49-092	238
49-094	238
49-100	238
49-101	238
49-102	238
49-103	238
49-104	238
49-105	238
49-106	238
49-107	238
49-108	238
49-109	238
49-110	238
49-111	238
49-113	238
49-120	239
49-121	239
49-122	239
49-123	239
49-124	239
49-125	239
49-126	239
49-127	239
49-128	239
49-129	239
49-140	239
49-141	239
49-142	239
49-143	239
49-144	239
49-145	239
49-146	239
49-147	239
49-148	239
49-149	239
49-151	239
49-153	239
49-160	240
49-161	240
49-162	240
49-163	240
49-164	240
49-165	240
49-166	240
49-167	240
49-168	240
49-169	240
49-170	240
49-200	240
49-201	240
49-203	240
49-205	240
49-207	240
49-209	240
49-213	240
49-220	240
49-223	240
49-234	240
49-236	240
49-240	240
50-001	62
500-012	321
5000-12-12	409
5000-16	409
5000-16-12	409
5000-2	409
500-020	321
5000-20-20	409
5000-24	409
500-028	321
5000-32	409
500-036	321
5000-4	409
5000-4-2	409
500-048	321
500-056	321
5000-6-4	409
5000-6-6	409
500-072	321

Part#	Page
5000-8	409
5000-8-4	409
5000-8-6	409
500-088	321
500-104	321
50-011	62
500-128	321
500-152	321
50-016	38
500-188	321
500-216	321
500-248	321
500-280	321
50-032	166
540402	124
540402S	124
540402SC	129
540404	124
540404S	124
540404SC	129
5404-12	409
5404-12-6	409
5404-12-8	409
5404-16	409
5404-16-12	409
5404-2	409
5404-20	409
5404-20-16	409
5404-24	409
5404-24-20	409
5404-32	409
5404-32-24	409
5404-4	409
5404-4-2	409
5404-6	409
5404-6-2	409
5404-6-4	409
5404-8	409
5404-8-4	409
5404-8-6	409
5405-12-12	409
5405-16-16	409
5405-16-20	409
5405-20-20	409
5405-20-24	409
5405-2-2	409
5405-2-4	409
5405-24-24	409
5405-4-2	409
5405-4-4	409
5405-6-4	409
5405-6-6	409
5405-6-8	409
5405-8-12	409
5405-8-8	409
540602	124
540602S	124
540602SC	129
540604	124
540604S	124
540604SC	129
540606	124
540606S	124
540606SC	129
540608	124
540608SC	129
5406-12-4	409
5406-12-6	409
5406-12-8	409
5406-16-12	409
5406-16-4	409
5406-16-6	409
5406-16-8	409
5406-20-16	409
5406-24-20	409
5406-32-20	409
5406-32-24	409
5406-4-2	409
5406-6-2	409
5406-6-4	409
5406-8-2	409
5406-8-4	409
5406-8-6	409
5406-C-12	410
5406-C-16	410
5406-C-2	410
5406-C-4	410
5406-C-6	410
5406-C-8	410
5406-FLP-12	410
5406-FLP-2	410
5406-FLP-4	410
5406-FLP-6	410
5406-FLP-8	410
5406-HHP-12	410
5406-HHP-16	410
5406-HHP-2	410
5406-HHP-20	410
5406-HHP-24	410
5406-HHP-4	410
5406-HHP-6	410
5406-HHP-8	410
5406-P-12	410
5406-P-16	410
5406-P-2	410
5406-P-20	410
5406-P-24	410
5406-P-32	410
5406-P-4	410
5406-P-6	410
5406-P-8	410
5406-SHP-12	410
5406-SHP-16	410
5406-SHP-2	410
5406-SHP-20	410
5406-SHP-24	410
5406-SHP-32	410
5406-SHP-4	410
5406-SHP-6	410
5406-SHP-8	410
540802C	129
540804	124
540804S	124
540804SC	129
540806	124
540806S	124
540806SC	129
540808	124
540808S	124
540808SC	129
541006	124
541006SC	129
541008	124
541008S	124
541008SC	129
541208	124
541208SC	129
541212	124
545302C	129
550-012	321
5500-12-12	410
5500-12-8	410
5500-16	410
5500-16-12	410
5500-2	410
550-020	321
5500-20-20	410
550-028	321
550-036	321
5500-4	410
550-048	321
550-056	321
5500-6	410
550-072	321
5500-8	410
5500-8-4	410
550-088	321
550-104	321
5501-12-12	411
5501-16-16	411
5501-2-2	411
550-128	321
5501-4-4	411
550-152	321
5501-6-6	411
5501-8	411
550-188	321
5502-12	411
550-216	321
5502-16-16	411
5502-2	411
5502-20	411
5502-24	411
5502-4	411
550-248	321
5502-6	411
5502-6-4	411
550-280	321
5502-8-4	411
5502-8-6	411
5502-8-8	411
550-312	321
5503-12-12	411
5503-16	411
5503-2	411
5503-4	411
5503-6	411
5503-8	411
5504-12	411
5504-16	411
5504-2	411
5504-20	411
5504-24	411
5504-4	411
5504-6	411
5504-8	411
5504-8-6	411
5505-12	411
5505-16	411
5505-20	411
5505-4	411
5505-6	411
5505-8	411
56-001	250
5600-12	412
5600-16	412
56-002	250
5600-2-2	412
56-003	250
56-004	250
5600-4-4	412
56-005	250
56-006	250
5600-6-6	412
56-007	250
56-008	250
5600-8-8	412
56-009	250
56-010	250
56-011	250
5601-12	412
5601-16	412
56-012	250
5601-2-2	412
56-013	250
56-014	250
5601-4-4	412
56-015	250
5601-6-6	412
56-017	250
56-020	250
56-021	250
5602-12	412
5602-16	412
56-022	250
5602-2-2	412
56-023	250
56-024	250
5602-4-4	412
56-025	250
56-026	250
5602-6-6	412
56-027	250
56-028	250
5602-8-8	412
56-029	250
56-030	250
56-031	250
5603-12	412
5603-16	412
56-032	250
5603-2-2	412
56-033	250
56-034	250
5603-4-4	412
56-035	250
56-036	250
5603-6-6	412
56-038	250
5603-8-8	412
56-040	251
56-041	251
5604-12	412
5604-16	412
56-042	251
5604-2-2	412
56-043	251
56-044	251
5604-4-4	412
56-045	251
56-046	251
5604-6-6	412
56-047	251
56-048	251
5604-8-8	412
56-049	251
56-050	251
56-051	251
5605-12	412
5605-16	412
56-052	251
5605-20	412
5605-2-2	412
56-053	251
56-054	251
5605-4-4	412
56-055	251
56-056	251
5605-6-6	412
5605-8	412
56-060	251
56-061	251
56-062	251
56-063	251
56-064	251
56-065	251
56-066	251
56-067	251
56-068	251
56-069	251
56-070	251
56-071	251
56-072	251
56-073	251
56-074	251
56-075	251
56-076	251
56-080	252
56-081	252
56-082	252
56-083	252
56-084	252
56-085	252
56-086	252
56-087	252
56-088	252
56-089	252
56-090	252
56-091	252
56-092	252
56-093	252
56-094	252
56-095	252
56-096	252
56-100	253
56-101	253
56-102	253
56-103	253
56-104	253
56-105	253
56-106	253
56-107	253
56-108	253
56-109	253
56-110	253
56-111	253
56-112	253
56-113	253
56-114	253
56-115	253
56-120	254
56-121	254
56-122	254
56-123	254
56-124	254
56-125	254
56-126	254
56-127	254
56-128	254
56-129	254
56-130	254
56-131	254
56-132	254
56-133	254
56-134	254
56-135	254
56-140	254
56-141	254
56-142	254
56-143	254
56-144	254
56-145	254
56-146	254
56-147	254
56-148	254
56-149	254
56-150	254
56-151	254
56-152	254
56-153	254
56-154	254
56-155	254
56-160	255
56-161	255
56-162	255
56-163	255
56-164	255
56-165	255
56-166	255
56-167	255
56-168	255
56-169	255
56-170	255
56-171	255
56-172	255
56-173	255
56-174	255
56-180	255
56-181	255
56-182	255
56-183	255
56-184	255
56-185	255
56-186	255
56-187	255
56-188	255
56-189	255
56-190	255
56-191	255
56-192	255
56-193	255
56-200	256
56-201	256
56-202	256
56-203	256
56-204	256
56-205	256
56-206	256

Part#	Page
56-207	256
56-208	256
56-209	256
56-210	256
56-211	256
56-212	256
56-213	256
56-220	256
56-221	256
56-223	256
56-224	256
56-225	256
56-226	256
56-227	256
56-228	256
56-229	256
56-240	251
56-241	251
56-242	251
56-243	251
56-244	251
56-245	251
56-246	251
56-247	251
56-250	252
56-251	252
56-252	252
56-253	252
56-254	252
56-255	252
56-256	252
56-257	252
56-260	253
56-261	253
56-262	253
56-263	253
56-264	253
56-265	253
56-266	253
56-267	253
56-270	254
56-271	254
56-272	254
56-273	254
56-275	254
56-280	254
56-281	254
56-282	254
56-283	254
56-285	254
56-290	255
56-291	255
56-292	255
56-293	255
56-294	255
56-295	255
56-296	255
56-297	255
56-300	257
56-330	256
56-331	256
56-332	256
56-430	251
57-001	250
57-002	250
57-003	250
57-004	250
57-005	250
57-006	250
57-007	250
57-008	250
57-009	250
57-010	250
57-011	250
57-012	250
57-013	250
57-014	250
57-015	250
57-017	250
57-020	250
57-021	250
57-022	250
57-023	250
57-024	250
57-025	250
57-026	250
57-027	250
57-028	250
57-029	250
57-030	250
57-031	250
57-032	250
57-033	250
57-034	250
57-035	250
57-036	250
57-040	251
57-041	251
57-042	251
57-043	251
57-044	251
57-045	251
57-046	251
57-047	251
57-048	251
57-049	251
57-050	251
57-051	251
57-052	251
57-053	251
57-054	251
57-055	251
57-056	251
57-060	251
57-061	251
57-062	251
57-063	251
57-064	251
57-065	251
57-066	251
57-067	251
57-068	251
57-069	251
57-070	251
57-071	251
57-072	251
57-073	251
57-074	251
57-075	251
57-076	251
57-080	252
57-081	252
57-082	252
57-083	252
57-084	252
57-085	252
57-086	252
57-087	252
57-088	252
57-089	252
57-090	252
57-091	252
57-092	252
57-093	252
57-094	252
57-095	252
57-096	252
57-100	253
57-101	253
57-102	253
57-103	253
57-104	253
57-105	253
57-106	253
57-107	253
57-108	253
57-109	253
57-110	253
57-111	253
57-112	253
57-113	253
57-114	253
57-115	253
57-120	254
57-121	254
57-122	254
57-123	254
57-124	254
57-125	254
57-126	254
57-127	254
57-128	254
57-129	254
57-130	254
57-131	254
57-132	254
57-133	254
57-134	254
57-135	254
57-140	254
57-141	254
57-142	254
57-143	254
57-144	254
57-145	254
57-146	254
57-147	254
57-148	254
57-149	254
57-150	254
57-151	254
57-152	254
57-153	254
57-154	254
57-155	254
57-160	255
57-161	255
57-162	255
57162TV	265
57162V	266
57-163	255
57-164	255
57164TV	265
57164V	266
57-165	255
57-166	255
57-167	255
57-168	255
57168TV	265
57168V	266
57-169	255
57-170	255
57170TV	265
57170V	266
57-171	255
57-172	255
57172TV	265
57172V	266
57-173	255
57-174	255
57174TV	265
57174V	266
57-180	255
57-181	255
57-182	255
57-183	255
57-184	255
57-185	255
57-186	255
57-187	255
57-188	255
57-189	255
57-190	255
57-191	255
57-192	255
57-193	255
57-200	256
57-201	256
57201TV	265
57201V	266
57-202	256
57-203	256
57203TV	265
57203V	266
57-204	256
57-205	256
57-206	256
57-207	256
57207TV	265
57207V	266
57-208	256
57-209	256
57209TV	265
57209V	266
57-210	256
57-211	256
57211TV	265
57211V	266
57-212	256
57-213	256
57213TV	265
57213V	266
57-220	256
57222TV	265
57-223	256
57223TV	265
57223V	266
57-224	256
57-225	256
57-226	256
57-227	256
57227TV	265
57227V	266
57-228	256
57228TV	265
57228V	266
57-229	256
57229TV	265
57229V	266
57-240	251
57-241	251
57-242	251
57-243	251
57-244	251
57-245	251
57-246	251
57-247	251
57-250	252
57-251	252
57-252	252
57-253	252
57-254	252
57-255	252
57-256	252
57-257	252
57-260	253
57-261	253
57-262	253
57-263	253
57-264	253
57-265	253
57-266	253
57-267	253
57-270	254
57-271	254
57-272	254
57-273	254
57-275	254
57-280	254
57-281	254
57-282	254
57-283	254
57-285	254
57-286	254
57-290	255
57-291	255
57-292	255
57-293	255
57-294	255
57-295	255
57-296	255
57-297	255
57-300	257
57-301	257
57-304	257
57-305	257
57-306	257
57-308	257
57-311	256
57-320	257
57-322	257
57-324	257
57-326	257
57-328	257
57-330	256
57-331	256
57-332	256
57332TV	265
57332V	266
57-430	251
57-431	251
57-433	251
59-001SMLS	258
59-002SMLS	258
59-003SMLS	258
59-004SMLS	258
59-005SMLS	258
59-006SMLS	258
59-007SMLS	258
59-009SMLS	258
59-010SMLS	258
59-011SMLS	258
59-020SMLS	258
59-021SMLS	258
59-022SMLS	258
59-023SMLS	258
59-024SMLS	258
59-025SMLS	258
59-026SMLS	258
59-027SMLS	258
59-028SMLS	258
59-029SMLS	258
59-030SMLS	258
59-031SMLS	258
59-032SMLS	258
59-033SMLS	258
59-034SMLS	258
59-036SMLS	258
590400	120
59-040SMLS	259
59-041SMLS	259
59-042SMLS	259
59-043SMLS	259
59-044SMLS	259
59-045SMLS	259
59-046SMLS	259
59-047SMLS	259
59-048SMLS	259
59-049SMLS	259
59-050SMLS	259
59-052SMLS	259
59-054SMLS	259
59-056SMLS	259
590600	120
59-060SMLS	259
59-060SMLSXX	264
59-061SMLS	259
59-062SMLS	259
59-062SMLSXX	264
59-063SMLS	259
59-064SMLS	259
59-064SMLSXX	264
59-065SMLS	259
59-066SMLS	259
59-066SMLSXX	264
59-067SMLS	259
59-068SMLS	259
59-069SMLS	259
59-070SMLS	259
59-070SMLSXX	264
59-071SMLS	259
59-072SMLS	259
59-073SMLS	259
59-074SMLS	259
59-075SMLS	259
59-076SMLS	259
590800	120
59-080SMLS	260

Part#	Page
59-080SMLSXX	264
59-081SMLS	260
59-082SMLS	260
59-082SMLSXX	264
59-083SMLS	260
59-084SMLS	260
59-085SMLS	260
59-086SMLS	260
59-086SMLSXX	264
59-087SMLS	260
59-088SMLS	260
59-089SMLS	260
59-090SMLS	260
59-090SMLSXX	264
59-091SMLS	260
59-092SMLS	260
59-094SMLS	260
59-096SMLS	260
59-100SMLS	260
59-100SMLSXX	264
59-101SMLS	260
59-101SMLSXX	264
59-102SMLS	260
59-103SMLS	260
59-103SMLSXX	264
59-104SMLS	260
59-105SMLS	260
59-105SMLSXX	264
59-106SMLS	260
59-107SMLS	260
59-108SMLS	260
59-109SMLS	260
59-109SMLSXX	264
59-110SMLS	260
59-111SMLS	260
59-111SMLSXX	264
59-112SMLS	260
59-113SMLS	260
59-114SMLS	260
59-115SMLS	260
59-115SMLSXX	264
59-120SMLS	261
59-121SMLS	261
59-122SMLS	261
59-123SMLS	261
59-124SMLS	261
59-125SMLS	261
59-126SMLS	261
59-127SMLS	261
59-128SMLS	261
59-129SMLS	261
59-130SMLS	261
59-131SMLS	261
59-132SMLS	261
59-133SMLS	261
59-134SMLS	261
59-135SMLS	261
59-140SMLS	261
59-141SMLS	261
59-142SMLS	261
59-143SMLS	261
59-144SMLS	261
59-145SMLS	261
59-146SMLS	261
59-147SMLS	261
59-148SMLS	261
59-149SMLS	261
59-150SMLS	261
59-151SMLS	261
59-152SMLS	261
59-153SMLS	261
59-154SMLS	261
59-155SMLS	261
59-160SMLS	262
59-160SMLSXX	264
59-161SMLS	262
59-161SMLSXX	264
59-162SMLS	262
59-162SMLSXX	264
59162TV	265
59162V	266
59-163SMLS	262
59-163SMLSXX	264
59-164SMLS	262
59-164SMLSXX	264
59164TV	265
59164V	266
59-165SMLS	262
59-166SMLS	262
59-166SMLSXX	264
59-167SMLS	262
59-168SMLS	262
59-168SMLSXX	264
59168TV	265
59168V	266
59-169SMLS	262
59-169SMLSXX	264
59-170SMLS	262
59-170SMLSXX	264
59170TV	265
59170V	266
59-171SMLS	262
59-171SMLSXX	264
59-172SMLS	262
59-172SMLSXX	264
59172TV	265
59172V	266
59-173SMLS	262
59-174SMLS	262
59-174SMLSXX	264
59174TV	265
59174V	266
59-179SMLSXX	264
59-180SMLS	262
59-181SMLS	262
59-182SMLS	262
59-183SMLS	262
59-184SMLS	262
59-185SMLS	262
59-186SMLS	262
59-187SMLS	262
59-188SMLS	262
59-189SMLS	262
59-190SMLS	262
59-191SMLS	262
59-192SMLS	262
59-193SMLS	262
59-196SMLS	262
59-197SMLS	262
59-198SMLS	262
59-199SMLS	262
59-200SMLS	263
59-201SMLS	263
59201TV	265
59201V	266
59-202SMLS	263
59-203SMLS	263
59203TV	265
59203V	266
59-204SMLS	263
59-205SMLS	263
59-206SMLS	263
59-207SMLS	263
59207TV	265
59207V	266
59-208SMLS	263
59-209SMLS	263
59209TV	265
59209V	266
59-210SMLS	263
59-211SMLS	263
59211TV	265
59211V	266
59-212SMLS	263
59-213SMLS	263
59213TV	265
59213V	266
59-220SMLS	263
59-221SMLS	263
59221TV	265
59221V	266
59222TV	265
59-223SMLS	263
59-224SMLS	263
59-225SMLS	263
59225TV	265
59225V	266
59-226SMLS	263
59-227SMLS	263
59227TV	265
59227V	266
59-228SMLS	263
59-229SMLS	263
59229TV	265
59229V	266
59-231SMLS	263
59231TV	265
59231V	266
59-300SMLS	263
59-301SMLS	263
59-305SMLS	263
59-306SMLS	263
59-308SMLS	263
59-320SMLS	263
59-322SMLS	263
59-324SMLS	263
59-326SMLS	263
59-328SMLS	263
595320	120
600-006	317
600-008	317
600-010	317
600-012	317
600-016	317
600-020	317
600-024	317
600-028	317
600-032	317
600-036	317
600-040	317
600-044	317
600-048	317
600-052	317
600-056	317
600-060	317
600-064	317
600-072	317
600-080	317
600-088	317
600-096	317
600-104	317
61-050	427
61-052	427
61-053	427
61-054	427
61-055	427
611-006	318
611-008	318
611-010	318
611-012	318
611-016	318
611-020	318
611-024	318
611-028	318
611-032	318
611-036	318
611-040	318
611-044	318
611-048	318
611-052	318
611-056	318
611-060	318
611-064	318
611-072	318
611-080	318
611-088	318
611-096	318
611-104	318
611-116	318
611-128	318
611-152	318
611-164	318
611-176	318
611-188	318
611-200	318
611-212	318
611-224	318
611-248	318
611-270	318
611-312	318
611-332	318
611-390	318
61-150	427
61-152	427
61-153	427
61-154	427
61-155	427
61-447	311
61-448	311
61-449	311
61-450	311
61-451	311
61-452	311
61-453	311
61-454	311
61-455	311
61-457	311
61775	234
61775	267
61776	234
61776	267
61777	234
61777	267
61778	234
61778	267
61-851	307
61-853	307
61-854	307
61-859	307
61-860	307
61-861	307
61-867	307
61-868	307
61-870	307
61-871	307
61-872	307
61-873	307
61-874	307
61-875	307
61-876	307
61-877	307
61-878	307
61-879	307
619-001	307
619-002	307
619-003	307
619-004	307
619-005	307
619-006	307
619-007	307
619-008	307
619-009	307
619-010	307
619-011	307
619-012	307
61-904	306
61-905	306
61-906	306
61-907	306
61-908	306
61-909	306
61-910	306
61-911	306
61-912	306
61-913	306
61-914	306
61-915	306
61-916	306
61-917	306
61-918	306
61-919	306
61-920	306
61-921	306
61-922	306
61-923	306
61-924	306
61-925	306
61-926	306
61-927	306
61-928	306
61-929	306
61-930	306
61-931	306
61-932	306
61-933	306
61-934	306
61-935	306
61-936	306
61-937	306
61-938	306
61-939	306
61-940	306
61-941	306
61-942	306
61-943	306
61-944	306
619-440	307
61-945	306
619-450	307
61-946	306
61-947	306
619-470	307
61-948	306
619-480	307
61-949	306
61-950	306
61-951	306
61-952	306
61-953	306
61-954	306
61-955	306
61-956	306
61-957	306
61-958	306
61-959	306
61-961	306
61-962	306
61-963	306
61-964	306
61-965	306
61-966	306
61-967	306
61-968	306
61-969	306
61-970	306
61-971	306
61-972	306
61-973	306
61-974	306
61-975	306
61-976	306
61-977	306
61-978	306
61-979	306
61-980	306
61-981	306
61-982	306
61-983	306
61-984	306
61-985	306
61-986	306
61-987	306
61-988	306
61-998	306
61-999	306
620-006	319
620-006SS	320
620-008	319
620-008SS	320
620-010	319
620-010SS	320
620-012	319
620-012SS	320
620-016	319
620-016SS	320
620-020	319
620-020SS	320
620-024	319

Part#	Page
620-024SS	320
620-028	319
620-028SS	320
620-032	319
620-032SS	320
620-036	319
620-036SS	320
620-040	319
620-040SS	320
620-044	319
620-044SS	320
620-048	319
620-048SS	320
620-052	319
620-052SS	320
620-056	319
620-056SS	320
620-060	319
620-060SS	320
620-064	319
620-064SS	320
620-072	319
620-072SS	320
620-080	319
620-088	319
620-096	319
620-104	319
620-116	319
620-128	319
620-152	319
620-164	319
620-176	319
620-188	319
620-200	319
620-212	319
620-224	319
620-248	319
620-270	319
620-312	319
620-332	319
620-390	319
620400	120
620400C	127
620409C	130
620532	120
620532C	127
620553C	130
620555C	130
620557C	130
620559C	130
620600	120
620600C	127
620604	120
620604C	130
620606C	130
62-075	245
62-076	245
62-077	245
62-078	245
62-079	245
62-080	245
620800	120
620800C	127
620806C	130
620808C	130
62-081	245
62-082	245
62-083	245
62-100	242
621000	120
621000C	127
62-101	242
62-102	242
62-103	242
62-104	242
62-105	242
62-106	242
62-107	242
62-108	242
62-109	242
62-110	242
62-112	242
621200	120
62-160	242
62-161	242
62-162	242
62-163	242
62-164	242
62-165	242
62-166	242
62-167	242
62-168	242
62-169	242
62-180	242
62-181	242
62-182	242
62-183	242
62-184	242
62-185	242
62-186	242
62-187	242
62-188	242
62-189	242
62-190	242
62-191	242
62-250	243
62-251	243
62-252	243
62-253	243
62-254	243
62-255	243
62-256	243
62-257	243
62-258	243
62-259	243
62-260	243
62-391	243
62-392	243
62-393	243
62-394	243
62-395	243
62-396	243
62-397	243
62-398	243
62-410	244
62-410B	244
62-411	244
62-411B	244
62-412	244
62-412B	244
62-413	244
62-413B	244
62-414	244
62-414B	244
62-415	244
62-415B	244
62415DC	234
62415HDDC	234
62-416	244
62-416B	244
62416DC	234
62416HDDC	234
62-417	244
62-417B	244
62417DC	234
62417HDDC	234
62-418	244
62-418B	244
62418DC	234
62418HDDC	234
62-419	244
62-420	244
62-420B	244
62-421	244
62-428	244
62-430	244
62-431	244
62-432	244
62-433	244
62-434	244
62-435	244
62-436	244
62-437	244
62-438	244
62-440	244
62-441	244
62-442	244
62-445	244
62-446	244
62-447	244
62-448	244
62-449	244
62-450	244
62-451	244
62-452	244
62-453	244
62-454	244
62-455	244
62-456	244
62-470	245
62-471	245
62-472	245
62-473	245
62-474	245
62-475	245
62-476	245
62-477	245
62-478	245
62-480	245
62-481	245
62-500	246
62-501	246
62-502	246
62-503	246
62-504	246
62-505	246
62-506	246
62-507	246
62-508	246
62-509	246
62-510	246
62-511	246
62-512	246
62-513	246
62-515	246
62-516	246
62-517	246
62-518	246
62-521	246
62-522	246
62-524	246
62-527	246
62-528	246
62-529	246
62-530	246
62-531	246
62-532	246
62-534	246
62-535	246
62-536	246
62-537	246
62-538	246
62-539	246
62-543	246
62-557	246
62-559	246
62-600	245
62-601	245
62-602	245
62-603	245
62-604	245
62-605	245
62-606	245
62-607	245
62-608	245
62-610	245
62-630	247
62-631	247
62-632	247
62-633	247
62-634	247
62-635	247
62-636	247
62-637	247
62-638	247
62-653	247
62-654	247
62-655	247
62-656	247
62-657	247
62-658	247
62-659	247
62-660	247
62-670	247
62-671	247
62-672	247
62-700	247
62-701	247
62-702	247
62-703	247
62-704	247
62-705	247
62-706	247
62-707	247
62-708	247
62-720	243
62-721	243
62-722	243
62-723	243
62-724	243
62-725	243
62-726	243
62-727	243
62-728	243
62-740	243
62-741	243
62-742	243
62-744	243
62-745	243
62-747	243
62-748	243
62-749	243
62-770	245
62-771	245
62-772	245
62-773	245
62-774	245
62-775	245
62-776	245
62-777	245
62-778	245
63-075	245
63-076	245
63-077	245
63-078	245
63-079	245
63-080	245
63-081	245
63-082	245
63-083	245
63-100	242
63-101	242
63-102	242
63-103	242
63-104	242
63-105	242
63-106	242
63-107	242
63-108	242
63-109	242
63-110	242
63-112	242
63-160	242
63-161	242
63-162	242
63-163	242
63-164	242
63-165	242
63-166	242
63-167	242
63-168	242
63-170	242
63-171	242
63-180	242
63-181	242
63-182	242
63-183	242
63-184	242
63-185	242
63-186	242
63-187	242
63-188	242
63-190	242
63-192	242
63214	13
63215	13
63216	13
63217	13
63218	13
63-250	243
63-251	243
63-252	243
63-253	243
63-254	243
63-255	243
63-256	243
63-257	243
63-258	243
63-260	243
63-261	243
63-390	243
63-391	243
63-392	243
63-393	243
63-394	243
63-395	243
63-396	243
63-397	243
63-398	243
63-400	243
63-401	243
63-410	244
63-410B	244
63-411	244
63-411B	244
63-412	244
63-412B	244
63-413	244
63-413B	244
63-414	244
63-414B	244
63-415	244
63-415B	244
63-416	244
63-416B	244
63-417	244
63-417B	244
63-418	244
63-418B	244
63-419	244
63-420	244
63-421	244
63-430	244
63-431	244
63-432	244
63-433	244
63-434	244
63-435	244
63-436	244
63-437	244
63-438	244
63-440	244
63-441	244
63-442	244
63-445	244
63-446	244
63-447	244
63-448	244
63-449	244
63-450	244
63-452	244
63-453	244
63-454	244
63-455	244
63-459	244
63-470	245
63-471	245
63-472	245

Part#	Page
63-473	245
63-474	245
63-475	245
63-476	245
63-477	245
63-478	245
63-480	245
63-500	246
63-501	246
63-502	246
63-504	246
63-505	246
63-506	246
63-507	246
63-508	246
63-509	246
63-510	246
63-511	246
63-512	246
63-513	246
63-516	246
63-517	246
63-518	246
63-521	246
63-522	246
63-523	246
63-524	246
63-527	246
63-528	246
63-529	246
63-530	246
63-531	246
63-534	246
63-535	246
63-537	246
63-538	246
63-540	246
63-541	246
63-543	246
63-550	246
63-600	245
63-601	245
63-602	245
63-603	245
63-604	245
63-605	245
63-606	245
63-607	245
63-608	245
63-610	245
63-630	247
63-631	247
63-632	247
63-633	247
63-634	247
63-635	247
63-636	247
63-637	247
63-638	247
63-641	247
63-653	247
63-654	247
63-655	247
63-656	247
63-657	247
63-658	247
63-660	248
63-661	248
63-662	248
63-663	248
63-664	248
63-665	248
63-670	247
63-671	247
63-672	247
63-680	248
63-681	248
63-682	248
63-683	248
63-684	248
63-701	247
63-702	247
63-703	247
63-704	247
63-705	247
63-706	247
63-707	247
63-708	247
63-720	243
63-721	243
63-722	243
63-723	243
63-724	243
63-725	243
63-726	243
63-727	243
63-728	243
63-740	243
63-741	243
63-742	243
63-744	243
63-745	243
63-747	243
63-748	243
63-749	243
63-759	248
63-760	248
63-761	248
63-762	248
63-763	248
63-764	248
63-765	248
63-771	245
63-772	245
63-773	245
63-774	245
63-775	245
63-776	245
63-777	245
63-778	245
63-850	311
63-851	311
63-852	311
63-853	311
63-854	311
63-855	311
63-856	311
63-857	311
639-001	311
639-002	311
639-003	311
639-004	311
63-911	309
63-912	309
63-913	309
63-914	309
63-915	309
63-916	309
63-917	309
63-918	309
63-919	309
63-921	309
63-922	309
63-923	309
63-924	309
63-925	309
63-926	309
63-927	309
63-928	309
63-929	309
63-931	309
63-932	309
63-933	309
63-934	309
63-935	309
63-936	309
63-937	309
63-938	309
63-939	309
63-941	309
63-942	309
63-943	309
63-944	309
639-440	311
63-945	309
639-450	311
63-946	309
63-947	309
639-470	311
63-948	309
639-480	311
63-949	309
63-950	309
63-951	309
63-952	309
63-953	309
63-954	309
63-955	309
63-956	309
63-957	309
63-958	309
63-959	309
63-961	309
63-962	309
63-963	309
63-964	309
63-965	309
63-966	309
63-967	309
63-968	309
63-969	309
63-971	309
63-972	309
63-973	309
63-974	309
63-975	309
63-976	309
63-977	309
63-978	309
63-979	309
63-980	309
63-981	309
63-982	309
63-983	309
63-984	309
63-985	309
63-986	309
63-987	309
63-988	309
63-989	309
63-999	309
6400-10	413
6400-10-12	413
6400-10-8	413
6400-12	413
6400-12-10	413
6400-12-14	413
6400-12-16	413
6400-12-8	413
6400-16	413
6400-16-12	413
6400-16-20	413
6400-2	413
6400-20	413
6400-20-24	413
6400-24-32	413
6400-4	413
6400-4-2	413
6400-4-6	413
6400-4-8	413
6400-5	413
6400-6	413
6400-6-10	413
6400-6-12	413
6400-6-4	413
6400-6-8	413
6400-8	413
6400-8-10	413
6400-8-12	413
6400-8-4	413
6400-8-6	413
6401-10-8	413
6401-12-12	413
6401-12-8	413
6401-16-16	413
6401-20-20	413
6401-4-4	413
6401-6-4	413
6401-6-6	413
6401-8-6	413
6401-8-8	413
6402-O-10-10	413
6402-O-12-12	413
6402-O-4-4	413
6402-O-6-6	413
6402-O-8-8	413
6403-O-12	413
6403-O-6	413
6403-O-8	413
640400	120
640400C	127
6404-10-8	413
6404-12-12	413
6404-4-4	413
6404-6-4	413
6404-6-6	413
6404-6-8	413
6404-8-8	413
6405-O-10-6	414
6405-O-10-8	414
6405-O-12-12	414
6405-O-12-8	414
6405-O-16-12	414
6405-O-16-16	414
6405-O-20-20	414
6405-O-24-24	414
6405-O-32-32	414
6405-O-4-2	414
6405-O-4-4	414
6405-O-6-4	414
6405-O-6-6	414
6405-O-8-6	414
6405-O-8-8	414
640600	120
640600C	127
640800	120
640800C	127
6408-H-O-10	414
6408-H-O-12	414
6408-H-O-14	414
6408-H-O-16	414
6408-H-O-2	414
6408-H-O-20	414
6408-H-O-24	414
6408-H-O-32	414
6408-H-O-4	414
6408-H-O-5	414
6408-H-O-6	414
6408-H-O-8	414
6408-O-10	414
6408-O-12	414
6408-O-14	414
6408-O-16	414
6408-O-2	414
6408-O-20	414
6408-O-24	414
6408-O-4	414
6408-O-5	414
6408-O-6	414
6408-O-8	414
64-100	270
641000	120
641000C	127
64-101	270
64-102	270
64-103	270
64-104	270
64-105	270
64-106	270
64-107	270
64-108	270
64-109	270
6410-O-12-8	414
6410-O-8-4	414
6410-O-8-6	414
6410-O-8-8	414
64-110	270
64-112	270
64-114	270
641200	120
64-122	270
64-123	270
64-124	270
64-126	270
64-127	270
64-130	270
64-131	270
64-133	270
64-134	270
64-136	270
64-137	270
64-138	270
64-140	270
64-141	270
64-142	270
64-145	270
64-146	270
64-148	270
64-160	270
64-161	270
64-162	270
64-163	270
64-164	270
64-165	270
64-166	270
64-167	270
64-168	270
64-169	270
64-170	270
64-171	270
64-180	271
64-181	271
64-182	271
64-183	271
64-184	271
64-185	271
64-186	271
64-187	271
64-188	271
64-189	271
64-190	271
64-191	271
64-192	271
64-200	271
64-201	271
64-202	271
64-203	271
64-204	271
64-205	271
64-206	271
64-207	271
64-208	271
64-209	271
64-210	271
64-211	271
64-250	272
64-251	272
64-252	272
64-253	272
64-254	272
64-255	272
64-256	272
64-257	272
64-258	272
64-259	272
64-260	272
64-261	272
64-262	272
64-268	272
64-269	272
64-273	272
64-276	272
64-279	272
64-280	273
64-282	272
64-283	272
64-286	272
64-289	273

Part#	Page
64-291	272
64-298	272
64-299	273
64-300	273
64-301	272
64-303	272
64-306	272
64-316	272
64-317	273
64-318	272
64-319	273
64-322	272
64-327	272
64-328	272
64-330	272
64-334	272
64-336	272
64-343	272
64-351	272
64-363	273
64-364	273
64-383	273
64-384	273
64-385	273
64-386	273
64-390	271
64-391	271
64-392	271
64-393	271
64-394	271
64-395	271
64-396	271
64-397	271
64-398	271
64-399	271
64-400	271
64-410	274
64-411	274
64-412	274
64-413	274
64-414	274
64-415	274
64-416	274
64-417	274
64-418	274
64-419	274
64-420	274
64-421	274
64-422	274
64-430	274
64-431	274
64-432	274
64-433	274
64-434	274
64-435	274
64-436	274
64-437	274
64-438	274
64-439	274
64-440	274
64-441	274
64-442	274
64-443	274
64-444	274
64-445	274
64-446	274
64-447	274
64-448	274
64-449	274
64-450	274
64-451	274
64-452	274
64-453	274
64-454	274
64-456	274
64-457	274
64-458	274
64-459	274
64-460	274
64-461	274
64-462	274
64-463	274
64-464	274
64-465	274
64-470	276
64-471	276
64-472	276
64-473	276
64-474	276
64-475	276
64-476	276
64-477	276
64-478	276
64-479	276
64-480	276
64-481	276
64-482	276
64-486	274
64-500	275
64-501	275
64-502	275
64-503	275
64-504	275
64-505	275
64-506	275
64-507	275
64-508	275
64-509	275
64-510	275
64-511	275
64-512	275
64-513	275
64-514	275
64-515	275
64-516	275
64-517	275
64-518	275
64-519	275
64-520	275
64-521	275
64-522	275
64-523	275
64-524	275
64-525	275
64-526	275
64-527	275
64-528	275
64-529	275
64-530	275
64-531	275
64-532	275
645320C	127
64-533	275
64-534	275
64-535	275
64-537	275
64-538	275
64-539	275
64-540	275
64-541	275
64-542	275
64-543	275
64-545	275
64-546	275
64-547	275
64-549	275
64-550	275
64-551	275
64-552	275
64-553	275
64-573	277
64-574	277
64-575	277
64-576	277
64-577	277
64-578	277
64-583	277
64-584	277
64-585	277
64-586	277
64-587	277
64-588	277
64-600	276
64-601	276
64-602	276
64-603	276
64-604	276
64-605	276
64-606	276
64-607	276
64-608	276
64-609	276
64-610	276
64-611	276
64-651	276
64-652	276
64-653	276
64-654	276
64-655	276
64-656	276
64-657	276
64-658	276
64-659	276
64-660	276
64-661	276
64-692	278
64-693	278
64-694	278
64-695	278
64-696	278
64-697	278
64-703	277
64-704	277
64-705	277
64-706	277
64-707	277
64-708	277
64-721	272
64-729	272
64-733	273
64-770	267
64-771	267
64-772	267
64-773	267
64-773H	267
64-774	267
64-774H	267
64-775	267
64-775H	267
64-776	267
64-776H	267
64-777	267
64-777H	267
64-778	267
64-778H	267
64-779	267
64-780	267
64-780H	267
64-781	267
64-781H	267
6500-10	415
6500-12	415
6500-16	415
6500-24	415
6500-4	415
6500-6	415
6500-8	415
6501-10-8	415
6501-12-12	415
6501-16-16	415
6501-4-4	415
6501-6-6	415
6501-8-8	415
6502-10	415
6502-12	415
6502-16	415
6502-4	415
6502-6	415
6502-8	415
6503-12-12	415
6503-4-4	415
6503-6-6	415
6503-8-8	415
650400	120
650400C	127
6504-10-10	415
6504-12-12	415
6504-16-16	415
6504-20-20	415
6504-4-4	415
6504-6-6	415
6504-8-8	415
6505-12-12	415
6505-16-16	415
6505-24-24	415
6505-4-2	415
6505-4-4	415
6505-4-6	415
6505-6-4	415
6505-6-6	415
6505-8-6	415
6505-8-8	415
650600	120
650600C	127
6506-10-6	416
6506-12-12	416
6506-16-16	416
6506-20-20	416
6506-4-2	416
6506-4-4	416
6506-6-4	416
6506-6-6	416
6506-6-8	416
6506-8-6	416
6506-8-8	416
650800	120
650800C	127
65-100	270
65-101	270
65-102	270
65-103	270
65-104	270
65-105	270
65-106	270
65-107	270
65-108	270
65-109	270
65-110	270
65-112	270
65-114	270
65-115	270
65-122	270
65-123	270
65-124	270
65-126	270
65-127	270
65-130	270
65-131	270
65-133	270
65-134	270
65-136	270
65-137	270
65-138	270
65-140	270
65-141	270
65-142	270
65-145	270
65-146	270
65-148	270
65-150	270
65-151	270
65-160	270
65-161	270
65-162	270
65-163	270
65-164	270
65-165	270
65-166	270
65-167	270
65-168	270
65-169	270
65-170	270
65-171	270
65-180	271
65-181	271
65-182	271
65-183	271
65-184	271
65-185	271
65-186	271
65-187	271
65-188	271
65-189	271
65-190	271
65-191	271
65-192	271
65-194	271
65-200	271
65-201	271
65-202	271
65-203	271
65-204	271
65-205	271
65-206	271
65-207	271
65-208	271
65-209	271
65-210	271
65-211	271
65-250	272
65-251	272
65-252	272
65-253	272
65-254	272
65-255	272
65-256	272
65-257	272
65-258	272
65-259	272
65-260	272
65-261	272
65-262	272
65-264	272
65-267	273
65-268	272
65-269	272
65-273	272
65-276	272
65-279	272
65-280	273
65-282	272
65-283	272
65-286	272
65-287	273
65-288	273
65-289	273
65-291	272
65-292	273
65-293	273
65-294	273
65-295	273
65-296	273
65-297	273
65-298	272
65-299	273
65-300	273
65-301	272
65-303	272
65-305	273
65-306	272
65-309	273
65-310	273
65-312	273
65-313	273
65-316	272
65-317	273
65-318	272
65-319	273
65-322	272
65-327	272
65-328	272
65-330	272
65-334	272
65-336	272
65-342	272
65-343	272
65-346	273
65-347	273

Part#	Page
65-349	273
65-350	273
65-351	272
65-359	272
65-363	273
65-364	273
65-372	273
65-375	273
65-377	273
65-383	273
65-384	273
65-385	273
65-386	273
65-387	273
65-388	273
65-390	271
65-391	271
65-392	271
65-393	271
65-394	271
65-395	271
65-396	271
65-397	271
65-398	271
65-399	271
65-400	271
65-401	271
65-410	274
65-411	274
65-412	274
65-413	274
65-414	274
65-415	274
65-416	274
65-417	274
65-418	274
65-419	274
65-420	274
65-421	274
65-422	274
65-430	274
65-431	274
65-432	274
65-433	274
65-434	274
65-435	274
65-436	274
65-437	274
65-438	274
65-439	274
65-440	274
65-441	274
65-442	274
65-443	274
65-444	274
65-445	274
65-446	274
65-447	274
65-448	274
65-449	274
65-450	274
65-451	274
65-452	274
65-453	274
65-454	274
65-456	274
65-457	274
65-458	274
65-459	274
65-460	274
65-461	274
65-462	274
65-463	274
65-464	274
65-465	274
65-470	276
65-471	276
65-472	276
65-473	276
65-474	276
65-475	276
65-476	276
65-477	276
65-478	276
65-479	276
65-480	276
65-481	276
65-482	276
65-486	274
65-491	274
65-500	275
65-501	275
65-502	275
65-503	275
65-504	275
65-505	275
65-506	275
65-507	275
65-508	275
65-509	275
65-510	275
65-511	275
65-512	275
65-513	275
65-514	275
65-515	275
65-516	275
65-517	275
65-518	275
65-519	275
65-520	275
65-521	275
65-522	275
65-523	275
65-524	275
65-525	275
65-526	275
65-527	275
65-528	275
65-529	275
65-530	275
65-531	275
65-532	275
655320	120
655320C	127
65-533	275
65-534	275
65-535	275
65-537	275
65-538	275
65-539	275
65-540	275
65-541	275
65-542	275
65-543	275
65-544	275
65-545	275
65-546	275
65-547	275
65-549	275
65-550	275
65-551	275
65-552	275
65-553	275
65-555	275
65-573	277
65-574	277
65-575	277
65-576	277
65-577	277
65-578	277
65-583	277
65-584	277
65-585	277
65-586	277
65-587	277
65-588	277
65-600	276
65-601	276
65-602	276
65-603	276
65-604	276
65-605	276
65-606	276
65-607	276
65-608	276
65-609	276
65-610	276
65-611	276
65-621	278
65-622	278
65-623	278
65-650	276
65-651	276
65-652	276
65-653	276
65-654	276
65-655	276
65-656	276
65-657	276
65-658	276
65-659	276
65-660	276
65-661	276
65-662	276
65-664	276
65-692	278
65-693	278
65-694	278
65-695	278
65-696	278
65-697	278
65-703	277
65-704	277
65-705	277
65-706	277
65-707	277
65-708	277
65-721	272
65-733	273
65-770	267
65770API	268
65-770H	267
65-771	267
65771API	268
65-771H	267
65-772	267
65772API	268
65-772H	267
65-773	267
65773API	268
65-773H	267
65-774	267
65774API	268
65-774H	267
65-775	267
65775API	268
65-775H	267
65-776	267
65776API	268
65-776H	267
65-777	267
65777API	268
65-777H	267
65-778	267
65778API	268
65-778H	267
65-779	267
65779API	268
65-779H	267
65-780	267
65780API	268
65-780H	267
65-781	267
65781API	268
65-781H	267
65-782	267
65-783	267
65783API	268
65784API	268
65-963	277
65-964	277
65-965	277
65-966	277
65-967	277
65-968	277
65-969	277
65-970	277
65-971	277
66000	313
66001	313
6600-10	416
6600-12	416
6600-16	416
66002	313
6600-20	416
66003	313
66004	313
6600-4-4	416
66005	313
66006	313
6600-6-6	416
66007	313
66008	313
6600-8-8	416
66009	313
66010	313
66011	313
66012	313
66013	313
66-015	311
66-015	313
6602-12	416
6602-16	416
6602-24	416
6602-4	416
6602-5	416
6602-6	416
6602-8	416
660402	121
660402C	127
660404	121
660404C	127
660406C	127
660602	121
660602C	127
660604	121
660604C	127
660606	121
660606C	127
660608C	127
660802C	127
660804	121
660804C	127
660806	121
660806C	127
660808	121
660808C	127
66-470	279
66-471	279
66-472	279
66-473	279
66-474	279
66-475	279
66-476	279
66-477	279
66-478	279
66-500	279
66-501	279
66-502	279
66-503	279
66-504	279
66-505	279
66-506	279
66-507	279
66-508	279
66-509	279
66-510	279
66-511	279
66-512	279
66-513	279
665302C	127
665304C	127
66-630	280
66-631	280
66-632	280
66-633	280
66-634	280
66-635	280
66-636	280
66-637	280
66-638	280
66-653	280
66-654	280
66-655	280
66-656	280
66-657	280
66-658	280
66-670	280
66-671	280
66-672	280
66-700	279
66-701	279
66-702	279
66-704	279
66-705	279
66-708	279
66-709	279
66-712	279
66-713	279
66-760	280
66-761	280
66-762	280
66-763	280
66-764	280
66-765	280
66-766	280
66-767	280
66-768	280
66-769	280
66-770	280
66-771	280
66-772	280
66-773	280
66-774	280
66-775	280
66-776	280
66-777	280
66-778	280
67-470	279
67-471	279
67-472	279
67-473	279
67-474	279
67-475	279
67-476	279
67-477	279
67-500	279
67-501	279
67-502	279
67-503	279
67-504	279
67-505	279
67-506	279
67-507	279
67-508	279
67-509	279
67-510	279
67-511	279
67-512	279
67-513	279
67-514	279
67-630	280
67-631	280
67-632	280
67-633	280
67-634	280
67-635	280
67-636	280
67-637	280
67-638	280
67-653	280
67-654	280
67-655	280
67-656	280
67-657	280
67-658	280
67-669	280

Part#	Page
67-670	280
67-671	280
67-672	280
67-700	279
67-701	279
67-702	279
67-703	279
67-704	279
67-705	279
67-707	279
67-708	279
67-709	279
67-711	279
67-712	279
67-713	279
67-760	280
67-761	280
67-762	280
67-763	280
67-764	280
67-765	280
67-766	280
67-767	280
67-768	280
67-769	280
67-770	280
67-771	280
67-772	280
67-773	280
67-774	280
67-775	280
67-776	280
67-777	280
67-778	280
6801-NW0-6-8	417
6801-NWO-10	417
6801-NWO-10-8	417
6801-NWO-12	417
6801-NWO-12-10	417
6801-NWO-12-16	417
6801-NWO-16	417
6801-NWO-20	417
6801-NWO-4	417
6801-NWO-4-6	417
6801-NWO-6	417
6801-NWO-6-4	417
6801-NWO-8	417
6801-NWO-8-10	417
6801-NWO-8-12	417
6801-NWO-8-6	417
6802-NWO-10	417
6802-NWO-10-8	417
6802-NWO-12	417
6802-NWO-16	417
6802-NWO-2	417
6802-NWO-20	417
6802-NWO-4	417
6802-NWO-6	417
6802-NWO-8	417
6802-NWO-8-10	417
6802-NWO-8-6	417
680302	121
6803-NWO-10	417
6803-NWO-12	417
6803-NWO-16	417
6803-NWO-4	417
6803-NWO-6	417
6803-NWO-8	417
680402	121
680402C	128
680404	121
680404C	128
680406	121
680406C	128
680421	121
6804-NWO-10	417
6804-NWO-12	417
6804-NWO-16	417
6804-NWO-4	417
6804-NWO-6	417
6804-NWO-8	417
6805-NWO-10-8	417
6805-NWO-12-12	417
6805-NWO-12-8	417
6805-NWO-16-16	417
6805-NWO-4-4	417
6805-NWO-6-6	417
6805-NWO-8-8	417
680602	121
680602C	128
680604	121
680604C	128
680606	121
680606C	128
680608	121
680608C	128
6806-NWO-12-12	418
6806-NWO-16-16	418
6806-NWO-4-4	418
6806-NWO-6-6	418
6806-NWO-8-8	418
680804	121
680804C	128
680806	121
680806C	128
680808	121
680808C	128
6809-NWO-12-12	418
6809-NWO-4-4	418
6809-NWO-6-6	418
6809-NWO-8-8	418
681006	121
681006C	128
681008	121
681008C	128
681208	121
681208C	128
681212	121
6815-NWO-10-10	418
6815-NWO-12-12	418
6815-NWO-4-4	418
6815-NWO-6-6	418
6815-NWO-8-8	418
685301C	128
685302C	128
685304C	128
685320	121
685321	121
685322	121
6900-O-10-12	418
6900-O-10-8	418
6900-O-12-12	418
6900-O-12-8	418
6900-O-16-16	418
6900-O-4-2	418
6900-O-4-4	418
6900-O-6-4	418
6900-O-6-6	418
6900-O-6-8	418
6900-O-8-12	418
6900-O-8-6	418
6900-O-8-8	418
6901-NWO-10-6	418
6901-NWO-10-8	418
6901-NWO-12-12	418
6901-NWO-12-6	418
6901-NWO-12-8	418
6901-NWO-16-12	418
6901-NWO-16-16	418
6901-NWO-20-20	418
6901-NWO-4-4	418
6901-NWO-6-4	418
6901-NWO-6-6	418
6901-NWO-6-8	418
6901-NWO-8-12	418
6901-NWO-8-4	418
6901-NWO-8-6	418
6901-NWO-8-8	418
6902-NWO-10-8	419
6902-NWO-12-12	419
6902-NWO-12-8	419
6902-NWO-16-16	419
6902-NWO-4-4	419
6902-NWO-6-4	419
6902-NWO-6-6	419
6902-NWO-8-8	419
690302	122
690402	122
690402S	122
690402SC	128
690404	122
690404S	122
690404SC	128
690406	122
690406S	122
690406SC	128
690602	122
690602S	122
690602SC	128
690604	122
690604S	122
690604SC	128
690606	122
690606S	122
690606SC	128
690608	122
690608S	122
690608SC	128
690804	122
690804S	122
690804SC	128
690806	122
690806S	122
690806SC	128
690808	122
690808S	122
690808SC	128
691006	122
691006S	122
691006SC	128
691008	122
691008S	122
691008SC	128
69-101	281
69-102	281
69-103	281
69-104	281
69-105	281
69-106	281
69-107	281
69-108	281
691208	122
691208S	122
691208SC	128
691212	122
691212S	122
69-161	281
69-162	281
69-163	281
69-164	281
69-165	281
69-166	281
69-167	281
69-168	281
69-181	281
69-182	281
69-183	281
69-184	281
69-185	281
69-186	281
69-187	281
69-188	281
69-252	281
69-253	281
69-254	281
69-255	281
69-256	281
69-257	281
69-258	281
69-411	281
69-412	281
69-413	281
69-414	281
69-415	281
69-416	281
69-417	281
69-418	281
69-432	282
69-434	282
69-435	282
69-438	282
69-441	282
69-442	282
69-471	282
69-472	282
69-473	282
69-474	282
69-475	282
69-476	282
69-477	282
69-478	282
695302	122
695322	122
695322S	122
695322SC	128
69-600	282
69-601	282
69-602	282
69-603	282
69-604	282
69-605	282
69-606	282
69-607	282
69-608	282
7000-10-12	423
7000-10-8	423
7000-12-12	423
7000-12-8	423
7000-16-16	423
7000-20-20	423
7000-4-2	423
7000-4-4	423
7000-6-4	423
7000-6-6	423
7000-6-8	423
7000-8-12	423
7000-8-6	423
7000-8-8	423
7002-10-8	424
7002-12-12	424
7002-12-16	424
7002-16-16	424
7002-4-2	424
7002-4-4	424
7002-4-6	424
7002-4-8	424
7002-6-4	424
7002-6-6	424
7002-6-8	424
7002-8-12	424
7002-8-6	424
7002-8-8	424
700402	123
700402SC	128
700404	123
700404S	123
700404SC	128
700406	123
700406SC	128
7005-10-18	425
7005-10-20	425
7005-10-22	425
7005-12-22	425
7005-12-27	425
7005-4-10	425
7005-4-12	425
7005-4-14	425
7005-4-18	425
7005-5-12	425
7005-5-14	425
7005-6-14	425
7005-6-16	425
7005-6-18	425
7005-8-16	425
7005-8-18	425
7005-8-22	425
700602	123
700602C	128
700604	123
700604SC	128
700606	123
700606SC	128
700608SC	128
700804C	128
700806	123
700806SC	128
700808	123
700808SC	128
7022-10-8	425
7022-12-12	425
7022-16-16	425
7022-4-2	425
7022-4-4	425
7022-6-6	425
7022-8-8	425
7025-10-22	426
7025-12-27	426
7025-16-33	426
7025-4-10	426
7025-4-12	426
7025-5-12	426
7025-6-14	426
7025-6-16	426
7025-8-16	426
7042-12-12	425
7042-16-16	425
7042-2-2	425
7042-4-2	425
7042-4-4	425
7042-6-6	425
7042-8-8	425
7045-12-27	426
7045-16-33	426
7045-2-10	426
7045-4-12	426
7045-4-14	426
7045-6-12	426
7045-6-16	426
7045-6-18	426
7045-8-16	426
7045-8-18	426
7045-8-22	426
705302C	128
705304C	128
710402	123
710402S	124
710402SC	129
710404	123
710404S	124
710404SC	129
71040604	123
710604	123
71060404	123
71060406	123
710604S	124
710604SC	129
710606	123
710606S	124
710606SC	129
710608	123
710608SC	129
710804C	129
710804S	124
710806	123
710806S	124
710806SC	129
710808C	129
710808S	124
715301C	129
715302C	129
715304C	129
7200-12-12	423
7200-16-16	423
7200-4-2	423
7200-4-4	423
7200-6-4	423

Part#	Page
7200-6-6	423
7200-6-8	423
7200-8-6	423
7200-8-8	423
7202-NWO-10-8	424
7202-NWO-12-12	424
7202-NWO-12-16	424
7202-NWO-16-16	424
7202-NWO-4-2	424
7202-NWO-4-4	424
7202-NWO-6-4	424
7202-NWO-6-6	424
7202-NWO-6-8	424
7202-NWO-8-12	424
7202-NWO-8-6	424
7202-NWO-8-8	424
720302	124
720402	124
720402S	125
720402SC	129
720404	124
720404S	125
720404SC	129
720406SC	129
7205-NWO-10-18	426
7205-NWO-4-10	426
7205-NWO-4-12	426
7205-NWO-4-14	426
7205NWO-5-12	426
7205-NWO-6-14	426
7205-NWO-6-16	426
7205-NWO-8-16	426
7205-NWO-8-18	426
7205-NWO-8-22	426
720602S	125
720604	124
72060404	124
720604S	125
720604SC	129
720606	124
720606S	125
720606SC	129
720608C	129
720804	124
720804C	129
720804S	125
720806	124
720806S	125
720806SC	129
720808	124
720808S	125
720808SC	129
721006C	129
72100808	124
721008C	129
7240-10	424
7240-12	424
7240-16	424
7240-4	424
7240-6	424
7240-8	424
725301C	129
725302C	129
725304C	129
73-003	314
73-004	314
73-005	314
73-006	314
73-007	314
73-008	314
73-009	314
73-010	314
73-011	314
73-023	314
73-024	314
73-025	314
73-026	314
73-027	314
73-028	314
73-029	314
73-030	314
73-031	314
73-033	314
73-035	314
73-036	314
73-037	314
73-038	314
73-039	314
73-040	314
73-041	314
73-043	314
73-044	314
73-045	314
73-046	314
73-047	314
73-048	314
73-049	314
73-050	314
73-051	314
73-056	314
73-057	314
73-058	314
73-059	314
73-060	314
73-063	314
73-064	314
73-065	314
73-066	314
73-067	314
73-068	314
73-069	314
73-070	314
73-071	314
73-200B	338
73-200N5	337
73-200U	338
73-201B	338
73-201G	338
73-201U	338
73-203B	338
73-203B1	338
73-203B5	338
73-203G	338
73-203G1	338
73-203G5	338
73-203N1	337
73-203N5	337
73-203O	338
73-203R	338
73-203R1	338
73-203R5	338
73-203U	338
73-203U1	338
73-203U5	338
73-203W	338
73-203Y	338
73-204B	338
73-204G	338
73-204N5	337
73-204U	338
73-204Y	338
73-205B	338
73-205B5	338
73-205G	338
73-205R	338
73-205U	338
73-205Y	338
73-206B	338
73-206B1	338
73-206B5	338
73-206G	338
73-206N1	337
73-206N5	337
73-206R	338
73-206R5	338
73-206U	338
73-206U5	338
73-206W	338
73-206Y	338
73-207B	338
73-207B5	338
73-207G	338
73-207N5	337
73-207R	338
73-207U	338
73-207W	338
73-207W5	338
73-207Y	338
73-208B	338
73-230B	339
73-231B	339
73-232B	339
73-232N5	339
73-233B	339
73-238B	339
73-238U	339
73-341B	336
73-341R	336
73-341U	336
73-343B	336
73-343R	336
73-343U	336
73-345B	336
73-345R	336
73-345U	336
73-346B	336
73-346R	336
73-346U	336
73-670	312
73-671	312
73-672	312
73-673	312
73-674	312
73-951	27
73-951	247
73-952	27
73-952	247
73-953	27
73-953	247
73-954	27
73-954	247
73-955	27
73-955	247
73-956	27
73-956	247
73-957	27
73-957	247
73-958	27
73-958	247
73-959	27
73-959	247
73-960	27
73-960	247
73-961	247
73-970	27
73-970	248
73-971	27
73-971	248
73-972	27
73-972	248
73-973	27
73-973	248
73-974	27
73-974	248
73-975	27
73-975	248
73-976	27
73-976	248
73-977	27
73-977	248
73-979	27
73-979	248
73-980	27
73-980	248
73-981	27
73-981	248
73-982	27
73-982	248
73-983	312
73-984	312
73-985	312
73-986	312
73-987	312
7420-10-8	423
7420-12-12	423
7420-12-8	423
7420-16-12	423
7420-16-16	423
7420-2-2	423
7420-4-2	423
7420-6-4	423
7420-6-6	423
7420-8-6	423
7420-8-8	423
7425-10	424
7425-12	424
7425-16	424
7425-2	424
7425-4	424
7425-8	424
7520-10-10	423
7520-12-12	423
7520-2-2	423
7520-4-4	423
7520-6-6	423
7520-8-8	423
770402	125
770402C	129
770404	125
770404C	129
770604	125
770604C	129
770806C	129
771004C	129
77-100	288
77-101	288
77-102	288
77-104	288
77-107	288
77-108	288
77-110	288
77-113	288
77-114	288
77-116	288
77-124	288
77-125	288
77-126	288
77-127	288
77-128	288
77-129	288
77-130	288
77-131	288
77-132	288
77-139	288
77-140	288
77-141	288
77-142	288
77-143	288
77-144	288
77-145	288
77-154	288
77-155	288
77-156	288
77-157	288
77-158	288
77-159	288
77-160	288
77-161	289
77-162	289
77-163	289
77-164	289
77-165	289
77-166	289
77-167	289
77-168	289
77-169	289
77-170	289
77-177	289
77-178	289
77-179	289
77-180	289
77-181	289
77-182	289
77-183	289
77-184	289
77-185	289
77-201	289
77-202	289
77-203	289
77-204	289
77-205	289
77-206	289
77-207	289
77-208	289
77-209	289
77-210	289
77-219	289
77-220	289
77-222	289
77-223	289
77-224	289
77-225	289
77-226	289
77-227	289
77-238	290
77-240	290
77-241	290
77-242	290
77-244	290
77-252	290
77-253	290
77-254	290
77-255	290
77-256	290
77-258	290
77-262	290
77-263	290
77-265	290
77-267	290
77-268	290
77-269	290
77-270	290
77-271	290
77-272	290
77-273	290
77-275	290
77-276	290
77-277	290
77-280	290
77-291	290
77-292	290
77-293	290
77-294	290
77-295	290
77-296	290
77-297	290
77-298	290
77-300	290
77-303	291
77-306	291
77-307	291
77-308	291
77-309	291
77-311	291
77-312	291
77-314	291
77-318	291
77-322	291
77-331	291
77-333	291
77-334	291
77-335	291
77-336	291
77-337	291
77-341	292
77-343	292
77-345	292
77-346	292
77-347	292
77-349	292
77-352	290
77-354	290
77-355	290
77-357	290
77-358	290
77-359	290
77-360	290
77-361	290

Part#	Page
77-363	290
77-365	290
77-393	291
77-394	291
77-395	291
77-398	291
77-401	291
77-402	292
77-406	292
77-410	292
77-413	292
77-419	292
77-420	292
77-423	292
77-424	292
77-429	292
77-430	292
77-431	292
77-432	292
77-433	292
77-434	292
77-435	292
77-436	292
77-437	292
77-453	292
77-454	292
77-455LF	292
77-456LF	292
77-457LF	292
77-461	292
77-462	292
77-463	292
77-464	292
77-467	293
77-468	293
77-470	293
77-473	293
77-481	293
77-483	293
77-485	293
77-486	293
77-488	293
77-489	293
77-490	293
77-493	293
77-496	293
77-498	293
77-499	293
77-501	293
77-504	293
77-506	293
77-507	293
77-508	293
77-514	293
77-518	293
77-519	293
77-522	293
77-523	293
77-543	293
77-547	293
77-548	293
77-549	293
77-606LF	292
77-607LF	292
77-608LF	292
7802-12	424
7802-16	424
7802-4	424
7802-6	424
7802-8	424
7825-12	424
7825-16	424
7825-2	424
7825-4	424
7825-6	424
7825-8	424
80-001	367
80-002	367
80-003	367
80-004	367
80-005	367
80-006	367
80-007	367
80-020	367
80-031	367
80-032	367
80-033	367
80-034	367
80-035	367
80-036	367
80-061	368
80-062	368
80-063	368
80-064	368
80-065	368
80-066	368
80-067	368
80-068	368
80-069	368
80-080	368
80-081	368
80-100	368
80-101	368
80-102	368
80-103	368
80-104	368
80-105	368
80-201	368
80-202	368
80-203	368
80-204	368
80-205	368
80-206	368
80-207	368
80-208	368
80-209	368
80-301	367
80-302	367
80-303	367
80-304	367
80-305	367
80-306	367
80-307	367
80-331	367
80-332	367
80-333	367
80-334	367
80-335	367
80-336	367
80-463	368
80-501	367
80-502	367
80-503	367
80-504	367
80-505	367
80-506	367
80-511	367
80-512	367
80-513	367
80-514	367
80-515	367
80-516	367
80-601	368
80-602	368
80-603	368
80-604	368
80-605	368
80-606	368
80-611	368
80-612	368
80-613	368
80-614	368
80-615	368
80-616	368
820400	125
820400C	130
820600	125
820600C	130
820800	125
820800C	130
821000	125
821000C	130
825320C	130
830808	125
840-1088	322
840-131	322
840-150	322
840-175	322
840-188	322
840-200	322
840-225	322
840-238	322
840-250	322
840-256	322
840-263	322
840-275	322
840-288	322
840-300	322
840-312	322
840-325	322
840-350	322
840-375	322
840-382	322
840-400	322
840-425	322
840-450	322
840-475	322
840-500	322
840-525	322
840-550	322
840-575	322
840-600	322
840-625	322
840-650	322
840-675	322
840-700	322
840-750	322
840-800	322
840-850	322
840-888	322
841-004	325
841-005	325
841-040	325
841-045	325
841-050	325
841-175	325
841-200	325
841-250	325
841-300	325
841-350	325
841-400	325
841-450	325
841-500	325
842-010	324
842-012	324
842-016	324
842-020	324
842-024	324
842-200	324
842-250	324
842-300	324
842-350	324
842-400	324
842-450	324
842-500	324
843-321	324
843-382	324
843-388	324
843-450	324
843-461	324
843-475	324
843-525	324
843-588	324
844-213	323
844-225	323
844-238	323
844-250	323
844-263	323
844-275	323
844-300	323
844-306	323
844-313	323
844-325	323
844-338	323
844-350	323
844-356	323
844-363	323
844-375	323
844-406	323
844-413	323
844-425	323
844-456	323
844-500	323
844-525	323
844-600	323
844-625	323
845-200	326
845-300	326
845-350	326
845-400	326
845-500	326
845-500SS	326
845-600	326
846-200	326
846-250	326
846-275	326
846-300	326
846-350	326
846-400	326
846-500	326
847-200	326
847-250	326
847-275	326
847-300	326
847-350	326
847-400	326
847-500	326
847-600	326
848-200	326
848-225	326
848-250	326
848-275	326
848-300	326
848-350	326
848-400	326
848-500	326
848-600	326
848-700	326
8555-H-10	426
8555-H-12	426
8555-H-14	426
8555-H-16	426
8555-H-18	426
8555-H-20	426
8555-H-22	426
8555-H-26	426
8555-H-30	426
8555-P-10	426
8555-P-12	426
8555-P-14	426
8555-P-16	426
8555-P-18	426
8555-P-20	426
8555-P-22	426
8555-P-26	426
8555-P-30	426
86-001	347
86-002	347
86-005	347
86-006	347
86-012	347
86-013	347
86-017	347
86-018	347
86-020	347
86-022	347
86-030	346
86-030RG	347
86-030SS	346
86-031	346
86-031RG	347
86-031SS	346
86-032	346
86-035	346
86-035RG	347
86-035SS	346
86-036	346
86-036RG	347
86-036SS	346
86-037	346
86-040	346
860402	125
860402C	130
860404	125
860404C	130
86-040SS	346
86-041	346
86-041SS	346
86-042	346
86-045	346
86-045SS	346
86-046	346
86-046SS	346
86-047	346
860604	125
860604C	130
860606	125
860606C	130
860806C	130
860808	125
860808C	130
865304C	130
87001	359
87002	359
87003	359
87004	359
87008	359
87009	359
87020	359
87021	359
87023	359
87-400	364
87-402	364
87-404	364
87-406	364
87-408	365
87-410	365
87-412	365
87-414	366
87-416	366
87-418	366
87-420	366
87-422	366
88-024	332
88-028	332
88-032	332
88-038	332
880402C	130
880406C	130
880408C	130
88-050	332
88-056	332
88-065	332
88-075	332
88-085	332
88-095	332
88-112	332
89-024	332
89-028	332
89-032	332
89-038	332
89-044	332
89-050	332
89-056	332
89-065	332
89-075	332
89-085	332
89-095	332
89-112	332
899000	212
899001	212
899002	212
899003	212
899004	212
899005	212
899050	212
899051	212
899052	212

Part#	Page
899053	212
899054	212
899055	212
90-001	283
90-002	283
90-003	283
90-004	283
90-005	283
90-006	283
90-007	283
90-008	283
90-009	283
90-010	283
90-011	283
90-100	284
90-102	284
90-103	284
90-104	284
90-105	284
90-106	284
90-107	284
90-108	284
90-109	284
90-110	284
90-111	284
90-114	284
90-115	284
90-116	284
90-117	284
90-118	284
90-119	284
90-120	284
90-121	284
90-122	284
90-123	284
90-124	284
90-125	284
90-126	284
90-127	284
90-128	284
90-129	284
90-130	284
90-131	284
90-132	284
90-133	284
90-140	284
90-141	284
90-150	284
90-152	284
90-212	283
90-213	283
90-215	283
91-007	283
91-008	283
91-009	283
91-010	283
91-011	283
91-707	340
92-010	332
92-011	332
92-012	332
92-013	332
92-014	332
92-015	332
92-016	332
92-017	332
92-102	284
92-107	284
92-108	284
92-109	284
92-110	284
92-111	284
92-114	284
92-115	284
92-116	284
92-119	284
92-120	284
92-121	284
92-122	284
92-123	284
92-128	284
93-001	283
93-008	332
93-009	332
93-011	332
93-013	332
93-014	332
93-016	332
93-017	332
93-113	283
93-121	283
93-122	283
93-123	283
93-124	283
93-125	283
93-127	283
93-128	283
93-129	283
93-130	283
93-131	283
93-139	283
93-212	283
935044LF	167
935045LF	167
940-121	190
940-122	190
940-123	190
940-130	192
940-130LF	172
940-131	192
940-131LF	172
940-132	192
940-132LF	172
940-133	192
940-133LF	172
940-134	192
940-134LF	172
940-135	192
940-135LF	172
940-136	192
940-136LF	172
940-137	192
940-137LF	172
940-138	192
940-139	192
940-140	192
940-142LF	172
940-143LF	172
940-144LF	172
940-145LF	172
940-146LF	172
940-147LF	172
940-171	173
940-171L	174
940-171LF	170
940-171T	175
940-172	173
940-172L	174
940-172LF	170
940-172T	175
940-173	173
940-173L	174
940-173LF	170
940-173T	175
940-174	173
940-174L	174
940-174LF	170
940-174T	175
940-175	173
940-175L	174
940-175LF	170
940-176	173
940-176L	174
940-176LF	170
940-177	173
940-177L	174
940-177LF	170
940-178	173
940-178L	174
940-178LF	170
940-179	173
940-179LF	170
940-180	173
940-180LF	170
940-181	173
940-181LF	170
940-212LF	171
940-213LF	171
940-214LF	171
940-215LF	171
940-216LF	171
940-217LF	171
940-281	212
940-282	212
940-284	212
940-285	212
940-286	212
940-287	212
940-288	212
940-289	212
940-291	212
940-292	212
940-294	212
940-295	212
940-296	212
940-297	212
940-298	212
940-299	212
940-300	212
940-301	212
940-302	212
940-325	213
940-326	213
940-327	213
940-328	213
940-329	213
940-330	213
940-331	213
940-332	213
940-333	213
940-334	213
940-335	213
940-336	213
940-352	195
940-352B	195
940-352LF	172
940-353	195
940-353B	195
940-353LF	172
940-354	195
940-354B	195
940-354LF	172
940-355	195
940-355B	195
940-355LF	172
940-356	195
940-356B	195
940-356LF	172
940-357	195
940-357B	195
940-357LF	172
940-358	195
940-359	195
940-360	195
940-362LF	172
940-363LF	172
940-364LF	172
940-365LF	172
940-366LF	172
940-367LF	172
940-461	190
940-462	190
940-464	190
940-465	190
940-521	194
940-522	194
940-523	194
940-523LF	172
940-524	194
940-525	194
940-526	194
940-527	194
940-528	194
940-529	194
940-530	194
940-800	356
940-801	356
940-803	356
940-804	356
940-805	356
940-806	356
940-810	357
940-811	357
940-812	357
940-813	357
940-814	357
940-815	357
940-822	357
940-823	357
940-824	357
940-825	357
940-826	357
940-827	357
940-840	357
940-841	357
940-842	357
940-843	357
940-844	357
940-845	357
940-846	357
940-847	357
940-848	357
941-121NP	177
941-122NP	177
941-123NP	177
941-124NP	177
941-125NP	177
941-126NP	177
941-127NP	177
941-128NP	177
941-133	193
941-134	193
941-135	193
941-136	193
941-137	193
941-138	193
941-140	193
941-141	193
941151LF	169
941151NP	176
941152LF	169
941152NP	176
941153LF	169
941153NP	176
941154LF	169
941154NP	176
941155LF	169
941155NP	176
941156LF	169
941156NP	176
941157LF	169
941157NP	176
941158LF	169
941158NP	176
941163LF	169
941164LF	169
941165LF	169
941166LF	169
941167LF	169
941168LF	169
942-100	191
942-101	191
942-102	191
942-142	191
942-170	191
942-171	191
942-208	178
942-209	178
942-210	178
943-200	178
943-201	178
943-202	178
943-203	178
943-204	178
943-205	178
943-206	178
943-207	178
943-212	185
943-213	185
943-233LF	171
943-234LF	171
943-235LF	171
943-236LF	171
943-237LF	171
943-238LF	171
943-284	191
943-287	191
943-311	185
943-312	185
943-313	185
943331	185
943332	185
943342	185
943343	185
943344	185
943345	185
943347	185
943348	185
943350	185
943351	185
943-612LF	170
943-613LF	170
943-614LF	170
943-615LF	170
943-616LF	170
943-617LF	170
944-100	189
944-101	189
944-102	189
944-103	189
944-104	189
944-106	189
944-107	189
944-109	189
944-110	189
944-112	189
944-113	189
944-116	189
944-117	189
944-128	189
944-130	189
944-132	189
944-134	189
944-134LF	161
944-134LF	189
944-135	189
944-136	189
944-138	189
944-139	189
944-140	189
944-142	189
944-142LF	161
944-142LF	189
944-401	197
944-402	197
944-402V	197
944-403	197
944-403V	197
944-404	197
944-404V	197
944-405	197
944-405V	197
944-406	197
944-406V	197
944-407	197
944-407V	197
944-408	197
944-408V	197
944-409	197
944-409V	197
944-410	197
944-410V	197
944-411	197
944-411V	197
944-428	196
944-429	196
944-430	196
944-430LF	172

Part#	Page
944-431	196
944-431LF	172
944-432	196
944-432LF	172
944-433	196
944-433LF	172
944-434	196
944-434LF	172
944-435	196
944-435LF	172
947-055	191
947-055LF	191
947-103	183
947-104	183
947-105	183
947-111	183
947-112	183
947-113	183
947-125	184
947-126	184
947-133	191
947-134	191
947-140	196
947-141	196
947-142	196
947-143	196
947-144	196
947-145	196
948-101	180
948-102	180
948-103	180
948-104	180
948-105	180
948-106	180
948-107	180
948-108	180
948-131	184
948-132	184
948-133	184
948-134	184
948-135	184
948-141	184
948-142	184
948-143	184
948-144	184
948-170	179
948-170L	182
948-170T	181
948-171	179
948-171L	182
948-171T	181
948-172	179
948-172L	182
948-172T	181
948-173	179
948-173L	182
948-173T	181
948-174	179
948-174L	182
948-174T	181
948-175	179
948-175L	182
948-176	179
948-176L	182
948-176T	181
948-177	179
948-177L	182
949-101	199
949-102	199
949-103	199
949-104	199
949-105	199
949-106	199
949-107	199
949-108	199
949-111	209
949-112	209
949-113	209
949-114	209
949-115	209
949-116	209
949-117	209
949-118	209
949-121	208
949-122	208
949-123	208
949-124	208
949-125	208
949-126	208
949-127	208
949-128	208
949-161	200
949-162	200
949-163	200
949-164	200
949-165	200
949-166	200
949-167	200
949-168	200
949-170	200
949-171	198
949-172	198
949-173	198
949-174	198
949-175	198
949-176	198
949-177	198
949-178	198
949-180	200
949-253	207
949-254	207
949-255	207
949-256	207
949-257	207
949-258	207
949-303	207
949-304	207
949-305	207
949-306	207
949-307	207
949-308	207
949-353	207
949-354	207
949-355	207
949-356	207
949-357	207
949-358	207
949-401	204
949-402	204
949-403	204
949-404	204
949-405	204
949-406	204
949-407	204
949-408	204
949-430	203
949-431	203
949-432	203
949-441	206
949-442	206
949-443	206
949-444	206
949-445	206
949-446	206
949-447	206
949-448	206
949-451	205
949-452	205
949-453	205
949-454	205
949-455	205
949-471	205
949-472	205
949-473	205
949-474	205
949-475	205
949-481	206
949-482	206
949-483	206
949-484	206
949-485	206
949-486	206
949-487	206
949-488	206
949-521	207
949-522	207
949-523	207
949-524	207
949-525	207
949-526	207
949-527	207
949-528	207
9508-12	423
9508-16	423
9508-2	423
9508-4	423
9508-6	423
9508-8	423
9522-H-12	425
9522-H-16	425
9522-H-2	425
9522-H-4	425
9522-H-6	425
9522-H-8	425
9522-P-12	425
9522-P-16	425
9522-P-2	425
9522-P-4	425
9522-P-6	425
9522-P-8	425
95-300	333
95-301	333
95-302	333
95-303	333
95-304	333
95-305	333
95-306	333
95-307	333
95-308	333
95-309	333
95-310	333
95-311	333
95-312	333
95-313	333
95-314	333
95-315	333
95-316	333
95-317	333
95-318	333
95-319	333
95-320	333
95-321	333
95-322	333
95-323	333
95-324	333
95-325	333
95-326	333
95-327	333
95-328	333
95-329	333
95-330	333
95-331	333
95402	333
95404	333
95406	333
95408	333
95410	333
95414	333
95418	333
95422	333
95424	333
95427	333
95432	333
95433	333
95434	333
95450	388
95451	388
95452	388
95504	333
95506	333
95508	333
95510	333
95512	333
95514	333
95516	333
95518	333
95522	333
95523	333
95524	333
95601	389
95602	389
95603	389
95604	389
95605	389
95606	389
95610	389
95611	389
95612	389
95613	389
95620	390
95621	390
95622	390
95623	390
95624	390
95625	390
95626	390
95627	390
95628	390
95631	373
95640	373
95641	373
96022	332
96027	332
96032	332
96040	332
96050	332
96060	332
96070	332
96080	332
96090	332
96100	332
96110	332
96120	332
96130	332
96140	332
96150	332
96160	332
96-301	333
96-302	333
96-303	333
96-304	333
96-305	333
96-306	333
96-307	333
96-308	333
96-310	333
96-312	333
96-314	333
96-316	333
96-318	333
96-320	333
96-322	333
96-323	333
970-300	232
970-301	232
970-302	232
970-303	232
970-304	232
970-305	232
970-306	232
970-307	232
970-308	232
970-309	232
970-310	232
970-311	232
970-312	232
970-313	232
970-314	232
970-330	232
970-331	232
970-332	232
970-333	232
970-700	232
970-701	232
970-702	232
970-703	232
970-704	232
970-705	232
970-706	232
970-707	232
972-171	341
972-172	341
972-173	341
972-180	341
972-181	341
972-182	341
972-183	341
972-184	341
972-185	341
972-186	341
972-187	341
972-190	341
972-191	341
972-192	341
972-193	341
972-194	341
972-195	341
973-200	337
973-201	337
973-203	337
973-204	337
973-205	337
973-206	337
973-207	337
973-208	337
973-210	337
973-211	337
973-215	340
973-216	340
973-217	340
973-219	340
973-221	340
973-223	340
973-224	340
973-226	339
973-230	339
973-231	339
973-232	339
973-233	339
973-234	339
973-238	339
973-252	340
973-253	340
973-255	340
973-262	340
973-323	339
973-325	339
973-326	339
973-327	339
973-329	339
973-332	339
973-334	339
973-341	336
973-343	336
973-345	336
973-346	336
973-567	257
973-568	257
973-569	257
973-600	312
973-601	312
973-602	312
973-603	312
973-604	312
973-605	312
973-606	312
973-607	312
973-620	312
973-621	312
973-622	312
973-623	312
973-624	312
973-625	312
973-626	312
973-627	312
973-628	312
973-650	312
973-651	312

Part#	Page
973-652	312
973-653	312
973-654	312
973-655	312
973-656	312
973-657	312
973-658	312
973-659	312
973-667	257
973-668	257
973-669	257
973-700	312
973-701	312
973-702	312
973-703	312
973-704	312
973-705	312
973-706	312
973-707	312
973-708	312
973-850	312
973-851	312
973-852	312
973-853	312
973-854	312
973-855	312
973-856	312
973-857	312
973-858	312
973-859	312
973-861	312
973-862	312
973-863	312
973-864	312
973-865	312
973-866	312
973-867	312
973-868	312
973-869	312
973-870	312
973-871	312
973-872	312
973-873	312
973-874	312
973-875	312
973-876	312
973-877	312
973-878	312
973-879	312
973-880	312
973-881	312
973-884	312
973-885	312
973-886	312
973-887	312
973-888	312
973-890	312
973-891	312
973-892	312
973-893	312
973-894	312
973-895	312
973-900	233
973-901	233
973-902	233
973-903	233
973-904	233
973-905	233
973-906	233
973-907	233
973-908	233
973-909	233
973-910	233
973-911	233
973-912	233
973-913	233
973-914	233
973-925	233
973925SS	234
973926SS	234
973-927	233
973927SS	234
973-928	233
973928SS	234
973-929	233
973-930	233
973930SS	234
973947SS	234
973-948	233
973948SS	234
973-949	233
973949SS	234
973-951	27
973-951	247
973-952	27
973-952	247
973-953	27
973-953	247
973-954	27
973-954	247
973-955	27
973-955	247
973-956	27
973-956	247
973-957	27
973-957	247
973-958	27
973-958	247
973-959	27
973-959	247
973960LF	234
973961LF	234
973962LF	234
973963LF	234
973-965	233
973965LF	234
973-966	233
973966LF	234
973-967	233
973967LF	234
973969LF	234
973970LF	234
973971LF	234
973-975	233
973975LF	234
973-976	233
973976LF	234
973-977	233
973-978	233
973-979	233
973-980	233
973980SS	234
973-981	233
973-982	233
973982SS	234
973985SS	234
973-990	27
973-990	247
973-991	27
973-991	247
974-264	233
974-265	233
974-266	233
974-267	233
979-215	167
982-107	370
982-108	370
982-109	370
982-110	370
982-120	370
982-121	370
982-122	370
982-125	370
982-126	370
982-127	370
982-130	370
982-131	370
982-132	370
982-135	370
982-136	370
982-137	370
982-138	370
982140	370
983100	370
983101	370
983102	370
983110	370
983111	370
983115	370
983116	370
983120	370
983121	370
983125	370
983126	370
983130	370
98-801	350
98-802	350
98-810	349
98-811	349
98-812	349
98-814	350
98-815	350
98-823	349
98-824	349
98-825	349
98-828	350
98-830	350
98-840	349
98-841	349
98-842	350
990-570	340
990-571	340
990-781	257
990-782	257
990-783	257
990-784	257
990-785	257
990-786	257
990790	390
990791	390
990792	390
990793	390
990794	390
991-249	369
991-250	369
991-251	369
991-259	369
995-210	369
995-211	369
995-212	369
995-213	369
995-214	369
995-215	369
995-216	369
995-217	369
99-803	350
99-804	350
99-812	349
99-813	349
99-816	350
99-817	350
99-825	349
99-826	349
99-828	350
99-830	350
99-841	349
99-843	349
ANV-12-F	427
ANV-12-M	427
ANV-14-F	427
ANV-14-M	427
ANV-1-F	427
ANV-1-M	427
ANV-34-F	427
ANV-34-M	427
ANV-38-F	427
ANV-38-M	427
AR2	358
BG-100	311
BG-125	311
BG-150	311
BG-200	311
BG-250	311
BG-300	311
BG-400	311
BG-50	311
BG-500	311
BG-600	311
BG-75	311
BG-800	311
CS-3751	330
CS-5001	330
CS-6251	330
CS-7501	330
DX140030MG	343
DX140040MG	343
DX140050MG	343
DX140060MG	343
DX140070MG	343
DX141530MG	343
DX141540MG	343
DX141550MG	343
DX141560MG	343
DX141570MG	343
DX142530MG	343
DX142540MG	343
DX142550MG	343
DX142560MG	343
DX142570MG	343
DX144030MG	343
DX144040MG	343
DX144050MG	343
DX144060MG	343
DX144070MG	343
DX250030	343
DX250040	343
DX250050	343
DX250060	343
DX251530	343
DX251540	343
DX251550	343
DX251560	343
DX252530	343
DX252540	343
DX252550	343
DX252560	343
DX254030	343
DX254040	343
DX254050	343
DX254060	343
DX256500	343
DX259520	343
DX259530	343
DX259540	343
DX259550	343
DX259560	343
DX259570	343
DX35TR25	344
DX35TR38	344
DX4324	345
DX4336	345
DX4424	345
DX4436	345
DX4524VG	345
DX4536VG	345
DX5005	345
DX5006	345
DX5022	345
DX5090	345
DX5190	345
DX5197	345
DX60021	344
DX60021V	344
DX60022	344
DX60022V	344
DX60023	344
DX60023V	344
DX60092	344
DX722530	344
DX722540	344
DX722550	344
DX722560	344
DX723230	344
DX723240	344
DX723250	344
DX723260	344
DX724030	344
DX724040	344
DX724050	344
DX724060	344
DX725030	344
DX725040	344
DX725050	344
DX725060	344
F-10	329
F-100	331
F-11	329
F-12	329
F-14	329
F-16	329
F-18	329
F-20	329
F-3	329
F-311	329
F-38	331
F-4	329
F-40	331
F-5	329
F-6	329
F-7	329
F-8	329
F-9	329
FF-1012F	428
FF-1234-F	428
FF-1234-M	428
FF-12-F	428
FF-12-M	428
FF-14-F	428
FF-14-M	428
FF-1-F	428
FF-1-M	428
FF-3416-F	428
FF-3416-M	428
FF-34-F	428
FF-34-M	428
FF-3812-F	428
FF-3812-M	428
FF-38-F	428
FF-38-M	428
FLJS-203	330
FLJS-204	330
FLJS-205	330
FLJS-207	330
FLJS-208	330
FLJS-209	330
FS-10	329
FS-11	329
FS-12	329
FS-14	329
FS-16	329
FS-18	329
FS-20	329
FS-24	329
FS2500-10-10	421
FS2500-12-12	421
FS2500-16-16	421
FS2500-4-4	421
FS2500-6-6	421
FS2501-12-12	421
FS2501-16-16	421
FS2501-20-20	421
FS2501-4-4	421
FS2501-6-4	421
FS2501-6-6	421
FS2501-8-6	421
FS2501-8-8	421
FS2503-12-12	421
FS2503-16-16	421
FS2503-4-4	421
FS2503-6-6	421
FS2503-8-8	421
FS2603-12-12	421
FS2603-4-4	421
FS2603-6-6	421
FS2603-8-8	421
FS-28	329
FS-4	329
FS-5	329

Part#	Page
FS-6	329
FS6400-O-10-10	422
FS6400-O-10-8	422
FS6400-O-12-10	422
FS6400-O-12-12	422
FS6400-O-12-16	422
FS6400-O-12-8	422
FS6400-O-16-12	422
FS6400-O-16-16	422
FS6400-O-20-20	422
FS6400-O-24-24	422
FS6400-O-4-4	422
FS6400-O-4-6	422
FS6400-O-6-4	422
FS6400-O-6-6	422
FS6400-O-6-8	422
FS6400-O-8-6	422
FS6402-10-10	422
FS6402-12-12	422
FS6402-4-4	422
FS6402-6-6	422
FS6402-8-8	422
FS6500-12-12	422
FS6500-4-4	422
FS6500-6-6	422
FS6500-8-8	422
FS6504-10-10	422
FS6504-16-16	422
FS6504-4-4	422
FS6504-6-6	422
FS6504-8-8	422
FS6801-12-12	422
FS6801-16-16	422
FS6801-20-20	422
FS6801-4-4	422
FS6801-6-6	422
FS6801-8-6	422
FS6801-8-8	422
FS6802-10-10	422
FS6802-12-12	422
FS6802-16-16	422
FS6802-20-20	422
FS6802-4-4	422
FS6802-6-6	422
FS6802-8-8	422
FS6809-12-12	423
FS6809-4-4	423
FS6809-6-6	423
FS6809-8-8	423
FS-7	329
FS-8	329
FS-9	329
FSO2403-12-12	420
FSO2403-16-16	420
FSO2403-4-4	420
FSO2403-6-6	420
FSO2403-8-8	420
FSO2404-12-12	420
FSO2404-16-16	420
FSO2404-4-4	420
FSO2404-6-4	420
FSO2404-6-6	420
FSO2404-8-4	420
FSO2404-8-8	420
FSO2406-10-6	421
FSO2406-10-8	421
FSO2406-12-6	421
FSO2406-6-4	421
FSO2406-8-4	421
FSO2408-10	421
FSO2408-12	421
FSO2408-16	421
FSO2408-20	421
FSO2408-24	421
FSO2408-4	421
FSO2408-6	421
FSO2408-8	421
FSO304-C-10	420
FSO304-C-12	420
FSO304-C-16	420
FSO304-C-20	420
FSO304-C-24	420
FSO304-C-4	420
FSO304-C-6	420
FSO304-C-8	420
FSO306-12	420
FSO306-16	420
FSO306-4	420
FSO306-6	420
FSO306-8	420
FSO318-10	419
FSO318-12	419
FSO318-16	419
FSO318-20	419
FSO318-24	419
FSO318-4	419
FSO318-6	419
FSO318-8	419
FSO319-10	420
FSO319-12	420
FSO319-16	420
FSO319-20	420
FSO319-24	420
FSO319-4	420
FSO319-6	420
FSO319-8	420
GB2-20T-SAE+	210
GB2-24T-SAE+	210
GB2-32T-SAE+	210
GB3L-20T-SAE+	210
GB3L-24T-SAE+	210
GB3L-32T-SAE+	210
GE2-04-SAE	210
GE2-06-SAE	210
GE2-08-SAE	210
GE2-112T-NPT	210
GE2-114T-NPT	210
GE2-12-NPT	210
GE2-12-SAE	210
GE2-14-NPT	210
GE2-16-SAE	210
GE2-1-NPT	210
GE2-2T-NPT	210
GE2-34-NPT	210
GE2-38-NPT	210
GE3L-04-SAE	210
GE3L-06-SAE	210
GE3L-08-SAE	210
GE3L-112T-NPT	210
GE3L-114T-NPT	210
GE3L-12-NPT	210
GE3L-12-SAE	210
GE3L-14-NPT	210
GE3L-16-SAE	210
GE3L-1-NPT	210
GE3L-2T-NPT	210
GE3L-34-NPT	210
GE3L-38-NPT	210
GT15	369
GT30	369
GT60	369
HNV-12-F	427
HNV-12-F-B	427
HNV-12-M	427
HNV-12-M-B	427
HNV-14-F	427
HNV-14-F-B	427
HNV-14-M	427
HNV-14-M-B	427
HNV-1-F	427
HNV-1-F-B	427
HNV-1-M	427
HNV-1-M-B	427
HNV-34-F	427
HNV-34-F-B	427
HNV-34-M	427
HNV-34-M-B	427
HNV-38-F	427
HNV-38-F-B	427
HNV-38-M	427
HNV-38-M-B	427
K-10	329
K-11	329
K-12	329
K-14	329
K-16	329
K-18	329
K-20	329
K-24	329
K-28	329
K-3	329
K-311	329
K-4	329
K-5	329
K-6	329
K-7	329
K-8	329
K-9	329
KS-10	329
KS-11	329
KS-12	329
KS-14	329
KS-16	329
KS-18	329
KS-20	329
KS-3	329
KS-311	329
KS-4	329
KS-5	329
KS-6	329
KS-7	329
KS-8	329
KS-9	329
KZE-B-14-PF	429
KZE-B-14-SM	429
KZE-B-38-PF	429
KZE-B-38-SM	429
LSQ-VEP-12-PF	428
LSQ-VEP-12-SF	428
LSQ-VEP-1-PF	428
LSQ-VEP-1-SF	428
LSQ-VEP-20-PF	428
LSQ-VEP-20-SF	428
LSQ-VEP-24-PF	428
LSQ-VEP-24-SF	428
LSQ-VEP-34-PF	428
LSQ-VEP-34-SF	428
MB40-04	431
MB40-06	431
MB40-08	431
MB40-12	431
MB40-16	431
MFC-12-N	431
MFC-34-N	431
MFC-38-N	431
MMFC12NPT	430
MMFC16NPT	430
MMFC20NPT	430
MMFC4NPT	430
MMFC6NPT	430
MMFC8NPT	430
MMNV12NPT	430
MMNV16NPT	430
MMNV4NPT	430
MMNV6NPT	430
MMNV8NPT	430
NV-12-F	429
NV-12-M	429
NV-14-F	429
NV-14-M	429
NV-1-F	429
NV-1-M	429
NV-34-F	429
NV-34-M	429
NV-38-F	429
NV-38-M	429
SG300	311
SG400	311
SG-5000	330
SS-3751	330
SS-5001	330
SS-6251	330
SS-7501	330
VG100	311
VG150	311
VG200	311
VG250	311
VG300	311
VG400	311