

STAINLESS STEEL SELF LOCKING CAM & GROOVE

- Automatic Self-Locking Arms Prevent Accidental Disconnection
- Machined multi-serrated shank with interlocking groove
- Aluminum with Brass Self Locking Arms
- 316 Stainless with Investment Cast Self-Locking Arms
- Available in sizes 2" through 6"
- 2" @250 psi 3" & 4" @150 psi 6" @75 psi
- 6" @150 psi 4 arms
- Configurations
 - Dust Cap
 - Part B
 - Part C
 - Part D

Sample item code	Description
CDCL-XXX-SS1	X" DUST CAP STAINLESS CRIMPLOK 316 SELF LOCKING
CGBSL-XXX-SS1	X" PART B STAINLESS CRIMPLOK 316 SELF LOCKING
CGCSL-XXXCR-SS1	X" PART C STAINLESS 316 CRIMPLOK SELF LOCKING
CGDSL-XXX-SS1	X" PART D STAINLESS CRIMPLOK 316 SELF LOCKING

Designed for use with Buchanan Crimp Sleeves and Interlocking Ferrules

FEMALE COUPLER X MALE NPT
TYPE B

CGBSL



PART#	SIZE
CGBSL-200-SS1	2"
CGBSL-300-SS1	3"
CGBSL-400-SS1	4"
CGBSL-600-SS1	6"

FEMALE COUPLER X FEMALE NPT
TYPE D

CGDSL



PART#	SIZE
CGDSL-200-SS1	2"
CGDSL-300-SS1	3"
CGDSL-400-SS1	4"
CGDSL-600-SS1	5"

FEMALE COUPLER X HOSE SHANK
TYPE C

CGCSL



PART#	SIZE
CGCSL-200CR-SS1	2"
CGCSL-300CR-SS1	3"
CGCSL-400CR-SS1	4"
CGCSL-600CR-SS1	6"

DUST CAP
TYPE DC

CDCSL



PART#	SIZE
CDCSL-200-SS1	2"
CDCSL-300-SS1	3"
CDCSL-400-SS1	4"
CDCSL-600-SS1	5"