

GAS BALL VALVES

VALVES



CSA AGA 3.88 5 PSIG

- Material: C37700
- Forged brass, Regular port, Thread*Flare Thread
- Thread ends in ANSI B1.20.1
- Working temperature: 0-65°(32-149°)
- Pressure :1/2PSI;5PSI;

GAS BALL VALVES


ISO 9002 MANUFACTURER
FEATURES

- ASME B16.44/CR91; ANSI Z21.15/CSA9.1
- UL 125 For LP-Gas 125psig
- Made in China



GAS BALL VALVE (2-PIECE)
FEMALE X FEMALE

| PART# | SIZE | WTG | BOX/CASE | |
|--------|------|------|----------|------|
| 943311 | 3/8" | 0.35 | 10/100 | ---- |
| 943312 | 1/2" | 0.44 | 10/100 | |
| 943313 | 3/4" | 0.62 | 10/100 | ---- |
| 943314 | 1" | | | |



| NO. | ITEM | TOTAL | MATERIAL |
|-----|-----------------|-------|--------------|
| 10 | BALL VALVE CAP | 1 | BRASS |
| 9 | HANDLE | 1 | AL-alloy |
| 8 | PACKING | 1 | PTFE |
| 7 | HANDLE NUT | 1 | PLATED STEEL |
| 6 | STEM | 1 | BRASS |
| 5 | PACKING NUT | 1 | BRASS |
| 4 | O-RING | 1 | NBR |
| 3 | BALL | 1 | BRASS |
| 2 | SEALING WASHER | 2 | PTFE |
| 1 | BALL VALVE BODY | 1 | BRASS |
| | | | |

| SIZE | ∅D | A | B | C | E | F | G | H |
|------|-------|-------|-------|------|-------|-------|-------|-------|
| 3/8" | 0.394 | 1.752 | 1.437 | 1.28 | 0.472 | 0.945 | 1.909 | 2.146 |
| 1/2" | 0.394 | 2.204 | 1.437 | 1.28 | 0.606 | 1.043 | 1.961 | 2.461 |
| 3/4" | 0.591 | 2.362 | 1.535 | 1.28 | 0.626 | 1.299 | 2.815 | 2.476 |



FLARE X FLARE

| PART# | SIZE | |
|--------|-------|------|
| 943342 | 3/8 | ---- |
| 943343 | 1/2 | ---- |
| 943345 | 5/8 | ---- |
| 943344 | 15/16 | ---- |



FLARE X MIP

| PART# | SIZE | |
|--------|-----------|------|
| 943347 | 3/8 x 1/2 | ---- |
| 943348 | 1/2 x 1/2 | ---- |




FLARE X FIP

| PART# | SIZE | |
|--------|-------------|------|
| 943331 | 3/8 x 1/2 | ---- |
| 943332 | 1/2 x 1/2 | ---- |
| 943351 | 5/8 x 3/4 | ---- |
| 943350 | 15/16 x 3/4 | ---- |

- For use with natural, manufactured, mixed liquified, petroleum and LP gas-air mixtures.
- Deeper thread connections. Smooth quarter-turn.
- Manufactured to ANSI Z21.15, C.G.A. 9.1-M81, 9.2-M88, 1/2 psig, 372 also to A.G.A.3-8, C.G.A. CR91-002, 2 psig.
- Solid chrome plated brass ball
- Bottom entry
- Blow out proof design.
- Double Fluoroelastomer o-rings stem seals
- Polytetrafluoroethylene seats for durability.
- Forged construction for greater strength.
- Larger ports for increased flow capacity.
- Red Reversible handle.
- May be used with water 400 WOG.

MADE IN ITALY



| Components | Materials |
|------------------|----------------|
| 1 Body | Forged Brass |
| 2 End Connection | Forged Brass |
| 3 Ball | Forged Brass |
| 4 Ball Seats | P.T.F.E. |
| 5 Stem | Brass |
| 6 O-Ring | NBR |
| 7 Butterfly | Steel |
| 8 Screw | UNI 5771 Steel |




CSA AGA 3.88 5 PSIG



Manual Valve LISTED Threaded NPT UL 842, UL 258, UL 125

GAS BALL VALVES FEMALE X FEMALE



| PART# | SIZE | DIMENSION INCHES | | | | | | | | | |
|--------|------|------------------|------|------|------|-----|------|-----|-----------|-------|----------|
| | | G | DN | A | B | C | E | CH | PN in psi | WTG | Box/Case |
| 943212 | 1/2" | .47 | 2.26 | 1.45 | 2.28 | .55 | .98 | 600 | 0.33 | 20/80 | |
| 943213 | 3/4" | .59 | 2.48 | 1.57 | 2.28 | .57 | 1.22 | 600 | 0.45 | 14/56 | ---- |

WARNING: This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov