

**MIDLAND INDUSTRIES**  
**AWWA C515 NRS RESILIENT SEATED GATE VALVES**



**9600FL Series**  
**Flanged Ends**



**9600MJ Series**  
**MJ x MJ Ends**



**9600FJ Series**  
**FL x MJ Ends**

Introducing Our Midland Industries  
**AWWA C515 NRS RESILIENT**  
**SEATED GATE VALVE**

The Midland Industries 9600 Series, Non Rising Stem, UL/FM/NSF, Ductile Iron Mechanical Joint Gate Valves are manufactured to meet or exceed ANSI and AWWA C509 and C515 Standards. Mechanical Joint ends conform to AWWA C111 / AWWA C153 Standard. The body is coated Internally and Externally with a Fusion Bonded Epoxy (FBE) Coating creating a smooth finish throughout the valve. Midland Industries 9600 Series Gate Valves have a Working Temperature rating of 248°F with a working pressure of 300PSI. All Valves are tested and are UL Listed, FM Approved and NSF-61/372 Certified by UL Water Quality.

**Need help knowing if our Seated Gate Valves are right for you?**

**Specifications**

- AWWA C515 Compliant
- Meets or Exceeds the Requirements of AWWA C509
- Non-Rising Stem, Resilient Seated
- Triple O-Ring Stem Seal
- Lifting Lugs built into the stuffing gland
- All flange & bolt patterns conform to ANSI/ASME B16.1 or B16.42, Class 125 or 150 per AWWA C515
- Mechanical Joint Ends conforms to ANSI/ AWWA C153 A21.53
- UL Listed @ 300PSI
- FM Approved @ 300PSI
- Certified to NSF 61/372

**Working Pressure**

- 300 PSI

**Working Temperature**

- 42°F to 248°F

**FOR MORE INFORMATION**

**CALL US**

PHONE: 800-821-5725

**VISIT US**

MIDLANDINDUSTRIES.COM

3145 OAK ST,

KANSAS CITY, MO 64111

FIND US ON:   

**FOR MORE INFORMATION ON OUR FULL VALVE SELECTION GIVE US A CALL!**