



MANUFACTURED FOR QUALITY **HOSE BARB FITTINGS**

Here at Midland Industries, we have all of the Hose Barb Fittings and options you need, including brass, stainless steel, plastic, and even in lead free options!

These Hose Barb Fittings are designed to connect equipment to hoses, or even hoses together with other hoses in a variety of industries including agriculture, air, automotive, construction, hydraulic, irrigation or other fluidbased applications, mining, and oil & gas.

Assmebly Instructions:

- 1- Cut hose cleanly and squarely to length.
- 2- Slide clamp on hose.
- 3- Lubricate hose. Push hose on fitting until hose bottoms against stop ring or hex.
- 4- Position hose clamp as shown below and secure with a scredriver or wrench.

Innovative, efficient and reliable. **Our Hose Barb Fittings** come in a variety of options for any application you need!

- Temperature & Working Pressure Ranges: From -40°F to +160°F at 150 PSI maximum
- Tolerance: +/- .02 on all dimensions. Dimension Data can change without notice. Please call us when dimensions are critical.
- Note: These fittings are intended for use with hose clamp, similar type clamp, or a crimped ferrule.

SELECT FITTINGS ALSO AVAILABLE STAINLESS STEEL, LEAD FREE, & PLASTIC!

FOR MORE INFORMATION

CALL US
PHONE: 800-821-5725
VISIT US
MIDLANDINDUSTRIES.COM
3145 OAK ST,
KANSAS CITY, MO 64111

FIND US ON: f in

