



PLACE AN ORDER TODAY!

Industry Standard LEVER & WEIGHT CHECK VALVE

The first valve in the Midland Industries offering to be manufactured to an AWWA standard. This AWWA C508, lever and weight, ductile iron body, flanged check valve is made to handle any application from pump and well to lift stations. This valve has industry standard lay lengths and can be used without the lever and weight depending upon the application. This 300 PSI working pressure, AWWA C550 epoxy coated valve is now stocked in sizes 3"-12".

FOR MORE INFORMATION

CALL US PHONE: 800-821-5725 MIDI

VISIT US MIDLANDINDUSTRIES.COM 3145 OAK ST, KANSAS CITY, MO 64111 ORDER PART NUMBER: 9620 SERIES VALVES

Innovative, efficient and reliable. Designed for a variety of applications.

- Manufactured to AWWA C508 Standard
- Size Ranges 3"-12"
- Ductile Iron Body rated to 300 PSI
- AWWA C550 Fusion Bonded Epoxy Inside and Out
- Resilient Seat
- Outside Bolts and Nuts are 304SS
- SS 420 Hinge Pin
- Designed to work with or without Lever and Weight
- May Be Fitted with additional Spring Kit
- Lifting Eye for installation

FIND US ON: **f** 🗇 in